



2-2X12 FL SP #2 2.000" X 12.000" 2-Ply - PASSED

Level: Level



Member Information

Type:	Girder
Plies:	2
Moisture Condition:	Dry
Deflection LL:	480
Deflection TL:	360
Importance:	Normal - II
Temperature:	Temp <= 100°F

Application:	Floor
Design Method:	ASD
Building Code:	IBC/IRC 2015
Load Sharing:	No
Deck:	Not Checked
Ceiling:	Gypsum 1/2"

Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind	Const
1	Vertical	891	891	0	0	0
2	Vertical	918	918	0	0	0

Bearings

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	2.500"	Vert	42%	891 / 891	1782	L	D+L
2 - SPF End Grain	3.500"	Vert	31%	918 / 918	1837	L	D+L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	2160 ft-lb	2'8 1/2"	3955 ft-lb	0.546 (55%)	D+L	L
Unbraced	2160 ft-lb	2'8 1/2"	3746 ft-lb	0.577 (58%)	D+L	L
Shear	1028 lb	1'1 3/4"	3938 lb	0.261 (26%)	D+L	L
LL Defl inch	0.010 (L/6001)	2'8 1/2"	0.128 (L/480)	0.080 (8%)	L	L
TL Defl inch	0.020 (L/3001)	2'8 1/2"	0.171 (L/360)	0.120 (12%)	D+L	L

Design Notes

- 1 Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- 2 Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- 3 Refer to last page of calculations for fasteners required for specified loads.
- 4 Fill all hanger nailing holes.
- 5 Left Header: SPF, Thickness: 3 1/2"
- 6 Girders are designed to be supported on the bottom edge only.
- 7 Top loads must be supported equally by all plies.
- 8 Top must be laterally braced at end bearings.
- 9 Lateral slenderness ratio based on single ply width.



ID	Load Type	Location	Trib Width	Side	Dead 0.9	Live 1	Snow 1.15	Wind 1.6	Const. 1.25	Comments
1	Uniform			Top	329 PLF	329 PLF	0 PLF	0 PLF	0 PLF	

Manufacturer Info

This design is valid until 6/28/2026

2-2X12 FL SP #2 2.000" X 12.000" 2-Ply - PASSED

Level: Level



Multi-Ply Analysis

Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c.. Maximum end distance not to exceed 6".

Capacity	0.0 %
Load	0.0 PLF
Yield Limit per Foot	202.6 PLF
Yield Limit per Fastener	101.3 lb.
C _m	1
Yield Mode	IV
Edge Distance	1 1/2"
Min. End Distance	3"
Load Combination	
Duration Factor	1.00

Manufacturer Info	

This design is valid until 6/28/2026