


Job 22050129 - Opt Bonus Room	Truss A1	Truss Type Piggyback Base Supported Gable	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	-------------	--	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:51

Page: 1

ID:p7SafMqETF1yP1?2bgwmKDzD8Og-PCXffcfHugVaC_ugwwDBmTzY3LXNyK4OqVNNWEzD2k6



Scale = 1:65.5

Plate Offsets (X, Y): [10:0-4-8,0-2-8], [16:0-4-4,0-2-4], [33:0-2-0,0-0-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.11	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.07	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.14	Horiz(TL)	0.01	25	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0											
											Weight: 311 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 10-16.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 16-32, 15-34, 14-35, 13-36, 12-37, 11-39, 9-40, 17-31

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 38-10-0.
(lb) - Max Horiz 46=-197 (LC 9)
Max Uplift All uplift 100 (lb) or less at joint(s) 25, 26, 27, 28, 29, 30, 31, 34, 35, 36, 37, 40, 41, 42, 43, 44, 45, 46
Max Grav All reactions 250 (lb) or less at joint (s) 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 36, 37, 39, 40, 41, 42, 43, 44, 45, 46

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 7-8=-173/250, 8-9=-161/256, 9-10=-199/302, 10-11=-171/271, 11-12=-171/271, 12-13=-171/271, 13-14=-171/271, 14-15=-171/271, 15-16=-171/271, 16-17=-201/304

NOTES
1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) 0-1-12 to 4-0-6, Exterior(2N) 4-0-6 to 14-3-12, Corner(3R) 14-3-12 to 18-2-6, Exterior(2N) 18-2-6 to 24-6-4, Corner(3R) 24-6-4 to 28-6-4, Exterior(2N) 28-6-4 to 38-8-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=18.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- 5) Provide adequate drainage to prevent water ponding.
- 6) All plates are 2x4 MT20 unless otherwise indicated.
- 7) Gable requires continuous bottom chord bearing.
- 8) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- 9) Gable studs spaced at 2-0-0 oc.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 46, 25, 34, 35, 36, 37, 40, 41, 42, 43, 44, 45, 31, 30, 29, 28, 27, 26.
- 12) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss A2	Truss Type Piggyback Base	Qty 4	Ply 1	Job Reference (optional)
-------------------------------------	-------------	------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:51

Page: 1

ID: xMC3p_njP0XWwQiHMqsq9NzD8Ok-PCXfchHugVaC_ujwwDBmTzNPLMFyCpOqVNNWEzD2k6



Scale = 1:67.8

Plate Offsets (X, Y): [4:0-6-4,0-2-4], [6:0-6-4,0-2-4], [10:Edge,0-8-2], [18:Edge,0-8-2]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.79	Vert(LL)	-0.14	16-17	>999	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.78	Vert(CT)	-0.26	16-17	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.67	Horz(CT)	0.08	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 265 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (4-4-9 max.): 4-6.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 2-16, 5-14, 8-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 10=1356/ Mechanical, (min. 0-1-8), 18=1356/ Mechanical, (min. 0-1-8)
 Max Horiz 18=-197 (LC 9)
 Max Grav 10=1725 (LC 25), 18=1725 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-19=-2397/72, 2-19=-2219/99, 2-20=-1973/133, 3-20=-1860/156, 3-4=-1857/175, 4-21=-1664/188, 5-21=-1664/188, 5-22=-1664/188, 6-22=-1664/188, 6-7=-1857/175, 7-23=-1860/156, 8-23=-1973/133, 8-24=-2219/99, 9-24=-2397/72, 1-18=-1609/87, 9-10=-1609/87
 BOT CHORD 17-18=-178/477, 17-25=-58/2024, 16-25=-58/2024, 15-16=0/1582, 15-26=0/1582, 14-26=0/1582, 14-27=0/1555, 13-27=0/1555, 12-13=0/1555, 12-28=-13/1921, 11-28=-13/1921, 10-11=-49/335

WEBS 2-16=-567/110, 4-16=0/602, 4-14=-104/352, 5-14=-330/83, 6-14=-104/352, 6-12=0/602, 8-12=-567/110, 1-17=-7/1618, 9-11=-5/1618

NOTES
 1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 4-0-6, Interior (1) 4-0-6 to 14-3-12, Exterior(2R) 14-3-12 to 19-9-11, Interior (1) 19-9-11 to 24-6-4, Exterior(2R) 24-6-4 to 30-0-2, Interior (1) 30-0-2 to 38-8-4 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=18.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- 4) Provide adequate drainage to prevent water ponding.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 6) Refer to girder(s) for truss to truss connections.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss A3	Truss Type Piggyback Base	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	-------------	------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:51

Page: 1

ID:MC3p_njP0XWwQIHMQsq9NzD80k-PCXfCfHugVaC_ugwwDBmTzOHLLtyAhOqVNNWEzD2k6



Scale = 1:79.1

Plate Offsets (X, Y): [4:0-4-4,0-2-4], [6:0-4-4,0-2-4], [10:Edge,0-8-2], [11:0-3-8,0-3-0], [22:0-3-8,0-3-0], [23:Edge,0-8-2]

Loading	(psf)	Spacing	2-0-0	CSI	0.74	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.74	Vert(LL)	-0.17	16-18	>999	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.87	Vert(CT)	-0.34	16-18	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.81	Horz(CT)	0.07	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 273 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.1 *Except* T3:2x4 SP No.2
BOT CHORD 2x4 SP 2400F 2.0E *Except* B2:2x4 SP No.1
WEBS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (4-0-0 max.): 4-6.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. Except:
5-0-0 oc bracing: 14-20
WEBS 1 Row at midpt 2-21, 8-12, 5-20, 5-14

REACTIONS (lb/size) 10=1546/ Mechanical, (min. 0-1-8), 23=1546/ Mechanical, (min. 0-1-8)
Max Horiz 23=-197 (LC 9)
Max Grav 10=2013 (LC 25), 23=2013 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-24=-2844/0, 2-24=-2665/0, 2-25=-2463/0, 3-25=-2349/0, 3-4=-2347/0, 4-26=-1969/0, 5-26=-1969/0, 5-27=-1969/0, 6-27=-1969/0, 6-7=-2347/0, 7-28=-2349/0, 8-28=-2463/0, 8-29=-2665/0, 9-29=-2844/0, 1-23=-1890/0, 9-10=-1890/0
BOT CHORD 22-23=-163/522, 22-30=0/2395, 21-30=0/2395, 19-21=0/2204, 19-31=0/2204, 18-31=0/2204, 16-18=0/3348, 16-32=0/2204, 13-32=0/2204, 12-13=0/2204, 12-33=0/2292, 11-33=0/2292, 10-11=-35/379, 20-34=-1530/0, 17-34=-1530/0, 15-17=-1530/0, 15-35=-1530/0, 14-35=-1530/0
WEBS 2-21=-521/134, 4-21=0/1030, 6-12=0/1030, 8-12=-521/134, 1-22=0/1945, 9-11=0/1945, 20-21=-634/0, 5-20=-304/134, 5-14=-304/134, 12-14=-634/0, 14-16=0/1378, 18-20=0/1378

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 4-0-6, Interior (1) 4-0-6 to 14-3-12, Exterior(2R) 14-3-12 to 19-9-11, Interior (1) 19-9-11 to 24-6-4, Exterior(2R) 24-6-4 to 30-0-2, Interior (1) 30-0-2 to 38-8-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=18.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- 200.0lb AC unit load placed on the bottom chord, 19-5-0 from left end, supported at two points, 5-0-0 apart.
- Provide adequate drainage to prevent water ponding.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

NOTES

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


Job 22050129 - Opt Bonus Room	Truss A4	Truss Type Piggyback Base	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	-------------	------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:52

Page: 1

ID: xMC3p_njP0XWwQIHMQsq9NzD8Ok-tO41tyfvf_dQq8TTekQJhWbYlihc8X296w3gzD2k5



Scale = 1:79.1

Plate Offsets (X, Y): [4:0-4-4,0-2-4], [6:0-4-4,0-2-4], [10:Edge,0-8-2], [11:0-3-8,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	-0.23	21-22	>999	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.77	Vert(CT)	-0.40	21-22	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.86	Horz(CT)	0.07	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 283 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2 *Except* T4,T5:2x4 SP 2400F 2.0E
BOT CHORD 2x4 SP 2400F 2.0E *Except* B2:2x4 SP No.1
WEBS 2x4 SP No.3 *Except* W2:2x4 SP No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 3-1-2 oc purlins, except end verticals, and 2-0-0 oc purlins (3-9-12 max.): 4-6.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. Except:
5-2-0 oc bracing: 14-20
WEBS 1 Row at midpt 8-12, 3-21, 5-20, 5-14

NOTES
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 11-1-12 to 15-0-6, Interior (1) 15-0-6 to 25-3-12, Exterior(2R) 25-3-12 to 29-2-6, Interior (1) 29-2-6 to 35-6-4, Exterior(2R) 35-6-4 to 39-4-13, Interior (1) 39-4-13 to 49-8-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=18.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
4) Unbalanced snow loads have been considered for this design.
5) 200.0lb AC unit load placed on the bottom chord, 19-5-0 from left end, supported at two points, 5-0-0 apart.
6) Provide adequate drainage to prevent water ponding.
7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
8) Refer to girder(s) for truss to truss connections.

9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

REACTIONS (lb/size) 10=1546/ Mechanical, (min. 0-1-8), 23=1546/ Mechanical, (min. 0-1-8)
Max Horiz 23=193 (LC 12)
Max Grav 10=2084 (LC 53), 23=2023 (LC 3)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD
1-24=-2365/110, 2-24=-2340/118,
2-25=-2852/217, 3-25=-2766/234,
3-26=-2488/150, 26-27=-2472/166,
4-27=-2376/179, 4-28=-1998/192,
28-29=-1998/192, 29-30=-1998/192,
5-30=-1998/192, 5-31=-1995/191,
31-32=-1995/191, 32-33=-1995/191,
6-33=-1995/191, 6-7=-2375/168,
7-34=-2381/149, 34-35=-2418/142,
35-36=-2525/126, 8-36=-2544/121,
8-37=-2786/143, 9-37=-2976/116,
9-10=-1960/141, 1-23=-1960/127

Job 22050129 - Opt Bonus Room	Truss A6	Truss Type Piggyback Base	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	-------------	------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:53

Page: 1

ID: xMC3p_njP0XWwQIHMQsq9NzD8Ok-LaeP4jgXQHIS231LFfru2mt90JQ5vgHpsTb6D2k4




Plate Offsets (X, Y): [1:0-2-4,Edge], [7:0-4-0,0-2-13], [9:0-4-0,0-2-13]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.60	Vert(LL)	-0.25	23-25	>999	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.91	Vert(CT)	-0.43	23-25	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.76	Horz(CT)	0.10	13	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 364 lb	FT = 20%

LUMBER
 TOP CHORD 2x6 SP No.2 *Except* T4:2x6 SP 2400F 2.0E
 BOT CHORD 2x4 SP No.2 *Except* B3:2x4 SP No.1
 WEBS 2x4 SP No.3 *Except* W4:2x4 SP No.2
 SLIDER Right 2x4 SP No.3 -- 2-6-0

BRACING
 TOP CHORD Structural wood sheathing directly applied or 3-3-12 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 7-9.
 BOT CHORD Rigid ceiling directly applied or 4-11-8 oc bracing. Except: 4-10-0 oc bracing: 17-22
 WEBS 1 Row at midpt 8-23, 8-15, 11-15, 6-23, 6-25

WEBS
 5-25=-853/176, 7-23=0/953, 22-23=-714/0, 8-22=-358/106, 15-17=-559/0, 9-15=0/895, 11-15=-637/228, 11-14=0/284, 6-25=-432/0, 3-27=-2481/208, 3-25=-86/3093, 2-27=-990/162, 17-19=0/1228, 21-22=0/1197

8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 9) Refer to girder(s) for truss to truss connections.
 10) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 27. This connection is for uplift only and does not consider lateral forces.
 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

NOTES
 1) Unbalanced roof live loads have been considered for this design.
 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-0 to 4-11-13, Interior (1) 4-11-13 to 25-3-12, Exterior(2R) 25-3-12 to 30-5-0, Interior (1) 30-5-0 to 35-6-4, Exterior(2R) 35-6-4 to 40-6-0, Interior (1) 40-6-0 to 49-10-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=18.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
 4) Unbalanced snow loads have been considered for this design.
 5) 200.0lb AC unit load placed on the bottom chord, 30-5-0 from left end, supported at two points, 5-0-0 apart.
 6) Provide adequate drainage to prevent water ponding.
 7) All plates are 4x5 MT20 unless otherwise indicated.

LOAD CASE(S) Standard

REACTIONS (lb/size) 1=124/0-3-8, (min. 0-1-8), 13=1474/ Mechanical, (min. 0-1-8), 27=2253/0-3-8, (min. 0-3-7)
 Max Horiz 1=188 (LC 12)
 Max Uplift 1=-59 (LC 11)
 Max Grav 1=176 (LC 58), 13=2003 (LC 53), 27=2923 (LC 3)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-36=-115/494, 2-36=-13/521, 2-37=-61/1173, 37-38=-53/1175, 3-38=-46/1232, 3-4=-1687/80, 4-5=-1662/94, 5-39=-2020/184, 39-40=-1953/186, 6-40=-1882/201, 6-41=-2249/169, 7-41=-2134/182, 7-42=-1801/196, 8-42=-1801/196, 8-43=-1897/209, 9-43=-1897/209, 9-10=-2237/178, 10-44=-2265/158, 44-45=-2323/140, 11-45=-2405/136, 11-46=-2738/164, 46-47=-2796/148, 47-48=-2838/143, 12-48=-2892/137, 12-13=-1093/52

Job 22050129 - Opt Bonus Room	Truss B1	Truss Type Piggyback Base Supported Gable	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	-------------	--	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:53

Page: 1

ID:Di7JHOT6IAPWGVkdGoUTyrzD8Od-LaeP4IqXQHHSI231LFru2gy9AZQDKgHpsTb6zD2k4




Plate Offsets (X, Y): [16:0-2-8,0-1-13], [21:Edge,0-1-8], [22:Edge,0-1-8], [28:0-3-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.98	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.28	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.22	Horz(CT)	0.01	22	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 252 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 16-21.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 21-22, 20-23, 19-24, 18-25, 17-26, 15-27

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 34-9-8.
(lb) - Max Horiz 2=298 (LC 14), 39=298 (LC 14)
Max Uplift All uplift 100 (lb) or less at joint(s)
2, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 33, 34, 35, 36, 37, 38, 39
Max Grav All reactions 250 (lb) or less at joint (s)
2, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 33, 34, 35, 36, 37, 39 except 38=387 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-477/251, 3-4=-435/219, 4-5=-425/224, 5-6=-406/213, 6-7=-388/202, 7-8=-383/207, 8-9=-371/200, 9-10=-349/189, 10-11=-351/189, 11-12=-351/201, 12-42=-344/189, 13-42=-333/202, 13-14=-283/175
BOT CHORD 2-38=-306/200
WEBS 3-38=-265/123

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -0-11-13 to 2-5-15, Exterior(2N) 2-5-15 to 26-0-4, Corner(3R) 26-0-4 to 29-6-0, Exterior(2N) 29-6-0 to 34-7-12 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=18.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- 6) Provide adequate drainage to prevent water ponding.
- 7) All plates are 2x4 MT20 unless otherwise indicated.
- 8) Gable requires continuous bottom chord bearing.
- 9) Gable studs spaced at 2-0-0 oc.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 33, 34, 35, 36, 37, 38, 2, 2.
- 12) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job 22050129 - Opt Bonus Room	Truss B2	Truss Type Piggyback Base	Qty 5	Ply 1	Job Reference (optional)
-------------------------------------	-------------	------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:54

Page: 1

ID:2sU_YRxtLOAg_QBnd3btB6zD8OX-pnCnlehABbt83SdFb3nuO6bx7ZMa9Z4qWTb17ZzD2k3




Plate Offsets (X, Y): [8:0-2-8,0-1-13], [10:Edge,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	I/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.63	Vert(LL)	-0.24	11-12	>999	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.93	Vert(CT)	-0.38	11-12	>729	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.70	Horz(CT)	0.02	11	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 225 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3 *Except* W11:2x4 SP No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 5-7-9 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 8-10.
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 1 Row at midpt 10-11, 9-11, 7-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 2=322/0-3-8, (min. 0-1-8), 11=775/0-3-8, (min. 0-1-8), 16=1382/0-3-8, (min. 0-2-1)
Max Horiz 2=298 (LC 14)
Max Uplift 2=-48 (LC 11), 11=-37 (LC 12), 16=-12 (LC 15)
Max Grav 2=401 (LC 33), 11=1042 (LC 46), 16=1767 (LC 3)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-21=-535/55, 3-21=-504/70, 3-22=-293/518, 4-22=-278/581, 4-5=-848/92, 5-6=-827/108, 6-23=-1040/203, 7-23=-888/218, 7-24=-755/199, 24-25=-659/211, 8-25=-636/223, 8-26=-545/217, 9-26=-545/217
BOT CHORD 2-17=-353/468, 16-17=-334/468, 15-16=-608/102, 14-15=-608/102, 13-14=-288/755, 13-29=-288/755, 29-30=-288/755, 12-30=-288/755, 12-31=-178/349, 31-32=-178/349, 11-32=-178/349
WEBS 6-14=-524/190, 9-12=-99/649, 9-11=-826/258, 7-12=-408/164, 4-16=-1296/247, 4-14=-132/1390, 3-17=0/252, 3-16=-998/169

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E)-0-11-13 to 2-5-15, Interior (1) 2-5-15 to 26-0-4, Exterior(2R) 26-0-4 to 29-6-0, Interior (1) 29-6-0 to 34-7-12 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=18.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- 5) Provide adequate drainage to prevent water ponding.
- 6) All plates are 3x5 MT20 unless otherwise indicated.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 11, 2, and 16. This connection is for uplift only and does not consider lateral forces.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job 22050129 - Opt Bonus Room	Truss B3	Truss Type Piggyback Base Girder	Qty 1	Ply 2	Job Reference (optional)
-------------------------------------	-------------	-------------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:54

Page: 1

ID:2sU_YRxtL0Ag_QBnd3btB6zD8OX-pnClchABt83Sdfb3nuO6b_iZXA9g6qWTb17ZzD2k3




Plate Offsets (X, Y): [8:0-6-4,0-2-4], [11:0-6-4,0-2-4], [12:0-3-8,0-2-12], [17:0-5-8,0-1-8], [20:0-2-8,0-3-0]

Loading	(psf)	Spacing	1-11-4	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.40	Vert(LL)	-0.02	29-32	>999	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.19	Vert(CT)	-0.04	29-32	>999	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.25	Horz(CT)	0.03	15	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
Weight: 680 lb FT = 20%												

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2 *Except* B4,B6:2x4 SP No.3
 WEBS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 8-11, 12-14. Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 26-28,20-21.
 WEBS 1 Row at midpt 14-15

REACTIONS All bearings 0-3-8. except 15= Mechanical
 (lb) - Max Horiz 2=280 (LC 10)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 28
 Max Grav All reactions 250 (lb) or less at joint (s) except 2=389 (LC 29), 15=672 (LC 26), 21=1814 (LC 3), 28=1634 (LC 64)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-528/92, 3-33=-87/487, 33-34=-78/518, 4-34=-73/548, 4-5=-751/25, 5-6=-731/34, 6-35=-879/64, 7-35=-734/79, 7-36=-643/113, 8-36=-523/125, 8-9=-346/128, 9-37=0/298, 37-38=0/298, 10-38=0/298, 10-11=0/296, 12-13=-283/0, 13-39=-567/0, 14-39=-567/0, 14-15=-619/0
 BOT CHORD 2-29=-197/448, 28-29=-119/448, 27-28=-561/16, 26-27=-561/16, 25-26=-65/679, 24-25=-65/679, 23-24=-74/667, 23-40=-73/440, 22-40=-73/440, 20-21=-1744/0, 10-20=-419/0, 18-19=-4/293, 17-18=0/520
 WEBS 6-26=-442/64, 8-23=-20/552, 20-22=-114/493, 9-20=-653/0, 11-20=-763/0, 11-19=0/517, 14-17=0/628, 9-22=-67/261, 8-22=-496/24, 7-23=-467/74, 4-28=-1153/99, 4-26=-11/1203, 3-28=-955/38, 12-18=0/662, 12-19=-566/0, 13-18=-675/0

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=18.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- All plates are 3x5 MT20 unless otherwise indicated.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 21, and 28. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Load case(s) 1, 2 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard
 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (lb/ft)
 Vert: 1-6=-46, 6-8=-46, 8-10=-56, 10-11=-136, 11-12=-126, 12-14=-136, 21-30=-19, 17-20=-19, 15-16=-19
 2) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (lb/ft)
 Vert: 1-6=-58, 6-8=-58, 8-10=-58, 10-11=-178, 11-12=-178, 12-14=-178, 21-30=-19, 17-20=-19, 15-16=-19

NOTES


Job 22050129 - Opt Bonus Room	Truss B4	Truss Type Piggyback Base	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	-------------	------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:55

Page: 1

ID:p7SafMqETF1yP1?2bgwmKDzD8Og-lzm9V_joyv??hcCS9ml7wJ85EzqDu4fzk7Laf?zD2k2



Scale = 1:77.9

Plate Offsets (X, Y): [4:0-5-12,0-2-0], [7:0-2-8,0-1-13], [9:0-3-2,0-2-2], [14:0-1-8,0-2-0], [14:0-5-8,0-1-2], [16:0-5-8,0-1-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.61	Vert(LL)	-0.04	20-21	>999	240	MT20 244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.40	Vert(CT)	-0.08	22-23	>999	180	
TCDL	10.0	Rep Stress Incr	YES	WB	0.42	Horz(CT)	0.03	11	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH							
BCDL	10.0										Weight: 299 lb FT = 20%

- LUMBER**
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2 *Except* B3,B5:2x4 SP No.3
WEBS 2x4 SP No.3
- BRACING**
TOP CHORD Structural wood sheathing directly applied or 4-10-3 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-7, 9-10.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
4-7-4 oc bracing: 16-17
6-0-0 oc bracing: 15-16.
- WEBS**
1 Row at midpt 5-18, 4-18, 3-20

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- REACTIONS** (lb/size)
11=215/ Mechanical, (min. 0-1-8),
17=1229/0-3-8, (min. 0-1-12),
23=762/ Mechanical, (min. 0-1-8)
Max Horiz 23=261 (LC 12)
Max Uplift 11=45 (LC 11), 17=38 (LC 12),
23=7 (LC 15)
Max Grav 11=330 (LC 56), 17=1472 (LC 52),
23=958 (LC 64)

- FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-24=-981/194, 2-24=-949/203,
2-25=-1003/268, 3-25=-851/283,
3-26=-707/297, 26-27=-614/309,
4-27=-594/321, 4-28=-393/297,
5-28=-393/297, 10-11=-310/208,
1-23=-864/221
BOT CHORD 22-23=-334/265, 21-22=-313/982,
20-21=-242/817, 19-20=-153/526,
19-33=-153/526, 18-33=-153/526,
16-17=-1400/414, 6-16=-576/212,
15-16=-277/216, 14-15=-152/259

- WEBS**
2-22=-350/171, 4-20=-117/688,
16-18=-166/622, 5-16=-620/209,
6-15=-107/387, 8-15=-300/138,
1-22=-203/1038, 9-12=-274/135,
12-14=-138/252, 10-12=-158/253,
5-18=-122/271, 4-18=-583/170,
3-20=-614/186, 3-21=-30/354, 2-21=-290/106

- NOTES**
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 11-10-4 to 14-10-4, Interior (1) 14-10-4 to 26-0-4, Exterior(2R) 26-0-4 to 29-0-4, Interior (1) 29-0-4 to 36-2-12, Exterior(2R) 36-2-12 to 39-2-12, Interior (1) 39-2-12 to 42-6-13 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=18.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
4) Unbalanced snow loads have been considered for this design.
5) Provide adequate drainage to prevent water ponding.
6) All plates are 3x5 MT20 unless otherwise indicated.
7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
8) Refer to girder(s) for truss to truss connections.
9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 45 lb uplift at joint 11 and 7 lb uplift at joint 23.
10) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 17. This connection is for uplift only and does not consider lateral forces.

- 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss B6	Truss Type Piggyback Base	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	-------------	------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:56

Page: 1

ID:3Gnz_mjZEitNoPKRF_3rcF_zD3uv-m9KYjJiQIC7sJmneiTpMTXgFTM69dYd7zn48CRzD2k1



Scale = 1:77.9

Plate Offsets (X, Y): [4:0-5-12,0-2-0], [7:0-2-8,0-1-13], [14:Edge,0-1-12], [16:0-5-8,0-1-4], [22:Edge,0-8-2]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.68	Vert(LL)	-0.08	20-21	>999	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.61	Vert(CT)	-0.15	20-21	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.38	Horz(CT)	0.04	11	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 278 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2 *Except* B3,B5:2x4 SP No.3
WEBS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 4-5-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-7.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
4-8-0 oc bracing: 16-17
6-0-0 oc bracing: 15-16.
WEBS 1 Row at midpt 2-20, 5-18, 4-18

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 11=209/ Mechanical, (min. 0-1-8), 17=1206/0-3-8, (min. 0-1-11), 22=767/ Mechanical, (min. 0-1-8)
Max Horiz 22=251 (LC 10)
Max Uplift 11=52 (LC 9), 17=-18 (LC 10), 22=-3 (LC 13)
Max Grav 11=365 (LC 25), 17=1434 (LC 3), 22=1006 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-23=-1253/108, 2-23=-1166/136, 2-24=-756/175, 3-24=-643/198, 3-4=-639/217, 4-5=-388/231, 1-22=-895/108, 10-11=-343/174
BOT CHORD 21-22=-234/424, 21-28=-134/1082, 20-28=-134/1082, 19-20=-61/571, 19-29=-61/571, 18-29=-61/571, 16-17=-1359/203, 6-16=-520/137
WEBS 2-21=0/302, 2-20=-655/102, 4-20=0/619, 16-18=-76/640, 5-16=-592/108, 6-15=-48/320, 8-15=-259/93, 1-21=0/728, 4-18=-582/90, 9-12=-251/121

NOTES
1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 3-2-15, Interior (1) 3-2-15 to 14-3-12, Exterior(2R) 14-3-12 to 18-8-6, Interior (1) 18-8-6 to 24-6-4, Exterior(2R) 24-6-4 to 28-7-9, Interior (1) 28-7-9 to 30-10-5 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=18.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- 4) Provide adequate drainage to prevent water ponding.
- 5) All plates are 3x5 MT20 unless otherwise indicated.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 3 lb uplift at joint 22 and 52 lb uplift at joint 11.
- 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 17. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job 22050129 - Opt Bonus Room	Truss C1	Truss Type Common Structural Gable	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	-------------	---------------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:56

Page: 1

ID:hd9gwgw4XFOoL1WZLRBilTzD8Ot-m9KYJiQic7sJmneiTpMTXgHvMAUdbr7zn48CRzD2k1




Plate Offsets (X, Y): [27:0-3-0,0-3-0], [30:0-2-8,0-3-0], [31:Edge,0-8-2]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.55	Vert(LL)	-0.01	30	>999	240	MT20 244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.33	Vert(CT)	-0.09	30-31	>999	180	
TCDL	10.0	Rep Stress Incr	YES	WB	0.17	Horz(CT)	0.01	21	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH							
BCDL	10.0										Weight: 211 lb FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing, Except: 10-0-0 oc bracing: 30-31.
WEBS 1 Row at midpt 12-28, 13-27
JOINTS 1 Brace at Jt(s): 9, 7, 11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 14-7-0. except 31=0-3-8
(lb) - Max Horiz 31=202 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) 21, 22, 23, 24, 25, 26, 27, 28, 29, 31
Max Grav All reactions 250 (lb) or less at joint (s) 21, 22, 23, 24, 25, 26, 27, 28 except 29=540 (LC 25), 31=592 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-566/143, 2-31=-520/155, 3-5=-476/87, 5-7=-484/90, 7-9=-514/106, 9-11=-556/127
BOT CHORD 30-31=-182/411
WEBS 12-28=-253/11, 11-30=-90/433, 11-29=-412/106

NOTES
1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E)-0-11-8 to 2-0-8, Interior (1) 2-0-8 to 13-11-8, Exterior(2R) 13-11-8 to 16-11-8, Interior (1) 16-11-8 to 27-9-4 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- 6) All plates are 2x4 MT20 unless otherwise indicated.
- 7) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- 8) Gable studs spaced at 2-0-0 oc.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 10) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 31, 21, 28, 27, 26, 25, 24, 23, 22, and 29. This connection is for uplift only and does not consider lateral forces.
- 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss C2	Truss Type Common	Qty 5	Ply 1	Job Reference (optional)
-------------------------------------	-------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:56

Page: 1

ID:Aqj28FhiHZWfzB5lu9ixrhzD8Os-m9KYjJiQIC7sJmneiTpMTXgEQM95dYj7zn48CRzD2k1



Scale = 1:66.2

Plate Offsets (X, Y): [9:Edge,0-8-2], [14:Edge,0-8-2]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.71	Vert(LL)	-0.05	12-13	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.42	Vert(CT)	-0.12	12-13	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.37	Horz(CT)	0.03	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 169 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-9-5 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 3-12, 7-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 9=934/0-3-8, (min. 0-1-8),
 14=989/0-3-8, (min. 0-1-8)
 Max Horiz 14=202 (LC 10)
 Max Grav 9=1104 (LC 2), 14=1172 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1475/142, 3-4=-1072/174,
 4-15=-947/177, 5-15=-944/197,
 5-6=-928/198, 6-16=-946/178,
 7-16=-1074/168, 7-8=-1475/141,
 2-14=-1105/154, 8-9=-1036/115

BOT CHORD 13-14=-189/472, 12-13=-55/1139,
 11-12=-49/1141, 10-11=-49/1141,
 9-10=-52/260

WEBS 2-13=0/801, 3-12=-474/129, 5-12=-77/685,
 7-12=-483/131, 8-10=0/886

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -0-11-8 to 2-0-8, Interior (1) 2-0-8 to 13-11-8, Exterior(2R) 13-11-8 to 16-11-8, Interior (1) 16-11-8 to 27-9-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33

- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 14 and 9. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss C3	Truss Type Common Girder	Qty 1	Ply 2	Job Reference (optional)
-------------------------------------	-------------	-----------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:56

Page: 1

ID:2sU_YRxtL0Ag_QBnd3btB6zD8OX-m9KYjJiQIC7sJmneiTpMTXglcM7pdOq7zn48CRzD2k1



Scale = 1:68.4

Plate Offsets (X, Y): [1:Edge,0-6-1], [3:0-4-0,0-3-12], [5:0-1-0,0-1-8], [8:0-1-9,0-2-8], [12:Edge,0-6-1], [15:0-3-8,0-6-4], [17:0-8-0,0-6-4], [18:0-3-8,0-6-0], [19:0-3-8,0-6-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.51	Vert(LL)	-0.18	17-18	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.57	Vert(CT)	-0.34	17-18	>969	180		
TCDL	10.0	Rep Stress Incr	NO	WB	1.00	Horz(CT)	0.11	12	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 523 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP No.2 *Except* T1:2x6 SP 2400F 2.0E
BOT CHORD 2x8 SP 2400F 2.0E
WEBS 2x4 SP No.3 *Except* W7:2x4 SP 2400F 2.0E, W5,W9:2x4 SP No.2
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING
TOP CHORD Structural wood sheathing directly applied or 4-4-10 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 5-17

REACTIONS (lb/size) 1=11020/0-3-8, (req. 0-5-8), 12=9500/(0-3-8 + bearing block), (req. 0-4-9)
Max Horiz 1=173 (LC 8)
Max Grav 1=13217 (LC 20), 12=10984 (LC 21)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-11743/0, 2-3=-16159/0, 3-4=-16931/0, 4-5=-14859/0, 5-6=-11469/0, 6-7=-11459/0, 7-8=-11477/0, 8-9=-11483/0, 9-10=-14083/0, 10-11=-14995/0, 11-12=-10580/0
BOT CHORD 1-2=0/12923, 19-20=0/12923, 19-29=0/14520, 29-30=0/14520, 18-30=0/14520, 18-31=0/12390, 31-32=0/12390, 17-32=0/12390, 17-33=0/11746, 16-33=0/11746, 16-34=0/11746, 15-34=0/11746, 15-35=0/12173, 35-36=0/12173, 14-36=0/12173, 14-37=0/12173, 13-37=0/12173, 12-13=0/12173
WEBS 7-17=0/12282, 5-17=-4976/0, 4-19=0/2085, 4-18=-2696/0, 5-18=0/5851, 9-17=-3922/0, 9-15=0/4366, 10-15=-654/490, 10-14=-298/1130, 3-19=0/2624, 3-20=-1076/0

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x8 - 3 rows staggered at 0-5-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - 2x8 SP 2400F 2.0E bearing block 12" long at jt. 12 attached to each face with 4 rows of 10d (0.131"x3") nails spaced 3" o.c. 16 Total fasteners per block. Bearing is assumed to be SP 2400F 2.0E.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - WARNING: Required bearing size at joint(s) 1 greater than input bearing size.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 12. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Use MiTek THD26 (With 18-16d nails into Girder & 12-10d x 1-1/2 nails into Truss) or equivalent spaced at 2-0-12 oc max. starting at 1-0-0 from the left end to 27-0-0 to connect truss(es) A2 (1 ply 2x4 SP), A3 (1 ply 2x4 SP), A4 (1 ply 2x4 SP), A8 (1 ply 2x4 SP), A6 (1 ply 2x4 SP), A5 (1 ply 2x4 SP), A6 (1 ply 2x4 SP), B6 (1 ply 2x4 SP), A7 (1 ply 2x4 SP), B5 (1 ply 2x4 SP), A7 (1 ply 2x4 SP), B5 (1 ply 2x4 SP), A7 (1 ply 2x4 SP), B4 (1 ply 2x4 SP) to front face of bottom chord.
 - Fill all nail holes where hanger is in contact with lumber.
 - WARNING: The following hangers are manually applied but fail due to geometric considerations: THD26 on front face at 13-0-0 from the left end, THD26 on front face at 21-0-12 from the left end, THD26 on front face at 23-0-0 from the left end, THD26 on front face at 25-0-0 from the left end, THD26 on front face at 27-0-0 from the left end.
- LOAD CASE(S)** Standard
1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-7=-48, 7-12=-48, 21-25=-20
Concentrated Loads (lb)
Vert: 19=-1336 (F), 14=-785 (F), 20=-1336 (F), 13=-789 (F), 23=-1337 (F), 29=-1336 (F), 30=-1526 (F), 31=-1796 (F), 32=-1719 (F), 33=-1719 (F), 34=-1719 (F), 35=-1719 (F), 36=-747 (F), 37=-785 (F)

NOTES


Job 22050129 - Opt Bonus Room	Truss D1	Truss Type Attic Supported Gable	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	-------------	-------------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:57

Page: 1

ID:Aqj28FhiHZwzB5lu9ixrhzD8Os-EMuwfwj2TWFjvwMqGBk0kDZlmaJm2sGCRqhtzD2k0



Scale = 1:82.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.10	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.10	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.19	Horz(CT)	0.01	12	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 221 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP No.2
BOT CHORD 2x10 SP 2400F 2.0E
WEBS 2x4 SP No.3 *Except* W2:2x4 SP No.2
OTHERS 2x4 SP No.3
WEDGE Left: 2x4 SP No.3
Right: 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
JOINTS 1 Brace at Jt(s): 20

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 20-7-0.
(lb) - Max Horiz 2=204 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s)
12 except 14=-1060 (LC 26),
18=-432 (LC 20), 19=-127 (LC 13)
Max Grav All reactions 250 (lb) or less at joint
(s) 12, 14, 18, 19 except 2=461 (LC
27), 13=1045 (LC 26), 15=1059
(LC 27), 17=939 (LC 26)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250
(lb) or less except when shown.
TOP CHORD 2-3=-420/28, 3-4=-393/30, 4-5=-343/58,
5-6=-436/120, 8-9=-436/120, 9-10=-303/53,
10-28=-370/0, 11-28=-396/0, 11-12=-377/0
BOT CHORD 2-19=-136/259, 18-19=0/259, 17-18=0/259,
16-17=0/258, 15-16=0/258, 14-15=0/258,
13-14=0/258, 12-13=0/259
WEBS 9-15=-287/32, 5-17=-310/53

NOTES
1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -0-9-14 to 2-3-5, Exterior(2N) 2-3-5 to 10-3-8, Corner(3R) 10-3-8 to 13-3-8, Exterior(2N) 13-3-8 to 20-7-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- 6) All plates are 3x6 MT20 unless otherwise indicated.
- 7) Gable requires continuous bottom chord bearing.
- 8) Gable studs spaced at 2-0-0 oc.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 10) Ceiling dead load (10.0 psf) on member(s). 5-6, 8-9, 6-20, 8-20
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 12 except (jt=lb) 18=431, 19=126, 14=1059.
- 12) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 13) This truss has large uplift reaction(s) from gravity load case(s). Proper connection is required to secure truss against upward movement at the bearings. Building designer must provide for uplift reactions indicated.
- 14) Attic room checked for L/360 deflection.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss D2	Truss Type Attic	Qty 5	Ply 1	Job Reference (optional)
-------------------------------------	-------------	---------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:57

Page: 1

ID:e0HQLbiK2seWaLfxSsEANuzD8Or-EMuwvfj2TWFjvwMqGBKb0kDLemY4M04GCRqhtzD2k0



Scale = 1:82

Plate Offsets (X, Y): [6:0-3-15,0-1-12]

Loading	(psf)	Spacing	2-0-0	CSI	1.00	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	1.00	Vert(LL)	-0.15	9-11	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.24	Vert(CT)	-0.25	9-11	>985	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.30	Horz(CT)	0.02	2	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH		Attic	-0.06	9-11	>999	360		
BCDL	10.0										Weight: 201 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP No.2
BOT CHORD 2x10 SP 2400F 2.0E
WEBS 2x4 SP No.3 *Except* W2:2x4 SP No.2
WEDGE Left: 2x4 SP No.3
Right: 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

JOINTS
1 Brace at Jt(s): 12
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size)
2=883/0-3-8, (min. 0-1-8),
8=842/0-3-8, (min. 0-1-8)
Max Horiz 2=204 (LC 12)
Max Grav 2=1215 (LC 26), 8=1177 (LC 26)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1420/3, 3-19=-834/81, 4-19=-711/96,
4-5=-53/281, 5-6=-53/282, 6-20=-711/97,
7-20=-834/82, 7-8=-1419/0
BOT CHORD 2-11=-111/859, 10-11=0/860, 9-10=0/860,
8-9=0/859
WEBS 7-9=0/629, 3-11=0/629, 4-12=-1224/203,
6-12=-1224/203

NOTES
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf, BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -0-9-14 to 2-2-2, Interior (1) 2-2-2 to 10-3-8, Exterior(2R) 10-3-8 to 13-3-8, Interior (1) 13-3-8 to 20-7-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (10.0 psf) on member(s). 3-4, 6-7, 4-12, 6-12
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (5.0 psf) applied only to room. 9-11
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 8. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Attic room checked for L/360 deflection.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss D3	Truss Type Attic	Qty 4	Ply 1	Job Reference (optional)
-------------------------------------	-------------	---------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:57

Page: 1

ID:2sU_YRxtL0Ag_QBnd3btB6zD8OX-EMuwvfj2TWFjvwMqGBk0kDLdmY4M04GCRqhtzD2k0




Job 22050129 - Opt Bonus Room	Truss D4	Truss Type Attic Girder	Qty 1	Ply 2	Job Reference (optional)
-------------------------------------	-------------	----------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:58

Page: 1

ID:2sU_YRxtL0Ag_QBnd3btB6zD8OX-iYSI8?kgEqNaY3x0qurqYymdmAtS5S9PR5ZEKGzD2k?



Scale = 1:86.6

Plate Offsets (X, Y): [8:0-6-12,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	Vert(LL)	-0.12	8-10	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	Vert(CT)	-0.27	8-10	>920	180		
TCDL	10.0	Rep Stress Incr	NO	WB	Horz(CT)	0.01	1	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH							
BCDL	10.0										
											Weight: 397 lb FT = 20%

LUMBER
TOP CHORD 2x6 SP 2400F 2.0E *Except* T2:2x6 SP No.2
BOT CHORD 2x10 SP 2400F 2.0E
WEBS 2x4 SP No.3 *Except* W2:2x4 SP No.2
WEDGE Left: 2x4 SP No.3
Right: 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
JOINTS 1 Brace at Jt(s): 11

REACTIONS (lb/size) 1=2085/0-3-8, (min. 0-1-8),
7=2665/0-3-8, (min. 0-1-8)
Max Horiz 1=193 (LC 8)
Max Grav 1=2656 (LC 21), 7=3369 (LC 20)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-3569/0, 2-3=-1908/0, 3-4=-420/569,
4-5=-414/593, 5-6=-1884/0, 6-7=-3583/0
BOT CHORD 1-10=-50/2186, 10-18=0/2191, 9-18=0/2191,
9-19=0/2191, 8-19=0/2191, 8-20=0/2185,
20-21=0/2185, 7-21=0/2185
WEBS 6-8=0/2159, 2-10=0/2105, 3-11=-3262/129,
5-11=-3262/129

NOTES
1) 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x10 - 2 rows staggered at 0-7-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
3) Unbalanced roof live loads have been considered for this design.

- 4) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.33
- 5) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 7. This connection is for uplift only and does not consider lateral forces.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) Load case(s) 1 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- 10) Use MiTek THDH26-2 (With 22-16d nails into Girder & 8-16d nails into Truss) or equivalent spaced at 3-4-11 oc max. starting at 8-7-5 from the left end to 12-0-0 to connect truss(es) I1 (2 ply 2x6 SP), B3 (2 ply 2x4 SP) to front face of bottom chord.

- 11) Use MiTek THD26 (With 18-16d nails into Girder & 12-10d x 1-1/2 nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 14-0-0 from the left end to 19-10-8 to connect truss(es) B4 (1 ply 2x4 SP), B5 (1 ply 2x4 SP), B6 (1 ply 2x4 SP) to front face of bottom chord.
- 12) Fill all nail holes where hanger is in contact with lumber.

LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-4=-48, 4-7=-48, 12-15=-20
Concentrated Loads (lb)
Vert: 4=-536, 9=-579 (F), 17=-192 (F), 18=-1187 (F),
19=-234 (F), 20=-314 (F), 21=-314 (F)


Job 22050129 - Opt Bonus Room	Truss E1	Truss Type Common Supported Gable	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	-------------	--------------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:58

Page: 1

ID:e0HQLbiK2seWalFxSsEANuzD8Or-iYSi8?kgEqNaY3x0qurqYymjpAwi5T0PR5ZEgkzD2k?



Scale = 1:55.6

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.14	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.09	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.32	Horz(CT)	0.00	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0										Weight: 84 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 12-4-8.
(lb) - Max Horiz 15=161 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 9, 10, 11, 13, 15 except 14=102 (LC 10)
Max Grav All reactions 250 (lb) or less at joint (s) 9, 10, 11, 12, 13, 14, 15

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 4-5=-231/283, 5-6=-231/283
WEBS 5-12=-329/203

NOTES
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -0-11-4 to 2-3-12, Exterior(2N) 2-3-12 to 6-3-12, Corner(3R) 6-3-12 to 9-3-12, Exterior(2N) 9-3-12 to 12-2-12 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 15, 9, 12, 13, 14, 11, and 10. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss E2	Truss Type Common	Qty 2	Ply 1	Job Reference (optional)
-------------------------------------	-------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:58

Page: 1

ID:6CroYxjypAnMCVE70aIQw6zD8Oq-iYSI8?kgEqNaY3x0qurqYymb4AuW5WIPR5ZEGKzD2k?



Scale = 1:54.6

Plate Offsets (X, Y): [2:Edge,0-3-9], [4:0-1-12,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	0.70	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.70	Vert(LL)	0.00	6	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.23	Vert(CT)	-0.03	6-7	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.11	Horz(CT)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 78 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS (lb/size) 5=407/ Mechanical, (min. 0-1-8), 7=463/0-3-8, (min. 0-1-8)
Max Horiz 7=161 (LC 10)
Max Grav 5=480 (LC 2), 7=551 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-459/104, 3-4=-443/99, 2-7=-496/116, 4-5=-428/93

BOT CHORD 6-7=-209/316

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -0-11-4 to 2-0-12, Interior (1) 2-0-12 to 6-3-12, Exterior(2R) 6-3-12 to 9-3-12, Interior (1) 9-3-12 to 12-2-12 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.

Job 22050129 - Opt Bonus Room	Truss E3	Truss Type Common	Qty 3	Ply 1	Job Reference (optional)
-------------------------------------	-------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:58

Page: 1

ID:W22MlnyV6JIXcamzBm66kKzD8OW-iYSI8?kgEqNaY3x0qurqYymbEAuN5WRPR5ZEgkzD2k?




Plate Offsets (X, Y): [2:Edge,0-3-9], [4:Edge,0-3-9]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.69	Vert(LL)	0.00	6	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.24	Vert(CT)	-0.03	5-6	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.10	Horz(CT)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 79 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7 and 5. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS (lb/size) 5=415/0-3-8, (min. 0-1-8),
 7=472/0-3-8, (min. 0-1-8)
 Max Horiz 7=158 (LC 10)
 Max Grav 5=490 (LC 2), 7=561 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-471/104, 3-4=-463/97, 2-7=-506/117,
 4-5=-436/94

BOT CHORD 6-7=-207/312

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -0-11-4 to 2-0-12, Interior (1) 2-0-12 to 6-3-12, Exterior(2R) 6-3-12 to 9-3-12, Interior (1) 9-3-12 to 12-5-12 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.


Job 22050129 - Opt Bonus Room	Truss E4	Truss Type Common Girder	Qty 1	Ply 2	Job Reference (optional)
-------------------------------------	-------------	-----------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:58

Page: 1

ID:W22MlnyV6JlXcamzBm66kKzD8OW-iYSI8?kgEqNaY3x0qurqYymaRArZ5M8PR5ZEGKzD2k?



Scale = 1:56.2

Plate Offsets (X, Y): [1:Edge,0-3-8], [3:Edge,0-3-8], [5:0-5-0,0-4-12], [6:0-5-0,0-4-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.74	Vert(LL)	-0.06	5-6	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.42	Vert(CT)	-0.11	5-6	>999	180	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	NO	WB	0.76	Horz(CT)	0.01	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 182 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x6 SP 2400F 2.0E
WEBS 2x4 SP No.3 *Except* W1:2x4 SP No.1

BRACING
TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=4640/0-3-8, (min. 0-2-6), 7=4722/0-3-8, (min. 0-2-7)
Max Horiz 7=-142 (LC 5)
Max Grav 4=5739 (LC 3), 7=5931 (LC 21)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-5012/0, 2-3=-5306/0, 1-7=-4300/0, 3-4=-4726/0
BOT CHORD 7-8=-63712, 8-9=-63712, 6-9=-63712, 6-10=0/2478, 10-11=0/2478, 5-11=0/2478, 5-12=0/486, 4-12=0/486
WEBS 1-6=0/3026, 3-5=0/3403, 2-6=0/3698, 2-5=0/3526

NOTES
1) 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-6-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
3) Unbalanced roof live loads have been considered for this design.
4) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.33

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - All plates are MT20 plates unless otherwise indicated.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7 and 4. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Use MiTek THD26 (With 18-16d nails into Girder & 12-10d x 1-1/2 nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 1-0-0 from the left end to 11-0-0 to connect truss(es) A2 (1 ply 2x4 SP), A3 (1 ply 2x4 SP), A4 (1 ply 2x4 SP) to back face of bottom chord.
 - Fill all nail holes where hanger is in contact with lumber.
- LOAD CASE(S)** Standard
- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-48, 2-3=-48, 4-7=-20
Concentrated Loads (lb)
Vert: 5=-1526, 8=-1337, 9=-1336, 10=-1336, 11=-1336, 12=-1655


Job 22050129 - Opt Bonus Room	Truss G1	Truss Type Common Supported Gable	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	-------------	--------------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:58

Page: 1

ID:6CroYxjypAnMCVE70alQw6zD8Oq-iYSI8?kgEqNaY3x0qurqYymk8AxV5WvPR5ZEgKzD2k?



Scale = 1:39.5

Loading	(psf)	Spacing	1-11-4	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.12	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.04	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.07	Horz(CT)	0.00	12	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0										Weight: 77 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS All bearings 13-7-8.
(lb) - Max Horiz 20=113 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) 12, 13, 14, 15, 17, 18, 19, 20
Max Grav All reactions 250 (lb) or less at joint (s) 12, 13, 14, 15, 16, 17, 18, 19, 20

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -0-11-8 to 2-0-8, Exterior(2N) 2-0-8 to 6-9-12, Corner(3R) 6-9-12 to 9-9-12, Exterior(2N) 9-9-12 to 14-7-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.

- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 20, 12, 17, 18, 19, 15, 14, 13.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 22050129 - Opt Bonus Room	Truss G2	Truss Type Common	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	-------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:59

Page: 1

ID:aPPBmHjaaUvDqfpKaHGfSjzD8Op-Ak?gLLII?7VRADWDOcM359IuaDqqz9ZfkJopmzD2k_




Plate Offsets (X, Y): [6:Edge,0-8-2], [8:Edge,0-8-2]

Loading	(psf)	Spacing	1-11-4	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.76	Vert(LL)	0.00	7	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.29	Vert(CT)	-0.04	7-8	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.07	Horz(CT)	0.01	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 76 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 6=488/0-3-8, (min. 0-1-8),
 8=488/0-3-8, (min. 0-1-8)
 Max Horiz 8=113 (LC 12)
 Max Grav 6=581 (LC 2), 8=581 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-9=-558/88, 3-9=-440/108, 3-10=-440/108,
 4-10=-558/88, 2-8=-524/155, 4-6=-524/155
 BOT CHORD 7-8=-163/414, 6-7=-138/336

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -0-11-8 to 2-0-8, Interior (1) 2-0-8 to 6-9-12, Exterior(2R) 6-9-12 to 9-9-12, Interior (1) 9-9-12 to 14-7-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

- 6) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 8 and 6. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss H1	Truss Type Monopitch Girder	Qty 1	Ply 2	Job Reference (optional)
-------------------------------------	-------------	--------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:59

Page: 1

ID: _Fckz7z7tdQODjLAKUdLGzxD8OV-Ak?gLLII?7V/RADWDOcM359IsEaAhq_FZfkJopmzD2k_



Loading	(psf)	Spacing	1-11-4	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.29	Vert(LL)	-0.03	3-6	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.49	Vert(CT)	-0.06	3-6	>965	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.00	1	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 44 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-3-8 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=492/0-3-8, (min. 0-1-8),
3=621/0-3-8, (min. 0-1-8)
Max Horiz 1=39 (LC 10)
Max Grav 1=584 (LC 2), 3=737 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-311/32
BOT CHORD 1-7=-15/323

NOTES

- 2-ply truss to be connected together as follows:
Top chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected with 10d (0.131"x3") nails as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed;
Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10; Min. flat roof snow load governs.
- Unbalanced snow loads have been considered for this design.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 3. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Use MiTek THD26 (With 18-16d nails into Girder & 12-10d x 1-1/2 nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 2-0-0 from the left end to 4-0-0 to connect truss(es) E2 (1 ply 2x4 SP) to back face of bottom chord.
 - Fill all nail holes where hanger is in contact with lumber.
- LOAD CASE(S)** Standard
- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-46, 3-4=-19
Concentrated Loads (lb)
Vert: 7=-387, 8=-387


Job 22050129 - Opt Bonus Room	Truss H2	Truss Type Monopitch	Qty 4	Ply 1	Job Reference (optional)
-------------------------------------	-------------	-------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:59

Page: 1

ID:Wfp9oMCyPvLCm4fEBU9Bg4zD2sR-AK?gLLII?7VRADWDOcM359IiWaFBqV7ZfkJopmzD2k_



Scale = 1:61.6

Loading	(psf)	Spacing	1-11-4	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.91	Vert(LL)	0.00	5	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.14	Vert(CT)	-0.01	5-6	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.33	Horz(CT)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 68 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3 *Except* W5:2x4 SP No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 8'-4" oc bracing.
WEBS 1 Row at midpt 3-4

REACTIONS (lb/size) 4=269/ Mechanical, (min. 0-1-8), 6=269/0-3-8, (min. 0-1-8)
Max Horiz 6=259 (LC 10)
Max Uplift 4=-123 (LC 10)
Max Grav 4=377 (LC 24), 6=366 (LC 25)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-337/148, 1-6=-334/68
BOT CHORD 5-6=-499/500, 4-5=-230/353
WEBS 1-5=-152/278, 2-4=-398/216

- NOTES**
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 3-1-12, Interior (1) 3-1-12 to 8-4-1 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-0" tall by 2'-0" wide will fit between the bottom chord and any other members.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 123 lb uplift at joint 4.

- 6) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 6. This connection is for uplift only and does not consider lateral forces.
 - 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- LOAD CASE(S)** Standard


Job 22050129 - Opt Bonus Room	Truss I1	Truss Type Roof Special Girder	Qty 1	Ply 2	Job Reference (optional)
-------------------------------------	-------------	-----------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:59

Page: 1

ID:p?koGIHLm3DC69ha6SnqSYzD2sK-Ak?gLLI?7VRADWDCm359Ih4aDvqszZfkJopmzD2K_



Scale = 1:78.5

Plate Offsets (X, Y): [2:0-3-8,0-3-0]

Loading	(psf)	Spacing	1-11-4	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	1.00	Vert(LL)	0.03	4-5	>999	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.28	Vert(CT)	-0.04	4-5	>999	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.53	Horz(CT)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0											
											Weight: 209 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 8-2-9 oc purlins, except end verticals, and 2-0-0 oc purlins (3-1-0 max.): 2-3.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 1-6, 3-4

REACTIONS (lb/size) 4=1103/ Mechanical, (min. 0-1-8), 6=1103/0-3-8, (min. 0-1-8)
Max Horiz 6=-297 (LC 7)
Max Uplift 4=-124 (LC 8), 6=-139 (LC 7)
Max Grav 4=1643 (LC 24), 6=1633 (LC 25)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-7=-406/60, 3-7=-406/60, 3-4=-1140/6
BOT CHORD 6-8=-159/443, 5-8=-159/443
WEBS 2-6=-1367/165, 2-5=-516/733, 3-5=-217/839

- NOTES**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.33

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=18.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
 - Unbalanced snow loads have been considered for this design.
 - Provide adequate drainage to prevent water ponding.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 124 lb uplift at joint 4.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 6. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Load case(s) 1, 2 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - Use MiTek THD26 (With 18-16d nails into Girder & 12-10d x 1-1/2 nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 1-0-8 from the left end to 7-0-8 to connect truss(es) H2 (1 ply 2x4 SP) to back face of bottom chord.
 - Fill all nail holes where hanger is in contact with lumber.
- LOAD CASE(S)** Standard
- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-126, 2-3=-136, 4-6=-19
Concentrated Loads (lb)


Job 22050129 - Opt Bonus Room	Truss PB1	Truss Type Piggyback	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	--------------	-------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:59

Page: 1

ID:aPPBmHjaaUvDqfpKaHGfSjzD8Op-Ak?gLLII?7V/RADWDOcM359lwqaHkq_eZfkJopmzD2k_



Scale = 1:32.3

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.04	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.00	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 39 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 8-7-13.
(lb) - Max Horiz 2=60 (LC 12), 11=60 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) 8, 10
Max Grav All reactions 250 (lb) or less at joint (s) 2, 6, 8, 9, 10, 11, 15

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-3-7 to 3-1-4, Interior (1) 3-1-4 to 5-1-4, Exterior(2R) 5-1-4 to 8-1-4, Interior (1) 8-1-4 to 9-11-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.

- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 6, 9, 10, and 8. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss PB2	Truss Type Piggyback	Qty 14	Ply 1	Job Reference (optional)
-------------------------------------	--------------	-------------------------	-----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:39:59

Page: 1

ID:2bzZzdkCLn14RpOW7_nu?XzD8Oo-Ak?gLLII?7VRADWDOcM359ItraEOq_uZfkJopmzD2k_



Scale = 1:32.6

Plate Offsets (X, Y): [2:0-2-11,0-1-8], [4:0-2-11,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							
BCDL	10.0									Weight: 35 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS

All bearings 8-7-13.
 (lb) - Max Horiz 2=-60 (LC 11), 7=-60 (LC 11)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 7, 11
 Max Grav All reactions 250 (lb) or less at joint (s) 2, 4, 7, 11 except 6=263 (LC 2)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-3-7 to 3-3-7, Interior (1) 3-3-7 to 5-1-4, Exterior(2R) 5-1-4 to 8-1-4, Interior (1) 8-1-4 to 9-11-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10

- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 4, and 6. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss PB3	Truss Type Piggyback	Qty 1	Ply 2	Job Reference (optional)
-------------------------------------	--------------	-------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:00

Page: 1

ID:2bzZzdkCLn14RpOW7_nu?XzD8Oo-exZ2YhmwmRdlN5PxJtldNr4c_chZQLiuO2LKczD2jz



Scale = 1:32.3

Loading	(psf)	Spacing	1-11-4	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.12	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.12	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.01	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 70 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 8-7-13.

(lb) - Max Horiz 2=-58 (LC 11), 7=-58 (LC 11)
Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 7, 11
Max Grav All reactions 250 (lb) or less at joint (s) 2, 4, 7, 11 except 6=256 (LC 2)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- 2-ply truss to be connected together as follows:
Top chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-3-7 to 3-3-7, Interior (1) 3-3-7 to 5-1-4, Exterior(2R) 5-1-4 to 8-1-4, Interior (1) 8-1-4 to 9-11-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 4, and 6. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss PB4	Truss Type Piggyback	Qty 5	Ply 1	Job Reference (optional)
-------------------------------------	--------------	-------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:00

Page: 1

ID:2bzZzdkCLn14RpOW7_nu?XzD8Oo-exZ2YhmwmRdlN5PxJtldNr2r_chZQYiuO2LKzD2jz



Scale = 1:34.2

Plate Offsets (X, Y): [4:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.23	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.12	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.06	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0											
										Weight: 32 lb	FT = 20%	

LUMBER

- TOP CHORD 2x4 SP No.2
- BOT CHORD 2x4 SP No.2
- WEBS 2x4 SP No.3
- OTHERS 2x4 SP No.3

BRACING

- TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
- BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 7-11-15.

- (lb) - Max Horiz 2=65 (LC 12), 8=65 (LC 12)
- Max Uplift All uplift 100 (lb) or less at joint(s) 2, 6, 8
- Max Grav All reactions 250 (lb) or less at joint (s) 2, 6, 8 except 7=382 (LC 2)

FORCES

- (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
- WEBS 3-7=-273/79

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-3-7 to 3-3-7, Interior (1) 3-3-7 to 5-1-4, Exterior(2R) 5-1-4 to 8-1-4, Interior (1) 8-1-4 to 8-7-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 6, 2, and 7. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss PB5	Truss Type Piggyback	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	--------------	-------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:00

Page: 1

ID:2bzZzdkCLn14RpOW7_nu?XzD8Oo-exZ2YhmwmRdlN5PxJtldNr4P_dzZQtuO2LKzD2jz



Scale = 1:32

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.04	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.04	Horz(CT)	n/a	-	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 36 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 7-11-15.
(lb) - Max Horiz 2=65 (LC 12), 11=65 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) 2, 7, 8, 10, 11
Max Grav All reactions 250 (lb) or less at joint (s) 2, 7, 8, 9, 10, 11

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-3-7 to 3-1-4, Interior (1) 3-1-4 to 5-1-4, Exterior(2R) 5-1-4 to 8-1-4, Interior (1) 8-1-4 to 8-7-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10

- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- 6) Gable requires continuous bottom chord bearing.
- 7) Gable studs spaced at 2-0-0 oc.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7, 2, 9, 10, and 8. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 11) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard

Job 22050129 - Opt Bonus Room	Truss VL1	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:00

Page: 1

ID:2bzZzdkCLn14RpOW7_nu?XzD8Oo-exZ2YhwmRdlnN5PxJtlDnr3e_bxZNGiuO2LKzD2jz




Plate Offsets (X, Y): [5:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.18	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.21	Horiz(TL)	0.00	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 101 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 4) All plates are 2x4 MT20 unless otherwise indicated.
- 5) Gable requires continuous bottom chord bearing.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1, 13, 14, 15 except (jt=lb) 10=112.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS All bearings 20-11-6.
(lb) - Max Horiz 1=165 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 1, 13, 14, 15 except 10=-112 (LC 14)
Max Grav All reactions 250 (lb) or less at joint (s) 1, 9 except 10=387 (LC 25), 12=426 (LC 25), 13=446 (LC 24), 14=431 (LC 24), 15=338 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 3-14=-256/154

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-6 to 3-0-6, Interior (1) 3-0-6 to 12-0-0, Exterior(2R) 12-0-0 to 15-0-0, Interior (1) 15-0-0 to 20-10-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10


Job 22050129 - Opt Bonus Room	Truss VL2	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:00

Page: 1

ID: _z4JOJmTtPHoh6YvFFPpM4yzD8Om-exZ2YhmwmRdlnN5PxJtlidNr2J_buZOQiuO2LKcZD2jz



Scale = 1:46.2

Plate Offsets (X, Y): [7:0-2-8,0-2-5]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	I/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.20	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.13	Horiz(TL)	0.00	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 85 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3
 SLIDER Right 2x4 SP No.3 -- 1-0-12

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 5) Gable requires continuous bottom chord bearing.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1, 7, 12, 13, 9, 8, 7.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS

All bearings 18-11-6.
 (lb) - Max Horiz 1=121 (LC 10)
 Max Uplift All uplift 100 (lb) or less at joint(s) 1, 7, 8, 9, 12, 13, 16
 Max Grav All reactions 250 (lb) or less at joint (s) 1, 7, 16 except 8=329 (LC 25), 9=446 (LC 25), 11=363 (LC 24), 12=452 (LC 24), 13=318 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 3-12=-277/142, 5-9=-273/139

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-6 to 3-0-6, Interior (1) 3-0-6 to 10-0-0, Exterior(2R) 10-0-0 to 13-0-0, Interior (1) 13-0-0 to 18-11-12 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 4) All plates are 2x4 MT20 unless otherwise indicated.


Job 22050129 - Opt Bonus Room	Truss VL3	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
----------------------------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:01

Page: 1

ID:SAehcen5eiPFIg75o7Kbd9zD8OI-677Rm1mZXII9PXfbV1PXAaODfNyqlsxs72ovsfzD2jy



Scale = 1:41.7

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.23	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.13	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.12	Horiz(TL)	0.00	8	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 64 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins.
 BOT CHORD Rigid ceiling directly applied or 6'-0" oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 8, 6.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS All bearings 15-11-4.
 (lb) - Max Horiz 1=97 (LC 10)
 Max Uplift All uplift 100 (lb) or less at joint(s) 6, 8
 Max Grav All reactions 250 (lb) or less at joint (s) 1, 5 except 6=366 (LC 25), 7=302 (LC 2), 8=385 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-8=-277/143, 4-6=-267/143

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-6 to 3-0-6, Interior (1) 3-0-6 to 8-0-0, Exterior(2R) 8-0-0 to 11-0-0, Interior (1) 11-0-0 to 15-6-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - 4) Gable requires continuous bottom chord bearing.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-0" tall by 2'-0" wide will fit between the bottom chord and any other members.


Job 22050129 - Opt Bonus Room	Truss VL4	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
----------------------------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:01

Page: 1

ID:SAehcen5eiPflG75o7Kbd9zD80l-677Rm1mZXlI9PXfbV1PXAAeONySitus72ovsfzD2jy



Scale = 1:36.4

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.18	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.09	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.05	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 45 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1, 8, 6.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS All bearings 11-11-4.
(lb) - Max Horiz 1=72 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) 1, 6, 8
Max Grav All reactions 250 (lb) or less at joint (s) 1, 5 except 6=305 (LC 25), 7=260 (LC 2), 8=309 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-8=-260/182, 4-6=-251/176

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-6 to 3-0-6, Interior (1) 3-0-6 to 6-0-0, Exterior(2R) 6-0-0 to 9-0-0, Interior (1) 9-0-0 to 11-11-10 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - 4) Gable requires continuous bottom chord bearing.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.


Job 22050129 - Opt Bonus Room	Truss VL5	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
----------------------------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:01

Page: 1

ID:SAehcen5eiPflG75o7Kbd9zD8Ol-677Rm1mZXli9PXfbV1PXAAoODANxrlsNs72ovsfzD2jy



Scale = 1:30.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.20	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.19	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.09	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0											
											Weight: 27 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 7-11-4 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 12 lb uplift at joint 1 and 9 lb uplift at joint 3.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS (lb/size) 1=31/7-11-4, (min. 0-1-8), 3=34/7-11-4, (min. 0-1-8), 4=47/7-11-4, (min. 0-1-8)
 Max Horiz 1=-47 (LC 9)
 Max Uplift 1=-12 (LC 31), 3=-9 (LC 30)
 Max Grav 1=67 (LC 30), 3=70 (LC 31), 4=558 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-4=-401/188

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-6 to 3-0-6, Interior (1) 3-0-6 to 4-0-0, Exterior(2R) 4-0-0 to 7-0-7, Interior (1) 7-0-7 to 7-11-10 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.


Job 22050129 - Opt Bonus Room	Truss VL6	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:01

Page: 1

ID:SAehcen5eiPfiG75o7Kbd9zD8OI-677Rm1mZXII9PXfbV1PXAaOFTNyltks72ovsfzD2jy



Scale = 1:30.4

Plate Offsets (X, Y): [2:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.11	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.10	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0											
											Weight: 11 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-11-4 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=133/3-11-4, (min. 0-1-8),
3=133/3-11-4, (min. 0-1-8)
Max Horiz 1=22 (LC 12)
Max Grav 1=158 (LC 2), 3=158 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Gable requires continuous bottom chord bearing.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss VL7	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:01

Page: 1

ID:SAehcen5eiPfiG75o7Kbd9zD8OI-677Rm1mZXII9PXfbV1PXAaO43NmlItks72ovsfzD2jy



Scale = 1:22.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.78	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.87	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.02	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 22 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 7-6-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 8 lb uplift at joint 3 and 4 lb uplift at joint 1.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS (lb/size) 1=244/7-4-3, (min. 0-1-8),
3=244/7-4-3, (min. 0-1-8)
Max Horiz 1=47 (LC 12)
Max Uplift 1=-4 (LC 11), 3=-8 (LC 15)
Max Grav 1=305 (LC 21), 3=317 (LC 21)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-6=-936/293, 1-6=-918/296
BOT CHORD 1-3=-396/901

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-0 to 3-1-0, Interior (1) 3-1-0 to 7-3-7 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10; Min. flat roof snow load governs.
- 3) Unbalanced snow loads have been considered for this design.
- 4) Gable requires continuous bottom chord bearing.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.


Job 22050129 - Opt Bonus Room	Truss VL8	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:01

Page: 1

ID:SAehcen5eiPfiG75o7Kbd9zD8OI-677Rm1mZXII9PXfbV1PXAaOB8NtNlts72ovsfzD2jy



Scale = 1:20.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.33	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.41	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.01	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0											
										Weight: 15 lb	FT = 20%	

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-3-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 5 lb uplift at joint 3 and 3 lb uplift at joint 1.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS (lb/size) 1=173/5-3-0, (min. 0-1-8),
 3=173/5-3-0, (min. 0-1-8)
 Max Horiz 1=32 (LC 12)
 Max Uplift 1=-3 (LC 11), 3=-5 (LC 15)
 Max Grav 1=225 (LC 21), 3=225 (LC 21)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-6=-588/267, 1-6=-572/269
 BOT CHORD 1-3=-354/562

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust)
 Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-0 to 3-1-0, Interior (1) 3-1-0 to 5-2-4 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10; Min. flat roof snow load governs.
- 3) Unbalanced snow loads have been considered for this design.
- 4) Gable requires continuous bottom chord bearing.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.


Job 22050129 - Opt Bonus Room	Truss VL9	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:01

Page: 1

ID:xMC3p_njP0XWwQIHMQsq9NzD8Ok-677Rm1mZXI9PXfbV1PXAAOCdNwPlrps72ovsfzD2jy



Scale = 1:42.4

Plate Offsets (X, Y): [3:0-2-8,Edge], [5:Edge,0-3-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.30	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.22	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.19	Horiz(TL)	0.00	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
										Weight: 44 lb	FT = 20%	

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6'-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6'-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 4) Gable requires continuous bottom chord bearing.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06-00 tall by 2'-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1 except (jt=lb) 5=181, 7=121, 6=137.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS All bearings 9-11-4.
(lb) - Max Horiz 1=96 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 1 except 5=-182 (LC 30), 6=-138 (LC 14), 7=-121 (LC 13)
Max Grav All reactions 250 (lb) or less at joint (s) 1, 5 except 6=326 (LC 25), 7=597 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-145/265, 4-5=-324/435
WEBS 2-7=-461/224, 4-6=-418/295

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 5-4-0, Exterior(2R) 5-4-0 to 8-4-0, Interior (1) 8-4-0 to 9-9-12 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10


Job 22050129 - Opt Bonus Room	Truss VL10	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
----------------------------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:01

Page: 1

ID:WnXxBzlr659x3yzihil7YkzD8On-677Rm1mZXII9PXfbV1PXAaOD1Nwglrs72ovsfzD2zyj



Scale = 1:35.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.21	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.20	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.12	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0											
										Weight: 32 lb	FT = 20%	

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 7-11-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 15 lb uplift at joint 1, 13 lb uplift at joint 3 and 38 lb uplift at joint 4.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS (lb/size) 1=28/7-11-8, (min. 0-1-8), 3=31/7-11-8, (min. 0-1-8), 4=479/7-11-8, (min. 0-1-8)
Max Horiz 1=-71 (LC 9)
Max Uplift 1=-15 (LC 31), 3=-13 (LC 30), 4=-38 (LC 13)
Max Grav 1=65 (LC 30), 3=67 (LC 31), 4=566 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-4=-418/161

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 4-0-0, Exterior(2R) 4-0-0 to 7-3-9, Interior (1) 7-3-9 to 7-11-12 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Gable requires continuous bottom chord bearing.


Job 22050129 - Opt Bonus Room	Truss VL11	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:02

Page: 1

ID:WnXxBzlr659x3yzihil7YkzD8On-aJhpzNnBI2101hEo3kwmjowQfnl61KF?LiXSO5zD2jx



Scale = 1:30.9

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.12	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.05	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0											
										Weight: 21 lb	FT = 20%	

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-3-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 10 lb uplift at joint 4.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS (lb/size) 1=43/5-3-8, (min. 0-1-8),
3=45/5-3-8, (min. 0-1-8),
4=271/5-3-8, (min. 0-1-8)
Max Horiz 1=-46 (LC 9)
Max Uplift 4=-10 (LC 13)
Max Grav 1=64 (LC 30), 3=66 (LC 31), 4=319 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.


Job 22050129 - Opt Bonus Room	Truss VL12	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:02

Page: 1

ID:WnXxBzlr659x3yzihil7YkzD8On-ajhpzNnBI2i01hEo3kwmjowRDnJM1K_?LiXSO5zD2jx



Scale = 1:29.9

Plate Offsets (X, Y): [2:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.05	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.04	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0											
										Weight: 8 lb	FT = 20%	

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-7-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=89/2-7-8, (min. 0-1-8),
3=89/2-7-8, (min. 0-1-8)
Max Horiz 1=21 (LC 12)
Max Grav 1=105 (LC 2), 3=105 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Gable requires continuous bottom chord bearing.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss VL14	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:02

Page: 1

ID: _z4JOJmTtPHoh6YvFPpM4yzD8Om-aJhpzNnBl2t01hEo3kwjowDMnFq1lx?LiXSO5zD2jx



Scale = 1:55.2

Plate Offsets (X, Y): [10:Edge,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.94	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.27	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.13	Horiz(TL)	0.00	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 108 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10'-0" oc bracing.
WEBS 1 Row at midpt 9-10, 8-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 15-0-6.
(lb) - Max Horiz 1=282 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 1, 10, 11, 12, 13, 14, 15, 16
Max Grav All reactions 250 (lb) or less at joint (s) 1, 10, 11, 12, 13, 14, 15 except 16=284 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-448/371, 2-3=-387/311, 3-4=-337/286, 4-5=-285/250

NOTES
1) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-6 to 3-0-6, Interior (1) 3-0-6 to 14-11-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2'-0" oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1, 10, 14, 15, 16, 13, 12, 11.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050129 - Opt Bonus Room	Truss VL15	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:02

Page: 1

ID:SAehcen5eiPflG75o7Kbd9zD8Ol-aJhpzNnBl2t01hEo3kwmjowEgnGC1lg?LiXSO5zD2jx



Scale = 1:66.5

Plate Offsets (X, Y): [5:0-3-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.85	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.25	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.15	Horiz(TL)	0.00	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 85 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 6-7

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1, 7, 8, 10, 11, 9.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS All bearings 14-1-7.

(lb) - Max Horiz 1=265 (LC 10)
 Max Uplift All uplift 100 (lb) or less at joint(s) 1, 7, 8, 9, 10, 11
 Max Grav All reactions 250 (lb) or less at joint (s) 1, 7, 8 except 9=342 (LC 24), 10=451 (LC 24), 11=310 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-439/304, 2-14=-381/238,
 3-14=-369/271, 3-4=-281/212
 WEBS 3-10=-268/132

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust)
 Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-6 to 3-0-6, Interior (1) 3-0-6 to 14-0-1 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Gable requires continuous bottom chord bearing.


Job 22050129 - Opt Bonus Room	Truss VL16	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:02

Page: 1

ID:WnXxBzlr659x3yzihil7YkzD8On-ajHpzNnBI2t01hEo3kwmjowK3nH81JW?LiXS05zD2jx



Scale = 1:51.3

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.51	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.19	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.09	Horiz(TL)	0.00	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 74 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6'-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10'-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06-00 tall by 2'-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 7, 8, 11, 10 except (jt=lb) 9=200.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS All bearings 11-1-7.
(lb) - Max Horiz 1=206 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 7, 8, 10, 11 except 9=-200 (LC 19)
Max Grav All reactions 250 (lb) or less at joint (s) 1, 7, 8, 9 except 10=397 (LC 24), 11=489 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-14=-350/228, 2-14=-329/254
WEBS 2-11=-291/153

- NOTES**
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-6 to 3-0-6, Interior (1) 3-0-6 to 11-0-1 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - 3) All plates are 2x4 MT20 unless otherwise indicated.
 - 4) Gable requires continuous bottom chord bearing.


Job 22050129 - Opt Bonus Room	Truss VL17	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
----------------------------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:02

Page: 1

ID: z4JOJmTtPHoh6YvFPpM4yzD8Om-aJhpzNnB12t01hEo3kwmjowLan1p1KE?LiXS05zD2jx



Scale = 1:47

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.41	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.08	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.05	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 40 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 8-1-7.
(lb) - Max Horiz 1=148 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 5, 6, 7
Max Grav All reactions 250 (lb) or less at joint (s) 1, 5, 6 except 7=271 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-290/202

- NOTES**
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-6 to 2-11-13, Interior (1) 2-11-13 to 8-0-1 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - 3) Gable requires continuous bottom chord bearing.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 5, 6, 7.


Job 22050129 - Opt Bonus Room	Truss VL18	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:02

Page: 1

ID: _z4JOJmTtPHoh6YvFPpM4yzD8Om-aJhpzNnBI2i01hEo3kwmjowPont1KG?LiXSO5zD2jx



Scale = 1:34.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.14	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.08	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.05	Horiz(TL)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 22 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING
TOP CHORD Structural wood sheathing directly applied or 5-1-7 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=77/5-1-7, (min. 0-1-8),
4=48/5-1-7, (min. 0-1-8),
5=212/5-1-7, (min. 0-1-8)
Max Horiz 1=90 (LC 10)
Max Uplift 4=-14 (LC 10), 5=-33 (LC 13)
Max Grav 1=98 (LC 25), 4=63 (LC 24), 5=255 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-6 to 2-10-4, Interior (1) 2-10-4 to 5-0-1 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - 3) Gable requires continuous bottom chord bearing.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 14 lb uplift at joint 4 and 33 lb uplift at joint 5.


Job 22050129 - Opt Bonus Room	Truss VL19	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:03

Page: 1

ID:GOjvnfg_Xiwl6TszAyu6Q?zD2t6-aJhpzNnBI2t01hEo3kwnjowJZn911Jk?LiXSO5zD2jx



Scale = 1:35.4

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.54	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.64	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.08	Horiz(TL)	0.01	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 57 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 6, 8, 7.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS All bearings 15-2-15.
(lb) - Max Horiz 1=129 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) 6, 7, 8
Max Grav All reactions 250 (lb) or less at joint (s) 1, 6 except 7=255 (LC 21), 8=611 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-11=-710/114
BOT CHORD 1-8=-188/682
WEBS 2-8=-395/148

- NOTES**
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-0 to 3-1-0, Interior (1) 3-1-0 to 15-2-3 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10; Min. flat roof snow load governs.
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) Gable requires continuous bottom chord bearing.


Job 22050129 - Opt Bonus Room	Truss VL20	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:03

Page: 1

ID:GOjvnfg_Xiwl6TszAyu6Q?zD2i6-3WFBjop3M?tfqp_dSR?F?TYWbBemnG9aMH?xXzD2jw



Scale = 1:35.8

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.27	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.23	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.06	Horiz(TL)	0.00	8	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 38 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 6, 1, 8, 7.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS All bearings 10-1-12.
 (lb) - Max Horiz 1=92 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 1, 6, 7, 8
 Max Grav All reactions 250 (lb) or less at joint (s) 1, 6, 7 except 8=463 (LC 21)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-11=-378/64, 1-11=-367/66
 BOT CHORD 1-8=-183/361
 WEBS 2-8=-316/170

- NOTES**
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-0 to 3-1-0, Interior (1) 3-1-0 to 10-1-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10; Min. flat roof snow load governs.
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) Gable requires continuous bottom chord bearing.


Job 22050129 - Opt Bonus Room	Truss VL21	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-------------------------------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:40:03

Page: 1

ID:2TFnb0BKecDL8w42eney7szD2sS-3WFBjop3M?tfqp_dSR?F?TbLbDzmnE9aMH?xXzD2jw



Scale = 1:22.9

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.11	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0											
										Weight: 11 lb	FT = 20%	

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-11-10 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=96/2-11-10, (min. 0-1-8),
3=96/2-11-10, (min. 0-1-8)
Max Horiz 1=49 (LC 10)
Max Uplift 3=-8 (LC 13)
Max Grav 1=113 (LC 2), 3=118 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Gable requires continuous bottom chord bearing.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 8 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard