



■	THD26-2	USP	1	NA	16d/3-1/2"	10d/3"
■	HUS26	USP	3	NA	16d/3-1/2"	16d/3-1/2"

= 1st Level Wall

= 2nd Level Wall

Truss Placement Plan
SCALE: 3/8"=1'

▲ = Indicates Left End of Truss
(Reference Engineered Truss Drawing)
Do NOT Erect Truss Backwards

LOAD CHART FOR JACK STUDS		
(BASED ON TABLES R502.5(1) & (2))		
END REACTION (UP TO) (LB)	NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADERS/ROOF	END REACTION (UP TO) (LB)
1700	1	3400
3400	2	6800
5100	3	10200
6800	4	13600
8500	5	17000
10200	6	
11900	7	
13600	8	
15300	9	

BUILDER	-	CITY / CO.	- / -
JOB NAME	Wayfare B OH	ADDRESS	-
PLAN	Wayfare B 3Car	MODEL	Roof
SEAL DATE	10/6/2020	DATE REV.	/ /
QUOTE #	WAYFARE B	DRAWN BY	Marshall Naylor
JOB #	J1120-5228	SALES REP.	Marshall Naylor

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY.					
These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com					
Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.					
Signature <u>Marshall Naylor</u> Marshall Naylor					

comTECH
ROOF & FLOOR TRUSSES & BEAMS
Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787 Fax: (910) 864-4444