


Job 22050128	Truss A01	Truss Type Common Supported Gable	Qty 2	Ply 1	Job Reference (optional)
-----------------	--------------	--------------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:06

Page: 1

ID:svmrgyDFAqxt3KP5cXkZVozDAKf-XN4TWtoe2Ek939RkydgNYenoUzR5DLOnv_ZOAA4zD2w3



Scale = 1:55.4
Plate Offsets (X, Y): [13:0-3-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.15	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.09	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.16	Horz(CT)	0.01	20	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0											
											Weight: 223 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 10-29, 9-30, 11-27

REACTIONS All bearings 30-1-0.
(lb) - Max Horiz 37=-215 (LC 11)
Max Uplift All uplift 100 (lb) or less at joint(s) 20, 22, 23, 24, 25, 26, 27, 30, 31, 32, 33, 34, 35 except 21=-107 (LC 14), 36=-135 (LC 10), 37=-175 (LC 11)
Max Grav All reactions 250 (lb) or less at joint(s) 20, 21, 22, 23, 24, 25, 26, 27, 29, 30, 31, 32, 33, 34, 35, 36, 37

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 9-10=-180/291, 10-11=-180/291
WEBS 10-29=-258/103

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner(3E) 0-1-12 to 3-0-8, Exterior(2N) 3-0-8 to 15-0-8, Corner(3R) 15-0-8 to 18-0-10, Exterior(2N) 18-0-10 to 31-0-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf, Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2-0-0 oc.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 20, 30, 31, 32, 33, 34, 35, 27, 26, 25, 24, 23, 22 except (jt=lb) 37=175, 36=135, 21=106.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 22050128	Truss A02	Truss Type Common	Qty 1	Ply 1	Job Reference (optional)
-----------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:06

Page: 1

ID:WU0omsZSLkbn1n7fp7mMBVzDAKC-XN4TWtoo2Ek939RkydgNYenetzlaDH0nv_ZOA4zD2w3




Plate Offsets (X, Y): [9:Edge,0-8-2], [14:Edge,0-8-2]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.83	Vert(LL)	-0.10	12-13	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.70	Vert(CT)	-0.19	12-13	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.44	Horz(CT)	0.04	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 182 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 6-12, 2-12

REACTIONS (lb/size) 9=1062/0-3-8, (min. 0-1-11), 14=1008/ Mechanical, (min. 0-1-8)
Max Horiz 14=-215 (LC 9)
Max Grav 9=1413 (LC 26), 14=1351 (LC 25)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-1784/152, 2-3=-1289/168, 3-15=-1178/190, 4-15=-1167/212, 4-16=-1166/211, 5-16=-1178/189, 5-6=-1287/167, 6-7=-1785/153, 1-14=-1231/123, 7-9=-1293/162
BOT CHORD 13-14=-172/500, 13-17=-23/1539, 12-17=-23/1539, 11-12=-14/1402, 11-18=-14/1402, 10-18=-14/1402, 9-10=-81/449
WEBS 4-12=-82/946, 6-12=-631/139, 6-10=0/289, 2-12=-641/141, 2-13=0/285, 1-13=0/1102, 7-10=0/1029

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 3-1-14, Interior (1) 3-1-14 to 15-0-8, Exterior(2R) 15-0-8 to 18-0-10, Interior (1) 18-0-10 to 31-0-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 9. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss A03	Truss Type Roof Special	Qty 5	Ply 1	Job Reference (optional)
-----------------	--------------	----------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:06

Page: 1

ID:hcBz4dhLI6zCsTTnyxSy7qzDAK1-XN4TWtoo2Ek939RkydgNYeneKzLADD6nv_ZOA4zD2w3



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.80	Vert(LL)	-0.16	9-10	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.47	Vert(CT)	-0.29	9-10	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.69	Horz(CT)	0.04	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 187 lb	FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP 2400F 2.0E *Except* T1:2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 5-0-12 oc purlins, except end verticals.
BOT CHORD 2x4 SP 2400F 2.0E	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 3-13, 6-9
REACTIONS (lb/size) 9=1062/0-3-8, (min. 0-1-8), 14=1008/ Mechanical, (min. 0-1-8) Max Horiz 14=-211 (LC 13) Max Grav 9=1468 (LC 30), 14=1367 (LC 29)	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-1340/141, 2-15=-1712/268, 3-15=-1554/293, 3-16=-1605/334, 16-17=-1504/353, 4-17=-1502/374, 4-18=-1627/406, 18-19=-1637/383, 5-19=-1655/379, 5-6=-1753/360, 6-20=-613/251, 7-20=-797/215, 7-9=-656/267, 1-14=-1461/140
BOT CHORD	13-21=-91/1498, 21-22=-91/1498, 12-22=-91/1498, 12-23=0/1055, 11-23=0/1055, 11-24=0/1055, 10-24=0/1055, 10-25=-101/1434, 25-26=-101/1434, 9-26=-101/1434
WEBS	2-13=-799/222, 3-12=-395/247, 4-12=-120/825, 4-10=-155/846, 6-10=-367/274, 6-9=-1178/42, 1-13=-163/1704

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDD=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 5-1-12 to 7-0-0, Interior (1) 7-0-0 to 20-0-8, Exterior(2R) 20-0-8 to 23-0-10, Interior (1) 23-0-10 to 36-0-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10; Min. flat roof snow load governs.
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDD = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 9. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss A04	Truss Type Roof Special	Qty 9	Ply 1	Job Reference (optional)
-----------------	--------------	----------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:06

Page: 1

ID:TQBPJA?1so7fMjtawhPpe5zDAJe-XN4TWtoo2Ek939RkydgNYeneKzLADGwnv_ZOA4zD2w3



Scale = 1:66.8

Plate Offsets (X, Y): [3:0-5-8,0-2-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.80	Vert(LL)	-0.16	10-11	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.47	Vert(CT)	-0.29	10-11	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.51	Horz(CT)	0.04	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 202 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2 *Except* T3,T4:2x4 SP 2400F 2.0E
BOT CHORD 2x4 SP 2400F 2.0E
WEBS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 3-10-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 2-16.
WEBS 1 Row at midpt 4-15, 7-10

REACTIONS (lb/size) 2=132/0-3-8, (min. 0-1-8), 10=1052/0-3-8, (min. 0-1-8), 16=1281/0-3-8, (min. 0-1-8)
Max Horiz 2=213 (LC 14)
Max Uplift 2=-89 (LC 11)
Max Grav 2=276 (LC 40), 10=1453 (LC 30), 16=1743 (LC 29)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-20=-149/483, 3-20=-60/537, 3-4=-1407/284, 4-21=-1544/336, 21-22=-1471/349, 22-23=-1456/352, 5-23=-1442/376, 5-24=-1614/407, 24-25=-1619/384, 6-25=-1637/379, 6-7=-1730/362, 7-26=-609/258, 8-26=-793/225, 8-10=-653/272
BOT CHORD 2-16=-512/135, 15-16=-66/1214, 15-27=-87/1420, 14-27=-87/1420, 14-28=-87/1420, 13-28=-87/1420, 13-29=0/1025, 12-29=0/1025, 12-30=0/1025, 11-30=0/1025, 11-31=-101/1406, 31-32=-101/1406, 10-32=-101/1406
WEBS 3-16=-2198/242, 3-15=0/425, 4-15=-328/53, 4-13=-355/243, 5-13=-116/765, 5-11=-159/848, 7-11=-370/278, 7-10=-1146/37

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -0-11-13 to 2-6-5, Interior (1) 2-6-5 to 20-0-8, Exterior(2R) 20-0-8 to 23-6-10, Interior (1) 23-6-10 to 36-0-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10; Min. flat roof snow load governs.
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 10. This connection is for uplift only and does not consider lateral forces.
 - One RT16A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 16. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss A05	Truss Type Roof Special	Qty 1	Ply 1	Job Reference (optional)
-----------------	--------------	----------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:07

Page: 1

ID:6?RNP5LD1inYKnb97HQcJcZDAJB-?ZerjDpQpYs0gJ0wWKBc4sKp4NkWyjAw8elxIWzD2w2



Scale = 1:62.3

Plate Offsets (X, Y): [3:0-4-0,0-2-0], [9:Edge,0-8-2]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.80	Vert(LL)	-0.06	10-12	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.27	Vert(CT)	-0.12	10-12	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.51	Horz(CT)	0.02	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 192 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP 2400F 2.0E
 WEBS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 4-0-8 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
 WEBS 1 Row at midpt 3-14, 3-12, 6-12

REACTIONS (lb/size) 9=910/0-3-8, (min. 0-1-8), 14=1160/0-3-8, (min. 0-1-8)
 Max Horiz 14=-211 (LC 13)
 Max Grav 9=1218 (LC 30), 14=1498 (LC 3)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 3-17=-147/365, 3-18=-945/209, 18-19=-846/222, 4-19=-841/243, 4-20=-837/247, 20-21=-847/225, 5-21=-865/220, 5-6=-958/203, 6-22=-1349/209, 7-22=-1476/164, 7-9=-1097/238
 BOT CHORD 13-14=-29/778, 13-23=-26/786, 12-23=-26/786, 11-12=-30/1146, 11-24=-30/1146, 10-24=-30/1146, 9-10=-120/442
 WEBS 3-14=-1470/336, 4-12=-81/594, 6-12=-655/203, 6-10=0/307, 7-10=0/780, 3-13=0/260

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 5-1-12 to 7-0-0, Interior (1) 7-0-0 to 20-0-8, Exterior(2R) 20-0-8 to 23-0-10, Interior (1) 23-0-10 to 36-0-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10; Min. flat roof snow load governs.
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT16A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 14. This connection is for uplift only and does not consider lateral forces.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 9. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss A06	Truss Type Common	Qty 7	Ply 1	Job Reference (optional)
-----------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:07

Page: 1

ID:degafFhHcW_Pjdbq?TUGJzDALK-?ZerjDpQpYs0gJ0wWKBc4sKpZNMfMydEw8elxiWzD2w2



Scale = 1:73.2

Plate Offsets (X, Y): [1:Edge,0-1-12], [10:Edge,0-8-2], [12:0-3-12,0-1-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.77	Vert(LL)	-0.27	15-17	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.60	Vert(CT)	-0.54	15-17	>578	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.89	Horz(CT)	0.03	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 208 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP 2400F 2.0E
 WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-11-13 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. Except: 6-0-0 oc bracing: 14-19
 WEBS 1 Row at midpt 4-12, 4-20, 7-12

REACTIONS (lb/size) 10=1009/0-3-8, (min. 0-1-8), 21=1430/0-3-8, (min. 0-1-9)
 Max Horiz 21=-215 (LC 9)
 Max Grav 10=1351 (LC 26), 21=1908 (LC 25)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-121/335, 2-3=-954/0, 3-4=-839/0, 4-23=-1130/23, 5-23=-1030/47, 5-24=-1138/21, 6-24=-1147/0, 6-7=-1263/0, 7-8=-1671/0, 8-10=-1215/61
 BOT CHORD 20-21=0/669, 20-25=0/1074, 18-25=0/1074, 16-18=0/1074, 16-26=0/1074, 13-26=0/1074, 12-13=0/1074, 11-12=0/1307, 10-11=-52/466
 WEBS 12-14=-274/39, 19-20=-598/33, 4-19=-431/99, 2-20=0/1122, 2-21=-2118/0, 1-21=-349/205, 7-12=-547/176, 5-12=0/954, 8-11=0/913

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 3-1-14, Interior (1) 3-1-14 to 15-0-8, Exterior(2R) 15-0-8 to 18-0-10, Interior (1) 18-0-10 to 31-0-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- 200.0lb AC unit load placed on the bottom chord, 11-0-8 from left end, supported at two points, 5-0-0 apart.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 10. This connection is for uplift only and does not consider lateral forces.
- One RT16A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 21. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss A07	Truss Type Common	Qty 1	Ply 1	Job Reference (optional)
-----------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:07

Page: 1

ID:xhsVomqJc?ps8wfrTh8_xezDAIZ-?ZerjDpQpYs0gJ0wWKBc4sKo_NcOybw8elxiWzD2w2



Scale = 1:61.2

Plate Offsets (X, Y): [9:Edge,0-8-2], [14:Edge,0-8-2]

Loading	(psf)	Spacing	2-0-0	CSI	0.87	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.87	Vert(LL)	-0.25 12-13	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.79	Vert(CT)	-0.42 12-13	>696	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.97	Horz(CT)	0.02 9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH							
BCDL	10.0									Weight: 180 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 4-6-12 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 6-12

REACTIONS (lb/size) 9=847/0-3-8, (min. 0-1-8), 13=1223/2-11-8, (min. 0-1-14)
 Max Horiz 13=-215 (LC 11)
 Max Grav 9=1135 (LC 26), 13=1588 (LC 3)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-219/438, 2-3=-833/89, 3-15=-720/111, 4-15=-712/133, 4-16=-704/134, 5-16=-715/112, 5-6=-825/89, 6-7=-1342/88, 7-9=-1013/122
 BOT CHORD 13-17=-102/399, 17-18=-102/399, 12-18=-102/399, 11-12=0/1030, 11-19=0/1030, 10-19=0/1030, 9-10=-73/433
 WEBS 2-13=-1303/318, 2-12=0/465, 4-12=-7/442, 6-12=-648/152, 6-10=0/291, 1-13=-424/405, 7-10=0/670

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 3-1-14, Interior (1) 3-1-14 to 15-0-8, Exterior(2R) 15-0-8 to 18-0-10, Interior (1) 18-0-10 to 31-0-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT16A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 13. This connection is for uplift only and does not consider lateral forces.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 9. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss A08	Truss Type Common	Qty 2	Ply 1	Job Reference (optional)
-----------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:07

Page: 1

ID:fcTHvByaF34SKSQm2nKkLlzDAIP-?ZerjDpQpYs0gJ0wWKBc4sKohNf2ydXw8elxiWzD2w2



Scale = 1:61.2

Plate Offsets (X, Y): [9:Edge,0-8-2], [14:Edge,0-8-2]

Loading	(psf)	Spacing	2-0-0	CSI	0.89	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.89	Vert(LL)	-0.12 12-13	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.62	Vert(CT)	-0.20 12-13	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.87	Horz(CT)	0.01 9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH							
BCDL	10.0										Weight: 181 lb FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 12-13.
WEBS 1 Row at midpt 6-12

REACTIONS (lb/size) 9=776/0-3-8, (min. 0-1-8), 13=1294/0-3-8, (min. 0-2-0)
Max Horiz 13=-215 (LC 9)
Max Grav 9=1045 (LC 26), 13=1675 (LC 3)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-253/492, 2-3=-673/56, 3-15=-560/77, 4-15=-553/100, 4-16=-547/96, 5-16=-557/74, 5-6=-668/52, 6-7=-1203/52, 7-9=-925/99
BOT CHORD 11-12=0/916, 11-19=0/916, 10-19=0/916, 9-10=-72/420
WEBS 2-13=-1329/342, 2-12=-44/704, 4-12=-18/307, 6-12=-670/154, 6-10=0/314, 1-13=-497/458, 7-10=0/569

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 3-1-14, Interior (1) 3-1-14 to 15-0-8, Exterior(2R) 15-0-8 to 18-0-10, Interior (1) 18-0-10 to 31-0-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT16A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 13. This connection is for uplift only and does not consider lateral forces.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 9. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss B01	Truss Type Common Supported Gable	Qty 1	Ply 1	Job Reference (optional)
-----------------	--------------	--------------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:07

Page: 1

ID:qkdRCy5UFSu99lTBb0wH4zDAIE-?ZerjDpQpYs0gJ0wWKBc4sK_Ino7yonw8elxiWzD2w2



Scale = 1:46

Plate Offsets (X, Y): [16:0-1-11,0-0-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.11	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.04	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.15	Horz(CT)	0.00	16	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0											
											Weight: 141 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6'-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6'-0-0 oc bracing.

REACTIONS All bearings 22-11-0.
(lb) - Max Horiz 29--153 (LC 13)
Max Uplift All uplift 100 (lb) or less at joint(s) 16, 17, 18, 19, 20, 21, 24, 25, 26, 27, 28, 29
Max Grav All reactions 250 (lb) or less at joint(s) 16, 17, 18, 19, 20, 21, 23, 24, 25, 26, 27, 28, 29

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner(3E) -0-11-8 to 2-0-8, Exterior(2N) 2-0-8 to 11-5-8, Corner(3R) 11-5-8 to 14-5-8, Exterior(2N) 14-5-8 to 23-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2-0-0 oc.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06-00 tall by 2'-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 29, 16, 24, 25, 26, 27, 28, 21, 20, 19, 18, 17.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 22050128	Truss B02	Truss Type Common	Qty 6	Ply 1	Job Reference (optional)
-----------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:08

Page: 1

ID:Ear?PnK1yb_2YDHjMoNc5lZDAHw-TICDxZq3as_tITa642ird3t23n_Lh4x4NI2VFyzD2w1




Plate Offsets (X, Y): [2:Edge,0-2-12], [6:Edge,0-2-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.53	Vert(LL)	-0.11	9-11	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.68	Vert(CT)	-0.17	9-11	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.86	Horz(CT)	0.04	8	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 133 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 4-8-8 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 8=819/0-3-8, (min. 0-1-8), 12=819/0-3-8, (min. 0-1-8)
 Max Horiz 12=-153 (LC 13)
 Max Grav 8=1088 (LC 30), 12=1088 (LC 29)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-507/109, 3-13=-1300/146, 13-14=-1232/159, 4-14=-1222/177, 4-15=-1222/177, 15-16=-1232/159, 5-16=-1300/146, 5-6=-506/109, 2-12=-443/120, 6-8=-443/120
 BOT CHORD 11-12=-46/1224, 11-17=0/846, 10-17=0/846, 10-18=0/846, 9-18=0/846, 8-9=-36/1122
 WEBS 4-9=-41/584, 5-9=-261/147, 4-11=-41/584, 3-11=-261/147, 3-12=-968/44, 5-8=-967/44

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -0-11-8 to 2-0-8, Interior (1) 2-0-8 to 11-5-8, Exterior(2R) 11-5-8 to 14-5-8, Interior (1) 14-5-8 to 23-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 12 and 8. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss B03	Truss Type Common	Qty 2	Ply 1	Job Reference (optional)
-----------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:08

Page: 1

ID:bYeuSVOAn7cLf_Ah9LznoLzDAHr-TICDxZq3as_tITa642ird3t2un_Vh394NI2VFyzD2w1



Scale = 1:46.6

Plate Offsets (X, Y): [1:Edge,0-2-12], [5:Edge,0-2-12]

Loading	(psf)	Spacing	2-0-0	CSI	0.54	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.54	Vert(LL)	-0.11	8-10	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.67	Vert(CT)	-0.17	8-10	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.91	Horz(CT)	0.04	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 132 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 4-8-7 oc purlins, except end verticals.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 7=820/0-3-8, (min. 0-1-8), 11=765/0-3-8, (min. 0-1-8)
 Max Horiz 11=-149 (LC 11)
 Max Grav 7=1088 (LC 30), 11=1025 (LC 29)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-440/77, 2-12=-1305/149, 12-13=-1237/162, 3-13=-1225/180, 3-14=-1221/177, 14-15=-1231/159, 4-15=-1300/146, 4-5=-506/108, 1-11=-338/68, 5-7=-442/120
 BOT CHORD 10-11=-48/1232, 9-10=0/846, 9-16=0/846, 8-16=0/846, 7-8=-36/1123
 WEBS 3-8=-41/584, 4-8=-261/147, 3-10=-42/590, 2-10=-271/149, 2-11=-1023/72, 4-7=-967/45

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 3-1-12, Interior (1) 3-1-12 to 11-5-8, Exterior(2R) 11-5-8 to 14-5-8, Interior (1) 14-5-8 to 23-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 11 and 7. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss B04	Truss Type Common	Qty 1	Ply 1	Job Reference (optional)
-----------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:08

Page: 1

ID:bYeuSVOAn7cLf_Ah9LznoLzDAHr-TICDxZq3as_tITa642ird3t3gn_Lh394NI2VfyzD2w1



Scale = 1:43.5

Plate Offsets (X, Y): [1:Edge,0-3-4], [5:Edge,0-3-4]

Loading	(psf)	Spacing	2-0-0	CSI	0.49	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.49	Vert(LL)	-0.11	7-9	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.68	Vert(CT)	-0.17	7-9	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.91	Horz(CT)	0.04	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 130 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 4-9-15 oc purlins, except end verticals.

Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 6=766/0-3-8, (min. 0-1-8), 10=766/0-3-8, (min. 0-1-8)
 Max Horiz 10=-141 (LC 13)
 Max Grav 6=1028 (LC 29), 10=1028 (LC 28)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-439/77, 2-11=-1311/150, 11-12=-1243/163, 3-12=-1231/181, 3-13=-1231/181, 13-14=-1243/162, 4-14=-1311/150, 4-5=-439/77, 1-10=-337/68, 5-6=-337/68
 BOT CHORD 9-10=-79/1231, 9-15=0/843, 8-15=0/843, 8-16=0/843, 7-16=0/843, 6-7=-70/1127
 WEBS 3-7=-43/594, 4-7=-271/149, 3-9=-43/593, 2-9=-271/149, 2-10=-1030/72, 4-6=-1030/72

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 3-1-12, Interior (1) 3-1-12 to 11-5-8, Exterior(2R) 11-5-8 to 14-5-8, Interior (1) 14-5-8 to 22-9-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 10 and 6. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss C01	Truss Type Common Supported Gable	Qty 1	Ply 1	Job Reference (optional)
-----------------	--------------	--------------------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:08

Page: 1

ID:4GF7oTp7Xu0NLNLPiB5_jjzDAHI-TICDxZq3as_tITa642ird3t9dn8WhHm4NI2VfyzD2w1



Scale = 1:31.5

Plate Offsets (X, Y): [9:0-1-11,0-0-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.11	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.03	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.00	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0											
											Weight: 63 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.

Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS

All bearings 12-7-0.
 (lb) - Max Horiz 15=92 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 9, 10, 11, 13, 14, 15
 Max Grav All reactions 250 (lb) or less at joint(s) 9, 10, 11, 12, 13, 14, 15

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner(3E) -0-11-8 to 2-3-8, Exterior(2N) 2-3-8 to 6-3-8, Corner(3R) 6-3-8 to 9-3-8, Exterior(2N) 9-3-8 to 12-5-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 15, 9, 13, 14, 11, 10.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss C02	Truss Type Common	Qty 2	Ply 1	Job Reference (optional)
-----------------	--------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:08

Page: 1

ID: MdAmGsuWu1vNhSNld9jdVCzDAHB-TICDxZq3as_tITa642ird3t_9n53hGp4NI2VfyzD2w1



Scale = 1:36.7

Plate Offsets (X, Y): [5:Edge,0-6-12], [7:Edge,0-6-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.78	Vert(LL)	0.00	6	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.25	Vert(CT)	-0.04	6-7	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.10	Horz(CT)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 67 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 5=414/0-3-8, (min. 0-1-8), 7=471/0-3-8, (min. 0-1-8)
 Max Horiz 7=92 (LC 12)
 Max Grav 5=489 (LC 2), 7=561 (LC 2)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-8=-563/83, 8-9=-468/90, 3-9=-464/109, 3-10=-461/106, 10-11=-464/87, 4-11=-557/80, 2-7=-507/163, 4-5=-434/113
 BOT CHORD 6-7=-168/387, 5-6=-90/283

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -0-11-8 to 2-0-8, Interior (1) 2-0-8 to 6-3-8, Exterior(2R) 6-3-8 to 9-3-8, Interior (1) 9-3-8 to 12-5-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss C03	Truss Type Common Girder	Qty 1	Ply 2	Job Reference (optional)
-----------------	--------------	-----------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:08

Page: 1

ID:U7Th?I3fq1YXIRfIOSgXzDAH_TICDxZq3as_tITa642ird3t38n04h3r4NI2VFyzD2w1



Scale = 1:38

Loading	(psf)	Spacing	2-0-0	CSI	0.46	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.46	Vert(LL)	-0.08	6-13	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.57	Vert(CT)	-0.13	6-13	>999	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.93	Horz(CT)	0.01	1	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 129 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP 2400F 2.0E
 WEBS 2x4 SP No.3
 SLIDER Left 2x4 SP No.3 -- 2-6-0, Right 2x4 SP No.3 -- 2-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-4-12 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=3034/0-3-8, (min. 0-1-10), 5=3771/0-3-8, (min. 0-2-1)
 Max Horiz 1=69 (LC 35)
 Max Grav 1=3995 (LC 24), 5=5002 (LC 25)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-3845/0, 2-3=-4792/0, 3-4=-4793/0, 4-5=-3815/0
 BOT CHORD 1-15=0/4152, 15-16=0/4152, 6-16=0/4152, 6-17=0/4152, 17-18=0/4152, 5-18=0/4152
 WEBS 3-6=0/4554

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-7-0 oc.
 Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Use MiTek THD26 (With 18-16d nails into Girder & 12-10d x 1-1/2 nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 2-0-0 from the left end to 12-0-0 to connect truss(es) A02 (1 ply 2x4 SP), A03 (1 ply 2x4 SP) to back face of bottom chord.
- Fill all nail holes where hanger is in contact with lumber.

LOAD CASE(S) Standard

- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (lb/ft)
 Vert: 1-3=-48, 3-5=-48, 7-11=-20
 Concentrated Loads (lb)

Job 22050128	Truss C03	Truss Type Common Girder	Qty 1	Ply 2	Job Reference (optional)
-----------------	--------------	-----------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:08

Page: 2

ID:U7Th?I3fq1YXIRfFtOSgXzDAH_-TICDxZq3as_tITa642ird3t38n04h3r4NI2VFyzD2w1

Vert: 6=-992, 13=-996, 15=-988, 16=-992, 17=-992, 18=-992


Job 22050128	Truss E01	Truss Type Monopitch	Qty 1	Ply 1	Job Reference (optional)
-----------------	--------------	-------------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:08

Page: 1

ID:z7cLv4hHa?59_RrFwJOtevdDAGA-TICDxZq3as_tITa642ird3t3Jn4_hHN4NI2VFyzD2w1



Scale = 1:23.1

Loading	(psf)	Spacing	1-11-4	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.45	Vert(LL)	0.04	3-6	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.32	Vert(CT)	-0.08	3-6	>813	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.01	1	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							Weight: 18 lb	FT = 20%
BCDL	10.0											

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-3-8 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size)

1=169/0-3-8, (min. 0-1-8), 3=169/0-3-8, (min. 0-1-8)
 Max Horiz 1=41 (LC 14)
 Max Uplift 1=-2 (LC 11), 3=-6 (LC 15)
 Max Grav 1=220 (LC 21), 3=220 (LC 21)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-0 to 3-0-0, Interior (1) 3-0-0 to 5-1-12 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10; Min. flat roof snow load governs.
- Unbalanced snow loads have been considered for this design.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 3. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss VL01	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-----------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:08

Page: 1

ID: _P2IPONP6pa16KvbtmTcX7zDAKS-TICDxZq3as_tITa642ird3t88n6nhFZ4NI2VFyZD2w1



Scale = 1:50.1

Plate Offsets (X, Y): [20:0-2-6,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.14	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.14	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.18	Horiz(TL)	0.00	13	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 157 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 10-0-0 oc purlins.
Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 27-6-2.
(lb) - Max Horiz 1=148 (LC 11)
Max Uplift All uplift 100 (lb) or less at joint(s) 1, 14, 15, 16, 17, 18, 21, 22, 23, 24, 25
Max Grav All reactions 250 (lb) or less at joint(s) 1, 13, 15, 16, 17, 18, 19, 21, 22, 23, 24 except 14=303 (LC 35), 25=298 (LC 28)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-7 to 3-0-7, Interior (1) 3-0-7 to 13-9-8, Exterior(2R) 13-9-8 to 16-9-8, Interior (1) 16-9-8 to 27-6-9 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 21, 22, 23, 24, 25, 18, 17, 16, 15, 14.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss VL02	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-----------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:09

Page: 1

ID:DPdasHhj_prLEKuaPEXjbczDAK2-xymb8vqhlL96kwd9JelD4AHPHNBRlQfIDbxn2nOzD2w0



Scale = 1:48.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.30	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.25	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.38	Horiz(TL)	0.00	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 116 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 10-0-0 oc purlins.
Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 26-5-6.
(lb) - Max Horiz 1=142 (LC 14)
Max Uplift All uplift 100 (lb) or less at joint(s) 1, 8, 9, 12, 13
Max Grav All reactions 250 (lb) or less at joint(s) 1, 7 except 8=517 (LC 29), 9=417 (LC 29), 11=565 (LC 28), 12=422 (LC 28), 13=510 (LC 28)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-177/287
WEBS 4-11=-356/0, 3-12=-269/121, 2-13=-299/113, 5-9=-275/120, 6-8=-302/114

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-7 to 3-0-7, Interior (1) 3-0-7 to 13-3-2, Exterior(2R) 13-3-2 to 16-3-2, Interior (1) 16-3-2 to 26-5-13 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 12, 13, 9, 8.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss VL03	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-----------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:09

Page: 1

ID:DPdasHhj_prLEKuaPEXjbczDAK2-xymb8vqhL96kwd9JelD4AHPITBSYQipDbxn2nOzD2w0



Scale = 1:43.1

Loading	(psf)	Spacing	2-0-0	CSI	0.23	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.23	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.18	Horiz(TL)	0.00	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 96 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
OTHERS	2x4 SP No.3

BRACING

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 22-9-7.
(lb) - Max Horiz 1=122 (LC 14)
Max Uplift All uplift 100 (lb) or less at joint(s) 1, 8, 9, 12, 13
Max Grav All reactions 250 (lb) or less at joint(s) 1, 7 except 8=382 (LC 29), 9=432 (LC 29), 11=427 (LC 28), 12=436 (LC 28), 13=378 (LC 28)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 3-12=-286/127, 5-9=-291/126

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-7 to 3-0-7, Interior (1) 3-0-7 to 11-5-2, Exterior(2R) 11-5-2 to 14-5-2, Interior (1) 14-5-2 to 22-9-14 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 12, 13, 9, 8.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss VL04	Truss Type Valley	Qty 2	Ply 1	Job Reference (optional)
-----------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:09

Page: 1

ID:9S6CRvqfXJO7nZ2d1yFj6zDALL-xymb8vqhl96kwd9JelD4AHPHDBRnQIRDbxn2nOzD2w0



Scale = 1:36.2

Loading	(psf)	Spacing	2-0-0	CSI	0.31	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.31	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.22	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.14	Horiz(TL)	0.00	8	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 71 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
OTHERS	2x4 SP No.3

BRACING

TOP CHORD	
BOT CHORD	

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 18-2-9.
(lb) - Max Horiz 1=97 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) 6, 9
Max Grav All reactions 250 (lb) or less at joint(s) 1, 5 except 6=435 (LC 22), 8=332 (LC 2), 9=447 (LC 28)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 3-8=-281/1, 2-9=-321/131, 4-6=-321/131

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-7 to 3-0-7, Interior (1) 3-0-7 to 9-1-11, Exterior(2R) 9-1-11 to 12-1-11, Interior (1) 12-1-11 to 17-8-15 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9, 6.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 22050128	Truss VL05	Truss Type Valley	Qty 2	Ply 1	Job Reference (optional)
-----------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:09

Page: 1

ID:W14fvUznKBx60jCpGNLZgzDAJg-yymb8vqhL96kwd9JelD4AHPiKBTzQjXDbxn2nOzD2w0



Scale = 1:30.7

Loading	(psf)	Spacing	2-0-0	CSI	0.24	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.24	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.08	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.07	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 50 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 13-7-11.
 (lb) - Max Horiz 1=72 (LC 11)
 Max Uplift All uplift 100 (lb) or less at joint(s) 1, 6, 8
 Max Grav All reactions 250 (lb) or less at joint(s) 1, 5 except 6=361 (LC 22), 7=298 (LC 2), 8=353 (LC 21)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-8=-290/137, 4-6=-293/134

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-7 to 2-9-14, Interior (1) 2-9-14 to 6-10-5, Exterior(2R) 6-10-5 to 9-10-5, Interior (1) 9-10-5 to 13-8-2 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8, 6.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard




Job 22050128	Truss VL07	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-----------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:09

Page: 1

ID:rurriSkoeEbbT29099SpolzDAG6-xymb8vqhL96kwd9JelD4AHPJJBBSQkdDbxn2nOzD2w0



Scale = 1:25.4

Plate Offsets (X, Y): [2:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.15	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.13	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.01	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 13 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 4-6-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=152/4-6-0, (min. 0-1-8), 3=152/4-6-0, (min. 0-1-8)
Max Horiz 1=22 (LC 12)
Max Grav 1=180 (LC 2), 3=180 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-294/123

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Gable requires continuous bottom chord bearing.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.



Job 22050128	Truss VL08	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-----------------	---------------	----------------------	----------	----------	--------------------------

Carter Components - Sanford, Sanford, NC, user

Run: 8.53 S Mar 28 2022 Print: 8.530 S Mar 28 2022 MiTek Industries, Inc. Wed May 25 17:27:09

Page: 1

ID:uuZXwuTZ7HVL_3C13JbQapzDAHk-xymb8vqhL96kwd9JelD4AHPJJBBSQkdDbxn2nOzD2w0



Scale = 1:25.4

Plate Offsets (X, Y): [2:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.15	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.13	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.01	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 13 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 4-6-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=152/4-6-0, (min. 0-1-8), 3=152/4-6-0, (min. 0-1-8)
 Max Horiz 1=22 (LC 14)
 Max Grav 1=180 (LC 2), 3=180 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-294/123

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=13.9 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.