

<u>Truss Placement Plan</u> SCALE: 1/4" = 1'

LO	LOAD CHART FOR JACK STUDS								
	(BASED ON TABLES R502.5(1) & (b))								
NU	NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADER/GIRDER								
END REACTION (UP T0)	REQ'D STUBS FOR (2) PLY HEADER		END REACTION (UP TO)	REQ'D STUDS FOR (3) PLY HEADER		END REACTION (UP TO)	REQ'D STUDS FOR (4) PLY HEADER		
1700	1		2550	1		3400	1		
3400	2		5100	2		6800	2		
5100	3		7650	3		10200	3		
6800	4		10200	4		13600	4		
8500	5		12750	5		17000	5		
10200	6		15300	6					
11900	7								
13600	8								
15300	9								

BUILDER	Signature Home Builders	COUNTY	Harnett	TH The buil
JOB NAME	B NAME Lot 85 South Creek		Lot 85 South Creek	resp over wall rega
PLAN	1718 <i>G</i> L	MODEL	Roof	Bear pres
SEAL DATE	10/21/20	DATE REV.	02/00/22	(de four than be r
QUOTE#	UOTE# Quote#		Hampton Horrocks	spec reta
JOB#	J0223-0629	SALESMAN	Anthony Williams	

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. This is a trues placement i blackam only.

These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com

Searing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables derived from the prescriptive Code requirements) to determine the minimum oundation size and number of wood studs required to support reactions greater han 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be etained to design the support system for all reactions that exceed 15000#.

Hampton Horrocks



Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787 Fax: (910) 864-4444