




ATTIC VENTILATION:
THE NET FREE VENTILATING AREA SHALL BE NOT LESS THAN 1 TO 120 OF THE AREA OF THE SPACE VENTILATED EXCEPT THAT THE AREA MAY BE 1 TO 300 PROVIDED AT LEAST 80 PERCENT OF THE REQUIRED VENTILATING AREA IS PROVIDED BY VENTILATORS LOCATED IN THE UPPER PORTION OF THE SPACE TO BE VENTILATED AT LEAST 3 FEET ABOVE EAVE OR CORNICE VENTS WITH THE BALANCE OF THE REQUIRED VENTILATION TO BE PROVIDED BY EAVE OR CORNICE VENTS.
GROSS ATTIC AREA TO BE VENTILATED 1642 SQ.FT.
1642/300 = 5.47 SQ.FT. NET FREE AREA
50% OF VENTING MUST BE 3FT. ABOVE EAVE OR 50PFT VENTS.

THIS PLAN DESIGNED UNDER NORTH CAROLINA
RESIDENTIAL CODE 2018 EDITION (2018 IRC)
NC (2018 NRC) ; Wind : 115 - 120 mph



FOUNDATION STRUCTURAL NOTES:

- 1) (B) 2 x 10 SPF #2 GIRDER DROPPED, TYPICAL UNO.
 - 2) CONCRETE BLOCK PIER SIZE SHALL BE:
 SIZE HOLLOW MASONRY SOLID MASONRY
 8 x 16 UP TO 32' HIGH UP TO 5'-0" HIGH
 12 x 16 UP TO 48' HIGH UP TO 9'-0" HIGH
 16 x 16 UP TO 64' HIGH UP TO 12'-0" HIGH
 24 x 24 UP TO 96' HIGH UP TO 18'-0" HIGH
 WITH 50' x 50' x 10' CONCRETE FOOTINGS, UNO.
 - 3) WALL FOOTING AS FOLLOWS:
 DEPTH: 8" - UP TO 2-1/2 STORY
 10" - 3 STORY
 WIDTH: SIDING (OR EQUAL)
 - 16" - UP TO 2-1/2 STORY
 - 18" - 3 STORY
 BRICK VENEER
 - 16" - 1 STORY
 - 20" - 2 STORY
 - 24" - 3 STORY
- FOR FOUNDATION WALL HEIGHT AND BACKFILL REQUIREMENTS, REFER TO NORTH CAROLINA RESIDENTIAL CODE TABLE R404.1.1 (1 THRU 4).
 NOTE: ASSUMED SOIL BEARING CAPACITY = 2000 PSF. CONTRACTOR MUST VERIFY SITE CONDITIONS AND CONTACT SOILS ENGINEER IF MARGINAL OR UNSTABLE SOILS ARE ENCOUNTERED.
- ATTACH SILL PLATE WITH 1/2" dia. ANCHOR BOLTS AT 6'-0" CENTERS (7" EMBEDMENT) AND 12" FROM EACH FLATE END. (SECTION R 403.1.6)
- 4) ■ DESIGNATES A SIGNIFICANT POINT LOAD TO HAVE SOLID BLOCKING TO PIER. SOLID BLOCK: ALL BEAM BEARING POINTS NOTED TO HAVE THREE OR MORE STUDS TO END, TYPICAL.
- 5) ABBREVIATIONS:
 "SJ" = SINGLE JOIST
 "DJ" = DOUBLE JOIST
 "TJ" = TRIPLE JOIST


FOUNDATION VENTING

SECTION R408 UNDER FLOOR SPACE


R408.1 Ventilation. The under-floor space between the bottom of the floor joists and the earth under any building (except space occupied by a basement or cellar) shall be provided with ventilation openings through foundation walls or exterior walls. The minimum net area of ventilation openings shall not be less than 1 square foot for each 150 square feet (13.7 m squared) of under-floor space area. One such ventilating opening shall be within 3 feet (914 mm) of each corner of solid building.

CRAWL AREA TO BE VENTED: 761 SQ.FT.
 761/1500 = .51 NET FREE VENTING AREA REQUIRED

R408.2 Ground Vapor Retarder
 A minimum 6 mil. polyethylene vapor retarder shall be installed to cover all earth in the crawl space with joints lapped not less than 12"




2/15/2023
 P.E. TEAGUE, P.E., PLLC
 2705 WATERLOO CT. NC 27613
 PETEAGUE50@GMAIL.COM
 (919)247-2572 (Lic. #P-0207)



VERIFY ALL DIMENSIONS BEFORE CONSTRUCTION!

FOUNDATION
 SCALE 1/4" = 1'-0"





2/15/2023
 P.E. TEAGUE, P.E., PLLC
 2705 WATERLOO CT. NC 27613
 PETEAGUE50@GMAIL.COM
 (919)247-2572 (Lic. #P-0207)

- BEAM SCHEDULE
- (A) 2-2"x10" FLUSH
 - (B) 2-2"x10" DROPPED
 - (C) 2-2"x8" FLUSH
 - (D) 2-2"x8" DROPPED
 - (E) 2-1.75"x9.25" LVL FLUSH
 - (F) 2-1.75"x9.25" DROPPED
 - (G) 2- 1.75"x11 7/8" LVL FLUSH
 - (H) 3-1.75"x11 7/8" LVL FLUSH
 - (J) 3-1.75"x14" DROPPED
 - (K) W 8X15 OR 4-1.75"x9.25" LVL FLUSH WITH 5/8" BOLTS @20" OC
 - (M) W 8X24 STEEL FLUSH
 - (N) 2-1.75"x14" LVL DROPPED
 - (P) 2-1.75"x14" LVL BOTTOM FLUSH
 - (R) 2-1.75"x24" LVL DROPPED
 - (S) W 8X18 STEEL FLUSH
 - (T) 2-2"x12" DROPPED


WALL BRACING NOTES:
 WALL BRACING SHALL BE IN ACCORDANCE WITH SECTION R602.10.3 CONTINUOUS SHEATHING BRACING METHOD. CH-100P SHALL BE USED IN ACCORDANCE WITH TABLE R602.10.1.
 1. THE REQUIRED LENGTH OF BRACING FOR EACH SIDE OF A RECTANGLE CIRCUMSCRIBED AROUND THE PLAN OR A PORTION OF THE PLAN AT EACH STORY LEVEL SHALL BE IN ACCORDANCE WITH TABLE R602.10.1 AND FIGURE R602.10.3(H), UNLESS NOTED OTHERWISE. THE ENTIRE STRUCTURE IS ASSUMED TO BE CIRCUMSCRIBED WITH A SINGLE RECTANGLE.
 2. MINIMUM PANEL WIDTH IS 34". SEE SECTION R602.10.3 FOR ADDITIONAL INFORMATION. CONNECTION CRITERIA SHALL BE IN ACCORDANCE WITH TABLE R602.10.1.
 3. PORTAL FRAME CONSTRUCTION SHALL BE IN ACCORDANCE WITH FIGURE R602.10.1.
 4. HOLD DOWN DEVICES SHALL BE AS FOLLOWS: SIMPSON LSTA24 STRAP (OR EQUIVALENT) BETWEEN FLOORS EXTENDING FROM BOTTOM OF FLOOR BAND AND UP THE STUDS PER SITE PER BUILDER. SIMPSON H09 HOLD DOWN (OR EQUIVALENT) WHERE REQUIRED TO CONNECT DIRECTLY TO FOUNDATION.

BEAM CONNECTION DETAIL "A"

ATTACH BEAMS WITH A L 5 1/2" X 10" X 1/2" STEEL ANGLE EACH SIDE
 USE (2) 5/8" DIA. A325 BOLTS PER CONNECTION
 1/4" WELD EACH SIDE



STAIR CROSS SECTION (S/4)



FIRST FLOOR PLAN
 SCALE 1/4" = 1'-0"

SQUARE FOOTAGE - PLAN 'A'	
FIRST FLOOR	1243 SQ.FT.
SECOND FLOOR	1366 SQ.FT.
TOTAL HTD.	2609 SQ.FT.
GARAGE	465 SQ.FT.
COV. FRONT PORCH	150 SQ.FT.
SCREENED PORCH	160 SQ.FT.

THIS PLAN DESIGNED UNDER NORTH CAROLINA RESIDENTIAL CODE 2018 EDITION (2018 IRC)


The Jade 2
 GARAGE LEFT

GEMSTONE HOMES



2/15/2023
 P.E. TEAGUE, P.E., PLLC
 2705 WATERLOO CT. NC 27613
 PETEAGUE50@GMAIL.COM
 (919)247-2572 (Lic. #P-0207)

- BEAM SCHEDULE
- (A) 2-2"x10" FLUSH
 - (B) 2-2"x10" DROPPED
 - (C) 2-2"x8" FLUSH
 - (D) 2-2"x8" DROPPED
 - (E) 2-1.75"x9.25" LVL FLUSH
 - (F) 2-1.75"x9.25" DROPPED
 - (G) 2- 1.75"x11 7/8" LVL FLUSH
 - (H) 3-1.75"x11 7/8" LVL FLUSH
 - (J) 3-1.75"x14" DROPPED
 - (K) W 8X15 OR 4-1.75"x9.25" LVL FLUSH WITH 5/8" BOLTS @20' OC
 - (M) W 8X24 STEEL FLUSH
 - (N) 2-1.75"x14" LVL DROPPED
 - (P) 2-1.75"x14" LVL BOTTOM FLUSH
 - (R) 2-1.75"x24" LVL DROPPED
 - (S) W 8X18 STEEL FLUSH
 - (T) 2-2"x12" DROPPED




SECOND FLOOR PLAN
 SCALE 1/4" = 1'-0"

22/15/2023
 P.E. TEAGUE, P.E., PLLC
 2705 WATERLOO CT. NC 27613
 PETEAGUE50@GMAIL.COM
 (919)247-2572 (Lic. #P-0207)



ROOF FRAMING NOTES:

- (1) (115-120) MPH WIND ZONE
- (1) ALL RAFTERS TO BE 2x8 @ 16" O.C. WITH 2 X 12 RIDGE, UNO.
- (2) (2)2x10 OR (1) 1.75" X 11 7/8" LVL HIP. (2)2x10 HIPS MAY BE SPLICED WITH A MINIMUM 6'-0" OVERLAP AT CENTER.
- (3) (2)2x10 OR (1) 1.75" X 9.25" LVL VALLEY. DO NOT SPLICE VALLEYS
- (4) 1-1.75x11 7/8" LVL VALLEY
- (5) FALSE FRAME VALLEY ON 2x10 FLAT PLATE
- (6) 2"x6" RAFTERS @16" O.C. W/ 2x8 RIDGE
- (7) 2"x10" RAFTERS @16" O.C. W/ 2x12 RIDGE
- "SR" = SINGLE RAFTER
- "DR" = DOUBLE RAFTER
- "TR" = TRIPLE RAFTER
- "RS" = ROOF SUPPORT FOR RAFTER SPLICE
- "S" = (3) STUD OR 4x4 POST FOR ROOF SUPPORT
- FIR DOWN 2x8 RAFTERS OR USE 2x10 AT CATHEDRAL CEILINGS
- ATTACH VAULTED RAFTERS WITH HURRICANE CLIPS, SIMPSON "H-5" OR EQUIVALENT
- 2"x6" COLLAR TIES @32" TYPICAL



ROOF PLAN
 SCALE 1/4" = 1'-0"


THIS PLAN DESIGNED UNDER NORTH CAROLINA
 RESIDENTIAL CODE 2018 EDITION (2018 IRC)

The Jade 2
 GARAGE LEFT

GEMSTONE HOMES



2/15/2023
P.E. TEAGUE, P.E., PLLC
 2705 WATERLOO CT. NC 27613
 PETEAGUES0@GMAIL.COM
 (919)247-2572 (Lic. #P-0207)



SEE ROOF PLAN FOR DETAIL


ROOF PLAN OPT. 3RD CAR
 SCALE 1/4" = 1'-0"

ROOF FRAMING NOTES:


- (1) (15-120) MPH WIND ZONE
- (1) ALL RAFTERS TO BE 2x8 @ 16" O.C. WITH 2 X 12 RIDGE, UNO.
- (2) (2)2x10 OR (1) 1.75" X 11 7/8" LVL HIP, (2)2x10 HIPS MAY BE SPLICED WITH A MINIMUM 6'-0" OVERLAP AT CENTER.
- (3) (2)2x10 OR (1) 1.75" X 9.25" LVL VALLEY, DO NOT SPLICE VALLEYS
- (4) 1.75"X11 7/8" LVL VALLEY
- (5) FALSE FRAME VALLEY ON 2x10 FLAT PLATE
- (6) 2"x6" RAFTERS @ 16" O.C. W/ 2x8 RIDGE
- (7) 2"x10" RAFTERS @ 16" O.C. W/ 2x12 RIDGE
- "SR" = SINGLE RAFTER
- "DR" = DOUBLE RAFTER
- "TR" = TRIPLE RAFTER
- "RS" = ROOF SUPPORT FOR RAFTER SPLICE
- "R" = (3) STUD OR 4x4 POST FOR ROOF SUPPORT
- FIR DOWN 2x8 RAFTERS OR USE 2x10 AT CATHEDRAL CEILINGS
- ATTACH VAULTED RAFTERS WITH HURRICANE CLIPS, SIMPSON "H-5" OR EQUIVALENT
- 2"x6" COLLAR TIES @ 32" TYPICAL

BEAM SCHEDULE


A	2-2"x10" FLUSH
B	2-2"x10" DROPPED
C	2-2"x8" FLUSH
D	2-2"x8" DROPPED
E	2-1.75"x9.25" LVL FLUSH
F	2-1.75"x9.25" DROPPED
G	2- 1.75"x11 7/8" LVL FLUSH
H	3-1.75"x11 7/8" LVL FLUSH
J	3-1.75"x14" DROPPED
K	W 8X15 OR 4-1.75"x9.25" LVL FLUSH WITH 5/8" BOLTS @ 20" O.C.
M	W 8X24 STEEL FLUSH
N	2-1.75"x14" LVL DROPPED
P	2-1.75"x14" LVL BOTTOM FLUSH
R	2-1.75"x24" LVL DROPPED
S	W 8X18 STEEL FLUSH
T	2-2"x12" DROPPED





THIRD CAR OPTION



FRONT ELEVATION 3rd CAR OPTION
 SCALE 1/4" = 1'-0"



LEFT SIDE ELEVATION



FOUNDATION 3rd CAR OPT.
 SCALE 1/4" = 1'-0"

VERIFY ALL DIMENSIONS BEFORE CONSTRUCTION!

THIS PLAN DESIGNED UNDER NORTH CAROLINA RESIDENTIAL CODE 2018 EDITION (2018 IRC)

The Jade 2
 GARAGE LEFT

GEMSTONE HOMES

2/15/2022
 200512

STRUCTURAL NOTES

1) ALL CONSTRUCTION SHALL CONFORM TO THE LATEST REQUIREMENTS OF THE NORTH CAROLINA STATE RESIDENTIAL CODE - 2018 EDITION (2018 IRC), PLUS ALL LOCAL CODES AND REGULATIONS.
ALL MEMBERS SHALL BE FRAMED, ANCHORED, TIED AND BRACED IN ACCORDANCE WITH GOOD CONSTRUCTION PRACTICE AND THE BUILDING CODE.

2) DESIGN LOADS SEE TABLE R301.5

WIND SPEED: (REFER TO TABLE R301.2.4)
VERIFY ZONE BEFORE CONSTRUCTION.

3) WALL BRACING: WALLS SHALL BE BRACED ALONG BRACED WALL LINES ACCORDING TO SECTION R602.10. THE AMOUNT, LOCATION AND CONSTRUCTION OF BRACING SHALL COMPLY WITH R602.10. NOTE THAT THE BRACING SHOWN ON THE PLANS IS BASED ON THE PRESCRIPTIVE BRACING REQUIREMENTS OF THE CODE AND SHALL BE VERIFIED AND/OR APPROVED BY THE CODE OFFICIAL.

4) CONCRETE SHALL HAVE A MINIMUM 28 DAY STRENGTH OF 3000 PSI AND A MAXIMUM SLUMP OF 5 INCHES UNLESS NOTED OTHERWISE (NO). AIR ENTRAINMENT PER TABLE 402.2. ALL CONCRETE SHALL BE PROPORTIONED, MIXED, HANDLED, SAMPLED, TESTED AND PLACED IN ACCORDANCE WITH ACI STANDARDS. ALL SAMPLES FOR PUMPING SHALL BE TAKEN FROM THE EXIT END OF THE PUMP.

5) ALLOWABLE SOIL BEARING PRESSURE ASSUMED TO BE 2000 PSF. THE CONTRACTOR MUST CONTACT A GEOTECHNICAL ENGINEER AND THE STRUCTURAL ENGINEER IF UNSATISFACTORY SUBSURFACE CONDITIONS ARE ENCOUNTERED. THE SURFACE AREA ADJACENT TO THE FOUNDATION WALL SHALL BE PROVIDED WITH ADEQUATE DRAINAGE, AND SHALL BE GRADED SO AS TO DRAIN SURFACE WATER AWAY FROM FOUNDATION WALLS.

6) ALL FRAMING LUMBER SHALL BE SPF #2 (FB = 875 PSI) UNLESS NOTED OTHERWISE (NO). ALL TREATED LUMBER SHALL BE SYP #2 (FB=475 PSI). PLATE MATERIAL MAY BE SPF #3 OR SYP #3 (FC/PERP) = 425 PSI - MIN.

7) ALL WOODEN BEAMS AND HEADERS SHALL HAVE THE FOLLOWING END SUPPORTS: (1) 2X4 STUD COLUMN FOR 6'-0" MAX. BEAM SPAN (NO), (2) 2X4 STUDS FOR BEAM SPAN GREATER THAN 6'-0" (NO).

8) L.V.L. SHALL BE LAMINATED VENEER LUMBER, FB=2600 PSI, FV=285 PSI, E=1,900,000 PSI. P.S.L. SHALL BE PARALLEL STRAND LUMBER, FB=2400 PSI, FV=280 PSI, E=2,000,000 PSI. L.S.L. SHALL BE LAMINATED STRAND LUMBER, FB=2250 PSI, FV=400 PSI, E=1,950,000 PSI. INSTALL ALL CONNECTIONS PER MANUFACTURER'S INSTRUCTIONS.

9) ALL ROOF TRUSS AND I-JOIST LAYOUTS SHALL BE PREPARED IN ACCORDANCE WITH THE SEALED STRUCTURAL DRAWINGS. TRUSSES AND I-JOISTS SHALL BE INSTALLED ACCORDING TO THE MANUFACTURER'S SPECIFICATIONS.

10) ALL STRUCTURAL STEEL SHALL BE ASTM A-36. STEEL BEAMS SHALL BE SUPPORTED AT EACH END WITH A MINIMUM BEARING LENGTH OF 3 1/2" INCHES AND FULL FLANGE WIDTH. PROVIDE SOLID BEARING FROM BEAM SUPPORT TO FOUNDATION. BEAMS SHALL BE ATTACHED TO EACH SUPPORT WITH TWO LAG SCREWS (1/2" DIAMETER X 4" LONG). LATERAL SUPPORT IS CONSIDERED ADEQUATE PROVIDED THE JOIST ARE TOE NAILED TO THE SOLE PLATE, AND SOLE PLATE IS NAILED OR BOLTED TO THE BEAM FLANGE @ 48" O.C. ALL STEEL TUBING SHALL BE ASTM A500.

11) REBAR SHALL BE DEFORMED STEEL, ASTM615, GRADE 60.

12) FLITCH BEAMS SHALL BE BOLTED TOGETHER USING (2) ROWS OF 1/2" DIAMETER BOLTS (ASTM A307) WITH WASHERS PLACED UNDER THE THREADED END OF BOLT. BOLTS SHALL BE SPACED AT 24" O.C. (MAX), AND STAGGERED AT THE TOP AND BOTTOM OF BEAM (2" EDGE DISTANCE), WITH 2 BOLTS LOCATED AT 6" FROM EACH END.

13) BRICK LINTELS SHALL BE 3 1/2"x3 1/2"x1/4" STEEL ANGLE FOR UP TO 6'-0" SPAN AND 6"x4"x5/16" STEEL ANGLE WITH 6" LEG VERTICAL FOR SPANS UP TO 9'-0" (NO).

14) THE POSITIVE AND NEGATIVE DESIGN PRESSURE FOR DOORS AND WINDOWS SEE R301.2(6).

DWELLING / GARAGE SEPARATION

REFER TO SECTIONS R302.3, R302.6, AND R302.7

WALLS. A minimum 1/2" gypsum board must be installed on all walls supporting floor/ceiling assemblies used for separation required by this section.

CEILINGS. A minimum of 1/2" gypsum must be installed on the underside and exposed sides of all stairways.

OPENING PENETRATIONS. Openings between the garage and residence shall be equipped with solid wood doors not less than 1 3/8 inches (35 mm) in thickness, solid or honeycomb core steel doors not less than 1 3/8 inches (35 mm) thick, or 20-minute fire-rated doors.


DUCT PENETRATIONS. Ducts in the garage and ducts penetrating the walls or ceilings separating the dwelling from the garage shall be constructed of a minimum No. 26 gage (0.48 mm) sheet steel or other approved material and shall have no openings into the garage.

OTHER PENETRATIONS. Penetrations through the separation required in Section R302.6 shall be protected as required by Section R302.11, Item 4.

ATTIC ACCESS

SECTION R307
R307.1 Attic access. An attic access opening shall be provided to attic areas that exceed 400 square feet (37.16 m²) and have a vertical height of 60 inches (1524 mm) or greater. The net clear opening shall not be less than 20 inches by 30 inches (508 mm by 762 mm) and shall be located in a hallway or other readily accessible location. A 30-inch (762 mm) minimum unobstructed headroom in the attic space shall be provided at some point above the access opening. See Section M305.1.3 for access requirements where mechanical equipment is located in attics.

Exceptions:
1. Concealed areas not located over the main structure including porches, areas behind knee walls, dormers, bay windows, etc., are not required to have access.
2. Pull down stair treads, stringers, handrails, and hardware may protrude into the net clear opening.




STAIR NOTES:

1. STAIRS RISERS MUST BE UNIFORM AND NOT EXCEED 8 1/4".
2. TREADS SHALL NOT BE LESS THAN 10" DEEP A 1" PROJECTION OVER RISER IS PERMITTED.
3. A MINIMUM OF 6'8" HEADROOM MUST BE MAINTAINED AT ALL PLACES ON STAIR.
4. THE WIDTH OF THE STAIR SHALL BE A MINIMUM OF 3'0". HANDRAIL MAY PROJECT FROM EACH SIDE OF STAIR A DISTANCE OF 3 1/2" INTO THE REQUIRED WIDTH.
5. WINDERS MUST BE A MINIMUM OF 4" IN WIDTH AT 12" FROM THE NARROWEST SIDE. TREAD SHALL BE NO NARROWER THAN 4" AT ANY POINT AND AVERAGE NO LESS THAN 9 INCHES.
6. HANDRAILS SHALL BE NO LESS THAN 34" AND NO MORE THAN 38" ABOVE TREAD NOSING.
7. WINDERS AND SPIRAL STAIRS SHALL HAVE THE HANDRAIL LOCATED ON THE OUTSIDE RADIUS.
8. ALL REQUIRED HANDRAILS SHALL BE CONTINUOUS THE FULL LENGTH OF THE STAIRS.


STAIR DETAIL

NO SCALE




DECK ATTACHMENT DETAIL TO FRAMED WALL

SCALE 3/4" = 1'-0"




DROPPED/ FLUSH PIER

SCALE 3/4" = 1'-0"




TYPICAL WALL SECTION

SCALE 3/4" = 1'-0"



SECTION AT GARAGE SLAB



SECTION AT CRAWL

TABLE R602.1.2 INSULATION AND PENETRATION REQUIREMENTS BY COMPONENT^a

CLIMATE ZONE	FENESTRATION U-FACTOR ^b	SKYLIGHT U-FACTOR ^b	CEILING U-FACTOR ^b	CEILING PENETRATION U-FACTOR ^b	FRAME WALL R-VALUE	WALL R-VALUE	FLOOR R-VALUE	BASEMENT WALL R-VALUE	SLAB R-VALUE	GRAVEL SPACE R-VALUE	CRAWL SPACE R-VALUE
3	0.35	0.55	0.30	38 or 30 ^c	15 or 15-25 ^d	5/13 or 5/10 ^e	19	5/19	0	5/13	
4	0.35	0.55	0.30	38 or 30 ^c	15 or 15-25 ^d	5/13 or 5/10 ^e	19	10/15	10	10/12	
5	0.35	0.55	NR	38 or 30 ^c	12 ^f or 13-15 ^d	13/17 or 13/12.5 ^e	30 ^g	10/12	10	10/19	

TABLE R602.1.4 EQUIVALENT U-FACTORS^a

CLIMATE ZONE	FENESTRATION U-FACTOR ^b	SKYLIGHT U-FACTOR ^b	CEILING U-FACTOR ^b	FRAME WALL U-FACTOR ^b	WALL U-FACTOR ^b	FLOOR U-FACTOR ^b	BASEMENT WALL U-FACTOR ^b	CRAWL SPACE WALL U-FACTOR ^b
3	0.35	0.55	0.030	0.027	0.141	0.047	0.099 ^f	0.136
4	0.35	0.55	0.030	0.027	0.141	0.047	0.055	0.085
5	0.35	0.55	0.030	0.061	0.482	0.033	0.055	0.085

^a Nonresidential U-factors shall be obtained from measurement, calculation or an approved source.
^b Where more than half the transmission is on the interior, the mean wall U-factor shall be a maximum of 0.027 in Climate Zone 3, 0.021 in Climate Zone 4 and 0.028 in Climate Zone 5.
^c Basement wall U-factor of 0.040 in warm humid locations as defined by Figures R301.1 and Table R301.1.
^d A maximum of 2% glass fenestration product assemblies, having a U-factor no greater than 0.25 and a SHGC no greater than 0.20 shall be permitted to be substituted for minimum code comparison fenestration product assemblies without penalty. When applying this rule, use the REScheck "3A Trade-off" conditions instead to allow continued use of the software. The applicable fenestration product shall be modeled as meeting the U-factor of 0.25 and the SHGC of 0.20, as applicable, per the fenestration product actual U-factor and actual SHGC shall be used in the common section of the software for documentation of application of this rule to the applicable product. Compliance for these substitution products shall be verified compared to the above substantial maximum U-value requirement and maximum SHGC requirement, as applicable.