

Trenco  
818 Soundside Rd  
Edenton, NC 27932

Re: J0423-1518  
Lot 90 South Creek

The truss drawing(s) referenced below have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Comtech, Inc - Fayetteville.

Pages or sheets covered by this seal: I57574255 thru I57574262

My license renewal date for the state of North Carolina is December 31, 2023.

North Carolina COA: C-0844



April 5, 2023

---

Gilbert, Eric


**IMPORTANT NOTE:** The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

Job J0423-1518	Truss F01	Truss Type Floor Girder	Qty 1	Ply 1	Lot 90 South Creek Job Reference (optional)	157574255
-------------------	--------------	----------------------------	----------	----------	--	-----------

Comtech, Inc. Fayetteville, NC - 28314,

8.430 s Jan 6 2022 MiTek Industries, Inc. Tue Apr 4 13:17:31 2023 Page 1

ID:ZyxR5MYexMn1OuisRggYZvzvq71-sR5ollaVkc0epRJHxHvWC16fVgPUGqFPTgbaW6zU4v2



LOADING (psf)	SPACING-	CSL	DEFL.	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.21	Vert(LL) -0.01 29-30 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.09	Vert(CT) -0.01 29-30 >999 360		
BCLL 0.0	Rep Stress Incr NO	WB 0.17	Horz(CT) 0.00 19 n/a n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S		Weight: 137 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** All bearings 9-7-8 except (jt=length) 32=2-8-0, 31=2-8-0, 31=2-8-0, 19=0-3-8.  
 (lb) - Max Uplift All uplift 100 lb or less at joint(s) except 32=-143(LC 4)  
 Max Grav All reactions 250 lb or less at joint(s) 32, 26, 23, 25, 24 except 28=747(LC 12), 28=730(LC 1), 31=787(LC 11), 31=764(LC 1), 22=447(LC 11), 22=444(LC 1), 19=261(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=0/385, 3-4=0/386, 4-5=-369/0, 5-6=-369/0, 6-7=-369/0, 7-9=0/392, 9-10=0/391  
 BOT CHORD 29-30=0/369  
 WEBS 2-31=-357/0, 4-31=-565/0, 4-30=0/359, 7-28=-566/0, 7-29=0/360, 10-28=-335/0, 16-22=-305/0, 17-19=-298/0


- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) Plates checked for a plus or minus 1 degree rotation about its center.
  - 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 143 lb uplift at joint 32.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) CAUTION, Do not erect truss backwards.
  - 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 136 lb down at 19-1-4, and 136 lb down at 21-1-4, and 139 lb down at 23-1-4 on top chord. The design/selection of such connection device(s) is the responsibility of others.
  - 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard

- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)  
 Vert: 19-32=-10, 1-18=-100

Concentrated Loads (lb)  
 Vert: 16=-56(B) 17=-72(B) 35=-56(B)



April 5, 2023

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

**ENGINEERING BY**  
**TRENCO**  
 A MiTek Affiliate

818 Soundside Road  
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 90 South Creek
J0423-1518	F02	Floor	4	1	I57574256
					Job Reference (optional)

Comtech, Inc. Fayetteville, NC - 28314,

8.430 s Jan 6 2022 MiTek Industries, Inc. Tue Apr 4 13:17:33 2023 Page 1  
ID:ZyxR5MYexMn1OulsRggYZvzvq71-oqCYjRcmGEGM2kTg2ix\_ISBuyTx2kbKiw\_4ga?zU4v0




Plate Offsets (X, Y)--	[7:0-1-8,Edge], [8:0-1-8,Edge], [24:0-1-8,Edge], [25:0-1-8,Edge]
------------------------	--

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00		TC 0.67	Vert(LL) -0.26	32-33	>908	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00		BC 0.66	Vert(CT) -0.36	32-33	>664	360		
BCLL 0.0	Rep Stress Incr YES		WB 0.65	Horz(CT) 0.05	26	n/a	n/a		
BCDL 5.0	Code IRC2015/TP12014		Matrix-S						
								Weight: 166 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP 2400F 2.0E(flat) *Except* 22-28: 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (size) 36=0-3-0, 26=0-5-4, 23=0-3-8, 22=Mechanical  
Max Uplift 22=-461(LC 3)  
Max Grav 36=975(LC 5), 26=1740(LC 3), 23=1093(LC 14)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-1790/0, 3-4=-2975/0, 4-6=-2975/0, 6-7=-3521/0, 7-8=-3566/0, 8-9=-3119/0,  
9-10=-2112/0, 10-11=-2112/0, 11-13=-444/53, 13-14=0/1997, 14-15=0/1998,  
15-16=-70/1353, 16-17=-70/1353, 17-18=-70/1353, 18-19=0/1499, 19-20=0/1500  
BOT CHORD 35-36=0/1058, 34-35=0/2490, 33-34=0/3395, 32-33=0/3566, 31-32=0/3566, 30-31=0/3566,  
29-30=0/2737, 27-29=0/1377, 26-27=-698/0, 25-26=-1608/0, 24-25=-1353/70,  
23-24=-1251/0, 22-23=-683/0  
WEBS 2-36=-1406/0, 13-26=-1729/0, 2-35=0/1017, 13-27=0/1355, 3-35=-974/0, 11-27=-1317/0,  
3-34=0/659, 11-29=0/1016, 6-34=-571/0, 9-29=-864/0, 6-33=-25/319, 9-30=0/597,  
7-33=-364/264, 8-30=-791/0, 7-32=-280/108, 8-31=-82/307, 15-26=-675/0, 15-25=0/595,  
18-23=-516/21, 18-24=-139/309, 16-25=-328/0, 20-23=-1082/0, 20-22=0/838

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) Plates checked for a plus or minus 1 degree rotation about its center.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 461 lb uplift at joint 22.
  - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 7) CAUTION, Do not erect truss backwards.



April 5, 2023

<p><b>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.</b></p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see <b>ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information</b> available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601</p>	<p>ENGINEERING BY</p> <p><b>TRENCO</b></p> <p>A MITEK Affiliate</p> <p>818 Soundside Road Edenton, NC 27932</p>
--	---

Job	Truss	Truss Type	Qty	Ply	Lot 90 South Creek
J0423-1518	F04	Floor	5	1	I57574257
					Job Reference (optional)

Comtech, Inc. Fayetteville, NC - 28314,

8.430 s Jan 6 2022 MiTek Industries, Inc. Tue Apr 4 13:17:35 2023 Page 1  
ID:ZyxR5MYexMn1OulsRggYZvzvq71-kDKJ87d0orX4I2d2A7\_SNtGA7HdLCVl?OlZnftzU4v\_




Plate Offsets (X,Y)--	[7:0-1-8,Edge], [8:0-1-8,Edge], [24:0-1-8,Edge], [25:0-1-8,Edge]
-----------------------	--


<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.94	Vert(LL) -0.26 33-34 >910 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.67	Vert(CT) -0.36 33-34 >669 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.65	Horz(CT) 0.05 27 n/a n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S		Weight: 167 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP 2400F 2.0E(flat) *Except* 22-29: 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (size) 37=0-3-0, 27=0-5-4, 22=0-3-0  
Max Uplift 22=-22(LC 3)  
Max Grav 37=970(LC 10), 27=2105(LC 1), 22=549(LC 4)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-1779/0, 3-4=-2953/0, 4-5=-2953/0, 5-7=-3489/0, 7-8=-3525/0, 8-9=-3069/0,  
9-10=-2053/0, 10-11=-2053/0, 11-12=-369/229, 12-13=0/2285, 13-14=0/2285,  
14-16=-350/1220, 16-17=-1097/537, 17-18=-1097/537, 18-19=-1097/537, 19-20=-874/110  
BOT CHORD 36-37=0/1053, 35-36=0/2474, 34-35=0/3369, 33-34=0/3525, 32-33=0/3525, 31-32=0/3525,  
30-31=0/2681, 28-30=0/1309, 27-28=-962/0, 26-27=-1516/0, 25-26=-888/822,  
24-25=-537/1097, 23-24=-263/1117, 22-23=-41/578  
WEBS 2-37=-1399/0, 12-27=-1761/0, 2-36=0/1010, 12-28=0/1367, 3-36=-967/0, 11-28=-1344/0,  
3-35=0/652, 11-30=0/1047, 5-35=-565/0, 9-30=-885/0, 5-34=-46/296, 9-31=0/617,  
7-34=-330/296, 8-31=-824/0, 7-33=-295/93, 8-32=-66/322, 14-27=-1218/0, 14-26=0/822,  
16-26=-888/0, 16-25=0/907, 17-25=-515/0, 20-22=-767/55, 20-23=-96/413,  
19-23=-337/213, 19-24=-495/0

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) Plates checked for a plus or minus 1 degree rotation about its center.
  - 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 22 lb uplift at joint 22.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) CAUTION, Do not erect truss backwards.



April 5, 2023

<p><b>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.</b></p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see <b>ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information</b> available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601</p>	<p>818 Soundside Road Edenton, NC 27932</p>
--	---

Job	Truss	Truss Type	Qty	Ply	Lot 90 South Creek	I57574258
J0423-1518	F05	Floor	8	1	Job Reference (optional)	

Comtech, Inc. Fayetteville, NC - 28314,

8.430 s Jan 6 2022 MiTek Industries, Inc. Tue Apr 4 13:17:36 2023 Page 1  
ID:ZyxR5MYexMn1OulsRggYZvzvq71-DPuhLTeeZ9fwvCBFkrVhv5pRlhyax?m8cyJKAKzU4uz




Plate Offsets (X, Y)--	[18:0-1-8,Edge], [19:0-1-8,Edge]					PLATES	GRIP
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	
TCLL 40.0	Plate Grip DOL 1.00	TC 0.53	Vert(LL) -0.21	18-19	>996	480	<b>MT20</b>
TCDL 10.0	Lumber DOL 1.00	BC 0.74	Vert(CT) -0.29	18-19	>724	360	<b>244/190</b>
BCLL 0.0	Rep Stress Incr YES	WB 0.47	Horz(CT) 0.06	14	n/a	n/a	
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S					
							Weight: 94 lb FT = 20%F, 11%E

<b>LUMBER-</b>		<b>BRACING-</b>	
TOP CHORD 2x4 SP No.1(flat)		TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)		BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)			

**REACTIONS.** (size) 14=0-3-8, 22=0-3-8  
Max Grav 14=961(LC 1), 22=961(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
**TOP CHORD** 2-3=-1757/0, 3-4=-2926/0, 4-6=-2926/0, 6-7=-3482/0, 7-8=-3482/0, 8-9=-3482/0, 9-10=-2926/0, 10-11=-2926/0, 11-12=-1757/0  
**BOT CHORD** 21-22=0/1042, 20-21=0/2442, 19-20=0/3273, 18-19=0/3482, 17-18=0/3273, 15-17=0/2442, 14-15=0/1042  
**WEBS** 2-22=-1385/0, 2-21=0/994, 3-21=-953/0, 3-20=0/658, 12-14=-1385/0, 12-15=0/994, 11-15=-953/0, 11-17=0/658, 9-17=-472/0, 6-20=-472/0, 6-19=-67/597, 7-19=-312/0, 9-18=-67/597, 8-18=-312/0

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 3) Plates checked for a plus or minus 1 degree rotation about its center.
  - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



April 5, 2023






Job J0423-1518	Truss F07	Truss Type Floor	Qty 4	Ply 1	Lot 90 South Creek Job Reference (optional)	157574260
-------------------	--------------	---------------------	----------	----------	--	-----------

Comtech, Inc. Fayetteville, NC - 28314,

8.430 s Jan 6 2022 MiTek Industries, Inc. Tue Apr 4 13:17:38 2023 Page 1

ID:ZyxR5MYexMn1OulsRggYZvzvq71-9o0Rm9fu5mve9VLdrGX9?WuuiUp8P06R4GoRECzU4ux



Scale = 1:9.4


Plate Offsets (X,Y)-- [1:Edge,0-1-8]		CSL		DEFL.				PLATES	GRIP
LOADING (psf)	SPACING- 2-0-0	TC	0.09	in	(loc)	l/defl	L/d	MT20	244/190
TCLL 40.0	Plate Grip DOL 1.00	BC	0.03	Vert(LL)	-0.00	6	>999		
TCDL 10.0	Lumber DOL 1.00	WB	0.04	Vert(CT)	-0.00	5	>999		
BCLL 0.0	Rep Stress Incr YES	Matrix-P		Horz(CT)	0.00	4	n/a		
BCDL 5.0	Code IRC2015/TPI2014							Weight: 22 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 3-1-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (size) 6=Mechanical, 4=Mechanical  
Max Grav 6=156(LC 1), 4=156(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Plates checked for a plus or minus 1 degree rotation about its center.
  - 2) Refer to girder(s) for truss to truss connections.
  - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



April 5, 2023

<p><b>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.</b></p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see <b>ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information</b> available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601</p>	<p>ENGINEERING BY</p> <p><b>TRENCO</b></p> <p>A MiTek Affiliate</p> <p>818 Soundside Road Edenton, NC 27932</p>
--	---


Job J0423-1518	Truss FKW1	Truss Type Floor Supported Gable	Qty 1	Ply 1	Lot 90 South Creek Job Reference (optional)	157574261
-------------------	---------------	-------------------------------------	----------	----------	--	-----------

Comtech, Inc. Fayetteville, NC - 28314,

8.430 s Jan 6 2022 MiTek Industries, Inc. Tue Apr 4 13:17:39 2023 Page 1  
ID:ZyxR5MYexMn1OulsRggYZvzvq71-d\_aq\_UgXs41VmfwgPz2OXjR3Nu8d8TOalwX?nezU4uw

0.1-8

Scale = 1:17.7



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.09	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	9	n/a		
BCDL 5.0	Code IRC2015/TPI2014		Matrix-R						
								Weight: 44 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

**REACTIONS.** All bearings 9-8-0.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 16, 9, 15, 14, 13, 12, 11, 10

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 2) Plates checked for a plus or minus 1 degree rotation about its center.
  - 3) Gable requires continuous bottom chord bearing.
  - 4) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - 5) Gable studs spaced at 1-4-0 oc.
  - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 7) CAUTION, Do not erect truss backwards.



April 5, 2023



Job J0423-1518	Truss FKW2	Truss Type GABLE	Qty 1	Ply 1	Lot 90 South Creek Job Reference (optional)	157574262
-------------------	---------------	---------------------	----------	----------	--	-----------


Comtech, Inc. Fayetteville, NC - 28314,

8.430 s Jan 6 2022 MiTek Industries, Inc. Tue Apr 4 13:17:40 2023 Page 1  
ID:ZyxR5MYexMn1OuisRggYZzvq71-5A7CBqh9dN9MOpV0zgZd4xzFIIUptwfkXaHYJ5zU4uv

0-1/8

0-1/8

Scale = 1:29.6



1-4-0	2-8-0	4-0-0	5-4-0	6-8-0	8-0-0	9-4-0	10-8-0	12-0-0	13-4-0	14-8-0	16-0-0	17-4-0	17-10-0
1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	0-6-0

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.02	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	17	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014		Matrix-R						Weight: 80 lb	FT = 20%F, 11%E

**LUMBER-**

TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)  
 OTHERS 2x4 SP No.3(flat)

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.**

All bearings 17-10-0.


(lb) - Max Grav All reactions 250 lb or less at joint(s) 32, 17, 31, 30, 29, 28, 27, 26, 25, 24, 23, 22, 20, 19, 18

**FORCES.**

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-**

- All plates are 1.5x3 MT20 unless otherwise indicated.
- Plates checked for a plus or minus 1 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



April 5, 2023

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road  
 Edenton, NC 27932

# Symbols

## PLATE LOCATION AND ORIENTATION



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



For 4 x 2 orientation, locate plates 0- 1/16" from outside edge of truss.



This symbol indicates the required direction of slots in connector plates.


\* Plate location details available in **MITek 20/20 software** or upon request.

## PLATE SIZE

**4 X 4**


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

## LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

## BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number where bearings occur. Min size shown is for crushing only.

### Industry Standards:

ANSI/TPI 1: National Design Specification for Metal Plate Connected Wood Truss Construction.  
DSB-89: Design Standard for Bracing, Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses.

# Numbering System

6-4-8  
dimensions shown in ft-in-sixteenths  
(Drawings not to scale)



**JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.**

**CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.**

## PRODUCT CODE APPROVALS

ICC-ES Reports:

ESR-1311, ESR-1352, ESR1988  
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TPI 1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MITteK® All Rights Reserved



MITek Engineering Reference Sheet: Mill-7473 rev. 5/19/2020



# General Safety Notes

## Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TPI 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TPI 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TPI 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.