


| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | A01 | GABLE | 1 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:11 2023 Page 1
ID:NpSit5YZ_4qsCWpC5omWUAYBIV_-DsUxdD?ZsOfC5w58VslfenBEVLpKFztey3YPK2zKrmY

-0-10-8 18-0-0 36-0-0 36-10-8
0-10-8 18-0-0 18-0-0 0-10-8

Scale = 1:62.8



| | | | | | | | | | |
|--|----------------------|-------|-------------|--------------|----------|--------|-----|----------------|-------------|
| Plate Offsets (X,Y)-- [30:0-4-0,0-4-8], [34:0-4-0,0-4-8] | | | | | | | | | |
| LOADING (psf) | SPACING- | 2-0-0 | CSI. | DEFL. | in (loc) | l/defl | L/d | PLATES | GRIP |
| TCLL 20.0 | Plate Grip DOL | 1.15 | TC 0.06 | Vert(LL) | 0.00 | 22 | n/r | MT20 | 244/190 |
| TCDL 10.0 | Lumber DOL | 1.15 | BC 0.02 | Vert(CT) | 0.00 | 22 | n/r | | |
| BCLL 0.0 * | Rep Stress Incr | YES | WB 0.13 | Horz(CT) | 0.01 | 22 | n/a | | |
| BCDL 10.0 | Code IRC2015/TPI2014 | | Matrix-S | | | | | | |
| | | | | | | | | Weight: 295 lb | FT = 20% |

| | |
|--|---|
| LUMBER- | BRACING- |
| TOP CHORD 2x6 SP No.1 | TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins. |
| BOT CHORD 2x6 SP No.1 | BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. |
| OTHERS 2x4 SP No.2 | WEBS 1 Row at midpt 12-32 |
| MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide. | |

REACTIONS. All bearings 36-0-0.
(lb) - Max Horz 2=220(LC 12)
Max Uplift All uplift 100 lb or less at joint(s) 2, 22, 33, 34, 35, 36, 37, 38, 39, 40, 31, 29, 28, 27, 26, 25, 24 except 30=101(LC 13)
Max Grav All reactions 250 lb or less at joint(s) 2, 22, 32, 33, 34, 35, 36, 37, 38, 39, 40, 31, 30, 29, 28, 27, 26, 25, 24

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-288/94, 9-42=-98/288, 10-42=-81/298, 10-11=-123/370, 11-12=-140/416, 12-13=-140/419, 13-14=-123/373, 14-43=-81/300, 15-43=-98/291


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-8-10 to 3-8-3, Exterior(2) 3-8-3 to 18-0-0, Corner(3) 18-0-0 to 22-4-13, Exterior(2) 22-4-13 to 36-8-10 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 22, 33, 34, 35, 36, 37, 38, 39, 40, 31, 29, 28, 27, 26, 25, 24 except (jt=lb) 30=101.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

| | | | | | |
|-------------------|--------------|----------------------|----------|----------|--------------------|
| Job J0523-2069 | Truss A02 | Truss Type COMMON | Qty 2 | Ply 1 | 109-23-107 Coleman |
|-------------------|--------------|----------------------|----------|----------|--------------------|

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:12 2023 Page 1
ID:NpSit5YZ_4qsCWpC5omWUAYBIV_-h22JqZ?Bdhn3j4gK2aHuA?kKY10Y_MXnAjlysUzKrmX



Scale = 1:66.1




Plate Offsets (X,Y)-- [2:0-1-14,Edge], [8:0-1-14,Edge]

| LOADING (psf) | SPACING- | CSI. | DEFL. | in (loc) | l/defl | L/d | PLATES | GRIP |
|---------------|----------------------|----------|----------|----------|--------|------|--------|-------------------------|
| TCLL 20.0 | 2-0-0 | TC 0.36 | Vert(LL) | -0.24 | 10-13 | >999 | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.53 | Vert(CT) | -0.36 | 10-13 | >999 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.43 | Horz(CT) | 0.06 | 8 | n/a | | |
| BCDL 10.0 | Rep Stress Incr YES | Matrix-S | Wind(LL) | 0.07 | 2-13 | >999 | | |
| | Code IRC2015/TPI2014 | | | | | | | Weight: 230 lb FT = 20% |

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-6-4 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1480/0-3-8 (min. 0-1-12), 8=1480/0-3-8 (min. 0-1-12)
 Max Horz 2=141(LC 11)
 Max Uplift 2=-184(LC 12), 8=-184(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-14=-2519/725, 3-14=-2445/754, 3-4=-2232/710, 4-15=-2107/730, 5-15=-2097/754,
 5-16=-2097/754, 6-16=-2107/730, 6-7=-2232/710, 7-17=-2445/754, 8-17=-2519/725
 BOT CHORD 2-13=-523/2174, 12-13=-200/1419, 12-18=-200/1419, 18-19=-200/1419, 11-19=-200/1419,
 10-11=-200/1419, 8-10=-535/2174
 WEBS 5-10=-209/911, 7-10=-544/390, 5-13=-209/911, 3-13=-544/390


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-8-10 to 3-8-3, Interior(1) 3-8-3 to 18-0-0, Exterior(2) 18-0-0 to 22-4-13, Interior(1) 22-4-13 to 36-8-10 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=184, 8=184.
 - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | A03 | COMMON | 5 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:12 2023 Page 1
ID:NpSit5YZ_4qsCWpC5omWUAYBIV_-h22JqZ?Bdhn3j4gK2aHuA?kKOIOP_MMnAjlysUzKrmX



Scale = 1:65.0




Plate Offsets (X,Y)-- [2:0-1-14,Edge], [8:0-1-14,Edge]

| LOADING (psf) | SPACING- | CSI. | DEFL. | in (loc) | l/defl | L/d | PLATES | GRIP |
|---------------|----------------------|----------|----------------|----------|--------|-----|----------------|----------|
| TCLL 20.0 | 2-0-0 | TC 0.37 | Vert(LL) -0.25 | 9-12 | >999 | 360 | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.54 | Vert(CT) -0.36 | 9-12 | >999 | 240 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.44 | Horz(CT) 0.06 | 8 | n/a | n/a | | |
| BCDL 10.0 | Rep Stress Incr YES | Matrix-S | Wind(LL) 0.07 | 2-12 | >999 | 240 | | |
| | Code IRC2015/TPI2014 | | | | | | Weight: 228 lb | FT = 20% |

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-5-2 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1483/0-3-8 (min. 0-1-12), 8=1430/Mechanical
 Max Horz 2=143(LC 11)
 Max Uplift 2=-184(LC 12), 8=-169(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-13=-2526/728, 3-13=-2452/757, 3-4=-2239/713, 4-14=-2114/733, 5-14=-2104/756,
 5-15=-2112/774, 6-15=-2123/751, 6-7=-2248/730, 7-16=-2441/778, 8-16=-2537/749
 BOT CHORD 2-12=-552/2180, 11-12=-216/1425, 11-17=-216/1425, 17-18=-216/1425, 10-18=-216/1425,
 9-10=-216/1425, 8-9=-556/2195
 WEBS 5-9=-215/923, 7-9=-555/398, 5-12=-210/911, 3-12=-544/390


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-8-10 to 3-8-3, Interior(1) 3-8-3 to 18-0-0, Exterior(2) 18-0-0 to 22-4-13, Interior(1) 22-4-13 to 35-11-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Refer to girder(s) for truss to truss connections.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=184, 8=169.
 - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | A06 | COMMON | 2 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:14 2023 Page 1
 ID:NpSit5YZ_4qsCWpC5omWUAYbIV_dR94FE1R9J1nyOqiA?JMFQpg2Yi0SG14e1n3xNzKrmV



Scale = 1:66.1




Plate Offsets (X,Y)-- [2:0-1-14,Edge], [8:0-1-14,Edge]

| LOADING (psf) | SPACING- | CSI. | DEFL. | in (loc) | l/defl | L/d | PLATES | GRIP |
|---------------|----------------------|----------|----------|----------|--------|------|----------------|----------|
| TCLL 20.0 | 2-0-0 | TC 0.36 | Vert(LL) | -0.24 | 10-13 | >999 | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.53 | Vert(CT) | -0.36 | 10-13 | >999 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.43 | Horz(CT) | 0.06 | 8 | n/a | | |
| BCDL 10.0 | Rep Stress Incr YES | Matrix-S | Horz(LL) | 0.07 | 2-13 | >999 | | |
| | Code IRC2015/TPI2014 | | | | | | Weight: 230 lb | FT = 20% |

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-6-4 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1480/0-3-8 (min. 0-1-12), 8=1480/0-3-8 (min. 0-1-12)
 Max Horz 2=141(LC 11)
 Max Uplift 2=-184(LC 12), 8=-184(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-14=-2519/725, 3-14=-2445/754, 3-4=-2232/710, 4-15=-2107/730, 5-15=-2097/754,
 5-16=-2097/754, 6-16=-2107/730, 6-7=-2232/710, 7-17=-2445/754, 8-17=-2519/725
 BOT CHORD 2-13=-523/2174, 12-13=-200/1419, 12-18=-200/1419, 18-19=-200/1419, 11-19=-200/1419,
 10-11=-200/1419, 8-10=-535/2174
 WEBS 5-10=-209/911, 7-10=-544/390, 5-13=-209/911, 3-13=-544/390


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-8-10 to 3-8-3, Interior(1) 3-8-3 to 18-0-0, Exterior(2) 18-0-0 to 22-4-13, Interior(1) 22-4-13 to 36-8-10 zone; cantilever left exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=184, 8=184.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | A07 | COMMON | 2 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:14 2023 Page 1
 ID:NpSit5YZ_4qsCWpC5omWUAYBIV_-dR94FE1R9J1nyOqiA?JMFQpg9YgaSH94e1n3xNzKrmV



Scale = 1:61.9



| | | | | | | | | | |
|----------------------|----------------------|-------|-------------|--------------|-------------|--------|-----|----------------|-------------|
| LOADING (psf) | SPACING- | 2-0-0 | CSI. | DEFL. | in (loc) | l/defl | L/d | PLATES | GRIP |
| TCLL 20.0 | Plate Grip DOL | 1.15 | TC 0.36 | Vert(LL) | -0.19 10-13 | >999 | 360 | MT20 | 244/190 |
| TCDL 10.0 | Lumber DOL | 1.15 | BC 0.69 | Vert(CT) | -0.44 10-13 | >850 | 240 | | |
| BCLL 0.0 * | Rep Stress Incr | YES | WB 0.36 | Horz(CT) | 0.04 9 | n/a | n/a | | |
| BCDL 10.0 | Code IRC2015/TPI2014 | | Matrix-S | Wind(LL) | 0.06 2-13 | >999 | 240 | | |
| | | | | | | | | Weight: 217 lb | FT = 20% |

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-9-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 6-9

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1375/0-3-8 (min. 0-1-10), 9=1358/0-3-8 (min. 0-1-10)
 Max Horz 2=195(LC 12)
 Max Uplift 2=-85(LC 12), 9=-9(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-14=-2315/401, 3-14=-2239/430, 3-4=-2009/371, 4-15=-1884/391, 5-15=-1877/414,
 5-16=-1459/354, 6-16=-1559/330
 BOT CHORD 2-13=-378/1991, 12-13=-100/1168, 12-17=-100/1168, 17-18=-100/1168, 18-19=-100/1168,
 19-20=-100/1168, 11-20=-100/1168, 10-11=-100/1168, 9-10=-199/1182
 WEBS 3-13=-543/401, 5-13=-73/1020, 5-10=0/370, 6-10=0/343, 6-9=-1711/270


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-8-10 to 3-8-3, Interior(1) 3-8-3 to 18-0-0, Exterior(2) 18-0-0 to 22-4-13, Interior(1) 22-4-13 to 31-1-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) 200.0lb AC unit load placed on the bottom chord, 18-0-0 from left end, supported at two points, 3-0-0 apart.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 9.
 - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | A08 | COMMON | 2 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:15 2023 Page 1
ID:NpSit5YZ_4qsCWpC5omWUAYBIV_-5djSTa23wcAdaXPvjiqbodMp3y_TBjrDshWcTpzKrmU



Scale = 1:61.9



| | | | | | | | | | |
|----------------------|----------------------|-------|-------------|--------------|----------|--------|------|----------------|-------------|
| LOADING (psf) | SPACING- | 2-3-0 | CSI. | DEFL. | in (loc) | l/defl | L/d | PLATES | GRIP |
| TCLL 20.0 | Plate Grip DOL | 1.15 | TC 0.47 | Vert(LL) | -0.15 | 2-13 | >999 | MT20 | 244/190 |
| TCDL 10.0 | Lumber DOL | 1.15 | BC 0.78 | Vert(CT) | -0.31 | 2-13 | >999 | | |
| BCLL 0.0 * | Rep Stress Incr | NO | WB 0.39 | Horz(CT) | 0.06 | 9 | n/a | | |
| BCDL 10.0 | Code IRC2015/TPI2014 | | Matrix-S | Wind(LL) | 0.06 | 10-13 | >999 | | |
| | | | | | | | | Weight: 235 lb | FT = 20% |

| | |
|---------------------------|--|
| LUMBER- | BRACING- |
| TOP CHORD 2x6 SP No.1 | TOP CHORD 2-0-0 oc purlins (4-5-1 max.), except end verticals |
| BOT CHORD 2x6 SP No.1 | (Switched from sheeted: Spacing > 2-0-0). |
| WEBS 2x4 SP No.2 *Except* | BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. |
| W3: 2x6 SP No.1 | WEBS 1 Row at midpt 6-9 |

REACTIONS. (lb/size) 2=1537/0-3-8 (min. 0-1-13), 9=1514/0-3-8 (min. 0-1-13)
 Max Horz 2=219(LC 12)
 Max Uplift 2=-107(LC 12), 9=-24(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-14=-2572/496, 3-14=-2489/528, 3-4=-2228/462, 4-15=-2087/485, 5-15=-2077/511, 5-16=-1572/448, 6-16=-1708/422
 BOT CHORD 2-13=-463/2212, 12-13=-165/1255, 12-17=-142/1293, 17-18=-142/1293, 18-19=-142/1293, 19-20=-142/1293,
 11-20=-142/1293, 10-11=-164/1258, 9-10=-257/1307
 WEBS 3-13=-613/446, 5-13=-103/1115, 5-10=0/374, 6-10=0/352, 6-9=-1883/368


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-10 to 3-8-3, Interior(1) 3-8-3 to 18-0-0, Exterior(2) 18-0-0 to 22-4-13, Interior(1) 22-4-13 to 31-1-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) 200.0lb AC unit load placed on the bottom chord, 18-0-0 from left end, supported at two points, 3-0-0 apart.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9 except (jt=lb) 2=107.
 - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

| | | | | | |
|------------|-------|----------------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | A10 | COMMON SUPPORTED GAB | 1 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:17 2023 Page 1
ID:NpSit5YZ_4qsCWpC5omWUAYBlV_-10rCuG3KSEQLqrZHR7s3t2RFbmsvfh9WK??jYizKrmS



Scale = 1:58.7




Plate Offsets (X,Y)-- [25:0-4-0,0-4-8], [29:0-4-0,0-4-8]

| LOADING (psf) | SPACING- | CSI. | DEFL. | in (loc) | l/defl | L/d | PLATES | GRIP |
|---------------|----------------------|----------|----------------|----------|--------|-----|----------------|----------|
| TCLL 20.0 | 2-0-0 | TC 0.09 | Vert(LL) -0.00 | 1 | n/r | 120 | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.01 | Vert(CT) -0.00 | 1 | n/r | 120 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.15 | Horz(CT) 0.00 | 20 | n/a | n/a | | |
| BCDL 10.0 | Rep Stress Incr YES | Matrix-S | | | | | | |
| | Code IRC2015/TPI2014 | | | | | | | |
| | | | | | | | Weight: 243 lb | FT = 20% |

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS T-Brace: 2x4 SPF No.2 - 12-27
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
 Brace must cover 90% of web length.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 31-4-8.
 (lb) - Max Horz 2=308(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 28, 29, 30, 31, 32, 33, 34, 26, 25, 24, 23, 22 except 35=110(LC 12), 21=113(LC 13)
 Max Grav All reactions 250 lb or less at joint(s) 20, 2, 28, 29, 30, 31, 32, 33, 34, 35, 26, 25, 24, 23, 22, 21 except 27=269(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-312/140, 7-8=-77/276, 8-9=-68/281, 9-37=-100/342, 10-37=-84/347, 10-11=-124/418, 11-12=-147/477, 12-13=-147/478, 13-14=-124/420, 14-38=-84/348, 15-38=-100/343, 15-16=-77/283
 WEBS 12-27=-272/41


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf, BCDL=6.0psf, h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-10-8 to 3-6-5, Exterior(2) 3-6-5 to 18-0-0, Corner(3) 18-0-0 to 22-4-13, Exterior(2) 22-4-13 to 31-1-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 28, 29, 30, 31, 32, 33, 34, 26, 25, 24, 23, 22 except (jt=lb) 35=110, 21=113.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

LOAD CASE(S) Standard

| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | B1 | GABLE | 1 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:18 2023 Page 1
 ID:NpSit5YZ_4qsCWpC5omWUAYBiV_-WCPa5c4yDXYCR?7UPrOIQG_R6AC_OAugZfG48zKrmR



Scale = 1:38.7




Plate Offsets (X,Y)-- [18:0-4-0,0-4-8]

| LOADING (psf) | SPACING- | CSI. | DEFL. | in (loc) | l/defl | L/d | PLATES | GRIP |
|---------------|----------------------|----------|---------------|----------|--------|-----|----------------|----------|
| TCLL 20.0 | 2-0-0 | TC 0.04 | Vert(LL) 0.00 | 12 | n/r | 120 | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.02 | Vert(CT) 0.00 | 12 | n/r | 120 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.05 | Horz(CT) 0.00 | 12 | n/a | n/a | | |
| BCDL 10.0 | Rep Stress Incr YES | Matrix-S | | | | | | |
| | Code IRC2015/TPI2014 | | | | | | | |
| | | | | | | | Weight: 145 lb | FT = 20% |

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 21-0-0.
 (lb) - Max Horz 2=132(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 12, 19, 20, 21, 17, 16, 15 except 22=-112(LC 12), 14=-111(LC 13)
 Max Grav All reactions 250 lb or less at joint(s) 2, 12, 18, 19, 20, 21, 22, 17, 16, 15, 14

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 6-7=-89/267, 7-8=-89/270

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) 0-8-10 to 3-8-3, Exterior(2) 3-8-3 to 10-6-0, Corner(3) 10-6-0 to 14-10-13, Exterior(2) 14-10-13 to 21-8-10 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 12, 19, 20, 21, 17, 16, 15 except (jt=lb) 22=112, 14=111.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | B2 | COMMON | 7 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:18 2023 Page 1
 ID:NpSit5YZ_4qsCWpC5omWUAYBIV_-WCPa5c4yDXYCR?7UPrOIQG_JOA6XO55gZfIG48zKrmR




Plate Offsets (X,Y)-- [2:0-0-6,0-0-2], [5:0-3-0,Edge], [8:0-0-6,0-0-2]

| LOADING (psf) | SPACING- | CSI. | DEFL. | in (loc) | l/defl | L/d | PLATES | GRIP |
|---------------|----------------------|----------|----------|-------------|--------|-----|----------------|----------|
| TCLL 20.0 | 2-0-0 | TC 0.53 | Vert(LL) | -0.18 10-12 | >999 | 360 | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.43 | Vert(CT) | -0.28 10-12 | >892 | 240 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.36 | Horz(CT) | 0.02 8 | n/a | n/a | | |
| BCDL 10.0 | Rep Stress Incr YES | Matrix-S | Wind(LL) | 0.10 12 | >999 | 240 | | |
| | Code IRC2015/TPI2014 | | | | | | Weight: 123 lb | FT = 20% |

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-8-1 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=880/0-3-8 (min. 0-1-8), 8=880/0-3-8 (min. 0-1-8)
 Max Horz 2=-85(LC 10)
 Max Uplift 2=-113(LC 12), 8=-113(LC 13)
 Max Grav 2=932(LC 2), 8=932(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-13=-1492/374, 3-13=-1374/387, 3-4=-1182/438, 4-5=-142/671, 5-6=-142/671,
 6-7=-1182/438, 7-14=-1374/387, 8-14=-1492/374
 BOT CHORD 2-12=-215/1220, 12-15=-215/1220, 11-15=-215/1220, 11-16=-215/1220, 10-16=-215/1220,
 8-10=-215/1220
 WEBS 3-12=0/431, 7-10=0/431, 4-6=-1969/623

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-10 to 3-8-3, Interior(1) 3-8-3 to 10-6-0, Exterior(2) 10-6-0 to 14-7-12, Interior(1) 14-7-12 to 21-8-10 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-0-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=113, 8=113.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | B3 | COMMON | 3 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:18 2023 Page 1
 ID:NpSit5YZ_4qsCWpC5omWUAYBIV_-WCPa5c4yDXYCR?7UPrOIQG_JDA6QO50gZfIG48zKrmR




Plate Offsets (X,Y)-- [4:0-3-0,Edge]

| LOADING (psf) | SPACING- | 2-0-0 | CSI. | DEFL. | in (loc) | l/defl | L/d | PLATES | GRIP |
|---------------|----------------------|-------|----------|----------|----------|--------|------|----------------|----------|
| TCLL 20.0 | Plate Grip DOL | 1.15 | TC 0.54 | Vert(LL) | -0.18 | 8-10 | >999 | MT20 | 244/190 |
| TCDL 10.0 | Lumber DOL | 1.15 | BC 0.44 | Vert(CT) | -0.29 | 8-10 | >872 | | |
| BCLL 0.0 * | Rep Stress Incr | YES | WB 0.36 | Horz(CT) | 0.02 | 7 | n/a | | |
| BCDL 10.0 | Code IRC2015/TPI2014 | | Matrix-S | Wind(LL) | 0.10 | 10 | >999 | | |
| | | | | | | | | Weight: 118 lb | FT = 20% |

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-5-11 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=828/0-3-8 (min. 0-1-8), 7=828/0-3-8 (min. 0-1-8)
 Max Horz 1=80(LC 11)
 Max Uplift 1=-97(LC 12), 7=-97(LC 13)
 Max Grav 1=889(LC 2), 7=889(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-11=-1493/385, 2-11=-1380/398, 2-3=-1187/453, 3-4=-167/687, 4-5=-167/687,
 5-6=-1187/453, 6-12=-1380/398, 7-12=-1493/385
 BOT CHORD 1-10=-243/1224, 10-13=-243/1224, 9-13=-243/1224, 9-14=-243/1224, 8-14=-243/1224,
 7-8=-243/1224
 WEBS 2-10=0/425, 6-8=0/425, 3-5=-1992/669


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-1-12 to 4-6-9, Interior(1) 4-6-9 to 10-6-0, Exterior(2) 10-6-0 to 14-7-12, Interior(1) 14-7-12 to 20-10-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-0-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | C1 | KINGPOST | 1 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:19 2023 Page 1
ID:NpSit5YZ_4qsCWpC5omWUAYBlV_-OzzJy5a_rg339igyYvXyTWW5ZV_7aspnJUqcazKrmQ



Scale = 1:34.7



| | | | | | | | | | |
|----------------------|----------------------|-------|-------------|--------------|----------|--------|------|----------------|-------------|
| LOADING (psf) | SPACING- | 2-0-0 | CSI. | DEFL. | in (loc) | l/defl | L/d | PLATES | GRIP |
| TCLL 20.0 | Plate Grip DOL | 1.15 | TC 0.41 | Vert(LL) | -0.01 | 15 | >999 | MT20 | 244/190 |
| TCDL 10.0 | Lumber DOL | 1.15 | BC 0.16 | Vert(CT) | -0.02 | 2-15 | >999 | | |
| BCLL 0.0 * | Rep Stress Incr | YES | WB 0.20 | Horz(CT) | 0.00 | 13 | n/a | | |
| BCDL 10.0 | Code IRC2015/TPI2014 | | Matrix-S | Wind(LL) | -0.01 | 13-15 | >999 | | |
| | | | | | | | | Weight: 123 lb | FT = 20% |

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 16

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 13=1226/0-3-8 (min. 0-1-8), 2=298/0-3-8 (min. 0-1-8)
 Max Horz 2=114(LC 12)
 Max Uplift 13=-373(LC 13), 2=-151(LC 12)
 Max Grav 13=1226(LC 1), 2=392(LC 23)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-18=-405/119, 18-19=-335/127, 3-19=-333/136, 3-4=-489/410, 4-5=-491/449,
 5-6=-346/346, 6-7=-738/637, 7-20=-681/558, 20-21=-686/523, 8-21=-689/510,
 8-9=-721/531
 BOT CHORD 2-15=-124/373, 14-15=-122/378, 13-14=-122/378, 12-13=-456/733, 11-12=-456/733,
 9-11=-456/733
 WEBS 3-17=-623/354, 16-17=-609/343, 13-16=-646/374, 6-13=-734/780


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) 0-8-10 to 3-8-3, Interior(1) 3-8-3 to 9-0-0, Exterior(2) 9-0-0 to 13-4-13, Interior(1) 13-4-13 to 18-8-10 zone; cantilever right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) All plates are 2x4 MT20 unless otherwise indicated.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 13=373, 2=151.
 - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | C2 | COMMON | 2 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:19 2023 Page 1
 ID:NpSit5YZ_4qsCWpC5omWJAYBIV_-OzzJy5a_rg339igyYvXyTWWmZUf7WfpnJUqcazKrmQ



Scale = 1:34.7




Plate Offsets (X,Y)-- [2-0-0-2,0-0-2]

| LOADING (psf) | SPACING- | CSI. | DEFL. | in | (loc) | l/defl | L/d | PLATES | GRIP |
|---------------|----------------------|----------|----------|-------|-------|--------|-----|----------------|----------|
| TCLL 20.0 | 2-0-0 | TC 0.43 | Vert(LL) | -0.02 | 2-8 | >999 | 360 | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.25 | Vert(CT) | -0.04 | 2-8 | >999 | 240 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.47 | Horz(CT) | 0.00 | 6 | n/a | n/a | | |
| BCDL 10.0 | Rep Stress Incr YES | Matrix-S | Wind(LL) | 0.02 | 2-8 | >999 | 240 | | |
| | Code IRC2015/TPI2014 | | | | | | | Weight: 108 lb | FT = 20% |

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=1250/0-3-8 (min. 0-1-8), 2=273/0-3-8 (min. 0-1-8)
 Max Horz 2=73(LC 11)
 Max Uplift 6=-161(LC 13), 2=-73(LC 12)
 Max Grav 6=1250(LC 1), 2=378(LC 23)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-9=-545/252, 9-10=-521/253, 3-10=-519/302, 3-11=-841/849, 11-12=-846/729,
 4-12=-866/705
 BOT CHORD 2-8=-224/589, 7-8=-263/531, 6-7=-263/531, 4-6=-650/897
 WEBS 3-6=-1159/928

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-10 to 3-8-3, Interior(1) 3-8-3 to 9-0-0, Exterior(2) 9-0-0 to 13-4-13, Interior(1) 13-4-13 to 18-8-10 zone; cantilever right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2 except (jt=lb) 6=161.
 - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

| | | | | | |
|------------|-------|---------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | C3 | Common Girder | 1 | 2 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:20 2023 Page 1
ID:NpSit5YZ_4qsCWpC5omWUAYBIV_-SbXLWI6Ck9owhJHsWfQmVh3iKzItxEx0zEN81zKrmP

Scale = 1:33.1




Plate Offsets (X,Y)-- [4:0-6-13,0-0-8], [6:0-5-3,0-1-0]

| LOADING (psf) | SPACING- | CSI. | DEFL. | in (loc) | l/defl | L/d | PLATES | GRIP |
|---------------|----------------------|----------|----------|----------|--------|------|----------------|----------|
| TCLL 20.0 | 2-0-0 | TC 0.38 | Vert(LL) | -0.08 | 1-6 | >999 | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.57 | Vert(CT) | -0.15 | 1-6 | >867 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.64 | Horz(CT) | 0.01 | 4 | n/a | | |
| BCDL 10.0 | Rep Stress Incr NO | Matrix-S | Wind(LL) | 0.06 | 1-6 | >999 | | |
| | Code IRC2015/TPI2014 | | | | | | Weight: 233 lb | FT = 20% |

LUMBER-
TOP CHORD 2x6 SP No.1
BOT CHORD 2x8 SP 2400F 2.0E
WEBS 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 1=4120/0-3-8 (min. 0-1-12), 4=4364/0-3-8 (min. 0-1-13)
Max Horz 1=68(LC 24)
Max Uplift 1=-555(LC 8), 4=-549(LC 9)
Max Grav 1=4203(LC 19), 4=4364(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-4016/576, 2-3=-201/623
BOT CHORD 1-7=-498/3514, 7-8=-498/3514, 8-9=-498/3514, 6-9=-498/3514, 6-10=-261/1402,
5-10=-261/1402, 4-5=-261/1402, 3-4=-451/245
WEBS 2-4=-4182/590, 2-6=-602/5194

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x8 - 2 rows staggered at 0-3-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=555, 4=549.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1412 lb down and 188 lb up at 1-0-12, 1411 lb down and 189 lb up at 3-0-12, 1411 lb down and 189 lb up at 5-0-12, and 1411 lb down and 189 lb up at 7-0-12, and 1411 lb down and 189 lb up at 9-0-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard
1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-2=-60, 2-3=-60, 1-3=-20

| | | | | | |
|------------|-------|---------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | C3 | Common Girder | 1 | 2 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:20 2023 Page 2
ID:NpSit5YZ_4qsCWpC5omWUAYBIV_-SbXLWI6Ck9owhJHsWFQmVh3iKzItsxEz0zEN81zKrmP

LOAD CASE(S) Standard

Concentrated Loads (lb)


Vert: 6--1411(B) 7--1412(B) 8--1411(B) 9--1411(B) 10--1411(B)

| | | | | | |
|------------|-------|----------------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | D1 | COMMON SUPPORTED GAB | 1 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:20 2023 Page 1
 ID:NpSit5YZ_4qsCWpC5omWUAYBIV_-SbXLWl6Ck9owhJHsWFQmVh3nFztFs39z0zEN81zKrmP

Scale = 1:21.9



| LOADING (psf) | SPACING- | CSI. | DEFL. | PLATES | GRIP |
|---------------|----------------------|----------|-------------------------|---------------|----------|
| TCLL 20.0 | 2-0-0 | TC 0.06 | in (loc) l/defl L/d | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.03 | Vert(LL) 0.00 6 n/r 120 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.07 | Vert(CT) 0.00 7 n/r 120 | | |
| BCDL 10.0 | Rep Stress Incr YES | Matrix-S | Horz(CT) 0.00 6 n/a n/a | | |
| | Code IRC2015/TPI2014 | | | Weight: 67 lb | FT = 20% |

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10'-0" oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 11-0-0.
 (lb) - Max Horz 2=73(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 6 except 10=-151(LC 12), 8=-150(LC 13)
 Max Grav All reactions 250 lb or less at joint(s) 2, 6, 9 except 10=282(LC 1), 8=282(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 3-10=-199/375, 5-8=-199/375


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-8-10 to 3-6-0, Exterior(2) 3-6-0 to 5-6-0, Corner(3) 5-6-0 to 9-10-13, Exterior(2) 9-10-13 to 11-8-10 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2'-0" oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-6" tall by 2'-0" wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 6 except (jt=lb) 10=151, 8=150.
 - Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 6.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | VB-1 | Valley | 1 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:21 2023 Page 1
ID:NpSit5YZ_4qsCWpC5omWUAYBIV_-wn5jld6qVSwnISs34zx?1ucvqNCLbXy6FdzwhTzKrmO



Scale: 3/4"=1'



| LOADING (psf) | SPACING- | CSI. | DEFL. | PLATES | GRIP |
|---------------|----------------------|----------|-------------------------|---------------|----------|
| TCLL 20.0 | 2-0-0 | TC 0.20 | in (loc) l/defl L/d | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.11 | Vert(LL) n/a - n/a 999 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.03 | Vert(CT) n/a - n/a 999 | | |
| BCDL 10.0 | Rep Stress Incr YES | Matrix-P | Horz(CT) 0.00 3 n/a n/a | | |
| | Code IRC2015/TPI2014 | | | Weight: 28 lb | FT = 20% |

LUMBER-
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=155/8-10-1 (min. 0-1-8), 3=155/8-10-1 (min. 0-1-8), 4=299/8-10-1 (min. 0-1-8)
Max Horz 1=-29(LC 8)
Max Uplift 1=-35(LC 12), 3=-40(LC 13), 4=-1(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3, 4.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | VB-2 | Valley | 1 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:21 2023 Page 1
ID:NpSit5YZ_4qsCWpC5omWUAYBIV_-wn5jld6qVSwmISs34zx?1ucyENDdbXA6FdzwhTzKrmO



Scale = 1:8.9

| LOADING (psf) | SPACING- | CSI. | DEFL. | PLATES | GRIP |
|---------------|----------------------|----------|-------------------------|---------------|----------|
| TCLL 20.0 | 2-0-0 | TC 0.05 | in (loc) l/defl L/d | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.02 | Vert(LL) n/a - n/a 999 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.02 | Vert(CT) n/a - n/a 999 | | |
| BCDL 10.0 | Rep Stress Incr YES | Matrix-P | Horz(CT) 0.00 3 n/a n/a | | |
| | Code IRC2015/TPI2014 | | | Weight: 14 lb | FT = 20% |

LUMBER-
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.2

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 4-10-1 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=73/4-10-1 (min. 0-1-8), 3=73/4-10-1 (min. 0-1-8), 4=142/4-10-1 (min. 0-1-8)
Max Horz 1=-14(LC 8)
Max Uplift 1=-17(LC 12), 3=-19(LC 13)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

| | | | | | |
|---|---------------|----------------------|----------|----------|--------------------------|
| Job J0523-2069 | Truss VC-1 | Truss Type Valley | Qty 1 | Ply 1 | 109-23-107 Coleman |
| Comtech, Inc., Fayetteville, NC 28309, James Naylor | | | | | Job Reference (optional) |

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:22 2023 Page 1
ID:NpSit5YZ_4qsCWpC5omWUAYbIV_-Oze5xz7SGm2ewcRFegSEa686jnYtK_0FTHjUDvzKrmN



Scale = 1:23.1

Plate Offsets (X,Y)-- [4:0-0-0,0-0-0]

| LOADING (psf) | SPACING- | 2-0-0 | CSI. | DEFL. | in | (loc) | l/defl | L/d | PLATES | GRIP |
|---------------|----------------------|-------|----------|----------|------|-------|--------|-----|---------------|----------|
| TCLL 20.0 | Plate Grip DOL | 1.15 | TC 0.13 | Vert(LL) | n/a | - | n/a | 999 | MT20 | 244/190 |
| TCDL 10.0 | Lumber DOL | 1.15 | BC 0.09 | Vert(CT) | n/a | - | n/a | 999 | | |
| BCLL 0.0 * | Rep Stress Incr | YES | WB 0.04 | Horz(CT) | 0.00 | 5 | n/a | n/a | | |
| BCDL 10.0 | Code IRC2015/TPI2014 | | Matrix-S | | | | | | Weight: 50 lb | FT = 20% |

LUMBER-
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 14-1-1.
(lb) - Max Horz 1=-49(LC 8)
Max Uplift All uplift 100 lb or less at joint(s) 1, 8, 6
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=283(LC 1), 8=310(LC 23), 6=310(LC 24)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-7-7 to 5-0-3, Interior(1) 5-0-3 to 7-0-8, Exterior(2) 7-0-8 to 11-5-5, Interior(1) 11-5-5 to 13-5-10 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 8, 6.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | VC-2 | Valley | 1 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:22 2023 Page 1
ID:NpSit5YZ_4qsCWpC5omWUyBIV_-Oze5xz7SGm2ewcRFegSEa684ZnX0K_4FTHjUDvzKrmN



Scale = 1:17.2

| LOADING (psf) | SPACING- | CSI. | DEFL. | PLATES | GRIP |
|---------------|----------------------|----------|-------------------------|---------------|----------|
| TCLL 20.0 | 2-0-0 | TC 0.20 | in (loc) l/defl L/d | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.14 | Vert(LL) n/a - n/a 999 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.04 | Vert(CT) n/a - n/a 999 | | |
| BCDL 10.0 | Rep Stress Incr YES | Matrix-S | Horz(CT) 0.00 3 n/a n/a | | |
| | Code IRC2015/TPI2014 | | | Weight: 33 lb | FT = 20% |

LUMBER-
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=162/10-1-1 (min. 0-1-8), 3=162/10-1-1 (min. 0-1-8), 4=384/10-1-1 (min. 0-1-8)
Max Horz 1=33(LC 11)
Max Uplift1=-32(LC 12), 3=-38(LC 13), 4=-19(LC 12)
Max Grav 1=164(LC 23), 3=164(LC 24), 4=384(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-4=-254/216


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3, 4.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

| | | | | | |
|------------|-------|------------|-----|-----|--------------------------|
| Job | Truss | Truss Type | Qty | Ply | 109-23-107 Coleman |
| J0523-2069 | VC-3 | Valley | 1 | 1 | Job Reference (optional) |

Comtech, Inc., Fayetteville, NC 28309, James Naylor

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon May 1 14:52:22 2023 Page 1
 ID:NpSit5YZ_4qsCWpC5omWUyBlV_-Oze5xz7SGm2ewcRFegSEa686PnZZK_KFTHjUDvzKrmN



Scale: 1"=1'

| LOADING (psf) | SPACING- | CSI. | DEFL. | PLATES | GRIP |
|---------------|----------------------|----------|-------------------------|---------------|----------|
| TCLL 20.0 | 2-0-0 | TC 0.08 | in (loc) l/defl L/d | MT20 | 244/190 |
| TCDL 10.0 | Plate Grip DOL 1.15 | BC 0.04 | Vert(LL) n/a - n/a 999 | | |
| BCLL 0.0 * | Lumber DOL 1.15 | WB 0.02 | Vert(CT) n/a - n/a 999 | | |
| BCDL 10.0 | Rep Stress Incr YES | Matrix-P | Horz(CT) 0.00 3 n/a n/a | | |
| | Code IRC2015/TPI2014 | | | Weight: 19 lb | FT = 20% |

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=99/6-1-1 (min. 0-1-8), 3=99/6-1-1 (min. 0-1-8), 4=191/6-1-1 (min. 0-1-8)
 Max Horz 1=-18(LC 8)
 Max Uplift1=-23(LC 12), 3=-26(LC 13), 4=-1(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3, 4.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard