

<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL 1.15	TC 0.57	Vert(LL) -0.15 13-15 >999 360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.55	Vert(CT) -0.23 13-15 >999 240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.35	Horz(CT) 0.07 9 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.05 2-15 >999 240		Weight: 294 lb FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-4-2 oc purlins, except 2-0-0 oc purlins (4-9-4 max.): 5-6.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS T-Brace: 2x4 SPF No.2 - 5-13, 6-13  
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.  
 Brace must cover 90% of web length.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=1686/0-3-8 (min. 0-2-4), 9=1686/0-3-8 (min. 0-2-4)  
 Max Horz 2=-260(LC 10)  
 Max Uplift 2=-80(LC 12), 9=-80(LC 13)  
 Max Grav 2=1889(LC 19), 9=1889(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-16=-2777/524, 3-16=-2705/555, 3-17=-2621/602, 4-17=-2587/605, 4-5=-2513/645, 5-18=-1877/519, 18-19=-1877/519, 6-19=-1877/519, 6-7=-2513/645, 7-20=-2587/605, 8-20=-2621/602, 8-21=-2705/555, 9-21=-2777/524  
 BOT CHORD 2-22=-318/2378, 22-23=-318/2378, 15-23=-318/2378, 15-24=-119/1801, 14-24=-119/1801, 14-25=-119/1801, 13-25=-119/1801, 13-26=-128/1762, 12-26=-128/1762, 12-27=-128/1762, 11-27=-128/1762, 11-28=-327/2228, 28-29=-327/2228, 9-29=-327/2228  
 WEBS 3-15=-492/298, 5-15=-158/921, 5-13=-53/362, 6-13=-53/362, 6-11=-158/921, 8-11=-492/298

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-9 to 3-4-4, Interior(1) 3-4-4 to 15-4-0, Exterior(2) 15-4-0 to 21-6-11, Interior(1) 21-6-11 to 25-4-0, Exterior(2) 25-4-0 to 31-6-11, Interior(1) 31-6-11 to 41-8-9 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 9.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - 9) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.


**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	A2	HIP	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:27 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-B3AevtP2R4HrOfuFS5UDRkmG0yUYAq3gihTfcpzIXqY

41-10-8  
0-3-8  
1-2-8  
Scale = 1:74.2



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	2-0-0	TC 0.26	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.49	Vert(LL) -0.15 14-16 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.31	Vert(CT) -0.24 14-16 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.07 10 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.05 14 >999 240		Weight: 296 lb FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1  
WEBS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 4-8-8 oc purlins, except 2-0-0 oc purlins (5-2-9 max.): 5-7.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
WEBS T-Brace: 2x4 SPF No.2 - 6-14  
Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.  
Brace must cover 90% of web length.




MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=1686/0-3-8 (min. 0-2-0), 10=1686/0-3-8 (min. 0-2-0)  
Max Horz 2=-220(LC 10)  
Max Uplift 2=-65(LC 12), 10=-65(LC 13)  
Max Grav 2=1704(LC 2), 10=1704(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-17=-2571/562, 3-17=-2498/586, 3-4=-2379/559, 4-5=-2285/595, 5-18=-2132/606,  
6-18=-2134/606, 6-19=-2134/606, 7-19=-2132/606, 7-8=-2285/595, 8-9=-2379/559,  
9-20=-2498/586, 10-20=-2571/562  
BOT CHORD 2-16=-360/2133, 16-21=-173/1765, 15-21=-173/1765, 15-22=-173/1765, 14-22=-173/1765,  
14-23=-181/1765, 13-23=-181/1765, 13-24=-181/1765, 12-24=-181/1765, 10-12=-369/2061  
WEBS 3-16=-404/257, 5-16=-68/641, 5-14=-141/641, 6-14=-538/267, 7-14=-141/641,  
7-12=-68/641, 9-12=-404/257

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-9 to 3-4-4, Interior(1) 3-4-4 to 12-10-0, Exterior(2) 12-10-0 to 19-0-11, Interior(1) 19-0-11 to 27-10-0, Exterior(2) 27-10-0 to 34-1-1, Interior(1) 34-1-1 to 41-8-9 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - 9) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

**LOAD CASE(S)** Standard



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.33	Vert(LL) -0.17 15-17	>999 360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.51	Vert(CT) -0.33 15-17	>999 240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.55	Horz(CT) 0.07 11	n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL) 0.09 15-17	>999 240		
						Weight: 305 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-8-11 oc purlins, except 2-0-0 oc purlins (4-8-3 max.): 6-9.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS T-Brace: 2x4 SPF No.2 - 6-17  
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.  
 Brace must cover 90% of web length.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=1686/0-3-8 (min. 0-2-0), 11=1686/0-3-8 (min. 0-2-0)  
 Max Horz 2=-211(LC 10)  
 Max Uplift 2=-63(LC 13), 11=-159(LC 13)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-19=-2528/506, 3-19=-2418/529, 3-4=-2167/503, 4-20=-2131/505, 5-20=-2075/537,  
 5-6=-2106/584, 6-7=-2481/654, 7-8=-2481/652, 8-21=-2483/654, 9-21=-2481/654,  
 9-22=-2236/553, 10-22=-2302/523, 10-23=-2409/578, 11-23=-2486/560  
 BOT CHORD 2-18=-306/2114, 17-18=-306/2114, 17-24=-278/2213, 16-24=-278/2213, 16-25=-278/2213,  
 15-25=-278/2213, 14-15=-207/1861, 14-26=-207/1861, 13-26=-207/1861, 11-13=-363/1995  
 WEBS 3-17=-487/195, 5-17=-495/2100, 6-17=-1668/501, 6-15=-92/510, 8-15=-609/290,  
 9-15=-192/827, 9-13=-2/470, 10-13=-317/194

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-9 to 3-4-4, Interior(1) 3-4-4 to 12-2-0, Exterior(2) 12-2-0 to 14-0-0, Interior(1) 14-0-0 to 30-4-0, Exterior(2) 30-4-0 to 34-8-13, Interior(1) 34-8-13 to 41-8-9 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2 except (jt=lb) 11=159.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.


**LOAD CASE(S)** Standard



Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	A5GR	Roof Special Girder	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:29 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-8RIPJYRlzhXZez2eaWxhXlrbpl67ee9zA?ymghzlxqV



Scale = 1:76.1




Plate Offsets (X,Y)-- [5:0-3-0,0-2-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.30	Vert(LL)	-0.24 13-15	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.74	Vert(CT)	-0.49 13-15	>997	240		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.66	Horz(CT)	0.07 10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.22 13-15	>999	240		
								Weight: 568 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except
BOT CHORD 2x6 SP No.1	2-0-0 oc purlins (6-0-0 max.): 4-5, 6-9.
WEBS 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 2=2008/0-3-8 (min. 0-1-8), 10=2444/0-3-8 (min. 0-1-8)  
Max Horz 2=159(LC 26)  
Max Uplift 2=189(LC 8), 10=527(LC 9)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-3080/331, 3-4=-2892/342, 4-5=-2340/301, 5-6=-7325/1183, 6-18=-6369/1297,  
18-19=-6370/1297, 7-19=-6371/1297, 7-8=-6369/1296, 8-20=-6371/1297, 20-21=-6369/1297,  
21-22=-6369/1296, 9-22=-6367/1296, 9-10=-3852/842  
BOT CHORD 2-17=-312/2453, 17-23=-408/3376, 16-23=-408/3376, 16-24=-408/3376, 15-24=-408/3376,  
14-15=-838/6257, 14-25=-838/6257, 13-25=-838/6257, 13-26=-616/3120, 26-27=-616/3120,  
27-28=-616/3120, 12-28=-616/3120, 12-29=-613/3131, 10-29=-613/3131  
WEBS 4-17=-135/1214, 5-17=-1468/329, 5-15=-934/5373, 6-15=-4322/912, 6-13=-794/672,  
7-13=-853/529, 9-13=-610/3546, 9-12=0/448

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope);  
Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=189, 10=527.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	A5GR	Roof Special Girder	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:29 2023 Page 2  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-8RIPJYRlzhXZez2eaWXhXlrpl67ee9zA?ymghzlXqW

**NOTES-**

11) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 111 lb down and 106 lb up at 24-5-8, 110 lb down and 102 lb up at 25-3-4, 110 lb down and 102 lb up at 27-3-4, 110 lb down and 102 lb up at 29-3-4, 110 lb down and 102 lb up at 31-3-4, and 110 lb down and 102 lb up at 33-3-4, and 110 lb down and 106 lb up at 35-4-0 on top chord, and 495 lb down and 22 lb up at 24-5-8, 36 lb down at 25-3-4, 36 lb down at 27-3-4, 36 lb down at 29-3-4, 36 lb down at 31-3-4, 36 lb down at 33-3-4, and 36 lb down at 35-3-4, and 168 lb down and 78 lb up at 37-3-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

**LOAD CASE(S)** Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-4=-60, 4-5=-60, 5-6=-60, 6-9=-60, 9-11=-60, 2-10=-20

Concentrated Loads (lb)

Vert: 9=-42(B) 7=-42(B) 13=-18(B) 12=-18(B) 14=-495(B) 18=-54(B) 19=-42(B) 20=-42(B) 21=-42(B) 22=-42(B) 25=-18(B) 26=-18(B) 27=-18(B) 28=-18(B) 29=-168(B)

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	B1	PIGGYBACK BASE	5	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:29 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-8RIPJYRlzhXZez2eaWXhXlrbelBTejLzA?ymghzXqV




Plate Offsets (X,Y)-- [6:0-2-4,0-2-12], [12:0-3-0,0-3-8], [13:0-5-15,0-2-8], [14:0-5-4,0-3-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.31	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.40	Vert(LL) -0.10 12-13 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.33	Vert(CT) -0.23 12-13 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.10 10 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.05 13 >999 240		
				Weight: 279 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-10-14 oc purlins, except 2-0-0 oc purlins (5-5-14 max.): 6-7.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS 1 Row at midpt 6-14, 7-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=1526/0-3-8 (min. 0-1-13), 10=1526/0-3-8 (min. 0-1-13)  
 Max Horz 2=-268(LC 10)  
 Max Uplift 2=-83(LC 12), 10=-83(LC 13)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-15=-2202/492, 3-15=-2109/509, 3-4=-1967/456, 4-16=-1827/481, 5-16=-1821/485,  
 5-6=-1991/669, 6-7=-2018/504, 7-17=-2218/745, 8-17=-2245/704, 8-9=-2287/693,  
 9-18=-2052/486, 10-18=-2266/457  
 BOT CHORD 2-14=-304/1757, 13-14=-86/1722, 12-13=-110/2059, 10-12=-288/1787  
 WEBS 3-14=-314/172, 5-14=-397/267, 6-13=-26/857, 9-12=-610/377, 7-13=0/925, 6-14=-248/368,  
 7-12=-406/294


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-9 to 3-4-4, Interior(1) 3-4-4 to 15-8-6, Exterior(2) 15-8-6 to 27-2-5, Interior(1) 27-2-5 to 37-8-9 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	B2	PIGGYBACK BASE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:30 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-cdsnXuRrk?fQF7dq8D2w3yOmT9XiNAh7OfhJD8zIXqV



Scale = 1:71.5




Plate Offsets (X,Y)-- [6:0-2-4,0-2-12], [11:0-3-0,0-3-8], [12:0-5-15,0-2-8], [13:0-5-4,0-3-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.31	Vert(LL)	-0.10	11-12	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.40	Vert(CT)	-0.23	11-12	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.32	Horz(CT)	0.10	10	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.05	12	>999		
	Code IRC2015/TPI2014						Weight: 276 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-10-9 oc purlins, except 2-0-0 oc purlins (5-5-10 max.): 6-7.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS 1 Row at midpt 6-13, 7-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=1531/0-3-8 (min. 0-1-13), 10=1457/Mechanical  
 Max Horz 2=263(LC 9)  
 Max Uplift 2=-83(LC 12), 10=-67(LC 13)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-14=-2210/494, 3-14=-2117/511, 3-4=-1975/461, 4-15=-1835/486, 5-15=-1829/490,  
 5-6=-1998/675, 6-7=-2031/519, 7-16=-2241/759, 8-16=-2267/717, 8-9=-2322/707,  
 9-17=-2077/502, 10-17=-2268/474  
 BOT CHORD 2-13=-345/1764, 12-13=-142/1731, 11-12=-144/2073, 10-11=-315/1817  
 WEBS 3-13=-314/172, 5-13=-397/267, 6-12=-40/866, 9-11=-627/386, 7-12=0/921, 6-13=-224/353,  
 7-11=-398/304

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-9 to 3-4-4, Interior(1) 3-4-4 to 15-8-6, Exterior(2) 15-8-6 to 27-2-5, Interior(1) 27-2-5 to 36-7-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 6) Refer to girder(s) for truss to truss connections.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.


**LOAD CASE(S)** Standard



Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	B3	Piggyback Base	5	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:31 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-4qP9kESZVloHtHC0hwZ9cAxxYZuF6XyGdJRslaziXqJ



Scale = 1:65.8

Plate Offsets (X,Y)-- [6:0-0-6,Edge], [7:0-3-0,0-3-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.29	Vert(LL) -0.08	7-8	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.31	Vert(CT) -0.17	7-8	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.70	Horz(CT) 0.05	6	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL) 0.03	7	>999	240		
	Code IRC2015/TPI2014						Weight: 219 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2 \*Except\*  
 W1: 2x6 SP No.1

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 5-10-13 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 2-3.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS 1 Row at midpt 2-9, 3-7

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 9=1055/0-3-8 (min. 0-1-8), 6=1055/Mechanical  
 Max Horz 9=-268(LC 13)  
 Max Uplift 9=-55(LC 13), 6=-43(LC 13)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-1003/242, 3-4=-1539/565, 4-11=-1561/526, 5-11=-1612/514, 5-12=-1362/300,  
 6-12=-1553/271  
 BOT CHORD 8-9=-65/651, 7-8=0/1103, 6-7=-157/1227  
 WEBS 2-8=-28/859, 5-7=-635/389, 3-8=-84/301, 2-9=-1135/153, 3-7=-439/778


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-12 to 4-7-9, Interior(1) 4-7-9 to 5-8-6, Exterior(2) 5-8-6 to 17-2-5, Interior(1) 17-2-5 to 26-7-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Refer to girder(s) for truss to truss connections.
  - Bearing at joint(s) 9 considers parallel to grain value using ANSII/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9, 6.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSII/TPI 1.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	B4	Piggyback Base	4	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:31 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-4qP9kESZVloHtHC0hwZ9cAxx0ZuS6Y0GdJRslaziXqJ



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.45	Vert(LL)	-0.08 13-14	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.30	Vert(CT)	-0.16 13-14	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.70	Horz(CT)	0.04 7	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.02 13	>999	240		
								Weight: 244 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1  
WEBS 2x4 SP No.2 \*Except\*  
W1,W9: 2x6 SP No.1

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals, and 2'-0" oc purlins (6'-0" max.): 2-3.  
BOT CHORD Rigid ceiling directly applied or 10'-0" oc bracing.  
WEBS 1 Row at midpt 2-14, 3-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 7=1049/0-3-8 (min. 0-1-8), 14=1039/0-3-8 (min. 0-1-8)  
Max Horz 14=-177(LC 8)  
Max Uplift 7=-17(LC 13), 14=-24(LC 13)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-16=-904/258, 16-17=-904/258, 3-17=-904/258, 3-4=-1002/346, 4-18=-898/248,  
18-19=-916/245, 5-19=-1080/226, 5-7=-975/238  
BOT CHORD 13-14=-116/622, 12-13=-57/880, 9-12=-94/776, 8-9=-133/829  
WEBS 2-14=-1148/236, 2-13=0/678, 4-12=-280/170, 5-8=-126/795


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-4 to 4-9-1, Interior(1) 4-9-1 to 5-8-6, Exterior(2) 5-8-6 to 11-11-0, Interior(1) 11-11-0 to 14-11-10, Exterior(2) 14-11-10 to 21-2-5, Interior(1) 21-2-5 to 26-3-12 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 6) Bearing at joint(s) 14 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 14.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	C1	ROOF SPECIAL	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:32 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-Y0zXyaTBGcw8VRnDFe4O8NT4LzEvr27QszAQH0ziXqT



Scale = 1:44.6



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	2-0-0	TC 0.41	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.31	Vert(LL) -0.06 6-7 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.45	Vert(CT) -0.12 6-7 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.03 6 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.03 6-7 >999 240		Weight: 159 lb FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 5-9-15 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 3-4.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 6=963/Mechanical, 2=1038/0-3-8 (min. 0-1-8)  
 Max Horz 2=153(LC 9)  
 Max Uplift 6=-36(LC 13), 2=-93(LC 12)  
 Max Grav 6=971(LC 20), 2=1038(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-10=-1426/284, 10-11=-1324/292, 3-11=-1318/314, 3-12=-1081/325, 4-12=-1081/325,  
 4-5=-1180/346, 5-13=-1165/282, 6-13=-1313/251  
 BOT CHORD 2-9=-148/1092, 8-9=-219/1339, 7-8=-219/1339, 7-14=-95/970, 6-14=-95/970  
 WEBS 3-9=0/431, 4-9=-406/89, 4-7=-779/259, 5-7=-125/956


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-9 to 3-4-4, Interior(1) 3-4-4 to 6-5-12, Exterior(2) 6-5-12 to 10-10-9, Interior(1) 10-10-9 to 15-6-0, Exterior(2) 15-6-0 to 19-10-13, Interior(1) 19-10-13 to 24-3-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCCL = 10.0psf.
  - 6) Refer to girder(s) for truss to truss connections.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 2.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	C1GR	Roof Special Girder	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:33 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-0CXv9wUp0w2?6aMPpLbdhb0lCMbtAZAZ5dwzpsZlXqS



Scale = 1:44.6



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.15	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.24	Vert(LL) -0.04 10-11 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.21	Vert(CT) -0.09 10-11 >999 240		
BCDL 10.0	Rep Stress Incr NO	Matrix-S	Horz(CT) 0.02 7 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.03 10 >999 240		
				Weight: 334 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except
BOT CHORD 2x6 SP No.1	2-0-0 oc purlins (6-0-0 max.): 3-4.
WEBS 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 7=1034/0-3-8 (min. 0-1-8), 2=1294/0-3-8 (min. 0-1-8)  
Max Horz 2=153(LC 24)  
Max Uplift 7=-49(LC 9), 2=-155(LC 8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-2029/178, 3-12=-2518/195, 12-13=-2518/195, 4-13=-2518/195, 4-5=-1326/109, 5-6=-1310/131, 6-7=-1516/123  
BOT CHORD 2-14=-170/1619, 11-14=-170/1619, 11-15=-176/1598, 15-16=-176/1598, 10-16=-176/1598, 9-10=-185/2530,  
8-9=-185/2530, 7-8=-55/1199  
WEBS 3-11=0/460, 3-10=-41/994, 4-8=-1710/206, 5-8=-52/1107, 6-8=-252/153

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7 except (jt=lb) 2=155.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 86 lb down and 71 lb up at 4-7-4, and 86 lb down and 79 lb up at 6-6-8 on top chord, and 96 lb down and 54 lb up at 2-7-4, and 15 lb down at 4-7-4, and 231 lb down at 6-6-8 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

**LOAD CASE(S)** Standard  
1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-60, 3-4=-60, 4-5=-60, 5-7=-60, 2-7=-20

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	C1GR	Roof Special Girder	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:33 2023 Page 2  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-0CXv9wUp0w2?6aMPpLbdhb0ICMbtiaZAZ5dwzpSziXqS


**LOAD CASE(S)** Standard  
Concentrated Loads (lb)

Vert: 12=-5(B) 13=-21(B) 14=-84(B) 15=-7(B) 16=-216(B)

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	D1	ATTIC	4	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:33 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-0CXv9wUp0w2?6aMPpLbdhb0ENMW6aaxZ5dwpzSziXqS



Scale = 1:70.3

Plate Offsets (X,Y)-- [2:0-1-4,0-2-0], [3:0-4-0,Edge], [6:0-4-0,Edge], [9:0-4-0,Edge], [10:0-1-4,0-2-0], [13:0-4-12,0-3-8], [14:0-4-12,0-3-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	1-7-3	TC 0.39	Vert(LL)	-0.17	13-14	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.54	Vert(CT)	-0.23	13-14	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.16	Horz(CT)	0.01	12	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.07	14-15	>999		
	Code IRC2015/TPI2014						Weight: 245 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1 \*Except\*  
T2: 2x10 SP No.1  
BOT CHORD 2x6 SP No.1 \*Except\*  
B2: 2x10 SP No.1  
WEBS 2x6 SP No.1 \*Except\*  
W2: 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 15=957/0-3-8 (min. 0-1-8), 12=957/0-3-8 (min. 0-1-8)  
Max Horz 15=205(LC 11)  
Max Grav 15=1161(LC 20), 12=1161(LC 21)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-16=-1298/39, 3-16=-1190/40, 3-4=-1161/58, 4-17=-918/137, 5-17=-805/160, 5-6=-50/435,  
6-7=-51/432, 7-18=-808/159, 8-18=-921/136, 8-9=-1165/57, 9-19=-1194/39,  
10-19=-1302/38, 2-15=-1144/126, 10-12=-1148/125  
BOT CHORD 14-15=-241/419, 13-14=0/935, 12-13=-64/269  
WEBS 5-7=-1390/269, 4-14=0/490, 8-13=0/490, 2-14=-3/791, 10-13=-12/798

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-3, Interior(1) 3-4-3 to 12-0-0, Exterior(2) 12-0-0 to 16-4-13, Interior(1) 16-4-13 to 25-0-10 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Ceiling dead load (10.0 psf) on member(s). 4-5, 7-8, 5-7; Wall dead load (5.0psf) on member(s).4-14, 8-13
  - Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 13-14
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Attic room checked for L/360 deflection.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	D1GE	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:34 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-UP5HNGVRnDAskkbN36sEoZP6msLJ1AiJHfXMvzIXqR




Plate Offsets (X,Y)-- [2:0-1-4,0-2-0], [3:0-4-0,Edge], [6:0-4-0,0-4-4], [9:0-4-0,Edge], [10:0-1-4,0-2-0], [13:0-4-12,0-3-8], [14:0-4-12,0-3-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	1-7-3	TC 0.39	Vert(LL)	-0.17	13-14	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.54	Vert(CT)	-0.23	13-14	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.16	Horz(CT)	0.01	12	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.09	14-15	>999		
	Code IRC2015/TPI2014						Weight: 265 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1 *Except* T2: 2x10 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x6 SP No.1 *Except* B2: 2x10 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x6 SP No.1 *Except* W2: 2x4 SP No.2	
OTHERS 2x4 SP No.2	

**REACTIONS.** (lb/size) 15=957/0-3-8 (min. 0-1-8), 12=957/0-3-8 (min. 0-1-8)  
Max Horz 15=-256(LC 10)  
Max Uplift 15=-50(LC 12), 12=-50(LC 13)  
Max Grav 15=1159(LC 20), 12=1159(LC 21)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-1303/78, 3-4=-1167/92, 4-5=-922/199, 5-6=-84/443, 6-7=-81/439, 7-8=-925/199,  
8-9=-1172/91, 9-10=-1309/77, 2-15=-1140/159, 10-12=-1145/159  
BOT CHORD 14-15=-315/471, 13-14=0/952, 12-13=-123/283  
WEBS 5-7=-1381/368, 4-14=0/490, 8-13=0/490, 2-14=-50/825, 10-13=-61/834


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -1-0-10 to 3-4-3, Exterior(2) 3-4-3 to 12-0-0, Corner(3) 12-0-0 to 16-4-13, Exterior(2) 16-4-13 to 25-0-10 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - 4) All plates are 2x4 MT20 unless otherwise indicated.
  - 5) Gable studs spaced at 2-0-0 oc.
  - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 7) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 8) Ceiling dead load (10.0 psf) on member(s). 4-5, 7-8, 5-7; Wall dead load (5.0psf) on member(s). 4-14, 8-13
  - 9) Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 13-14
  - 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 15, 12.
  - 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 12) Attic room checked for L/360 deflection.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	D2	ATTIC	6	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:34 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-UP5HNGVRnDAskkbN36sEoZPwmsJJ1viJHfXMvziXqR



6x8 =

Scale = 1:70.3




Plate Offsets (X,Y)-- [2:0-1-4,0-2-0], [3:0-4-0,Edge], [6:0-4-0,Edge], [9:0-4-0,Edge], [10:0-1-4,0-2-0], [12:0-4-12,0-3-8], [13:0-4-12,0-3-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	1-7-3	TC 0.40	Vert(LL)	-0.17 12-13	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.55	Vert(CT)	-0.24 12-13	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.18	Horz(CT)	0.01 11	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.07 11-12	>999	240		
	Code IRC2015/TPI2014						Weight: 242 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1 \*Except\*  
T2: 2x10 SP No.1  
BOT CHORD 2x6 SP No.1 \*Except\*  
B2: 2x10 SP No.1  
WEBS 2x6 SP No.1 \*Except\*  
W2: 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 14=959/0-3-8 (min. 0-1-8), 11=894/0-3-8 (min. 0-1-8)  
Max Horz 14=198(LC 9)  
Max Grav 14=1163(LC 20), 11=1103(LC 21)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-15=-1304/40, 3-15=-1196/41, 3-4=-1168/59, 4-16=-921/136, 5-16=-808/159, 5-6=-62/447,  
6-7=-54/448, 7-17=-812/164, 8-17=-925/141, 8-9=-1161/54, 9-10=-1297/32,  
2-14=-1149/127, 10-11=-1103/70  
BOT CHORD 13-14=-254/406, 12-13=0/929  
WEBS 5-7=-1412/287, 4-13=0/493, 8-12=0/471, 2-13=-4/802, 10-12=0/840

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-3, Interior(1) 3-4-3 to 12-0-0, Exterior(2) 12-0-0 to 16-4-13, Interior(1) 16-4-13 to 23-9-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Ceiling dead load (10.0 psf) on member(s). 4-5, 7-8, 5-7; Wall dead load (5.0psf) on member(s). 4-13, 8-12
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 12-13
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Attic room checked for L/360 deflection.


**LOAD CASE(S)** Standard



Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	D2GR	ATTIC	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:35 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-ybfgacV3YXijMuWowmd5m05bRAED2U4sYxP4uLzIXqQ



6x8 =

Scale = 1:70.2




Plate Offsets (X,Y)-- [3:0-4-0,Edge], [6:0-4-0,Edge], [9:0-4-0,Edge], [12:0-4-12,0-3-8], [13:0-4-12,0-3-8]

LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.36	Vert(LL)	-0.11 12-13	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.44	Vert(CT)	-0.18 12-13	>999	240		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.12	Horz(CT)	0.01 11	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.08 12-13	>999	240		
								Weight: 484 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1 \*Except\*  
T2: 2x10 SP No.1  
BOT CHORD 2x6 SP No.1 \*Except\*  
B2: 2x10 SP No.1  
WEBS 2x6 SP No.1 \*Except\*  
W2: 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 14=1286/0-3-8 (min. 0-1-8), 11=1128/0-3-8 (min. 0-1-8)  
Max Horz 14=198(LC 7)  
Max Uplift 14=-88(LC 8), 11=-32(LC 9)  
Max Grav 14=1435(LC 34), 11=1297(LC 35)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-1642/132, 3-4=-1498/137, 4-5=-1078/141, 5-6=-135/635, 6-7=-117/602,  
7-8=-1116/162, 8-9=-1455/121, 9-10=-1593/110, 2-14=-1448/118, 10-11=-1354/92  
BOT CHORD 13-14=-298/485, 13-15=-49/1155, 12-15=-49/1155  
WEBS 5-7=-1861/320, 4-13=-128/722, 8-12=-70/574, 2-13=-81/940, 10-12=-126/1090

**NOTES-**

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x10 - 2 rows staggered at 0-9-0 oc.  
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x10 - 2 rows staggered at 0-9-0 oc.  
Webs connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Ceiling dead load (10.0 psf) on member(s). 4-5, 7-8, 5-7; Wall dead load (5.0psf) on member(s). 4-13, 8-12
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 12-13
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 14, 11.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 561 lb down and 265 lb up at 10-0-8 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- Attic room checked for L/360 deflection.

**LOAD CASE(S)** Standard

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	D2GR	ATTIC	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:35 2023 Page 2  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-ybfgacV3YXijMuWowmd5m05bRAED2U4sYxP4uLzIXqQ

**LOAD CASE(S)** Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 11-14=-16, 1-2=-48, 2-4=-48, 4-5=-64, 5-6=-48, 6-7=-48, 7-8=-64, 8-10=-48, 5-7=-16

Drag: 4-13=-8, 8-12=-8


Concentrated Loads (lb)

Vert: 15=-561(B)

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	E1	ATTIC	6	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:35 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-ybfgacV3YXlJmUwWowmd5m05TEA752PSsYxP4uLzIXqQ



Scale = 1:65.1

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.88	Vert(LL)	-0.43 11-13	>666	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.89	Vert(CT)	-0.57 11-13	>502	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.42	Horz(CT)	0.02 10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.19 2-13	>999	240		
								Weight: 202 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x6 SP No.1  
 SLIDER Right 2x4 SP No.2 - 4-0-12

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 10=947/0-3-8 (min. 0-1-8), 2=1022/0-3-8 (min. 0-1-10)  
 Max Horz 2=256(LC 9)  
 Max Uplift 10=-39(LC 13), 2=-57(LC 12)  
 Max Grav 10=1281(LC 21), 2=1351(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-14=-1763/194, 3-14=-1567/197, 3-4=-1562/219, 4-15=-1063/289, 5-15=-993/301,  
 5-6=-57/376, 6-7=-53/380, 7-16=-988/305, 8-16=-1058/293, 8-17=-1554/218,  
 9-17=-1603/199, 9-10=-1759/197  
 BOT CHORD 2-18=-5/1187, 13-18=-5/1187, 12-13=-5/1187, 11-12=-5/1187, 11-19=-5/1187,  
 10-19=-5/1187  
 WEBS 8-11=0/828, 4-13=0/832, 5-7=-1561/445


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-3, Interior(1) 3-4-3 to 12-0-0, Exterior(2) 12-0-0 to 16-4-13, Interior(1) 16-4-13 to 23-10-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - All plates are 2x4 MT20 unless otherwise indicated.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 11-13
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 10, 2.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - ATTIC SPACE SHOWN IS DESIGNED AS UNINHABITABLE.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	E1GR	ATTIC	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:36 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-RnD2nxWhJrQZz24\_UU9KJDehFaT2nw3?nb8dQnzIXqP



Scale = 1:65.1

Plate Offsets (X,Y)-- [2:0-0,0,0-0], [6:0-3,0,Edge], [10:0-1,10,0-1-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.67	Vert(LL)	-0.29 11-13	>993	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.85	Vert(CT)	-0.47 11-13	>600	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.14	Horz(CT)	0.02 10	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-S	Wind(LL)	0.24 11-13	>999	240		
	Code IRC2015/TPI2014						Weight: 405 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x6 SP No.1  
 SLIDER Right 2x4 SP No.2 -p 4-0-12

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 10=1254/0-3-8 (min. 0-1-8), 2=1450/0-3-8 (min. 0-1-8)  
 Max Horz 2=256(LC 25)  
 Max Uplift 10=-166(LC 9), 2=-233(LC 8)  
 Max Grav 10=1551(LC 35), 2=1728(LC 34)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-2354/367, 3-4=-2150/373, 4-5=-1333/288, 5-6=-136/568, 6-7=-113/522,  
 7-8=-1379/311, 8-9=-2097/349, 9-10=-2304/308  
 BOT CHORD 2-14=-175/1571, 13-14=-175/1571, 13-15=-175/1571, 12-15=-175/1571, 11-12=-175/1571,  
 11-16=-175/1571, 10-16=-175/1571  
 WEBS 8-11=-133/1087, 4-13=-201/1242, 5-7=-2164/490

**NOTES-**

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
 Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
 Webs connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
- All plates are 2x4 MT20 unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 11-13
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 10=166, 2=233.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 735 lb down and 311 lb up at 10-0-8 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- ATTIC SPACE SHOWN IS DESIGNED AS UNINHABITABLE.

**LOAD CASE(S)** Standard

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	E1GR	ATTIC	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:36 2023 Page 2  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-RnD2nxWhJrQZz24\_UU9KJDehFaT2nw3?nb8dQnzIXqP

**LOAD CASE(S)** Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-6=-60, 6-10=-60, 2-10=-20


Concentrated Loads (lb)

Vert: 15=-735(F)

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	E2	ATTIC	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:36 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-RnD2nxWhJrQZz24\_UU9KJDeesaTQnIO?nb8dQnzIXp



Scale = 1:55.2

Plate Offsets (X,Y)-- [2:0-8-0,0-0-4], [5:0-3-0,0-3-0], [6:0-3-0,0-3-0], [10:0-1-6,0-2-0], [11:0-3-0,0-2-0], [13:0-3-0,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.89	Vert(LL)	-0.41 11-13	>696	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.89	Vert(CT)	-0.54 11-13	>527	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.88	Horz(CT)	0.02 10	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.19 2-13	>999	240		
	Code IRC2015/TPI2014						Weight: 196 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x6 SP No.1 \*Except\*  
 W2: 2x4 SP No.1  
 SLIDER Right 2x4 SP No.2 -p 4-0-12

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except 2-0-0 oc purlins (10-0-0 max.): 5-6.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 10=947/0-3-8 (min. 0-1-8), 2=1022/0-3-8 (min. 0-1-9)  
 Max Horz 2=226(LC 9)  
 Max Uplift 10=-35(LC 13), 2=-53(LC 12)  
 Max Grav 10=1263(LC 21), 2=1333(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-14=-1719/232, 14-15=-1585/235, 3-15=-1520/254, 3-4=-1023/333, 4-5=-90/627,  
 5-6=-148/866, 6-7=-82/635, 7-8=-1016/338, 8-16=-1512/258, 16-17=-1561/243,  
 9-17=-1573/239, 9-10=-1716/237  
 BOT CHORD 2-18=-36/1161, 13-18=-36/1161, 12-13=-36/1161, 11-12=-36/1161, 11-19=-36/1161,  
 10-19=-36/1161  
 WEBS 3-13=0/829, 8-11=0/830, 4-7=-1963/546

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-3, Interior(1) 3-4-3 to 10-4-13, Exterior(2) 10-4-13 to 19-9-14, Interior(1) 19-9-14 to 23-10-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCCL = 10.0psf.
  - 6) Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 11-13
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 10, 2.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - 10) ATTIC SPACE SHOWN IS DESIGNED AS UNINHABITABLE.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	E3	ATTIC	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:37 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-v\_nQ?HXK48YQbCfA2BgZrRbN\_oPWNF9?EuByEzIXqO




Plate Offsets (X,Y)-- [2:0-5-8,Edge], [5:0-3-0,Edge], [6:0-3-0,Edge], [9:0-1-2,0-2-0], [12:0-4-12,0-2-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.98	Vert(LL) -0.45	10-12	>635	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.90	Vert(CT) -0.59	10-12	>482	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.14	Horz(CT) 0.02	9	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL) 0.16	10	>999	240		
	Code IRC2015/TPI2014						Weight: 192 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x6 SP No.1 \*Except\*  
 W1: 2x4 SP No.2  
 WEDGE  
 Left: 2x4 SP No.2  
 SLIDER Right 2x4 SP No.2 -p 4-0-12

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied, except 2-0-0 oc purlins (6-0-0 max.): 5-6.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 9=947/0-3-8 (min. 0-1-8), 2=1022/0-3-8 (min. 0-1-8)  
 Max Horz 2=194(LC 9)  
 Max Uplift 9=30(LC 13), 2=47(LC 12)  
 Max Grav 9=1221(LC 21), 2=1236(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-13=-1705/302, 13-14=-1595/315, 3-14=-1590/322, 3-4=-1580/348, 4-5=-935/333,  
 5-6=-1000/345, 6-7=-935/346, 7-15=-1358/258, 8-15=-1407/240, 8-16=-1457/238,  
 9-16=-1565/232  
 BOT CHORD 2-12=-174/1298, 11-12=-33/1017, 10-11=-33/1017, 10-17=-33/1017, 9-17=-33/1017  
 WEBS 4-12=-56/940, 7-10=0/776, 3-12=-441/222


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-3, Interior(1) 3-4-3 to 8-10-10, Exterior(2) 8-10-10 to 21-4-1, Interior(1) 21-4-1 to 23-10-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 10-12
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9, 2.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - ATTIC SPACE SHOWN IS DESIGNED AS UNINHABITABLE.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	E4	HIP	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:37 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-v\_nQ?HXK48YQbCfA2BgZrRBzX\_x4WLA9?EuByEzIXqO



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.25	Vert(LL)	-0.09 7-9	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.35	Vert(CT)	-0.14 7-9	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.27	Horz(CT)	0.02 6	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.02 2-9	>999	240		
								Weight: 167 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 3-5.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 6=947/0-3-8 (min. 0-1-8), 2=1022/0-3-8 (min. 0-1-8)  
 Max Horz 2=159(LC 9)  
 Max Uplift 6=-22(LC 13), 2=-39(LC 12)  
 Max Grav 6=1019(LC 2), 2=1082(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-10=-1340/237, 10-11=-1234/256, 3-11=-1224/287, 3-12=-905/329, 4-12=-906/329,  
 4-13=-909/326, 5-13=-907/326, 5-14=-1194/292, 14-15=-1228/263, 6-15=-1340/243  
 BOT CHORD 2-16=-71/929, 9-16=-71/929, 9-17=-117/998, 17-18=-117/998, 8-18=-117/998,  
 7-8=-117/998, 7-19=-65/920, 6-19=-65/920  
 WEBS 3-9=0/543, 4-9=-257/141, 4-7=-254/142, 5-7=0/540

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-3, Interior(1) 3-4-3 to 7-2-6, Exterior(2) 7-2-6 to 13-5-1, Interior(1) 13-5-1 to 16-9-10, Exterior(2) 16-9-10 to 23-0-4, Interior(1) 23-0-4 to 23-10-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 2.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.


**LOAD CASE(S)** Standard



Job J0223-0563	Truss E5GR	Truss Type Hip Girder	Qty 1	Ply 2	VILLEGAS/CARDILLO 14122023
-------------------	---------------	--------------------------	----------	----------	----------------------------

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:38 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-NAKoCdYyrSgHDMENcuBoOejAaNgcFqDIEudkVgzIXqN



Scale = 1:42.6




Plate Offsets (X,Y)-- [6:0-1-13,Edge]					
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL 1.15	TC 0.11	Vert(LL) -0.04 9-10 >999 360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.33	Vert(CT) -0.08 9-10 >999 240		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.16	Horz(CT) 0.02 6 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.05 7-9 >999 240		Weight: 334 lb FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 3-5.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	

**REACTIONS.** (lb/size) 6=2228/0-3-8 (min. 0-1-8), 2=2303/0-3-8 (min. 0-1-8)  
Max Horz 2=125(LC 7)  
Max Uplift 6=525(LC 4), 2=530(LC 5)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-3119/807, 3-4=-3212/901, 4-5=-3212/901, 5-6=-3102/806  
BOT CHORD 2-11=-644/2244, 10-11=-644/2244, 10-12=-637/2215, 12-13=-637/2215, 13-14=-637/2215,  
9-14=-637/2215, 9-15=-557/2221, 8-15=-557/2221, 8-16=-557/2221, 7-16=-557/2221,  
7-17=-564/2250, 6-17=-564/2250  
WEBS 3-10=-246/947, 3-9=-436/1290, 4-9=-460/160, 5-9=-436/1286, 5-7=-243/950

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 6=525, 2=530.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 380 lb down and 129 lb up at 4-0-0, 258 lb down and 117 lb up at 6-0-0, 258 lb down and 117 lb up at 8-0-0, 258 lb down and 117 lb up at 10-0-0, 258 lb down and 117 lb up at 12-0-0, 258 lb down and 117 lb up at 14-0-0, 258 lb down and 117 lb up at 16-0-0, and 258 lb down and 117 lb up at 18-0-0, and 380 lb down and 129 lb up at 20-0-0 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

**LOAD CASE(S)** Standard

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	E5GR	Hip Girder	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:38 2023 Page 2  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-NAKoCdYyrSgHDMENcuBoOejAaNGcFqDIEudkVgzIXqN

**LOAD CASE(S)** Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-3=-60, 3-5=-60, 5-6=-60, 2-6=-20


Concentrated Loads (lb)

Vert: 8=-258(B) 9=-258(B) 11=-380(B) 12=-258(B) 13=-258(B) 14=-258(B) 15=-258(B) 16=-258(B) 17=-380(B)

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	F1	COMMON	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:39 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-rMuAQzYaclo8qVpZ9ci1xsGHMncp\_lzRTYNH16zIXqM



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.36	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.33	Vert(LL) -0.04 2-6 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.13	Vert(CT) -0.08 2-6 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.01 4 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.03 2-6 >999 240		
				Weight: 107 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD  
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=766/0-3-8 (min. 0-1-8), 4=766/0-3-8 (min. 0-1-8)  
 Max Horz 2=158(LC 11)  
 Max Uplift 2=53(LC 12), 4=53(LC 13)  
 Max Grav 2=853(LC 19), 4=849(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-8=-1013/150, 8-9=-903/156, 3-9=-892/187, 3-10=-892/187, 10-11=-903/156,  
 4-11=-1013/150  
 BOT CHORD 2-7=0/771, 6-7=0/771, 6-12=0/771, 4-12=0/771  
 WEBS 3-6=0/560


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-9 to 3-4-4, Interior(1) 3-4-4 to 8-10-0, Exterior(2) 8-10-0 to 13-2-13, Interior(1) 13-2-13 to 18-8-9 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	F2	Common	2	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:39 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-rMuAQzYaclo8qVpZ9ci1xsGGpnco\_lzRTYNH16zIXqM



Scale = 1:39.6

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.40	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.33	Vert(LL) -0.04 1-5 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.13	Vert(CT) -0.08 1-5 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.01 3 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.03 3-5 >999 240		
				Weight: 104 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=696/Mechanical, 3=772/0-3-8 (min. 0-1-8)  
 Max Horz 1=-153(LC 8)  
 Max Uplift1=-37(LC 12), 3=-54(LC 13)  
 Max Grav 1=787(LC 19), 3=854(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-7=-994/159, 2-7=-895/192, 2-8=-903/188, 8-9=-916/158, 3-9=-1024/151  
 BOT CHORD 1-6=0/781, 5-6=0/781, 5-10=0/781, 3-10=0/781  
 WEBS 2-5=0/562

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-0-12 to 4-5-9, Interior(1) 4-5-9 to 8-10-0, Exterior(2) 8-10-0 to 13-2-13, Interior(1) 13-2-13 to 18-8-9 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Refer to girder(s) for truss to truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	F3GR	Hip Girder	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:40 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-JZSZdJZCN3w?SfOljJdGT3pW2B?BjmRbiC6rZYzlXqL

Scale = 1:35.7




Plate Offsets (X,Y)--	[4:0-5-4,0-2-12]				
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL 1.15	TC 0.11	Vert(LL) -0.01 2-10 >999 360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.13	Vert(CT) -0.02 2-10 >999 240		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.05	Horz(CT) 0.01 7 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.01 10 >999 240		
				Weight: 253 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1  
WEBS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 4-5.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 2=1147/0-3-8 (min. 0-1-8), 7=1147/0-3-8 (min. 0-1-8)  
Max Horz 2=-118(LC 25)  
Max Uplift 2=-231(LC 8), 7=-231(LC 9)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-12=-1549/377, 3-12=-1445/369, 3-13=-1359/349, 4-13=-1239/347, 4-14=-1092/320, 14-15=-1092/320, 5-15=-1092/320, 5-16=-1240/346, 6-16=-1361/348, 6-17=-1446/369, 7-17=-1550/377  
BOT CHORD 2-18=-326/1213, 18-19=-326/1213, 11-19=-326/1213, 10-11=-326/1213, 10-20=-274/1090, 20-21=-274/1090, 9-21=-274/1090, 9-22=-257/1214, 22-23=-257/1214, 7-23=-257/1214  
WEBS 4-10=0/427, 5-9=0/427

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=231, 7=231.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 102 lb down and 83 lb up at 2-4-12, 99 lb down and 81 lb up at 4-4-12, 124 lb down and 124 lb up at 6-4-0, 128 lb down and 120 lb up at 8-4-12, 128 lb down and 120 lb up at 9-3-4, 124 lb down and 124 lb up at 11-4-0, and 99 lb down and 81 lb up at 13-3-4, and 102 lb down and 83 lb up at 15-3-4 on top chord, and 51 lb down at 2-4-12, 47 lb down at 4-4-12, 52 lb down at 6-4-12, 52 lb down at 8-4-12, 52 lb down at 9-3-4, 52 lb down at 11-3-4, and 47 lb down at 13-3-4, and 51 lb down at 15-3-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	F3GR	Hip Girder	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:40 2023 Page 2  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-JZSZdJZCN3w?SfOljJDGT3pW2B?BjmRbiC6rZYzIXqL

**LOAD CASE(S)** Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-4=-60, 4-5=-60, 5-8=-60, 2-7=-20


Concentrated Loads (lb)

Vert: 4=-68(B) 5=-68(B) 10=-26(B) 9=-26(B) 12=-62(B) 13=-59(B) 14=-68(B) 15=-68(B) 16=-59(B) 17=-62(B) 18=-35(B) 19=-35(B) 20=-26(B) 21=-26(B) 22=-35(B) 23=-35(B)

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	G1	Roof Special	3	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:41 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-nlOxrfaq8N2s4pzxH1kV0HLfubJ3S0hkwsO6?zlxQk



Scale: 3/16"=1'

Plate Offsets (X,Y)-- [2:0-8-8,0-0-0], [8:0-8-8,0-0-0], [11:0-1-0,0-2-8], [13:0-5-12,0-3-8], [14:0-5-12,0-3-8], [16:0-1-0,0-2-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.23	Vert(LL)	-0.13	13-14	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.28	Vert(CT)	-0.30	13-14	>826		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.88	Horz(CT)	0.36	19	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.25	13-14	>990		
	Code IRC2015/TPI2014						Weight: 181 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2 \*Except\*  
 W1: 2x4 SP No.1  
 OTHERS 2x6 SP No.1

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-7-3 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:  
 7-3-15 oc bracing: 14-15,12-13.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 18=888/0-3-8 (min. 0-1-8), 19=888/0-3-8 (min. 0-1-8)  
 Max Horz 18=229(LC 11)  
 Max Uplift 18=-99(LC 9), 19=-99(LC 8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-16=-270/142, 2-3=-1808/1587, 3-20=-2674/1780, 4-20=-2583/1784, 4-5=-2589/1869,  
 5-6=-2589/1899, 6-21=-2583/1788, 7-21=-2674/1784, 7-8=-1808/1551  
 BOT CHORD 15-16=-325/511, 14-15=-1146/1741, 13-14=-21/857, 12-13=-1143/1741, 11-12=-287/394  
 WEBS 5-13=-1438/1851, 5-14=-1383/1851, 2-15=-789/1051, 3-15=-573/196, 3-14=-52/675,  
 8-12=-819/1051, 7-12=-592/209, 7-13=-86/675, 2-18=-934/906, 8-19=-934/907


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-4, Interior(1) 3-4-4 to 10-5-0, Exterior(2) 10-5-0 to 14-9-13, Interior(1) 14-9-13 to 21-10-10 zone; end vertical left and right exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Bearing at joint(s) 18, 19 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 18, 19.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	G1GE	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:41 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-nlOxrfaq8N2s4pzxH1kV0HLfubJ3S0hkwsO6?zIXqK



Scale = 1:65.0

Plate Offsets (X,Y)-- [2:0-8-8,0-0-0], [8:0-8-8,0-0-0], [11:0-1-0,0-2-8], [13:0-5-12,0-3-8], [14:0-5-12,0-3-8], [16:0-1-0,0-2-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.23	Vert(LL)	-0.13	13-14	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.28	Vert(CT)	-0.30	13-14	>826		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.88	Horz(CT)	0.36	26	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.25	13-14	>990		
	Code IRC2015/TPI2014						Weight: 196 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2 \*Except\*  
 W1: 2x4 SP No.1  
 OTHERS 2x4 SP No.2 \*Except\*  
 BL1: 2x6 SP No.1

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-7-3 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 7-3-15 oc bracing: 14-15,12-13.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 25=888/0-3-8 (min. 0-1-8), 26=888/0-3-8 (min. 0-1-8)  
 Max Horz 25=229(LC 11)  
 Max Uplift 25=-99(LC 9), 26=-99(LC 8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-16=-270/142, 2-3=-1808/1587, 3-27=-2674/1780, 4-27=-2583/1784, 4-5=-2589/1869,  
 5-6=-2589/1899, 6-28=-2583/1788, 7-28=-2674/1784, 7-8=-1808/1551  
 BOT CHORD 15-16=-325/511, 14-15=-1146/1741, 13-14=-21/857, 12-13=-1143/1741, 11-12=-287/394  
 WEBS 5-13=-1438/1851, 5-14=-1383/1851, 2-15=-789/1051, 3-15=-573/196, 3-14=-52/675,  
 8-12=-819/1051, 7-12=-592/209, 7-13=-86/675, 2-25=-934/906, 8-26=-934/907

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-4, Interior(1) 3-4-4 to 10-5-0, Exterior(2) 10-5-0 to 14-9-13, Interior(1) 14-9-13 to 21-10-10 zone; end vertical left and right exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Bearing at joint(s) 25, 26 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 25, 26.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard






Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	G2GR	ROOF SPECIAL	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:42 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-FxaJ2?bSvGajizY8rkFkYUuqe?ajBWcu9WbyeRzlXqJ



Scale: 3/16"=1'




Plate Offsets (X,Y)-- [13:0-5-0,0-6-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.23	Vert(LL)	-0.06 12-13	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.60	Vert(CT)	-0.12 12-13	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.64	Horz(CT)	0.01 8	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-S	Wind(LL)	0.04 12-13	>999	240		
	Code IRC2015/TPI2014						Weight: 433 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x6 SP No.1 *Except* B1: 2x8 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. Except: 6-0-0 oc bracing: 10-12
WEBS 2x4 SP No.2 *Except* W9,W1: 2x6 SP No.1	

**REACTIONS.** (lb/size) 14=3849/0-3-8 (min. 0-2-4), 12=4118/0-3-8 (min. 0-2-7), 8=338/0-3-8 (min. 0-1-8)  
 Max Horz 14=221(LC 5)  
 Max Uplift 14=-262(LC 9), 12=-149(LC 8), 8=-117(LC 9)  
 Max Grav 14=3853(LC 19), 12=4118(LC 1), 8=367(LC 34)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-3066/283, 3-4=-2983/397, 4-5=-292/311, 5-6=-323/220, 6-7=-714/262, 7-8=-362/143,  
 2-14=-2619/219  
 BOT CHORD 14-15=-253/634, 15-16=-253/634, 13-16=-253/634, 13-17=-48/412, 17-18=-48/412,  
 18-19=-48/412, 12-19=-48/412, 10-12=-542/163, 5-10=-251/124, 9-10=-201/633  
 WEBS 3-13=-372/306, 6-10=-420/216, 7-9=-133/461, 2-13=-130/1741, 4-12=-1825/192,  
 4-13=-385/4024

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
 Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
 Bottom chords connected as follows: 2x8 - 2 rows staggered at 0-7-0 oc, 2x6 - 2 rows staggered at 0-9-0 oc.  
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Bearing at joint(s) 8 considers parallel to grain value using ANS/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 14=262, 12=149, 8=117.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANS/TPI 1.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1437 lb down and 86 lb up at 1-7-4, 1035 lb down and 63 lb up at 3-7-4, 1035 lb down and 63 lb up at 5-7-4, 1035 lb down and 63 lb up at 7-7-4, and 1035 lb down and 63 lb up at 9-7-4, and 1035 lb down and 63 lb up at 11-7-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	G2GR	ROOF SPECIAL	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:42 2023 Page 2  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-FxaJ2?bSvgAjizY8rkFkYUuqe?aJBWcu9WbyeRzlXqJ

**NOTES-**

11) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

**LOAD CASE(S)** Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-2=-60, 2-4=-60, 4-7=-60, 12-14=-20, 11-12=-20, 8-10=-20


Concentrated Loads (lb)

Vert: 13=-1035(B) 15=-1437(B) 16=-1035(B) 17=-1035(B) 18=-1035(B) 19=-1035(B)

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	G3GE	Common Supported Gable	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:43 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-j88hFLc4g\_laJ77KOSnz5iQ0XO1Xw6x1OALVAtzIXJ



Scale = 1:64.8

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.16	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.15	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.13	Horz(CT)	-0.00	8	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-R						
								Weight: 138 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1  
WEBS 2x6 SP No.1  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
WEBS T-Brace: 2x4 SPF No.2 - 7-8, 6-9, 5-10  
Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.  
Brace must cover 90% of web length.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 12-5-0.  
(lb) - Max Horz 14=233(LC 12)  
Max Uplift All uplift 100 lb or less at joint(s) 8, 10, 11 except 14=-219(LC 10), 13=-391(LC 12)  
Max Grav All reactions 250 lb or less at joint(s) 8, 9, 10, 11, 12 except 14=435(LC 12), 13=332(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-14=-347/258, 1-2=-449/374  
WEBS 2-13=-320/316

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Corner(3) 0-2-12 to 4-7-9, Exterior(2) 4-7-9 to 10-1-8, Corner(3) 10-1-8 to 12-2-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8, 10, 11 except (jt=lb) 14=219, 13=391.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.


**LOAD CASE(S)** Standard



Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	H1GE	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:44 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-CKi3ThcjRIQRxHiWY9ICevz8zoJkfYzBdq42IKzIXqH



Scale = 1:46.5

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.37	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.35	Vert(LL) -0.04 1-4 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.14	Vert(CT) -0.08 1-4 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.01 3 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.04 1-4 >999 240		
				Weight: 134 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=678/0-3-8 (min. 0-1-8), 3=678/0-3-8 (min. 0-1-8)  
 Max Horz 1=-216(LC 8)  
 Max Uplift 1=-120(LC 12), 3=-120(LC 13)  
 Max Grav 1=791(LC 19), 3=791(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-20=-936/150, 20-21=-831/153, 2-21=-821/187, 2-22=-820/187, 22-23=-831/152,  
 3-23=-936/150  
 BOT CHORD 1-18=-29/677, 5-18=-29/677, 4-5=-29/677, 4-19=-29/677, 3-19=-29/677  
 WEBS 2-4=0/625


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) 0-1-12 to 4-6-9, Interior(1) 4-6-9 to 8-7-8, Exterior(2) 8-7-8 to 13-0-5, Interior(1) 13-0-5 to 17-1-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCCL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=120, 3=120.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	M1	MONO TRUSS	2	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:44 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-CKi3ThcjRIQRxHiWY9lCevz8loKwFVbBdq42IKzIXqH



Scale = 1:58.8

Plate Offsets (X,Y)-- [2:0-5-8,0-2-0], [4:0-6-8,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.35	Vert(LL)	-0.07	7-8	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.27	Vert(CT)	-0.13	7-8	>913	240	M18AHS	186/179
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.36	Horz(CT)	0.14	10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.01	6	>999	240		
									Weight: 106 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2 \*Except\*  
 W1: 2x6 SP No.1  
 OTHERS 2x6 SP No.1

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 9-3-9 oc bracing.  
 WEBS T-Brace: 2x4 SPF No.2 - 2-7  
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.  
 Brace must cover 90% of web length.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 8=461/0-3-8 (min. 0-1-8), 10=515/0-3-8 (min. 0-1-8)  
 Max Horz 8=334(LC 12)  
 Max Uplift 10=-265(LC 12)  
 Max Grav 8=461(LC 1), 10=568(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-11=-384/157, 3-11=-349/179, 3-4=-340/236, 2-8=-370/0  
 BOT CHORD 7-8=-678/794  
 WEBS 2-7=-733/651, 4-10=-724/557

**NOTES-**


- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-3, Interior(1) 3-4-3 to 12-0-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) All plates are MT20 plates unless otherwise indicated.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Bearing at joint(s) 10 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 10=265.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	M1GR	Roof Special Girder	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:45 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-gWGSg0dLCbYIZQGjWtpRA7WM1CiZO12KrUqcFmzIXqG



Scale = 1:23.6

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.16	Vert(LL) 0.01 7-8 >999 240	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.18	Vert(CT) -0.01 7-8 >999 240		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.02	Horz(CT) -0.00 7 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S			Weight: 152 lb FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1  
WEBS 2x6 SP No.1 \*Except\*  
W2,W3: 2x4 SP No.2

**BRACING-**  
TOP CHORD 2-0-0 oc purlins (6-0-0 max.): 1-5, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. Except:  
10-0-0 oc bracing: 8-10

**REACTIONS.** (lb/size) 11=779/Mechanical, 7=601/Mechanical, 10=1260/0-3-8 (min. 0-1-8)  
Max Uplift 11=-302(LC 4), 7=-261(LC 5), 10=-496(LC 5)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-11=-724/330  
BOT CHORD 8-10=-265/570, 3-10=-722/300

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Refer to girder(s) for truss to truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 11=302, 7=261, 10=496.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 475 lb down and 233 lb up at 1-1-12, and 474 lb down and 232 lb up at 3-1-12 on top chord, and 495 lb down and 285 lb up at 5-1-12, and 495 lb down and 285 lb up at 7-1-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

**LOAD CASE(S)** Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-2=-60, 2-4=-60, 4-5=-60, 10-12=-20, 8-9=-20, 6-8=-20  
Concentrated Loads (lb)  
Vert: 13=-458 14=-458 15=-495 16=-495



Job J0223-0563	Truss M2	Truss Type MONO TRUSS	Qty 2	Ply 1	VILLEGAS/CARDILLO 14122023
Comtech, Inc., Fayetteville, NC 28309, Robert Lewis					Job Reference (optional)

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:45 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-gWGSg0dLCbYIZQGjWtpRA7WK0Cg0OzKKrUqcFmzIXqG




Plate Offsets (X,Y)-- [2:0-6-0,0-0-12], [5:0-6-8,Edge]							
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc)	l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.29	Vert(LL) -0.07	2-8 >999 360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.28	Vert(CT) -0.14	2-8 >833 240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.26	Horz(CT) -0.03	10 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL) -0.01	2-8 >999 240		
						Weight: 97 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	
OTHERS 2x6 SP No.1	
	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=459/0-3-8 (min. 0-1-8), 10=518/0-3-8 (min. 0-1-8)  
 Max Horz 2=337(LC 12)  
 Max Uplift 10=-231(LC 12)  
 Max Grav 2=459(LC 1), 10=561(LC 19)


**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-11=-342/30, 3-11=-302/69, 3-4=-301/97, 4-5=-270/149, 8-9=-107/389, 5-9=-107/389  
 BOT CHORD 2-8=-170/322  
 WEBS 3-8=-398/223, 5-10=-684/499

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-3, Interior(1) 3-4-3 to 12-0-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Bearing at joint(s) 10 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 10=231.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job J0223-0563	Truss PB1	Truss Type Piggyback	Qty 2	Ply 1	VILLEGAS/CARDILLO 14122023
Comtech, Inc., Fayetteville, NC 28309, Robert Lewis					Job Reference (optional)

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:46 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-8jppuMezzvg9Aarv4aKgJk2Xtc3r7UIT48Z9nCzIXqf



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.18	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.11	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 4 n/a n/a		
	Code IRC2015/TPI2014			Weight: 32 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 9-4-15.  
 (lb) - Max Horz 1=-71(LC 8)  
 Max Uplift All uplift 100 lb or less at joint(s) except 1=-240(LC 19), 5=-210(LC 20), 2=-183(LC 12), 4=-170(LC 13)  
 Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 2=460(LC 19), 4=441(LC 20), 6=253(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - Gable requires continuous bottom chord bearing.
  - Gable studs spaced at 4-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 240 lb uplift at joint 1, 210 lb uplift at joint 5, 183 lb uplift at joint 2 and 170 lb uplift at joint 4.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	PB2	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:46 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-8jpuMezzvg9Aarv4aKgjK2Zlc4H7UPT48Z9nCzIXqf



Scale = 1:17.8

Plate Offsets (X,Y)-- [4:0-2-0,Edge], [6:0-2-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.03	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.02	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Horz(CT)	0.00	8	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S						
	Code IRC2015/TPI2014						Weight: 33 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 4-6.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 9-4-15.  
 (lb) - Max Horz 1=44(LC 9)  
 Max Uplift All uplift 100 lb or less at joint(s) 1, 9, 2, 8, 11, 12, 10  
 Max Grav All reactions 250 lb or less at joint(s) 1, 9, 2, 8, 11, 12, 10

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - 4) Provide adequate drainage to prevent water ponding.
  - 5) Gable requires continuous bottom chord bearing.
  - 6) Gable studs spaced at 2-0-0 oc.
  - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 8) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 9, 2, 8, 11, 12, 10.
  - 10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 11) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
  - 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	PB3	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:47 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-cvNC5ifbDp0okQ5dHrvFYbkQQWsxbdJoJjJeziXqE



Scale = 1:17.8




Plate Offsets (X,Y)-- [3:0-2-0,Edge], [7:0-2-0,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.03	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.02	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.02	Horz(CT)	0.00	9	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S					Weight: 30 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 3-7.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 9-4-15.  
(lb) - Max Horz 1=29(LC 9)  
Max Uplift All uplift 100 lb or less at joint(s) 1, 9, 2, 8, 11, 12, 10  
Max Grav All reactions 250 lb or less at joint(s) 1, 9, 2, 8, 11, 12, 10

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - Provide adequate drainage to prevent water ponding.
  - Gable requires continuous bottom chord bearing.
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 9, 2, 8, 11, 12, 10.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	PB4	GABLE	11	1	Job Reference (optional)


Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:48 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-45xaJ2fDUWxsQu?IB?M8oI8v4PmfbO0mXS2Gr5zIXqD



4x4 =

Scale = 1:13.6



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.04	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.03	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.01	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 4 n/a n/a		
	Code IRC2015/TPI2014			Weight: 17 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 5-4-15 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 5-4-15.  
 (lb) - Max Horz 1=-39(LC 8)  
 Max Uplift All uplift 100 lb or less at joint(s) 1, 5, 2, 4  
 Max Grav All reactions 250 lb or less at joint(s) 1, 5, 2, 4, 6

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - Gable requires continuous bottom chord bearing.
  - Gable studs spaced at 4-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5, 2, 4.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	Q01	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:48 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-45xaJ2fDUWxsQu?lB?M8ol8uPPmpbOLmXS2Gr5zIXqD



Scale = 1:32.7

Plate Offsets (X,Y)-- [6:0-2-14,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.08	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.02	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.05	Horz(CT)	0.00	5	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P					Weight: 24 lb	FT = 20%
	Code IRC2015/TPI2014							

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 WEBS 2x4 SP No.2  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 2-11-5 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 2-11-5.  
 (lb) - Max Horz 1=-136(LC 13)  
 Max Uplift All uplift 100 lb or less at joint(s) 7, 4 except 1=-120(LC 11), 5=-144(LC 13)  
 Max Grav All reactions 250 lb or less at joint(s) 7, 1, 4, 6, 5

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-350/459, 2-3=-223/285  
 WEBS 3-5=-270/297


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Gable requires continuous bottom chord bearing.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Bearing at joint(s) 1, 4, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 4 except (jt=lb) 1=120, 5=144.
  - 7) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 4, 5.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	Q02	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:48 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-45xaJ2fDUWxsQu?IB?M8ol8u0PmXbLpmXS2Gr5zIXqD



4x4 =

Scale: 1/8"=1'




Plate Offsets (X,Y)-- [5:0-2-8,0-3-0], [12:Edge,0-1-8], [16:0-3-0,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.11	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.04	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.21	Horz(CT)	0.01	12	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S						
	Code IRC2015/TPI2014						Weight: 213 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 OTHERS 2x4 SP No.2 \*Except\*  
 ST7,ST6,ST8: 2x4 SP No.1

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS T-Brace: 2x4 SPF No.2 - 7-18, 6-20, 5-21, 9-15  
 2x6 SPF No.2 - 8-17  
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.  
 Brace must cover 90% of web length.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.**

All bearings 22-11-10.  
 (lb) - Max Horz 1=358(LC 9)  
 Max Uplift All uplift 100 lb or less at joint(s) 18, 20, 21, 22, 23, 15, 14, 13 except  
 12=-149(LC 11), 1=-142(LC 10), 16=-130(LC 13), 24=-118(LC 12)  
 Max Grav All reactions 250 lb or less at joint(s) 16, 17, 18, 20, 21, 22, 23, 15, 14,  
 13 except 12=257(LC 8), 1=331(LC 12), 24=251(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-527/465, 2-3=-376/319, 3-4=-263/220  
 WEBS 8-17=-265/196


**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-2 to 4-10-13, Interior(1) 4-10-13 to 14-10-13, Exterior(2) 14-10-13 to 19-3-10, Interior(1) 19-3-10 to 22-9-3 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 12, 15, 14, 13 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 18, 20, 21, 22, 23, 15, 14, 13 except (jt=lb) 12=149, 1=142, 16=130, 24=118.
- Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 12, 15, 14, 13.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

**LOAD CASE(S)** Standard

Job J0223-0563	Truss Q03	Truss Type GABLE	Qty 1	Ply 1	VILLEGAS/CARDILLO 14122023
Comtech, Inc., Fayetteville, NC 28309, Robert Lewis					Job Reference (optional)

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:49 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-YHVyWQgrFq3j12aUliuNKzg2Sp6yKqQwm6opOXzIXqC



Scale = 1:52.1

Plate Offsets (X,Y)-- [7:Edge,0-1-8], [10:0-3-0,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.02	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.13	Horz(CT)	0.00	7	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						
								Weight: 72 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 11-3-14.  
 (lb) - Max Horz 1=198(LC 12)  
 Max Uplift All uplift 100 lb or less at joint(s) 1, 7, 10, 13, 12, 11, 8  
 Max Grav All reactions 250 lb or less at joint(s) 1, 7, 10, 13, 12, 11, 9, 8

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-321/267

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-2 to 4-8-15, Interior(1) 4-8-15 to 8-1-1, Exterior(2) 8-1-1 to 11-1-7 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Bearing at joint(s) 7, 9, 8 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7, 10, 13, 12, 11, 8.
  - Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 7, 9, 8.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


**LOAD CASE(S)** Standard



Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	Q04	GABLE	1	1	Job Reference (optional)


Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:50 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-0U3LkKhT08BafC9gJQPctADDcDRg3Gj3?mXNwzzlXqB



4x4 =

Scale = 1:58.4



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.10	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.06	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.19	Horz(CT)	0.00	7	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						
								Weight: 93 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
WEBS T-Brace: 2x4 SPF No.2 - 4-10  
Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.  
Brace must cover 90% of web length.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 12-10-11.  
(lb) - Max Horz 1=-248(LC 8)  
Max Uplift All uplift 100 lb or less at joint(s) except 1=-142(LC 10), 7=-116(LC 11), 11=-159(LC 12), 12=-197(LC 12), 9=-158(LC 13), 8=-198(LC 13)  
Max Grav All reactions 250 lb or less at joint(s) 1, 7, 10, 11, 9 except 12=270(LC 19), 8=271(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-13=-392/285, 2-13=-372/305, 6-14=-372/305, 7-14=-391/285  
BOT CHORD 1-12=-214/273, 11-12=-214/273, 10-11=-214/273, 9-10=-214/273, 8-9=-214/273, 7-8=-214/273  
WEBS 3-11=-286/291, 2-12=-340/343, 5-9=-286/291, 6-8=-340/343


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-3-4 to 4-5-5, Interior(1) 4-5-5 to 6-5-5, Exterior(2) 6-5-5 to 10-10-2, Interior(1) 10-10-2 to 12-7-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 142 lb uplift at joint 1, 116 lb uplift at joint 7, 159 lb uplift at joint 11, 197 lb uplift at joint 12, 158 lb uplift at joint 9 and 198 lb uplift at joint 8.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

**LOAD CASE(S)** Standard

Job J0223-0563	Truss V01	Truss Type Valley	Qty 1	Ply 1	VILLEGAS/CARDILLO 14122023
-------------------	--------------	----------------------	----------	----------	----------------------------


Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:50 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-0U3LkKhT08BafC9gJQPctADChDPA3G53?mXNwzIqB



4x4 =

Scale = 1:53.9



<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL 1.15	TC 0.16	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.15	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.16	Horz(CT) 0.00 6 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S		Weight: 77 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
WEBS 2x4 SP No.2  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
WEBS T-Brace: 2x4 SPF No.2 - 4-7  
Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.  
Brace must cover 90% of web length.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 13-6-7.  
(lb) - Max Horz 1=227(LC 12)  
Max Uplift All uplift 100 lb or less at joint(s) 1, 6 except 8=-141(LC 12), 9=-105(LC 12)  
Max Grav All reactions 250 lb or less at joint(s) 1, 6 except 7=462(LC 19), 8=481(LC 19), 9=285(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-2=-291/287  
WEBS 3-8=-366/266, 2-9=-282/220


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 4-9-10, Interior(1) 4-9-10 to 10-6-14, Exterior(2) 10-6-14 to 13-5-2 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 6 except (j=lb) 8=141, 9=105.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	V02	Valley	1	1	Job Reference (optional)


Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:50 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-0U3LkxhT08BafC9gJQPctADBvDPE3G03?mXNwzzlXqB



4x4 =

Scale = 1:46.0



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.21	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.15	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.17	Horz(CT)	0.00	5	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S					Weight: 63 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
WEBS 2x4 SP No.2  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 11-11-3.  
(lb) - Max Horz 1=184(LC 12)  
Max Uplift All uplift 100 lb or less at joint(s) 1, 5 except 7=-165(LC 12)  
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 6=440(LC 19), 7=546(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
WEBS 2-7=-423/302


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 4-11-11, Interior(1) 4-11-11 to 8-11-11, Exterior(2) 8-11-11 to 11-9-15 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Gable requires continuous bottom chord bearing.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 7=165.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	V03	Valley	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:51 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-Ugdjx4i6nRJRHLkss7wrQOmNidlmok3DEQHwSQzIXqA



Scale = 1:38.1

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.14	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.13	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.12	Horz(CT)	0.00	5	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S					Weight: 51 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
WEBS 2x4 SP No.2  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 10-4-0.  
(lb) - Max Horz 1=140(LC 12)  
Max Uplift All uplift 100 lb or less at joint(s) 1, 5 except 7=-134(LC 12)  
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 6=440(LC 19), 7=396(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
WEBS 2-7=-349/264


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 4-9-10, Interior(1) 4-9-10 to 7-4-7, Exterior(2) 7-4-7 to 10-2-11 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Gable requires continuous bottom chord bearing.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 7=134.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	V04	Valley	1	1	Job Reference (optional)


Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:51 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-Ugdjx4i6nRJRHkss7wrQOmNTdmeokuDEQHwSQzIXqA



4x4 =

Scale = 1:31.1



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.16	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.07	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.07	Horz(CT)	0.00		n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P					Weight: 40 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
WEBS 2x4 SP No.2  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 8-8-13.  
(lb) - Max Horz 1=105(LC 9)  
Max Uplift All uplift 100 lb or less at joint(s) 1, 5 except 7=-140(LC 12)  
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 6=271(LC 19), 7=356(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
WEBS 2-7=-360/291

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 4-9-10, Interior(1) 4-9-10 to 5-9-4, Exterior(2) 5-9-4 to 8-7-8 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Gable requires continuous bottom chord bearing.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 7=140.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	V05	Valley	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:52 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-zsB58QikYIRIuVJ3QrR4ybIYR06kXCXMS40T\_szlXq9




Plate Offsets (X,Y)-- [3:0-2-0,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.15	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.08	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.04	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 30 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 WEBS 2x4 SP No.2  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-4.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=132/7-1-10 (min. 0-1-8), 5=89/7-1-10 (min. 0-1-8), 6=308/7-1-10 (min. 0-1-8)  
 Max Horz 1=83(LC 12)  
 Max Uplift 5=15(LC 13), 6=44(LC 12)  
 Max Grav 1=133(LC 23), 5=98(LC 24), 6=309(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 5-2-6, Interior(1) 5-2-6 to 7-0-5 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) Gable requires continuous bottom chord bearing.
  - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 6) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 6.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	V06	Valley	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:52 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-zsB58QikYIRIuVJ3QrR4yblZz07XCiMS40T\_szlXq9




Plate Offsets (X,Y)-- [2:0-2-13,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.11	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.05	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00		n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P					Weight: 23 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
WEBS 2x4 SP No.2  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 5-6-14 oc purlins, except end verticals, and 2-0-0 oc purlins: 2-3.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=104/5-6-7 (min. 0-1-8), 4=84/5-6-7 (min. 0-1-8), 5=214/5-6-7 (min. 0-1-8)  
Max Horz 1=72(LC 12)  
Max Uplift 4=-14(LC 8), 5=-29(LC 12)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 5.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard

Job J0223-0563	Truss V07	Truss Type Valley	Qty 1	Ply 1	VILLEGAS/CARDILLO 14122023
-------------------	--------------	----------------------	----------	----------	----------------------------

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:53 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-R3kTMlJMJ3Z9WfuF\_YyJVprkQTaGe4Vhkm1XlzlXq8



Scale = 1:15.7

Plate Offsets (X,Y)-- [2:0-2-13,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.11	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.04	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.02	Horz(CT)	0.00		n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						Weight: 18 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 WEBS 2x4 SP No.2  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 3-11-11 oc purlins, except end verticals, and 2-0-0 oc purlins: 2-3.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=104/3-11-11 (min. 0-1-8), 4=5/3-11-11 (min. 0-1-8), 5=165/3-11-11 (min. 0-1-8)  
 Max Horz 1=72(LC 12)  
 Max Uplift 4=-25(LC 3), 5=-22(LC 12)  
 Max Grav 1=104(LC 1), 4=5(LC 1), 5=169(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) Gable requires continuous bottom chord bearing.
  - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 6) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 5.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.


**LOAD CASE(S)** Standard




Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	V08	Valley	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:53 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-R3kTMljMJ3Z9WfuF\_YyJVprlhQtGePVhkm1XlzlXq8



Scale = 1:12.6



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.05	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.03	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00		n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P					Weight: 9 lb	FT = 20%
	Code IRC2015/TPI2014							

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 2-4-7 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=73/2-4-7 (min. 0-1-8), 3=73/2-4-7 (min. 0-1-8)  
 Max Horz 1=50(LC 12)  
 Max Uplift 3=-28(LC 12)  
 Max Grav 1=73(LC 1), 3=81(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Gable requires continuous bottom chord bearing.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	V09	Valley	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:54 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-vFirZ5k\_4Mh08pTRYGTY10OtcqoW?5efwOVA3kzIXq7



Scale = 1:20.8



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.23	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.13	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00		n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P						
	Code IRC2015/TPI2014						Weight: 19 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-4-7 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=153/4-4-0 (min. 0-1-8), 3=153/4-4-0 (min. 0-1-8)  
 Max Horz 1=104(LC 12)  
 Max Uplift 3=-60(LC 12)  
 Max Grav 1=153(LC 1), 3=169(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Gable requires continuous bottom chord bearing.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	V10	Valley	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:54 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-vFIrZ5k\_4Mh08pTRYGTY100v2qpu?5efwOVa3kzIXq7



Scale = 1:14.2



<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL 1.15	TC 0.07	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.04	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.00	Horz(CT) 0.00 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P		Weight: 11 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
WEBS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 2-9-4 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=89/2-8-13 (min. 0-1-8), 3=89/2-8-13 (min. 0-1-8)  
Max Horz 1=60(LC 12)  
Max Uplift 3=-35(LC 12)  
Max Grav 1=89(LC 1), 3=98(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Gable requires continuous bottom chord bearing.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


**LOAD CASE(S)** Standard



Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	V12	VALLEY	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:55 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-NRsEnRlrcgptlz1e5z\_naEw3bE7jkYuo82F8bBzlXq6



Scale = 1:17.9

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.15	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.13	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P					Weight: 18 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-7-7 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=133/4-6-14 (min. 0-1-8), 3=-293/4-6-14 (min. 0-1-8), 4=484/4-6-14 (min. 0-1-8)  
 Max Horz 1=90(LC 12)  
 Max Uplift 3=-321(LC 19), 4=-238(LC 12)  
 Max Grav 1=133(LC 1), 3=171(LC 12), 4=528(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-4=-583/466


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Gable requires continuous bottom chord bearing.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Bearing at joint(s) 3 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 3=321, 4=238.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	V13	VALLEY	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:55 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-NRrEnRlrcgptlz1e5z\_naEw3RE6UkTho82F8bBzIXq6



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.16	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.21	Vert(LL) 0.00 6 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.33	Vert(CT) 0.00 7 n/r 120		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 8 n/a n/a		
	Code IRC2015/TPI2014			Weight: 89 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 WEBS 2x4 SP No.2  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10'-0" oc bracing.  
 WEBS T-Brace: 2x4 SPF No.2 - 6-8  
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.  
 Brace must cover 90% of web length.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 16-3-1.  
 (lb) - Max Horz 1=342(LC 12)  
 Max Uplift All uplift 100 lb or less at joint(s) 8, 1, 11, 12 except 9=101(LC 12)  
 Max Grav All reactions 250 lb or less at joint(s) 8, 1 except 9=593(LC 19), 11=415(LC 19), 12=353(LC 19)


**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-459/444, 2-3=-340/280, 3-4=-327/320  
 WEBS 5-9=-325/211, 4-11=-284/159, 2-12=-304/200

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-5-15 to 4-10-12, Interior(1) 4-10-12 to 16-3-6 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Gable requires continuous bottom chord bearing.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8, 1, 11, 12 except (jt=lb) 9=101.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 7) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

**LOAD CASE(S)** Standard

Job J0223-0563	Truss V14	Truss Type VALLEY	Qty 1	Ply 1	VILLEGAS/CARDILLO 14122023
Comtech, Inc., Fayetteville, NC 28309, Robert Lewis					Job Reference (optional)

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:56 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-reQc\_nmEc\_xkN7cqfgW07RTD?eSuTzDyNi\_h7dzlXq5



Scale = 1:51.9

<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL 1.15	TC 0.24	Vert(LL) 0.00 4 n/r 120	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.20	Vert(CT) 0.00 5 n/r 120		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.19	Horz(CT) 0.00 6 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S		Weight: 70 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
WEBS 2x4 SP No.2  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
WEBS T-Brace: 2x4 SPF No.2 - 4-6  
Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.  
Brace must cover 90% of web length.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 13-9-1.  
(lb) - Max Horz 1=288(LC 12)  
Max Uplift All uplift 100 lb or less at joint(s) 6, 7 except 8=121(LC 12)  
Max Grav All reactions 250 lb or less at joint(s) 1, 6 except 7=554(LC 19), 8=498(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-9=-375/328, 2-9=-344/359  
WEBS 3-7=-301/204, 2-8=-374/241


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-5-15 to 4-10-12, Interior(1) 4-10-12 to 13-9-6 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Gable requires continuous bottom chord bearing.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 7 except (jt=lb) 8=121.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 7) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	V15	VALLEY	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:56 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-reQc\_nmEc\_xkN7cqfgW07RTEAeT5T\_RyNi\_h7dzlXq5



Scale = 1:42.6

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.16	Vert(LL)	0.00	4	n/r	120	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.18	Vert(CT)	0.00	5	n/r	120		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.11	Horz(CT)	0.00	6	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S							
									Weight: 54 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
WEBS 2x4 SP No.2  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 11-3-1.  
(lb) - Max Horz 1=234(LC 12)  
Max Uplift All uplift 100 lb or less at joint(s) 1, 6, 8 except 7=102(LC 12)  
Max Grav All reactions 250 lb or less at joint(s) 1, 6 except 7=497(LC 19), 8=282(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-2=-339/314  
WEBS 3-7=-337/230, 2-8=-261/190

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-5-15 to 4-10-12, Interior(1) 4-10-12 to 11-3-6 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Gable requires continuous bottom chord bearing.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 6, 8 except (jt=lb) 7=102.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


**LOAD CASE(S)** Standard



Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	V16	VALLEY	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:57 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-Jq\_C7msNH3b?GB0DO1F#0001oiCSa5cMkEg3zlXq4



Scale = 1:34.6

<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL 1.15	TC 0.20	Vert(LL) -0.00 3 n/r 120	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.16	Vert(CT) 0.00 4 n/r 120		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.05	Horz(CT) 0.00 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P		Weight: 39 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 WEBS 2x4 SP No.2  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=121/8-9-1 (min. 0-1-8), 5=126/8-9-1 (min. 0-1-8), 6=401/8-9-1 (min. 0-1-8)  
 Max Horz 1=179(LC 12)  
 Max Uplift 5=-42(LC 12), 6=-116(LC 12)  
 Max Grav 1=122(LC 21), 5=205(LC 19), 6=473(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-257/238  
 WEBS 2-6=-383/270


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-5-15 to 4-10-12, Interior(1) 4-10-12 to 8-9-6 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Gable requires continuous bottom chord bearing.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5 except (jt=lb) 6=116.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job J0223-0563	Truss V17	Truss Type VALLEY	Qty 1	Ply 1	VILLEGAS/CARDILLO 14122023
-------------------	--------------	----------------------	----------	----------	----------------------------

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:57 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-Jq\_\_C7msNH3b?GB0D01Fff0Py1pkCSI5cMkEg3zlXq4



Scale = 1:24.7

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.16	Vert(LL)	-0.00	3	n/r	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.09	Vert(CT)	0.00	4	n/r		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.04	Horz(CT)	0.00		n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P					Weight: 26 lb	FT = 20%
	Code IRC2015/TPI2014							

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
WEBS 2x4 SP No.2  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=-20/6-3-1 (min. 0-1-8), 5=135/6-3-1 (min. 0-1-8), 6=333/6-3-1 (min. 0-1-8)  
Max Horz 1=125(LC 12)  
Max Uplift 1=-52(LC 10), 5=-44(LC 12), 6=-96(LC 12)  
Max Grav 1=89(LC 12), 5=147(LC 19), 6=357(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
WEBS 2-6=-324/253


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-5-15 to 4-10-12, Interior(1) 4-10-12 to 6-3-6 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Gable requires continuous bottom chord bearing.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5, 6.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	W1GR	Half Hip Girder	2	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:58 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-n0YMPtnV8bBScQmDn5YUCsYXqR5vxxvJER0ToCWzIXq3



Scale = 1:25.4



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.34	Vert(LL) -0.04	2-8	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.35	Vert(CT) -0.08	2-8	>969		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.02	Horz(CT) 0.00	7	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL) 0.05	2-8	>999	Weight: 49 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-5.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 7=400/Mechanical, 2=523/0-3-8 (min. 0-1-8)  
 Max Horz 2=134(LC 8)  
 Max Uplift 7=109(LC 8), 2=73(LC 8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Provide adequate drainage to prevent water ponding.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Refer to girder(s) for truss to truss connections.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2 except (jt=lb) 7=109.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - 9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 105 lb down and 104 lb up at 5-3-1 on top chord, and 120 lb down and 37 lb up at 1-4-12, and 120 lb down and 45 lb up at 3-4-12, and 35 lb down at 5-4-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
  - 10) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).


**LOAD CASE(S)** Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-3=-60, 3-4=-60, 4-5=-20, 2-6=-20  
 Concentrated Loads (lb)  
 Vert: 3=-40(F) 8=-17(F) 9=-120(F) 10=-120(F)

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	W2	HALF HIP GIRDER	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:58 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-n0YMPtV8bBScQmDn5YUCsYbmR9MxveEr0ToCWzIXq3



Scale = 1:16.8




Plate Offsets (X,Y)-- [3:0-2-0,0-3-13]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.09	Vert(LL)	-0.00	2-7	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.07	Vert(CT)	-0.01	2-7	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	7	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-R	Wind(LL)	0.00	2-7	>999	240		
	Code IRC2015/TPI2014							Weight: 27 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-5.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 7=188/Mechanical, 2=253/0-3-8 (min. 0-1-8)  
 Max Horz 2=92(LC 8)  
 Max Uplift 7=-58(LC 5), 2=-29(LC 8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Refer to girder(s) for truss to truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 2.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 107 lb down and 103 lb up at 2-4-13 on top chord, and 60 lb down at 2-5-9 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
  - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-3=-60, 3-4=-60, 4-5=-20, 2-6=-20  
 Concentrated Loads (lb)  
 Vert: 3=-41(B) 8=-30(B)

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	W3	HALF HIP GIRDER	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:59 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-FD6kcpo7vvJJEaLPKp3jk45nMrWlGmuO3gDLkyziXq2



Scale = 1:14.2

Plate Offsets (X,Y)-- [3:0-2-0,0-3-13]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.04	Vert(LL)	-0.00	2	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.02	Vert(CT)	-0.00	2	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	7	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-R	Wind(LL)	-0.00	2	>999	240		
	Code IRC2015/TPI2014							Weight: 21 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 2-11-0 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-5.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 7=102/Mechanical, 2=192/0-3-8 (min. 0-1-8)  
 Max Horz 2=75(LC 8)  
 Max Uplift 7=-34(LC 5), 2=-19(LC 8)  
 Max Grav 7=117(LC 33), 2=192(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 6) Refer to girder(s) for truss to truss connections.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 2.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - 10) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 86 lb down and 55 lb up at 1-9-3 on top chord, and 24 lb down at 1-9-15 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
  - 11) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-3=-60, 3-4=-60, 4-5=-20, 2-6=-20  
 Concentrated Loads (lb)  
 Vert: 8=-12(F)

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	W4	JACK-OPEN	2	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:59 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-FD6kcpo7vvJJEaLPKp3jk45mNrVVgMuO3gDLkylXq2



Scale = 1:20.0

Plate Offsets (X,Y)-- [3:0-2-0,0-3-13]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.10	Vert(LL)	-0.00	2-5	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.08	Vert(CT)	-0.01	2-5	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.02	4	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P	Wind(LL)	0.01	2-5	>999	240		
									Weight: 29 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 4-9-10 oc purlins, except 2-0-0 oc purlins: 3-4.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 4=119/Mechanical, 2=265/0-3-8 (min. 0-1-8), 5=55/Mechanical  
Max Horz 2=114(LC 12)  
Max Uplift 4=47(LC 9), 2=4(LC 12)  
Max Grav 4=119(LC 1), 2=265(LC 1), 5=87(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-**

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 2.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	W4A	JACK-OPEN GIRDER	2	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:28:59 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-FD6kcpo7vvJJEaLPKp3jk45mIrVPgMuO3gDLkylXq2




Plate Offsets (X,Y)-- [3-0-2-0,0-3-13]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.11	Vert(LL)	-0.00	2-5	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.08	Vert(CT)	-0.01	2-5	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.01	4	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-P	Wind(LL)	0.01	2-5	>999	240		
	Code IRC2015/TPI2014							Weight: 28 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 4-9-10 oc purlins, except 2-0-0 oc purlins: 3-4.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 4=122/Mechanical, 2=270/0-3-8 (min. 0-1-8), 5=55/Mechanical  
Max Horz 2=70(LC 8)  
Max Uplift 4=-48(LC 5), 2=-45(LC 8)  
Max Grav 4=122(LC 1), 2=275(LC 33), 5=89(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 6) Refer to girder(s) for truss to truss connections.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 2.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - 10) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 66 lb down and 36 lb up at 2-10-6 on top chord, and 62 lb down and 32 lb up at 1-7-3, and 9 lb down at 2-10-6 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
  - 11) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-60, 3-4=-60, 2-5=-20  
Concentrated Loads (lb)  
Vert: 7=-6(B) 8=-1(B)


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	X1	Jack-Partial	7	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:00 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-kPg7q9plgCRAskwbuWayHHet8FpbPoCXIJyvGOzIXq1



Scale = 1:29.3



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.35	Vert(LL) -0.03	2-6	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.21	Vert(CT) -0.07	2-6	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.12	Horz(CT) -0.00	5	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Wind(LL) 0.01	2-6	>999	240		
	Code IRC2015/TPI2014						Weight: 47 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD  
 BOT CHORD

Structural wood sheathing directly applied or 6'-0-0 oc purlins.  
 Rigid ceiling directly applied or 10'-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=358/0-3-8 (min. 0-1-8), 5=278/Mechanical  
 Max Horz 2=159(LC 9)  
 Max Uplift 5=97(LC 9)  
 Max Grav 2=358(LC 1), 5=280(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-7=-347/132, 3-7=-251/150  
 BOT CHORD 2-6=-428/347  
 WEBS 3-6=-430/532

**NOTES-**

- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-9 to 3-6-14, Interior(1) 3-6-14 to 7-2-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3'-6-0 tall by 2'-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


**LOAD CASE(S)** Standard




Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	X1A	Jack-Open	2	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:00 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-kPg7q9plgCRAskwbuWayHHex\_Fs7Pp7XJyvGOzIXq1



Scale = 1:23.2



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.11	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.05	Vert(LL) -0.00 2-4 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Vert(CT) -0.01 2-4 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) -0.00 3 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.00 2 **** 240	Weight: 25 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 3-11-4 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 3=100/Mechanical, 2=232/0-3-8 (min. 0-1-8), 4=37/Mechanical  
 Max Horz 2=130(LC 12)  
 Max Uplift 3=88(LC 12)  
 Max Grav 3=121(LC 19), 2=232(LC 1), 4=75(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-3, Interior(1) 3-4-3 to 3-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	X1B	Half Hip	2	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:01 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-CbDV1VpNQWZ0TuVoSE5BqVA6CfCb8GNhXziSprziXq0



Scale = 1:16.8

Plate Offsets (X,Y)-- [3:0-2-0,0-3-13]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.08	Vert(LL)	-0.00	2-7	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.04	Vert(CT)	-0.00	2-7	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	7	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-R	Wind(LL)	-0.00	2-7	>999	240		
	Code IRC2015/TPI2014							Weight: 27 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 3-11-4 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-5.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 7=140/Mechanical, 2=224/0-3-8 (min. 0-1-8)  
 Max Horz 2=92(LC 12)  
 Max Uplift 7=-25(LC 9), 2=-8(LC 12)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Provide adequate drainage to prevent water ponding.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Refer to girder(s) for truss to truss connections.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 2.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	X1C	Half Hip Girder	2	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:01 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-CbDV1VpNQWZ0TuVoSE5BqVA7YfCb8GNhXziSprziXq0




Plate Offsets (X,Y)-- [3:0-2-0,0-3-13]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.06	Vert(LL)	-0.00	2-7	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.04	Vert(CT)	-0.00	2-7	>999	240		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.00	Horz(CT)	0.00	7	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-R	Wind(LL)	-0.00	2	>999	240		
									Weight: 24 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 3-11-4 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-5.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 7=140/Mechanical, 2=224/0-3-8 (min. 0-1-8)  
 Max Horz 2=48(LC 8)  
 Max Uplift 7=-17(LC 5), 2=-18(LC 8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Provide adequate drainage to prevent water ponding.
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 5) Refer to girder(s) for truss to truss connections.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 2.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - 9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 50 lb down and 15 lb up at 0-9-10, and 55 lb down and 14 lb up at 2-0-0 on top chord. The design/selection of such connection device(s) is the responsibility of others.

**LOAD CASE(S)** Standard  
 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-3=-60, 3-4=-60, 4-5=-20, 2-6=-20


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	X1D	Jack-Open Supported Gable	4	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:01 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-CbDV1VpNQWZ0TuVoSE5BqVA71fC38GNhXziSprziXq0



Scale = 1:10.4



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.03	Vert(LL) 0.00	1	n/r	120	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.01	Vert(CT) -0.00	1	n/r	120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT) 0.00	3	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P						
	Code IRC2015/TPI2014						Weight: 11 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1

**BRACING-**  
TOP CHORD  
BOT CHORD

Structural wood sheathing directly applied or 1-4-0 oc purlins.  
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 3=15/1-4-0 (min. 0-1-8), 2=141/1-4-0 (min. 0-1-8), 4=13/1-4-0 (min. 0-1-8)  
Max Horz 2=48(LC 12)  
Max Uplift 3=-16(LC 12), 2=-18(LC 12)  
Max Grav 3=21(LC 19), 2=141(LC 1), 4=27(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-**


- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Corner(3) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 2-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	X2	Jack-Open	6	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:02 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-gontFqq?Bqit524\_0xcQMijHR2YZtjdqldR?LHziXq?



Scale = 1:23.5



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.11	Vert(LL)	-0.00	2-4	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.05	Vert(CT)	-0.01	2-4	>999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P	Wind(LL)	0.00	2	****	Weight: 26 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1

**BRACING-**  
 TOP CHORD  
 BOT CHORD

Structural wood sheathing directly applied or 4-0-0 oc purlins.  
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 3=102/Mechanical, 2=235/0-3-8 (min. 0-1-8), 4=38/Mechanical  
 Max Horz 2=131(LC 12)  
 Max Uplift 3=90(LC 12)  
 Max Grav 3=123(LC 19), 2=235(LC 1), 4=76(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-3, Interior(1) 3-4-3 to 3-11-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	X2A	JACK-OPEN	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:02 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-gontFqq?Bqit524\_0xcQMijlB2YrtjdqldR?LHziXq?



Scale = 1:17.0



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.06	Vert(LL)	-0.00	2-4	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.03	Vert(CT)	-0.00	2-4	>999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P	Wind(LL)	0.00	2	****	Weight: 21 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 3-4-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 3=101/Mechanical, 2=210/0-3-8 (min. 0-1-8), 4=50/Mechanical  
Max Horz 2=90(LC 12)  
Max Uplift 3=87(LC 12), 2=8(LC 12)  
Max Grav 3=114(LC 37), 2=210(LC 1), 4=100(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 83 lb down and 93 lb up at 3-3-4 on top chord, and 38 lb down at 3-3-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
  - 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-60, 2-4=-20  
Concentrated Loads (lb)  
Vert: 3=-21(F) 4=-19(F)

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	X2GR	Jack-Open Girder	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:03 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-8\_LFSArdy7qkCfAZf8fvwGT9SnlcAt\_HBZtjzIXq



Scale = 1:23.3

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.05	Vert(LL) -0.01	1-3	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.40	Vert(CT) -0.03	1-3	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT) -0.00	2	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-P	Wind(LL) 0.01	1-3	>999	240		
	Code IRC2015/TPI2014						Weight: 45 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 1=618/0-3-8 (min. 0-1-8), 2=114/Mechanical, 3=515/Mechanical  
 Max Horz 1=116(LC 8)  
 Max Uplift 2=93(LC 8), 3=-2(LC 4)  
 Max Grav 1=618(LC 1), 2=134(LC 15), 3=515(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 2-ply truss to be connected together as follows:  
 Top chords connected with 10d (0.131"x3") nails as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
 Bottom chords connected with 10d (0.131"x3") nails as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Refer to girder(s) for truss to truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 3.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 943 lb down and 56 lb up at 2-0-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

**LOAD CASE(S)** Standard  
 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-2=-60, 1-3=-20  
 Concentrated Loads (lb)  
 Vert: 4=-943(F)


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	X3	JACK-OPEN	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:03 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-8\_LFSArdy7qkCfAZf8fvwGT\_StDcAt\_HBZtjzIXq



Scale = 1:19.1



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.06	Vert(LL)	-0.00	2	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.03	Vert(CT)	-0.00	2-4	>999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P	Wind(LL)	0.00	2	****	Weight: 20 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 2-11-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 3=65/Mechanical, 2=196/0-3-8 (min. 0-1-8), 4=27/Mechanical  
 Max Horz 2=102(LC 12)  
 Max Uplift 3=65(LC 12)  
 Max Grav 3=82(LC 19), 2=196(LC 1), 4=54(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


**LOAD CASE(S)** Standard




Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	X3A	JACK-OPEN	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:04 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-cAvdgWsGjRybKLDm7MfuR7oe5sDZLd77Dxw6P9zIXpz



Scale = 1:14.4



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.04	Vert(LL)	-0.00	2	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.02	Vert(CT)	-0.00	2	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P	Wind(LL)	0.00	2	****	240		
									Weight: 17 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1

**BRACING-**  
 TOP CHORD  
 BOT CHORD

Structural wood sheathing directly applied or 2-6-8 oc purlins.  
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 3=52/Mechanical, 2=183/0-3-8 (min. 0-1-8), 4=32/Mechanical  
 Max Horz 2=72(LC 12)  
 Max Uplift 3=48(LC 12), 2=-12(LC 12)  
 Max Grav 3=76(LC 37), 2=183(LC 1), 4=64(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 72 lb down and 65 lb up at 2-5-12 on top chord, and 18 lb down at 2-5-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
  - 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).


**LOAD CASE(S)** Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-3=-60, 2-4=-20  
 Concentrated Loads (lb)  
 Vert: 4=-9(B)


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	X3GR	Jack-Open Girder	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:04 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-cAvdgWsGjRybKLDM7MfuR7oeJsB2Ld77Dxw6P9zlXpz



Scale = 1:18.9



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.02	Vert(LL) -0.00	1-3	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.18	Vert(CT) -0.01	1-3	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT) -0.00	2	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-P	Wind(LL) 0.00	1-3	>999	240		
	Code IRC2015/TPI2014						Weight: 33 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 2-11-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 1=577/0-3-8 (min. 0-1-8), 2=81/Mechanical, 3=236/Mechanical  
Max Horz 1=87(LC 8)  
Max Uplift1=-2(LC 8), 2=-70(LC 8)  
Max Grav 1=600(LC 2), 2=97(LC 15), 3=251(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 2-ply truss to be connected together as follows:  
Top chords connected with 10d (0.131"x3") nails as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Bottom chords connected with 10d (0.131"x3") nails as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Refer to girder(s) for truss to truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 2.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 729 lb down and 55 lb up at 0-11-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

**LOAD CASE(S)** Standard  
1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-2=-60, 1-3=-20  
Concentrated Loads (lb)  
Vert: 4=-678(B)


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	X4	Jack-Open	4	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:04 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-cAvdgWsGjRybKLDm7MfuR7oc9sCcLd77Dxw6P9zlXpz



Scale = 1:26.7



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.16	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.08	Vert(LL) -0.01 2-4 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Vert(CT) -0.01 2-4 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) -0.00 3 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.00 2 **** 240	Weight: 30 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1

**BRACING-**  
 TOP CHORD  
 BOT CHORD

Structural wood sheathing directly applied or 4-9-10 oc purlins.  
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 3=128/Mechanical, 2=265/0-3-8 (min. 0-1-8), 4=46/Mechanical  
 Max Horz 2=153(LC 12)  
 Max Uplift 3=-107(LC 12)  
 Max Grav 3=152(LC 19), 2=265(LC 1), 4=92(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-**


- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-0-10 to 3-4-3, Interior(1) 3-4-3 to 4-8-14 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 3=107.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	Y4	Jack-Open	2	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:05 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-4MT0tstuU14SyVoZh3A7\_LLlowGZs44NGSbggxczlXpy



Scale = 1:13.7



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.03	Vert(LL)	-0.00	2	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.01	Vert(CT)	-0.00	2	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P	Wind(LL)	0.00	2	****	240		
									Weight: 16 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1

**BRACING-**  
TOP CHORD  
BOT CHORD

Structural wood sheathing directly applied or 2-4-0 oc purlins.  
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 3=44/Mechanical, 2=176/0-3-8 (min. 0-1-8), 4=21/Mechanical  
Max Horz 2=68(LC 12)  
Max Uplift 3=-34(LC 12), 2=-13(LC 12)  
Max Grav 3=52(LC 19), 2=176(LC 1), 4=42(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	Y4A	Jack-Open	2	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:05 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-4MT0tstuU14SyVoZh3A7\_LLo?GZ044NGSbggxczlXpy



Scale = 1:10.0



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.03	Vert(LL)	-0.00	2	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.00	Vert(CT)	-0.00	2	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P	Wind(LL)	0.00	2	****	240	Weight: 10 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 1-2-13 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 3=7/Mechanical, 2=141/0-3-8 (min. 0-1-8), 4=12/Mechanical  
 Max Horz 2=45(LC 12)  
 Max Uplift 3=-12(LC 12), 2=-20(LC 12)  
 Max Grav 3=12(LC 19), 2=141(LC 1), 4=24(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	Z2	JACK-OPEN GIRDER	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:06 2023 Page 1  
 ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-YZ1O4CtWF2CJafNIFnhMXytcgvbpXdQgFPDT2zlXpx



Scale = 1:16.6

Plate Offsets (X,Y)-- [2:0-0-1,0-0-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.10	Vert(LL)	-0.00	2-4	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.05	Vert(CT)	-0.00	2-4	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-P	Wind(LL)	0.00	2	****	240		
	Code IRC2015/TPI2014							Weight: 24 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 3-8-4 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 3=67/Mechanical, 2=294/0-4-11 (min. 0-1-8), 4=34/Mechanical  
 Max Horz 2=88(LC 12)  
 Max Uplift 3=-49(LC 12), 2=-29(LC 12)  
 Max Grav 3=68(LC 19), 2=294(LC 1), 4=69(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -1-9-14 to 2-6-15, Interior(1) 2-6-15 to 3-7-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	VILLEGAS/CARDILLO 14122023
J0223-0563	Z3	JACK-OPEN GIRDER	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Robert Lewis

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:06 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-YZ1O4CtWF2CJafNIFnhMXytcgv\_pXdQgFPDT2zlXpx



Scale = 1:14.0




Plate Offsets (X,Y)-- [2:0-0,1,0-0-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.10	Vert(LL)	-0.00	2	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.02	Vert(CT)	-0.00	2	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-P	Wind(LL)	0.00	2	****	240		
	Code IRC2015/TPI2014							Weight: 19 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 2-8-1 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 3=22/Mechanical, 2=268/0-4-11 (min. 0-1-8), 4=24/Mechanical  
Max Horz 2=71(LC 12)  
Max Uplift 3=30(LC 12), 2=33(LC 12)  
Max Grav 3=27(LC 19), 2=268(LC 1), 4=48(LC 3)


**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job J0223-0563	Truss Z4	Truss Type Diagonal Hip Girder	Qty 2	Ply 1	VILLEGAS/CARDILLO 14122023
Comtech, Inc., Fayetteville, NC 28309, Robert Lewis					Job Reference (optional)

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Mon Feb 13 14:29:06 2023 Page 1  
ID:ole4s?tmDns?Y8LXaW6dBoyCOyJ-YZ1O4CtWF2CJafNIFnhMXyTyKgvTpXdQgFPDT2zlXpx



Scale = 1:13.2




Plate Offsets (X,Y)-- [2:0-0-1,0-0-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.12	Vert(LL)	0.00	2	>999	240	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.05	Vert(CT)	-0.00	2	>999	240		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.00	Horz(CT)	0.00		n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						Weight: 18 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 2-5-3 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=257/0-4-11 (min. 0-1-8), 4=38/Mechanical  
Max Horz 2=85(LC 5)  
Max Uplift 2=-76(LC 5), 4=-16(LC 5)  
Max Grav 2=257(LC 1), 4=49(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 77 lb down and 13 lb up at 1-2-11 on top chord, and at 1-2-11 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
  - 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-60, 2-4=-20