

WKR-006  
RHSL GARAGE


NOTES:  
1. ALL FINAL MATERIALS ARE TO BE CHOSEN BY THE ARCHITECT.  
2. FINAL NUMBER OF EXTERIOR STEPS WILL BE DETERMINED ON SITE BY GRADE.  
3. CONTRACTOR MUST MEET OR EXCEED ALL REQUIREMENTS OF ALL APPLICABLE LOCAL, STATE AND FEDERAL CODES.  
4. DESIGNER ASSUMES NO RESPONSIBILITY FOR CHANGES TO DRAWINGS BY OTHERS DURING CONSTRUCTION.  
5. ALL STRUCTURAL INFO SHOWN ON PLANS ARE FOR INFORMATION ONLY. CONSULT WITH ARCHITECT FOR STRUCTURAL ENGINEER REVIEW AND DESIGN ALL STRUCTURAL ELEMENTS.



DATE: 6-9-2021  
SUBDIVISION:  
BUILDER:

**BEN STOUT CONSTRUCTION**

NOTE:  
BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE (ICC, IBC, IRC, ASCE, IBC, IFPP)



STONE COLUMNS


FRONT ELEVATION

SCALE: 1/4" = 1'0"

ATTIC VENTILIZATION - 3670 S/F / 300 = 12.23 S/F REQUIRED

9'0" FINISHED CEILING HEIGHT ON FIRST FLOOR  
14" WINDOW HEADER HEIGHT ON FIRST FLOOR  
8'0" FINISHED CEILING HEIGHT ON SECOND FLOOR  
6'8" WINDOW HEADER HEIGHT ON SECOND FLOOR  
CANTILEVER ALL ROOF TRUSSES


NO SKIRT ACCENT




LEFT ELEVATION  
SCALE: 1/8" = 1'0"




OPT. FRONT ENTRY  
DOUBLE GARAGE  
SCALE: 1/4" = 1'0"



RIGHT ELEVATION  
SCALE: 1/8" = 1'0"




OPT. SINGLE GARAGE  
SCALE: 1/8" = 1'0"



REAR ELEVATION  
SCALE: 1/8" = 1'0"



NOTES:  
1. ALL FINAL MATERIALS ARE TO BE CHOSEN BY THE OWNER.  
2. FINAL NUMBER OF EXTERIOR STEPS WILL BE DETERMINED ON SITE BY GRADE.  
3. CONTRACTOR MUST MEET OR EXCEED ALL APPLICABLE CODES.  
4. DESIGNER ASSUMES NO RESPONSIBILITY FOR CHANGES TO DRAWINGS BY OTHERS DURING CONSTRUCTION.  
5. ALL STRUCTURAL INFO SHOWN ON PLANS ARE FOR INFORMATION ONLY. CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AND DESIGN ALL STRUCTURAL ELEMENTS.



DATE: 6-9-2021  
SUBDIVISION:  
BUILDER:

**BEN STOUT CONSTRUCTION**

NOTE:  
BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE (ICC, IBC, IRC, IFC, IAP, IFPH)



ELEC. CONTRACTOR TO CONFIRM  
OUTLET LOCATION AND FIXTURE TYPES  
WITH OWNER  
9'0" FINISHED CEILING HEIGHT ON FIRST FLOOR  
1'4" WINDOW HEADER HEIGHT ON FIRST FLOOR  
8'0" FINISHED CEILING HEIGHT ON SECOND FLOOR  
6'8" WINDOW HEADER HEIGHT ON SECOND FLOOR  
CANTILEVER ALL ROOF TRUSSES


FIRST FLOOR  
SCALE: 1/4" = 1'0"

HOUSEHOLD FIRE ALARMS SYSTEMS INSTALLED IN ACCORDANCE WITH BOTH INTERNATIONAL AND LOCAL BUILDING CODES IN THE FOLLOWING LOCATIONS.

1. IN EACH SLEEPING ROOM
2. OUTSIDE EACH SEPARATE SLEEPING AREAS IN THE IMMEDIATE VICINITY OF BEDROOMS AND WIRED TOGETHER IN SUCH A MANNER THAT WHEN ONE IS ACTIVATED ALL SHALL ACTIVATE


1962 S/F ON FIRST FLOOR  
665 S/F IN BONUS ROOM AND BEDROOM #4  
631 S/F IN DOUBLE GARAGE  
274 S/F IN OPT. GARAGE  
204 S/F ON FRONT PORCH  
142 S/F ON REAR PORCH

NOTES:  
1. ALL FINAL MATERIALS ARE TO BE CHOSEN BY THE ARCHITECT.  
2. FINAL NUMBER OF EXTERIOR STEPS WILL BE DETERMINED ON SITE BY GRADE.  
3. CONTRACTOR MUST MEET OR EXCEED ALL APPLICABLE LOCAL, STATE AND FEDERAL REQUIREMENTS.  
4. DESIGNER ASSUMES NO RESPONSIBILITY FOR CHANGES TO DRAWINGS BY OTHERS DURING CONSTRUCTION.  
5. ALL STRUCTURAL INFO SHOWN ON PLANS ARE FOR INFORMATION ONLY. CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AND APPROVALS FROM ALL APPLICABLE AGENCIES.  
6. ALL STRUCTURAL INFO SHOWN ON PLANS ARE FOR INFORMATION ONLY. CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AND APPROVALS FROM ALL APPLICABLE AGENCIES.  
7. CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND LOCATIONS OF ALL STRUCTURAL ELEMENTS.



DATE: 6-9-2021  
SUBDIVISION:  
BUILDER:


**BEN STOUT CONSTRUCTION**



**OPT. BONUS ROOM  
AND BEDROOM#4**  
SCALE: 1/4" = 1'0"

ELEC. CONTRACTOR TO CONFIRM  
OUTLET LOCATION AND FIXTURE TYPES  
WITH OWNER

665 S/F IN BONUS ROOM AND BEDROOM #4  
DOEN'T INCLUDE STAIRS



**OPT. BONUS ROOM  
AND BEDROOM#4**  
SCALE: 1/4" = 1'0"


HYAC CONTRACTOR TO CONFIRM  
LOCATION OF UNIT/SIZE

665 S/F IN BONUS ROOM AND BEDROOM #4  
DOEN'T INCLUDE STAIRS

NOTE:  
BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS  
PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE  
ICC, IBC, IRC, IFC, IFGC, IFPH









TYPICAL STAIR DETAIL

NTS




OVERHANG DETAIL

SCALE: 1" = 1'0"




PORCH ROOF/HEADER W/BOXED OR ROUND COLUMN

SCALE: 3/4" = 1'0"




TOP VIEW OF DOUBLE-SIDED BRACED WALL

SCALE: 1" = 1'0"




TYP. OVERHANG DETAIL

SCALE: 1" = 1'0"




DOUBLE-SIDED BRACED WALL - BRICK INTERIOR

SCALE: 1" = 1'0"




TYP. LVL BEAM

NTS




TYP. TIE DOWN DETAIL

NTS




TYP LUG FOOTING

NTS



TYP. CONC. SLAB W/BRICK FTG.


SCALE: 1" = 1'0"



TYP. CONC. SLAB W/SIDING FTG.

SCALE: 1" = 1'0"

NOTES:  
 1. ALL FINAL MATERIALS ARE TO BE CHOSEN BY THE ARCHITECT.  
 2. FINAL NUMBER OF EXTERIOR STEPS WILL BE DETERMINED ON SITE BY GRADE.  
 3. CONTRACTOR MUST MEET OR EXCEED ALL APPLICABLE CODES AND REGULATIONS.  
 4. DESIGNER ASSUMES NO RESPONSIBILITY FOR CHANGES TO DRAWINGS BY OTHERS DURING CONSTRUCTION.  
 5. ALL STRUCTURAL INFO SHOWN ON PLANS ARE FOR INFORMATION ONLY. CONSULT STRUCTURAL ENGINEER FOR ALL STRUCTURAL ELEMENTS.  
 6. ALL STRUCTURAL ELEMENTS MUST BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH THE LATEST EDITIONS OF THE INTERNATIONAL BUILDING CODE (IBC) AND THE INTERNATIONAL RESIDENTIAL CODE (IRC).



DATE: 6-9-2021  
 SUBDIVISION:  
 BUILDER:

**BEN STOUT CONSTRUCTION**

NOTE:  
 BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE (ICC, IBC, IRC, IFC, IFBC, IFBC).



# ROOF & FLOOR TRUSSES & BEAMS

Reilly Road Industrial Park  
Fayetteville, N.C. 28309  
Phone: (910) 864-8787  
Fax: (910) 864-4444


Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables ( derived from the prescriptive Code requirements ) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.

Signature Neil Baggett  
Neil Baggett

### LOAD CHART FOR JACK STUDS

(BASED ON TABLES R502.5(1) & (b))  
NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADER/GIRDER

END REACTION (UP TO)	REQ. STUDS FOR (1) PLY HEADER	END REACTION (UP TO)	REQ. STUDS FOR (2) PLY HEADER	END REACTION (UP TO)	REQ. STUDS FOR (3) PLY HEADER
1700	1	2550	1	3400	1
3400	2	5100	2	6800	2
5100	3	7650	3	10200	3
6800	4	10200	4	13600	4
8500	5	12750	5	17000	5
10200	6	15300	6		
11900	7				
13600	8				
15300	9				



▲ = Indicates Left End of Truss  
(Reference Engineered Truss Drawing)  
Do Not Erect Trusses Backwards

1 Truss Placement Plan  
Scale: 3/16"=1'

All Walls Shown Are Considered Load Bearing

Roof Area = 4416.21 sq.ft.  
Ridge Line = 119.73 ft.  
Hip Line = 0 ft.  
Horiz. OH = 157.77 ft.  
Raked OH = 206.29 ft.  
Decking = 152 sheets

Hatch Legend

Light Storage
Tray Ceiling
Drop Beam
Flush Beam
Mechanical Storage

Products

PlotID	Length	Product	Plies	Net Qty	Fab Type
BM2	6' 0"	1-3/4"x 9-1/4" LVL Kerto-S	2	6	FF
BM1	12' 0"	1-3/4"x 11-7/8" LVL Kerto-S	2	2	FF
GDH-SL	24' 0"	1-3/4"x 23-7/8" LVL Kerto-S	2	2	FF

Connector Information

Sym	Product	Manuf	Qty	Supported Member	Header	Truss
■	HUS26	USP	3	BM1	16d/3-1/2"	16d/3-1/2"
■	THD26-2	USP	1	Varies	16d/3-1/2"	10d/3"

Truss Placement Plan  
SCALE: NTS

▲ = Indicates Left End of Truss  
(Reference Engineered Truss Drawing)  
Do NOT Erect Truss Backwards

BUILDER	Ben Stout Real Estate	CITY / CO.	Fayetteville / Cumberland
JOB NAME	Lot 1 Walker Road 15 Acre	ADDRESS	Walker Road
PLAN	Ivey / BSC-2022 w-SL	MODEL	Roof
SEAL DATE	N/A	DATE REV.	04/17/23
QUOTE #	Quote #	DRAWN BY	Neil Baggett
JOB #	JO423-1745	SALES REP.	Marshall Naylor

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com