Owner Addres Propos Location	for ON-S ses: /80 Based Facility: on of Site:	SOIL/SI SITE WA Applican	TE EVALUATI STEWATER S t: // Date Design	Evaluated: in Flow (.1949): crty Recorded:	OT 114 Property S				
Evalua Type o	Supply: ation Method of Wastewate								
R O F I L E	.1940 Landscape Position/ Slope %	Horizon Depth (In.)	SOIL MORPHOLOGY .1941		OTHER PROFILE FACTORS				
			.1941 Structure/ Texture	.1941 Consistence Mineralogy	Soil Wetness/ Color	.1943 Soil Depth (IN.)	.1956 Sapro Class	.1944 Restr Horiz	Profile Class & LTAR
	L;55	0-14	6+/25	Fr, NS LP, SEXT Fi, SSAP, SEXT Fr, NS, NP, SEX					Group
Pit		19-22	ws/s/c/scl	Fi, SSAP, SEX	*				PS
		22-48	S/Dess	Fr, Ngnp, Sex	NO	487	N/0	No	0.6
									4
							_		
				3					
					i i				
			1						
		-	L _{Sa}						
Description Initial Repair System System Available Space (.1945)				· · ·	Other Factors (.1946): Site Classification (.1948): Evaluated By: Others Present:				
System Type(s) Others Present: MA TELIV A. 7.									

COMMENTS: ____

LANDSCAPE POSITIONS	GROUP	TEXTURES	. <u>1955 LTAR</u>	CONSISTENCE MOIST	WET
R-RIDGE S-SHOULDER SLOPE L-LINEAR SLOPE	I	S-SAND LS-LOAMY SAND	1.2 - 0.8	VFR-VERY FRIABLE FR-FRIABLE	NS-NON-STICKY SS-SLIGHTY STICKY
FS-FOOT SLOPE N-NOSE SLOPE H-HEAD SLOPE	II	SL-SANDY LOAM L-LOAM	0.8 - 0.6	FI-FIRM VFI-VERY FIRM EFI-EXTREMELY FIRM	S-STICKY VS-VERY STICKY NP-NON-PLASTIC
CC-CONCLAVE SLOPE CV-CONVEX SLOPE T-TERRACE FP-FLOOD PLAN	Ш	SI-SILT SIL-SILT LOAM CL-CLAY LOAM SCL-SANDY CLAY LOAM	0.6 - 0.3		SP-SLIGHTLY STICKY P-PLASTIC VP-VERY PLASTIC

IV SIC-SILTY CLAY 0.4 - 0.1 C-CLAY

SC-SANDY CLAY

STRUCTURE SG-SINGLE GRAIN M- MASSIVE CR-CRUMB **GR-GRANULAR**

MINERALOGY SLIGHTLY EXPANSIVE

EXPANSIVE

SBK-SUBANGULAR BLOCKY ABK-ANGULAR BLOCKY

PL-PLATY PR-PRISMATIC

Show profile locations and other site features (dimensions, references or benchmark, and North) TOPOFRIAGE

Beacon Hill