

Job 72320742	Truss F200	Truss Type Truss	Qty 7	Ply 1	PBS/APEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:29

Page: 1

ID:Jv3BhEMefC3hhjpA8mAc6CyyymFH-9wgNfYSPmd7LZ85ZaU2Zib8fo3sXqNpfSAbu3z8Pd9




Plate Offsets (X, Y): [11:0-1-8,Edge], [13:0-2-0,Edge], [18:0-1-8,Edge], [19:0-1-8,Edge], [21:0-2-0,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.84	Vert(LL)	-0.24	19-20	>693	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.76	Vert(CT)	-0.33	19-20	>502	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.40	Horz(CT)	0.03	13	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 109 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS (lb/size) 13=329/0-3-8, (min. 0-1-8), 17=1067/0-3-8, (min. 0-1-8), 21=565/0-3-8, (min. 0-1-8)
 Max Grav 13=348 (LC 7), 17=1067 (LC 1), 21=582 (LC 10)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1566/0, 3-4=-1696/0, 4-5=-1696/0, 5-6=-1696/0, 6-7=0/477, 7-8=0/477, 8-9=0/477, 9-10=-663/0, 10-11=-663/0
 BOT CHORD 20-21=0/1231, 19-20=0/1824, 18-19=0/1696, 17-18=0/1108, 16-17=0/513, 15-16=0/513, 14-15=0/663, 13-14=0/663
 WEBS 8-17=-258/0, 9-17=-837/0, 11-13=-705/0, 9-15=0/310, 5-18=-391/0, 2-21=-1319/0, 2-20=0/435, 3-20=-336/0, 3-19=-291/99, 6-17=-1397/0, 6-18=0/849

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 3) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.



Job 72320742	Truss F201	Truss Type Truss	Qty 1	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFPI Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:29

Page: 1

ID:FIAY5vNvBpJPw1zYFBC4BdyymFF-d7ElsuS1XxFCBHfI8BZoEphqQWL0GFHy6w8QVz8Pd8




Plate Offsets (X, Y): [14:0-2-0,Edge], [22:0-1-8,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFLL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.91	Vert(LL)	-0.26	22-23	>824	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.97	Vert(CT)	-0.36	22-23	>596	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.55	Horz(CT)	0.06	17	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 112 lb	FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat)	BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS	(lb/size)
14=-72/0-3-8, (min. 0-1-8), 17=1312/0-3-8, (min. 0-1-8), 24=721/0-3-8, (min. 0-1-8)	
Max Uplift 14=-207 (LC 3)	
Max Grav 14=116 (LC 4), 17=1312 (LC 1), 24=724 (LC 10)	

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-2069/0, 3-4=-2870/0, 4-5=-2870/0, 5-6=-2859/0, 6-7=-2383/0, 7-8=-2383/0, 8-9=-1436/0, 9-10=0/1126, 10-11=0/1122, 11-12=-41/492
BOT CHORD	23-24=0/1582, 22-23=0/2507, 21-22=0/2870, 20-21=0/2743, 19-20=0/2033, 18-19=0/801, 17-18=0/801, 16-17=-492/41, 15-16=-492/41, 14-15=-492/41
WEBS	11-17=-891/0, 12-14=-46/614, 5-21=-370/41, 2-24=-1697/0, 2-23=0/634, 3-23=-570/0, 3-22=0/600, 9-17=-1995/0, 9-19=0/836, 8-19=-786/0, 8-20=0/462, 6-20=-476/0, 6-21=-89/548

- NOTES**
- Unbalanced floor live loads have been considered for this design.
 - All plates are 1.5x3 MT20 unless otherwise indicated.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 207 lb uplift at joint 14.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.




Job 72320742	Truss F202	Truss Type Truss	Qty 5	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:30

Page: 1

ID:FlAy5vNvBpJPw1zYFBC4BdyymFF-5Jo73ETfFN3pREyiv41n0E0uwjr?j956mfyxz8Pd7



Scale = 1:41.9

Plate Offsets (X, Y): [15:0-1-8,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.80	Vert(LL)	-0.28	14	>762	480	MT18HS	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.79	Vert(CT)	-0.39	14-15	>555	360	MT20	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.51	Horz(CT)	0.06	11	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 89 lb	FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 5-1-10 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS	(lb/size)	11=788/0-3-8, (min. 0-1-8), 18=788/0-3-8, (min. 0-1-8)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	2-3=-2300/0, 3-4=-3396/0, 4-5=-3396/0, 5-6=-3393/0, 6-7=-3102/0, 7-8=-3102/0, 8-9=-2297/0	
BOT CHORD	17-18=0/1742, 16-17=0/2818, 15-16=0/2818, 14-15=0/3396, 13-14=0/3365, 12-13=0/2820, 11-12=0/1740	
WEBS	5-14=-286/137, 2-18=-1868/0, 2-17=0/726, 3-17=-675/0, 3-15=0/813, 9-11=-1867/0, 9-12=0/725, 8-12=-680/0, 8-13=0/368, 6-13=-401/0, 6-14=-255/436	

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72320742	Truss F203	Truss Type Truss	Qty 2	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:30

Page: 1

ID:juKJFOXy7RGYAYIpukJjryymFE-5Jo73ETIFN3pREyiv41n0E3LwkT?jI56mfyxz8Pd7



Scale = 1:41.5

Plate Offsets (X, Y):	[11:0-2-0,Edge], [16:0-1-8,Edge]											
Loading	(psf)	Spacing	1-7-3	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.58	Vert(LL)	-0.26	15-16	>822	480	MT18HS	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.75	Vert(CT)	-0.35	15-16	>600	360	MT20	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.50	Horz(CT)	0.06	11	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 88 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS	(lb/size)	11=775/ Mechanical, (min. 0-1-8), 18=775/0-3-8, (min. 0-1-8)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD		2-3=-2254/0, 3-4=-3293/0, 4-5=-3293/0, 5-6=-3293/0, 6-7=-3293/0, 7-8=-2700/0, 8-9=-1649/0
BOT CHORD		17-18=0/1710, 16-17=0/2756, 15-16=0/3293, 14-15=0/3072, 13-14=0/3072, 12-13=0/2302, 11-12=0/971
WEBS		2-18=-1834/0, 2-17=0/708, 3-17=-654/0, 3-16=0/784, 9-11=-1216/0, 9-12=0/883, 8-12=-850/0, 8-13=0/519, 7-13=-484/0, 7-15=-74/551

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



Job 72320742	Truss F204	Truss Type Truss	Qty 3	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:30

Page: 1

ID:jUkKJFOxy7RGYAYlpukJjryymFE-5Jo73ETfIFN3pREyiv41n0E3ZwhM?jS56mfyxz8Pd7




Plate Offsets (X, Y): [13:0-1-8,Edge], [14:0-1-8,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.63	Vert(LL)	-0.28	14-15	>751	480	MT18HS	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.95	Vert(CT)	-0.38	14-15	>556	360	MT20	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.49	Horz(CT)	0.07	10	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 85 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS	(lb/size)	10=763/ Mechanical, (min. 0-1-8), 16=763/ Mechanical, (min. 0-1-8)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	2-3=-2207/0, 3-4=-3193/0, 4-5=-3193/0, 5-6=-3193/0, 6-7=-2207/0, 7-8=-2207/0	
BOT CHORD	15-16=0/1678, 14-15=0/2694, 13-14=0/3193, 12-13=0/2694, 11-12=0/2694, 10-11=0/1678	
WEBS	2-16=-1799/0, 2-15=0/689, 3-15=-634/0, 3-14=0/763, 8-10=-1799/0, 8-11=0/689, 6-11=-634/0, 6-13=0/763	

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.




Job 72320742	Truss F205	Truss Type Truss	Qty 1	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:31

Page: 1

ID:jUkKJFOXy7RGYAYlpukJjryymFE-5Jo73ETIFN3pREYiv41n0E3swiS?j556mfxyz8Pd7



Scale = 1:39

Plate Offsets (X, Y): [14:0-1-8,Edge]


Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.61	Vert(LL)	-0.22	14-15	>871	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.88	Vert(CT)	-0.31	14-15	>624	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.45	Horz(CT)	0.05	10	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 80 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS (lb/size) 10=703/0-3-3, (min. 0-1-8), 16=703/ Mechanical, (min. 0-1-8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1995/0, 3-4=-2710/0, 4-5=-2710/0, 5-6=-2710/0, 6-7=-2710/0, 7-8=-1972/0
 BOT CHORD 15-16=0/1531, 14-15=0/2407, 13-14=0/2710, 12-13=0/2392, 11-12=0/2392, 10-11=0/1530
 WEBS 2-16=-1642/0, 2-15=0/604, 3-15=-537/0, 3-14=0/555, 8-10=-1641/0, 8-11=0/576, 7-11=-546/0, 7-13=0/578

- NOTES
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72320742	Truss F206	Truss Type Truss	Qty 6	Ply 1	PBSAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:31

Page: 1

ID:jUkKJFOxy7RGYAYIpukJjryymFE-ZVLVHZUH3YVwQbp8FcbGJEmE9J2hkAVFLQPFVFNz8Pd6



Scale = 1:38.7

Plate Offsets (X, Y):	[9:0-2-0,0-1-8], [12:0-1-8,Edge], [14:0-1-8,0-1-8]											
Loading	(psf)	Spacing	1-7-3	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.64	Vert(LL)	-0.22	12-13	>872	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.88	Vert(CT)	-0.31	12-13	>626	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.44	Horz(CT)	0.05	9	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 79 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS	(lb/size)	9=695/0-3-8, (min. 0-1-8), 14=695/ Mechanical, (min. 0-1-8)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD		2-3=-1964/0, 3-4=-2642/0, 4-5=-2642/0, 5-6=-2642/0, 6-7=-1939/0
BOT CHORD		13-14=0/1510, 12-13=0/2366, 11-12=0/2642, 10-11=0/2351, 9-10=0/1508
WEBS		2-14=-1619/0, 2-13=0/591, 3-13=-523/0, 3-12=0/528, 7-9=-1618/0, 7-10=0/561, 6-10=-537/0, 6-11=0/559

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) Bearing at joint(s) 9 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 3) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.




Job 72320742	Truss F207	Truss Type Truss	Qty 4	Ply 1	PBSAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.62 S Sep 22 2022 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:31

Page: 1

ID: jUkKJFOxy7RGYAYIpuKjryymFE-ZVLVHZUH3YVwQbp8FcbGjEmEsJ6XkBmFLQPfVnz8Pd6



Scale = 1:45.9

Plate Offsets (X, Y): [8:0-1-8,Edge], [9:0-1-8,Edge], [18:0-1-8,Edge], [19:0-1-8,Edge], [20:0-2-0,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.59	Vert(LL)	-0.14	19-20	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.63	Vert(CT)	-0.22	19-20	>673	360		
BCLL	0.0	Rep Stress Incr	NO	WB	0.36	Horz(CT)	0.02	16	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 98 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		


REACTIONS (lb/size) 13=1053/0-3-8, (min. 0-1-8), 16=908/0-3-8, (min. 0-1-8), 20=490/0-3-8, (min. 0-1-8)
Max Grav 13=1110 (LC 4), 16=909 (LC 3), 20=498 (LC 14)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1366/0, 3-4=-1366/0, 4-5=-1366/0, 5-6=0/677, 6-7=0/677, 7-8=0/677, 8-9=-156/350, 9-10=0/364, 10-11=0/362
BOT CHORD 19-20=0/1008, 18-19=0/1366, 17-18=0/720, 16-17=0/720, 15-16=-350/156, 14-15=-350/156, 13-14=-350/156
WEBS 10-13=-258/0, 2-20=-1080/0, 2-19=0/388, 5-16=-1273/0, 5-18=0/753, 9-13=-515/0, 8-16=-589/0, 11-13=-828/0

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 3) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 4) Magnitude of user added load(s) on this truss have been applied uniformly across all gravity load cases with no adjustments.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard


- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (lb/ft)
Vert: 12-20=-8, 1-11=-80
Concentrated Loads (lb)
Vert: 11=-768



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



Job 72320742	Truss F208	Truss Type Truss	Qty 7	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---



Scale = 1:41.4
Plate Offsets (X, Y): [8:0-1-8,Edge], [10:0-1-8,Edge], [16:0-1-8,Edge], [17:0-1-8,Edge], [18:0-2-0,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.54	Vert(LL)	-0.15	17-18	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.58	Vert(CT)	-0.23	17-18	>658	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.34	Horz(CT)	0.02	14	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 92 lb	FT = 20%F, 11%E

LUMBER
TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS (lb/size) 10=179/0-3-0, (min. 0-1-8), 14=945/0-3-8, (min. 0-1-8), 18=496/0-3-8, (min. 0-1-8)
Max Grav 10=224 (LC 7), 14=945 (LC 1), 18=510 (LC 10)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1438/0, 3-4=-1438/0, 4-5=-1438/0, 5-6=0/548, 6-7=0/548, 7-8=0/548, 8-9=-265/54, 9-10=-266/54
BOT CHORD 17-18=0/1039, 16-17=0/1438, 15-16=0/836, 14-15=0/836, 13-14=-54/265, 12-13=-54/265
WEBS 2-18=-1113/0, 2-17=0/431, 5-14=-1243/0, 5-16=0/719, 8-14=-702/0, 10-12=-66/325

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 10.
 - 3) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) Gap between inside of top chord bearing and first diagonal or vertical web shall not exceed 0.500in.
 - 6) CAUTION, Do not erect truss backwards.




Job 72320742	Truss F209	Truss Type Truss	Qty 2	Ply 1	PBS/APEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:32

Page: 1

ID:n6dZuZMHQWBYlOMhUhreQyymFG-2ivUvVwqsdn2lOKpK7VsRJSRJyXTgLOa48o1qz8Pd5



Scale = 1:36.1

Plate Offsets (X, Y): [2:0-1-8,Edge], [5:Edge,0-2-0], [7:0-1-8,Edge], [9:0-2-0,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.35	Vert(LL)	-0.02	8-9	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.20	Vert(CT)	-0.03	8-9	>999	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.21	Horz(CT)	0.00	5	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 35 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS (lb/size) 5=262/0-3-0, (min. 0-1-8), 9=257/ Mechanical, (min. 0-1-8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-412/0, 3-4=-412/0, 4-5=-416/0

BOT CHORD 8-9=0/412, 7-8=0/412

WEBS 5-7=0/440, 2-9=-437/0

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) Gap between inside of top chord bearing and first diagonal or vertical web shall not exceed 0.500in.
 - 5) CAUTION, Do not erect truss backwards.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72320742	Truss F210	Truss Type Truss	Qty 2	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:32

Page: 1

ID:FIAY5vNvBpJPw1zYFBC4BdyymFF-2ivtUvVwqsdn2IOkPk7VsRJSgYITgUOa48o1qz8Pd5



Scale = 1:45.8

Plate Offsets (X, Y): [2:0-1-8,Edge], [6:0-1-8,Edge], [14:0-2-0,Edge], [24:0-2-0,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFLL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.36	Vert(LL)	-0.04	17-18	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.25	Vert(CT)	-0.06	17-18	>999	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.20	Horz(CT)	0.01	17	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 105 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS
 All bearings 0-3-8, except 24= Mechanical
 (lb) - Max Uplift All uplift 100 (lb) or less at joint(s) 14
 Max Grav All reactions 250 (lb) or less at joint(s) 14 except 17=631 (LC 14), 21=746 (LC 16), 24=328 (LC 14)

FORCES
 (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-599/0, 3-4=-599/0, 4-5=0/256, 5-6=0/256, 6-7=-558/0, 7-8=-558/0
 BOT CHORD 23-24=0/599, 22-23=0/599, 21-22=0/551, 20-21=0/558, 19-20=0/558, 18-19=0/558, 17-18=0/476
 WEBS 4-21=-690/0, 2-24=-637/0, 8-17=-692/0, 6-21=-716/0, 11-17=-356/0

- NOTES**
- Unbalanced floor live loads have been considered for this design.
 - All plates are 1.5x3 MT20 unless otherwise indicated.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 14.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.




Job 72320742	Truss F211	Truss Type Truss	Qty 1	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:33

Page: 1

ID:FIAY5vNvBpJPw1zYFBC4BdyymFF-WuTGIFVYbAlegvzWN1ekPfsd07pdC6tYokuMZGz8P4d



Scale = 1:32.9

Plate Offsets (X, Y): [7:0-2-0,Edge], [8:0-1-8,Edge], [9:0-1-8,Edge], [10:0-2-0,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.36	Vert(LL)	-0.12	9-10	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.53	Vert(CT)	-0.18	9-10	>799	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.32	Horz(CT)	0.02	7	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 60 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS (lb/size) 7=525/0-3-3, (min. 0-1-8), 10=525/0-3-8, (min. 0-1-8)


FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1537/0, 3-4=-1537/0, 4-5=-1537/0

BOT CHORD 9-10=0/1077, 8-9=0/1537, 7-8=0/1077

WEBS 5-7=-1153/0, 2-10=-1153/0, 5-8=0/571, 2-9=0/571

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72320742	Truss F212	Truss Type Truss	Qty 9	Ply 1	PBS/APEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:33

Page: 1

ID:gts4kxPnUkhznUi7wJmnpGyymFC-WuTGiFVYbAlegvzWN1ekPfsYj7jvC1KYokuMZGz8Pd4



Scale = 1:43.4

Plate Offsets (X, Y): [16:0-1-8,Edge], [20:0-3-8,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFLL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.70	Vert(LL)	-0.49	15-16	>513	480	MT18HS	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.96	Vert(CT)	-0.68	15-16	>370	360	MT20	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.61	Horz(CT)	0.10	12	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH								
											Weight: 104 lb	FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 5-0-4 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
WEBS 2x4 SP No.3(flat)	2-2-0 oc bracing: 16-17,15-16.
OTHERS 2x4 SP No.3(flat)	

REACTIONS	(lb/size)
	12=919/0-3-8, (min. 0-1-8), 20=914/0-3-8, (min. 0-1-8)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-2818/0, 3-4=-3912/0, 4-5=-4622/0, 5-6=-4622/0, 6-7=-4622/0, 7-8=-4622/0, 8-9=-3920/0, 9-10=-2777/0
BOT CHORD	19-20=0/2108, 18-19=0/3489, 17-18=0/4334, 16-17=0/4622, 15-16=0/4335, 14-15=0/3460, 13-14=0/3460, 12-13=0/2067
WEBS	5-17=-286/0, 2-20=-2249/0, 2-19=0/924, 3-19=-873/0, 3-18=0/551, 4-18=-550/0, 4-17=-81/676, 10-12=-2218/0, 10-13=0/924, 9-13=-889/0, 9-15=0/598, 8-15=-541/0, 8-16=-128/688

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 4) Required 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.




Job 72320742	Truss F213	Truss Type Truss	Qty 1	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:33

Page: 1

ID:oSfikeObPdvU?xOiAqinbLyymDx-WuTGiFvYbAlegvzWN1ekPfsTK7kcC32YokuMZGz8Pd4



Scale = 1:52.9

Plate Offsets (X, Y):	[5:0-3-0,Edge], [11:0-1-8,Edge], [18:0-2-0,Edge], [27:0-1-8,Edge], [28:0-1-8,Edge]
-----------------------	--

Loading	(psf)	Spacing	1-7-3	CSI	DEFLL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.98	Vert(LL)	-0.13	28-29	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.85	Vert(CT)	-0.20	28-29	>761	360		
BCLL	0.0	Rep Stress Incr	NO	WB	0.50	Horz(CT)	0.03	21	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 134 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 3-11-15 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS All bearings 0-3-8.
 (lb) - Max Uplift All uplift 100 (lb) or less at joint(s) 18
 Max Grav All reactions 250 (lb) or less at joint(s) 18 except 21=610 (LC 4), 24=1185 (LC 16), 29=737 (LC 14)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 3-32=-2380/0, 4-32=-2380/0, 4-5=-2380/0, 5-6=-2380/0, 6-7=-2380/0, 7-8=-1425/0, 8-9=0/859, 9-10=0/859, 10-11=0/859, 11-12=-348/315, 12-13=-348/315, 13-14=0/372, 14-15=0/367
 BOT CHORD 28-29=0/1740, 27-28=0/2380, 26-27=0/1882, 25-26=0/955, 24-25=0/955, 23-24=-315/348, 22-23=-315/348, 21-22=-213/338
 WEBS 8-24=-1727/0, 3-29=-1853/0, 8-26=0/648, 3-28=0/734, 7-26=-637/0, 7-27=0/784, 4-28=-258/0, 5-27=-409/0, 13-21=-609/0, 11-24=-926/0, 15-21=-433/0

- NOTES**
- Unbalanced floor live loads have been considered for this design.
 - All plates are 1.5x3 MT20 unless otherwise indicated.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 18.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Use MiTek MSH422 (With 10d nails into Girder & 6-10d nails into Truss) or equivalent at 4-7-4 from the left end to connect truss(es) to front face of top chord.
 - Fill all nail holes where hanger is in contact with lumber.

LOAD CASE(S)	Standard
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00	
Uniform Loads (lb/ft)	
Vert: 18-29=-8, 1-17=-80	
Concentrated Loads (lb)	
Vert: 32=-315	



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72320742	Truss F214	Truss Type Truss	Qty 1	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:34

Page: 1

ID:GrEoEXnEBGba?Fa5FKp2ZoyymEj-.41evbWAMTtV13Yjxl9zxsOq7XFexb5h1Odv5iz8Pd3



Scale = 1:43.1

Plate Offsets (X, Y): [4:Edge,0-1-8], [5:0-2-0,Edge], [8:0-2-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFLL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.21	Vert(LL)	0.00	7	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.16	Vert(CT)	-0.01	7	>999	360		
BCLL	0.0	Rep Stress Incr	NO	WB	0.13	Horz(CT)	0.00	5	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 28 lb	FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 3-10-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	


REACTIONS (lb/size) 5=523/0-3-8, (min. 0-1-8), 8=374/ Mechanical, (min. 0-1-8)
Max Grav 5=567 (LC 4), 8=395 (LC 3)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 5-10=-268/0, 4-10=-268/0, 2-3=-443/0
BOT CHORD 7-8=0/443, 6-7=0/443, 5-6=0/443
WEBS 3-5=-520/0, 2-8=-534/0

- NOTES**
- Unbalanced floor live loads have been considered for this design.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - Use MiTek MSH422 (With 10d nails into Girder & 6-10d nails into Truss) or equivalent spaced at 1-7-3 oc max. starting at 1-7-12 from the left end to 3-2-15 to connect truss(es) to back face of top chord.
 - Fill all nail holes where hanger is in contact with lumber.

LOAD CASE(S) Standard

- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (lb/ft)
Vert: 5-8=-10, 1-4=-100
Concentrated Loads (lb)
Vert: 2=-247, 11=-267



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72320742	Truss L200	Truss Type Truss	Qty 1	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:34

Page: 1

ID:ChiiWbP9jRZ79K7xNcFYG2yymFD-_41evbWAMTtVl3Yjxl9zxsOs9XH_xdfh1Odv5iz8Pd3



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-R							Weight: 94 lb	FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS All bearings 22-8-0.
(lb) - Max Grav All reactions 250 (lb) or less at joint(s) 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.




Job 72320742	Truss L202	Truss Type Truss	Qty 1	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:35

Page: 1

ID:ChliWbP9jRZ79K7xNcFYG2yymFD-SHb07xXo7n0MvC7vUSgCU4x1uxd3g4vrG2NTE9z8Pd2



Scale = 1:45.7


Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.02	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-R							Weight: 87 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat) *Except* BL2:2x4 SP No.2(flat)		

REACTIONS All bearings 20-9-8.
(lb) - Max Grav All reactions 250 (lb) or less at joint(s) 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 3) Gable requires continuous bottom chord bearing.
 - 4) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 5) Gable studs spaced at 1-4-0 oc.
 - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 7) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72320742	Truss L203	Truss Type Truss	Qty 2	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:35

Page: 1

ID:ChliWbP9jRZ79K7xNcFYG2yymFD-SHb07xXo7n0MvC7vUSgCU4x1Qxd3g4vrG2NTE9z8Pd2



Scale = 1:33


Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.11	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.02	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-R							Weight: 52 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS All bearings 12-4-0.
(lb) - Max Grav All reactions 250 (lb) or less at joint(s) 11, 12, 13, 14, 15, 16, 17, 18, 19, 20

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72320742	Truss L204	Truss Type Truss	Qty 1	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:35

Page: 1

ID:ChiiWbP9jRZ79K7xNcFYG2yymFD-SHb07xXo7n0MvC7vUSgCU4x1uxd3g4vrG2NTE9z8Pd2



Scale = 1:25.9


Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.02	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr		YES	0.03	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-R							Weight: 34 lb	FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS All bearings 7-7-0.
(lb) - Max Grav All reactions 250 (lb) or less at joint(s) 8, 9, 10, 11, 12, 13, 14

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72320742	Truss L206	Truss Type Truss	Qty 1	Ply 1	PBSVAPEX TRADITIONAL 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	---

UFPI Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.620 S Sep 22 2022 MiTek Industries, Inc. Thu Jun 08 08:42:35

Page: 1

ID:ChliWbP9jRZ79K7xNcFYG2yymFD-SHb07xXo7n0MvC7vUSgCU4x1uxd3g4vrG2NTE9z8Pd2



Scale = 1:38.7

Plate Offsets (X, Y): [14:0-2-8,Edge], [26:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.02	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-R							Weight: 68 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS All bearings 16-2-0.
(lb) - Max Grav All reactions 250 (lb) or less at joint(s) 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) Bearing at joint(s) 26, 14 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 7) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

