



Product	Length	Product	Pieces	Net Qty	Fab Type
FJ1	28'-5-7"	14" NI-40X	1	6	FF
FJ2	28'-3-0"	14" NI-40X	1	3	FF
FJ3	27'-3-6"	14" NI-40X	1	8	FF
FJ4	15'-8-7"	14" NI-40X	1	1	FF
FJ5	15'-8-1"	14" NI-40X	1	1	FF
FJ6	13'-3-3"	14" NI-40X	1	2	FF
FJ7	3'-6-12"	14" NI-40X	1	1	FF
DB1	14'-0-0"	1-3/4" x 9-1/4" LVL Kerto-S	2	2	FF
DB2	4'-0-0"	1-3/4" x 9-1/4" LVL Kerto-S	3	3	FF
Front GDH	21'-0-0"	1-3/4" x 11-7/8" LVL Kerto-S	3	3	FF
FB1	16'-0-0"	1-3/4" x 14" LVL Kerto-S	2	2	FF
TFB2	21'-0-0"	1-3/4" x 18" LVL Kerto-S	3	3	FF
3rd Car GDH	12'-0-0"	2x12 SP No.2	3	3	FF
RIM1	12'-0-0"	1 1/8" x 14" Rim Board	1	10	FF
BK1	2'-0-0"	14" NI-40X	1	11	FF

THF25140	USP	27	NA	10d/3"	10d/3"
----------	-----	----	----	--------	--------

LOAD CHART FOR JACK STUDS	
PARTS ON JACK REACTION FOR	
MAXIMUM ALLOWABLE LOADS	MINIMUM JACK STUD SPACING
NO. OF JACK REACTION PARTS	MINIMUM JACK STUD SPACING
1	2500
2	3500
3	4500
4	5500
5	6500
6	7500
7	8500
8	9500
9	10500

BUILDER	Onsite Homes	COUNTY	
JOB NAME		ADDRESS	
PLAN	Berton B 2nd Floor I-Joist	MODEL	I-Joists
SEAL DATE	6/8/2021	DATE REV.	06/15/23
QUOTE #	Quote #	DRAWN BY	Marshall Naylor
JOB #	J0623-3103	SALESMAN	Marshall Naylor

Truss Placement Plan
SCALE: NTS

▲ = Indicates Left End of Truss
(Reference Engineered Truss Drawing)
Do NOT Erect Truss Backwards

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. The trusses are designed as individual building components to be interconnected into a complete truss system. The contractor is responsible for the final design and construction of the truss system and for the final assembly of the building system. The contractor shall provide the final design and construction of the building system. The contractor shall provide the final design and construction of the building system. The contractor shall provide the final design and construction of the building system.

comTECH
ROOF & FLOOR TRUSSES & BEAMS
Rellly Road Industrial Park
Fayetteville, N.C. 28309
Phone: (910) 864-8787
Fax: (910) 864-4444