Harnett County Department of Public Health

SR, 1418

Improvement Permit

A building permit cannot be issued with only an Improvement Permit

	PROPERTY LOCA	1710N. 3/8 No. 40	DOT Trace . Fun	may Varina	27526
ISSUED TO: KMB Building LLC NEW TREPAIR EXPANS	SUBDIVISION	Exptains	Landing	LOT #	25
NEW REPAIR EXPANS	ION	Site Improvements rec	quired prior to Construction	Authorization Issuance:	
Type of Structure: SFP 34'x 47'		-			
Proposed Wastewater System Type: 25% 728	DUCTUN				
Projected Daily Flow: 360 GPD					
	rupants: 6 max				
Basement Yes No					-
	quired based on final location and elev				
Type of Water Supply: Community Public Permit conditions: NET-DS TAGE	Well Distance from well	teet 1	Permit valid	for: Five year	
Permit conditions: NICE STATE	A to Be ISSUR		monstrates	_ No expira	ation
1012	1 Par RSH	3			
Authorized State Agent: ames C	Nashard Date:	7-19-2	23	SEE ATTACHED SITE SKETC	Н
The issuance of this permit by the Health Department in no way gua					
site is subject to revocation if the size plan, plat, or the intended us the Laws and Rules for Sewage Treatment and Disposal and to condit	e changes. The Improvement Permit shall not be	affected by a change in own	ership of the site. This permit is so	ubject to compliance with the p	provisions of
	Construction Au	thorization			
	(Required for Build				
The construction and installation requirements of Rules .1950, .1952, with the attached system layout.	The second secon		into this permit and shall be met	. Systems shall be installed in	accordance
12 12 1. 11.	(ca. a.a.	710	N 1 T	r	07/0
ISSUED TO: KMB Building LLC	PROPERT	LOCATION: 318	Natchez Trace,	ruguay Varina	75/5/20
Facility Type: SFD 34x 47'	SUBDIVISI	ON <u>Captains</u>	Landing	LOT # _	25
Facility Type: SFD 34×47'		sion 🔲 Repair			
	ixtures? Yes No			-1-	
Type of Wastewater System**	CUTUUCH		(Initial) Wastewater	Flow: _360	GPD
(See note below, if applicable)					
Installation Requirements/Conditions	Number of trenches				
Septic Tank Sizegallons	Exact length of each trench _	feet	Trench Spacing:		
Pump Tank Sizegallons	Trenches shall be installed on o	contour at a	Soil Cover:	inches	
	Maximum Trench Depth of:	inches	(Maximum soil cover	shall not exceed	
	(Trench bottoms shall be level	to +/-1/4"	36" above the tren	ch bottom)	
	in all directions)				
Pump Requirements:ft. TDH vs	GPM			inches be	elow pipe
1			Aggregate Depth:	inches a	bove pipe
Conditions:				ind	
WATER LINES (INCLUDING IRRIGATION) MUST	BE 10FT. FROM ANY PART OF S	SEPTIC SYSTEM OR I	REPAIR AREA.		
NO UTILITIES ALLOWED IN INITIAL OR REPAIR	DRAIN FIELD AREA.				
**If applicable: 1 understand the system type specifi	ed is different from the type specifi	ied on the application	. I accept the specification	ons of this permit.	
Owner/Level Bernardsting Comment			Dates		
0 1 0					
This Construction Authorization is subject to revocation if the site plan Construction Authorization is subject to compliance with the provisions				SEE ATTACHED SITE	
construction authorization is subject to compliance with the provisions	of the Laws and notes for sewage freatment a	no posposal and to the condit	ions of this permit.	JEE MINCHED SHE	JAL I CH
Authorized State Agent:					
	Construction Autho	rization Expiration [)ate:		