Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit

0 111 5 1 11	PROPERTY LOCATION: 14 DIVE BOTTO SE (SIX 1233)	
ISSUED TO: Smith Douglas Homes	SUBDIVISION Duncan's Crossing	LOT # 53
NEW REPAIR EXPANSION	Site Improvements required prior to Construction Authoriz	ation Issuance:
Type of Structure: 48'x58' SFD		
Proposed Wastewater System Type: 25% reduction		
Projected Daily Flow: 360 GPD		
Number of bedrooms: 3 Number of Occupants: 6	_max	
Basement Yes X No		
Pump Required: Yes No May be required based on final	location and elevations of facilities	
Type of Water Supply: Community Public Well Dista		★ Five years
Permit conditions:		☐ No expiration
.11 M		
Authorized State Agent:: Mah W REHS	Date: 08-01-23 SEE ATTA	CHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issuance of oth		meeting their requirements. This
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement	nt Permit shall not be affected by a change in ownership of the site. This permit is subject to co	ompliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.		
Const	ruction Authorization	
	equired for Building Permit)	
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957		shall be installed in accordance
with the attached system layout.	7, 1730, and 1737 are incorporated by references into this permit and shall be mec systems s	shall be histalied ill accordance
ISSUED TO: Smith Douglas Homes	PROPERTY LOCATION: 74 Dive Bomb St (SR 125	53)
	SUBDIVISION Duncan's Crossing	LOT # 53
Facility Type: 48'x58' SFD		
Basement? Yes No Basement Fixtures? Yes		
	⊠ No	
	/I :: I) W/	200 CDD
Type of Wastewater System**	(Initial) Wastewater Flow:	360 GPD
(See note below, if applicable)	(Initial) Wastewater Flow: 3	360 GPD
71	(Initial) Wastewater Flow: 3	360 GPD
(See note below, if applicable)	(Repair)	360 GPD
(See note below, if applicable)	iches 1 (Repair)	
(See note below, if applicable)	(Repair) siches 1 each trench 225 feet Trench Spacing: 9	Feet on Center
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Number of tren Septic Tank Size 1000 gallons Exact length of Pump Tank Size gallons Trenches shall be	(Repair) sches 1 each trench 225 feet Trench Spacing: 9 be installed on contour at a Soil Cover: 6	Feet on Center
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size gallons Maximum Trence	(Repair) Inches 1 Inches (Maximum soil cover shall no	Feet on Center nches ot exceed
(See note below, if applicable)	(Repair) ches 1 each trench 225 be installed on contour at a shall be level to +/-1/4" Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall no 36" above the trench bottom)	Feet on Center nches ot exceed
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size gallons Maximum Trence	(Repair) ches 1 each trench 225 be installed on contour at a shall be level to +/-1/4" Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall no 36" above the trench bottom)	Feet on Center nches ot exceed
(See note below, if applicable)	(Repair) ches 1 each trench 225 be installed on contour at a shall be level to +/-1/4" Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall no 36" above the trench bottom)	Feet on Center nches ot exceed
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size gallons Frenches shall be Maximum Trence (Trench bottoms in all directions	(Repair) ches 1 each trench 225 be installed on contour at a shall be level to +/-1/4" Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall no 36" above the trench bottom)	Feet on Center nches ot exceed om)
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Maximum Trenc (Trench bottoms in all directions Pump Requirements:ft. TDH vsGPM	(Repair) Inches 1 I each trench 225 feet Trench Spacing: 9 Soil Cover: 6 inches (Maximum soil cover shall not so shall be level to +/-1/4" Trench Spacing: 9 Soil Cover: 6 inches (Maximum soil cover shall not so shall be level to +/-1/4" 36" above the trench bottons	Feet on Center nches ot exceed om) inches below pipe inches above pipe
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size gallons Frenches shall be Maximum Trence (Trench bottoms in all directions	(Repair) Inches 1 I each trench 225 feet Trench Spacing: 9 Soil Cover: 6 inches (Maximum soil cover shall not so shall be level to +/-1/4" Trench Spacing: 9 Soil Cover: 6 inches (Maximum soil cover shall not so shall be level to +/-1/4" 36" above the trench bottons	Feet on Center nches ot exceed om) inches below pipe
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Maximum Trenc (Trench bottoms in all directions Pump Requirements:ft. TDH vsGPM Conditions:	(Repair) Inches 1 Inches 20 Inches 21 Inches 21 Inches 20 Inch	Feet on Center nches ot exceed om) inches below pipe inches above pipe
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Frenches shall be Maximum Trenc (Trench bottoms in all directions in all directions Pump Requirements:ft. TDH vsGPM Conditions:	(Repair) Joches 1 Jeach trench 225 Joe installed on contour at a shall be level to +/-1/4" ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.	Feet on Center nches ot exceed om) inches below pipe inches above pipe
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Maximum Trenc (Trench bottoms in all directions Pump Requirements:ft. TDH vsGPM Conditions:	(Repair) Joches 1 Jeach trench 225 Joe installed on contour at a shall be level to +/-1/4" ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.	Feet on Center nches ot exceed om) inches below pipe inches above pipe
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Frenches shall be Maximum Trenc (Trench bottoms in all directions in all directions Pump Requirements:ft. TDH vsGPM Conditions: WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE	(Repair) I caches 1 I each trench 225 feet Trench Spacing: 9 Soil Cover: 6 in feet Trench Spacing: 9 Soil Cover: 6 in feet Trench Spacing: 9 Soil Cover: 6 in feet Trench Spacing: 9 (Maximum soil cover shall not so shall be level to +/-1/4" 36" above the trench botto soil Spacing Aggregate Depth: Aggregate Depth: ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.	Feet on Center nches ot exceed om) inches below pipe inches above pipe inches total
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Frenches shall be Maximum Trenc (Trench bottoms in all directions in all directions Pump Requirements:ft. TDH vsGPM Conditions:	(Repair) I caches 1 I each trench 225 feet Trench Spacing: 9 Soil Cover: 6 in feet Trench Spacing: 9 Soil Cover: 6 in feet Trench Spacing: 9 Soil Cover: 6 in feet Trench Spacing: 9 (Maximum soil cover shall not so shall be level to +/-1/4" 36" above the trench botto soil Spacing Aggregate Depth: Aggregate Depth: ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.	Feet on Center nches ot exceed om) inches below pipe inches above pipe inches total
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Size gallons Frenches shall be Maximum Trence (Trench bottoms in all directions) Pump Requirements: ft. TDH vs GPM Conditions: WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARRIVATION ARE A STATE AND A STATE AN	(Repair) Joches 1 Leach trench 225 Jeech trench Spacing: 9 Soil Cover: 6 Jeech trench Spacing: 9 Jee	Feet on Center nches ot exceed om) inches below pipe inches above pipe inches total
See note below, if applicable 25% reduction	(Repair) Joches 1 Leach trench 225 Jeech trench Spacing: 9 Jeech trench Spacing: 9 Jeech trench Spacing: 9 Jeech S	Feet on Center nches ot exceed om) inches below pipe inches above pipe inches total his permit.
See note below, if applicable 25% reduction 1000	(Repair) I each trench 225 feet Trench Spacing: 9 I be installed on contour at a Soil Cover: 6 in the shall be level to +/-1/4" ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. If the type specified on the application. I accept the specifications of the type specified on Authorization shall not be transferred when there is a change in own the sacchange in t	Feet on Center niches ot exceed om) inches below pipe inches above pipe inches total inches total
See note below, if applicable 25% reduction	(Repair) I each trench 225 feet Trench Spacing: 9 I be installed on contour at a Soil Cover: 6 in the shall be level to +/-1/4" ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. If the type specified on the application. I accept the specifications of the type specified on Authorization shall not be transferred when there is a change in own the sacchange in t	Feet on Center nches ot exceed om) inches below pipe inches above pipe inches total his permit.
See note below, if applicable 25% reduction 1000	(Repair) I each trench 225 feet Trench Spacing: 9 I be installed on contour at a Soil Cover: 6 in the shall be level to +/-1/4" ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. If the type specified on the application. I accept the specifications of the type specified on Authorization shall not be transferred when there is a change in own the sacchange in t	Feet on Center niches ot exceed om) inches below pipe inches above pipe inches total inches total
See note below, if applicable 25% reduction	(Repair) Inches 1 I each trench 225 feet Trench Spacing: 9 I be installed on contour at a Soil Cover: 6 in the Depth of: 18–24 inches shall be level to +/-1/4" Any Part of Septic System or Repair Area. Any Part of Septic System or Repair Area. I the type specified on the application. I accept the specifications of the changes. The Construction Authorization shall not be transferred when there is a change in ower sewage Treatment and Disposal and to the conditions of this permit. See Area of the Specification of the Specif	Feet on Center niches ot exceed om) inches below pipe inches above pipe inches total inches total
See note below, if applicable 25% reduction 1000	(Repair) I each trench 225 feet Trench Spacing: 9 I be installed on contour at a Soil Cover: 6 in the shall be level to +/-1/4" ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. If the type specified on the application. I accept the specifications of the type specified on Authorization shall not be transferred when there is a change in own the sacchange in t	Feet on Center niches ot exceed om) inches below pipe inches above pipe inches total inches total

Harnett County Department of Public Health Site Sketch

Property Location: 74 Dive Bomb St (SR 1253) Issued To: Smith Douglas Homes Subdivision Duncan's Crossing Lot # 53 Date: 08-01-23 Authorized State Agent: 125.00 205.00 15' UTILITY EASEMENT

This drawing is for illustrative purposes only. System installation must meet all pertinent laws, rules, and regulations.