


Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	A1	ROOF SPECIAL	2	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:35 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-Rffs6A2gLtc1Ru?v0GLc1E?Oam6fHmDR6z4Euyb9?1



Scale = 1:83.2

Plate Offsets (X,Y)-- [1:0-1-10,0-0-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.63	Vert(LL)	-0.16	11-13	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.39	Vert(CT)	-0.22	11-13	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.71	Horz(CT)	0.16	11	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.08	14	>999		
	Code IRC2015/TPI2014						Weight: 262 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1 \*Except\*  
 T4: 2x4 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2  
 SLIDER Left 2x4 SP No.2 - 4-10-10

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-10-11 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:  
 6-0-0 oc bracing: 9-11.  
 WEBS 1 Row at midpt 7-11, 5-13

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=958/0-3-8 (min. 0-1-8), 11=1958/0-3-8 (min. 0-2-5)  
 Max Horz 1=-315(LC 10)  
 Max Uplift1=-49(LC 12), 11=-143(LC 9)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-2423/216, 2-15=-2317/224, 3-15=-2283/254, 3-4=-2258/323, 4-16=-2155/342,  
 5-16=-2141/376, 5-17=-818/208, 6-17=-827/175, 6-7=-869/156, 7-8=-1192/1528,  
 8-18=-1211/1296, 9-18=-1221/1236  
 BOT CHORD 1-14=-264/2148, 13-14=0/691, 13-19=-4/435, 12-19=-4/435, 12-20=-4/435, 11-20=-4/435,  
 9-11=-1202/1226  
 WEBS 3-14=-392/357, 5-14=-275/2015, 7-13=-204/311, 7-11=-2298/1290, 8-11=-311/239,  
 5-13=-286/214


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-7 to 4-7-4, Interior(1) 4-7-4 to 15-0-0, Exterior(2) 15-0-0 to 19-4-13, Interior(1) 19-4-13 to 36-10-8 zone; cantilever right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Bearing at joint(s) 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 49 lb uplift at joint 1 and 143 lb uplift at joint 11.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	A2	ROOF SPECIAL	5	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:36 2023 Page 1  
 ID: MNXubvpAOspM1cCRTzrReHybiS3-vrCEJW2l6Bku32a6a\_sraRXY?9Qz0FVNgmimKyb9?H



Scale = 1:80.6

Plate Offsets (X,Y)-- [1:0-2-12,0-0-3], [5:0-3-12,0-2-0], [9:0-0-2,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.65	Vert(LL)	-0.16 13-15	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.52	Vert(CT)	-0.29 13-15	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.55	Horz(CT)	0.21 12	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.09 16	>999	240		
	Code IRC2015/TPI2014						Weight: 272 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1 \*Except\*  
 T4: 2x4 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2  
 SLIDER Left 2x4 SP No.2 -x 4-10-10

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-2-7 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:  
 6-0-0 oc bracing: 10-12.  
 WEBS 1 Row at midpt 7-15, 5-15

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=1150/0-3-8 (min. 0-1-8), 12=1766/0-3-8 (min. 0-2-1)  
 Max Horz 1=-315(LC 10)  
 Max Uplift1=-50(LC 12), 12=-120(LC 13)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-2959/327, 2-17=-2838/337, 3-17=-2805/366, 3-4=-2744/447, 4-18=-2665/466,  
 5-18=-2658/500, 5-19=-1117/334, 6-19=-1125/300, 6-7=-1166/288, 7-8=-1556/61,  
 8-9=-1569/26, 9-12=-2320/717, 9-20=-935/1105, 10-20=-945/1046  
 BOT CHORD 1-16=-267/2568, 15-16=0/936, 15-21=-12/940, 14-21=-12/940, 14-22=-12/940,  
 13-22=-12/940, 12-13=0/1136, 10-12=-1028/963  
 WEBS 3-16=-351/334, 5-16=-278/2318, 7-15=-448/240, 5-15=-199/307, 7-13=-55/393


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-7 to 4-7-4, Interior(1) 4-7-4 to 15-0-0, Exterior(2) 15-0-0 to 19-4-13, Interior(1) 19-4-13 to 36-10-8 zone; cantilever right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCCL = 10.0psf.
  - 5) Bearing at joint(s) 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 50 lb uplift at joint 1 and 120 lb uplift at joint 12.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	A2A	ROOF SPECIAL	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:37 2023 Page 1  
 ID: MNXubvpAOspM1cCRTzrReHybiS3-N2mcWs3wtUshC9I7hN46f4jkZmCilIwVQSBInyb9?G



Scale = 1:80.6

Plate Offsets (X,Y)-- [1:0-2-12,0-0-3], [5:0-3-12,0-2-0], [9:0-0-2,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.65	Vert(LL)	-0.16	13-15	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.52	Vert(CT)	-0.29	13-15	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.55	Horz(CT)	0.21	12	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.09	16	>999		
	Code IRC2015/TPI2014						Weight: 272 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1 \*Except\*  
 T4: 2x4 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2  
 SLIDER Left 2x4 SP No.2 -x 4-10-10

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-2-7 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:  
 6-0-0 oc bracing: 10-12.  
 WEBS 1 Row at midpt 7-15, 5-15

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=1150/Mechanical, 12=1766/0-3-8 (min. 0-2-1)  
 Max Horz 1=-315(LC 10)  
 Max Uplift1=-50(LC 12), 12=-120(LC 13)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-2959/327, 2-17=-2838/337, 3-17=-2805/366, 3-4=-2744/447, 4-18=-2665/466,  
 5-18=-2658/500, 5-19=-1117/334, 6-19=-1125/300, 6-7=-1166/288, 7-8=-1556/61,  
 8-9=-1569/26, 9-12=-2320/717, 9-20=-935/1105, 10-20=-945/1046  
 BOT CHORD 1-16=-267/2568, 15-16=0/936, 15-21=-12/940, 14-21=-12/940, 14-22=-12/940,  
 13-22=-12/940, 12-13=0/1136, 10-12=-1028/963  
 WEBS 3-16=-351/334, 5-16=-278/2318, 7-15=-448/240, 5-15=-199/307, 7-13=-55/393


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-7 to 4-7-4, Interior(1) 4-7-4 to 15-0-0, Exterior(2) 15-0-0 to 19-4-13, Interior(1) 19-4-13 to 36-10-8 zone; cantilever right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCCL = 10.0psf.
  - Refer to girder(s) for truss to truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 50 lb uplift at joint 1 and 120 lb uplift at joint 12.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	A3	ROOF SPECIAL	3	1	

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:37 2023 Page 1  
 ID:MNxubvpaOspM1cCRTzrReHybiS3-N2mcWs3wtUslhC9I7hN46f4nEZmzlf2WvQSBlnyb9?G



Scale = 1:80.3

Plate Offsets (X,Y)-- [1:0-1-2,0-3-1]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.43	Vert(LL)	-0.21	10-11	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.53	Vert(CT)	-0.34	10-11	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.72	Horz(CT)	0.20	10	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.09	12	>999		
	Code IRC2015/TPI2014						Weight: 236 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2 \*Except\*  
 W6: 2x6 SP No.1  
 SLIDER Left 2x4 SP No.2 -x 4-10-10

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-2-15 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS 1 Row at midpt 7-11, 7-10, 5-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=1138/Mechanical, 10=1145/0-3-8 (min. 0-1-8)  
 Max Horz 1=311(LC 9)  
 Max Uplift1=-46(LC 12), 10=-37(LC 13)  
 Max Grav 1=1138(LC 1), 10=1193(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-2870/482, 2-13=-2750/493, 3-13=-2716/522, 3-4=-2658/600, 4-14=-2579/619,  
 5-14=-2569/653, 5-15=-1056/403, 6-15=-1066/369, 6-7=-1107/350, 7-16=-471/105,  
 8-16=-605/78, 8-10=-488/129  
 BOT CHORD 1-12=-345/2482, 11-12=-6/886, 11-17=-131/838, 17-18=-131/838, 10-18=-131/838  
 WEBS 3-12=-357/319, 5-12=-365/2254, 7-11=-363/278, 7-10=-900/262, 5-11=-188/271


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-7 to 4-7-4, Interior(1) 4-7-4 to 15-0-0, Exterior(2) 15-0-0 to 19-4-13, Interior(1) 19-4-13 to 28-7-12 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCCL = 10.0psf.
  - Refer to girder(s) for truss to truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 46 lb uplift at joint 1 and 37 lb uplift at joint 10.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	A3A	ROOF SPECIAL	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:38 2023 Page 1  
 ID:MNxubvpAOspM1cCRTzrReHybiS3-rEK\_kC4Yeo\_cIMkUhpUjfsdxkz5NU9Ng74BkrDyb9?F



Scale = 1:80.3

Plate Offsets (X,Y)-- [1:0-1-2,0-3-1]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	4-0-0	TC 0.51	Vert(LL)	-0.21	10-11	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.59	Vert(CT)	-0.34	10-11	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.52	Horz(CT)	0.20	10	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-S	Wind(LL)	0.09	12	>999		
	Code IRC2015/TPI2014						Weight: 473 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2 \*Except\*  
 W6: 2x6 SP No.1  
 SLIDER Left 2x4 SP No.2 -x 4-10-10

**BRACING-**

TOP CHORD 2-0-0 oc purlins (6-0-0 max.), except end verticals  
 (Switched from sheeted: Spacing > 2-0-0).  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS 1 Row at midpt 5-11

**REACTIONS.** (lb/size) 1=2275/Mechanical, 10=2290/0-3-8 (min. 0-1-8)  
 Max Horz 1=623(LC 9)  
 Max Uplift 1=-92(LC 12), 10=-75(LC 13)  
 Max Grav 1=2275(LC 1), 10=2386(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-5740/964, 2-13=-5500/987, 3-13=-5432/1044, 3-4=-5316/1200, 4-14=-5159/1238,  
 5-14=-5139/1306, 5-15=-2112/806, 6-15=-2131/739, 6-7=-2214/701, 7-16=-943/210,  
 8-16=-1210/156, 8-10=-976/259  
 BOT CHORD 1-12=-690/4965, 11-12=-12/1771, 11-17=-262/1677, 17-18=-262/1677, 10-18=-262/1677  
 WEBS 3-12=-713/638, 5-12=-730/4507, 7-11=-725/557, 7-10=-1801/525, 5-11=-375/542

**NOTES-**


- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
 Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-7 to 4-7-4, Interior(1) 4-7-4 to 15-0-0, Exterior(2) 15-0-0 to 19-4-13, Interior(1) 19-4-13 to 28-7-12 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 92 lb uplift at joint 1 and 75 lb uplift at joint 10.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	B1	FINK	6	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:38 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-rEK\_kC4Yeo\_cIMkUhPuJfsd?Dz7tUBig74BkrDyb9?F



5x5 =

Scale = 1:79.1




Plate Offsets (X,Y)-- [2:0-3-0,0-0-8], [10:0-3-5,0-0-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.22	Vert(LL)	-0.12 11-13	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.49	Vert(CT)	-0.17 11-13	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.44	Horz(CT)	0.03 10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.02 2-13	>999	240		
								Weight: 240 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2  
 SLIDER Left 2x4 SP No.2 -x 4-9-12, Right 2x4 SP No.2 -x 4-9-12

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 5-11-13 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS 1 Row at midpt 6-13, 6-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=1246/0-3-8 (min. 0-1-12), 10=1199/Mechanical  
 Max Horz 2=314(LC 9)  
 Max Uplift 2=-60(LC 12), 10=-50(LC 13)  
 Max Grav 2=1486(LC 19), 10=1443(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-1809/296, 3-4=-1686/334, 4-5=-1668/449, 5-20=-1566/467, 6-20=-1539/501,  
 6-21=-1541/509, 7-21=-1568/475, 7-8=-1670/456, 8-22=-1589/338, 9-22=-1687/309,  
 9-10=-1809/300  
 BOT CHORD 2-14=-106/1451, 14-15=-106/1451, 13-15=-106/1451, 13-16=0/967, 12-16=0/967,  
 12-17=0/967, 11-17=0/967, 11-18=-93/1285, 18-19=-93/1285, 10-19=-93/1285  
 WEBS 4-13=-508/350, 6-13=-218/948, 6-11=-219/952, 8-11=-507/352


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-9-1 to 3-7-12, Interior(1) 3-7-12 to 15-0-0, Exterior(2) 15-0-0 to 19-4-13, Interior(1) 19-4-13 to 30-0-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 5) Refer to girder(s) for truss to truss connections.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 60 lb uplift at joint 2 and 50 lb uplift at joint 10.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	B1GE	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:39 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-JQuNxY5AP66TwwJhF6PYC499INX4DeGpMxkInfyb9?E



Scale = 1:82.3




Plate Offsets (X,Y)-- [2:0-2-8,0-1-0], [2:1-11-0,0-2-4], [5:0-2-0,Edge], [7:0-2-0,Edge], [10:0-3-5,0-0-9], [10:1-9-4,0-2-0], [33:2-2-12,0-2-8], [46:2-1-4,0-2-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.26	Vert(LL)	-0.02	14-16	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.24	Vert(CT)	-0.03	14-16	>999	M18AHS	186/179
BCLL 0.0 *	Lumber DOL 1.15	WB 0.42	Horz(CT)	0.01	10	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-S	Wind(LL)	0.02	14-16	>999		
	Code IRC2015/TPI2014						Weight: 382 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1  
WEBS 2x4 SP No.2  
OTHERS 2x4 SP No.2  
SLIDER Left 2x4 SP No.2 -x 4-9-12, Right 2x6 SP No.1 -x 4-9-12

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
WEBS 1 Row at midpt 6-19, 6-14

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 14-7-8 except (jt=length) 10=6-3-8, 12=6-3-8, 11=6-3-8, 16=0-3-8, 13=0-3-8.  
(lb) - Max Horz 2=393(LC 26)  
Max Uplift All uplift 100 lb or less at joint(s) 23, 11, 16, 13 except 2=-138(LC 9), 19=-411(LC 8), 10=-226(LC 9), 17=-161(LC 34), 12=-166(LC 1)  
Max Grav All reactions 250 lb or less at joint(s) 17, 18, 20, 21, 22, 23, 12, 11 except 2=463(LC 1), 19=749(LC 33), 10=708(LC 1), 16=546(LC 34), 13=418(LC 34)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-534/196, 3-4=-312/231, 4-5=-349/304, 5-6=-227/357, 6-7=-657/517, 7-8=-790/464, 8-9=-670/312, 9-10=-910/274  
BOT CHORD 2-23=-192/407, 23-47=-192/407, 22-47=-192/407, 21-22=-192/407, 21-48=-192/407, 20-48=-192/407, 19-20=-192/407, 18-19=-78/387, 18-49=-78/387, 17-49=-78/387, 16-17=-78/387, 15-16=-78/387, 15-50=-78/387, 50-51=-78/387, 14-51=-78/387, 14-52=-94/574, 52-53=-94/574, 13-53=-94/574, 12-13=-94/574, 12-54=-94/574, 11-54=-94/574, 10-11=-94/574  
WEBS 4-19=-484/470, 6-19=-448/52, 6-14=-432/661, 8-14=-460/467

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - All plates are MT20 plates unless otherwise indicated.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 23, 11, 16, 13 except (jt=lb) 2=138, 19=411, 10=226, 17=161, 12=166.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 44 lb down and 41 lb up at 15-11-4, 44 lb down and 41 lb up at 17-11-4, and 44 lb down and 41 lb up at 19-11-4, and 44 lb down and 41 lb up at 21-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	B1GE	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:40 2023 Page 2  
 ID:MNxubvpAOspM1cCRTzrReHybiS3-ncSI9u6pAPEJYgutpqwnkHik2ntJy5WzbOgrv5yb9?D

**LOAD CASE(S)** Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 2-10=-20, 1-6=-60, 6-10=-60

Concentrated Loads (lb)


Vert: 15=-39 14=-39 50=-39 53=-39



Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	B2	ROOF TRUSS	3	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:40 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-ncSI9u6pAPEJYgutpqwnkHiBUnoxy23zbOgrv5yb9?D



Scale = 1:79.1




Plate Offsets (X,Y)-- [2:0-0,0-0-0-5], [3:0-4-0,Edge], [4:0-9-1,Edge], [6:0-4-0,Edge], [8:0-9-13,0-0-4], [9:0-4-0,Edge], [10:0-1-4,0-1-8], [13:0-5-0,0-6-8], [15:0-6-4,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.88	Vert(LL)	-0.40	13-15	>846	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.52	Vert(CT)	-0.66	13-15	>521	M18AHS	186/179
BCLL 0.0 *	Lumber DOL 1.15	WB 0.64	Horz(CT)	0.02	12	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.11	13-15	>999		
	Code IRC2015/TPI2014							Weight: 306 lb FT = 20%

**LUMBER-**  
**TOP CHORD** 2x10 SP No.1 \*Except\*  
T1,T3: 2x6 SP No.1  
**BOT CHORD** 2x10 SP 2400F 2.0E  
**WEBS** 2x6 SP No.1 \*Except\*  
W3: 2x4 SP No.2  
**WEDGE**  
Left: 2x4 SP No.2

**BRACING-**  
**TOP CHORD** Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.  
**BOT CHORD** Rigid ceiling directly applied or 10-0-0 oc bracing.  
**WEBS** 1 Row at midpt 5-7

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=1566/0-3-8 (min. 0-1-10), 12=1550/0-3-8 (min. 0-1-10)  
Max Horz 2=306(LC 9)  
Max Grav 2=1940(LC 20), 12=1959(LC 21)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
**TOP CHORD** 2-16=-2739/0, 3-16=-2593/0, 3-4=-2507/0, 4-5=-1718/137, 5-6=-38/429, 6-7=-66/400,  
7-8=-1759/137, 8-17=-2405/0, 9-17=-2418/0, 9-10=-2569/0, 10-12=-2317/0  
**BOT CHORD** 2-15=0/1803, 14-15=0/1806, 13-14=0/1806  
**WEBS** 4-15=0/1370, 8-13=0/1174, 10-13=0/1723, 5-7=-2162/92


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-9-1 to 3-7-12, Interior(1) 3-7-12 to 15-0-0, Exterior(2) 15-0-0 to 19-7-2, Interior(1) 19-7-2 to 28-7-12 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - All plates are MT20 plates unless otherwise indicated.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Ceiling dead load (10.0 psf) on member(s). 4-5, 7-8, 5-7; Wall dead load (5.0psf) on member(s).4-15, 8-13
  - Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 13-15
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Attic room checked for L/360 deflection.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	B2A	ROOF TRUSS	2	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:41 2023 Page 1  
 ID: MNXubvpAOspM1cCRTzrReHybiS3-Fp07MD6RjMA9pT3MXS0HVEM9A5VhPH6q2QPRYyb9?C



Scale = 1:79.1




Plate Offsets (X,Y)-- [2:0-1-15,0-2-3], [3:0-4-0,Edge], [4:0-9-5,0-1-4], [6:0-4-0,Edge], [8:0-9-9,0-1-4], [12:0-7-4,0-1-8], [14:0-7-0,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	5-0-0	TC 0.88	Vert(LL)	-0.46 12-14	>760	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.69	Vert(CT)	-0.73 12-14	>472	240	M18AHS	186/179
BCLL 0.0 *	Lumber DOL 1.15	WB 0.96	Horz(CT)	0.03 11	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-S	Wind(LL)	0.12 12-14	>999	240		
	Code IRC2015/TPI2014							Weight: 627 lb FT = 20%

- LUMBER-**  
 TOP CHORD 2x10 SP 2400F 2.0E \*Except\*  
 T1,T3: 2x8 SP No.1  
 BOT CHORD 2x10 SP 2400F 2.0E  
 WEBS 2x6 SP No.1  
 WEDGE  
 Left: 2x6 SP No.1  
 SLIDER Right 2x8 SP No.1 -x 2-7-2
- BRACING-**  
 TOP CHORD 2-0-0 oc purlins (4-8-13 max.)  
 (Switched from sheeted: Spacing > 2-0-0).  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 2=3946/0-3-8 (min. 0-2-0), 11=3882/0-3-8 (min. 0-2-0)  
 Max Horz 2=770(LC 11)  
 Max Grav 2=4892(LC 20), 11=4891(LC 21)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-15=-6988/0, 3-15=-6622/0, 3-4=-6435/0, 4-5=-4403/345, 5-6=-187/927, 6-7=-211/914,  
 7-8=-4425/352, 8-16=-6739/0, 9-16=-6793/0, 9-10=-7050/0, 10-11=-7252/0  
 BOT CHORD 2-14=0/4601, 13-14=0/4609, 12-13=0/4609, 11-12=0/4598  
 WEBS 4-14=0/3497, 8-12=0/3944, 5-7=-5299/245


- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
 Top chords connected as follows: 2x8 - 2 rows staggered at 0-9-0 oc, 2x10 - 2 rows staggered at 0-9-0 oc.  
 Bottom chords connected as follows: 2x10 - 2 rows staggered at 0-9-0 oc.  
 Webs connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-7-11 to 3-9-2, Interior(1) 3-9-2 to 15-0-0, Exterior(2) 15-0-0 to 19-7-2, Interior(1) 19-7-2 to 29-0-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - All plates are MT20 plates unless otherwise indicated.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Ceiling dead load (10.0 psf) on member(s). 4-5, 7-8, 5-7; Wall dead load (5.0psf) on member(s). 4-14, 8-12
  - Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 12-14
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Attic room checked for L/360 deflection.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	B2GE	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:42 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-k?aVaZ73i1U1nz2FwEzFpinhQaZbQ2aF2i9y\_\_yb9?B



Scale = 1:81.7




Plate Offsets (X,Y)-- [3:0-4-0,Edge], [6:0-4-0,0-4-4], [9:0-4-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.14	Vert(LL)	-0.01 13-14	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.18	Vert(CT)	-0.01 13-14	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.25	Horz(CT)	0.01 11	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-S	Wind(LL)	0.00 14-16	>999	240		
	Code IRC2015/TPI2014						Weight: 332 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x10 SP No.1 \*Except\*  
T1,T3: 2x6 SP No.1  
BOT CHORD 2x10 SP No.1  
WEBS 2x6 SP No.1 \*Except\*  
W3: 2x4 SP No.2  
OTHERS 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
WEBS 1 Row at midpt 5-7

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.**

All bearings 11-11-8 except (jt=length) 14=0-3-8, 14=0-3-8, 16=0-3-8.  
(lb) - Max Horz 2=380(LC 5)  
Max Uplift All uplift 100 lb or less at joint(s) 2, 11, 12 except 17=-320(LC 28), 13=-305(LC 29), 18=-116(LC 14), 20=-303(LC 8)  
Max Grav All reactions 250 lb or less at joint(s) 18, 19, 20, 12 except 2=618(LC 17), 17=1020(LC 16), 13=942(LC 17), 11=761(LC 16), 14=748(LC 14), 14=309(LC 1), 16=657(LC 14)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-864/53, 3-4=-668/66, 4-5=-815/176, 5-6=-322/135, 6-7=-326/135, 7-8=-815/157, 8-9=-620/39, 9-10=-770/18, 10-11=-666/30  
BOT CHORD 2-20=0/566, 19-20=0/566, 18-19=0/566, 17-18=0/566, 16-17=0/564, 16-33=0/564, 33-34=0/564, 15-34=0/564, 14-15=0/564, 13-14=0/564  
WEBS 4-17=-635/440, 8-13=-611/375, 10-13=0/522, 5-7=-306/145

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x6 MT20 unless otherwise indicated.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Ceiling dead load (10.0 psf) on member(s). 4-5, 7-8, 5-7; Wall dead load (5.0psf) on member(s).4-17, 8-13
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 16-17, 14-16, 13-14
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 11, 12 except (jt=lb) 17=320, 13=305, 18=116, 20=303.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 72 lb down and 51 lb up at 13-3-4, and 72 lb down and 51 lb up at 15-3-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- Attic room checked for L/360 deflection.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	B2GE	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:42 2023 Page 2  
 ID:MNxubvpAOspM1cCRTzrReHybiS3-k?aVaZ73i1U1nz2FwEzFpinhQaZbQ2aF2i9y\_\_yb9?B

**LOAD CASE(S)** Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-4=-60, 4-5=-80, 5-6=-60, 6-7=-60, 7-8=-80, 8-10=-60, 2-17=-20, 13-17=-40, 11-13=-20, 5-7=-20

Drag: 4-17=-10, 8-13=-10


Concentrated Loads (lb)

Vert: 33=-68 34=-68

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	C1	COMMON	3	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:42 2023 Page 1  
 ID: MNXubvpAOspM1cCRTzrReHybiS3-k?VaZ73i1U1nz2FwEzFpinhvaWfQ?RF2i9y\_\_yb9?B



Scale = 1:69.2

Plate Offsets (X,Y)-- [2:0-5-13,Edge], [10:0-5-13,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.18	Vert(LL)	-0.10	10-12	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.37	Vert(CT)	-0.18	10-12	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.39	Horz(CT)	0.01	10	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.12	10-12	>999		
	Code IRC2015/TPI2014						Weight: 209 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	WEBS 1 Row at midpt 6-14, 6-12
SLIDER Left 2x4 SP No.2 -x 4-2-9, Right 2x4 SP No.2 -x 4-2-9	

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=561/0-3-8 (min. 0-1-8), 14=841/0-3-8 (min. 0-1-8), 10=741/0-3-8 (min. 0-1-8)  
 Max Horz 2=-271(LC 10)  
 Max Uplift 2=-37(LC 13), 14=-69(LC 9), 10=-132(LC 8)  
 Max Grav 2=573(LC 20), 14=992(LC 2), 10=777(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-509/229, 3-15=-424/235, 4-15=-406/261, 4-5=-388/306, 5-16=-362/316,  
 6-16=-342/350, 6-17=-555/623, 7-17=-574/589, 7-8=-606/579, 8-18=-658/532,  
 9-18=-676/506, 9-10=-760/491  
 BOT CHORD 2-19=-142/412, 19-20=-142/412, 14-20=-142/412, 14-21=-57/311, 13-21=-57/311,  
 13-22=-57/311, 12-22=-57/311, 12-23=-270/519, 23-24=-270/519, 10-24=-270/519  
 WEBS 4-14=-468/291, 6-14=-408/234, 8-12=-449/305, 6-12=-668/576

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-9-1 to 3-7-12, Interior(1) 3-7-12 to 12-10-0, Exterior(2) 12-10-0 to 17-2-13, Interior(1) 17-2-13 to 26-5-1 zone; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 14 except (jt=lb) 10=132.
  - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	C1GE	COMMON STRUCTURAL GA	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:43 2023 Page 1  
 ID: MNXubvpAOspM1cCRTzrReHybiS3-CB7mv8hTKcuP7cSUyJUMwKra\_v39TcPHMvVWQyb9?A

-0-10:8 12-10-0 17-10-0 25-8-0 26-6-8  
 0-10-8 12-10-0 5-0-0 7-10-0 0-10-8

Scale = 1:68.7




Plate Offsets (X,Y)-- [7:0-4-0,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.25	Vert(LL) -0.02	8-10	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.17	Vert(CT) -0.04	8-10	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.33	Horz(CT) 0.01	8	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL) 0.02	8-10	>999	240		
	Code IRC2015/TPI2014						Weight: 258 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x8 SP No.1  
 WEBS 2x6 SP No.1 \*Except\*  
 W2: 2x4 SP No.2  
 OTHERS 2x4 SP No.2  
 WEDGE  
 Left: 2x4 SP No.2 , Right: 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS 1 Row at midpt 7-13  
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 10-3-8 except (jt=length) 8=0-3-8, 12=0-3-8.  
 (lb) - Max Horz 2=-339(LC 10)  
 Max Uplift All uplift 100 lb or less at joint(s) 2, 8, 17 except 14=-208(LC 12), 16=-297(LC 12), 13=-400(LC 13)  
 Max Grav All reactions 250 lb or less at joint(s) 17, 15, 13 except 2=341(LC 21), 8=860(LC 20), 14=497(LC 19), 16=372(LC 19), 12=510(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-25=-439/214, 3-25=-403/247, 3-4=-269/29, 6-27=-264/106, 7-27=-287/71, 7-28=-785/66, 8-28=-907/32  
 BOT CHORD 2-17=-243/423, 16-17=-243/423, 15-16=-243/423, 14-15=-243/423, 13-14=-243/423, 12-13=0/606, 11-12=0/606, 11-29=0/606, 10-29=0/606, 10-30=0/606, 8-30=0/606  
 WEBS 7-10=0/529, 5-14=-335/269, 3-16=-397/347, 7-13=-751/352


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -0-9-1 to 3-7-12, Interior(1) 3-7-12 to 12-10-0, Exterior(2) 12-10-0 to 17-2-13, Interior(1) 17-2-13 to 26-5-1 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - 4) All plates are 2x6 MT20 unless otherwise indicated.
  - 5) Gable studs spaced at 2-0-0 oc.
  - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 7) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8, 17 except (jt=lb) 14=208, 16=297, 13=400.
  - 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	D1	ATTIC	9	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:44 2023 Page 1  
 ID: MNXubvpAOSPm1cCRTzrReHybiS3-gOhF\_F9JEekIOHBe2f?jv7sy9O7?uvdYW0e32tyb9?9



6x8 =

Scale = 1:78.6




Plate Offsets (X,Y)-- [2:0-1-0,0-2-0], [3:0-4-0,Edge], [6:0-4-0,Edge], [9:0-4-0,Edge], [10:0-1-0,0-2-0], [13:0-4-0,0-5-12], [15:0-4-0,0-5-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.45	Vert(LL)	-0.17	13-15	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.70	Vert(CT)	-0.28	13-15	>946		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.41	Horz(CT)	0.01	12	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.05	13-15	>999		
	Code IRC2015/TPI2014						Weight: 267 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x10 SP No.1 \*Except\*  
 T1: 2x6 SP No.1  
 BOT CHORD 2x10 SP No.1  
 WEBS 2x6 SP No.1 \*Except\*  
 W2: 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 5-3-11 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 16=1263/0-3-8 (min. 0-1-13), 12=1263/0-3-8 (min. 0-1-13)  
 Max Horz 16=-339(LC 10)  
 Max Grav 16=1549(LC 21), 12=1549(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-1773/0, 3-17=-1644/0, 4-17=-1619/0, 4-18=-1109/107, 5-18=-981/151, 7-19=-981/151,  
 8-19=-1109/107, 8-20=-1618/0, 9-20=-1644/0, 9-10=-1772/0, 2-16=-1756/6,  
 10-12=-1757/6  
 BOT CHORD 15-16=-324/474, 14-15=0/1144, 13-14=0/1144  
 WEBS 5-7=-1292/170, 4-15=0/859, 8-13=0/859, 2-15=0/1033, 10-13=0/1038

**NOTES-**


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-9-2 to 3-7-11, Interior(1) 3-7-11 to 11-4-0, Exterior(2) 11-4-0 to 15-8-13, Interior(1) 15-8-13 to 23-5-2 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Ceiling dead load (10.0 psf) on member(s). 4-5, 7-8, 5-7; Wall dead load (5.0psf) on member(s). 4-15, 8-13
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 13-15
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Attic room checked for L/360 deflection.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	D1GE	ATTIC	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:44 2023 Page 1  
 ID: MNXubvpAOspM1cCRTzrReHybiS3-gOhF\_F9JEeki0HBe2f?jv7sy9O7?uvdYW0e32tyb9?9



6x8 =

Scale = 1:78.6




Plate Offsets (X,Y)-- [2:0-1-0,0-2-0], [3:0-4-0,Edge], [6:0-4-0,Edge], [9:0-4-0,Edge], [10:0-1-0,0-2-0], [13:0-4-0,0-5-12], [15:0-4-0,0-5-12]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.45	Vert(LL)	-0.17 13-15	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.70	Vert(CT)	-0.28 13-15	>946	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.41	Horz(CT)	0.01 12	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.06 13-15	>999	240		
								Weight: 267 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x10 SP No.1 \*Except\*  
 T1: 2x6 SP No.1  
 BOT CHORD 2x10 SP No.1  
 WEBS 2x6 SP No.1 \*Except\*  
 W2: 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 5-3-11 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 16=1263/0-3-8 (min. 0-1-13), 12=1263/0-3-8 (min. 0-1-13)  
 Max Horz 16=-424(LC 10)  
 Max Grav 16=1543(LC 21), 12=1543(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-1789/0, 3-4=-1635/5, 4-5=-1116/188, 7-8=-1116/188, 8-9=-1634/5, 9-10=-1788/0,  
 2-16=-1766/37, 10-12=-1767/37  
 BOT CHORD 15-16=-421/566, 14-15=0/1173, 13-14=0/1173  
 WEBS 5-7=-1284/249, 4-15=0/859, 8-13=0/859, 2-15=-2/1073, 10-13=-10/1080

**NOTES-**

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-9-2 to 3-7-11, Exterior(2) 3-7-11 to 11-4-0, Corner(3) 11-4-0 to 15-8-13, Exterior(2) 15-8-13 to 23-5-2 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Ceiling dead load (10.0 psf) on member(s). 4-5, 7-8, 5-7; Wall dead load (5.0psf) on member(s).4-15, 8-13
- 6) Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 13-15
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Attic room checked for L/360 deflection.

**LOAD CASE(S)** Standard






Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	D3	ATTIC	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:45 2023 Page 1  
 ID: MNXubvpAOspM1cCRTzrReHybiS3-8aFeCb9x?ysceRmqbNWyRLPCboZPdQeikgOcaJyb9?8



6x8 =

Scale = 1:78.6




Plate Offsets (X,Y)-- [3:0-4-0,Edge], [6:0-4-0,Edge], [9:0-4-0,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.15	Vert(LL)	-0.02	13	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.30	Vert(CT)	-0.04	13	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.17	Horz(CT)	0.00	12	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.02	13	>999	240		
									Weight: 265 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x10 SP No.1 \*Except\*  
 T1,T3: 2x6 SP No.1  
 BOT CHORD 2x10 SP No.1  
 WEBS 2x6 SP No.1 \*Except\*  
 W2,W5: 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 0-3-8.  
 (lb) - Max Horz 18=276(LC 9)  
 Max Uplift All uplift 100 lb or less at joint(s) 18 except 16=-249(LC 9)  
 Max Grav All reactions 250 lb or less at joint(s) except 18=999(LC 21), 12=963(LC 21), 16=605(LC 20), 15=997(LC 18)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-968/79, 3-19=-849/82, 4-19=-823/92, 4-20=-759/169, 5-20=-634/183, 7-21=-611/180,  
 8-21=-684/166, 8-9=-694/16, 9-10=-836/1, 2-18=-963/73, 10-12=-814/20  
 BOT CHORD 17-18=-255/297, 16-17=0/531, 15-16=0/531, 14-15=0/531, 13-14=0/531  
 WEBS 5-7=-660/241, 4-17=-351/267, 2-17=-27/584, 10-13=0/465


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-9-2 to 3-7-11, Interior(1) 3-7-11 to 11-4-0, Exterior(2) 11-4-0 to 15-8-13, Interior(1) 15-8-13 to 22-3-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Ceiling dead load (10.0 psf) on member(s). 4-5, 7-8, 5-7; Wall dead load (5.0psf) on member(s).4-17, 8-13
  - Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 16-17, 15-16, 13-15
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 18 except (jt=lb) 16=249.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Attic room checked for L/360 deflection.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Hamett
J0923-5312	D4	ATTIC	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:46 2023 Page 1  
 ID:MNxubvpAOspM1cCRTzrReHybiS3-cmp0PxAZIF\_TGbl1941B\_YyNKBveMturzJ797lyb9?7



Scale = 1:79.1

Plate Offsets (X,Y)-- [2:0-4-0,Edge], [5:0-4-0,Edge], [8:0-4-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.15	Vert(LL) -0.02	12	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.30	Vert(CT) -0.04	12	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.17	Horz(CT) 0.00	11	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL) 0.02	12	>999	240		
	Code IRC2015/TPI2014						Weight: 262 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x10 SP No.1 \*Except\*  
 T1: 2x6 SP No.1  
 BOT CHORD 2x10 SP No.1  
 WEBS 2x6 SP No.1 \*Except\*  
 W2: 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.**

All bearings 0-3-8.  
 (lb) - Max Horz 17=-257(LC 8)  
 Max Uplift All uplift 100 lb or less at joint(s) 17 except 15=-255(LC 9)  
 Max Grav All reactions 250 lb or less at joint(s) except 17=972(LC 21), 11=960(LC 21), 15=598(LC 20), 14=998(LC 18)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-954/77, 2-3=-813/90, 3-19=-758/168, 4-19=-633/182, 6-20=-607/179, 7-20=-680/164,  
 7-8=-691/14, 8-9=-833/0, 1-17=-930/50, 9-11=-811/18  
 BOT CHORD 16-17=-241/284, 15-16=0/529, 14-15=0/529, 13-14=0/529, 12-13=0/529  
 WEBS 4-6=-657/240, 3-16=-362/267, 1-16=-40/598, 9-12=0/462

**NOTES-**


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-12 to 4-10-12, Interior(1) 4-10-12 to 11-4-0, Exterior(2) 11-4-0 to 15-8-13, Interior(1) 15-8-13 to 22-3-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Ceiling dead load (10.0 psf) on member(s). 3-4, 6-7, 4-6; Wall dead load (5.0psf) on member(s).3-16, 7-12
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 15-16, 14-15, 12-14
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 17 except (jt=lb) 15=255.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Attic room checked for L/360 deflection.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	E1	COMMON	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:46 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-cmp0PxAZIF\_TGbL1941B\_YyLfBvxMppgrzJ797lyb9?7



5x5 =

Scale = 1:45.4




Plate Offsets (X,Y)-- [2:Edge,0-4-11], [4:Edge,0-4-11]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.26	Vert(LL)	-0.02	2-6	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.29	Vert(CT)	-0.04	2-6	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.44	Horz(CT)	0.01	4	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.04	4-6	>999	240		
									Weight: 115 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x8 SP No.1  
 WEBS 2x4 SP No.2  
 WEDGE  
 Left: 2x4 SP No.2 , Right: 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=682/0-3-8 (min. 0-1-8), 4=682/0-3-8 (min. 0-1-8)  
 Max Horz 2=-175(LC 10)  
 Max Uplift 2=-84(LC 9), 4=-84(LC 8)  
 Max Grav 2=759(LC 2), 4=759(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-7=-826/578, 3-7=-693/613, 3-8=-693/612, 4-8=-826/577  
 BOT CHORD 2-9=-268/529, 6-9=-268/529, 6-10=-268/529, 4-10=-268/529  
 WEBS 3-6=-539/597

**NOTES-**


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-9-1 to 3-7-12, Interior(1) 3-7-12 to 8-0-0, Exterior(2) 8-0-0 to 12-4-13, Interior(1) 12-4-13 to 16-9-1 zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	E1GE	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:47 2023 Page 1  
 ID:MNxubvpAOspM1cCRTzrReHybiS3-4zNodHBCWZ6KtkwDjoYQWmUWPbGM5Kh\_CzjtfByb9?6



Scale = 1:45.4



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	2-0-0	TC 0.26	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.21	Vert(LL) -0.02 2-6 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.13	Vert(CT) -0.04 2-6 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.01 4 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.02 2-6 >999 240		
				Weight: 145 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x8 SP No.1  
 WEBS 2x4 SP No.2  
 OTHERS 2x4 SP No.2  
 WEDGE  
 Left: 2x4 SP No.2 , Right: 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=682/0-3-8 (min. 0-1-8), 4=682/0-3-8 (min. 0-1-8)  
 Max Horz 2=-219(LC 10)  
 Max Uplift 2=-132(LC 12), 4=-132(LC 13)  
 Max Grav 2=785(LC 19), 4=785(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-883/207, 3-4=-882/207  
 BOT CHORD 2-19=-19/598, 6-19=-19/598, 6-20=-19/598, 4-20=-19/598  
 WEBS 3-6=0/597


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-9-1 to 3-7-12, Exterior(2) 3-7-12 to 8-0-0, Corner(3) 8-0-0 to 12-4-13, Exterior(2) 12-4-13 to 16-9-1 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=132, 4=132.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	G1GE	COMMON SUPPORTED GAB	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:47 2023 Page 1  
ID:MNxubvpAOspM1cCRtZrReHybiS3-4zN0dHBCWZ6KtkwDjoYQWmUaubJB5LB\_CzjtfByb9?6



Scale = 1:43.6

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.03	Vert(LL)	0.00	9	n/r	120	MT20
TCDL 10.0	Lumber DOL	1.15	BC 0.03	Vert(CT)	0.00	9	n/r	120	244/190
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.10	Horz(CT)	0.00	9	n/a	n/a	
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 119 lb FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1  
OTHERS 2x4 SP No.2  
SLIDER Left 2x6 SP No.1 -x 2-6-0, Right 2x6 SP No.1 -x 2-6-0

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 12-8-0.  
(lb) - Max Horz 1=-212(LC 10)  
Max Uplift All uplift 100 lb or less at joint(s) 1, 9 except 14=-114(LC 12), 15=-243(LC 12), 12=-111(LC 13), 11=-233(LC 13)  
Max Grav All reactions 250 lb or less at joint(s) 1, 9, 13, 14, 12, 11 except 15=250(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
WEBS 3-15=-260/254, 7-11=-260/245


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) 0-0-0 to 4-3-13, Exterior(2) 4-3-13 to 6-4-0, Corner(3) 6-4-0 to 10-8-13, Exterior(2) 10-8-13 to 13-5-2 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - 4) All plates are 2x4 MT20 unless otherwise indicated.
  - 5) Gable requires continuous bottom chord bearing.
  - 6) Gable studs spaced at 2-0-0 oc.
  - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 8) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 9 except (jt=lb) 14=114, 15=243, 12=111, 11=233.
  - 10) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 9.
  - 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	G2GDR	COMMON	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:48 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-Y9xmqdCqHtEBVuVPHV4f3z1gc?WFqjj8RdcGBeyb9?5



Scale = 1:45.0

Plate Offsets (X,Y)-- [4:0-6-9,0-1-4], [5:0-5-7,0-1-12]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.36	Vert(LL)	-0.03	4-5	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.55	Vert(CT)	-0.06	4-5	>999	240		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.40	Horz(CT)	0.01	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.02	4-5	>999	240		
									Weight: 228 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
BOT CHORD 2x10 SP No.1  
WEBS 2x4 SP No.2  
WEDGE

Left: 2x4 SP No.2 , Right: 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 1=4464/0-3-8 (min. 0-3-0), 3=3608/0-3-8 (min. 0-2-6)  
Max Horz 1=165(LC 24)  
Max Uplift 1=-225(LC 9), 3=-183(LC 8)  
Max Grav 1=5066(LC 2), 3=4067(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-2=-4499/254, 2-3=-4463/252  
BOT CHORD 1-6=-132/2961, 6-7=-132/2961, 5-7=-132/2961, 5-8=-94/1964, 8-9=-94/1964, 4-9=-94/1964,  
4-10=-113/2935, 3-10=-113/2935  
WEBS 2-5=-128/3298, 2-4=-125/3214

**NOTES-**

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Bottom chords connected as follows: 2x10 - 2 rows staggered at 0-5-0 oc.  
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=225, 3=183.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1382 lb down and 64 lb up at 0-7-4, 1377 lb down and 70 lb up at 2-7-4, 1377 lb down and 70 lb up at 4-7-4, 1377 lb down and 70 lb up at 6-7-4, and 1377 lb down and 70 lb up at 8-7-4, and 1377 lb down and 70 lb up at 10-7-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	G2GDR	COMMON	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:48 2023 Page 2  
 ID:MNxubvpAOspM1cCRTzrReHybiS3-Y9xmqdCqHtEBVuVPHV4f3z1gc?WFqjj8RdcGBeyb9?5

**LOAD CASE(S)** Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-3=-20, 1-2=-60, 2-3=-60

Concentrated Loads (lb)


Vert: 4=-1179(B) 6=-1185(B) 7=-1179(B) 8=-1179(B) 9=-1179(B) 10=-1179(B)



Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	H1GDR	Common Girder	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:48 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-Y9xmqdCqHTEBVuVPHV4f3z1fz?TVqik8RdcGBeyb9?5



Scale: 3/8"=1'

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.40	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.73	Vert(LL) -0.03 1-4 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.47	Vert(CT) -0.06 1-4 >999 240		
BCDL 10.0	Rep Stress Incr NO	Matrix-S	Horz(CT) 0.01 3 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.02 1-4 >999 240		
				Weight: 144 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x8 SP No.1  
 WEBS 2x4 SP No.2  
 WEDGE  
 Left: 2x4 SP No.2 , Right: 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 1=3662/0-3-8 (min. 0-2-3), 3=3867/0-3-8 (min. 0-2-5)  
 Max Horz 1=-114(LC 4)  
 Max Uplift 1=-182(LC 8), 3=-192(LC 9)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-3089/197, 2-3=-3112/198  
 BOT CHORD 1-5=-96/2211, 5-6=-96/2211, 4-6=-96/2211, 4-7=-96/2211, 7-8=-96/2211, 3-8=-96/2211  
 WEBS 2-4=-142/3807

**NOTES-**

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
 Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
 Bottom chords connected as follows: 2x8 - 2 rows staggered at 0-4-0 oc.  
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=182, 3=192.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 2238 lb down and 129 lb up at 1-10-8, 1118 lb down and 66 lb up at 3-11-4, 1118 lb down and 66 lb up at 5-11-4, and 1118 lb down and 66 lb up at 7-11-4, and 1138 lb down and 62 lb up at 10-1-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

**LOAD CASE(S)** Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-2=-60, 2-3=-60, 1-3=-20

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	H1GDR	Common Girder	1	2	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:48 2023 Page 2  
ID:MNxubvpAOspM1cCRTzrReHybiS3-Y9xmqdCqHtEBVuVPHV4f3z1fz?TVqk8RdcGBeyb9?5

**LOAD CASE(S)** Standard


Concentrated Loads (lb)

Vert: 3=-1138(F) 5=-2238(F) 6=-1118(F) 7=-1118(F) 8=-1118(F)


Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	M1GE	GABLE	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:49 2023 Page 1  
ID:MNxubvpAospM1cCRTzrReHybiS3-0LV82yDS2AM2724cqCbucBaw4P\_rZFhfHMqj4yb9?4



Scale = 1:10.8



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.05	Vert(LL) 0.00	1	n/r	120	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.02	Vert(CT) 0.00	1	n/r	120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.04	Horz(CT) -0.00	5	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P					Weight: 21 lb	FT = 20%
	Code IRC2015/TPI2014							

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x6 SP No.1  
WEBS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 4-8-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 4-8-0.  
(lb) - Max Horz 2=66(LC 8)  
Max Uplift All uplift 100 lb or less at joint(s) 5, 6, 2, 7  
Max Grav All reactions 250 lb or less at joint(s) 5, 6, 2, 7

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-10-8 to 3-6-5, Exterior(2) 3-6-5 to 4-8-0 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - 3) Gable requires continuous bottom chord bearing.
  - 4) Gable studs spaced at 2-0-0 oc.
  - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 6) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 6, 2, 7.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	M2	MONOPITCH	4	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:49 2023 Page 1  
ID:MNxubypAOspM1cCRTzrReHybiS3-0LV82yDS2AM2724cqCbucBawJP\_TZFHHfHMqj4yb9?4



Scale = 1:14.7

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.04	Vert(LL) -0.00	2	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.04	Vert(CT) -0.00	2	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT) 0.00	4	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Wind(LL) 0.00	2	****	240		
	Code IRC2015/TPI2014						Weight: 20 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1  
WEBS 2x6 SP No.1

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 2-10-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=160/0-3-8 (min. 0-1-8), 4=88/0-1-8 (min. 0-1-8)  
Max Horz 2=63(LC 12)  
Max Uplift 2=-2(LC 12), 4=-31(LC 12)  
Max Grav 2=160(LC 1), 4=98(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - 5) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	M3	MONOPITCH	6	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:50 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-VY3XFID4pUUvkCfoOw678O65LpKwliXRux5NGWYb9?3



Scale = 1:12.4

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.02	Vert(LL)	-0.00	2 >999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.03	Vert(CT)	-0.00	2 >999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	4 n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P	Wind(LL)	0.00	2 ****	240		
								Weight: 14 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1  
WEBS 2x6 SP No.1

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=125/0-3-8 (min. 0-1-8), 4=59/0-1-8 (min. 0-1-8)  
Max Horz 2=47(LC 12)  
Max Uplift 2=-3(LC 12), 4=-22(LC 12)  
Max Grav 2=125(LC 1), 4=66(LC 19)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - 5) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	VC1	VALLEY	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:50 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-VY3XFID4pUUVkCfoOw678O63Lplpf1Rux5NGWYb9?3




Plate Offsets (X,Y)-- [5:0-0-0,0-0-0], [6:0-0-0,0-0-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.15	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.16	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.22	Horz(CT)	0.01	7	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						
								Weight: 118 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS 1 Row at midpt 4-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 23-5-12.  
 (lb) - Max Horz 1=227(LC 9)  
 Max Uplift All uplift 100 lb or less at joint(s) 1 except 12=-136(LC 12), 13=-126(LC 12), 9=-136(LC 13), 8=-126(LC 13)  
 Max Grav All reactions 250 lb or less at joint(s) 1, 7 except 11=431(LC 22), 12=557(LC 19), 13=396(LC 19), 9=556(LC 20), 8=397(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 WEBS 3-12=-347/247, 2-13=-325/235, 5-9=-347/247, 6-8=-325/235

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 4-9-10, Interior(1) 4-9-10 to 11-9-5, Exterior(2) 11-9-5 to 16-2-2, Interior(1) 16-2-2 to 23-1-13 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) All plates are 2x4 MT20 unless otherwise indicated.
  - 4) Gable requires continuous bottom chord bearing.
  - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 6) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCCL = 10.0psf.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 12=136, 13=126, 9=136, 8=126.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	VC2	VALLEY	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:51 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-zkcvTeEiaodmMME\_yddMhcfEyCef17Ea7brwozyb9?2




Plate Offsets (X,Y)-- [5:0-0-0,0-0-0], [6:0-0-0,0-0-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.16	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.19	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.16	Horz(CT)	0.00	7	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S					Weight: 92 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 19-5-12.  
(lb) - Max Horz 1=-187(LC 8)  
Max Uplift All uplift 100 lb or less at joint(s) 1, 7, 13, 8 except 12=-141(LC 12), 9=-141(LC 13)  
Max Grav All reactions 250 lb or less at joint(s) 1, 7 except 11=437(LC 22), 12=475(LC 19), 13=269(LC 19), 9=475(LC 20), 8=269(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
**WEBS** 3-12=-358/254, 2-13=-271/214, 5-9=-358/254, 6-8=-271/214


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 4-9-10, Interior(1) 4-9-10 to 9-9-5, Exterior(2) 9-9-5 to 14-2-2, Interior(1) 14-2-2 to 19-1-13 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7, 13, 8 except (jt=lb) 12=141, 9=141.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	VC3	VALLEY	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:51 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-zkcvTeEiaodmMME\_yddMhcfE3Ce\_18Ea7brwozyb9?2



Scale = 1:39.2

Plate Offsets (X,Y)-- [4:0-0-0,0-0-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.15	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.17	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.10	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 68 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 15-5-12.  
 (lb) - Max Horz 1=147(LC 11)  
 Max Uplift All uplift 100 lb or less at joint(s) 1 except 8=-141(LC 12), 6=-141(LC 13)  
 Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=409(LC 19), 8=422(LC 19), 6=422(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 WEBS 2-8=-352/253, 4-6=-352/253

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 4-9-10, Interior(1) 4-9-10 to 7-9-5, Exterior(2) 7-9-5 to 12-2-2, Interior(1) 12-2-2 to 15-1-13 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Gable requires continuous bottom chord bearing.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 8=141, 6=141.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


**LOAD CASE(S)** Standard



Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	VC4	VALLEY	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:52 2023 Page 1  
 ID:MNxubvpAOspM1cCRTzrReHybiS3-RwAHg\_FKL5lc\_WoAWL8bDpCP7c?PmcAkLFaUKPyb9?1



Scale = 1:29.3

Plate Offsets (X,Y)-- [4:0-0-0,0-0-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.13	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.09	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.05	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 47 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 11-5-12.  
 (lb) - Max Horz 1=107(LC 9)  
 Max Uplift All uplift 100 lb or less at joint(s) 1, 5 except 8=-125(LC 12), 6=-125(LC 13)  
 Max Grav All reactions 250 lb or less at joint(s) 1, 5, 7 except 8=327(LC 19), 6=327(LC 20)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 WEBS 2-8=-320/253, 4-6=-320/253


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 4-9-10, Interior(1) 4-9-10 to 5-9-5, Exterior(2) 5-9-5 to 10-2-2, Interior(1) 10-2-2 to 11-1-13 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Gable requires continuous bottom chord bearing.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=125, 6=125.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	VC5	VALLEY	1	1	Job Reference (optional)


Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:52 2023 Page 1  
 ID: MNXubvpAOspM1cCRTzrReHybiS3-RwAHg\_FKL5lc\_WoAWL8bDpCPZc?UmcfkLFaUKPyb9?1



4x4 =

Scale = 1:20.7



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL	1.15	TC 0.17	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.08	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.02	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P					Weight: 28 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 OTHERS 2x4 SP No.2

**BRACING-**  
 TOP CHORD  
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=156/7-5-12 (min. 0-1-8), 3=156/7-5-12 (min. 0-1-8), 4=228/7-5-12 (min. 0-1-8)  
 Max Horz 1=-67(LC 8)  
 Max Uplift 1=-24(LC 13), 3=-30(LC 13)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	VC7	VALLEY	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:52 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-RwAHg\_FKL5lc\_WoAWL8bDpCRlc?omc0kLFaUKPyb9?1



Scale = 1:10.0

**Plate Offsets (X,Y)-- [2:0-2-0,Edge]**

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.03	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.06	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P						
	Code IRC2015/TPI2014						Weight: 11 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 3-6-10 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=110/3-5-12 (min. 0-1-8), 3=110/3-5-12 (min. 0-1-8)  
Max Horz 1=-27(LC 8)  
Max Uplift 1=-5(LC 12), 3=-5(LC 13)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	VG1	VALLEY	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:53 2023 Page 1  
ID: MNXubvpAOspM1cCRTzrReHybiS3-v7kftKGy6PtTbfnN32fqm1kZBOKXV2DtavK1sryb9?0



Scale: 3/8"=1'

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.24	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.16	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.07	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2015/TPI2014			Weight: 41 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=211/9-11-2 (min. 0-1-8), 3=211/9-11-2 (min. 0-1-8), 4=322/9-11-2 (min. 0-1-8)  
Max Horz 1=111(LC 9)  
Max Uplift 1=-28(LC 13), 3=-28(LC 13)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - Non Standard bearing condition. Review required.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	VG2	VALLEY	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:53 2023 Page 1  
ID:MNxubvpAOspM1cCRTzrReHybiS3-v7kftKGy6PtTbFNN32fqm1kac0L?V3ztavK1sryb9?0



Scale = 1:22.0

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.15	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.07	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P						
	Code IRC2015/TPI2014						Weight: 26 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1  
OTHERS 2x4 SP No.2

**BRACING-**  
TOP CHORD  
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.  
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=145/6-7-2 (min. 0-1-8), 3=145/6-7-2 (min. 0-1-8), 4=186/6-7-2 (min. 0-1-8)  
Max Horz 1=71(LC 9)  
Max Uplift 1=-26(LC 13), 3=-26(LC 13)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - Non Standard bearing condition. Review required.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	Southern Touch/34 West Preserve/Harnett
J0923-5312	VG3	VALLEY	1	1	Job Reference (optional)

Comtech, Inc., Fayetteville, NC 28309, Curtis Quick

Run: 8.430 s May 12 2021 Print: 8.430 s May 12 2021 MiTek Industries, Inc. Fri Sep 22 08:14:54 2023 Page 1  
ID:MNxubvpAOspM1cCRtZrReHybiS3-NJI15gGbtj?KDpyZdmB3JEHnEQhMEWW0pZ3bPlyb9??



Scale = 1:10.9

Plate Offsets (X,Y)-- [2:0-2-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.03	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.06	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P					Weight: 11 lb	FT = 20%
	Code IRC2015/TPI2014							

**LUMBER-**  
TOP CHORD 2x4 SP No.1  
BOT CHORD 2x4 SP No.1

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 3-3-14 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=105/3-3-2 (min. 0-1-8), 3=105/3-3-2 (min. 0-1-8)  
Max Horz 1=31(LC 9)  
Max Uplift1=-3(LC 13), 3=-3(LC 13)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - Non Standard bearing condition. Review required.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard