Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit

	PROPERTY LOCATION: 92 DEACOIT FIIII NO (SN 1291)	447
ISSUED TO: New Homes Inc	subdivision Duncans Creek	_LOT # 117
NEW REPAIR EXPANSION	Site Improvements required prior to Construction Authorization	ssuance:
Type of Structure: 40'x63'SFD		
Proposed Wastewater System Type: 25% reduction		
Projected Daily Flow: 360 GPD		
Number of bedrooms: 3 Number of Occupants: 6	max	
Basement Yes No		
	on final location and elevations of facilities	
Type of Water Supply: Community Public Well	Distance from well feet Permit valid for:	Five years
Permit conditions:		No expiration
Fernit conditions.		no expiration
11 11		
hadried from hours Mal Wa 25	Date: 11-01-23 SEE ATTACHED	CITE CRETCH
8 -/-		
	ince of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting mprovement Permit shall not be affected by a change in ownership of the site. This permit is subject to complian	
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this perm		
	Construction Analysis adam	
Ţ	Construction Authorization	
	(Required for Building Permit)	
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1	956, 1957, 1958, and 1959 are incorporated by references into this permit and shall be met. Systems shall be	installed in accordance
with the attached system layout.		
ISSUED TO: New Homes Inc	PROPERTY LOCATION: 92 Beacon Hill Rd (SR 1291)	
	SUBDIVISION Duncans Creek	LOT # 117
Facility Type: 40'x63' SFD	New Expansion Repair	
Basement? Yes No Basement Fixtures?		
	· —	600
The second secon	(Initial) Wastewater Flow:	GPD
(See note below, if applicable)		GPD
The second secon		GPD
(See note below, if applicable)pump to 25% red	uction (Repair)	GPD
(See note below, if applicable □) _pump to 25% red Installation Requirements/Conditions Number	uction (Repair) of trenches 1	
(See note below, if applicable)	of trenches 1	
(See note below, if applicable □) pump to 25% red Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size gallons Fixact le	of trenches 1 rench Spacing: 9 Feet of Shall be installed on contour at a Soil Cover: 6 inches	on Center
(See note below, if applicable □)	of trenches 1 ength of each trench 225 feet Trench Spacing: 9 Feet of shall be installed on contour at a feet Trench Depth of: 18-24 inches (Maximum soil cover shall not except the state of the shall be installed on contour at a feet Trench Spacing: 9 Feet of the shall be installed on contour at a feet Trench Spacing: 9 Feet of the shall be installed on contour at a feet Trench Spacing: 9 Feet of the shall be installed on contour at a feet of	on Center
(See note below, if applicable □)	of trenches 1 rench Spacing: 9 Feet of Shall be installed on contour at a Soil Cover: 6 inches	on Center
(See note below, if applicable □)	of trenches 1 ength of each trench 225 feet Trench Spacing: 9 Feet of shall be installed on contour at a feet Trench Depth of: 18-24 inches (Maximum soil cover shall not except the state of the shall be installed on contour at a feet Trench Spacing: 9 Feet of the shall be installed on contour at a feet Trench Spacing: 9 Feet of the shall be installed on contour at a feet Trench Spacing: 9 Feet of the shall be installed on contour at a feet of	on Center
(See note below, if applicable □)	of trenches 1 Ingth of each trench 225 Ingtho	on Center reed
(See note below, if applicable □)	of trenches 1 ength of each trench 225 feet shall be installed on contour at a m Trench Depth of: 18-24 inches bottoms shall be level to +/-1/4" Trench Spacing: 9 Feet Soil Cover: 6 inches (Maximum soil cover shall not exceed bottoms shall be level to +/-1/4" 36" above the trench bottom)	on Center reed inches below pipe
(See note below, if applicable □) pump to 25% red Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Sizegallons Trenches Maximum (Trenchesin all di Pump Requirements:ft. TDH vsGPM	of trenches 1 Ingth of each trench 225 Ingtho	on Center eed inches below pipe inches above pipe
(See note below, if applicable □)	of trenches 1 ength of each trench 225 feet shall be installed on contour at a m Trench Depth of: 18-24 inches bottoms shall be level to +/-1/4" Trench Spacing: 9 Feet Soil Cover: 6 inches (Maximum soil cover shall not exceed bottoms shall be level to +/-1/4" 36" above the trench bottom)	on Center reed inches below pipe
(See note below, if applicable □) pump to 25% red Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Sizegallons Trenches Maximum (Trenchesin all di Pump Requirements:ft. TDH vsGPM	of trenches 1 ength of each trench 225 feet shall be installed on contour at a m Trench Depth of: 18-24 inches bottoms shall be level to +/-1/4" Trench Spacing: 9 Feet Soil Cover: 6 inches (Maximum soil cover shall not exceed bottoms shall be level to +/-1/4" 36" above the trench bottom)	on Center eed inches below pipe inches above pipe
(See note below, if applicable ☐)	of trenches 1 ength of each trench 225 feet shall be installed on contour at a more Trench Depth of: 18-24 inches bottoms shall be level to +/-1/4" Aggregate Depth: Greet Trench Spacing: 9 Feet Soil Cover: 6 inches (Maximum soil cover shall not exceed above the trench bottom) Aggregate Depth:	on Center eed inches below pipe inches above pipe
(See note below, if applicable □)	of trenches 1	on Center eed inches below pipe inches above pipe
(See note below, if applicable □)	of trenches 1 ength of each trench 225 feet Trench Spacing: 9 Feet of shall be installed on contour at a more of trench Depth of: 18-24 inches bottoms shall be level to +/-1/4" FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. Sild AREA.	inches below pipe inches above pipe inches total
(See note below, if applicable □)	of trenches 1 ength of each trench 225 feet Trench Spacing: 9 Feet of shall be installed on contour at a more of trench Depth of: 18-24 inches bottoms shall be level to +/-1/4" FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. Sild AREA.	inches below pipe inches above pipe inches total
(See note below, if applicable □)	of trenches 1	inches below pipe inches above pipe inches total
See note below, if applicable	of trenches 1	inches below pipe inches above pipe inches total
See note below, if applicable	of trenches 1	inches below pipe inches above pipe inches total
See note below, if applicable	of trenches 1 Ingth of each trench 225 feet Trench Spacing: 9 Feet of shall be installed on contour at a soil Cover: 6 inches inches the following shall be level to +/-1/4" FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. SID AREA. The from the type specified on the application. I accept the specifications of this performed use changes. The Construction Authorization shall not be transferred when there is a change in ownership intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership.	inches below pipe inches above pipe inches total
See note below, if applicable	of trenches 1 Ingth of each trench 225 feet Trench Spacing: 9 Feet of shall be installed on contour at a soil Cover: 6 inches inches the following shall be level to +/-1/4" FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. SID AREA. The from the type specified on the application. I accept the specifications of this performed use changes. The Construction Authorization shall not be transferred when there is a change in ownership intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership.	inches below pipe inches above pipe inches total
See note below, if applicable	of trenches 1	inches below pipe inches above pipe inches total
See note below, if applicable	of trenches 1 Ingth of each trench 225 feet Trench Spacing: 9 Feet of shall be installed on contour at a soil Cover: 6 inches inches the following shall be level to +/-1/4" FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. SID AREA. The from the type specified on the application. I accept the specifications of this performed use changes. The Construction Authorization shall not be transferred when there is a change in ownership intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership.	inches below pipe inches above pipe inches total
See note below, if applicable	of trenches 1	inches below pipe inches above pipe inches total

Harnett County Department of Public Health Site Sketch

Issued To: New Homes Inc Subdivision Duncans Creek Lot # _	
	-
Authorized State Agent: Male A PEID Date: 11-01-23	
N 02'11'27" E 260.00'	
120.46' 139.54'	
SETBACK LINES	
117) Scale 65,000 S.F.	
65,000 S.F.	
Scall	
250.00	
□	
S 87.48'33" E 12'0'.	
87.48°33	
(5) 15.0° Z	
40'x63' 38'	
Pump TO FUTUR CAPAIR	
Secretary repair	
1 Pump TO FUT ACLO	
0.0,	
17'	
N 02*11'27" E 260.00'	
BEACON HILL ROAD	

This drawing is for illustrative purposes only. System installation must meet all pertinent laws, rules, and regulations.