



***DIMENSIONS ARE TO SHEATHING.
SHEATHING IS FLUSH WITH FOUNDATION.
*BBO = BEAM BY OTHERS.
*LG1 IS A MIN 2X6 LEDGER.
*LG2 IS A 2X4 LEDGER.**

Products				
PlotID	Length	Product	Plies	Net Qty
H4	6' 0"	1 3/4" x 9 1/4" 2.0E Microllam® LVL	2	2
GDH	20' 0"	1 3/4" x 11 7/8" 2.0E Microllam® LVL	2	2
FBM1	17' 0"	1 3/4" x 14" 2.0E Microllam® LVL	3	3
FBM2	17' 0"	1 3/4" x 14" 2.0E Microllam® LVL	3	3
FBM3	5' 0"	1 3/4" x 14" 2.0E Microllam® LVL	2	2
FBM4	4' 0"	1 3/4" x 14" 2.0E Microllam® LVL	2	2

Truss Connector Total List		
Manuf	Product	Qty
Simpson	HUS26	7
Simpson	LUS410	36

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY

These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult "Bracing of Wood Trusses" available from the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53179.

SHOP DRAWING APPROVAL

THIS LAYOUT IS THE SOLE SOURCE FOR FABRICATION OF TRUSSES AND VOIDS ALL PREVIOUS ARCHITECTURAL OR OTHER TRUSS LAYOUTS. REVIEW AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TRUSSES WILL BE BUILT. VERIFY ALL CONDITIONS TO INSURE AGAINST CHANGES THAT WILL RESULT IN EXTRA CHARGES TO YOU.



APPROVED BY: _____ DATE: _____
REVIEWED BY: _____

Job #: Q2302112	HUGHES 05-24-121	Plan: SCOTLAND-A 1ST FLOOR	APPROVED BY: _____ DATE: _____
Customer: VALUE BUILD HOMES		Date: 1/2/2024	
Site Address: 987 MARKS RD.		Sales Rep: JSL	
City, ST, ZIP: CA, ERPM, NC 28326		Designer: JSP	
		ROOF DATA	
		Roof Area: 2746.5 SF	

