


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	1F01	Floor Supported Gable	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:16

Page: 1

ID:MIJ2KKBYZpBWKx83rzg9ChzzQlk-CPU?ybrnQaSjJw0QBqLmisxEoWrag4?LCyJSPzzQNe



Scale = 1:30.8

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.02	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.02	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 72 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.2(flat)
 OTHERS 2x4 SP No.2(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 16-5-0.

(lb) - Max Grav All reactions 250 (lb) or less at joint
 (s) 16, 17, 18, 19, 20, 21, 22, 23,
 25, 26, 27, 28, 29

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- All plates are 1.5x3 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	1F02	Floor	8	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:18

Page: 1

ID: LGSwXS6P1f7PpuUWOk?NtDzzQgf-ZMI0IvwF750QhvNzNwxPweOxp?UfTPIVUg47czzQNZ



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	I/defl	L/d	PLATES	GRIP		
TCLL	40.0	Plate Grip DOL	1.00	TC	0.53	Vert(LL)	-0.23	15-16	>847	480	MT18HS	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.95	Vert(CT)	-0.31	15-16	>616	240	MT20	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.27	Horz(CT)	0.06	12	n/a	n/a		
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-S								
										Weight: 83 lb	FT = 20%F, 11%E	

LUMBER

TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.2(flat)
 OTHERS 2x4 SP No.2(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.

REACTIONS (lb/size) 12=889/ Mechanical, (min. 0-1-8),
 20=883/0-3-8, (min. 0-1-8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1845/0, 3-4=-2947/0, 4-5=-3410/0,
 5-6=-3410/0, 6-7=-3410/0, 7-8=-2947/0,
 8-9=-2947/0, 9-10=-1846/0
 BOT CHORD 19-20=0/1100, 18-19=0/2556, 17-18=0/3312,
 16-17=0/3312, 15-16=0/3410, 14-15=0/3312,
 13-14=0/2556, 12-13=0/1101
 WEBS 2-20=-1377/0, 10-12=-1381/0, 2-19=0/970,
 10-13=0/969, 3-19=-926/0, 9-13=-925/0,
 3-18=0/509, 9-14=0/509, 4-18=-475/0,
 7-14=-475/0, 4-16=-158/487, 7-15=-158/487,
 5-16=-292/69, 6-15=-292/69

NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are MT20 plates unless otherwise indicated.
- 3) All plates are 3x3 MT20 unless otherwise indicated.
- 4) Refer to girder(s) for truss to truss connections.
- 5) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 6) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 7) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	1F03	Floor	2	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:19

Page: 1

ID:AnSJeZDUbbUEtX0DL8j4QzzQfE-1YsGDewY0QDl2rTaX4RAY7BUMDM6_Ktuk8Pef2zzQNY



Scale = 1:39.2

Plate Offsets (X, Y): [22:0-1-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	Vert(LL)	-0.21	23-25	>944	480	MT18HS	244/190	
TCDL	10.0	Lumber DOL	1.00	BC	Vert(CT)	-0.29	23-25	>685	240	MT20	244/190	
BCLL	0.0	Rep Stress Incr	YES	WB	Horz(CT)	0.04	19	n/a	n/a			
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-S								
											Weight: 112 lb	FT = 20%F, 11%E

LUMBER
TOP CHORD 2x4 SP No.2(flat) *Except* T2:2x4 SP No.1 (flat)
BOT CHORD 2x4 SP No.2(flat) *Except* B2:2x4 SP No.1 (flat)
WEBS 2x4 SP No.2(flat)
OTHERS 2x4 SP No.2(flat)

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS (lb/size) 16=16/ Mechanical, (min. 0-1-8), 19=1573/0-3-8, (min. 0-1-8), 27=806/0-3-8, (min. 0-1-8)
Max Uplift 16=-207 (LC 3)
Max Grav 16=229 (LC 4), 19=1573 (LC 1), 27=809 (LC 10)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1657/0, 3-4=-2594/0, 4-5=-2820/0, 5-6=-2820/0, 6-7=-2820/0, 7-8=-2044/0, 8-9=-713/0, 9-10=0/1535, 10-11=0/1535, 11-12=0/1535, 12-13=-145/805, 13-14=-145/805
BOT CHORD 26-27=0/1002, 25-26=0/2283, 24-25=0/2847, 23-24=0/2847, 22-23=0/2820, 21-22=0/2558, 20-21=0/1540, 19-20=-275/0, 18-19=-805/145, 17-18=-805/145, 16-17=-308/211
WEBS 12-19=-1164/0, 14-16=-264/387, 2-27=-1254/0, 9-19=-1590/0, 2-26=0/852, 9-20=0/1151, 3-26=-815/0, 8-20=-1090/0, 3-25=0/405, 8-21=0/667, 4-25=-337/0, 7-21=-683/0, 4-23=-264/322, 7-22=0/659, 6-22=-383/0, 14-17=-634/0, 13-17=0/264

NOTES
1) Unbalanced floor live loads have been considered for this design.
2) All plates are MT20 plates unless otherwise indicated.
3) All plates are 3x3 MT20 unless otherwise indicated.
4) Refer to girder(s) for truss to truss connections.

- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 207 lb uplift at joint 16.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 7) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 8) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	1F04	Floor	2	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:19

Page: 1

ID:kHAC6MGVoYuW?rMUdKgLQ3zzQcb-1YsGDewY0QDl2rTaX4RAy7BTKDNC_Jiuk8Pef2zzQNY



Scale = 1:44.6

Plate Offsets (X, Y): [19:Edge,0-1-8], [27:0-1-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	I/defl	L/d	PLATES	GRIP		
TCLL	40.0	Plate Grip DOL	1.00	TC	0.91	Vert(LL)	-0.21	28-29	>953	480	MT18HS	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.79	Vert(CT)	-0.28	28-29	>695	240	MT20	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.33	Horz(CT)	0.04	23	n/a	n/a		
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-S								
										Weight: 132 lb	FT = 20%F, 11%E	

LUMBER

- TOP CHORD 2x4 SP No.2(flat)
- BOT CHORD 2x4 SP No.1(flat) *Except* B2:2x4 SP No.2 (flat)
- WEBS 2x4 SP No.2(flat)
- OTHERS 2x4 SP No.2(flat)

BRACING

- TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
- BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS

- All bearings 0-3-8, except 19= Mechanical
- (lb) - Max Uplift All uplift 100 (lb) or less at joint(s) except 19=-574 (LC 3)
- Max Grav All reactions 250 (lb) or less at joint (s) 19 except 20=1040 (LC 14), 23=1504 (LC 3), 31=802 (LC 5)

FORCES

- (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
- TOP CHORD 2-3=-1637/0, 3-4=-2558/0, 4-5=-2760/0, 5-6=-2760/0, 6-7=-2760/0, 7-8=-1963/0, 8-9=-608/0, 9-10=0/1665, 10-11=0/1665, 11-12=0/1665, 12-13=-139/982, 13-14=-139/982, 14-15=-139/982, 15-16=0/1054, 16-17=0/1053
- BOT CHORD 30-31=0/992, 29-30=0/2255, 28-29=0/2800, 27-28=0/2760, 26-27=0/2485, 25-26=0/2485, 24-25=0/1450, 23-24=-430/0, 22-23=-1272/0, 21-22=-982/139, 20-21=-831/0, 19-20=-488/0
- WEBS 12-23=-671/0, 15-20=-482/49, 12-22=0/565, 15-21=-193/253, 13-22=-278/0, 2-31=-1242/0, 9-23=-1549/0, 2-30=0/840, 9-24=0/1166, 3-30=-804/0, 8-24=-1113/0, 3-29=0/395, 8-25=0/683, 4-29=-314/0, 7-25=-700/0, 4-28=-305/285, 7-27=0/698, 17-19=0/764, 17-20=-878/0, 6-27=-406/0

NOTES

- Unbalanced floor live loads have been considered for this design.
- All plates are MT20 plates unless otherwise indicated.
- All plates are 3x3 MT20 unless otherwise indicated.
- Refer to girder(s) for truss to truss connections.

- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 573 lb uplift at joint 19.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	1F05	Floor	7	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:20

Page: 1

ID:OD211Le?yaFKhM4PIHj425zzQap-VlQeQ_wAnkLkf_2m5ozPULketdJHjmy1yo9BCVzzQNX



Scale = 1:45

Plate Offsets (X, Y): [26:0-1-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/def	L/d	PLATES	GRIP		
TCLL	40.0	Plate Grip DOL	1.00	TC	0.95	Vert(LL)	-0.21	27-28	>958	480	MT18HS	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.80	Vert(CT)	-0.28	27-28	>699	240	MT20	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.33	Horz(CT)	-0.04	30	n/a	n/a		
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-S								
										Weight: 130 lb	FT = 20%F, 11%E	

LUMBER

TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.1(flat) *Except* B2:2x4 SP No.2 (flat)
 WEBS 2x4 SP No.2(flat)
 OTHERS 2x4 SP No.2(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS (lb/size) 17=291/0-3-8, (min. 0-1-8),
 22=1747/0-3-8, (min. 0-1-8),
 30=778/0-3-8, (min. 0-1-8)
 Max Uplift 17=-51 (LC 3)
 Max Grav 17=421 (LC 4), 22=1747 (LC 1),
 30=792 (LC 10)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1614/0, 3-4=-2514/0, 4-5=-2688/0,
 5-6=-2688/0, 6-7=-2688/0, 7-8=-1864/0,
 8-9=-483/94, 9-10=0/1917, 10-11=0/1917,
 11-12=0/1917, 12-13=-361/952,
 13-14=-776/527, 14-15=-677/229
 BOT CHORD 29-30=0/980, 28-29=0/2221, 27-28=0/2742,
 26-27=0/2688, 25-26=0/2398, 24-25=0/2398,
 23-24=0/1338, 22-23=-659/0, 21-22=-1286/0,
 20-21=-527/776, 19-20=-527/776,
 18-19=-527/776, 17-18=-66/513
 WEBS 15-17=-641/82, 12-22=-1049/0, 12-21=0/718,
 14-18=-127/380, 13-21=-850/0,
 14-19=-261/0, 13-20=0/283, 9-22=-1578/0,
 2-30=-1227/0, 9-23=0/1182, 2-29=0/825,
 8-23=-1139/0, 3-29=-791/0, 8-24=0/709,
 3-28=0/382, 7-24=-730/0, 4-28=-297/0,
 7-26=0/726, 4-27=-333/250, 6-26=-421/0

NOTES

- Unbalanced floor live loads have been considered for this design.
- All plates are MT20 plates unless otherwise indicated.
- All plates are 3x3 MT20 unless otherwise indicated.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 51 lb uplift at joint 17.

- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	1F06	Floor Supported Gable	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:20

Page: 1

ID:2oJG7F_B7UvDfqnzVsktjCzzQaM-VIQeQ_wAnkLkf_2m5ozPULkrTdvejrp1yo9BCVzzQNX



Scale = 1:45

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.02	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 112 lb	FT = 20%F, 11%E

LUMBER

- TOP CHORD 2x4 SP No.2(flat)
- BOT CHORD 2x4 SP No.2(flat)
- WEBS 2x4 SP No.2(flat)
- OTHERS 2x4 SP No.2(flat)

BRACING

- TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
- BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing, Except:
10-0-0 oc bracing: 26-27,25-26,24-25,23-24.

REACTIONS All bearings 25-11-8.

- (lb) - Max Uplift All uplift 100 (lb) or less at joint(s)
44
- Max Grav All reactions 250 (lb) or less at joint (s)
23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- All plates are 1.5x3 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 44.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	1F07	Floor Supported Gable	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:21

Page: 1

ID:HLxymjq_wSis2NV0Tpy8szzQZQ-VlQeQ_wAnkLkf_2m5ozPULkrTdvUjrp1yo9BCVzzQNX



Scale = 1:19.2

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.02	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.02	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-R							Weight: 39 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.2(flat)
 OTHERS 2x4 SP No.2(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 8-8-0.

(lb) - Max Grav All reactions 250 (lb) or less at joint
 (s) 9, 10, 11, 12, 13, 14, 15, 16

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250
 (lb) or less except when shown.

NOTES

- All plates are 1.5x3 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	1F08	Floor	9	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:21

Page: 1

ID:xBjLMVHh92FBN6uLi7ek0ZzzQYi-zxz0eKxpX2TbH8dyfVUe1YGxv16pSGABBSukxzzQNW



Scale = 1:20.5

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.42	Vert(LL)	-0.06	8-9	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.59	Vert(CT)	-0.08	8-9	>999	240		
BCLL	0.0	Rep Stress Incr	YES	WB	0.14	Horz(CT)	0.01	7	n/a	n/a		
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 45 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.2(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 7=463/ Mechanical, (min. 0-1-8),
 11=463/ Mechanical, (min. 0-1-8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-899/0, 3-4=-899/0, 4-5=-766/0
 BOT CHORD 10-11=0/526, 9-10=0/899, 8-9=0/899,
 7-8=0/561
 WEBS 2-11=-660/0, 5-7=-704/0, 2-10=0/499,
 5-8=0/267

NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) Refer to girder(s) for truss to truss connections.
- 3) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 4) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard


Job Q2302112	Truss 1F09	Truss Type Floor Supported Gable	Qty 1	Ply 1	Hughes Job Reference (optional)
-----------------	---------------	-------------------------------------	----------	----------	------------------------------------

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.620 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:21

Page: 1

ID:i?joc2aMGkPdyI9gtabXrzzyJ-zxz0eKxpX2TbH8dyfVUe1YGD01FPSI3BBSukxzzQNW



Scale = 1:18.3

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.04	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.02	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-R							Weight: 18 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.2(flat)
 OTHERS 2x4 SP No.2(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-1-12 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 5=68/3-1-12, (min. 0-1-8),
 6=147/3-1-12, (min. 0-1-8),
 7=102/3-1-12, (min. 0-1-8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	1F10	Floor Supported Gable	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:21

Page: 1

ID:B?sSXqC_1iyF7xH8joWodozzQXV-zxz0eKxpX2TbH8dyfVUe1YG0D1FjSI3BBSukxzzQNW



Scale = 1:19.2

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.02	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.02	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-R							Weight: 18 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.2(flat)
 OTHERS 2x4 SP No.2(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-3-8 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 3-3-8.

(lb) - Max Grav All reactions 250 (lb) or less at joint (s) 5, 6, 7, 8

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	1F11	Floor Supported Gable	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:22

Page: 1

ID:Q?RH_jWlviEZExG8EG_uhHzzQX5-zxz0eKxpX2TbH8dyfVUe1YG0D1FtSI3BBSukxzzQNW



Scale = 1:25.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.02	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 58 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.2(flat)
 OTHERS 2x4 SP No.2(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 12-11-8.

(lb) - Max Grav All reactions 250 (lb) or less at joint
 (s) 12, 13, 14, 15, 16, 17, 18, 19,
 20, 21, 22

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- All plates are 1.5x3 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	1F12	Floor	6	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:23

Page: 1

ID:zFdkuhMe6PO?TluM8BiXrLzzQUj-wK5m3?z33fjW5nLmwW66zMJZqmZwAvUemNroqzzQNU



Scale = 1:29.2

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.28	Vert(LL)	-0.09	12-13	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.70	Vert(CT)	-0.13	12-13	>999	240		
BCLL	0.0	Rep Stress Incr	YES	WB	0.19	Horz(CT)	0.03	9	n/a	n/a		
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 68 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.2(flat)
 OTHERS 2x4 SP No.2(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 9=693/0-3-8, (min. 0-1-8), 16=699/Mechanical, (min. 0-1-8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1365/0, 3-4=-2037/0, 4-5=-2111/0, 5-6=-2037/0, 6-7=-1364/0
 BOT CHORD 15-16=0/855, 14-15=0/1839, 13-14=0/2111, 12-13=0/2111, 11-12=0/2111, 10-11=0/1839, 9-10=0/855
 WEBS 2-16=-1073/0, 7-9=-1070/0, 2-15=0/663, 7-10=0/663, 3-15=-618/0, 6-10=-618/0, 3-14=0/357, 6-11=0/357, 4-14=-349/78, 5-11=-349/78

NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are 3x3 MT20 unless otherwise indicated.
- 3) Refer to girder(s) for truss to truss connections.
- 4) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 5) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 6) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	1F13	Floor	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:23

Page: 1

ID: iLRxXc7DjGnH_k2QirKmm7zzQSR-wK5m3?z33fjWsnLmwW66zMJZqmswAvUemNroqzzQNU




Plate Offsets (X, Y): [17:0-1-8,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.28	Vert(LL)	-0.09	12-13	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.68	Vert(CT)	-0.12	12-13	>999	240		
BCLL	0.0	Rep Stress Incr	YES	WB	0.19	Horz(CT)	0.03	9	n/a	n/a		
BCDL	5.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 69 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.2(flat)
 OTHERS 2x4 SP No.2(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 9=683/0-3-8, (min. 0-1-8), 16=695/Mechanical, (min. 0-1-8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 2-3=-1356/0, 3-4=-2020/0, 4-5=-2093/0, 5-6=-2026/0, 6-7=-1379/0
 BOT CHORD 15-16=0/851, 14-15=0/1826, 13-14=0/2093, 12-13=0/2093, 11-12=0/2093, 10-11=0/1843, 9-10=0/881
 WEBS 2-16=-1067/0, 7-9=-1083/0, 2-15=0/658, 7-10=0/649, 3-15=-612/0, 6-10=-603/0, 3-14=0/348, 6-11=0/340, 4-14=-338/76, 5-11=-327/86

NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are 3x3 MT20 unless otherwise indicated.
- 3) Refer to girder(s) for truss to truss connections.
- 4) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 5) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 6) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	A01	Common	2	1	Job Reference (optional)



Scale = 1:55.8

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20 244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.08	Vert(CT)	n/a	-	n/a	999	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.13	Horz(CT)	0.00	15	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS							Weight: 167 lb FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.
 WEBS 1 Row at midpt 9-21

REACTIONS All bearings 25-11-8.
 (lb) - Max Horiz 2=155 (LC 11), 31=155 (LC 11)
 Max Uplift All uplift 100 (lb) or less at joint(s)
 16, 17, 18, 19, 20, 22, 24, 25, 26, 27
 Max Grav All reactions 250 (lb) or less at joint
 (s) 2, 15, 16, 17, 18, 19, 20, 21, 22, 24, 25, 26, 27, 28, 31

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=2ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) -0-11-0 to 2-11-12, Exterior(2N) 2-11-12 to 12-11-12, Corner(3R) 12-11-12 to 16-11-12, Exterior(2N) 16-11-12 to 25-11-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) All plates are 2x4 MT20 unless otherwise indicated.
- 5) Gable requires continuous bottom chord bearing.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 22, 24, 25, 26, 27, 20, 19, 18, 17, 16.
 - 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 11) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- LOAD CASE(S)** Standard




Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	A02	Common	12	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:24

Page: 1

ID:EZjksCXNt8nMC0tEYl4dCQzzRBh-OWf9GLzhqzr98cMXKd1LfbuRME2Bfb7dtQ7PLGzzQNT



Scale = 1:56.4

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	I/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.47	Vert(LL)	-0.32	8-10	>973	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.93	Vert(CT)	-0.47	8-10	>659	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.32	Horz(CT)	0.04	7	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS							Weight: 129 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.


REACTIONS (lb/size) 2=1094/0-3-8, (min. 0-1-8),
 7=1037/ Mechanical, (min. 0-1-8)
 Max Horiz 2=155 (LC 11)
 Max Uplift 2=-3 (LC 12)
 Max Grav 2=1221 (LC 17), 7=1170 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1667/49, 3-4=-1599/82, 4-17=-1534/93,
 5-17=-1501/120, 5-18=-1504/123,
 6-18=-1603/92, 6-7=-1671/51
 BOT CHORD 2-10=-10/1442, 9-10=0/918, 9-19=0/918,
 19-20=0/918, 8-20=0/918, 7-8=0/1338
 WEBS 6-8=-381/135, 5-10=-22/832, 5-8=-24/838,
 3-10=-378/135

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -0-11-0 to 3-1-0, Interior (1) 3-1-0 to 12-11-12, Exterior (2R) 12-11-12 to 16-11-12, Interior (1) 16-11-12 to 25-11-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Refer to girder(s) for truss to truss connections.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 3 lb uplift at joint 2.

- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 8) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- LOAD CASE(S)** Standard

Job Q2302112	Truss A03	Truss Type Common	Qty 7	Ply 1	Hughes Job Reference (optional)
-----------------	--------------	----------------------	----------	----------	------------------------------------



Scale = 1:67.8

Loading	(psf)	Spacing	2-0-0	CSI	0.45	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.45	Vert(LL)	-0.41	9	>762	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.92	Vert(CT)	-0.65	9	>478	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.51	Horz(CT)	0.05	7	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS							Weight: 143 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.1 *Except* B2:2x4 SP No.2
WEBS 2x4 SP No.3

7) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

BRACING
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied. Except:
6-0-0 oc bracing: 10-13

LOAD CASE(S) Standard

REACTIONS (lb/size) 2=1181/0-3-8, (min. 0-1-10),
7=1124/ Mechanical, (min. 0-1-8)
Max Horiz 2=155 (LC 11)
Max Grav 2=1398 (LC 17), 7=1348 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 2-3=-2014/0, 3-4=-1926/0, 4-21=-1861/0,
5-21=-1829/24, 5-22=-1833/27,
6-22=-1930/0, 6-7=-2000/0

BOT CHORD 2-14=0/1712, 12-14=0/1207, 12-23=0/1207,
9-23=0/1207, 9-24=0/1207, 24-25=0/1207,
8-25=0/1207, 7-8=0/1608

WEBS 5-10=0/1043, 8-10=-6/872, 6-8=-374/138,
13-14=-5/867, 5-13=0/1038, 3-14=-372/138

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft;
B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B;
Enclosed; MWFRS (directional) and C-C Exterior(2E)
-0-11-0 to 3-1-0, Interior (1) 3-1-0 to 12-11-12, Exterior (2R) 12-11-12 to 16-11-12, Interior (1) 16-11-12 to 25-11-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Refer to girder(s) for truss to truss connections.
 - 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	B01	Common Supported Gable	1	1	Job Reference (optional)



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.12	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.06	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.06	Horz(CT)	0.00	6	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS							Weight: 36 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.

REACTIONS All bearings 7-8-8.
 (lb) - Max Horiz 2=54 (LC 11), 11=54 (LC 11)
 Max Uplift All uplift 100 (lb) or less at joint(s)
 2, 6, 8, 10, 11, 17
 Max Grav All reactions 250 (lb) or less at joint
 (s) 2, 6, 8, 10, 11, 17 except 9=306
 (LC 1)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250
 (lb) or less except when shown.


WEBS 4-9=-283/95

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=2ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) -0-11-0 to 3-1-0, Exterior(2N) 3-1-0 to 3-10-4, Corner (3R) 3-10-4 to 7-8-8, Exterior(2N) 7-8-8 to 8-7-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 2, 6, 10, 8, 2, 6.

- Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 6.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Job Q2302112	Truss C01	Truss Type Common Structural Gable	Qty 1	Ply 1	Hughes Job Reference (optional)
-----------------	--------------	---------------------------------------	----------	----------	------------------------------------



Scale = 1:53.9

Plate Offsets (X, Y): [8:0-2-0,0-2-0], [14:0-1-6,0-1-8], [21:0-2-8,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	I/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.46	Vert(LL)	-0.04	16-34	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.31	Vert(CT)	-0.08	16-34	>999	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.28	Horz(CT)	0.00	14	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS								
										Weight: 147 lb	FT = 20%	

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
JOINTS 1 Brace at Jt(s): 25, 27

REACTIONS All bearings 12-10-8, except 14=0-3-8, 13=0-1-8
(lb) - Max Horiz 2=-124 (LC 10), 29=-124 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 2, 13, 19, 21, 22, 23, 29
Max Grav All reactions 250 (lb) or less at joint (s) 2, 13, 19, 20, 21, 22, 23, 29 except 14=279 (LC 1), 17=798 (LC 24), 18=274 (LC 1)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 9-35=0/276, 12-13=-330/0, 13-14=-265/0
WEBS 8-27=0/375, 16-27=0/417, 16-24=-311/0, 8-18=-255/0, 9-27=-707/0, 17-27=-752/0

NOTES
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -0-11-0 to 3-1-0, Interior (1) 3-1-0 to 10-0-1, Exterior(2R) 10-0-1 to 14-1-12, Interior (1) 14-1-12 to 21-2-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
4) All plates are 2x4 MT20 unless otherwise indicated.
5) Gable studs spaced at 2-0-0 oc.

6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
8) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 13.
9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 2, 21, 19, 22, 23, 13, 2.
10) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 13.
11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
12) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard
1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.00
Uniform Loads (lb/ft)
Vert: 1-8=-60, 8-15=-60, 29-32=-20
Concentrated Loads (lb)
Vert: 35=-635


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	C02	Common	5	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:26

Page: 1

ID:RCKRYxLuEQ0R1gcp8TE1cLzR83-Kvnhv1?xMa5tNvWwR23pkc_qp2qj7W?wLkcVP8zzQNR



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.28	Vert(LL)	-0.07	8-10	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.54	Vert(CT)	-0.11	10-13	>999	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.23	Horz(CT)	0.03	6	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS								
											Weight: 103 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS (lb/size) 2=867/0-3-8, (min. 0-1-8),
6=867/0-3-8, (min. 0-1-8)
Max Horiz 2=-126 (LC 10)
Max Uplift 2=-6 (LC 12), 6=-6 (LC 12)
Max Grav 2=955 (LC 17), 6=955 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250
(lb) or less except when shown.
TOP CHORD 2-3=-1251/45, 3-17=-1171/61,
4-17=-1095/91, 4-18=-1095/91,
5-18=-1172/61, 5-6=-1251/45
BOT CHORD 2-10=0/1092, 9-10=0/714, 9-19=0/714,
19-20=0/714, 8-20=0/714, 6-8=0/1010
WEBS 4-8=-17/587, 5-8=-289/104, 4-10=-17/587,
3-10=-289/104

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft;
B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B;
Enclosed; MWFRS (directional) and C-C Exterior(2E)
-0-11-0 to 3-1-0, Interior (1) 3-1-0 to 10-1-12, Exterior (2R) 10-1-12 to 14-1-12, Interior (1) 14-1-12 to 21-2-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 6 lb uplift at joint 2 and 6 lb uplift at joint 6.

- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 7) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	C03	Common	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:26

Page: 1

ID:JvbshtofotrMyxHHxcYgzzR7u-Kvnhv1?xMa5fNvWwR23pkc_qg2ql7W?wLkcVP8zzQNR



Scale = 1:47.9

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.29	Vert(LL)	-0.07	6-8	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.54	Vert(CT)	-0.12	8-11	>999	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.23	Horz(CT)	0.03	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS								
											Weight: 100 lb	FT = 20%

LUMBER **LOAD CASE(S)** Standard

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3


BRACING
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.

REACTIONS (lb/size) 1=812/0-3-8, (min. 0-1-8),
 5=812/0-3-8, (min. 0-1-8)
 Max Horiz 1=-116 (LC 10)
 Max Grav 1=905 (LC 17), 5=905 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1257/49, 2-15=-1178/66, 3-15=-1102/95,
 3-16=-1102/95, 4-16=-1178/66, 4-5=-1258/49
 BOT CHORD 1-8=-17/1093, 7-8=0/712, 7-17=0/712,
 17-18=0/712, 6-18=0/712, 5-6=0/1010
 WEBS 3-6=-18/593, 4-6=-293/105, 3-8=-18/593,
 2-8=-293/105

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust)
 Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft;
 B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B;
 Enclosed; MWFRS (directional) and C-C Exterior(2E)
 0-0-0 to 4-0-0, Interior (1) 4-0-0 to 10-1-12, Exterior(2R)
 10-1-12 to 14-1-12, Interior (1) 14-1-12 to 20-3-8 zone;
 cantilever left and right exposed; end vertical left and
 right exposed; C-C for members and forces & MWFRS
 for reactions shown; Lumber DOL=1.60 plate grip
 DOL=1.60
 - This truss has been designed for a 10.0 psf bottom
 chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf
 on the bottom chord in all areas where a rectangle
 3-06-00 tall by 2-00-00 wide will fit between the bottom
 chord and any other members, with BCDL = 10.0psf.
 - This truss is designed in accordance with the 2018
 International Residential Code sections R502.11.1 and
 R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16"
 structural wood sheathing be applied directly to the top
 chord and 1/2" gypsum sheetrock be applied directly to
 the bottom chord.

Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	C04	Common Girder	1	3	Job Reference (optional)



Scale = 1:46.8

Plate Offsets (X, Y): [1:0-1-12,0-1-1], [5:0-1-12,0-1-1], [6:0-4-0,0-4-12], [8:0-4-0,0-4-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	Vert(LL)	-0.12	6-12	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	Vert(CT)	-0.23	6-12	>999	180		
BCLL	0.0*	Rep Stress Incr	NO	WB	Horz(CT)	0.04	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-MS						Weight: 348 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP DSS
 WEBS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=5675/0-3-8, (min. 0-2-3), 5=5712/0-3-8, (min. 0-2-4)
 Max Horiz 1=-116 (LC 6)
 Max Grav 1=6552 (LC 13), 5=6699 (LC 14)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-9856/0, 2-3=-9507/0, 3-4=-9714/0, 4-5=-9787/0
 BOT CHORD 1-13=0/8051, 13-14=0/8051, 14-15=0/8051, 8-15=0/8051, 7-8=0/5466, 7-16=0/5466, 16-17=0/5466, 17-18=0/5466, 18-19=0/5466, 6-19=0/5466, 6-20=0/8144, 20-21=0/8144, 21-22=0/8144, 5-22=0/8144
 WEBS 3-6=0/5988, 4-6=-359/67, 3-8=0/5592, 2-8=-352/69


- 4) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1135 lb down at 2-0-12, 1135 lb down at 4-0-12, 1313 lb down at 6-0-12, 1311 lb down at 8-0-12, 1298 lb down at 10-0-12, 1310 lb down at 12-0-12, 1313 lb down at 14-0-12, and 1313 lb down at 15-9-12, and 1313 lb down at 18-0-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.00
 Uniform Loads (lb/ft)
 Vert: 1-3=-60, 3-5=-60, 1-5=-20
 Concentrated Loads (lb)
 Vert: 7=-1104, 13=-1017, 14=-1017, 15=-1104, 17=-1104, 19=-1104, 20=-1104, 21=-1104, 22=-1104

- NOTES**
- 1) 3-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-5-0 oc.
 Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - 2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - 3) Unbalanced roof live loads have been considered for this design.

Job Q2302112	Truss D01	Truss Type Common Supported Gable	Qty 1	Ply 1	Hughes Job Reference (optional)
-----------------	--------------	--------------------------------------	----------	----------	------------------------------------



Scale = 1:50

Plate Offsets (X, Y): [20:0-2-8,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.09	Horz(CT)	0.00	12	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS							Weight: 116 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS All bearings 19-11-0.

(lb) - Max Horiz 2--124 (LC 10), 23--124 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s)
2, 14, 15, 16, 17, 19, 20, 21, 22, 23
Max Grav All reactions 250 (lb) or less at joint
(s) 2, 12, 14, 15, 16, 17, 18, 19, 20,
21, 22, 23, 26

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250
(lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft;
B=58ft; L=40ft; eave=2ft; Ke=1.00; Cat. II; Exp B;
Enclosed; MWFRS (directional) and C-C Corner(3E)
-0-11-0 to 3-1-0, Exterior(2N) 3-1-0 to 9-11-8, Corner(3R)
9-11-8 to 13-11-8, Exterior(2N) 13-11-8 to 20-10-0 zone;
cantilever left and right exposed; end vertical left and
right exposed; C-C for members and forces & MWFRS
for reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60
- Truss designed for wind loads in the plane of the truss
only. For studs exposed to wind (normal to the face),
see Standard Industry Gable End Details as applicable,
or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.

- Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 100 lb uplift at joint
(s) 2, 19, 20, 21, 22, 17, 16, 15, 14, 2.
- Beveled plate or shim required to provide full bearing
surface with truss chord at joint(s) 26.
- This truss is designed in accordance with the 2018
International Residential Code sections R502.11.1 and
R802.10.2 and referenced standard ANSI/TPI 1.
- This truss design requires that a minimum of 7/16"
structural wood sheathing be applied directly to the top
chord and 1/2" gypsum sheetrock be applied directly to
the bottom chord.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	D02	Common	2	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:27

Page: 1

ID:HWJ7LU3zo2vH3US6SlnLMizzR5r-o5LHvN0a7uDk?356?mb2HpW_0S5hsz63ZOL3xbzzQNQ



Scale = 1:50.4

Plate Offsets (X, Y): [1:0-6-0,0-0-5], [5:0-6-0,0-0-5], [7:0-4-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	Vert(LL)	-0.15	7-10	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	Vert(CT)	-0.32	7-10	>740	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	Horz(CT)	0.02	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS						Weight: 94 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.

REACTIONS (lb/size) 1=795/0-3-8, (min. 0-1-8),
 5=853/0-3-8, (min. 0-1-8)

Max Horiz 1=-121 (LC 10)
 Max Uplift 5=-7 (LC 12)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-1099/65, 2-14=-844/37, 3-14=-753/67,
 3-15=-753/66, 4-15=-844/39, 4-5=-1096/63
 BOT CHORD 1-7=-25/882, 5-7=0/878
 WEBS 3-7=0/599, 4-7=-319/98, 2-7=-323/99

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust)
 Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft;
 B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B;
 Enclosed; MWFRS (directional) and C-C Exterior(2E)
 0-0-0 to 4-0-0, Interior (1) 4-0-0 to 9-11-8, Exterior(2R)
 9-11-8 to 13-11-8, Interior (1) 13-11-8 to 20-10-0 zone;
 cantilever left and right exposed; end vertical left and
 right exposed; C-C for members and forces & MWFRS
 for reactions shown; Lumber DOL=1.60 plate grip
 DOL=1.60
- This truss has been designed for a 10.0 psf bottom
 chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf
 on the bottom chord in all areas where a rectangle
 3-06-00 tall by 2-00-00 wide will fit between the bottom
 chord and any other members.
- Provide mechanical connection (by others) of truss to
 bearing plate capable of withstanding 7 lb uplift at joint 5.
- This truss is designed in accordance with the 2018
 International Residential Code sections R502.11.1 and
 R802.10.2 and referenced standard ANSI/TPI 1.

7) This truss design requires that a minimum of 7/16"
 structural wood sheathing be applied directly to the top
 chord and 1/2" gypsum sheetrock be applied directly to
 the bottom chord.

LOAD CASE(S) Standard

Job Q2302112	Truss D03	Truss Type Common	Qty 1	Ply 1	Hughes Job Reference (optional)
-----------------	--------------	----------------------	----------	----------	------------------------------------




Plate Offsets (X, Y): [1:0-6-0,0-0-5], [5:0-6-0,0-0-5], [6:0-4-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.38	Vert(LL)	-0.15	6-9	>999	240	MT20 244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.88	Vert(CT)	-0.32	6-9	>740	180	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.24	Horz(CT)	0.02	5	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS							Weight: 92 lb FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS (lb/size) 1=797/0-3-8, (min. 0-1-8),
5=797/0-3-8, (min. 0-1-8)
Max Horiz 1=113 (LC 11)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-1101/66, 2-13=-847/38, 3-13=-755/68,
3-14=-755/68, 4-14=-847/38, 4-5=-1101/66
BOT CHORD 1-6=-38/884, 5-6=0/884
WEBS 3-6=0/600, 4-6=-323/99, 2-6=-323/99

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft;
B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B;
Enclosed; MWFRS (directional) and C-C Exterior(2E)
0-0-0 to 4-0-0, Interior (1) 4-0-0 to 9-11-8, Exterior(2R)
9-11-8 to 13-11-8, Interior (1) 13-11-8 to 19-11-0 zone;
cantilever left and right exposed ; end vertical left and
right exposed;C-C for members and forces & MWFRS
for reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60
 - This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
 - This truss is designed in accordance with the 2018
International Residential Code sections R502.11.1 and
R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16"
structural wood sheathing be applied directly to the top
chord and 1/2" gypsum sheetrock be applied directly to
the bottom chord.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	E01	Common	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:28

Page: 1

ID:FXcRA2JCJ70XYTP5Y8fjaEzzR4D-GHuf6j1CuBLbdDf1ZT6Hp13A?rYobQBDo25cU1zzQNP



Scale = 1:43.2

Plate Offsets (X, Y): [22:0-2-8,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	Vert(LL)	0.07	19	>999	240	MT20	244/190	
TCDL	10.0	Lumber DOL	1.15	BC	Vert(CT)	-0.09	21-22	>999	180			
BCLL	0.0*	Rep Stress Incr	YES	WB	Horz(CT)	0.04	14	n/a	n/a			
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS								
											Weight: 116 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.
 JOINTS 1 Brace at Jt(s): 25, 27

REACTIONS (lb/size) 2=853/0-3-0, (min. 0-1-8),
 14=853/0-3-0, (min. 0-1-8)

Max Horiz 2=-82 (LC 10)

Max Uplift 2=-168 (LC 12), 14=-168 (LC 12)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250

(lb) or less except when shown.

TOP CHORD 2-3=-1383/913, 3-35=-1374/926,
 4-35=-1349/931, 4-5=-1295/896,
 5-6=-993/693, 6-7=-930/662, 7-8=-910/679,
 8-9=-910/679, 9-10=-930/662,
 10-11=-993/693, 11-12=-1295/896,
 12-36=-1349/931, 13-36=-1374/926,
 13-14=-1383/913
 BOT CHORD 2-24=-772/1210, 24-37=-772/1210,
 23-37=-772/1210, 22-23=-772/1210,
 21-22=-772/1210, 20-21=-772/1210,
 19-20=-776/1210, 18-19=-776/1210,
 17-18=-776/1210, 17-38=-776/1210,
 16-38=-776/1210, 14-16=-776/1210
 WEBS 8-20=-503/603, 20-27=-477/360,
 27-28=-461/348, 11-28=-456/341,
 5-26=-456/341, 25-26=-461/348,
 20-25=-477/360

NOTES

1) Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=115mph (3-second gust)
 Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft;
 B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B;
 Enclosed; MWFRS (directional) and C-C Exterior(2E)
 -0-10-8 to 3-1-8, Interior (1) 3-1-8 to 10-0-0, Exterior(2R)
 10-0-0 to 14-0-0, Interior (1) 14-0-0 to 20-10-8 zone;
 cantilever left and right exposed; end vertical left and
 right exposed; porch left and right exposed; C-C for
 members and forces & MWFRS for reactions shown;
 Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss
 only. For studs exposed to wind (normal to the face),
 see Standard Industry Gable End Details as applicable,
 or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom
 chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf
 on the bottom chord in all areas where a rectangle
 3-06-00 tall by 2-00-00 wide will fit between the bottom
 chord and any other members.
- Provide mechanical connection (by others) of truss to
 bearing plate capable of withstanding 168 lb uplift at joint
 2 and 168 lb uplift at joint 14.
- This truss is designed in accordance with the 2018
 International Residential Code sections R502.11.1 and
 R802.10.2 and referenced standard ANSI/TPI 1.
- This truss design requires that a minimum of 7/16"
 structural wood sheathing be applied directly to the top
 chord and 1/2" gypsum sheetrock be applied directly to
 the bottom chord.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	E02	Common	6	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:29

Page: 1

ID:urK_j9tKUhWq_JKPFfsX3lzzR41-kUS2J31qfVTSENEV7BdWMEcJJfmrKszM1iqA0TzzQNO



Scale = 1:43.2

Plate Offsets (X, Y): [8:0-4-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	Vert(LL)	0.29	8-14	>828	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	Vert(CT)	-0.33	8-11	>723	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	Horz(CT)	0.03	6	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS						Weight: 89 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS (lb/size) 2=853/0-3-0, (min. 0-1-8),
6=853/0-3-0, (min. 0-1-8)
Max Horiz 2=-82 (LC 10)
Max Uplift 2=-168 (LC 12), 6=-168 (LC 12)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250
(lb) or less except when shown.
TOP CHORD 2-15=-1343/813, 3-15=-1285/835,
3-16=-1010/714, 4-16=-937/737,
4-17=-937/737, 5-17=-1010/714,
5-18=-1285/835, 6-18=-1343/813
BOT CHORD 2-19=-707/1176, 19-20=-707/1176,
8-20=-707/1176, 8-21=-710/1176,
21-22=-710/1176, 6-22=-710/1176
WEBS 4-8=-577/604, 5-8=-396/225, 3-8=-396/225

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft;
B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B;
Enclosed; MWFRS (directional) and C-C Exterior(2E)
-0-10-8 to 3-1-8, Interior (1) 3-1-8 to 10-0-0, Exterior(2R)
10-0-0 to 14-0-0, Interior (1) 14-0-0 to 20-10-8 zone;
cantilever left and right exposed; end vertical left and
right exposed; porch left and right exposed; C-C for
members and forces & MWFRS for reactions shown;
Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
 - Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 168 lb uplift at joint
2 and 168 lb uplift at joint 6.

- This truss is designed in accordance with the 2018
International Residential Code sections R502.11.1 and
R802.10.2 and referenced standard ANSI/TPI 1.
- This truss design requires that a minimum of 7/16"
structural wood sheathing be applied directly to the top
chord and 1/2" gypsum sheetrock be applied directly to
the bottom chord.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	P01	Monopitch	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:29

Page: 1

ID: xSK6MK296SFPueuD8BSxUOzzRK3-kUS2J31qVTSENEV7BdWMEcMrFwgKw2M1iqA0TzzQNO



Scale = 1:32.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.23	Vert(LL)	0.03	6-9	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.27	Vert(CT)	-0.06	6-9	>999	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.02	Horz(CT)	0.00	2	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS							Weight: 22 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Rigid ceiling directly applied.

REACTIONS (lb/size) 2=290/0-4-8, (min. 0-1-8),
5=182/0-1-8, (min. 0-1-8)
Max Horiz 2=66 (LC 11)
Max Uplift 2=-32 (LC 12)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft;
B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B;
Enclosed; MWFRS (directional) and C-C Exterior(2E)
-1-4-11 to 2-7-5, Interior (1) 2-7-5 to 4-10-4 zone;
cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) Gable studs spaced at 2-0-0 oc.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 6) Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 7) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 5.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 32 lb uplift at joint 2.

- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	P02	Monopitch	6	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:30

Page: 1

ID: ?cGC4GREaHhskZLM0v1Rn8zzRJZ-Cg0QXP2SQpbJsXphgu8luS8WUfGX3MbWFMajYwzzQNN



Scale = 1:32.4

Plate Offsets (X, Y): [2:0-0-2,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	Vert(LL)	0.02	4-7	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	Vert(CT)	-0.05	4-7	>999	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	Horz(CT)	0.00	2	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS						Weight: 20 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied, except end verticals.
 BOT CHORD Rigid ceiling directly applied.

REACTIONS (lb/size) 2=290/0-4-8, (min. 0-1-8),
 4=182/0-1-8, (min. 0-1-8)
 Max Horiz 2=66 (LC 11)
 Max Uplift 2=-32 (LC 12)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -1-4-11 to 2-7-5, Interior (1) 2-7-5 to 4-10-4 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 4) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 5) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 32 lb uplift at joint 2.
 - 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

8) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard


Job Q2302112	Truss P03	Truss Type Roof Special	Qty 1	Ply 2	Hughes Job Reference (optional)
-----------------	--------------	----------------------------	----------	----------	------------------------------------

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:30

Page: 1

ID:GRKIA5r?zXKE3g_EUyBG60zzRMv-Cg0QXP2SQpbJsXpghu8luS8S3fHA3LuWFMajYwzzQNN



Scale = 1:31

Plate Offsets (X, Y): [5:0-3-0,0-0-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	Vert(LL)	0.00	8-11	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	Vert(CT)	-0.01	8	>999	180		
BCLL	0.0*	Rep Stress Incr	NO	WB	Horz(CT)	n/a	-	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-MP						Weight: 46 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins: 4-8, 4-6. Except: 6-0-0 oc bracing: 3-4
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=504/0-4-8, (min. 0-1-8), 5=695/0-1-8, (min. 0-1-8)
 Max Horiz 2=40 (LC 12)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-694/0
 BOT CHORD 2-8=0/620, 7-8=0/881
 WEBS 5-7=0/428, 4-7=-962/0

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -1-4-11 to 2-10-4, Interior (1) 2-10-4 to 5-3-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 5.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Load case(s) 1 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Gap between inside of top chord bearing and first diagonal or vertical web shall not exceed 0.500in.

LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.00
 Uniform Loads (lb/ft)
 Vert: 1-3=-60, 7-9=-20, 4-6=-180
 Concentrated Loads (lb)
 Vert: 3=-408


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	P04	Half Hip	3	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:30

Page: 1

ID:0NieSJoAocp9W8mRSYQrVuzzRiw-Cg0QXP2SQpbJsXphgu8luS8PcfDa3J?WFMajYwzzQNN



Scale = 1:27.4

Plate Offsets (X, Y): [2:0-0-2,Edge], [3:0-1-4,0-1-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	Vert(LL)	0.00	7	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	Vert(CT)	-0.03	7	>999	180		
BCLL	0.0*	Rep Stress Incr	NO	WB	Horz(CT)	0.01	6	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-MP						Weight: 24 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3 *Except* W1:2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-4-0 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-7, 4-5. Except: 6-0-0 oc bracing: 3-4
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=486/0-4-8, (min. 0-1-8), 6=461/0-3-8, (min. 0-1-8)
 Max Horiz 2=49 (LC 9)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-637/0, 3-4=-256/0
 BOT CHORD 2-7=0/569, 6-7=0/957
 WEBS 4-6=-1004/0

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -1-4-11 to 2-10-4, Interior (1) 2-10-4 to 5-2-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 7) Load case(s) 1 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.

- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 89 lb down and 69 lb up at 5-2-4 on top chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.00
 Uniform Loads (lb/ft)
 Vert: 1-3=-60, 6-8=-20, 4-5=-60
 Concentrated Loads (lb)
 Vert: 3=-408, 5=-41


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	V01	Valley	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:31

Page: 1

ID: ?Z8vPJd3?8W240IE1lcX9zzRC5-hsaokl34B6jAUhOIEbf_Rfhhi3cEomQfU0JG4MzzQNM



Scale = 1:44

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.27	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.20	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.22	Horiz(TL)	0.00	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS							Weight: 73 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.

REACTIONS All bearings 17-10-12.
 (lb) - Max Horiz 1=99 (LC 11)
 Max Uplift All uplift 100 (lb) or less at joint(s) 6, 9
 Max Grav All reactions 250 (lb) or less at joint (s) 1, 5 except 6=508 (LC 18), 7=519 (LC 17), 9=512 (LC 17)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-14=-19/272
 WEBS 3-7=-354/0, 2-9=-303/110, 4-6=-302/109

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-0-6 to 4-0-6, Interior (1) 4-0-6 to 8-11-12, Exterior(2R) 8-11-12 to 12-11-12, Interior (1) 12-11-12 to 17-11-2 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) Gable requires continuous bottom chord bearing.
 - 5) Gable studs spaced at 4-0-0 oc.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 9, 6.
 - 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	V02	Valley	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:31

Page: 1

ID: ?Z8vPJ3?8W240E1lcX9zzRC5-hsaokl34B6jAUhOIEbf_RfhjG3efooRfU0JG4MzzQNM



Scale = 1:38.7

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.17	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.11	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.09	Horiz(TL)	0.00	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS							Weight: 54 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.

REACTIONS All bearings 13-10-12.
 (lb) - Max Horiz 1=77 (LC 10)
 Max Uplift All uplift 100 (lb) or less at joint(s)
 6, 8
 Max Grav All reactions 250 (lb) or less at joint
 (s) 1, 5 except 6=325 (LC 24),
 7=305 (LC 1), 8=325 (LC 23)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250
 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust)
 Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft;
 B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B;
 Enclosed; MWFRS (directional) and C-C Exterior(2E)
 0-0-6 to 4-0-6, Interior (1) 4-0-6 to 6-11-12, Exterior(2R)
 6-11-12 to 10-11-12, Interior (1) 10-11-12 to 13-11-2
 zone; cantilever left and right exposed ; end vertical left
 and right exposed;C-C for members and forces &
 MWFRS for reactions shown; Lumber DOL=1.60 plate
 grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss
 only. For studs exposed to wind (normal to the face),
 see Standard Industry Gable End Details as applicable,
 or consult qualified building designer as per ANSI/TPI 1.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom
 chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf
 on the bottom chord in all areas where a rectangle
 3-06-00 tall by 2-00-00 wide will fit between the bottom
 chord and any other members.
 - Provide mechanical connection (by others) of truss to
 bearing plate capable of withstanding 100 lb uplift at joint
 (s) 8, 6.

- This truss is designed in accordance with the 2018
 International Residential Code sections R502.11.1 and
 R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16"
 structural wood sheathing be applied directly to the top
 chord and 1/2" gypsum sheetrock be applied directly to
 the bottom chord.
- LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	V03	Valley	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:31

Page: 1

ID: ?Z8vPJd3?8W240E1lcX9zzRC5-hsaackl34B6jAUhOIEbf_RfhiB3cdongfU0JG4MzzQNM



Scale = 1:32.4

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	Horiz(TL)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS						Weight: 35 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.

REACTIONS (lb/size) 1=44/9-10-12, (min. 0-1-8),
 3=44/9-10-12, (min. 0-1-8),
 4=703/9-10-12, (min. 0-1-8)
 Max Horiz 1=54 (LC 11)
 Max Uplift 1=-17 (LC 24), 3=-17 (LC 23), 4=-3 (LC 12)
 Max Grav 1=82 (LC 23), 3=82 (LC 24), 4=703 (LC 1)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-76/310, 2-3=-56/310
 WEBS 2-4=-541/147

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-0-6 to 4-0-6, Interior (1) 4-0-6 to 4-11-12, Exterior(2R) 4-11-12 to 8-11-15, Interior (1) 8-11-15 to 9-11-2 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 17 lb uplift at joint 1, 17 lb uplift at joint 3 and 3 lb uplift at joint 4.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	V04	Valley	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:32

Page: 1

ID:wgqFK5ZB?yHtBR_HBFZFK&zzR7n-938Ay44iyQr15qz4oJAD_tEuGT_1XGloJf3qdozzQNL



Scale = 1:27.3

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.10	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.05	Horiz(TL)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-AS							Weight: 20 lb	FT = 20%

LUMBER **LOAD CASE(S)** Standard

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.

REACTIONS (lb/size) 1=52/5-10-12, (min. 0-1-8),
 3=52/5-10-12, (min. 0-1-8),
 4=368/5-10-12, (min. 0-1-8)
 Max Horiz 1=-31 (LC 10)
 Max Grav 1=68 (LC 23), 3=68 (LC 24), 4=368 (LC 1)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	V11	Valley	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:32

Page: 1

ID:atEmpt8M9CnIPZVSMGP_8mzzR5k-938Ay44iyQr15qz4oJAD_tEo0TxDXFNofj3qdozzQNL



Scale = 1:51

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.49	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.28	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.11	Horiz(TL)	0.01	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 66 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 14-4-13.
(lb) - Max Horiz 8=-213 (LC 8)
Max Uplift All uplift 100 (lb) or less at joint(s) 6, 7, 8
Max Grav All reactions 250 (lb) or less at joint (s) 5, 8 except 6=502 (LC 18), 7=394 (LC 18)


FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 4-9=-292/191, 5-9=-310/177
BOT CHORD 7-8=-181/312, 6-7=-181/312, 6-10=-181/312, 5-10=-181/312
WEBS 4-6=-326/150

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-1-12 to 4-0-0, Interior (1) 4-0-0 to 13-8-5 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) Gable requires continuous bottom chord bearing.
 - 4) Gable studs spaced at 4-0-0 oc.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 8, 7, 6.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job Q2302112	Truss V12	Truss Type Valley	Qty 1	Ply 1	Hughes Job Reference (optional)
-----------------	--------------	----------------------	----------	----------	------------------------------------



Scale = 1:45.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.39	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.16	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.08	Horiz(TL)	0.00	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 50 lb	FT = 20%

- LUMBER**
- TOP CHORD 2x4 SP No.2
 - BOT CHORD 2x4 SP No.2
 - WEBS 2x4 SP No.3
 - OTHERS 2x4 SP No.3

- BRACING**
- TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 - BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

- REACTIONS** All bearings 11-2-6.
- (lb) - Max Horiz 8=-175 (LC 8)
 - Max Uplift All uplift 100 (lb) or less at joint(s) 6, 7, 8
 - Max Grav All reactions 250 (lb) or less at joint (s) 5, 8 except 6=303 (LC 18), 7=449 (LC 18)

- FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
- TOP CHORD 2-3=-305/181, 3-4=-314/148, 4-5=-361/181
 - BOT CHORD 8-9=-163/349, 7-9=-163/349, 6-7=-163/349, 6-10=-163/349, 5-10=-163/349
 - WEBS 2-7=-267/266

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=2ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) 0-1-12 to 4-0-0, Exterior(2N) 4-0-0 to 10-5-15 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) Gable requires continuous bottom chord bearing.
 - 4) Gable studs spaced at 4-0-0 oc.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 8, 7, 6.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job Q2302112	Truss V13	Truss Type Valley	Qty 1	Ply 1	Hughes Job Reference (optional)
-----------------	--------------	----------------------	----------	----------	------------------------------------

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:33

Page: 1

ID:4affPoqctPlo1hT7NuO18bzzR2G-938Ay44iyQr15qz4oJAD_tErqTzaXG9ofj3qdozzQNL



Scale = 1:35.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.31	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.13	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.06	Horiz(TL)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 35 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING
TOP CHORD Structural wood sheathing directly applied or 6'-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10'-0-0 oc bracing.

REACTIONS (lb/size) 3=96/8-0-0, (min. 0-1-8),
4=363/8-0-0, (min. 0-1-8),
5=120/8-0-0, (min. 0-1-8)
Max Horiz 5=-137 (LC 8)
Max Uplift 4=-39 (LC 12), 5=-19 (LC 8)
Max Grav 3=118 (LC 17), 4=363 (LC 1),
5=127 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-4=-272/178

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-1-12 to 5-9-10, Interior (1) 5-9-10 to 7-4-9 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) Gable requires continuous bottom chord bearing.
 - 4) Gable studs spaced at 4'-0-0 oc.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-0-0 tall by 2'-0-0 wide will fit between the bottom chord and any other members.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 19 lb uplift at joint 5 and 39 lb uplift at joint 4.


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	V14	Valley	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:33

Page: 1

ID: cw9AL4EJ5Yw6VIUTpKUn_YzzR1I-dFiY9Q4Kjkzuj_YGM0hSW4m19sKzGiwyyJoN9EzzQNK



Scale = 1:33.7

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.21	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.12	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.09	Horiz(TL)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 24 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 5-10-6 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=-27/5-10-0, (min. 0-1-8),
4=321/5-10-0, (min. 0-1-8),
5=125/5-10-0, (min. 0-1-8)
Max Horiz 5=-99 (LC 8)
Max Uplift 3=-48 (LC 18), 4=-34 (LC 12),
5=-14 (LC 8)
Max Grav 3=52 (LC 8), 4=321 (LC 1), 5=130 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-309/191
WEBS 2-4=-241/305

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=2ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) 0-1-12 to 4-0-0, Exterior(2N) 4-0-0 to 5-4-9 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) Gable requires continuous bottom chord bearing.
 - 4) Gable studs spaced at 4-0-0 oc.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 14 lb uplift at joint 5, 48 lb uplift at joint 3 and 34 lb uplift at joint 4.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	V15	Valley	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:33

Page: 1

ID:R4WRb714hOgGDgyc9abBDpzzR1f-dFiY9Q4Kjkzuj_YGM0hSW4m1IsKzGjKyyJoN9EzzQNK



Scale = 1:27.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.20	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.12	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 15 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-10-6 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=129/3-10-0, (min. 0-1-8),
 3=129/3-10-0, (min. 0-1-8)
 Max Horiz 3=-61 (LC 8)
 Max Uplift 3=-8 (LC 8)
 Max Grav 2=129 (LC 1), 3=133 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
 Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft;
 B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B;
 Enclosed; MWFRS (directional) and C-C Exterior(2E)
 zone; cantilever left and right exposed; end vertical left
 and right exposed; C-C for members and forces &
 MWFRS for reactions shown; Lumber DOL=1.60 plate
 grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom
 chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf
 on the bottom chord in all areas where a rectangle
 3-06-00 tall by 2-00-00 wide will fit between the bottom
 chord and any other members.
- 5) Provide mechanical connection (by others) of truss to
 bearing plate capable of withstanding 8 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018
 International Residential Code sections R502.11.1 and
 R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	V16	Valley	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:33

Page: 1

ID:50Ez6ESbs4BZfWsws6p?LzzR1T-dFiy9Q4Kjzuj_YGM0hSW4m1?skzGiwyyJoN9EzzQNK



Scale = 1:34.3

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	I/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.22	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.12	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.09	Horiz(TL)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 25 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6'-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10'-0-0 oc bracing.

REACTIONS (lb/size) 3=-7/6-0-8, (min. 0-1-8),
 4=317/6-0-8, (min. 0-1-8),
 5=125/6-0-8, (min. 0-1-8)
 Max Horiz 5=-103 (LC 8)
 Max Uplift 3=-34 (LC 11), 4=-34 (LC 12),
 5=-14 (LC 8)
 Max Grav 3=54 (LC 8), 4=317 (LC 1), 5=130 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-307/191
 WEBS 2-4=-238/297

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TC DL=6.0psf; BC DL=6.0psf; h=29ft; B=58ft; L=40ft; eave=2ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) 0-1-12 to 4-0-0, Exterior(2N) 4-0-0 to 5-7-1 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) Gable requires continuous bottom chord bearing.
 - 4) Gable studs spaced at 4'-0-0 oc.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 14 lb uplift at joint 5, 34 lb uplift at joint 3 and 34 lb uplift at joint 4.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	V17	Valley	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:34

Page: 1

ID:K7HN?JZFkrJHEv2fuVT6aEzzR1K-dFiY9Q4Kjkzuj_YGM0hSW4m_LsJeGiwyyJoN9EzzQNK



Scale = 1:39.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.39	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.14	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.09	Horiz(TL)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 36 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=105/8-0-8, (min. 0-1-8),
4=372/8-0-8, (min. 0-1-8),
5=118/8-0-8, (min. 0-1-8)
Max Horiz 5=-141 (LC 8)
Max Uplift 4=-40 (LC 12), 5=-20 (LC 8)
Max Grav 3=126 (LC 17), 4=372 (LC 1),
5=125 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-319/215
BOT CHORD 4-5=-178/299, 3-4=-178/299
WEBS 2-4=-279/290

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=2ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) 0-1-12 to 4-0-0, Exterior(2N) 4-0-0 to 7-7-1 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) Gable requires continuous bottom chord bearing.
 - 4) Gable studs spaced at 4-0-0 oc.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 20 lb uplift at joint 5 and 40 lb uplift at joint 4.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	V18	Valley	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:34

Page: 1

ID:ZrKnuOfudcS?pHENwu7DR8zzR1B-5RGxNm5zU16L87SvkDh3lJ9nGfP?9L5AzYwhzzQNJ



Scale = 1:46.2

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	I/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.41	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.08	Horiz(TL)	0.00	4	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 48 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 10-0-8.

(lb) - Max Horiz 7=-179 (LC 8)
 Max Uplift All uplift 100 (lb) or less at joint(s) 4, 5, 6, 7
 Max Grav All reactions 250 (lb) or less at joint (s) 4, 7 except 5=298 (LC 18), 6=457 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-8=-285/215, 3-8=-309/190, 3-4=-401/257
 BOT CHORD 6-7=-205/341, 5-6=-205/341, 5-9=-205/341, 4-9=-205/341
 WEBS 2-6=-268/260

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=2ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) 0-1-12 to 4-0-0, Exterior(2N) 4-0-0 to 9-7-1 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 4-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 7, 4, 6, 5.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	V19	Valley	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:34

Page: 1

ID:GnwZ?on9Ggia0q?IV_JzrFzzR11-5RGxNm5zU16IL87SvkDh3U6oGfa?8Z5AzYwhzzQNJ



Scale = 1:51.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	0.60	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.16	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.13	Horiz(TL)	0.01	4	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 60 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 1-7

REACTIONS All bearings 12-0-8.
(lb) - Max Horiz 7=-217 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 5, 6, 7
Max Grav All reactions 250 (lb) or less at joint (s) 4, 7 except 5=391 (LC 18), 6=440 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-8=-277/219, 3-8=-301/179, 3-4=-421/280
BOT CHORD 6-7=-233/383, 5-6=-233/383, 5-9=-233/383, 4-9=-233/383
WEBS 2-6=-260/236

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TC DL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=2ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) 0-1-12 to 4-0-0, Exterior(2N) 4-0-0 to 11-7-1 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) Gable requires continuous bottom chord bearing.
 - 4) Gable studs spaced at 4-0-0 oc.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 7, 6, 5.
 - 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	Hughes
Q2302112	V20	Valley	1	1	Job Reference (optional)

Carolina Structural Systems, Star, NC 27356, Jeremy Phillips

Run: 8.62 S Oct 13 2022 Print: 8.620 S Oct 13 2022 MiTek Industries, Inc. Tue Jan 02 11:30:34

Page: 1

ID:m_Pw7eHFZaAKDFrZW46Z55zzR5Z-5RGxNm5zU16lL87SvkDh3lJ5FGf6?7SS5AzYwhzzQNJ



Scale = 1:56.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.00	TC	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	Horiz(TL)	0.01	6	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S						Weight: 72 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 1-10

REACTIONS All bearings 13-10-0.
 (lb) - Max Horiz 10=-251 (LC 8)
 Max Uplift All uplift 100 (lb) or less at joint(s) 6, 7, 8, 9, 10
 Max Grav All reactions 250 (lb) or less at joint (s) 6, 10 except 7=313 (LC 18), 8=409 (LC 18), 9=476 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 3-4=-294/262, 4-5=-320/258, 5-6=-385/306
 BOT CHORD 9-10=-239/318, 9-11=-239/318, 8-11=-239/318, 7-8=-239/318, 7-12=-239/318, 6-12=-239/318
 WEBS 2-9=-263/144

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=29ft; B=58ft; L=40ft; eave=5ft; Ke=1.00; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-1-12 to 4-0-0, Interior (1) 4-0-0 to 13-4-9 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) Gable requires continuous bottom chord bearing.
 - 4) Gable studs spaced at 4-0-0 oc.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 10, 6, 9, 8, 7.
 - 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- LOAD CASE(S)** Standard