## Harnett County Department of Public Health

Improvement Permit

A	building permit cannot be issued with only an Improvement	Permit rueLove Rd, Holly Springs
ISSUED TO: James Wheeler	SUBDIVISION	LOT #
NEW REPAIR EXPANSION		uired prior to Construction Authorization Issuance:
Type of Structure: SFD 77' x 53'		
Proposed Wastewater System Type: 25% Redv	ction system	
Projected Daily Flow: 360 GPD  Number of bedrooms: 3 Number of Occup	antr: 6 may	
Basement Yes No	antsmax	
	red based on final location and elevations of facilities	
Type of Water Supply: Community Public		Permit valid for: Five years
Permit conditions:		No expiration
2	MI I DE REAS	
Authorized State Agent:	Date: 12-6-2	SEE ATTACHED SITE SKETCH
		cking with appropriate governing bodies in meeting their requirements. This
site is subject to revocation if the site plan, plat, or the intended use of the Laws and Rules for Sewage Treatment and Disposal and to condition		ership of the site. This permit is subject to compliance with the provisions of
the Laws and rules for sewage freatment and Disposal and to condition	s of this permit.	
	Construction Authorization	
The construction and installation requirements of Rules 1950 1952 19	(Required for Building Permit)	into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.	774, 1733, 1730, 1731, 1730, and 1777 are incorporated by references	mito this permit and shall be met. Systems shall be installed in actoroance
T .01 02102	DRODERTY LOCATION. 57	5 Touglave Pl Hally Cocass
ISSUED 10: James Wheeler	PROPERTY LOCATION:	5 True Love Rd, Holly Springs,
Facility Type: SED 77'X 53'	New   Fynancian   Renair	201 #
Facility Type: SFD 77'X53' Basement? Yes No Basement Fixe	tures? Yes 10 No	
Type of Wastewater System** 25%.	eduction System	(Initial) Wastewater Flow: 360 GPD
(See note below, if applicable $\square$ ) $25\%$ Rea	buction System (Repair)	
Installation Requirements/Conditions	Number of trenches Z	0
Septic Tank Size 1,000 gallons Pump Tank Size gallons	Exact length of each trench 114 feet	Trench Spacing: Feet on Center
Pump Tank Sizegallons	Trenches shall be installed on contour at a	Soil Cover: 6 inches
	Maximum Trench Depth of: 20 inches	(Maximum soil cover shall not exceed
		36" above the trench bottom)
D	in all directions)	-1-11-1
Pump Requirements:ft. TDH vs	GPM	inches below pipe
Conditions		Aggregate Depth:inches above pipe
Conditions:		inches total
WATER LINES (INCLUDING IRRICATION) MILET B	OF JOIT FROM ANY DART OF SERVIC SYSTEM OR	DEDAID ADEA
	BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR I	KEPAIK AKEA.
NO UTILITIES ALLOWED IN INITIAL OR REPAIR D		
**If applicable: 1 understand the system type specified	is different from the type specified on the application	I accept the specifications of this permit.
Owner/Legal Representative Signature:		Date:
The second control of	olat, or the intended use changes. The Construction Authorization shall not	
Construction Authorization is subject to compliance with the provisions of	the Laws and Rules for Sewage Treatment and Disposal and to the condit	ons of this permit. SEE ATTACHED SITE SKETCH
Authorized State Mant	Marker TEAS Date:	12-6-23
Authorized State Agent:	Construction Authorization Expiration C	

## Harnett County Department of Public Health Site Sketch

