

<u>Truss Placement Plan</u> SCALE: NTS

	Contrection         Radius and a static					
	LO	LOAD CHART FOR JACK STUDS (BASED ON TABLES R502.5(1) & (b))				
Plumbing Drop Notes         1. Plumbing drop locations shown are NOT exact.         2. Contractor to verify ALL plumbing drop locations prior to setting Floor Trusses.         3. Adjust spacing as needed not to exceed 24"oc.         Dimension Notes         1. All exterior wall to wall dimensions are to face of sheathing unless noted otherwise         2. All interior wall dimensions are to face of stud unless noted otherwise         3. All exterior wall to truss dimensions are to	END REACTION (UP TO)	BBER OF JA           BBER OF JA           Comparison           Co		REQUIREC /GIRDER ND-5 SOLDS ABOR SOLDS ABOR SOLDS ABOR ABOR ABOR ABOR ABOR ABOR ABOR ABOR	© EA END NO LLOG Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q	<ul> <li>REQ'D STUDS FOR</li> <li>(4) PLY HEADER</li> </ul>
Roof Area = 2220.56 sq.ft.         Ridge Line = 32.22 ft.         Hip Line = 0 ft.         Horiz. OH = 183.75 ft.         Raked OH = 168.3 ft.         Decking = 76 sheets         All Walls Shown Are         Considered Load Bearing         ▲ = Indicates Left End of Truss         (Reference Engineered Truss Drawing)         Do Not Erect Trusses Backwards	Lillington / Harnett	XXX Whistling Way	Floor	11/27/23	Johnnie Baggett	. Johnnie Baggett
WALL SCHEDULE         1st Floor Walls         2nd Floor Walls         Non-Bearing Walls         Garage Walls Dropped	CITY / CO.	ADDRESS	WODEL	DATE REV.	DRAWN BY	SALES REP
Connector Information       Nail Information         Sym       Product       Manuf       Qty       Supported Member       Header       Truss         Image: HUS410       USP       42       NA       16d/3-1/2"       16d/3-1/2"         Image: HUS410       USP       42       NA       16d/3-1/2"       16d/3-1/2"	New Home Inc	Lot 17 Heritage @ NC	The Holly -Craftsman	7/1/21	Quote #	J1123-6664
FB2       12' 0"       1-3/4"x 14" LVL Kerto-S       1       1         FB3       9' 0"       1-3/4"x 14" LVL Kerto-S       2       2         FB1       6' 0"       1-3/4"x 14" LVL Kerto-S       2       2         FB4       22' 0"       1-3/4"x 18" LVL Kerto-S       3       3         FB5       16' 0"       1-3/4"x 23-7/8" LVL Kerto-S       2       2	BUILDER	JOB NAME	PLAN	SEAL DATE	QUOTE #	JOB #
= Indicates Left End of Truss (Reference Engineered Truss Drawing) Do NOT Erect Truss Backwards	These to compose design See ind identifie designe perman for the suppor and col designe consult	A TRUSS russes an nents to b at the sp lividual de ed on the er is resp nent braci overall st t structur tumns is t ar. For ge BCSI-B1 elivery pa	re designo be incorpo ecification esign she placemen onsible fo ng of the ructure. 1 e includir the respo neral guid and BCS	ed as indi prated int n of the b ets for ea nt drawing r tempor roof and 'he desig g header nsibility of dance reg I-B3 prov	ividual bu o the buil uilding de ach truss g. The bu ary and floor sys n of the t s, beams of the buil arding br	ilding ding signer. design ilding em and uss walls, ding acing, the

ō 38'

ò <u>.</u>

in