


THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. The individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for the temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls and columns is the responsibility of the building designer. For general guidance regarding bracing, consult ICC-ES E-1000 and ICC-ES E-1001 provided with the truss delivery package or online @ secondary.com

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.

Signature: *Sales Area*

Sales Area

Roof Truss Plan




Nail Information		Connector Information				
Truss	Header	Supported Member	Qty	Manuf	Product	Sym
16d/3-1/2"	16d/3-1/2"	NA	9	USP	HUS26	■
10d/3"	10d/1-1/2"	NA	2	USP	HTW20	◆

Dimension Notes
 1. All exterior wall to wall dimensions are to face of sheathing unless noted otherwise.
 2. All interior wall dimensions are to face of stud unless noted otherwise.
 3. All exterior wall to truss dimensions are to face of stud unless noted otherwise.

1703.18 sq.ft. Roof Area
 53.63 ft. Ridge Line
 0.41 ft. Hip Line
 112.88 ft. Horiz. OH
 150.48 ft. Raked OH
 59 sheets Decking

= Denotes Left End of Truss ▲
 (Reference Engineered Truss Drawing)

Floor Truss Plan



Dimension Notes
 1. All exterior wall to wall dimensions are to face of sheathing unless noted otherwise.
 2. All interior wall dimensions are to face of stud unless noted otherwise.
 3. All exterior wall to truss dimensions are to face of stud unless noted otherwise.

Nail Information		Connector Information				
Truss	Header	Supported Member	Qty	Manuf	Product	Sym
10d/3"	16d/3-1/2"	NA	1	USP	HD416	●
16d/3-1/2"	16d/3-1/2"	NA	12	USP	HUS410	●

All Walls Shown Are Considered Load Bearing

= Denotes Left End of Truss ▲
 (Reference Engineered Truss Drawing)

Products					
Net Qty	Plies	Product	Length	PlotID	
2	2	1-3/4"x 16" LVL Kerto-S	21' 0"	(2) 1.75"x16" LVL	
3	3	1-3/4"x 16" LVL Kerto-S	20' 0"	(3) 1.75" x 16" LVL	
2	2	1-3/4"x 16" LVL Kerto-S	15' 0"	(2) 1.75"x16" LVL	
2	2	1-3/4"x 16" LVL Kerto-S	13' 0"	(2) 1.75" x 16" LVL	
2	2	1-3/4"x 16" LVL Kerto-S	5' 0"	(2) 1.75" x 16" LVL	
1	1	1-3/4"x 16" LVL Kerto-S	4' 0"	1.75" x 16" LVL	
2	2	1-3/4"x 16" LVL Kerto-S	4' 0"	(2) 1.75"x16" LVL	
3	3	1-3/4"x 23-7/8" LVL Kerto-S	20' 0"	GDH RIP to 20" Deep	

Truss Placement Plan

SCALE: 1/4" = 1'

CITY / CO.	Fuquay Varina / Hamnett
ADDRESS	22 Avents Creek Way
MODEL	Roof & Floor
DATE REV.	03/04/23
DRAWN BY	Hampton Horrocks
SALES REP.	Paul Hawkins

BUILDER	New Home, Inc.
JOB NAME	Lot 12 Woodbridge South
PLAN	Smithfield French Country SE / LH
SEAL DATE	12/20/23
QUOTE #	Quote #
JOB #	J0224-1230 & J0224-1231

LOAD CHART FOR JACK STUDS			
BASED ON TABLES 802.2.1 & 811			
NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADERS/ORDER			
REQ'D STUDS FOR (1) FT. HEADERS	REQ'D STUDS FOR (2) FT. HEADERS	REQ'D STUDS FOR (3) FT. HEADERS	REQ'D STUDS FOR (4) FT. HEADERS
1700 1	2550 1	3400 1	
3400 2	5100 2	6800 2	
5100 3	7650 3	10200 3	
6800 4	10200 4	13600 4	
8500 5	12750 5	17000 5	
10200 6	15300 6		
11900 7			
13600 8			
15300 9			