

Trenco  
818 Soundside Rd  
Edenton, NC 27932

Re: 23-7316-A  
RVF-LOT #29 ROOF

The truss drawing(s) referenced below have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Riverside Roof Truss.

Pages or sheets covered by this seal: I62587356 thru I62587381

My license renewal date for the state of North Carolina is December 31, 2023.

North Carolina COA: C-0844



December 18, 2023

Johnson, Andrew

**IMPORTANT NOTE:** The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

Job 23-7316-A	Truss GE01	Truss Type Common Supported Gable	Qty 1	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587356
------------------	---------------	--------------------------------------	----------	----------	--	-----------


Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:19:58 2023 Page 1

ID:Bxl2MwYau\_NHkbraGcmHloyOvst-Dh\_eopn1RAiD9MYWEFk4MAy5e4?Kf0pBrqwRrmy8ILF



Scale = 1:28.7



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.09	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.03	Vert(LL) -0.00 9 n/r 120		
TCDL 10.0	Lumber DOL 1.15	WB 0.04	Vert(CT) -0.00 9 n/r 120		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 10 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 67 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3	
OTHERS 2x4 SP No.3	

**REACTIONS.** All bearings 11-7-0.  
 (lb) - Max Horz 16=109(LC 15)  
 Max Uplift All uplift 100 lb or less at joint(s) 16, 10, 14, 15, 12, 11  
 Max Grav All reactions 250 lb or less at joint(s) 16, 10, 13, 14, 15, 12, 11

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) -1-0-0 to 1-9-8, Exterior(2N) 1-9-8 to 5-9-8, Corner(3R) 5-9-8 to 8-9-8, Exterior(2N) 8-9-8 to 12-7-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 16, 10, 14, 15, 12, 11.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




Job 23-7316-A	Truss M01	Truss Type MONOPITCH	Qty 6	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587357
------------------	--------------	-------------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:00 2023 Page 1

ID:Bxl2MwYau\_NHkbraGCmHloyOvst-946ODVpHzoyxPgiuMgmYRb1MEtcJ7n6UJ8PYwfy8ILD



Scale = 1:25.2


<b>LOADING (psf)</b>	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.40	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.38	Vert(LL) -0.03 6-9 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.56	Vert(CT) -0.07 6-9 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.01 5 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 54 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	

**REACTIONS.** (size) 2=0-3-8, 5=Mechanical  
 Max Horz 2=141(LC 15)  
 Max Uplift 2=-57(LC 16), 5=-30(LC 16)  
 Max Grav 2=523(LC 2), 5=458(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-849/193  
 BOT CHORD 2-6=-282/778, 5-6=-282/778  
 WEBS 3-6=0/259, 3-5=-805/241

- NOTES-**
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior(1) 2-0-0 to 11-6-4 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - 3) Unbalanced snow loads have been considered for this design.
  - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 6) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 7) Refer to girder(s) for truss to truss connections.
  - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 5.
  - 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




December 18, 2023

Job 23-7316-A	Truss M01GE	Truss Type MONOPITCH SUPPORTED	Qty 1	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587358
------------------	----------------	-----------------------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:01 2023 Page 1

ID:BxI2MwYau\_NHkbraGCmHloyOvst-dGgmQrqvk55o1qH5vNHnzoaa?H1UsMXdXo95S5y8ILC



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.21	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.06	Vert(LL) 0.00 1 n/r 120		
TCDL 10.0	Lumber DOL 1.15	WB 0.04	Vert(CT) -0.00 1 n/r 120		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 9 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 56 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	
OTHERS 2x4 SP No.3	

**REACTIONS.** All bearings 11-8-0.  
 (lb) - Max Horz 2=141(LC 13)  
 Max Uplift All uplift 100 lb or less at joint(s) 9, 2, 10, 11, 12, 13, 14  
 Max Grav All reactions 250 lb or less at joint(s) 9, 2, 10, 11, 12, 13, 14

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-304/151, 3-4=-257/135

- NOTES-**
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) -1-0-0 to 2-0-0, Exterior(2N) 2-0-0 to 11-6-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - 4) Unbalanced snow loads have been considered for this design.
  - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - 6) All plates are 2x4 MT20 unless otherwise indicated.
  - 7) Gable requires continuous bottom chord bearing.
  - 8) Gable studs spaced at 2-0-0 oc.
  - 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 10) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9, 2, 10, 11, 12, 13, 14.
  - 12) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 2.
  - 13) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



December 18, 2023

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**  
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPH Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)



ENGINEERING BY  
**TRENCO**  
 A MITEK Affiliate  
 818 Soundside Road  
 Edenton, NC 27932

Job 23-7316-A	Truss M02	Truss Type HALF HIP	Qty 3	Ply 1	RVF-LOT #29 ROOF	162587359
------------------	--------------	------------------------	----------	----------	------------------	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:02 2023 Page 1

ID: BxI2MwYau\_NHkbraGCmHloyOvst-5SD8eBqYVPDfezsHT5o0W07mwhM9bpZnmSuf\_Xy8ILB



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.14	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 16.5/15.0	Plate Grip DOL 1.15	BC 0.10	Vert(LL) -0.00 9 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.05	Vert(CT) -0.00 6-9 >999 180		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MP	Horz(CT) 0.00 5 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 16 lb	FT = 20%


<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 3-8-0 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-6, 3-4.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	

**REACTIONS.** (size) 2=0-3-8, 5=Mechanical  
 Max Horz 2=35(LC 15)  
 Max Uplift 2=14(LC 16)  
 Max Grav 2=263(LC 36), 5=325(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 WEBS 3-5=272/0

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior(1) 2-0-0 to 2-6-4, Exterior(2E) 2-6-4 to 3-6-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=16.5 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Refer to girder(s) for truss to truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Load case(s) 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard  
 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15



Continued on page 2

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

**ENGINEERING BY**  
**TRENCO**  
 A MiTek Affiliate

818 Soundside Road  
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	RVF-LOT #29 ROOF	162587359
23-7316-A	M02	HALF HIP	3	1		
						Job Reference (optional)

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:02 2023 Page 2  
ID:Bxl2MwYau\_NHKbraGCmHloyOvst-5SD8eBqYVPDfezsHT5o0W07mwhM9bpZnmSuf\_Xy8lLB

**LOAD CASE(S)** Standard

- Uniform Loads (plf)  
Vert: 1-3=-43, 5-7=-20, 3-4=-83
- Concentrated Loads (lb)  
Vert: 12=-160
- 2) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=60, 5-7=-20, 3-4=-90  
Concentrated Loads (lb)  
Vert: 12=-160
- 3) Dead + 0.75 Roof Live (balanced) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=50, 5-7=-20, 3-4=-139  
Concentrated Loads (lb)  
Vert: 12=-160
- 4) Dead + 0.75 Snow (balanced) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=37, 5-7=-20, 3-4=-133  
Concentrated Loads (lb)  
Vert: 12=-160
- 5) Dead + 0.75 Snow (Unbal. Left) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-10=-37, 3-10=-42, 5-7=-20, 3-4=-114  
Concentrated Loads (lb)  
Vert: 12=-160
- 6) Dead + 0.75 Snow (Unbal. Right) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-25, 5-7=-20, 3-4=-135  
Concentrated Loads (lb)  
Vert: 12=-160
- 7) Dead + Uninhabitable Attic Without Storage: Lumber Increase=1.25, Plate Increase=1.25  
Uniform Loads (plf)  
Vert: 1-3=20, 5-7=-40, 3-4=-50  
Concentrated Loads (lb)  
Vert: 12=-160
- 8) Dead + 0.6 C-C Wind (Pos. Internal) Case 1: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=60, 2-11=50, 3-11=34, 5-7=-12, 3-4=32  
Horz: 1-2=-72, 2-11=-62, 3-11=-46, 4-5=38, 3-4=62  
Concentrated Loads (lb)  
Vert: 12=-160
- 9) Dead + 0.6 C-C Wind (Pos. Internal) Case 2: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=58, 2-3=64, 5-7=-12, 3-4=32  
Horz: 1-2=-70, 2-3=-76, 4-5=-24, 3-4=62  
Concentrated Loads (lb)  
Vert: 12=-160
- 10) Dead + 0.6 C-C Wind (Neg. Internal) Case 1: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=1, 2-3=-46, 5-7=-20, 3-4=-64  
Horz: 1-2=-21, 2-3=26, 4-5=-35, 3-4=-26  
Concentrated Loads (lb)  
Vert: 12=-160
- 11) Dead + 0.6 C-C Wind (Neg. Internal) Case 2: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-41, 2-3=-46, 5-7=-20, 3-4=-64  
Horz: 1-2=21, 2-3=26, 4-5=27, 3-4=-26  
Concentrated Loads (lb)  
Vert: 12=-160
- 12) Dead + 0.6 MWFRS Wind (Pos. Internal) Left: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=28, 2-3=13, 5-7=-12, 3-4=8  
Horz: 1-2=-40, 2-3=-25, 4-5=18, 3-4=38  
Concentrated Loads (lb)  
Vert: 12=-160
- 13) Dead + 0.6 MWFRS Wind (Pos. Internal) Right: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=3, 2-3=8, 5-7=-12, 3-4=8  
Horz: 1-2=-15, 2-3=-20, 4-5=-15, 3-4=38  
Concentrated Loads (lb)  
Vert: 12=-160
- 14) Dead + 0.6 MWFRS Wind (Neg. Internal) Left: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-16, 2-3=-21, 5-7=-20, 3-4=-39  
Horz: 1-2=-4, 2-3=1, 4-5=7, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160

Continued on page 3

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))



818 Soundside Road  
Edenton, NC 27932



Job	Truss	Truss Type	Qty	Ply	RVF-LOT #29 ROOF	62587359
23-7316-A	M02	HALF HIP	3	1		
					Job Reference (optional)	

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:02 2023 Page 3  
ID:BxI2MwYau\_NHkbraGCmHloyOvst-5SD8eBqYVPDfezsHT5o0W07mwhM9bpZnmSuf\_Xy8ILB

**LOAD CASE(S)** Standard

- 15) Dead + 0.6 MWFRS Wind (Neg. Internal) Right: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-5, 2-3=-10, 5-7=-20, 3-4=-39  
Horz: 1-2=-15, 2-3=-10, 4-5=-25, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 16) Dead + 0.6 MWFRS Wind (Pos. Internal) 1st Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=32, 2-3=17, 5-7=-12, 3-4=-1  
Horz: 1-2=-44, 2-3=-29, 4-5=23, 3-4=29  
Concentrated Loads (lb)  
Vert: 12=-160
- 17) Dead + 0.6 MWFRS Wind (Pos. Internal) 2nd Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=21, 2-3=6, 5-7=-12, 3-4=-12  
Horz: 1-2=-33, 2-3=-18, 4-5=23, 3-4=18  
Concentrated Loads (lb)  
Vert: 12=-160
- 18) Dead + 0.6 MWFRS Wind (Neg. Internal) 1st Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-16, 2-3=-21, 5-7=-20, 3-4=-39  
Horz: 1-2=-4, 2-3=1, 4-5=12, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 19) Dead + 0.6 MWFRS Wind (Neg. Internal) 2nd Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-16, 2-3=-21, 5-7=-20, 3-4=-39  
Horz: 1-2=-4, 2-3=1, 4-5=12, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 20) Dead + Snow on Overhangs: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-2=-43, 2-3=-20, 5-7=-20, 3-4=-50  
Concentrated Loads (lb)  
Vert: 12=-160
- 21) Dead + Snow (Unbal. Left): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-10=-43, 3-10=-49, 5-7=-20, 3-4=-57  
Concentrated Loads (lb)  
Vert: 12=-160
- 22) Dead + Snow (Unbal. Right): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-27, 5-7=-20, 3-4=-85  
Concentrated Loads (lb)  
Vert: 12=-160
- 23) Dead: Lumber Increase=0.90, Plate Increase=0.90 Plt. metal=0.90  
Uniform Loads (plf)  
Vert: 1-3=-20, 5-7=-20, 3-4=-50  
Concentrated Loads (lb)  
Vert: 12=-160
- 24) Dead + 0.75 Snow (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Left): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-34, 2-3=-38, 5-7=-20, 3-4=-124  
Horz: 1-2=-3, 2-3=1, 4-5=5, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 25) Dead + 0.75 Snow (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Right): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-26, 2-3=-30, 5-7=-20, 3-4=-124  
Horz: 1-2=-11, 2-3=-7, 4-5=-19, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 26) Dead + 0.75 Snow (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-34, 2-3=-38, 5-7=-20, 3-4=-124  
Horz: 1-2=-3, 2-3=1, 4-5=9, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 27) Dead + 0.75 Snow (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-34, 2-3=-38, 5-7=-20, 3-4=-124  
Horz: 1-2=-3, 2-3=1, 4-5=9, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160

Continued on page 4

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))



818 Soundside Road  
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	RVF-LOT #29 ROOF	162587359
23-7316-A	M02	HALF HIP	3	1	Job Reference (optional)	

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:02 2023 Page 4  
ID:BxI2MwYau\_NHkbraGCmHloyOvst-5SD8eBqYVPDFeZsHT5o0W07mwhM9bpZnmSuf\_Xy8ILB

**LOAD CASE(S)** Standard

- 28) Dead + 0.75 Roof Live (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Left): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-47, 2-3=-51, 5-7=-20, 3-4=-129  
Horz: 1-2=-3, 2-3=1, 4-5=5, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 29) Dead + 0.75 Roof Live (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Right): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-39, 2-3=-43, 5-7=-20, 3-4=-129  
Horz: 1-2=-11, 2-3=-7, 4-5=-19, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 30) Dead + 0.75 Roof Live (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-47, 2-3=-51, 5-7=-20, 3-4=-129  
Horz: 1-2=-3, 2-3=1, 4-5=9, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 31) Dead + 0.75 Roof Live (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-47, 2-3=-51, 5-7=-20, 3-4=-129  
Horz: 1-2=-3, 2-3=1, 4-5=9, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 32) Dead + Minimum Snow: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-20, 5-7=-20, 3-4=-80  
Concentrated Loads (lb)  
Vert: 12=-160
- 33) Dead + 0.6 C-C Wind Min. Down: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=4, 2-3=-28, 5-7=-12, 3-4=-46  
Horz: 1-2=-16, 2-3=16, 4-5=-16, 3-4=-16  
Concentrated Loads (lb)  
Vert: 12=-160
- 34) Dead + 0.6 C-C Wind Min. Upward: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-3=4, 5-7=-12, 3-4=-14  
Horz: 1-3=-16, 4-5=16, 3-4=16  
Concentrated Loads (lb)  
Vert: 12=-160
- 35) 3rd Unbal.Dead + Snow (balanced) + Parallel: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-27, 5-7=-20, 3-4=-100  
Concentrated Loads (lb)  
Vert: 12=-160
- 36) 4th Unbal.Dead + Snow (balanced) + Parallel: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-70, 5-7=-20, 3-4=-57  
Concentrated Loads (lb)  
Vert: 12=-160
- 37) 5th Unbal.Dead + 0.75 Snow (balanced) + 0.75 Attic Floor + Parallel: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-25, 5-7=-20, 3-4=-146  
Concentrated Loads (lb)  
Vert: 12=-160
- 38) 6th Unbal.Dead + 0.75 Snow (balanced) + 0.75 Attic Floor + Parallel: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-57, 5-7=-20, 3-4=-114  
Concentrated Loads (lb)  
Vert: 12=-160
- 39) 7th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Left) + Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-22, 2-3=-26, 5-7=-20, 3-4=-137  
Horz: 1-2=-3, 2-3=1, 4-5=5, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 40) 8th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Left) + Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-54, 2-3=-58, 5-7=-20, 3-4=-105  
Horz: 1-2=-3, 2-3=1, 4-5=5, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160

Continued on page 5

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))



818 Soundside Road  
Edenton, NC 27932



Job	Truss	Truss Type	Qty	Ply	RVF-LOT #29 ROOF	162587359
23-7316-A	M02	HALF HIP	3	1	Job Reference (optional)	

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:02 2023 Page 5  
ID:Bxl2MwYau\_NHkbraGCmHloyOvst-5SD8eBqYVPDfezsHT5o0W07mwhM9bpZnmSuf\_Xy8ILB

**LOAD CASE(S)** Standard

- 41) 9th Unbal.Death + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Right) + Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-14, 2-3=-18, 5-7=-20, 3-4=-137  
Horz: 1-2=-11, 2-3=-7, 4-5=-19, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 42) 10th Unbal.Death + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Right) + Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-46, 2-3=-50, 5-7=-20, 3-4=-105  
Horz: 1-2=-11, 2-3=-7, 4-5=-19, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 43) 11th Unbal.Death + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-22, 2-3=-26, 5-7=-20, 3-4=-137  
Horz: 1-2=-3, 2-3=1, 4-5=9, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 44) 12th Unbal.Death + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-54, 2-3=-58, 5-7=-20, 3-4=-105  
Horz: 1-2=-3, 2-3=1, 4-5=9, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 45) 13th Unbal.Death + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-22, 2-3=-26, 5-7=-20, 3-4=-137  
Horz: 1-2=-3, 2-3=1, 4-5=9, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 46) 14th Unbal.Death + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-54, 2-3=-58, 5-7=-20, 3-4=-105  
Horz: 1-2=-3, 2-3=1, 4-5=9, 3-4=-1  
Concentrated Loads (lb)  
Vert: 12=-160
- 47) 15th Unbal.Death + Minimum Snow + Parallel: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-27, 5-7=-20, 3-4=-100  
Concentrated Loads (lb)  
Vert: 12=-160
- 48) 16th Unbal.Death + Minimum Snow + Parallel: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-70, 5-7=-20, 3-4=-57  
Concentrated Loads (lb)  
Vert: 12=-160
- 49) 1st Dead + Roof Live (unbalanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-60, 5-7=-20, 3-4=-90  
Concentrated Loads (lb)  
Vert: 12=-160
- 50) 2nd Dead + Roof Live (unbalanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-20, 5-7=-20, 3-4=-90  
Concentrated Loads (lb)  
Vert: 12=-160
- 51) 3rd Dead + 0.75 Roof Live (unbalanced) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-50, 5-7=-20, 3-4=-139  
Concentrated Loads (lb)  
Vert: 12=-160
- 52) 4th Dead + 0.75 Roof Live (unbalanced) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-20, 5-7=-20, 3-4=-139  
Concentrated Loads (lb)  
Vert: 12=-160

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))



818 Soundside Road  
Edenton, NC 27932

Job 23-7316-A	Truss M03	Truss Type MONOPITCH	Qty 6	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587360
------------------	--------------	-------------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC,


Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:03 2023 Page 1

ID:Bxl2MwYau\_NHkbraGcmHloyOvst-afnWrXrAGjLWG7QT1oKF3DfwN5ixKGfw?6eCWzy8lLA



Scale = 1:10.8



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.16	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.13	Vert(LL) -0.01 4-7 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Vert(CT) -0.01 4-7 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MP	Horz(CT) 0.00 2 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 14 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3


**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 3-8-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 4=Mechanical, 2=0-3-8  
Max Horz 2=48(LC 15)  
Max Uplift 4=5(LC 16), 2=44(LC 16)  
Max Grav 4=136(LC 21), 2=215(LC 21)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-**

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior(1) 2-0-0 to 3-6-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 2.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



December 18, 2023

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)



818 Soundside Road  
Edenton, NC 27932

Job 23-7316-A	Truss M03GE	Truss Type MONOPITCH SUPPORTED	Qty 1	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587361
------------------	----------------	-----------------------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC,


Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:04 2023 Page 1

ID:BxI2MwYau\_NHkbraGCmHloyOvst-2rLv2tso10TMuH?fbWUrUbRC6AU2g3j64DmNm3Qy8IL9



Scale = 1:10.8



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.09	Vert(LL) 0.00	1	n/r	120	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.03	Vert(CT) -0.00	1	n/r	120		
TCDL 10.0	Lumber DOL 1.15	WB 0.05	Horz(CT) 0.00	5	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P					Weight: 15 lb	FT = 20%
BCDL 10.0	Code IRC2018/TPI2014							

**LUMBER-**

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
WEBS	2x4 SP No.3
OTHERS	2x4 SP No.3

**BRACING-**


TOP CHORD	Structural wood sheathing directly applied or 3-8-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 5=3-8-0, 2=3-8-0, 6=3-8-0  
 Max Horz 2=47(LC 13)  
 Max Uplift 5=-3(LC 16), 2=-42(LC 16), 6=-4(LC 16)  
 Max Grav 5=63(LC 21), 2=134(LC 21), 6=154(LC 21)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-**

- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) -1-0-0 to 2-0-0, Exterior(2N) 2-0-0 to 3-6-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 2, 6.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



December 18, 2023

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))




818 Soundside Road  
Edenton, NC 27932

Job 23-7316-A	Truss M04	Truss Type HALF HIP	Qty 3	Ply 1	RVF-LOT #29 ROOF	162587362
------------------	--------------	------------------------	----------	----------	------------------	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:06 2023 Page 1

ID:Bx12MwYau\_NHkbraGCmHloyOvst-\_ETfTzU2Zej47b92iwtygsHF7IfaXchMh4ss7ly8IL7



Scale = 1:17.3





Plate Offsets (X,Y)-- [2:0-1-9,0-0-1]	0-6-8 0-6-8	6-8-0 6-1-8	7-8-0 1-0-0
<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>
TCLL (roof) 20.0	2-0-0	TC 0.95	in (loc) l/defl L/d
Snow (Pf/Pg) 16.5/15.0	Plate Grip DOL 1.15	BC 0.32	Vert(LL) -0.03 7-11 >999 240
TCDL 10.0	Lumber DOL 1.15	WB 0.11	Vert(CT) -0.08 7-11 >999 180
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MP	Horz(CT) 0.00 2 n/a n/a
BCDL 10.0	Code IRC2018/TPI2014		
			<b>PLATES</b> MT20
			<b>GRIP</b> 244/190
			Weight: 30 lb FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins: 4-7, 4-5.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	

**REACTIONS.** (size) 2=0-3-0, 6=Mechanical  
 Max Horz 2=104(LC 16)  
 Max Uplift 2=-22(LC 16)  
 Max Grav 2=465(LC 36), 6=458(LC 28)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 BOT CHORD 6-7=-74/421  
 WEBS 4-6=-557/85

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
  - C-C wind load user defined.
  - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=16.5 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Refer to girder(s) for truss to truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Load case(s) 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).



**LOAD CASE(S)**  
 Continued on page 2

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**  
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPH Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

**ENGINEERING BY**  
**TRENCO**  
 A MITEK Affiliate

818 Soundside Road  
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	RVF-LOT #29 ROOF	162587362
23-7316-A	M04	HALF HIP	3	1		
Job Reference (optional)						

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:06 2023 Page 2  
ID:Bxl2MwYau\_NHkbraGCmHloyOvst-\_ETfTzu2Zej47b92iwtysHF7IfaXchMh4ss7ly8IL7

### LOAD CASE(S)

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-43, 4-5=-83(F=-30), 6-8=-20  
Concentrated Loads (lb)  
Vert: 14=-160
- 2) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-60, 4-5=-90(F=-30), 6-8=-20  
Concentrated Loads (lb)  
Vert: 14=-160
- 3) Dead + 0.75 Roof Live (balanced) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-50, 4-5=-139(F=-89), 6-8=-20  
Concentrated Loads (lb)  
Vert: 14=-160
- 4) Dead + 0.75 Snow (balanced) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-37, 4-5=-133(F=-89), 6-8=-20  
Concentrated Loads (lb)  
Vert: 14=-160
- 5) Dead + 0.75 Snow (Unbal. Left) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-13=-37, 3-13=-42, 4-5=-114(F=-89), 6-8=-20  
Concentrated Loads (lb)  
Vert: 14=-160
- 6) Dead + 0.75 Snow (Unbal. Right) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-25, 4-5=-137(F=-89), 6-8=-20  
Concentrated Loads (lb)  
Vert: 14=-160
- 7) Dead + Uninhabitable Attic Without Storage: Lumber Increase=1.25, Plate Increase=1.25  
Uniform Loads (plf)  
Vert: 1-3=-20, 4-5=-50(F=-30), 6-8=-40  
Concentrated Loads (lb)  
Vert: 14=-160
- 8) Dead + 0.6 C-C Wind (Pos. Internal) Case 1: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=58, 2-12=45, 3-12=34, 4-5=16(F=-18), 6-8=-12  
Horz: 1-2=-70, 2-12=-57, 3-12=-46, 3-4=7, 5-6=36  
Concentrated Loads (lb)  
Vert: 14=-160
- 9) Dead + 0.6 C-C Wind (Pos. Internal) Case 2: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=29, 2-12=34, 3-12=45, 4-5=27(F=-18), 6-8=-12  
Horz: 1-2=-41, 2-12=-46, 3-12=-57, 3-4=-51, 5-6=-23  
Concentrated Loads (lb)  
Vert: 14=-160
- 10) Dead + 0.6 C-C Wind (Neg. Internal) Case 1: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-3, 2-3=-42, 4-5=-60(F=-18), 6-8=-20  
Horz: 1-2=-17, 2-3=22, 3-4=-30, 5-6=-33  
Concentrated Loads (lb)  
Vert: 14=-160
- 11) Dead + 0.6 C-C Wind (Neg. Internal) Case 2: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-37, 2-3=-42, 4-5=-60(F=-18), 6-8=-20  
Horz: 1-2=17, 2-3=22, 3-4=28, 5-6=25  
Concentrated Loads (lb)  
Vert: 14=-160
- 12) Dead + 0.6 MWFRS Wind (Pos. Internal) Left: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=28, 2-3=13, 4-5=8(F=-18), 6-8=-12  
Horz: 1-2=-40, 2-3=-25, 3-4=-11, 5-6=18  
Concentrated Loads (lb)  
Vert: 14=-160
- 13) Dead + 0.6 MWFRS Wind (Pos. Internal) Right: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=3, 2-3=8, 4-5=8(F=-18), 6-8=-12  
Horz: 1-2=-15, 2-3=-20, 3-4=-26, 5-6=-15  
Concentrated Loads (lb)  
Vert: 14=-160
- 14) Dead + 0.6 MWFRS Wind (Neg. Internal) Left: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-16, 2-3=-21, 4-5=-39(F=-18), 6-8=-20  
Horz: 1-2=-4, 2-3=1, 3-4=31, 5-6=7

Continued on page 3

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))



818 Soundside Road  
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	RVF-LOT #29 ROOF	162587362
23-7316-A	M04	HALF HIP	3	1		
					Job Reference (optional)	

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:06 2023 Page 3  
 ID:Bxl2MwYau\_NHkbraGCmHloyOvst\_ETTfZu2Zej47b92iwtysHF7IfaXchMh4ss7ly8IL7

**LOAD CASE(S)**

- Concentrated Loads (lb)  
Vert: 14=-160
- 15) Dead + 0.6 MWFRS Wind (Neg. Internal) Right: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-5, 2-3=-10, 4-5=-39(F=-18), 6-8=-20  
Horz: 1-2=-15, 2-3=-10, 3-4=-4, 5-6=-25  
Concentrated Loads (lb)  
Vert: 14=-160
- 16) Dead + 0.6 MWFRS Wind (Pos. Internal) 1st Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=32, 2-3=17, 4-5=-1(F=-18), 6-8=-12  
Horz: 1-2=-44, 2-3=-29, 3-4=-34, 5-6=23  
Concentrated Loads (lb)  
Vert: 14=-160
- 17) Dead + 0.6 MWFRS Wind (Pos. Internal) 2nd Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=21, 2-3=6, 4-5=-12(F=-18), 6-8=-12  
Horz: 1-2=-33, 2-3=-18, 3-4=-24, 5-6=23  
Concentrated Loads (lb)  
Vert: 14=-160
- 18) Dead + 0.6 MWFRS Wind (Neg. Internal) 1st Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-16, 2-3=-21, 4-5=-39(F=-18), 6-8=-20  
Horz: 1-2=-4, 2-3=1, 3-4=6, 5-6=12  
Concentrated Loads (lb)  
Vert: 14=-160
- 19) Dead + 0.6 MWFRS Wind (Neg. Internal) 2nd Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-16, 2-3=-21, 4-5=-39(F=-18), 6-8=-20  
Horz: 1-2=-4, 2-3=1, 3-4=6, 5-6=12  
Concentrated Loads (lb)  
Vert: 14=-160
- 20) Dead + Snow on Overhangs: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-2=-43, 2-3=-20, 4-5=-50(F=-30), 6-8=-20  
Concentrated Loads (lb)  
Vert: 14=-160
- 21) Dead + Snow (Unbal. Left): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-13=-43, 3-13=-49, 4-5=-57(F=-30), 6-8=-20  
Concentrated Loads (lb)  
Vert: 14=-160
- 22) Dead + Snow (Unbal. Right): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-27, 4-5=-88(F=-30), 6-8=-20  
Concentrated Loads (lb)  
Vert: 14=-160
- 23) Dead: Lumber Increase=0.90, Plate Increase=0.90 Plt. metal=0.90  
Uniform Loads (plf)  
Vert: 1-3=-20, 4-5=-50(F=-30), 6-8=-20  
Concentrated Loads (lb)  
Vert: 14=-160
- 24) Dead + 0.75 Snow (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Left): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-34, 2-3=-38, 4-5=-124(F=-79), 6-8=-20  
Horz: 1-2=-3, 2-3=1, 3-4=23, 5-6=5  
Concentrated Loads (lb)  
Vert: 14=-160
- 25) Dead + 0.75 Snow (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Right): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-26, 2-3=-30, 4-5=-124(F=-79), 6-8=-20  
Horz: 1-2=-11, 2-3=-7, 3-4=-3, 5-6=-19  
Concentrated Loads (lb)  
Vert: 14=-160
- 26) Dead + 0.75 Snow (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-34, 2-3=-38, 4-5=-124(F=-79), 6-8=-20  
Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9  
Concentrated Loads (lb)  
Vert: 14=-160
- 27) Dead + 0.75 Snow (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60

Continued on page 4

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPH Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))



818 Soundside Road  
Edenton, NC 27932



Job	Truss	Truss Type	Qty	Ply	RVF-LOT #29 ROOF	162587362
23-7316-A	M04	HALF HIP	3	1	Job Reference (optional)	

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:06 2023 Page 4  
ID:BxI2MwYau\_NHkbraGCmHloyOvst\_ETTfZu2Zej47b92iwtysHF7IfaXchMh4ss7ly8IL7

### LOAD CASE(S)

- Uniform Loads (plf)  
Vert: 1-2=-34, 2-3=-38, 4-5=-124(F=-79), 6-8=-20  
Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9
- Concentrated Loads (lb)  
Vert: 14=-160
- 28) Dead + 0.75 Roof Live (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Left): Lumber Increase=1.60, Plate Increase=1.60
- Uniform Loads (plf)  
Vert: 1-2=-47, 2-3=-51, 4-5=-129(F=-79), 6-8=-20  
Horz: 1-2=-3, 2-3=1, 3-4=23, 5-6=5
- Concentrated Loads (lb)  
Vert: 14=-160
- 29) Dead + 0.75 Roof Live (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Right): Lumber Increase=1.60, Plate Increase=1.60
- Uniform Loads (plf)  
Vert: 1-2=-39, 2-3=-43, 4-5=-129(F=-79), 6-8=-20  
Horz: 1-2=-11, 2-3=-7, 3-4=-3, 5-6=-19
- Concentrated Loads (lb)  
Vert: 14=-160
- 30) Dead + 0.75 Roof Live (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60
- Uniform Loads (plf)  
Vert: 1-2=-47, 2-3=-51, 4-5=-129(F=-79), 6-8=-20  
Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9
- Concentrated Loads (lb)  
Vert: 14=-160
- 31) Dead + 0.75 Roof Live (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60
- Uniform Loads (plf)  
Vert: 1-2=-47, 2-3=-51, 4-5=-129(F=-79), 6-8=-20  
Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9
- Concentrated Loads (lb)  
Vert: 14=-160
- 32) Dead + Minimum Snow: Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (plf)  
Vert: 1-3=-20, 4-5=-80(F=-30), 6-8=-20
- Concentrated Loads (lb)  
Vert: 14=-160
- 33) Dead + 0.6 C-C Wind Min. Down: Lumber Increase=1.60, Plate Increase=1.60
- Uniform Loads (plf)  
Vert: 1-2=4, 2-3=-28, 4-5=-46(F=-18), 6-8=-12  
Horz: 1-2=-16, 2-3=16, 3-4=-16, 5-6=-16
- Concentrated Loads (lb)  
Vert: 14=-160
- 34) Dead + 0.6 C-C Wind Min. Upward: Lumber Increase=1.60, Plate Increase=1.60
- Uniform Loads (plf)  
Vert: 1-3=4, 4-5=-14(F=-18), 6-8=-12  
Horz: 1-3=-16, 3-4=16, 5-6=16
- Concentrated Loads (lb)  
Vert: 14=-160
- 35) 3rd Unbal. Dead + Snow (balanced) + Parallel: Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (plf)  
Vert: 1-3=-27, 4-5=-100(F=-30), 6-8=-20
- Concentrated Loads (lb)  
Vert: 14=-160
- 36) 4th Unbal. Dead + Snow (balanced) + Parallel: Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (plf)  
Vert: 1-3=-70, 4-5=-57(F=-30), 6-8=-20
- Concentrated Loads (lb)  
Vert: 14=-160
- 37) 5th Unbal. Dead + 0.75 Snow (balanced) + 0.75 Attic Floor + Parallel: Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (plf)  
Vert: 1-3=-25, 4-5=-146(F=-89), 6-8=-20
- Concentrated Loads (lb)  
Vert: 14=-160
- 38) 6th Unbal. Dead + 0.75 Snow (balanced) + 0.75 Attic Floor + Parallel: Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (plf)  
Vert: 1-3=-57, 4-5=-114(F=-89), 6-8=-20
- Concentrated Loads (lb)  
Vert: 14=-160
- 39) 7th Unbal. Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Left) + Parallel: Lumber Increase=1.60, Plate Increase=1.60
- Uniform Loads (plf)  
Vert: 1-2=-22, 2-3=-26, 4-5=-137(F=-79), 6-8=-20  
Horz: 1-2=-3, 2-3=1, 3-4=23, 5-6=5
- Concentrated Loads (lb)  
Vert: 14=-160

Continued on page 5

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))



818 Soundside Road  
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	RVF-LOT #29 ROOF	162587362
23-7316-A	M04	HALF HIP	3	1	Job Reference (optional)	

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:06 2023 Page 5  
 ID:Bx12MwYau\_NHkbraGCmHloyOvst\_ETTfZu2Zej47b92iwtysHF7IfaXchMh4ss7ly8IL7

**LOAD CASE(S)**

- 40) 8th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Left) + Parallel: Lumber Increase=1.60, Plate Increase=1.60  
 Uniform Loads (plf)  
 Vert: 1-2=-54, 2-3=-58, 4-5=-105(F=-79), 6-8=-20  
 Horz: 1-2=-3, 2-3=1, 3-4=23, 5-6=5  
 Concentrated Loads (lb)  
 Vert: 14=-160
- 41) 9th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Right) + Parallel: Lumber Increase=1.60, Plate Increase=1.60  
 Uniform Loads (plf)  
 Vert: 1-2=-14, 2-3=-18, 4-5=-137(F=-79), 6-8=-20  
 Horz: 1-2=-11, 2-3=-7, 3-4=-3, 5-6=-19  
 Concentrated Loads (lb)  
 Vert: 14=-160
- 42) 10th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Right) + Parallel: Lumber Increase=1.60, Plate Increase=1.60  
 Uniform Loads (plf)  
 Vert: 1-2=-46, 2-3=-50, 4-5=-105(F=-79), 6-8=-20  
 Horz: 1-2=-11, 2-3=-7, 3-4=-3, 5-6=-19  
 Concentrated Loads (lb)  
 Vert: 14=-160
- 43) 11th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60  
 Uniform Loads (plf)  
 Vert: 1-2=-22, 2-3=-26, 4-5=-137(F=-79), 6-8=-20  
 Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9  
 Concentrated Loads (lb)  
 Vert: 14=-160
- 44) 12th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60  
 Uniform Loads (plf)  
 Vert: 1-2=-54, 2-3=-58, 4-5=-105(F=-79), 6-8=-20  
 Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9  
 Concentrated Loads (lb)  
 Vert: 14=-160
- 45) 13th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60  
 Uniform Loads (plf)  
 Vert: 1-2=-22, 2-3=-26, 4-5=-137(F=-79), 6-8=-20  
 Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9  
 Concentrated Loads (lb)  
 Vert: 14=-160
- 46) 14th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60  
 Uniform Loads (plf)  
 Vert: 1-2=-54, 2-3=-58, 4-5=-105(F=-79), 6-8=-20  
 Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9  
 Concentrated Loads (lb)  
 Vert: 14=-160
- 47) 15th Unbal.Dead + Minimum Snow + Parallel: Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-3=-27, 4-5=-100(F=-30), 6-8=-20  
 Concentrated Loads (lb)  
 Vert: 14=-160
- 48) 16th Unbal.Dead + Minimum Snow + Parallel: Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-3=-70, 4-5=-57(F=-30), 6-8=-20  
 Concentrated Loads (lb)  
 Vert: 14=-160
- 49) 1st Dead + Roof Live (unbalanced): Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-3=-60, 4-5=-50(F=-30), 6-8=-20  
 Concentrated Loads (lb)  
 Vert: 14=-160
- 50) 2nd Dead + Roof Live (unbalanced): Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-3=-20, 4-5=-90(F=-30), 6-8=-20  
 Concentrated Loads (lb)  
 Vert: 14=-160
- 51) 3rd Dead + 0.75 Roof Live (unbalanced) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-3=-50, 4-5=-109(F=-89), 6-8=-20  
 Concentrated Loads (lb)  
 Vert: 14=-160
- 52) 4th Dead + 0.75 Roof Live (unbalanced) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-3=-20, 4-5=-139(F=-89), 6-8=-20  
 Concentrated Loads (lb)  
 Vert: 14=-160

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))




818 Soundside Road  
 Edenton, NC 27932

Job 23-7316-A	Truss M04SGE	Truss Type GABLE	Qty 1	Ply 1	RVF-LOT #29 ROOF	162587363
------------------	-----------------	---------------------	----------	----------	------------------	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:07 2023 Page 1

ID:BxI2MwYau\_NHkbraGcmHloyOvst-SQ11huugKxrllkEGeOBD3qUki?CG4qWwkcQfIy8IL6



Scale = 1:17.3




Plate Offsets (X,Y)-- [2:0-2-8,0-1-6]	0-6-8 0-6-8	4-1-12 3-7-4	6-8-0 2-6-4	7-8-0 1-0-0
<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>
TCLL (roof) 20.0	2-0-0	TC 0.64	in (loc) l/defl L/d	MT20 244/190
Snow (Pf/Pg) 16.5/15.0	Plate Grip DOL 1.15	BC 0.36	Vert(LL) -0.02 13 >999 240	
TCDL 10.0	Lumber DOL 1.15	WB 0.05	Vert(CT) 0.02 13 >999 180	
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MP	Horz(CT) -0.00 2 n/a n/a	
BCDL 10.0	Code IRC2018/TPI2014			Weight: 33 lb FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins: 4-7, 4-5.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	
OTHERS 2x4 SP No.3	

**REACTIONS.** (size) 2=0-3-0, 6=Mechanical, 8=0-3-8  
 Max Horz 2=104(LC 16)  
 Max Uplift 2=40(LC 16)  
 Max Grav 2=384(LC 36), 6=382(LC 28), 8=185(LC 7)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 WEBS 4-6=-281/96

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) C-C wind load user defined.
  - 4) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - 5) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=16.5 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
  - 6) Unbalanced snow loads have been considered for this design.
  - 7) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - 8) Provide adequate drainage to prevent water ponding.
  - 9) Gable studs spaced at 2-0-0 oc.
  - 10) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 11) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 12) Refer to girder(s) for truss to truss connections.
  - 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2.
  - 14) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 15) Load case(s) 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - 16) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Continued on page 2

**LOAD CASE(S)**

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

**ENGINEERING BY**  
**TRENCO**  
 A MiTek Affiliate

818 Soundside Road  
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	RVF-LOT #29 ROOF	162587363
23-7316-A	M04SGE	GABLE	1	1	Job Reference (optional)	

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:07 2023 Page 2  
ID:BxI2MwYau\_NHKbraGCmHloyOvst-SQ11huugKrxrllkEGeOBD3qUki?CG4qWwkcQfly8IL6

### LOAD CASE(S)

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-43, 4-5=-83, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 2) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-60, 4-5=-90, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 3) Dead + 0.75 Roof Live (balanced) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-50, 4-5=-139, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 4) Dead + 0.75 Snow (balanced) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-37, 4-5=-133, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 5) Dead + 0.75 Snow (Unbal. Left) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-17=-37, 3-17=-42, 4-5=-114, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 6) Dead + 0.75 Snow (Unbal. Right) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-25, 4-5=-137, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 7) Dead + Uninhabitable Attic Without Storage: Lumber Increase=1.25, Plate Increase=1.25  
Uniform Loads (plf)  
Vert: 1-3=-20, 4-5=-50, 6-13=-40  
Concentrated Loads (lb)  
Vert: 18=-160
- 8) Dead + 0.6 C-C Wind (Pos. Internal) Case 1: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=61, 2-3=52, 4-5=34, 6-13=-12  
Horz: 1-2=-73, 2-3=-64, 3-4=7, 5-6=36  
Concentrated Loads (lb)  
Vert: 18=-160
- 9) Dead + 0.6 C-C Wind (Pos. Internal) Case 2: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=47, 2-3=52, 4-5=34, 6-13=-12  
Horz: 1-2=-59, 2-3=-64, 3-4=-69, 5-6=-23  
Concentrated Loads (lb)  
Vert: 18=-160
- 10) Dead + 0.6 C-C Wind (Neg. Internal) Case 1: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-3, 2-3=-42, 4-5=-60, 6-13=-20  
Horz: 1-2=-17, 2-3=22, 3-4=-48, 5-6=-33  
Concentrated Loads (lb)  
Vert: 18=-160
- 11) Dead + 0.6 C-C Wind (Neg. Internal) Case 2: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-37, 2-3=-42, 4-5=-60, 6-13=-20  
Horz: 1-2=17, 2-3=22, 3-4=28, 5-6=25  
Concentrated Loads (lb)  
Vert: 18=-160
- 12) Dead + 0.6 MWFRS Wind (Pos. Internal) Left: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=28, 2-3=13, 4-5=8, 6-13=-12  
Horz: 1-2=-40, 2-3=-25, 3-4=-11, 5-6=18  
Concentrated Loads (lb)  
Vert: 18=-160
- 13) Dead + 0.6 MWFRS Wind (Pos. Internal) Right: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=3, 2-3=8, 4-5=8, 6-13=-12  
Horz: 1-2=-15, 2-3=-20, 3-4=-26, 5-6=-15  
Concentrated Loads (lb)  
Vert: 18=-160
- 14) Dead + 0.6 MWFRS Wind (Neg. Internal) Left: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-16, 2-3=-21, 4-5=-39, 6-13=-20  
Horz: 1-2=-4, 2-3=1, 3-4=31, 5-6=7

Continued on page 3

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))



818 Soundside Road  
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	RVF-LOT #29 ROOF	162587363
23-7316-A	M04SGE	GABLE	1	1	Job Reference (optional)	

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:07 2023 Page 3  
ID:Bxl2MwYau\_NHKbraGCmHloyOvst-SQ11huugKrxllkEGeOBD3qUki?CG4qWwkcQfly8IL6

**LOAD CASE(S)**

- Concentrated Loads (lb)  
Vert: 18=-160
- 15) Dead + 0.6 MWFRS Wind (Neg. Internal) Right: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-5, 2-3=-10, 4-5=-39, 6-13=-20  
Horz: 1-2=-15, 2-3=-10, 3-4=-4, 5-6=-25  
Concentrated Loads (lb)  
Vert: 18=-160
- 16) Dead + 0.6 MWFRS Wind (Pos. Internal) 1st Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=32, 2-3=17, 4-5=-1, 6-13=-12  
Horz: 1-2=-44, 2-3=-29, 3-4=-34, 5-6=23  
Concentrated Loads (lb)  
Vert: 18=-160
- 17) Dead + 0.6 MWFRS Wind (Pos. Internal) 2nd Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=21, 2-3=6, 4-5=-12, 6-13=-12  
Horz: 1-2=-33, 2-3=-18, 3-4=-24, 5-6=23  
Concentrated Loads (lb)  
Vert: 18=-160
- 18) Dead + 0.6 MWFRS Wind (Neg. Internal) 1st Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-16, 2-3=-21, 4-5=-39, 6-13=-20  
Horz: 1-2=-4, 2-3=1, 3-4=6, 5-6=12  
Concentrated Loads (lb)  
Vert: 18=-160
- 19) Dead + 0.6 MWFRS Wind (Neg. Internal) 2nd Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-16, 2-3=-21, 4-5=-39, 6-13=-20  
Horz: 1-2=-4, 2-3=1, 3-4=6, 5-6=12  
Concentrated Loads (lb)  
Vert: 18=-160
- 20) Dead + Snow on Overhangs: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-2=-43, 2-3=-20, 4-5=-50, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 21) Dead + Snow (Unbal. Left): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-17=-43, 3-17=-49, 4-5=-57, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 22) Dead + Snow (Unbal. Right): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-27, 4-5=-88, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 23) Dead: Lumber Increase=0.90, Plate Increase=0.90 Plt. metal=0.90  
Uniform Loads (plf)  
Vert: 1-3=-20, 4-5=-50, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 24) Dead + 0.75 Snow (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Left): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-34, 2-3=-38, 4-5=-124, 6-13=-20  
Horz: 1-2=-3, 2-3=1, 3-4=23, 5-6=5  
Concentrated Loads (lb)  
Vert: 18=-160
- 25) Dead + 0.75 Snow (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Right): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-26, 2-3=-30, 4-5=-124, 6-13=-20  
Horz: 1-2=-11, 2-3=-7, 3-4=-3, 5-6=-19  
Concentrated Loads (lb)  
Vert: 18=-160
- 26) Dead + 0.75 Snow (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-34, 2-3=-38, 4-5=-124, 6-13=-20  
Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9  
Concentrated Loads (lb)  
Vert: 18=-160
- 27) Dead + 0.75 Snow (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60

Continued on page 4

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))



818 Soundside Road  
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	RVF-LOT #29 ROOF	162587363
23-7316-A	M04SGE	GABLE	1	1	Job Reference (optional)	

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:07 2023 Page 4  
ID:BxI2MwYau\_NHKbraGCmHloyOvst-SQ11huugKrxllkEGeOBD3qUki?CG4qWwkcQfly8IL6

**LOAD CASE(S)**

- Uniform Loads (plf)
  - Vert: 1-2=-34, 2-3=-38, 4-5=-124, 6-13=-20
  - Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9
- Concentrated Loads (lb)
  - Vert: 18=-160
- 28) Dead + 0.75 Roof Live (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Left): Lumber Increase=1.60, Plate Increase=1.60
  - Uniform Loads (plf)
    - Vert: 1-2=-47, 2-3=-51, 4-5=-129, 6-13=-20
    - Horz: 1-2=-3, 2-3=1, 3-4=23, 5-6=5
  - Concentrated Loads (lb)
    - Vert: 18=-160
- 29) Dead + 0.75 Roof Live (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Right): Lumber Increase=1.60, Plate Increase=1.60
  - Uniform Loads (plf)
    - Vert: 1-2=-39, 2-3=-43, 4-5=-129, 6-13=-20
    - Horz: 1-2=-11, 2-3=-7, 3-4=-3, 5-6=-19
  - Concentrated Loads (lb)
    - Vert: 18=-160
- 30) Dead + 0.75 Roof Live (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60
  - Uniform Loads (plf)
    - Vert: 1-2=-47, 2-3=-51, 4-5=-129, 6-13=-20
    - Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9
  - Concentrated Loads (lb)
    - Vert: 18=-160
- 31) Dead + 0.75 Roof Live (bal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60
  - Uniform Loads (plf)
    - Vert: 1-2=-47, 2-3=-51, 4-5=-129, 6-13=-20
    - Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9
  - Concentrated Loads (lb)
    - Vert: 18=-160
- 32) Dead + Minimum Snow: Lumber Increase=1.15, Plate Increase=1.15
  - Uniform Loads (plf)
    - Vert: 1-3=-20, 4-5=-80, 6-13=-20
  - Concentrated Loads (lb)
    - Vert: 18=-160
- 33) Dead + 0.6 C-C Wind Min. Down: Lumber Increase=1.60, Plate Increase=1.60
  - Uniform Loads (plf)
    - Vert: 1-2=4, 2-3=-28, 4-5=-46, 6-13=-12
    - Horz: 1-2=-16, 2-3=16, 3-4=-16, 5-6=-16
  - Concentrated Loads (lb)
    - Vert: 18=-160
- 34) Dead + 0.6 C-C Wind Min. Upward: Lumber Increase=1.60, Plate Increase=1.60
  - Uniform Loads (plf)
    - Vert: 1-3=4, 4-5=-14, 6-13=-12
    - Horz: 1-3=-16, 3-4=16, 5-6=16
  - Concentrated Loads (lb)
    - Vert: 18=-160
- 35) 3rd Unbal.Dead + Snow (balanced) + Parallel: Lumber Increase=1.15, Plate Increase=1.15
  - Uniform Loads (plf)
    - Vert: 1-3=-27, 4-5=-100, 6-13=-20
  - Concentrated Loads (lb)
    - Vert: 18=-160
- 36) 4th Unbal.Dead + Snow (balanced) + Parallel: Lumber Increase=1.15, Plate Increase=1.15
  - Uniform Loads (plf)
    - Vert: 1-3=-70, 4-5=-57, 6-13=-20
  - Concentrated Loads (lb)
    - Vert: 18=-160
- 37) 5th Unbal.Dead + 0.75 Snow (balanced) + 0.75 Attic Floor + Parallel: Lumber Increase=1.15, Plate Increase=1.15
  - Uniform Loads (plf)
    - Vert: 1-3=-25, 4-5=-146, 6-13=-20
  - Concentrated Loads (lb)
    - Vert: 18=-160
- 38) 6th Unbal.Dead + 0.75 Snow (balanced) + 0.75 Attic Floor + Parallel: Lumber Increase=1.15, Plate Increase=1.15
  - Uniform Loads (plf)
    - Vert: 1-3=-57, 4-5=-114, 6-13=-20
  - Concentrated Loads (lb)
    - Vert: 18=-160
- 39) 7th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Left) + Parallel: Lumber Increase=1.60, Plate Increase=1.60
  - Uniform Loads (plf)
    - Vert: 1-2=-22, 2-3=-26, 4-5=-137, 6-13=-20
    - Horz: 1-2=-3, 2-3=1, 3-4=23, 5-6=5
  - Concentrated Loads (lb)
    - Vert: 18=-160

Continued on page 5

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))



818 Soundside Road  
Edenton, NC 27932



Job	Truss	Truss Type	Qty	Ply	RVF-LOT #29 ROOF	I62587363
23-7316-A	M04SGE	GABLE	1	1	Job Reference (optional)	

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:07 2023 Page 5  
ID:BxI2MwYau\_NHKbraGCmHloyOvst-SQ11huugKxrllkEGeOBD3qUki?CG4qWwkcQfily8IL6

**LOAD CASE(S)**

- 40) 8th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Left) + Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-54, 2-3=-58, 4-5=-105, 6-13=-20  
Horz: 1-2=-3, 2-3=1, 3-4=23, 5-6=5  
Concentrated Loads (lb)  
Vert: 18=-160
- 41) 9th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Right) + Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-14, 2-3=-18, 4-5=-137, 6-13=-20  
Horz: 1-2=-11, 2-3=-7, 3-4=-3, 5-6=-19  
Concentrated Loads (lb)  
Vert: 18=-160
- 42) 10th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) Right) + Parallel: Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-46, 2-3=-50, 4-5=-105, 6-13=-20  
Horz: 1-2=-11, 2-3=-7, 3-4=-3, 5-6=-19  
Concentrated Loads (lb)  
Vert: 18=-160
- 43) 11th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-22, 2-3=-26, 4-5=-137, 6-13=-20  
Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9  
Concentrated Loads (lb)  
Vert: 18=-160
- 44) 12th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-54, 2-3=-58, 4-5=-105, 6-13=-20  
Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9  
Concentrated Loads (lb)  
Vert: 18=-160
- 45) 13th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-22, 2-3=-26, 4-5=-137, 6-13=-20  
Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9  
Concentrated Loads (lb)  
Vert: 18=-160
- 46) 14th Unbal.Dead + 0.75 Snow (unbal.) + 0.75 Attic Floor + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60  
Uniform Loads (plf)  
Vert: 1-2=-54, 2-3=-58, 4-5=-105, 6-13=-20  
Horz: 1-2=-3, 2-3=1, 3-4=5, 5-6=9  
Concentrated Loads (lb)  
Vert: 18=-160
- 47) 15th Unbal.Dead + Minimum Snow + Parallel: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-27, 4-5=-100, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 48) 16th Unbal.Dead + Minimum Snow + Parallel: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-70, 4-5=-57, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 49) 1st Dead + Roof Live (unbalanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-60, 4-5=-50, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 50) 2nd Dead + Roof Live (unbalanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-20, 4-5=-90, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 51) 3rd Dead + 0.75 Roof Live (unbalanced) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-50, 4-5=-109, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160
- 52) 4th Dead + 0.75 Roof Live (unbalanced) + 0.75 Attic Floor: Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (plf)  
Vert: 1-3=-20, 4-5=-139, 6-13=-20  
Concentrated Loads (lb)  
Vert: 18=-160

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))




818 Soundside Road  
Edenton, NC 27932

Job 23-7316-A	Truss T01	Truss Type Common	Qty 5	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587364
------------------	--------------	----------------------	----------	----------	--	-----------


Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:08 2023 Page 1

ID:BxI2MwYau\_NHkbraGcmHloyOvst-wcbPuEvi5FzoMujRqLvQIHnIC6Jh?WEf8OLzCBy8IL5



Scale = 1:22.4



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.47	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.47	Vert(LL) -0.05 6-12 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.11	Vert(CT) -0.09 6-12 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.01 4 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 44 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	

**REACTIONS.** (size) 2=0-3-8, 4=0-3-8  
 Max Horz 2=-37(LC 14)  
 Max Uplift 2=-61(LC 16), 4=-61(LC 16)  
 Max Grav 2=540(LC 2), 4=540(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-763/235, 3-4=-763/235  
 BOT CHORD 2-6=-115/652, 4-6=-115/652  
 WEBS 3-6=0/280

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior(1) 2-0-0 to 6-0-0, Exterior(2R) 6-0-0 to 9-0-0, Interior(1) 9-0-0 to 13-0-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




December 18, 2023


Job 23-7316-A	Truss T01GE	Truss Type GABLE	Qty 1	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587365
------------------	----------------	---------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:09 2023 Page 1  
ID:Bxl2MwYau\_NHkbraGCmHloyOvst-Op9o6awxsZ5f\_2udN3QflUvzFVmrk\_cpN25Xkdy8LL4



Scale = 1:22.4



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.07	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.03	Vert(LL) -0.00 9 n/r 120		
TCDL 10.0	Lumber DOL 1.15	WB 0.03	Vert(CT) -0.00 9 n/r 120		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 8 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 50 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
OTHERS 2x4 SP No.3


**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 12-0-0.  
(lb) - Max Horz 2=-37(LC 14)  
Max Uplift All uplift 100 lb or less at joint(s) 2, 8, 13, 14, 11, 10  
Max Grav All reactions 250 lb or less at joint(s) 2, 8, 12, 13, 14, 11, 10

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) -1-0-0 to 2-0-0, Exterior(2N) 2-0-0 to 6-0-0, Corner(3R) 6-0-0 to 9-0-0, Exterior(2N) 9-0-0 to 13-0-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8, 13, 14, 11, 10.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



December 18, 2023

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPH Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)



818 Soundside Road  
Edenton, NC 27932

Job 23-7316-A	Truss T02	Truss Type Common	Qty 1	Ply 1	RVF-LOT #29 ROOF	162587366
------------------	--------------	----------------------	----------	----------	------------------	-----------

Riverside Roof Truss, LLC,

Danville, Va - 24541,


8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:11 2023 Page 1

ID:BxI2MwYau\_NHkbraGcmHloyOvst-LBGyWGxBNALNDM20VUT7Nv?CPJFBCob6qMadoWy8IL2



4x5 ||

Scale = 1:51.3



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.54	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.81	Vert(LL) -0.16 9-11 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.39	Vert(CT) -0.25 11-12 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.04 8 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 150 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 4-7-10 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 3-12, 5-8

**REACTIONS.** (size) 12=0-3-8, 8=0-3-8  
 Max Horz 12=189(LC 15)  
 Max Uplift 12=-97(LC 16), 8=-97(LC 16)  
 Max Grav 12=1185(LC 28), 8=1185(LC 29)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-414/125, 3-4=-1368/197, 4-5=-1369/197, 5-6=-414/125, 2-12=-406/135, 6-8=-405/135  
 BOT CHORD 11-12=-60/1285, 9-11=0/910, 8-9=-49/1174  
 WEBS 4-9=-46/613, 5-9=-264/162, 4-11=-46/613, 3-11=-264/162, 3-12=-1151/49, 5-8=-1151/49

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=25ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior(1) 2-0-0 to 12-7-12, Exterior(2R) 12-7-12 to 15-7-12, Interior(1) 15-7-12 to 26-3-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - 4) Unbalanced snow loads have been considered for this design.
  - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 7) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 12, 8.
  - 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



Job 23-7316-A	Truss T02G	Truss Type COMMON GIRDER	Qty 1	Ply 3	RVF-LOT #29 ROOF	162587367
------------------	---------------	-----------------------------	----------	----------	------------------	-----------

Riverside Roof Truss, LLC,

Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:14 2023 Page 1

ID: Bxl2MwYau\_NHkbraGCmHloyOvst-lmyh9l\_3g5jy4pmaAc0q?YdcyWNPnYXJoIPry8IL?



4x6 ||

Scale = 1:59.2




Plate Offsets (X, Y)--	[2:0-2-12,0-2-0], [8:0-3-8,Edge], [10:0-3-8,0-5-0], [11:0-3-8,0-5-4], [12:0-6-0,0-6-4], [14:0-3-8,0-6-0], [15:0-3-8,0-3-8]
------------------------	--

LOADING (psf)	SPACING-	CSL	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.96	in (loc) l/defl L/d	MT20 244/190	
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.43	Vert(LL) -0.16 11-12 >999 240	MT20HS 187/143	
TCDL 10.0	Lumber DOL 1.15	WB 0.93	Vert(CT) -0.30 11-12 >999 180		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MS	Horz(CT) 0.05 9 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 618 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 4-3-12 oc purlins, except end verticals.
BOT CHORD 2x8 SP DSS	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3 *Except* 5-12,2-16: 2x4 SP No.2, 2-15,8-9,8-10: 2x4 SP No.1	

REACTIONS.
(size) 16=0-3-8, 9=0-3-8
Max Horz 16=181(LC 11)
Max Uplift 16=505(LC 12), 9=437(LC 12)
Max Grav 16=11412(LC 3), 9=13439(LC 3)

FORCES.
(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-15248/621, 3-4=-14264/545, 4-5=-11617/467, 5-6=-11617/467, 6-7=-14856/512, 7-8=-17112/536, 2-16=-9988/451, 8-9=-11092/357
BOT CHORD 15-16=-167/1661, 14-15=-470/13079, 12-14=-337/12297, 11-12=-307/12806, 10-11=-399/14702, 9-10=-74/1950
WEBS 5-12=-394/11421, 6-12=-4775/187, 6-11=-102/5292, 7-11=-2444/118, 7-10=-110/2558, 4-12=-3908/237, 4-14=-158/4290, 3-14=-1034/170, 3-15=-165/1055, 2-15=-386/11608, 8-10=-331/12964

- NOTES-**
- 3-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x4 - 1 row at 0-7-0 oc.  
Bottom chords connected as follows: 2x8 - 3 rows staggered at 0-5-0 oc.  
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=25ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - All plates are MT20 plates unless otherwise indicated.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Bearing at joint(s) 16, 9 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify compatibility of bearing surface.



**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

**ENGINEERING BY**  
**TRENCO**  
A MiTek Affiliate

818 Soundside Road  
Edenton, NC 27932

Job 23-7316-A	Truss T02G	Truss Type COMMON GIRDER	Qty 1	Ply <b>3</b>	RVF-LOT #29 ROOF Job Reference (optional)	162587367
------------------	---------------	-----------------------------	----------	-----------------	--	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:14 2023 Page 2  
ID:Bxl2MwYau\_NHkbraGCmHloyOvst-Imyh9l\_3g5jy4pmaAc0q?YdcyWNP1nYXJoIPry8IL?

**NOTES-**

- 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 16=505, 9=437.
- 13) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 14) Use Simpson Strong-Tie HUS28 (22-10d Girder, 4-10d Truss, Single Ply Girder) or equivalent spaced at 20-10-0 oc max. starting at 1-11-4 from the left end to 23-11-4 to connect truss(es) to front face of bottom chord.
- 15) Use Simpson Strong-Tie HUS26 (14-10d Girder, 4-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 3-11-4 from the left end to 20-9-4 to connect truss(es) to front face of bottom chord.
- 16) Fill all nail holes where hanger is in contact with lumber.

**LOAD CASE(S)** Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-2=-43, 2-5=-43, 5-8=-43, 9-16=-20

Concentrated Loads (lb)

Vert: 10=-1270(F) 17=-1170(F) 18=-1170(F) 19=-1170(F) 20=-1270(F) 21=-1270(F) 22=-1270(F) 23=-1270(F) 24=-1270(F) 25=-1270(F) 26=-1270(F) 27=-1270(F)  
28=-1170(F)

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Component Association ([www.sbcacomponents.com](http://www.sbcacomponents.com))



818 Soundside Road  
Edenton, NC 27932






Job 23-7316-A	Truss T03	Truss Type Common	Qty 6	Ply 1	RVF-LOT #29 ROOF	162587369
------------------	--------------	----------------------	----------	----------	------------------	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,


8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:17 2023 Page 1

ID:BxI2MwYau\_NHkbraGCmHloyOvst-9LdpmJ0yz06WxHV9rkaXdAFACkHlcQ8\_DH1y?9y8lKy

Job Reference (optional)



Scale = 1:65.2



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15		TC 0.77	Vert(LL) -0.29	13-15	>999	240	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Lumber DOL 1.15		BC 0.89	Vert(CT) -0.52	13-15	>885	180		
TCDL 10.0	Rep Stress Incr YES		WB 0.77	Horz(CT) 0.13	12	n/a	n/a		
BCLL 0.0 *	Code IRC2018/TPI2014		Matrix-MS					Weight: 215 lb	FT = 20%
BCDL 10.0									

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 3-1-4 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 7-15, 5-15, 3-18, 9-12

<b>REACTIONS.</b>	(size) 18=0-3-8, 12=0-3-8
	Max Horz 18=160(LC 15)
	Max Uplift 18=128(LC 16), 12=128(LC 16)
	Max Grav 18=1744(LC 28), 12=1744(LC 29)

<b>FORCES.</b>	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-611/102, 3-5=-2859/256, 5-6=-2123/271, 6-7=-2123/271, 7-9=-2859/256, 9-10=-611/102, 2-18=-457/147, 10-12=-457/147
BOT CHORD	17-18=-186/2715, 15-17=-127/2441, 13-15=-111/2383, 12-13=-175/2620
WEBS	6-15=-66/1294, 7-15=-723/136, 7-13=0/483, 5-15=-722/136, 5-17=0/483, 3-18=-2428/187, 9-12=-2428/186

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=38ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -1-0-0 to 2-10-0, Interior(1) 2-10-0 to 19-2-0, Exterior(2R) 19-2-0 to 23-0-0, Interior(1) 23-0-0 to 39-4-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - 4) Unbalanced snow loads have been considered for this design.
  - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 7) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 18=128, 12=128.
  - 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



Job 23-7316-A	Truss T03A	Truss Type Common	Qty 4	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587370
------------------	---------------	----------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:19 2023 Page 1

ID:BxI2MwYau\_NHkbraGCMHloyOvst-6klaC?2CVdMEBbfYz9c?ibKVkXzq4KhHgbW242y8IKw



Scale: 3/16"=1'




Plate Offsets (X,Y)-- [2:0-2-8,0-1-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.77	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.89	Vert(LL) -0.29 12-14 >999 240		
BCLL 10.0	Lumber DOL 1.15	WB 0.76	Vert(CT) -0.51 12-14 >883 180		
BCDL 0.0 *	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.13 11 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 212 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.1  
WEBS 2x4 SP No.3

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 3-1-9 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
WEBS 1 Row at midpt 5-14, 7-14, 3-17, 9-11

**REACTIONS.** (size) 17=0-3-8, 11=Mechanical  
Max Horz 17=161(LC 15)  
Max Uplift 17=-128(LC 16), 11=-91(LC 16)  
Max Grav 17=1732(LC 28), 11=1673(LC 29)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-610/102, 3-5=-2835/254, 5-6=-2097/269, 6-7=-2096/271, 7-9=-2786/259, 9-10=-408/63, 2-17=-456/146, 10-11=-295/75  
BOT CHORD 16-17=-218/2689, 14-16=-159/2412, 12-14=-143/2334, 11-12=-210/2518  
WEBS 5-16=0/484, 5-14=-723/136, 6-14=-66/1273, 7-14=-688/134, 7-12=0/441, 3-17=-2406/185, 9-11=-2535/222

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=38ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -1-0-0 to 2-9-10, Interior(1) 2-9-10 to 19-2-0, Exterior(2R) 19-2-0 to 22-11-10, Interior(1) 22-11-10 to 37-10-12 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Refer to girder(s) for truss to truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 11 except (jt=lb) 17=128.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



December 18, 2023

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)



818 Soundside Road  
Edenton, NC 27932


Job 23-7316-A	Truss T03AGE	Truss Type Common Supported Gable	Qty 1	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587371
------------------	-----------------	--------------------------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:21 2023 Page 1  
ID:Bxl2MwYau\_NHkbraGCmHloyOvst-26tKdh3S1FcyQupx4aeTn0P0uLs8YNSa8v?98xy8lKu



Scale = 1:63.2




<b>LOADING (psf)</b>	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.09	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.06	Vert(LL) -0.00 1 n/r 120		
TCDL 10.0	Lumber DOL 1.15	WB 0.17	Vert(CT) -0.00 1 n/r 120		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 25 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 250 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. Except:
WEBS 2x4 SP No.3	6-0-0 oc bracing: 46-47.
OTHERS 2x4 SP No.3	WEBS 1 Row at midpt 13-36

**REACTIONS.** All bearings 38-0-8.  
 (lb) - Max Horz 47=161(LC 15)  
 Max Uplift All uplift 100 lb or less at joint(s) 47, 25, 37, 38, 39, 41, 42, 43, 44, 45, 46, 35, 34, 33, 31, 30, 29, 28, 27, 26  
 Max Grav All reactions 250 lb or less at joint(s) 47, 25, 36, 37, 38, 39, 41, 42, 43, 44, 45, 46, 35, 34, 33, 31, 30, 29, 28, 27, 26

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 12-13=-112/277, 13-14=-112/277


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=38ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) -1-0-0 to 2-9-10, Exterior(2N) 2-9-10 to 19-2-0, Corner(3R) 19-2-0 to 23-2-0, Exterior(2N) 23-2-0 to 37-10-12 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 47, 25, 37, 38, 39, 41, 42, 43, 44, 45, 46, 35, 34, 33, 31, 30, 29, 28, 27, 26.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




Job 23-7316-A	Truss T03GE	Truss Type Common Supported Gable	Qty 1	Ply 1	RVF-LOT #29 ROOF 162587372
Riverside Roof Truss, LLC, Danville, Va - 24541,					Job Reference (optional)

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:23 2023 Page 1

ID:Bxl2MwYau\_NHkbraGcmHloyOvst\_V?42N5jYssgfCyJC?hxsRULY9Xg0HyrbDUGDpy8lKs



Scale = 1:65.2



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.14	Vert(LL) -0.00	25	n/r	120	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.06	Vert(CT) -0.01	25	n/r	120		
TCDL 10.0	Lumber DOL 1.15	WB 0.17	Horz(CT) 0.00	26	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S					Weight: 252 lb	FT = 20%
BCDL 10.0	Code IRC2018/TPI2014							

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3  
OTHERS 2x4 SP No.3


**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.  
WEBS 1 Row at midpt 13-37

**REACTIONS.** All bearings 38-4-0.  
(lb) - Max Horz 48=160(LC 14)  
Max Uplift All uplift 100 lb or less at joint(s) 48, 38, 39, 40, 42, 43, 44, 45, 46, 47, 36, 35, 34, 32, 31, 30, 29, 28, 27  
Max Grav All reactions 250 lb or less at joint(s) 48, 26, 37, 38, 39, 40, 42, 43, 44, 45, 46, 47, 36, 35, 34, 32, 31, 30, 29, 28, 27

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 12-13=-106/276, 13-14=-106/276

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=38ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) -1-0-0 to 2-10-0, Exterior(2N) 2-10-0 to 19-2-0, Corner(3R) 19-2-0 to 23-2-0, Exterior(2N) 23-2-0 to 39-4-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 48, 38, 39, 40, 42, 43, 44, 45, 46, 47, 36, 35, 34, 32, 31, 30, 29, 28, 27.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



December 18, 2023

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)



818 Soundside Road  
Edenton, NC 27932



Job 23-7316-A	Truss T04	Truss Type Common	Qty 9	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587373
------------------	--------------	----------------------	----------	----------	--	-----------


Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:26 2023 Page 1

ID:Bxl2MwYau\_NHkbraGcmHloyOvst-P4gDgO7brnEFWfhut7EeU46jnMLwDWDJHBIwp8y8lKp



Scale = 1:66.1



LOADING (psf)		SPACING-	2-0-0	CSI.	DEFLL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	Vert(LL)	-0.75	16	>602	MT20	244/190
Snow (Pf/Pg)	11.6/15.0	Lumber DOL	1.15	BC	Vert(CT)	-1.28	16	>354	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	Horz(CT)	0.08	11	n/a		
BCLL	0.0 *	Code IRC2018/TPI2014		Matrix-MS						
BCDL	10.0								Weight: 235 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP DSS *Except* 15-17: 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. Except: 6-0-0 oc bracing: 15-17
WEBS 2x4 SP No.3 *Except* 2-20: 2x6 SP No.2, 2-19,10-12: 2x4 SP No.2	

**REACTIONS.** (size) 20=0-3-8, 11=Mechanical  
 Max Horz 20=162(LC 15)  
 Max Uplift 20=69(LC 16), 11=-29(LC 16)  
 Max Grav 20=1939(LC 28), 11=1876(LC 29)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-3302/117, 3-5=-3121/108, 5-6=-3120/193, 6-7=-3101/190, 7-9=-3104/112,  
 9-10=-3228/126, 2-20=-1799/166, 10-11=-1741/112  
 BOT CHORD 19-20=-102/585, 18-19=-84/3077, 14-18=0/2170, 13-14=0/2170, 12-13=-81/2931,  
 11-12=-37/292  
 WEBS 3-18=-305/107, 5-18=-396/162, 17-18=-85/1184, 6-17=-28/1324, 6-15=-27/1292,  
 13-15=-83/1151, 7-13=-390/160, 9-13=-276/112, 2-19=-4/2537, 10-12=-45/2663

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=38ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -1-0-0 to 2-9-10, Interior(1) 2-9-10 to 19-2-0, Exterior(2R) 19-2-0 to 22-11-10, Interior(1) 22-11-10 to 37-10-12 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - 4) Unbalanced snow loads have been considered for this design.
  - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 11.6 psf on overhangs non-concurrent with other live loads.
  - 6) All plates are MT20 plates unless otherwise indicated.
  - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 8) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 9) Refer to girder(s) for truss to truss connections.
  - 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 20, 11.
  - 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.






Job 23-7316-A	Truss V01	Truss Type Valley	Qty 1	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587374
------------------	--------------	----------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:27 2023 Page 1  
ID:BxI2MwYau\_NHkbraGCmHloyOvst-tGEbt8Dc5M68pG4Rrt1Hf0bmtpy5ISWrSUMay8lKo



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.20	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.17	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.15	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 7 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 97 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	

**REACTIONS.** All bearings 23-0-10.  
 (lb) - Max Horz 1=128(LC 14)  
 Max Uplift All uplift 100 lb or less at joint(s) 11, 13, 9, 8  
 Max Grav All reactions 250 lb or less at joint(s) 1, 7 except 10=379(LC 27), 11=431(LC 27), 13=363(LC 27), 9=431(LC 28), 8=363(LC 28)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 WEBS 3-11=263/125, 5-9=263/125

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-6-8 to 3-6-12, Interior(1) 3-6-12 to 11-6-12, Exterior(2R) 11-6-12 to 14-6-12, Interior(1) 14-6-12 to 22-7-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - 4) Unbalanced snow loads have been considered for this design.
  - 5) All plates are 2x4 MT20 unless otherwise indicated.
  - 6) Gable requires continuous bottom chord bearing.
  - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 8) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 11, 13, 9, 8.
  - 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




Job 23-7316-A	Truss V02	Truss Type Valley	Qty 1	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587375
------------------	--------------	----------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:29 2023 Page 1

ID:Bxl2MwYau\_NHkbraGcmHloyOvst-pfMMIQ9T8icpO7QTYGnL6ikM2ZZQQ0Mlz9xaQTY8lKkm



Scale = 1:38.9

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.20	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.17	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.11	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 7 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 82 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	

**REACTIONS.** All bearings 20-2-6.  
 (lb) - Max Horz 1=112(LC 15)  
 Max Uplift All uplift 100 lb or less at joint(s) 1, 7, 12, 13, 9, 8  
 Max Grav All reactions 250 lb or less at joint(s) 1, 7 except 10=370(LC 27), 12=428(LC 27), 13=307(LC 27), 9=428(LC 28), 8=307(LC 28)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 WEBS 3-12=268/127, 5-9=268/127

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-6-8 to 3-6-8, Interior(1) 3-6-8 to 10-1-10, Exterior(2R) 10-1-10 to 13-1-10, Interior(1) 13-1-10 to 19-8-11 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - 4) Unbalanced snow loads have been considered for this design.
  - 5) All plates are 2x4 MT20 unless otherwise indicated.
  - 6) Gable requires continuous bottom chord bearing.
  - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 8) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7, 12, 13, 9, 8.
  - 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




Job 23-7316-A	Truss V03	Truss Type Valley	Qty 1	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587376
------------------	--------------	----------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:30 2023 Page 1

ID:BxI2MwYau\_NHkbraGCmHloyOvst-HrwkWmA6v0kg?H?f6zJafwHX4zu09T6vCpg8yvy8IKI



Scale = 1:35.3


<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.25	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.14	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.08	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 5 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 67 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	

**REACTIONS.** All bearings 17-4-1.  
 (lb) - Max Horz 1=95(LC 14)  
 Max Uplift All uplift 100 lb or less at joint(s) 9, 6  
 Max Grav All reactions 250 lb or less at joint(s) 1, 5, 7 except 9=391(LC 33), 6=391(LC 34)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
**WEBS** 2-9=-291/134, 4-6=-291/134

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-6-8 to 3-6-8, Interior(1) 3-6-8 to 8-8-7, Exterior(2R) 8-8-7 to 11-8-7, Interior(1) 11-8-7 to 16-10-7 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9, 6.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




December 18, 2023

Job 23-7316-A	Truss V04	Truss Type Valley	Qty 1	Ply 1	RVF-LOT #29 ROOF	162587377
------------------	--------------	----------------------	----------	----------	------------------	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:31 2023 Page 1  
ID:Bxl2MwYau\_NHkbraGCmHloyOvst-l2U6j6BkgJsXdRzSghqpB7qibNFuxc2RTQhVMY8lKk



Scale = 1:27.9

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.20	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.12	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.06	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 5 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 54 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	

**REACTIONS.** All bearings 14-5-13.  
(lb) - Max Horz 1=78(LC 14)  
Max Uplift All uplift 100 lb or less at joint(s) 8, 6  
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=272(LC 2), 8=321(LC 33), 6=321(LC 34)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-6-8 to 3-3-5, Interior(1) 3-3-5 to 7-3-5, Exterior(2R) 7-3-5 to 10-3-5, Interior(1) 10-3-5 to 14-0-2 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - 4) Unbalanced snow loads have been considered for this design.
  - 5) Gable requires continuous bottom chord bearing.
  - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 7) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8, 6.
  - 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



December 18, 2023

Job 23-7316-A	Truss V05	Truss Type Valley	Qty 1	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587378
------------------	--------------	----------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC, Danville, Va - 24541,



8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:32 2023 Page 1

ID:Bxl2MwYau\_NHkbraGcmHloyOvst-DE1UxRCMRd\_OFa82EOL2kLMqWnYKdNhBf79E1oy8IKj



4x5 =

Scale = 1:22.9



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.45	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.28	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.07	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 40 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	

**REACTIONS.** (size) 1=11-7-8, 3=11-7-8, 4=11-7-8  
 Max Horz 1=-62(LC 14)  
 Max Uplift 1=-26(LC 16), 3=-26(LC 16)  
 Max Grav 1=201(LC 2), 3=201(LC 2), 4=447(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
**WEBS** 2-4=-291/106

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-6-8 to 3-6-8, Interior(1) 3-6-8 to 5-10-3, Exterior(2R) 5-10-3 to 8-10-3, Interior(1) 8-10-3 to 11-1-14 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



December 18, 2023



Job 23-7316-A	Truss V06	Truss Type Valley	Qty 1	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587379
------------------	--------------	----------------------	----------	----------	--	-----------


Riverside Roof Truss, LLC, Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:33 2023 Page 1

ID:Bxl2MwYau\_NHkbraGcmHloyOvst-hQbs8nC\_Cx7FskjEn5sHGyV1KBwMrQLunvoZEy8lKI



Scale = 1:18.1



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.31	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.15	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.04	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 29 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	

**REACTIONS.** (size) 1=8-9-3, 3=8-9-3, 4=8-9-3  
 Max Horz 1=45(LC 15)  
 Max Uplift 1=26(LC 16), 3=26(LC 16)  
 Max Grav 1=162(LC 2), 3=162(LC 2), 4=296(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-6-8 to 3-6-8, Interior(1) 3-6-8 to 4-5-1, Exterior(2R) 4-5-1 to 7-5-1, Interior(1) 7-5-1 to 8-3-9 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - 4) Unbalanced snow loads have been considered for this design.
  - 5) Gable requires continuous bottom chord bearing.
  - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 7) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



December 18, 2023




Job 23-7316-A	Truss V07	Truss Type Valley	Qty 1	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587380
------------------	--------------	----------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC,

Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:34 2023 Page 1

ID:Bxl2MwYau\_NHkbraGcmHloyOvst-Ac9FL7DczEF6UuQLpNWpmSFHalD5ixU7Rel5gy8lKh



Scale = 1:13.2

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 20.0	2-0-0	TC 0.11	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 11.6/15.0	Plate Grip DOL 1.15	BC 0.06	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.03	Lum(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014			Weight: 19 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 OTHERS 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 5-11-13 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 1=5-10-15, 3=5-10-15, 4=5-10-15  
 Max Horz 1=-29(LC 14)  
 Max Uplift 1=-17(LC 16), 3=-17(LC 16)  
 Max Grav 1=102(LC 2), 3=102(LC 2), 4=187(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-**

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



December 18, 2023

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPH Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)



818 Soundside Road  
 Edenton, NC 27932


Job 23-7316-A	Truss V08	Truss Type Valley	Qty 1	Ply 1	RVF-LOT #29 ROOF Job Reference (optional)	162587381
------------------	--------------	----------------------	----------	----------	--	-----------

Riverside Roof Truss, LLC,

Danville, Va - 24541,

8.530 s Aug 2 2023 MiTek Industries, Inc. Fri Dec 15 10:20:35 2023 Page 1

ID:Bxl2MwYau\_NHkbraGCmHloyOvst-epjdZTEEKYNz62tdvWulMz\_QP\_efqkaeM5Ove7y8lKg



Scale = 1:7.3


Plate Offsets (X,Y)-- [2:0-2-0,Edge]		3-1-1		3-1-1		3-1-8		0-0-7				
<b>LOADING</b> (psf)		<b>SPACING-</b>	2-0-0	<b>CSI.</b>		<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.02	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	11.6/15.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCLL	0.0 *	Code IRC2018/TPI2014		Matrix-P							Weight: 8 lb	FT = 20%
BCDL	10.0											

<b>LUMBER-</b>		<b>BRACING-</b>	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 3-1-8 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 1=3-0-10, 3=3-0-10  
 Max Horz 1=12(LC 14)  
 Max Uplift 1=5(LC 16), 3=5(LC 16)  
 Max Grav 1=82(LC 2), 3=82(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=15.0 psf; Pf=11.6 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




December 18, 2023

# Symbols

## PLATE LOCATION AND ORIENTATION



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



For 4 x 2 orientation, locate plates 0- 1/16\" from outside edge of truss.



This symbol indicates the required direction of slots in connector plates.

\* Plate location details available in MITek software or upon request.

## PLATE SIZE

4 X 4

The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

## LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

## BEARING



Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.


## Industry Standards:

ANSI/TP1: National Design Specification for Metal Plate Connected Wood Truss Construction.  
DSB-22: Design Standard for Bracing.  
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

# Numbering System



1 TOP CHORDS  
2 Joint ID typ.



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

# Product Code Approvals

ICC-ES Reports:

ESR-1988, ESR-2362, ESR-2685, ESR-3282  
ESR-4722, ESL-1388

# Design General Notes

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 section 6.3. These truss designs rely on Lumber values established by others.

© 2023 MITek® All Rights Reserved

**MITek**

ENGINEERING BY  
**TRENGO**  
A MITek Affiliate

MITek Engineering Reference Sheet: MIL-7473 rev. 1/2/2023

# General Safety Notes

## Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability/bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.