	Pa	ige 1 of
PROPERTY ID #:	SFD	2401-0094
COUNTY:	Har	457

OCA	FACILITY FION OF SITE: R SUPPLY:		gle Family Well	OPOSED DESIGN I		4 <u>8</u> 0	PROPE	ERTY SIZ ERTY REC R SUPPLY		
	JATION METH		er Boring Pit		PE OF WASTE	WATER:	Domest	id High	Strength	IPWW
P R O F			SOIL MORPHOLOGY		ОТНЕ	E FACTO	ORS			
I L E	.0502 LANDSCAPE POSITION/ SLOPE %	HORIZON DEPTH (IN.)	.0503 STRUCTURE/ TEXTURE	.0503 CONSISTENCE/ MINERALOGY	.0504 SOIL WETNESS/ COLOR	.0505 SOIL DEPTH	.0506 SAPRO CLASS	.0507 RESTR HORIZ	.0509 PROFILE CLASS & LTAR*	.0503 SLOPE CORRE CTION
	2-3%	0-16	56,00	Fr, NS, NP, ST						
1		16-38	SCL 98K	Fr, SS, NP, SE	7.3/15/8 7/2=381	48"			,35	
1		38-40	CL/ WSEK	Fr, SS, ND, SE	7/2=32"	, -				
2				3701 1882 17						
	1-2% LS	0-21	SL, g(Fr, NS, NP, SE						
~	LS	21-48	SCLISER	Fr, SS, NP, SE		48"			.33	
1/4			,	/ / //						
3										
3										
4										
4										

DESCRIPTION	INITIAL SYSTEM	REPAIR SYSTEM	
Available Space (.0508)	/		SITE CLASSIFICATION (.0509): 5
System Type(s)	25%. Rea	50%. Rea	EVALUATED BY: RL/JM
Site LTAR	. 33	.35	OTHER(S) PRESENT:
Maximum Trench Depth	1811-24	18 -2411	
Comments:			

LEGEND

LANDSCAPE POSITION	SOIL GROUP	SOIL TEXTURE	CONVENTIONAL LTAR (gpd/ft²)	SAPROLITE LTAR (gpd/ft²)	LPP LTAR (gpd/ft²)	MINERALOGY/ CONSISTENCE		STRUCTURE
CC (Concave slope)		S (Sand)		0.6 - 0.8		MOIST	WET	SG (Single grain)
CV (Convex Slope)	1	LS (Loamy sand)	0.8 - 1.2	0.5 -0.7	0.4 -0.6	Lo (Loose)	NS (Non-sticky)	M (Massive)
D (Drainage way)	_ 11	SL (Sandy loam)	0.6 - 0.8	0.4 -0.6	0.3 - 0.4	VFR (Very friable)	SS (Slightly sticky)	GR (Granular)
FP (Flood plain)		L (Loam)	0.0	0.2 - 0.4		FR (Friable)	S (Sticky)	SBK (Subangular blocky)
FS (Foot slope)	III	SiL (Silt loam)		0.1 - 0.3		FI (Firm)	VS (Very sticky)	ABK (Angular blocky)
H (Head slope)		SCL (Sandy clay loam)		0.05 - 0.15**		VFI (Very firm)	NP (Non-plastic)	PR (Prismatic)
L (Linear Slope)		CL (Clay loam)	0.3 - 0.6		0.15 - 0.3	EFI (Extremely firm)	SP (Slightly plastic)	PL (Platy)
N (Nose slope)		SiCL (Silty clay loam)					P (Plastic)	
R (Ridge/summit)		Si (Silt)		None			VP (Very plastic)	2
S (Shoulder slope)	IV	SC (Sandy clay)				SEXP (Slightly expansive)		
T (Terrace)		SiC (Silty clay)	0.1 - 0.4		0.05 - 0.2	EXP (Expansive)		
TS (Toe Slope)		C (Clay)						
		O (Organic)	None					

HORIZON DEPTH DEPTH OF FILL

In inches from land surface

RESTRICTIVE HORIZON

SAPROLITE SOIL WETNESS CLASSIFICATION Thickness and depth from land surface

S(suitable) or U(unsuitable); Evaluation of saprolite shall be by pits.

Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation S (Suitable) or U (Unsuitable)

Show profile locations and other site features (dimensions, reference or benchmark, and North).

^{*} Adjust LTAR due to depth, consistence, structure, soil wetness, landscape, position, wastewater flow and quality.

**Sandy clay loam saprolite can only be used with advanced pretreatment in accordance with 15A NCAC 18E .1200. In inches below natural soil surface

