

HUS26	USP	8	NA	16d/3-1/2"	16d/3-1/2"
THD26-2	USP	1	NA	16d/3-1/2"	10d/3"

	Estir	mation	
Name	Selection	Formula	Calculation
Roof Area	1st Floor	Roof Area	3279.18
Roof Decking	1st Floor	Roof Decking	113

		BEAM LEGEND			
PlotID	Length	Product	Plies	Net Qty	Fab Type
GDH 9' FL (dropped)	13' 0"	1-3/4"x 11-7/8" LVL Kerto-S	2	2	FF
GDH 18' FL (dropped)	23' 0"	1-3/4"x 14" LVL Kerto-S	2	2	FF
PB1	18' 0"	2x10 SP No.2	2	2	FF
PB3	16' 0"	2x10 SP No.2	2	2	FF
PB2	6' 0"	2x10 SP No.2	2	2	FF

Truss Placement Plan SCALE: 1/4" = 1'0"

▲= Denotes Left End of Truss (Reference Engineered Truss Drawing)

All Truss Reactions are Less than 3,000 lbs. Unless Noted Otherwise.

-- Denotes Reaction Greater than 3,000 lbs.

Reaction / # of Studs



Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787 Fax: (910) 864-4444

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables ( derived from the prescriptive Code requirements ) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#

Lenny Norris

LOAD CHART FOR JACK STUDS
(BASED ON TABLES R502.5(1) & (b))

NON	NDLK C	HEADER/		A LIND	Oi
END REACTION (UP TO)	REQ'D STUDS FOR (2) PLY HEADER	END REACTION (UP TO)	REQ'D STUDS FOR (3) PLY HEADER	END REACTION	5
1700	1	2550	1	340	0
3400	2	5100	2	680	0
5100	3	7650	3	1020	00
6800	4	10200	4	1360	00
8500	5	12750	5	1700	00
10200	6	15300	6		
11900	7				
13600	8				
15300	9				

KLNN000	Harnett
ADDRESS	185 Hillwood Dr.
WODEL	ROOF
DATE REV.	02/08/24
DRAWN BY	DRAWN BY Lenny Norris
SALESMAN	SALESMAN Lenny Norris

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY.
These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com

Sinclair (190320B) 3Car

Quote#

Weaver Homes, Inc.