

RE: 3854181 - DREAMFINDERS HOMES, Embark (D_1), D, Lot 15, WATSON RIDGE

818 Soundside Rd
 Edenton, NC 27932

Site Information:

Project Customer: DREAMFINDERS HOMES Project Name:
 Lot/Block: 15 Subdivision: WATSON RIDGE
 Address: 165 ROCKING HORSE LANE
 City: Sanford State: NC

Name Address and License # of Structural Engineer of Record, If there is one, for the building.

Name: License #:
 Address:
 City, County: State:

General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):

Design Code: IRC2015/TPI2014 Design Program: MiTek 20/20 8.5
 Wind Code: ASCE 7-10 Design Method: MWFRS (Envelope)/C-C hybrid Wind ASCE 7-10
 Wind Speed: 150 mph
 Roof Load: 40.0 psf Floor Load: N/A psf


This package includes 1 individual, dated Truss Design Drawings and 0 Additional Drawings.

No.	Seal#	Job ID#	Truss Name	Date
1	165787584	3854181	A08	5/24/24

The truss drawing(s) referenced above have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Builders FirstSource-Sumter,SC.

Truss Design Engineer's Name: Gagan, Iqbal

My license renewal date for the state of North Carolina is December 31, 2024.



IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

May 24, 2024

Gagan, Iqbal

Job 3854181	Truss A08	Truss Type COMMON	Qty 6	Ply 1	DREAMFINDERS HOMES, Embark (D_1), D, Lot 15, WATSON RIDGE 165787584
----------------	--------------	----------------------	----------	----------	--


Builders FirstSource (Sumter, SC), Sumter, SC - 29153,

8.630 s Apr 26 2024 MiTek Industries, Inc. Thu May 23 09:51:00 2024 Page 1

ID:ght9E4_T2Ek4TgdRpkw?ez6kuZ-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKwrcDoi7J4zJC?f
 28-4-8 37-11-0 38-9-8
 0-10-8 9-6-8 18-11-8 9-5-0 9-5-0 9-6-8 0-10-8

REPAIR:
TRUSS INSTALLED BACKWARD
PLATE DAMAGE AT JOINT 12

Scale = 1:74.9



ATTACH 1/2" PLYWOOD OR OSB GUSSET (15/32" RATED SHEATHING 32/16 EXP 1)
 TO EACH FACE OF TRUSS WITH (0.131" X 2.5" MIN.) NAILS PER THE FOLLOWING NAIL SCHEDULE:
 2 X 4'S - 3 ROWS, 2 X 6'S AND LARGER - 4 ROWS: SPACED @ 4" O.C. NAILS TO BE DRIVEN FROM
 BOTH FACES. STAGGER SPACING FROM FRONT TO BACK FACE FOR A NET 2" O.C. SPACING IN
 EACH COVERED TRUSS MEMBER. USE 2" MEMBER END DISTANCE.

	12-8-3	18-11-8	25-2-13	37-11-0
	12-8-3	6-3-5	6-3-5	12-8-3
Plate Offsets (X, Y)--	[3:0-5-0,0-4-8], [5:0-5-0,0-4-8], [8:0-5-0,0-5-4]			

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.62	Vert(LL)	-0.38	9-10	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.90	Vert(CT)	-0.70	9-10	>653		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.65	Horz(CT)	0.08	6	n/a		
BCDL 10.0	Code IRC2015/TP12014		Matrix-AS	Wind(LL)	0.19	12-19	>999		
								Weight: 260 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.2	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3 *Except* 13-14: 2x4 SP No.2	WEBS 1 Row at midpt 4-8, 4-12, 13-14

REACTIONS. (size) 2=0-3-8, 6=0-3-8
 Max Horz 2=-295(LC 13)
 Max Uplift 2=-616(LC 12), 6=-616(LC 13)
 Max Grav 2=1658(LC 1), 6=1658(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2960/1579, 3-4=-2727/1531, 4-5=-2727/1531, 5-6=-2960/1579
 BOT CHORD 2-12=-1194/2595, 10-12=-565/1866, 9-10=-565/1866, 8-9=-565/1866, 6-8=-1196/2595
 WEBS 4-14=-463/1175, 8-14=-451/1062, 5-8=-572/763, 12-13=-451/1061, 4-13=-464/1175,
 3-12=-572/763

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=150mph Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 200.0lb AC unit load placed on the bottom chord, 18-11-8 from left end, supported at two points, 5-0-0 apart.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 616 lb uplift at joint 2 and 616 lb uplift at joint 6.
 - Load case(s) 2, 3, 19, 20, 21, 22, 25, 26 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard
 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-4=-60, 4-7=-60, 17-20=-20
 Concentrated Loads (lb)
 Vert: 10=-100 9=-100



May 24, 2024

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.
 Design valid for use only with MiTek@ connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932


Job 3854181	Truss A08	Truss Type COMMON	Qty 6	Ply 1	DREAMFINDERS HOMES, Embark (D_1), D, Lot 15, WATSON RIDGE 165787584 Job Reference (optional)
----------------	--------------	----------------------	----------	----------	--

Builders FirstSource (Sumter, SC), Sumter, SC - 29153,

8.630 s Apr 26 2024 MiTek Industries, Inc. Thu May 23 09:51:00 2024 Page 2
ID:ghlt9E4_T2Ek4TgdRpkw?ez6kuZ-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWRCDoi7J4zJC?f

LOAD CASE(S) Standard

- 2) Dead + 0.75 Roof Live (balanced) + 0.75 Uninhab. Attic Storage: Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-4=-50, 4-7=-50, 17-23=-20, 23-24=-50, 24-25=-20, 25-26=-50, 20-26=-20, 27-28=-30
Concentrated Loads (lb)
Vert: 10=-100 9=-100
- 3) Dead + Uninhabitable Attic Without Storage: Lumber Increase=1.25, Plate Increase=1.25
Uniform Loads (plf)
Vert: 1-4=-20, 4-7=-20, 17-20=-40, 27-28=-40
Concentrated Loads (lb)
Vert: 10=-100 9=-100
- 19) Dead + 0.75 Roof Live (bal.) + 0.75 Uninhab. Attic Storage + 0.75(0.6 MWFRS Wind (Neg. Int) Left): Lumber Increase=1.60, Plate Increase=1.60
Uniform Loads (plf)
Vert: 1-2=-42, 2-4=-50, 4-6=-33, 6-7=-26, 17-23=-20, 23-24=-50, 24-25=-20, 25-26=-50, 20-26=-20, 27-28=-30
Horz: 1-2=-8, 2-4=0, 4-6=17, 6-7=24
Concentrated Loads (lb)
Vert: 10=-100 9=-100
- 20) Dead + 0.75 Roof Live (bal.) + 0.75 Uninhab. Attic Storage + 0.75(0.6 MWFRS Wind (Neg. Int) Right): Lumber Increase=1.60, Plate Increase=1.60
Uniform Loads (plf)
Vert: 1-2=-26, 2-4=-33, 4-6=-50, 6-7=-42, 17-23=-20, 23-24=-50, 24-25=-20, 25-26=-50, 20-26=-20, 27-28=-30
Horz: 1-2=-24, 2-4=-17, 4-6=0, 6-7=8
Concentrated Loads (lb)
Vert: 10=-100 9=-100
- 21) Dead + 0.75 Roof Live (bal.) + 0.75 Uninhab. Attic Storage + 0.75(0.6 MWFRS Wind (Neg. Int) 1st Parallel): Lumber Increase=1.60, Plate Increase=1.60
Uniform Loads (plf)
Vert: 1-2=-5, 2-4=-13, 4-6=-35, 6-7=-28, 17-23=-20, 23-24=-50, 24-25=-20, 25-26=-50, 20-26=-20, 27-28=-30
Horz: 1-2=-45, 2-4=-37, 4-6=15, 6-7=22
Concentrated Loads (lb)
Vert: 10=-100 9=-100
- 22) Dead + 0.75 Roof Live (bal.) + 0.75 Uninhab. Attic Storage + 0.75(0.6 MWFRS Wind (Neg. Int) 2nd Parallel): Lumber Increase=1.60, Plate Increase=1.60
Uniform Loads (plf)
Vert: 1-2=-28, 2-4=-35, 4-6=-13, 6-7=-5, 17-23=-20, 23-24=-50, 24-25=-20, 25-26=-50, 20-26=-20, 27-28=-30
Horz: 1-2=-22, 2-4=-15, 4-6=37, 6-7=45
Concentrated Loads (lb)
Vert: 10=-100 9=-100
- 25) 3rd Dead + 0.75 Roof Live (unbalanced) + 0.75 Uninhab. Attic Storage: Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-4=-50, 4-7=-20, 17-23=-20, 23-24=-50, 24-25=-20, 25-26=-50, 20-26=-20, 27-28=-30
Concentrated Loads (lb)
Vert: 10=-100 9=-100
- 26) 4th Dead + 0.75 Roof Live (unbalanced) + 0.75 Uninhab. Attic Storage: Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-4=-20, 4-7=-50, 17-23=-20, 23-24=-50, 24-25=-20, 25-26=-50, 20-26=-20, 27-28=-30
Concentrated Loads (lb)
Vert: 10=-100 9=-100



May 24, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPH Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)




818 Soundside Road
Edenton, NC 27932

Symbols


PLATE LOCATION AND ORIENTATION



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



For 4 x 2 orientation, locate plates 0- 1/16\" from outside edge of truss.



This symbol indicates the required direction of slots in connector plates.

* Plate location details available in MITek software or upon request.

PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING



Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.


Industry Standards:

ANSI/TP1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-22: Design Standard for Bracing.
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

Numbering System



1 TOP CHORDS
2 Joint ID
3 typ.



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

Product Code Approvals

ICC-ES Reports:

ESR-1988, ESR-2362, ESR-2685, ESR-3282
ESR-4722, ESL-1388

Design General Notes

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 section 6.3. These truss designs rely on Lumber values established by others.

© 2023 MITek® All Rights Reserved

General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability/bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.

MITek

ENGINEERING BY
TRENGO
A MITek Affiliate

MITek Engineering Reference Sheet: MIL-7473 rev. 1/2/2023