
THIS IS A TRUSS/COMPONENT PLACEMENT DIAGRAM (TPD) ONLY; NOT AN ENGINEERED DOCUMENT. Trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual truss design drawings (TDD's) for each truss design identified on the TPD. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the support structure including but not limited to headers, beams, walls, and columns is also the responsibility of the building designer. For general guidance regarding installation and bracing, consult "Building Component Safety Information" (BCSI) available from the SBC Association (www.sbcacomponents.com). It is the responsibility of the General Contractor to very five the provided component along the provided plans containing the latest specifications and design of the roof and floor system and for the overall structure. The design of the support structure including but not limited to headers, beams, walls, and columns is also the responsibility of the headers, beams, walls, and columns is also the responsibility of the BCSI) available from the SBC Association (www.sbcacomponents.com). It is the responsibility of the peneral Contractor to very five the provided component along the five the responsibility of the peneral Contractor to notify UPP and provide plans containing the latest specifications and design at the support structure. The design of the support structure including designer is responsible to the responsibility of the peneral Contractor to wall the support structure. The design of the support structure including designer is responsible to the support structure. The design of the support structure including designer is responsible to the peneral contractor to wall the support structure. The design of the support structure. The design of the support structure including design at the support structure. The design of the support structure. including adjusting member spacing within tolerances to allow for the drop and rise of plumbing/HVAC, unless noted otherwise. Truss-to-wall connections, if shown, are for uplift only and do not consider lateral loads. All connectors on this project are to be installed per the connector manufacturer's specifications. All connectors shown that are not truss-to-truss are suggestions only and are to be verified by the Building Designer or Engineer of Record for suitability to this particular project. UFP accepts no responsibility for the specific application or suitability of any connector that is not truss-to-truss as they apply to this specific structure.



ROOF AREA: 3776.77\_RIDGE LINE: 117.22 \_ VALLEY LINES: 137.08 \_ HIP LINES:0

 $\triangle$  Indicates Left End of Truss

	DESIGNER LAYOUT DATE ARCH DATE STRUC DATE	REVISIONS		
ЮВ		DATE	DESCRIPTION	DSN
₽ #		-	-	-
		-	-	-
246		-		-
5	AM 2-5-24	-		-
4012358		-		-
"		-	-	-
		-	-	-
		-		

**RALEIGH FARMHOUSE ROOF** 

**DUNCAN'S CREEK RD. LILLINGTON, NC 27546**  **PBS** 

**LOT 144 DUNCAN'S CREEK** 

This drawing is property of UFP Site Built, LLC. Any unauthorized use of this document without written permission is prohibited. UFP relinquishes ownership of delivered product upon delivery. Owner of product must obtain UFP's authorization prior to any alteration or modification of product; UFP will not be held responsible for any unauthorized modifications done or costs incurred without prior written authorization from UFP.



**UFP** SITE BUILT

Burlington, NC Locust, NC Chesapeake, VA Liberty, NC Clinton, NC Ooltewah, TN Conway, SC Pearisburg, VA
Jefferson, GA Stanfield, NC

