

Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 45874

JOB: 24-1218-F02

JOB NAME: LOT 0.0043 HONEYCUTT HILLS

Wind Code: N/A

Wind Speed: Vult= N/A

Exposure Category: N/A

Mean Roof Height (feet): N/A

These truss designs comply with IRC 2015 as well as IRC 2018.

33 Truss Design(s)

Trusses:

F201, F202, F203, F204, F205, F206, F207, F208, F209, F210, F211, F212, F213, F214, F215, F216, F217, F218, F219, F220, F221, F222, F223, F224, F225, F226, F227, F228, F229, F230, F231, F232, F233



2/26/2024

Mark Morris

Warning !—Verify design parameters and read notes before use.

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for*

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F201	Floor Supported Gable	1	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:06 2024 Page 1
 ID:XfGBR?_CJqttCk9NOQCWjycQDJ-K4NbLjWV17PM32g4xy5WzD1hMpVF2KgGb30W1_zgth

0-1-8

Scale = 1:25.4




Plate Offsets (X,Y)-- [6:0-1-8,Edge], [20:0-1-8,Edge], [26:Edge,0-1-8]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.06	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 14 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH		Weight: 68 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)
 OTHERS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 15-5-14.
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 26, 14, 25, 24, 23, 22, 21, 20, 19, 18, 17, 16, 15

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (6-9)
- Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard





2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job 24-1218-F02	Truss F202	Truss Type Floor	Qty 2	Ply 1	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC	# 45874
--------------------	---------------	---------------------	----------	----------	--	---------

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:07 2024 Page 1
ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-oGxzY3X83RXChBFGVgdIWQajyDgonegQqjm3ZRzgtg



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.58	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.75	Vert(LL) -0.23 12-13 >786 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.62	Vert(CT) -0.32 12-13 >578 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.04 9 n/a n/a		
	Code IRC2021/TPI2014			Weight: 78 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP SS(flat)
WEBS 2x4 SP No.3(flat)


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 17=832/0-3-6 (min. 0-1-8), 9=838/Mechanical

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 17-18=-833/0, 1-18=-832/0, 8-9=-831/0, 1-2=-887/0, 2-3=-2249/0, 3-4=-2919/0, 4-5=-2976/0, 5-6=-2409/0, 6-7=-2409/0, 7-8=-1099/0
BOT CHORD 15-16=0/1717, 14-15=0/2919, 13-14=0/2919, 12-13=0/2919, 11-12=0/2880, 10-11=0/1926
WEBS 3-14=-6/312, 4-13=-279/38, 3-15=-923/0, 2-15=0/692, 2-16=-1080/0, 1-16=0/1110, 4-12=-281/279, 5-12=0/285, 5-11=-601/0, 7-11=0/617, 7-10=-1077/0, 8-10=0/1310

- NOTES-** (5-8)
- Unbalanced floor live loads have been considered for this design.
 - Refer to girder(s) for truss connections.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION. Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard





2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F203	Floor	1	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:08 2024 Page 1
 ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-GSUMmPXmqfJ3JLqS3N8_2e7yAd13W8qZ3NVc5tzgff



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.36	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.69	Vert(LL) -0.12 13-14 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.44	Vert(CT) -0.16 13-14 >989 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.03 11 n/a n/a		
	Code IRC2021/TPI2014			Weight: 80 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 11-12,10-11.

REACTIONS. (lb/size) 18=691/0-3-6 (min. 0-1-8), 11=972/0-3-8 (min. 0-1-8)
 Max Grav 18=705(LC 3), 11=972(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 18-19=-703/0, 1-19=-701/0, 1-2=-736/0, 2-3=-1791/0, 3-4=-2175/0, 4-5=-1952/0, 5-6=-1089/0
 BOT CHORD 16-17=0/1430, 15-16=0/2175, 14-15=0/2175, 13-14=0/2175, 12-13=0/1686, 11-12=-89/469
 WEBS 7-11=-285/0, 3-16=-588/0, 2-16=0/477, 2-17=-904/0, 1-17=0/919, 4-13=-493/0, 5-13=0/418, 5-12=-801/0, 6-12=0/830,
 6-11=-875/0

- NOTES-** (4-7)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 3) CAUTION. Do not erect truss backwards.
 - 4) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - 5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - 6) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - 7) SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F204	Floor	1	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:10 2024 Page 1
 ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-Drc6B4Z0MMvnYf_rAoAS73CleQiv_2PsWh_jAlzgttd




Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [8:0-1-8,Edge], [18:Edge,0-1-8]	
LOADING (psf)	SPACING- 2-0-0
TCLL 40.0	Plate Grip DOL 1.00
TCDL 10.0	Lumber DOL 1.00
BCLL 0.0	Rep Stress Incr YES
BCDL 5.0	Code IRC2021/TPI2014
	CSI.
	TC 0.36
	BC 0.69
	WB 0.43
	Matrix-SH
	DEFL. in (loc) l/defl L/d
	Vert(LL) -0.12 13-14 >999 480
	Vert(CT) -0.16 13-14 >987 360
	Horz(CT) 0.03 11 n/a n/a
	PLATES MT20
	GRIP 244/190
	Weight: 80 lb FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 11-12,10-11.

REACTIONS. (lb/size) 18=689/0-3-0 (min. 0-1-8), 11=970/0-3-8 (min. 0-1-8)
 Max Grav 18=703(LC 3), 11=970(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 18-19=-701/0, 1-19=-700/0, 1-2=-718/0, 2-3=-1776/0, 3-4=-2164/0, 4-5=-1944/0, 5-6=-1085/0
 BOT CHORD 16-17=0/1412, 15-16=0/2164, 14-15=0/2164, 13-14=0/2164, 12-13=0/1681, 11-12=-89/468
 WEBS 7-11=-285/0, 3-16=-591/0, 2-16=0/478, 2-17=-903/0, 1-17=0/906, 4-13=-489/0, 5-13=0/416, 5-12=-798/0, 6-12=0/827, 6-11=-873/0

- NOTES-** (4-7)
- Unbalanced floor live loads have been considered for this design.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION. Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard





2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F205	Floor	1	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:11 2024 Page 1
 ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-h1AUOQae7g1eApZ1kVhghGISWq3JjUL0ILkHiCzgtfc



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.42	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.59	Vert(LL) -0.09 20-21 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.45	Vert(CT) -0.12 20-21 >999 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.02 16 n/a n/a		
	Code IRC2021/TPI2014			Weight: 98 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 23=606/0-3-0 (min. 0-1-8), 12=132/0-3-8 (min. 0-1-8), 16=1371/0-3-8 (min. 0-1-8)
 Max Uplift 12=-104(LC 3)
 Max Grav 23=612(LC 3), 12=273(LC 4), 16=1371(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 23-24=-607/0, 1-24=-606/0, 1-2=-612/0, 2-3=-1447/0, 3-4=-1632/0, 4-5=-1209/0, 7-8=0/1306, 8-9=0/830, 9-10=-300/317
 BOT CHORD 21-22=0/1209, 20-21=0/1632, 19-20=0/1632, 18-19=0/1632, 17-18=0/819, 16-17=-820/0, 15-16=-1306/0, 14-15=-541/309, 13-14=-541/309, 12-13=-127/258
 WEBS 8-16=-613/0, 3-21=-291/0, 2-21=0/311, 2-22=-777/0, 1-22=0/771, 4-18=-558/0, 5-18=0/518, 5-17=-912/0, 7-17=0/949, 7-16=-983/0, 8-15=0/714, 9-15=-655/0, 9-13=-11/292, 10-12=-352/173

- NOTES-** (5-8)
- Unbalanced floor live loads have been considered for this design.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 104 lb uplift at joint 12.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard





2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F206	Floor	1	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:13 2024 Page 1
 ID:XfGBr?_CJqttCkF9NOQCWjycQDJ-dQIFp6bueHHMP6iQrWj9lhqn2elqBOrlCeDn4zgtta



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.41	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.59	Vert(LL) -0.09 24-25 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.45	Vert(CT) -0.12 24-25 >999 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.02 20 n/a n/a		
	Code IRC2021/TPI2014			Weight: 118 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. All bearings 0-3-8 except (jt=length) 27=0-3-0, 14=Mechanical.
 (lb) - Max Uplift All uplift 100 lb or less at joint(s) 14
 Max Grav All reactions 250 lb or less at joint(s) 14 except 27=612(LC 5), 20=1355(LC 3), 16=565(LC 4)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 27-28=-607/0, 1-28=-606/0, 1-2=-611/0, 2-3=-1446/0, 3-4=-1630/0, 4-5=-1206/0, 7-8=0/1299, 8-9=0/816, 9-10=-168/272
 BOT CHORD 25-26=0/1208, 24-25=0/1630, 23-24=0/1630, 22-23=0/1630, 21-22=0/816, 20-21=-812/0, 19-20=-1299/0, 18-19=-509/226, 17-18=-509/226
 WEBS 8-20=-595/0, 11-16=-314/0, 3-25=-293/0, 2-25=0/310, 2-26=-776/0, 1-26=0/771, 4-22=-557/0, 5-22=0/517, 5-21=-911/0, 7-21=0/948, 7-20=-985/0, 8-19=0/688, 9-19=-629/0, 9-17=-88/309, 10-17=-267/126, 10-16=-374/257, 12-14=-281/16

- NOTES-** (6-9)
- Unbalanced floor live loads have been considered for this design.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 14.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard





2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F207	Floor	1	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:14 2024 Page 1
 ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-5csd0ScXPbPD1GHcPeFOlVnX515UwrySRlyxJXzgtZ



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.46	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.62	Vert(LL) -0.09 24-25 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.46	Vert(CT) -0.12 24-25 >999 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.02 14 n/a n/a		
	Code IRC2021/TPI2014				Weight: 117 lb FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 27=594/0-3-0 (min. 0-1-8), 14=372/Mechanical, 20=1507/0-3-8 (min. 0-1-8)
 Max Grav 27=615(LC 3), 14=455(LC 4), 20=1507(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 27-28=-610/0, 1-28=-609/0, 13-14=-457/0, 1-2=-615/0, 2-3=-1458/0, 3-4=-1650/0,
 4-5=-1233/0, 5-6=-160/288, 6-7=-160/288, 7-8=0/1438, 8-9=-4/823, 9-10=-786/351,
 10-11=-786/351, 11-12=-811/83
 BOT CHORD 25-26=0/1215, 24-25=0/1650, 23-24=0/1650, 22-23=0/1650, 21-22=-29/848, 20-21=-949/0,
 19-20=-1438/0, 18-19=-564/528, 17-18=-564/528, 16-17=-186/934, 15-16=-9/658
 WEBS 8-20=-739/0, 3-25=-260/18, 2-25=0/316, 2-26=-781/0, 1-26=0/776, 4-22=-603/0,
 5-22=0/539, 5-21=-928/0, 7-21=0/966, 7-20=-978/0, 8-19=0/897, 9-19=-826/0, 9-17=0/479,
 11-17=-337/0, 12-15=-582/19, 13-15=0/446

- NOTES-** (5-8)
- Unbalanced floor live loads have been considered for this design.
 - Refer to girder(s) for truss to truss connections.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard





2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F208	Floor	2	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:16 2024 Page 1
 ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-1?zNR8enxCfGaR?X3HsNKSINrffOIRvcr2NPzgttX



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.41	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.64	Vert(LL) -0.10 24-25 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.46	Vert(CT) -0.12 24-25 >999 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.02 13 n/a n/a		
	Code IRC2021/TPI2014			Weight: 114 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 27=601/0-3-0 (min. 0-1-8), 13=381/Mechanical, 20=1491/0-3-8 (min. 0-1-8)
 Max Grav 27=636(LC 3), 13=438(LC 4), 20=1491(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 27-28=-632/0, 1-28=-631/0, 12-13=-428/0, 1-2=-639/0, 2-3=-1534/0, 3-4=-1772/0,
 4-5=-1401/0, 5-6=-379/365, 6-7=-379/365, 7-8=0/1392, 8-9=0/827, 9-10=-601/245,
 10-11=-815/29, 11-12=-382/0
 BOT CHORD 25-26=0/1262, 24-25=0/1772, 23-24=0/1772, 22-23=0/1772, 21-22=-146/1045, 20-21=-843/0,
 19-20=-1392/0, 18-19=-428/344, 17-18=-428/344, 16-17=-29/815, 15-16=-29/815,
 14-15=-29/815
 WEBS 8-20=-704/0, 3-25=-304/53, 2-25=0/354, 2-26=-810/0, 1-26=0/806, 4-22=-633/0,
 5-22=0/543, 5-21=-930/0, 7-21=0/967, 7-20=-966/0, 10-17=-461/0, 9-17=0/449,
 9-19=-844/0, 8-19=0/807, 11-14=-553/64, 12-14=0/505

- NOTES-** (5-8)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) Refer to girder(s) for truss to truss connections.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) CAUTION, Do not erect truss backwards.
 - 5) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - 7) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - 8) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard




2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F209	Floor	4	1	
Job Reference (optional)					# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:17 2024 Page 1
 ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-VBXIfUePiWnouk0B4mo5vX?TuF307EUu7GBbwszgtlW



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	1-4-0	TC 0.42	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.83	Vert(LL) -0.18 13-14 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.35	Vert(CT) -0.24 13-14 >765 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.03 10 n/a n/a		
	Code IRC2021/TPI2014			Weight: 82 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 18=563/0-2-10 (min. 0-1-8), 10=568/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 18-19=-565/0, 1-19=-554/0, 1-2=-561/0, 2-3=-1506/0, 3-4=-1987/0, 4-5=-2058/0, 5-6=-1725/0, 6-7=-1725/0, 7-8=-902/0
 BOT CHORD 16-17=0/1126, 15-16=0/1987, 14-15=0/1987, 13-14=0/1987, 12-13=0/2018, 11-12=0/1398, 10-11=0/384
 WEBS 3-16=-650/0, 2-16=0/494, 2-17=-736/0, 1-17=0/725, 5-12=-374/0, 7-12=0/418, 7-11=-645/0, 8-11=0/674, 8-10=-697/0

- NOTES-** (5-8)
- Unbalanced floor live loads have been considered for this design.
 - Provide mechanical connection (by others) of truss to bearing plate at joint(s) 18.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION. Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F210	Floor	2	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:18 2024 Page 1
 ID:XFGBr?_CJqttCk9NOQCWjycQDJ-_N58sqf1TpvfVubNeTJKSIXg4fT4sic1Mww8SlzgttV





Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [15:Edge,0-1-8], [16:0-1-8,0-1-8]					
LOADING (psf)	SPACING- 1-4-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.27	Vert(LL) -0.09 10-11 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.52	Vert(CT) -0.12 10-11 >999 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.29	Horz(CT) 0.02 8 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			Weight: 69 lb FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 15=481/0-2-10 (min. 0-1-8), 8=485/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 15-16=-480/0, 1-16=-471/0, 1-2=-470/0, 2-3=-1215/0, 3-4=-1512/0, 4-5=-1403/0, 5-6=-873/0
 BOT CHORD 13-14=0/948, 12-13=0/1512, 11-12=0/1512, 10-11=0/1512, 9-10=0/1252, 8-9=0/477
 WEBS 3-13=-436/0, 2-13=0/347, 2-14=-622/0, 1-14=0/607, 4-10=-269/10, 5-9=-493/0, 6-9=0/516, 6-8=-665/0

- NOTES-** (5-8)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 15.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) CAUTION, Do not erect truss backwards.
 - 5) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - 7) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - 8) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F211	Floor	10	1	
Job Reference (optional)					# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:19 2024 Page 1
 ID:XfGBr?_CJqttCkF9NOQCWjycQDJ-SafW49gfE72V71AaCBqZ?y4pQ2IYb8?Bbagi_kzgttU




Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [18:Edge,0-1-8], [19:0-1-8,0-1-8]					
LOADING (psf)	SPACING- 1-4-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.42	Vert(LL) -0.18 13-14 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.82	Vert(CT) -0.24 13-14 >770 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.34	Horz(CT) 0.03 10 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
				Weight: 82 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 18=562/0-2-10 (min. 0-1-8), 10=566/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 18-19=-564/0, 1-19=-553/0, 1-2=-560/0, 2-3=-1502/0, 3-4=-1980/0, 4-5=-2049/0, 5-6=-1713/0, 6-7=-1713/0, 7-8=-887/0
 BOT CHORD 16-17=0/1124, 15-16=0/1980, 14-15=0/1980, 13-14=0/1980, 12-13=0/2007, 11-12=0/1384, 10-11=0/368
 WEBS 3-16=-647/0, 2-16=0/492, 2-17=-734/0, 1-17=0/723, 5-12=-375/0, 7-12=0/420, 7-11=-647/0, 8-11=0/676, 8-10=-690/0

- NOTES-** (5-8)
- Unbalanced floor live loads have been considered for this design.
 - Provide mechanical connection (by others) of truss to bearing plate at joint(s) 18.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION. Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F212	Floor	3	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:20 2024 Page 1
 ID:XfGBr?_CJqtCk9NOQCWjycQDJ-wmDuHVhH?RAMIBImmuLoXAc?DS7tKbdKpEPFXAzgTt




Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [16:Edge,0-1-8], [17:0-1-8,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	1-4-0	TC 0.35	Vert(LL)	-0.14	11-12	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.69	Vert(CT)	-0.18	11-12	>941		
BCLL 0.0	Lumber DOL 1.00	WB 0.32	Horz(CT)	0.03	8	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH						
	Code IRC2021/TPI2014						Weight: 75 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 16=527/0-3-0 (min. 0-1-8), 8=531/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 16-17=-527/0, 1-17=-517/0, 7-8=-529/0, 1-2=-521/0, 2-3=-1376/0, 3-4=-1775/0, 4-5=-1765/0, 5-6=-1352/0, 6-7=-476/0
 BOT CHORD 14-15=0/1047, 13-14=0/1775, 12-13=0/1775, 11-12=0/1775, 10-11=0/1675, 9-10=0/1017
 WEBS 3-14=-554/0, 2-14=0/428, 2-15=-685/0, 1-15=0/672, 5-10=-420/0, 6-10=0/436, 6-9=-704/0, 7-9=0/666

- NOTES-** (4-7)
- Unbalanced floor live loads have been considered for this design.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F213	Floor	5	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:21 2024 Page 1
 ID: XfGBr?_CjqtCkf9NOQCWjycQDJ-OynGUrhwmkIDMLKyJct14N960sS931ZU2u9p3dzgttS




Plate Offsets (X,Y)--	[3:0-1-8,Edge], [4:0-1-8,Edge], [11:Edge,0-1-8], [22:Edge,0-1-8], [23:0-1-8,0-1-8]				
LOADING (psf)	SPACING- 1-4-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.61	Vert(LL) -0.28 17-18 >758 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.75	Vert(CT) -0.39 17-18 >551 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.40	Horz(CT) 0.04 11 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
				Weight: 93 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP SS(flat) *Except* B2: 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 22=649/0-3-0 (min. 0-1-8), 11=653/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 22-23=-653/0, 1-23=-641/0, 1-2=-657/0, 2-3=-1805/0, 3-4=-2480/0, 4-5=-2748/0, 5-6=-2622/0, 6-7=-2622/0, 7-8=-2008/0, 8-9=-980/0
 BOT CHORD 20-21=0/1313, 19-20=0/2480, 18-19=0/2480, 17-18=0/2480, 16-17=0/2821, 15-16=0/2422, 14-15=0/2422, 13-14=0/1600, 12-13=0/1600, 11-12=0/340
 WEBS 3-19=0/320, 4-18=-299/0, 3-20=-883/0, 2-20=0/641, 2-21=-854/0, 1-21=0/849, 4-17=-63/456, 5-16=-260/0, 7-16=0/256, 7-14=-528/0, 8-14=0/532, 8-12=-807/0, 9-12=0/832, 9-11=-761/0

- NOTES-** (4-7)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 3) CAUTION, Do not erect truss backwards.
 - 4) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - 5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - 6) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - 7) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F214	Floor Supported Gable	1	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:22 2024 Page 1
 ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-s9LeiBiYX2Q4_Vu8tJOGcbiQKgy?oaddHYUmB3zgtfR

0₁+8

Scale = 1:25.1




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [7:0-1-8,Edge], [19:0-1-8,Edge], [26:Edge,0-1-8], [27:0-1-8,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	14	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH					Weight: 70 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 15-5-10.
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 26, 14, 25, 24, 23, 22, 21, 20, 19, 18, 17, 16, 15

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (6-9)
- Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F215	Floor Girder	1	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:23 2024 Page 1
 ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-KLu1vXjAlMYxcFLTLR1vV9oEOxgIDX?dnWCev7VzgtIQ

Scale = 1:10.9




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [3:0-1-8,Edge], [9:0-1-8,Edge], [12:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.84	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	NO	WB 0.18	Horz(CT)	-0.00	9	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-P						Weight: 31 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)
 OTHERS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-11-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 5-11-0.
 (lb) - Max Uplift All uplift 100 lb or less at joint(s) 12, 7
 Max Grav All reactions 250 lb or less at joint(s) 12, 7, 8 except 11=511(LC 1), 10=664(LC 1), 9=783(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-11=-497/0, 3-10=-651/0, 4-9=-770/0

- NOTES-** (9-12)
- Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 12, 7.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent spaced at 2-0-0 oc max. starting at 2-1-4 from the left end to 4-1-4 to connect truss(es) F202 (1 ply 2x4 SP) to back face of top chord.
 - Fill all nail holes where hanger is in contact with lumber.
 - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 7-12=-10, 1-6=-100
 Concentrated Loads (lb)
 Vert: 4=-738(B) 13=-738(B)




2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-1218-F02	Truss F216	Truss Type Floor	Qty 1	Ply 1	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC	Job Reference (optional) # 45874
--------------------	---------------	---------------------	----------	----------	--	--

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:24 2024 Page 1
ID:XfGBr?_CJqtCk9NOQCWjycQDJ-oXSP7tko3fgoDp2X?kQki0nfM3eRGTWwksNTgyzgtP



Scale = 1:8.4




Plate Offsets (X,Y)-- [5:Edge,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.47	Vert(LL) -0.00	4	>999	480	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.01	Vert(CT) -0.00	4	>999	360		
BCLL 0.0	Lumber DOL 1.00	WB 0.01	Horz(CT) 0.00	3	n/a	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-P						
	Code IRC2021/TPI2014						Weight: 19 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 3-0-8 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 5=154/0-3-8 (min. 0-1-8), 3=154/Mechanical

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (3-6)
- 1) Refer to girder(s) for truss to truss connections.
 - 2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 3) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - 4) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - 5) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - 6) SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-1218-F02	Truss F217	Truss Type Floor Girder	Qty 1	Ply 1	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 45874
--------------------	---------------	----------------------------	----------	----------	--

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:24 2024 Page 1
ID:XfGbr?_CJqttCkf9NOQCWjycQDJ-oXSP7tko3fgoDp2X?kQki0nhT3clGQTwksNTgyzgtP



Scale = 1:11.8



LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.34	Vert(LL) -0.01 6 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.15	Vert(CT) -0.01 6-7 >999 360		
BCLL 0.0	Rep Stress Incr NO	WB 0.20	Horz(CT) 0.00 5 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-P		Weight: 35 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 8=366/0-3-8 (min. 0-1-8), 5=377/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-8=-361/0, 1-2=-332/0, 2-9=-529/0, 3-9=-529/0
BOT CHORD 6-7=0/625, 5-6=0/399
WEBS 1-7=0/424, 2-7=-382/0, 3-5=-527/0

NOTES- (5-8)

- 1) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 2) Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent at 3-9-12 from the left end to connect truss(es) F216 (1 ply 2x4 SP) to back face of top chord.
- 3) Fill all nail holes where hanger is in contact with lumber.
- 4) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- 5) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
- 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
- 7) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
- 8) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard

- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 5-8=-10, 1-4=-100
Concentrated Loads (lb)
Vert: 9=-54(B)



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F218	Floor Supported Gable	1	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:25 2024 Page 1
 ID:XfGBr?_CJqttCk9NOQCWjycQDJ-Gj0nKDIQpzofrydjYSxzEDKxbT_i?wN3zW70COzgttO

0₁1₈

0₁1₈

Scale = 1:21.6




Plate Offsets (X,Y)--		[6:0-1-8,Edge], [16:0-1-8,Edge], [22:Edge,0-1-8]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 40.0	Plate Grip DOL 1.00		TC 0.06
TCDL 10.0	Lumber DOL 1.00		BC 0.01
BCLL 0.0	Rep Stress Incr YES		WB 0.03
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH
			DEFL. in (loc) l/defl L/d
			Vert(LL) n/a - n/a 999
			Vert(CT) n/a - n/a 999
			Horz(CT) 0.00 12 n/a n/a
			PLATES GRIP
			MT20 244/190
			Weight: 58 lb FT = 20%F, 11%E


LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS. All bearings 13-1-0.
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 22, 12, 21, 20, 19, 18, 17, 16, 15, 14, 13

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (5-8)
- Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F219	Floor	5	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:26 2024 Page 1
 ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-lwa9YZI2aHwWT6Cw69SChRs12iBokGbDCAsZkqzgttN





Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [6:0-1-8,Edge], [14:Edge,0-1-8]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.33	Vert(LL) -0.10 11-12 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.59	Vert(CT) -0.13 11-12 >999 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.48	Horz(CT) 0.03 7 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
				Weight: 65 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 14=700/0-3-0 (min. 0-1-8), 7=700/0-3-0 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 14-15=-694/0, 1-15=-692/0, 7-16=-694/0, 6-16=-692/0, 1-2=-869/0, 2-3=-1848/0, 3-4=-2143/0, 4-5=-1848/0, 5-6=-869/0
 BOT CHORD 12-13=0/1542, 11-12=0/2143, 10-11=0/2143, 9-10=0/2143, 8-9=0/1542
 WEBS 3-12=-509/0, 2-12=0/428, 2-13=-876/0, 1-13=0/1012, 4-9=-509/0, 5-9=0/428, 5-8=-876/0, 6-8=0/1012


- NOTES-** (3-6)
- Unbalanced floor live loads have been considered for this design.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard




2/26/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale = 1:22.7



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.40	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.78	Vert(LL) -0.14 11-12 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.48	Vert(CT) -0.19 11-12 >805 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.03 8 n/a n/a		
	Code IRC2021/TPI2014			Weight: 70 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 16=738/Mechanical, 8=597/1-3-8 (min. 0-1-8), 9=158/0-3-8 (min. 0-1-8)
 Max Grav 16=738(LC 1), 8=597(LC 1), 9=165(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-16=-734/0, 1-2=-784/0, 2-3=-1898/0, 3-4=-2330/0, 4-5=-2169/0, 5-6=-1316/0
 BOT CHORD 14-15=0/1508, 13-14=0/2330, 12-13=0/2330, 11-12=0/2330, 10-11=0/1912, 9-10=0/807, 8-9=0/807
 WEBS 3-14=-642/0, 2-14=0/510, 2-15=-943/0, 1-15=0/1006, 4-11=-400/22, 5-11=0/377, 5-10=-783/0, 6-10=0/673,
 6-8=-1021/0

- NOTES-** (5-8)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) Refer to girder(s) for truss connections.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) CAUTION. Do not erect truss backwards.
 - 5) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - 7) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - 8) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard




2/26/2024


Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-1218-F02	Truss F221	Truss Type Floor	Qty 2	Ply 1	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 45874
--------------------	---------------	---------------------	----------	----------	--

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:28 2024 Page 1
ID:XFGBr?_CJqtCk9NOQCWjycQDJ-hliwzEnJ6uAEiQMIEaVgssyL5hpFCA_WfULgpjzgtL



Scale = 1:22.7



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.42	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.82	Vert(LL) -0.15 10-11 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.49	Vert(CT) -0.20 10-11 >809 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.03 8 n/a n/a		
	Code IRC2021/TPI2014			Weight: 70 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 15=750/Mechanical, 8=743/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-15=-746/0, 1-2=-798/0, 2-3=-1942/0, 3-4=-2401/0, 4-5=-2253/0, 5-6=-1477/0
BOT CHORD 13-14=0/1535, 12-13=0/2401, 11-12=0/2401, 10-11=0/2401, 9-10=0/2037, 8-9=0/889
WEBS 3-13=-678/0, 2-13=0/533, 2-14=-960/0, 1-14=0/1024, 4-10=-400/40, 5-10=0/358, 5-9=-729/0, 6-9=0/766, 6-8=-1125/0

- NOTES-** (5-8)
- Unbalanced floor live loads have been considered for this design.
 - Refer to girder(s) for truss to truss connections.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024


Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F222	Floor	1	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:29 2024 Page 1
 ID:XfGBr?_CJqttCkf9NOQCWjycQDJ-9VGIAaoxtCI5KaxVnH0vP3UVQ4Cjxchfu85EL9zgtIK



Scale = 1:27.5



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.45	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.58	Vert(LL) -0.09 18-19 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.52	Vert(CT) -0.12 18-19 >999 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.02 13 n/a n/a		
	Code IRC2021/TPI2014			Weight: 88 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. All bearings 3-3-0 except (jt=length) 21=Mechanical.
 (lb) - Max Uplift All uplift 100 lb or less at joint(s) except 12=-188(LC 4), 11=-295(LC 4)
 Max Grav All reactions 250 lb or less at joint(s) 12 except 21=632(LC 1), 13=1645(LC 1), 13=1645(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-21=-625/0, 1-2=-654/0, 2-3=-1510/0, 3-4=-1510/0, 4-5=-1706/0, 5-6=-1298/0, 6-7=-299/11, 7-8=0/1506, 8-9=0/633
 BOT CHORD 19-20=0/1266, 18-19=0/1706, 17-18=0/1706, 16-17=0/1706, 15-16=0/918, 14-15=-649/0, 13-14=-649/0, 12-13=-1506/0
 WEBS 8-13=-874/0, 4-19=-329/0, 2-19=0/319, 2-20=-796/0, 1-20=0/840, 5-16=-529/0, 6-16=0/495, 6-15=-899/0, 7-15=0/936,
 7-13=-1222/0, 8-12=0/1096, 9-12=-737/0

- NOTES-** (6-9)
- Unbalanced floor live loads have been considered for this design.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 188 lb uplift at joint 12 and 295 lb uplift at joint 11.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F223	Floor	1	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:31 2024 Page 1
 ID:XfGBr?_CJqttCk9NOQCWjycQDJ-5iN2bGpBPpYpZi5tvi2NUUamlupUPV5yLSaKP2zgtll



Scale = 1:40.0




Plate Offsets (X,Y)-- [2:0-1-8,Edge], [3:0-1-8,Edge], [8:0-1-8,Edge], [9:0-1-8,Edge], [30:Edge,0-1-8]

LOADING (psf)	SPACING	CSI	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.78	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.94	Vert(LL) -0.33 19-20 >636 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.59	Vert(CT) -0.45 19-20 >464 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.05 15 n/a n/a		
	Code IRC2021/TPI2014			Weight: 125 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat) *Except*
 B2: 2x4 SP SS(flat)
 WEBS 2x4 SP No.3(flat)


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-1-10 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.

REACTIONS. (lb/size) 30=228/0-3-8 (min. 0-1-8), 15=893/0-3-0 (min. 0-1-8), 25=1537/0-3-8 (min. 0-1-8)
 Max Uplift30=-42(LC 4)
 Max Grav30=332(LC 3), 15=902(LC 7), 25=1537(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-30=-335/24, 14-15=-901/0, 2-3=-455/311, 3-4=-28/735, 4-5=0/1102, 5-6=-872/0, 6-7=-872/0, 7-8=-2411/0, 8-9=-3265/0, 9-10=-3501/0, 10-11=-3134/0, 11-12=-3134/0, 12-13=-2043/0, 13-14=-337/0
 BOT CHORD 28-29=-311/455, 27-28=-311/455, 26-27=-311/455, 25-26=-1102/0, 24-25=-352/0, 23-24=0/1762, 22-23=0/1762, 21-22=0/3265, 20-21=0/3265, 19-20=0/3265, 18-19=0/3515, 17-18=0/2717, 16-17=0/1332
 WEBS 8-21=0/403, 9-20=-372/0, 4-25=-473/0, 2-29=-279/306, 1-29=-99/329, 3-26=-857/0, 4-26=0/568, 8-22=-1146/0, 7-22=0/877, 7-24=-1186/0, 5-24=0/1244, 5-25=-1305/0, 9-19=-147/502, 10-18=-486/0, 12-18=0/532, 12-17=-877/0, 13-17=0/926, 13-16=-1295/0, 14-16=0/908

- NOTES-** (5-8)
- Unbalanced floor live loads have been considered for this design.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 42 lb uplift at joint 30.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard




2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-1218-F02	Truss F224	Truss Type Floor	Qty 2	Ply 1	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC	Job Reference (optional) # 45874
--------------------	---------------	---------------------	----------	----------	--	--

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:33 2024 Page 1
ID:XfGBr?_CJqtCkf9NOQCWjycQDJ-1GVp0yrRxQoWpBEG074sZvf56iUCtPmFpm3RUWzgtJG



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	40.0	Plate Grip DOL	2.0-0	TC	0.85	Vert(LL)	-0.33 21-22 >631 480	MT20	244/190	Weight: 131 lb FT = 20%F, 11%E	
TCDL	10.0	Lumber DOL	1.00	BC	0.99	Vert(CT)	-0.43 21-22 >485 360				
BCLL	0.0	Rep Stress Incr	NO	WB	0.58	Horz(CT)	0.05 17 n/a n/a				
BCDL	5.0	Code IRC2021/TPI2014	NO	Matrix-SH							


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 5-6-9 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat) *Except* B2: 2x4 SP SS(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 32=230/0-3-8 (min. 0-1-8), 17=1319/0-3-8 (min. 0-1-8), 27=1517/0-3-8 (min. 0-1-8)
Max Uplift 32=40(LC 6)
Max Grav 32=334(LC 5), 17=1320(LC 4), 27=1520(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-32=-338/22, 16-33=-335/0, 33-34=-335/0, 15-34=-335/0, 2-3=-465/305, 3-4=-45/725,
4-5=0/1090, 5-6=-854/0, 6-7=-854/0, 7-8=-2355/0, 8-9=-3174/0, 9-10=-3376/0,
10-11=-2971/0, 11-12=-2971/0, 12-13=-1841/0
BOT CHORD 30-31=-305/465, 29-30=-305/465, 28-29=-305/465, 27-28=-1090/0, 26-27=-353/0,
25-26=0/1727, 24-25=0/1727, 23-24=0/3174, 22-23=0/3174, 21-22=0/3174, 20-21=0/3368,
19-20=0/2535, 18-19=0/1108, 17-18=-297/0, 16-17=-293/0
WEBS 8-23=0/384, 9-22=-353/6, 4-27=-473/0, 14-17=-1238/0, 2-31=-287/301, 1-31=-96/333,
3-28=-851/0, 4-28=0/565, 8-24=-1101/0, 7-24=0/849, 7-26=-1165/0, 5-26=0/1221,
5-27=-1284/0, 9-21=-202/457, 10-20=-506/0, 12-20=0/556, 12-19=-904/0, 13-19=0/954,
13-18=-1305/0, 14-18=0/876, 14-16=0/439

- NOTES-** (6-9)
- Unbalanced floor live loads have been considered for this design.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 40 lb uplift at joint 32.
 - Load case(s) 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION. Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024

Continued on Page 2 Design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F224	Floor	2	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:34 2024 Page 2
ID:XfGBr?_CJqttCkF9NOQCWjycQDJ-WS3BDlr3ikwNQLpSaqc567CGs5pRcs0O2Qo?0MzgtfF

LOAD CASE(S) Standard

- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-20, 4-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 5) 3rd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-100, 4-14=-20, 14-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 6) 4th Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-20, 4-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 7) 5th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 8) 6th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-20, 4-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 9) 7th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-100, 4-14=-20, 14-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 10) 8th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-20, 4-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 11) 1st chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-3=-100, 3-4=-20, 4-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 12) 2nd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-2=-20, 2-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 13) 3rd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-9=-100, 9-14=-20, 14-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 14) 4th chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-100, 4-8=-20, 8-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 15) 5th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-3=-100, 3-4=-20, 4-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 16) 6th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-2=-20, 2-14=-100, 14-15=-20



2/26/2024

Continued on Page 3 Design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F224	Floor	2	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:34 2024 Page 3
ID:XfGBr?_CJqtCkf9NOQCWjycQDJ-WS3BDlr3ikwNQLpSaqc567CGs5pRcs0O2Qo?0Mzgtlf

LOAD CASE(S) Standard

Concentrated Loads (lb)

Vert: 15=-300

17) 7th chase Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 16-32=-10, 1-9=-100, 9-14=-20, 14-15=-100

Concentrated Loads (lb)

Vert: 15=-300

18) 8th chase Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 16-32=-10, 1-4=-100, 4-8=-20, 8-14=-100, 14-15=-20

Concentrated Loads (lb)

Vert: 15=-300



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F225	Floor	2	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:36 2024 Page 1
 ID:XfGBr?_CJqttCk9NOQCWjycQDJ-SrBxeztKELB5gfzriFeZBYHcMvV_4mShVjH55FzgtID




Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [9:0-1-8,Edge], [10:0-1-8,Edge], [34:Edge,0-1-8], [35:0-1-8,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.85	Vert(LL)	-0.33	22-23	>632	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.99	Vert(CT)	-0.43	22-23	>485		
BCLL 0.0	Lumber DOL 1.00	WB 0.58	Horz(CT)	0.05	18	n/a		
BCDL 5.0	Rep Stress Incr NO	Matrix-SH						
	Code IRC2021/TPI2014							
							Weight: 142 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 5-6-9 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat) *Except* B2: 2x4 SP SS(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 34=390/0-3-8 (min. 0-1-8), 18=1319/0-3-8 (min. 0-1-8), 28=1604/0-3-8 (min. 0-1-8)
 Max Grav 34=485(LC 5), 18=1319(LC 1), 28=1606(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-34=-477/0, 17-35=-335/0, 35-36=-335/0, 16-36=-335/0, 1-2=-321/0, 2-3=-927/125,
 3-4=-919/397, 4-5=-278/849, 5-6=0/1180, 6-7=-838/0, 7-8=-838/0, 8-9=-2342/0,
 9-10=-3163/0, 10-11=-3367/0, 11-12=-2965/0, 12-13=-2965/0, 13-14=-1838/0
 BOT CHORD 32-33=-6/805, 31-32=-397/919, 30-31=-397/919, 29-30=-397/919, 28-29=-1180/0,
 27-28=-433/53, 26-27=0/1711, 25-26=0/1711, 24-25=0/3163, 23-24=0/3163, 22-23=0/3163,
 21-22=0/3361, 20-21=0/2531, 19-20=0/1107, 18-19=-297/0, 17-18=-292/0
 WEBS 3-31=-279/0, 4-30=0/326, 9-24=0/378, 10-23=-347/9, 5-28=-522/0, 15-18=-1237/0,
 3-32=0/348, 2-33=-629/7, 1-33=-1/519, 4-29=-1104/0, 5-29=0/695, 9-25=-1112/0,
 8-25=0/859, 8-27=-1171/0, 6-27=0/1227, 6-28=-1309/0, 10-22=-209/443, 11-21=-505/0,
 13-21=0/554, 13-20=-902/0, 14-20=0/952, 14-19=-1303/0, 15-19=0/874, 15-17=0/439

- NOTES-** (5-8)
- Unbalanced floor live loads have been considered for this design.
 - Load case(s) 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00



2/26/2024

Continued on Page 2 Design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F225	Floor	2	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:36 2024 Page 2
 ID:XfGBr?_CJqtCk9NOQCWjycQDJ-SrBxeztKELB5gfzriFeZBYHcMVV_4mShVjH55FzgtID

LOAD CASE(S) Standard

- Uniform Loads (plf)
 - Vert: 17-34=-10, 1-16=-100
- Concentrated Loads (lb)
 - Vert: 16=-300
- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-16=-100
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-15=-100, 15-16=-20
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-5=-20, 5-16=-100
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 5) 3rd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-5=-100, 5-15=-20, 15-16=-100
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 6) 4th Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-5=-20, 5-15=-100, 15-16=-20
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 7) 5th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-15=-100, 15-16=-20
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 8) 6th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-5=-20, 5-16=-100
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 9) 7th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-5=-100, 5-15=-20, 15-16=-100
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 10) 8th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-5=-20, 5-15=-100, 15-16=-20
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 11) 1st chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-4=-100, 4-5=-20, 5-15=-100, 15-16=-20
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 12) 2nd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-3=-20, 3-15=-100, 15-16=-20
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 13) 3rd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-10=-100, 10-15=-20, 15-16=-100
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 14) 4th chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-5=-100, 5-9=-20, 9-15=-100, 15-16=-20
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 15) 5th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-4=-100, 4-5=-20, 5-15=-100, 15-16=-20
 - Concentrated Loads (lb)
 - Vert: 16=-300
- 16) 6th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 17-34=-10, 1-3=-20, 3-15=-100, 15-16=-20



2/26/2024

Continued on Page 3 Design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F225	Floor	2	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:36 2024 Page 3
 ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-SrBxeztKELB5gfzriFeZBYHcMVV_4mShVjH55FzgtlD

LOAD CASE(S) Standard

Concentrated Loads (lb)
 Vert: 16=-300

17) 7th chase Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)
 Vert: 17-34=-10, 1-10=-100, 10-15=-20, 15-16=-100

Concentrated Loads (lb)
 Vert: 16=-300

18) 8th chase Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)
 Vert: 17-34=-10, 1-5=-100, 5-9=-20, 9-15=-100, 15-16=-20

Concentrated Loads (lb)
 Vert: 16=-300



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F226	Floor	1	1	# 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:38 2024 Page 1
 ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-OEI13fvamzRpv7Dpgg1GzMysjBOYg?_y1mC98zgttB




Plate Offsets (X,Y)-- [2:0-1-8,Edge], [3:0-1-8,Edge], [8:0-1-8,Edge], [9:0-1-8,Edge], [32:Edge,0-1-8], [33:0-1-8,0-1-8]							
LOADING (psf)	SPACING -	2-0-0	CSI.	DEFL.	in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.85	Vert(LL) -0.33 21-22	>631 480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.99	Vert(CT) -0.43 21-22	>485 360		
BCLL 0.0	Rep Stress Incr	NO	WB 0.58	Horz(CT) 0.05 17	n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH				
						Weight: 131 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat) *Except*
 B2: 2x4 SP SS(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-6-9 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.


REACTIONS. (lb/size) 32=233/0-3-8 (min. 0-1-8), 17=1319/0-3-8 (min. 0-1-8), 27=1518/0-3-8 (min. 0-1-8)
 Max Uplift 32=-39(LC 6)
 Max Grav 32=337(LC 5), 17=1320(LC 4), 27=1520(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-32=-340/22, 16-33=-335/0, 33-34=-335/0, 15-34=-335/0, 2-3=-473/306, 3-4=-517/26,
 4-5=0/1091, 5-6=-857/0, 6-7=-857/0, 7-8=-2358/0, 8-9=-3176/0, 9-10=-3377/0,
 10-11=-2972/0, 11-12=-2972/0, 12-13=-1841/0
 BOT CHORD 30-31=-306/473, 29-30=-306/473, 28-29=-306/473, 27-28=-1091/0, 26-27=-353/0,
 25-26=0/1730, 24-25=0/1730, 23-24=0/3176, 22-23=0/3176, 21-22=0/3176, 20-21=0/3369,
 19-20=0/2536, 18-19=0/1109, 17-18=-297/0, 16-17=-293/0
 WEBS 8-23=0/384, 9-22=-353/6, 4-27=-473/0, 14-17=-1238/0, 2-31=-287/299, 1-31=-97/339,
 3-28=-854/0, 4-28=0/566, 8-24=-1100/0, 7-24=0/849, 7-26=-1165/0, 5-26=0/1221,
 5-27=-1284/0, 9-21=-203/456, 10-20=-507/0, 12-20=0/557, 12-19=-904/0, 13-19=0/954,
 13-18=-1305/0, 14-18=0/876, 14-16=0/439

- NOTES-** (6-9)
- Unbalanced floor live loads have been considered for this design.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 39 lb uplift at joint 32.
 - Load case(s) 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION. Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard

2/26/2024



Continued on Page 2 Design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F226	Floor	1	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:39 2024 Page 2
ID:XFGBr?_CJqtCkF9NOQCWjycQDJ-sQs4G?vCWGZgX6iQNOBGPv7b6XdH7F7BhWlhazgtIA

LOAD CASE(S) Standard

- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-20, 4-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 5) 3rd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-100, 4-14=-20, 14-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 6) 4th Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-20, 4-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 7) 5th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 8) 6th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-20, 4-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 9) 7th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-100, 4-14=-20, 14-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 10) 8th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-20, 4-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 11) 1st chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-3=-100, 3-4=-20, 4-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 12) 2nd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-2=-20, 2-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 13) 3rd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-9=-100, 9-14=-20, 14-15=-100
Concentrated Loads (lb)
Vert: 15=-300
- 14) 4th chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-4=-100, 4-8=-20, 8-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 15) 5th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-3=-100, 3-4=-20, 4-14=-100, 14-15=-20
Concentrated Loads (lb)
Vert: 15=-300
- 16) 6th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 16-32=-10, 1-2=-20, 2-14=-100, 14-15=-20



2/26/2024

Continued on Page 3
Design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F226	Floor	1	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:39 2024 Page 3
 ID:XfGBr?_CJqtCk9NOQCWjycQDJ-sQs4G?vCWGZgX6iQNOBGpAv7b6XdH7F7BhWlhazgtlA

LOAD CASE(S) Standard

Concentrated Loads (lb)

Vert: 15=-300

17) 7th chase Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 16-32=-10, 1-9=-100, 9-14=-20, 14-15=-100

Concentrated Loads (lb)

Vert: 15=-300

18) 8th chase Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 16-32=-10, 1-4=-100, 4-8=-20, 8-14=-100, 14-15=-20

Concentrated Loads (lb)

Vert: 15=-300



2/26/2024


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-1218-F02	Truss F227	Truss Type Floor	Qty 1	Ply 1	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 45874
--------------------	---------------	---------------------	----------	----------	--

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:40 2024 Page 1
ID:XfGBr?_CJqttCkF9NOQCWjycQDJ-KcQSULwqHahX8GHcx5iVLOR12WtC0anHQLFJE0zgt9



Scale = 1:39.9



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL. in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.87	Vert(LL) -0.31	18-19	>662	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.97	Vert(CT) -0.43	18-19	>482		
BCLL 0.0	Rep Stress Incr	YES	WB 0.63	Horz(CT) 0.03	15	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH					
							Weight: 126 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat) *Except* B2: 2x4 SP SS(flat)	BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 28=86/0-3-8 (min. 0-1-8), 15=826/0-3-0 (min. 0-1-8), 24=1736/0-3-8 (min. 0-1-8)
Max Uplift 28=-173(LC 4)
Max Grav 28=283(LC 3), 15=832(LC 4), 24=1736(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-28=-286/167, 2-3=-316/627, 3-4=0/1349, 4-5=0/1872, 7-8=-1664/0, 8-9=-2646/0,
9-10=-3011/0, 10-11=-2781/0, 11-12=-2781/0, 12-13=-1834/0
BOT CHORD 26-27=-330/351, 25-26=-957/250, 24-25=-1872/0, 23-24=-1120/0, 22-23=0/939,
21-22=0/939, 20-21=0/2646, 19-20=0/2646, 18-19=0/2646, 17-18=0/3104, 16-17=0/2441,
15-16=0/1186
WEBS 8-20=0/443, 9-19=-412/0, 4-24=-699/0, 4-25=0/879, 3-25=-809/0, 3-26=0/429,
2-26=-387/0, 2-27=-316/315, 8-21=-1271/0, 7-21=0/956, 7-23=-1250/0, 5-23=0/1317,
5-24=-1321/0, 9-18=-10/599, 10-17=-412/0, 12-17=0/434, 12-16=-789/0, 13-16=0/843,
13-15=-1411/0

- NOTES-** (5-8)
- Unbalanced floor live loads have been considered for this design.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 173 lb uplift at joint 28.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard




2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-1218-F02	Truss F228	Truss Type Floor	Qty 1	Ply 1	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 45874
--------------------	---------------	---------------------	----------	----------	--

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:42 2024 Page 1
ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-H?YCV1y5pBxFOaQ_2WlZQpXoAKn0UcEatfkQlvzgt77



Scale = 1:33.8





Plate Offsets (X,Y)-- [1:Edge,0-1-8], [7:0-1-8,Edge], [8:0-1-8,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.19	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.05	Vert(LL) 0.00 15 **** 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.05	Vert(CT) -0.00 14-15 >999 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.00 14 n/a n/a		
	Code IRC2021/TPI2014				Weight: 104 lb FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 20-6-10.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 24, 20, 19, 21, 18, 14, 14 except 22=312(LC 1), 23=291(LC 1), 16=312(LC 1), 15=290(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (4-7)
- Unbalanced floor live loads have been considered for this design.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F229	Floor	5	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:43 2024 Page 2
 ID:XfGBr?_CJqttCkF9NOQCWjycQDJ-IB6a6NyjaV36?j?BcDGCz03s9kxIDwkj6JUzrLzgt6

LOAD CASE(S) Standard

- Concentrated Loads (lb)
Vert: 11=-800
- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-24=-7, 1-12=-67
Concentrated Loads (lb)
Vert: 11=-800
- 3) 1st chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-24=-7, 1-8=-67, 8-12=-13
Concentrated Loads (lb)
Vert: 11=-800
- 4) 2nd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-24=-7, 1-7=-13, 7-12=-67
Concentrated Loads (lb)
Vert: 11=-800
- 5) 3rd chase Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-24=-7, 1-8=-67, 8-12=-13
Concentrated Loads (lb)
Vert: 11=-800
- 6) 4th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-24=-7, 1-7=-13, 7-12=-67
Concentrated Loads (lb)
Vert: 11=-800




2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job 24-1218-F02	Truss F230	Truss Type Floor	Qty 2	Ply 1	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC # 45874
--------------------	---------------	---------------------	----------	----------	---

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:45 2024 Page 1
ID:XfGBr?_CJqtCk9NOQCWjycQDJ-haELX2_z66JpF19Zjelg2R9ExXaMhs10Zdz4vEzgt4



Scale = 1:35.2




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [7:0-1-8,Edge], [8:0-1-8,Edge], [25:Edge,0-1-8]

LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.48	Vert(LL)	-0.40	20	>632	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.97	Vert(CT)	-0.56	20	>459	360	MT20HS	187/143
BCLL 0.0	Rep Stress Incr	YES	WB 0.50	Horz(CT)	0.08	14	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH							
									Weight: 109 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 2-2-0 oc bracing: 20-21,19-20.

REACTIONS. (lb/size) 25=780/0-3-8 (min. 0-1-8), 14=780/Mechanical

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-25=-776/0, 1-2=-767/0, 2-3=-2224/0, 3-4=-3269/0, 4-5=-3269/0, 5-6=-3269/0, 6-7=-3816/0, 7-8=-3946/0, 8-9=-3656/0, 9-10=-2937/0, 10-11=-2937/0, 11-12=-1711/0
BOT CHORD 23-24=0/1608, 22-23=0/2820, 21-22=0/3650, 20-21=0/3946, 19-20=0/3946, 18-19=0/3391, 16-17=0/3391, 15-16=0/2400, 14-15=0/999
WEBS 7-21=-438/139, 6-21=0/350, 6-22=-486/0, 3-22=0/574, 3-23=-775/0, 2-23=0/802, 2-24=-1094/0, 1-24=0/1048, 8-18=-575/3, 9-18=0/437, 9-16=-580/0, 11-16=0/685, 11-15=-897/0, 12-15=0/926, 12-14=-1245/0

- NOTES-** (5-8)
- Unbalanced floor live loads have been considered for this design.
 - All plates are MT20 plates unless otherwise indicated.
 - Refer to girder(s) for truss to truss connections.
 - Required 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-1218-F02	Truss F231	Truss Type Floor	Qty 5	Ply 1	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 45874
--------------------	---------------	---------------------	----------	----------	--

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:46 2024 Page 1
ID:XFGBr?_CJqtCkF9NOQCWjycQDJ-9mnmjK0?btQRgsBkmHmpvbfhLyxyYQI79oHidRgzgtt3



Scale = 1:29.7



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	1-4-0	TC 0.72	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.84	Vert(LL) -0.23 16-17 >945 480	MT20HS	187/143
BCLL 0.0	Lumber DOL 1.00	WB 0.57	Vert(CT) -0.42 16-17 >512 360		
BCDL 5.0	Rep Stress Incr NO	Matrix-SH	Horz(CT) 0.06 11 n/a n/a		
	Code IRC2021/TPI2014			Weight: 94 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP SS(flat) *Except*
B2: 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 22=728/0-3-8 (min. 0-1-8), 11=1387/Mechanical

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-22=-722/0, 1-2=-271/0, 2-3=-1713/0, 3-4=-1713/0, 4-5=-2723/0, 5-6=-3282/0, 6-7=-3428/0, 7-8=-3179/0, 8-9=-2476/0
BOT CHORD 20-21=0/1090, 19-20=0/2300, 18-19=0/3282, 17-18=0/3282, 16-17=0/3282, 15-16=0/3430, 14-15=0/2923, 13-14=0/2923, 12-13=0/2017, 11-12=0/2017
WEBS 5-18=0/292, 6-17=-270/0, 5-19=-818/0, 4-19=0/577, 4-20=-763/0, 2-20=0/811, 2-21=-1066/0, 1-21=0/737, 6-16=-77/388, 7-15=-327/0, 8-15=0/333, 8-13=-581/0, 9-13=0/608, 9-11=-2418/0

- NOTES-** (7-10)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) Refer to girder(s) for truss to truss connections.
 - 4) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.
 - 7) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - 9) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - 10) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 11-22=-7, 1-10=-67



2/26/2024

Continued on Page 2 Design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F231	Floor	5	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:46 2024 Page 2
ID:XfGBr?_CJqtCkF9NOQCWjycQDJ-9mjkO?btQRgsBkmHmpvbfhLyxyYQI79oHidRgzgt3

LOAD CASE(S) Standard

- Concentrated Loads (lb)
Vert: 9=-800
- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 11-22=-7, 1-10=-67
Concentrated Loads (lb)
Vert: 9=-800
- 3) 1st chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 11-22=-7, 1-6=-67, 6-10=-13
Concentrated Loads (lb)
Vert: 9=-800
- 4) 2nd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 11-22=-7, 1-5=-13, 5-10=-67
Concentrated Loads (lb)
Vert: 9=-800
- 5) 3rd chase Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 11-22=-7, 1-6=-67, 6-10=-13
Concentrated Loads (lb)
Vert: 9=-800
- 6) 4th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 11-22=-7, 1-5=-13, 5-10=-67
Concentrated Loads (lb)
Vert: 9=-800



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC
24-1218-F02	F232	Floor Supported Gable	1	1	Job Reference (optional) # 45874

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:47 2024 Page 1
 ID:XfGBr?_CJqttCkF9NOQCWjycQDJ-dyL5yk0DekZXULJyr3K87sEh_LUR9tpJ1xSB_6zgtt2

0-1-8

Scale = 1:33.8




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [9:0-1-8,Edge], [28:0-1-8,Edge], [36:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	-0.00	19	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 89 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 20-6-8.
 (lb) - Max Uplift All uplift 100 lb or less at joint(s) 19
 Max Grav All reactions 250 lb or less at joint(s) 36, 19, 35, 34, 33, 32, 31, 30, 29, 28, 27, 26, 24, 23, 22, 21, 20

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (7-10)
- Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 19.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard




2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.

Job 24-1218-F02	Truss F233	Truss Type Floor Supported Gable	Qty 1	Ply 1	LOT 0.0043 HONEYCUTT HILLS 150 SHELBY MEADOW LANE ANGIER, NC	Job Reference (optional) # 45874
--------------------	---------------	-------------------------------------	----------	----------	--	--

Run: 86.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Tue Feb 27 17:37:48 2024 Page 1
ID:XfGBr?_CJqtCk9NOQCWjycQDJ-59vT940rP1hO6Vu8PnsNg4nrglq4uK1SGbBkWZzgt1



Scale = 1:8.4

Plate Offsets (X,Y)-- [1:Edge,0-1-8], [2:0-1-8,Edge], [5:Edge,0-1-8], [6:0-1-8,Edge], [8:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	5	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-P						Weight: 21 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 3-5-8 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 3-5-8.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 8, 5, 7, 6

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (5-8)
- Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



2/26/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D*Onofrio Drive, Madison, WI 53719.