
	HUS26	USP	5	NA	16d/3-1/2"	16d/3-1/2"
	JUS26	USP	6	NA	10d/3"	10d/3"

Truss Placement Plan  
SCALE: NTS

 = Indicates Left End of Truss  
( Reference Engineered Truss Drawing )  
Do NOT Erect Truss Backwards

LOAD CHART FOR JACK STUDS (BASED ON TABLES R502.5(1) & (b)) NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADERS/GUDES					
END REACTION (UP TO)	END REACTION (UP TO)	END REACTION (UP TO)	END REACTION (UP TO)	END REACTION (UP TO)	END REACTION (UP TO)
1700	2550	3400	4250	5100	5950
3400	5100	6800	8500	10200	11900
5100	6800	8500	10200	11900	13600
6800	8500	10200	11900	13600	15300
8500	10200	11900	13600	15300	
10200	11900	13600	15300		
11900	13600	15300			
13600	15300				
15300					

BUILDER	A & G Residential
JOB NAME	Lot 18 Jones Creek
PLAN	Rose B Roof
SEAL DATE	1/15/2025
QUOTE #	
JOB #	J1024-5560

CITY / CO.	Lilington / Harnett
ADDRESS	110 Mossy Bridge Ct.
MODEL	Roof
DATE REV.	02/17/25
DRAWN BY	Marshall Naylor
SALES REP.	Marshall Naylor

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSH-B1 and BCSH-B3 provided with the truss delivery package or online @ sbcindustry.com	
Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables ( derived from the prescriptive Code requirements ) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.	
Signature	Marshall Naylor Marshall Naylor

  
**ROOF & FLOOR  
TRUSSES & BEAMS**  
Reilly Road Industrial Park  
Fayetteville, N.C. 28309  
Phone: (910) 864-8787  
Fax: (910) 864-4444