



	Conne	Nail Information				
Sym	Product	Manuf	Qty	Supported Member	Header	Truss
	HUS26	USP	9	NA	16d/3-1/2"	16d/3-1/2"
	THD26-2	USP	1	NA	16d/3-1/2"	10d/3"

	COMTECH ROOF & FLOOR ROOF & FLOOR REILLY Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787										
	Phone: (910) 864-8787 Fax: (910) 864-4444 Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#. Signature David Landry										
	LOAD CHART FOR JACK STUDS (BASED ON TABLES R502.5(1) & (b))										
				REQUIRED /GIRDER WB2 STUDS FOR BEG D STUDS FOR BEG D STUDS FOR BEG D STUDS FOR FOR BEG D STUDS FOR BEG D STUDS FOR	EQUIRED @ EA END C STRDER NO STDLS Q OD STRDER NO C(L 4) 1 34000 2 68000 3 10200 4 17000						
	CITY / CO . Harnett / Harnett	22 Peach Orcahrd Ln.	Roof	03/29/24	DRAWN BY David Landry	SALES REP. Marshall Naylor					
	CITY / CO .	ADDRESS	MODEL	DATE REV.	DRAWN BY	SALES REP.					
	Onsite Homes, LLC	VE Lot 1 Peach Orchard	Avery "A" / 2GRF, CP	ΤΕ 9/28/2020		J0324-1871					
	BUILDER	JOB NAME	PLAN	SEAL DATE	QUOTE #	JOB #					
)	These to compore design See ind identified designed for the support and col designed	HIS IS A TRUSS PLACEMENT DIAGRAM ONLY. hese trusses are designed as individual building omponents to be incorporated into the building sign at the specification of the building designer. se individual design sheets for each truss design entified on the placement drawing. The building signer is responsible for temporary and rmanent bracing of the roof and floor system and r the overall structure. The design of the truss upport structure including headers, beams, walls, d columns is the responsibility of the building signer. For general guidance regarding bracing, build ECSLP1 and ECSLP2 provided with tho									

Indicates Left End of Truss
(Reference Engineered Truss Drawing)
Do NOT Erect Truss Backwards