

RE: J0425-1935
Lot 21 Turlington Acres

Trenco
818 Soundside Rd
Edenton, NC 27932

Site Information:

Customer: Project Name: J0425-1935
Lot/Block: Model:
Address: Subdivision:
City: State:

General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):

Design Code: IRC2021/TPI2014 Design Program: MiTek 20/20 8.6
Wind Code: ASCE 7-16 Wind Speed: 130 mph
Roof Load: 40.0 psf Floor Load: N/A psf

This package includes 16 individual, dated Truss Design Drawings and 0 Additional Drawings.

No.	Seal#	Truss Name	Date
1	I72199004	A01	3/24/2025
2	I72199005	A02	3/24/2025
3	I72199006	A03	3/24/2025
4	I72199007	A04	3/24/2025
5	I72199008	A05	3/24/2025
6	I72199009	A06	3/24/2025
7	I72199010	A07	3/24/2025
8	I72199011	A08	3/24/2025
9	I72199012	B01	3/24/2025
10	I72199013	B02	3/24/2025
11	I72199014	M01	3/24/2025
12	I72199015	M02	3/24/2025
13	I72199016	M03	3/24/2025
14	I72199017	M04	3/24/2025
15	I72199018	V01	3/24/2025
16	I72199019	V02	3/24/2025


The truss drawing(s) referenced above have been prepared by
Truss Engineering Co. under my direct supervision
based on the parameters provided by Comtech, Inc - Fayetteville.

Truss Design Engineer's Name: Gilbert, Eric

My license renewal date for the state of North Carolina is December 31, 2025.

North Carolina COA: C-0844

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to TRENCO. Any project specific information included is for TRENCO customers file reference purpose only, and was not taken into account in the preparation of these designs. TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.




Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	I72199004
J0425-1935	A01	Common Supported Gable	1	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:54

Page: 1

ID:xCjF5sS_An5AZx8iaaJP_qzvAPL-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?f



Scale = 1:75.9

Plate Offsets (X, Y): [8:0-0-0,0-0-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.05	Vert(LL)	n/a	-	n/a	999	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	n/a	-	n/a	999	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.12	Horz(CT)	0.00	24	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS							
Weight: 348 lb FT = 25%											

LUMBER
TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
OTHERS 2x4 SP No.2 *Except* 0-0,0-0,0-0:2x4 SPF No.2(flat)


BRACING
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Structural wood sheathing directly applied.
T-Brace: 2x4 SPF No.2 - 13-35, 12-36, 14-34
Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
Brace must cover 90% of web length.

REACTIONS (size)
2=43-0-0, 24=43-0-0, 25=43-0-0, 26=43-0-0, 27=43-0-0, 28=43-0-0, 29=43-0-0, 31=43-0-0, 32=43-0-0, 33=43-0-0, 34=43-0-0, 35=43-0-0, 36=43-0-0, 37=43-0-0, 39=43-0-0, 40=43-0-0, 41=43-0-0, 42=43-0-0, 43=43-0-0, 44=43-0-0, 45=43-0-0, 46=43-0-0, 49=43-0-0
Max Horiz 2=115 (LC 12), 46=115 (LC 12)
Max Uplift 2=-2 (LC 13), 25=-63 (LC 13), 26=-16 (LC 13), 27=-31 (LC 13), 28=-28 (LC 13), 29=-29 (LC 13), 31=-28 (LC 13), 32=-29 (LC 13), 33=-35 (LC 13), 34=-6 (LC 13), 36=-12 (LC 12), 37=-34 (LC 12), 39=-29 (LC 12), 40=-28 (LC 12), 41=-29 (LC 12), 42=-28 (LC 12), 43=-31 (LC 12), 44=-14 (LC 12), 45=-67 (LC 12), 46=-2 (LC 13)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/16, 2-3=-141/55, 3-4=-104/53, 4-5=-87/65, 5-6=-75/84, 6-7=-62/119, 7-9=-69/166, 9-10=-86/212, 10-11=-102/259, 11-12=-120/309, 12-13=-131/341, 13-14=-131/341, 14-15=-120/309, 15-16=-102/259, 16-17=-86/212, 17-19=-69/166, 19-20=-53/119, 20-21=-49/72, 21-22=-53/25, 22-23=-70/8, 23-24=-120/41
BOT CHORD 2-45=-37/162, 44-45=-37/162, 43-44=-37/162, 42-43=-37/162, 41-42=-37/162, 40-41=-37/162, 39-40=-37/162, 37-39=-37/162, 36-37=-37/162, 35-36=-37/162, 34-35=-37/162, 33-34=-37/162, 32-33=-37/162, 31-32=-37/162, 29-31=-37/162, 28-29=-37/162, 27-28=-37/162, 26-27=-37/162, 25-26=-37/162, 24-25=-37/162

WEBS
13-35=-129/12, 12-36=-120/58, 11-37=-122/109, 10-39=-120/98, 9-40=-120/97, 7-41=-120/97, 6-42=-120/97, 5-43=-123/101, 4-44=-100/82, 3-45=-183/199, 14-34=-120/58, 15-33=-122/109, 16-32=-120/98, 17-31=-120/97, 19-29=-120/97, 20-28=-120/97, 21-27=-123/100, 22-26=-99/81, 23-25=-187/221

NOTES
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Corner(3E) 0-0-8-7 to 3-6-0, Exterior(2N) 3-6-0 to 21-6-0, Corner(3R) 21-6-0 to 25-10-13, Exterior(2N) 25-10-13 to 43-0-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60



March 24, 2025

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompoments.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres
J0425-1935	A01	Common Supported Gable	1	1	I72199004
					Job Reference (optional)

- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) All plates are 2x4 MT20 unless otherwise indicated.
- 5) Gable requires continuous bottom chord bearing.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 2 lb uplift at joint 2, 12 lb uplift at joint 36, 34 lb uplift at joint 37, 29 lb uplift at joint 39, 28 lb uplift at joint 40, 29 lb uplift at joint 41, 28 lb uplift at joint 42, 31 lb uplift at joint 43, 14 lb uplift at joint 44, 67 lb uplift at joint 45, 6 lb uplift at joint 34, 35 lb uplift at joint 33, 29 lb uplift at joint 32, 28 lb uplift at joint 31, 29 lb uplift at joint 29, 28 lb uplift at joint 28, 31 lb uplift at joint 27, 16 lb uplift at joint 26, 63 lb uplift at joint 25 and 2 lb uplift at joint 2.
- 11) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 12) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	172199005
J0425-1935	A02	Common	5	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:55
ID: iB7t_85o5bhCGEe6_9FfiXzvAxN-RfC?PsB70Hq3NSgPqnL8w3uTXbGKWrCDoi7J4zJC?i

Page: 1




Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.39	Vert(LL)	-0.26	10-17	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.89	Vert(CT)	-0.50	10-14	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.42	Horz(CT)	0.10	8	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.10	14-20	>999	240	Weight: 281 lb	FT = 25%

LUMBER	
TOP CHORD	2x6 SP No.1
BOT CHORD	2x6 SP No.1
WEBS	2x4 SP No.2
BRACING	
TOP CHORD	Structural wood sheathing directly applied.
BOT CHORD	Structural wood sheathing directly applied.
REACTIONS	(size) 2=0-3-8, 8=0-3-8
	Max Horiz 2=115 (LC 12)
	Max Uplift 2=-18 (LC 12), 8=-9 (LC 13)
	Max Grav 2=2052 (LC 2), 8=2016 (LC 2)
FORCES	
	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=0/16, 2-3=-4012/452, 3-5=-3661/406, 5-7=-3662/412, 7-8=-4013/459
BOT CHORD	2-14=-323/3625, 10-14=-102/2440, 8-10=-309/3626
WEBS	5-14=0/1416, 3-14=-670/353, 7-10=-671/353, 5-10=0/1418

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -0-8-7 to 3-8-6, Interior (1) 3-8-6 to 21-6-0, Exterior(2R) 21-6-0 to 25-10-13, Interior (1) 25-10-13 to 43-0-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 200.0lb AC unit load placed on the bottom chord, 21-6-0 from left end, supported at two points, 5-0-0 apart.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
 - One RT3A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 8 and 2. This connection is for uplift only and does not consider lateral forces.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- LOAD CASE(S)** Standard



March 24, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompoments.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	172199006
J0425-1935	A03	Common	1	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:55

Page: 1

ID: iB7t_85o5bhCGEe6_9FFiXzvAxN-RfC?PsB70Hq3NSgPqnL8w3uTXbGKwRCDoi7J4zJC?i



Scale = 1:75.9

Plate Offsets (X, Y): [6:0-0-0,0-0-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.42	Vert(LL)	-0.36	10-19	>678	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.82	Vert(CT)	-0.68	10-19	>354	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.42	Horz(CT)	0.08	8	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.13	10-19	>999	240	Weight: 262 lb	FT = 25%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Structural wood sheathing directly applied.

REACTIONS

(size) 2=0-3-8, 8=0-3-8, 11=0-3-8
Max Horiz 2=115 (LC 12)
Max Uplift 2=-126 (LC 12), 8=-119 (LC 13)
Max Grav 2=1804 (LC 2), 8=1745 (LC 2),
11=344 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/16, 2-3=-3307/685, 3-5=-2994/660,
5-7=-2926/665, 7-8=-3241/691
BOT CHORD 2-13=-531/2998, 11-13=-257/1986,
10-11=-257/1986, 8-10=-515/2938
WEBS 3-13=-687/339, 5-13=-128/1177,
5-10=-125/1081, 7-10=-691/340

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) -0-8-7 to 3-8-6, Interior (1) 3-8-6 to 21-6-0,
Exterior(2R) 21-6-0 to 25-10-13, Interior (1) 25-10-13 to
43-0-0 zone; C-C for members and forces & MWFRS for
reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60
- This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members, with BCDL = 10.0psf.

- All bearings are assumed to be SP No.1 crushing
capacity of 565 psi.
- One RT3A MiTek connectors recommended to connect
truss to bearing walls due to UPLIFT at jt(s) 2, 8, and 11.
This connection is for uplift only and does not consider
lateral forces.
- This truss design requires that a minimum of 7/16"
structural wood sheathing be applied directly to the top
chord and 1/2" gypsum sheetrock be applied directly to
the bottom chord.

LOAD CASE(S) Standard



March 24, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	172199007
J0425-1935	A04	Roof Special	2	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:55
ID:tB31L5BtxkTGwK094INGJzvAqo-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:78.4

Plate Offsets (X, Y): [3:0-0-3,0-0-4], [16:0-4-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.58	Vert(LL)	-0.21	3-18	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.44	Vert(CT)	-0.42	3-18	>664	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.91	Horz(CT)	0.10	13	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.20	3-18	>999	240	Weight: 278 lb	FT = 25%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1 *Except* 19-3:2x4 SP No.2
WEBS 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Structural wood sheathing directly applied.
WEBS 1 Row at midpt 6-13, 4-15, 8-13

REACTIONS (size) 2=0-3-8, 9=0-3-8, 13=0-3-8
Max Horiz 2=-111 (LC 13)
Max Uplift 2=-60 (LC 12), 9=-158 (LC 13),
13=-126 (LC 12)
Max Grav 2=531 (LC 25), 9=549 (LC 26),
13=2683 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/16, 2-3=-288/125, 3-4=-352/194,
4-6=-48/1169, 6-8=-57/1423, 8-9=-492/680,
9-10=0/16

BOT CHORD 2-19=-81/171, 3-19=-48/235, 3-18=-75/287,
16-18=-74/286, 15-16=-238/1075,
14-16=-168/0, 13-14=-813/188,
11-13=-578/392, 9-11=-578/392


WEBS 6-15=-1485/290, 13-15=-1990/420,
4-15=-1324/321, 4-18=0/417,
8-13=-1243/347, 8-11=0/455

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) -0-8-7 to 3-8-6, Interior (1) 3-8-6 to 21-6-0,
Exterior(2R) 21-6-0 to 25-10-13, Interior (1) 25-10-13 to
43-8-7 zone; C-C for members and forces & MWFRS for
reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- One RT3A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 13, and 9. This connection is for uplift only and does not consider lateral forces.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



March 24, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompoments.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	172199008
J0425-1935	A05	Roof Special	4	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:55
ID:tsNQ4MhvhduUL5LB39sFrzvAP2-RfC?PsB70Hq3NSgPqnL8w3uITxbGKwRCdoi7J4zJC?f

Page: 1



Scale = 1:78.4

Plate Offsets (X, Y): [3:0-0-3,0-0-4], [15:0-4-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.58	Vert(LL)	-0.21	3-17	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.44	Vert(CT)	-0.42	3-17	>663	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.91	Horz(CT)	0.10	12	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.20	3-17	>999	240	Weight: 276 lb	FT = 25%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1 *Except* 18-3:2x4 SP No.2
WEBS 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Structural wood sheathing directly applied.
WEBS 1 Row at midpt 6-12, 4-14, 8-12

REACTIONS

(size) 2=0-3-8, 9=0-3-8, 12=0-3-8
Max Horiz 2=115 (LC 16)
Max Uplift 2=-58 (LC 12), 9=-145 (LC 13),
12=-129 (LC 12)
Max Grav 2=531 (LC 25), 9=506 (LC 26),
12=2683 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=0/16, 2-3=-288/117, 3-4=-352/180,
4-6=-51/1169, 6-8=-64/1422, 8-9=-494/679
BOT CHORD 2-18=-83/171, 3-18=-49/235, 3-17=-76/287,
15-17=-76/287, 14-15=-241/1075,
13-15=-168/0, 12-13=-813/186,
10-12=-577/395, 9-10=-577/395
WEBS 4-17=0/417, 6-14=-1484/296,
12-14=-1990/433, 8-10=0/456,
4-14=-1324/324, 8-12=-1246/348

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) -0-8-7 to 3-8-6, Interior (1) 3-8-6 to 21-6-0,
Exterior(2R) 21-6-0 to 25-10-13, Interior (1) 25-10-13 to
43-0-0 zone;C-C for members and forces & MWFRS for
reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60
- This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.

- * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- All bearings are assumed to be SP No.1 crushing
capacity of 565 psi.
- One RT3A MiTek connectors recommended to connect
truss to bearing walls due to UPLIFT at jt(s) 2, 12, and 9.
This connection is for uplift only and does not consider
lateral forces.
- This truss design requires that a minimum of 7/16"
structural wood sheathing be applied directly to the top
chord and 1/2" gypsum sheetrock be applied directly to
the bottom chord.

LOAD CASE(S) Standard



March 24, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	172199009
J0425-1935	A06	Common	1	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:55
ID:pHcUBcWkoMW0EiisJ5dEySzvAWU-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:75.9

Plate Offsets (X, Y): [6:0-0-0,0-0-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.41	Vert(LL)	-0.33	10-19	>720	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.80	Vert(CT)	-0.65	10-19	>372	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.43	Horz(CT)	0.08	8	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.12	10-19	>999	240	Weight: 262 lb	FT = 25%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Structural wood sheathing directly applied.

REACTIONS

(size) 2=0-3-8, 8=0-3-8, 11=0-3-8
Max Horiz 2=115 (LC 12)
Max Uplift 2=-128 (LC 12), 8=-121 (LC 13)
Max Grav 2=1788 (LC 2), 8=1727 (LC 2),
11=365 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/16, 2-3=-3300/699, 3-5=-2958/655,
5-7=-2885/661, 7-8=-3229/705
BOT CHORD 2-13=-549/2995, 11-13=-263/1961,
10-11=-263/1961, 8-10=-533/2932
WEBS 5-13=-114/1146, 7-10=-701/343,
5-10=-112/1044, 3-13=-696/342

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) -0-8-7 to 3-8-6, Interior (1) 3-8-6 to 21-6-0,
Exterior(2R) 21-6-0 to 25-10-13, Interior (1) 25-10-13 to
43-0-0 zone; C-C for members and forces & MWFRS for
reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members, with BCDL = 10.0psf.

- 5) All bearings are assumed to be SP No.1 crushing
capacity of 565 psi.
- 6) One RT3A MiTek connectors recommended to connect
truss to bearing walls due to UPLIFT at jt(s) 2, 8, and 11.
This connection is for uplift only and does not consider
lateral forces.
- 7) This truss design requires that a minimum of 7/16"
structural wood sheathing be applied directly to the top
chord and 1/2" gypsum sheetrock be applied directly to
the bottom chord.

LOAD CASE(S) Standard



March 24, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	172199010
J0425-1935	A07	Common	6	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:55
ID:LRhEpKx0?A55Jc70Ek7xMAzvAVA-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:77.1

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.41	Vert(LL)	-0.15	13-16	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.50	Vert(CT)	-0.31	13-16	>879	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.74	Horz(CT)	0.02	2	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.08	13-16	>999	240	Weight: 270 lb	FT = 25%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Structural wood sheathing directly applied.
WEBS 1 Row at midpt 5-11, 7-11

REACTIONS

(size) 2=0-3-8, 8= Mechanical, 11=0-3-8
Max Horiz 2=117 (LC 12)
Max Uplift 2=-88 (LC 12), 8=-85 (LC 13),
11=-65 (LC 12)
Max Grav 2=927 (LC 27), 8=711 (LC 28),
11=2199 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=0/16, 2-3=-1257/279, 3-5=-1105/343,
5-7=0/452, 7-8=-922/213
BOT CHORD 2-13=-166/1111, 11-13=-146/147,
9-11=-83/756, 8-9=-139/756
WEBS 5-13=-260/1456, 3-13=-681/343,
5-11=-1300/327, 7-11=-1161/314, 7-9=0/417

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) 0-8-7 to 3-8-6, Interior (1) 3-8-6 to 21-6-0,
Exterior(2R) 21-6-0 to 25-10-13, Interior (1) 25-10-13 to
42-8-8 zone; C-C for members and forces & MWFRS for
reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members, with BCDL = 10.0psf.

- 5) Bearings are assumed to be: Joint 2 SP No.1 crushing
capacity of 565 psi, Joint 11 SP No.1 crushing capacity
of 565 psi.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 85 lb uplift at joint
8.
- 8) One RT3A MiTek connectors recommended to connect
truss to bearing walls due to UPLIFT at jt(s) 2 and 11.
This connection is for uplift only and does not consider
lateral forces.
- 9) This truss design requires that a minimum of 7/16"
structural wood sheathing be applied directly to the top
chord and 1/2" gypsum sheetrock be applied directly to
the bottom chord.

LOAD CASE(S) Standard



March 24, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	I72199011
J0425-1935	A08	Common Supported Gable	1	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:55
ID:jD3PZT8pN991DPmVW73d_zvAUI-RfC?PsB70Hq3NSgPqnL8w3uiTXbGKwRCDoi7J4zJC?f

Page: 1



Scale = 1:77.1

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.05	Vert(LL)	n/a	-	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	n/a	-	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.12	Horz(CT)	0.00	24	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS							
Weight: 347 lb FT = 25%											

LUMBER
TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
OTHERS 2x4 SP No.2 *Except* 0-0,0-0,0-0:2x4 SPF No.2(flat)

BRACING
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Structural wood sheathing directly applied.
WEBS T-Brace: 2x4 SPF No.2 - 13-35, 12-36, 14-34
Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
Brace must cover 90% of web length.


REACTIONS (size)
2=42-8-8, 24=42-8-8, 25=42-8-8, 26=42-8-8, 27=42-8-8, 28=42-8-8, 29=42-8-8, 31=42-8-8, 32=42-8-8, 33=42-8-8, 34=42-8-8, 35=42-8-8, 36=42-8-8, 37=42-8-8, 39=42-8-8, 40=42-8-8, 41=42-8-8, 42=42-8-8, 43=42-8-8, 44=42-8-8, 45=42-8-8, 46=42-8-8, 49=42-8-8
Max Horiz 2=117 (LC 12), 46=117 (LC 12)
Max Uplift 2=-2 (LC 13), 25=-67 (LC 13), 26=-15 (LC 13), 27=-31 (LC 13), 28=-28 (LC 13), 29=-29 (LC 13), 31=-28 (LC 13), 32=-29 (LC 13), 33=-35 (LC 13), 34=-6 (LC 13), 36=-12 (LC 12), 37=-34 (LC 12), 39=-29 (LC 12), 40=-28 (LC 12), 41=-29 (LC 12), 42=-28 (LC 12), 43=-31 (LC 12), 44=-14 (LC 12), 45=-67 (LC 12), 46=-2 (LC 13)

Max Grav 2=176 (LC 1), 24=120 (LC 1), 25=256 (LC 26), 26=128 (LC 1), 27=167 (LC 26), 28=159 (LC 1), 29=160 (LC 26), 31=160 (LC 1), 32=160 (LC 1), 33=162 (LC 26), 34=160 (LC 26), 35=150 (LC 22), 36=160 (LC 25), 37=162 (LC 25), 39=160 (LC 1), 40=160 (LC 1), 41=160 (LC 25), 42=158 (LC 1), 43=168 (LC 25), 44=120 (LC 1), 45=271 (LC 25), 46=176 (LC 1), 49=120 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/16, 2-3=-141/55, 3-4=-106/53, 4-5=-89/66, 5-6=-76/84, 6-7=-63/121, 7-9=-70/167, 9-10=-87/214, 10-11=-103/261, 11-12=-121/311, 12-13=-132/343, 13-14=-132/343, 14-15=-121/311, 15-16=-103/261, 16-17=-87/214, 17-19=-70/167, 19-20=-54/121, 20-21=-51/74, 21-22=-54/26, 22-23=-70/7, 23-24=-122/39
BOT CHORD 2-45=-36/154, 44-45=-34/154, 43-44=-34/154, 42-43=-34/154, 41-42=-34/154, 40-41=-34/154, 39-40=-34/154, 37-39=-34/154, 36-37=-34/154, 35-36=-34/154, 34-35=-34/154, 33-34=-34/154, 32-33=-34/154, 31-32=-34/154, 29-31=-34/154, 28-29=-34/154, 27-28=-34/154, 26-27=-34/154, 25-26=-34/154, 24-25=-34/154

WEBS 13-35=-130/12, 12-36=-120/58, 11-37=-122/109, 10-39=-120/98, 9-40=-120/97, 7-41=-120/97, 6-42=-120/97, 5-43=-123/101, 4-44=-100/82, 3-45=-183/199, 14-34=-120/58, 15-33=-122/109, 16-32=-120/98, 17-31=-120/97, 19-29=-120/97, 20-28=-120/97, 21-27=-122/100, 22-26=-103/83, 23-25=-176/223

NOTES
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Corner(3E) 0-8-7 to 3-6-0, Exterior(2N) 3-6-0 to 21-6-0, Corner(3R) 21-6-0 to 25-10-13, Exterior(2N) 25-10-13 to 42-8-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.



March 24, 2025

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompoments.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres
J0425-1935	A08	Common Supported Gable	1	1	I72199011
					Job Reference (optional)

- 4) All plates are 2x4 MT20 unless otherwise indicated.
- 5) Gable requires continuous bottom chord bearing.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 2 lb uplift at joint 2, 12 lb uplift at joint 36, 34 lb uplift at joint 37, 29 lb uplift at joint 39, 28 lb uplift at joint 40, 29 lb uplift at joint 41, 28 lb uplift at joint 42, 31 lb uplift at joint 43, 14 lb uplift at joint 44, 67 lb uplift at joint 45, 6 lb uplift at joint 34, 35 lb uplift at joint 33, 29 lb uplift at joint 32, 28 lb uplift at joint 31, 29 lb uplift at joint 29, 28 lb uplift at joint 28, 31 lb uplift at joint 27, 15 lb uplift at joint 26, 67 lb uplift at joint 25 and 2 lb uplift at joint 2.
- 11) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 12) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

LOAD CASE(S) Standard

⚠ WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)



818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	172199012
J0425-1935	B01	Common Supported Gable	1	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:56

Page: 1

ID:wL1gjtqczubHZHm5lUXntzvAlg-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKwRCDoi7J4zJC?f



Scale = 1:39.7

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.03	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.03	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.00	8	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS						Weight: 87 lb	FT = 25%

LUMBER

TOP CHORD	2x6 SP No.1
BOT CHORD	2x6 SP No.1
OTHERS	2x4 SP No.2
WEDGE	Left: 2x4 SP No.2 Right: 2x4 SP No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied.
BOT CHORD	Structural wood sheathing directly applied.

REACTIONS (size)	2=12-0-0, 8=12-0-0, 10=12-0-0, 11=12-0-0, 12=12-0-0, 13=12-0-0, 14=12-0-0, 15=12-0-0, 19=12-0-0
Max Horiz	2=108 (LC 11), 15=108 (LC 11)
Max Uplift	2=-20 (LC 8), 10=-72 (LC 13), 11=-34 (LC 13), 13=-34 (LC 12), 14=-76 (LC 12), 15=-20 (LC 8)
Max Grav	2=144 (LC 20), 8=143 (LC 1), 10=186 (LC 20), 11=169 (LC 20), 12=121 (LC 1), 13=170 (LC 19), 14=192 (LC 19), 15=144 (LC 20), 19=143 (LC 1)

FORCES

	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=0/24, 2-3=-93/66, 3-4=-90/94, 4-5=-106/182, 5-6=-106/183, 6-7=-68/88, 7-8=-69/35, 8-9=0/24
BOT CHORD	2-14=-70/133, 13-14=-32/133, 12-13=-32/133, 11-12=-32/133, 10-11=-32/133, 8-10=-32/133
WEBS	5-12=-80/0, 4-13=-135/149, 3-14=-135/203, 6-11=-133/147, 7-10=-136/202

NOTES

- Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C
Corner(3E) -0-8-12 to 3-8-1, Exterior(2N) 3-8-1 to 6-0-0,
Corner(3R) 6-0-0 to 10-4-13, Exterior(2N) 10-4-13 to
12-8-12 zone; C-C for members and forces & MWFRS
for reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60
- Truss designed for wind loads in the plane of the truss
only. For studs exposed to wind (normal to the face),
see Standard Industry Gable End Details as applicable,
or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- All bearings are assumed to be SP No.1 crushing
capacity of 565 psi.
- Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 20 lb uplift at joint
2, 34 lb uplift at joint 13, 76 lb uplift at joint 14, 34 lb
uplift at joint 11, 72 lb uplift at joint 10 and 20 lb uplift at
joint 2.
- This truss design requires that a minimum of 7/16"
structural wood sheathing be applied directly to the top
chord and 1/2" gypsum sheetrock be applied directly to
the bottom chord.

LOAD CASE(S) Standard



March 24, 2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Comtech, Inc, Fayetteville, NC - 28314, Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:56 Page: 1
ID:qTJoJifeK6zTEbtpxaPuezvAHH-RfC?PsB70Hg3NSgPqnL8w3ulTXbGKwRCdoi7J4zJC?f




LUMBER		5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
TOP CHORD	2x6 SP No.1	
BOT CHORD	2x8 SP No.1	6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
WEBS	2x4 SP No.2	
BRACING		7) All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.	8) One RT3A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 3. This connection is for uplift only and does not consider lateral forces.
BOT CHORD	Structural wood sheathing directly applied or 10-0-0 oc bracing.	9) Use MiTek JUS24 (With 4-10d nails into Girder & 2-10d nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 1-0-12 from the left end to 11-0-12 to connect truss(es) to back face of bottom chord.
REACTIONS		10) Fill all nail holes where hanger is in contact with lumber.
	(size) 1=0-3-8, 3=0-3-8	
	Max Horiz 1=-96 (LC 4)	LOAD CASE(S) Standard
	Max Uplift 1=-313 (LC 8), 3=-318 (LC 9)	1) Dead + Roof Live (balanced): Lumber Increase=1.15
	Max Grav 1=2471 (LC 2), 3=2515 (LC 2)	
FORCES		
	(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-2483/347, 2-3=-2464/347	
BOT CHORD	1-4=-232/2003, 3-4=-232/2003	
WEBS	2-4=-265/2356	

- NOTES**

 - 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x8 - 2 rows staggered at 0-9-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60

Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-60, 2-3=-60, 5-8=-20
Concentrated Loads (lb)
Vert: 11=-668 (B), 12=-668 (B), 13=-668 (B), 14=-668 (B), 15=-668 (B), 16=-668 (B)





March 24, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpin.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbccomponents.com)




818 Soundside Road
Bakersfield, CA 93309

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	I72199014
J0425-1935	M01	Monopitch Supported Gable	1	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:56
ID:pgMaLi7Xssps16ifOhm6Yizv9mS-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:23

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.25	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.25	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS							Weight: 18 lb	FT = 25%

LUMBER

TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
WEBS 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals.

BOT CHORD Structural wood sheathing directly applied.

REACTIONS (size) 2=5-0-0, 4=5-0-0, 5=5-0-0
Max Horiz 2=50 (LC 8), 5=50 (LC 8)
Max Uplift 2=-50 (LC 8), 4=-23 (LC 12), 5=-50 (LC 8)
Max Grav 2=251 (LC 1), 4=192 (LC 1), 5=251 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=0/13, 2-3=-133/86, 3-4=-125/215
BOT CHORD 2-4=-153/144

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Corner(3E) -0-10-8 to 3-6-5, Exterior(2N) 3-6-5 to 4-10-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 2-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

- 7) All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 50 lb uplift at joint 2, 23 lb uplift at joint 4 and 50 lb uplift at joint 2.
- 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



March 24, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	
J0425-1935	M02	Monopitch	13	1		I72199015
Job Reference (optional)						

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:56
ID:8ATQ2HsdTMuq3a4DbdXycwzvB60-RfC?PsB70Hq3NSgPqnL8w3uiTXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:28.4

Plate Offsets (X, Y): [2:0-2-8,Edge], [4:Edge,0-2-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.28	Vert(LL)	-0.02	4-7	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.29	Vert(CT)	-0.05	4-7	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.08	4-7	>690	240	Weight: 18 lb	FT = 25%

LUMBER

TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
WEBS 2x4 SP No.1

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Structural wood sheathing directly applied.

REACTIONS (size) 2=0-3-8, 4=0-1-8

Max Horiz 2=50 (LC 8)
Max Uplift 2=-104 (LC 8), 4=-77 (LC 8)
Max Grav 2=251 (LC 1), 4=189 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=0/13, 2-3=-129/234, 3-4=-125/185
BOT CHORD 2-4=-260/114

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) -0-10-8 to 3-6-5, Interior (1) 3-6-5 to 4-10-4
zone; porch left and right exposed; C-C for members and
forces & MWFRS for reactions shown; Lumber
DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SP No.1 crushing
capacity of 565 psi.
- 5) Bearing at joint(s) 4 considers parallel to grain value
using ANSI/TPI 1 angle to grain formula. Building
designer should verify capacity of bearing surface.
- 6) Provide mechanical connection (by others) of truss to
bearing plate at joint(s) 4.

- 7) One RT3A MiTek connectors recommended to connect
truss to bearing walls due to UPLIFT at jt(s) 2 and 4.
This connection is for uplift only and does not consider
lateral forces.
- 8) This truss design requires that a minimum of 7/16"
structural wood sheathing be applied directly to the top
chord and 1/2" gypsum sheetrock be applied directly to
the bottom chord.

LOAD CASE(S) Standard



March 24, 2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Comtech, Inc, Fayetteville, NC - 28314, Run: 8.630 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:56 Page: 1
ID:zQxOaal215DKxxkRxAsJcXzvB4s-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWRcd0J7J4zJC?i



LUMBER		7) Load case(s) 1 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
TOP CHORD	2x4 SP No.1	
BOT CHORD	2x6 SP No.1	
WEBS	2x4 SP No.2	
BRACING		8) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
TOP CHORD	Structural wood sheathing directly applied.	
BOT CHORD	Structural wood sheathing directly applied.	
REACTIONS	(size) 2=0-5-8, 4= Mechanical	9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 55 lb down and 50 lb up at 4-1-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
	Max Horiz 2=44 (LC 8)	
	Max Uplift 2=-6 (LC 8)	
	Max Grav 2=355 (LC 1), 4=595 (LC 1)	
FORCES	(lb) - Maximum Compression/Maximum Tension	10) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
TOP CHORD	1-2=0/13, 2-3=-99/40	LOAD CASE(S) Standard
BOT CHORD	2-5=-22/19, 4-5=0/0	1) Dead + Roof Live (balanced): Lumber Increase=1.15,
WEBS	3-5=-113/110	Plate Increase=1.15

- ## NOTES
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) -0-10-8 to 3-6-5, Interior (1) 3-6-5 to 4-1-12
zone; C-C for members and forces & MWFRS for
reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60
 - 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
 - 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
 - 4) Bearings are assumed to be: Joint 2 SP No.1 crushing
capacity of 565 psi.
 - 5) Refer to girder(s) for truss to truss connections.
 - 6) One RT3A MiTek connectors recommended to connect
truss to bearing walls due to UPLIFT at jt(s) 2. This
connection is for uplift only and does not consider lateral
forces.

- 7) Load case(s) 1 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- 8) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 55 lb down and 50 lb up at 4-1-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 10) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15,
Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-3=-60, 2-4=-20
Concentrated Loads (lb)
Vert: 5=-550 (F=-55)



March 24, 2025



Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcacomponents.com)




818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	
J0425-1935	M04	Monopitch	1	1	Job Reference (optional)	I72199017

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:56
ID:1_iLULWdxLB0257wp8OxuvzvAzQ-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?i

Page: 1



Scale = 1:24.9

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.13	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.15	Vert(CT)	n/a	-	n/a	999	244/190
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS							Weight: 18 lb FT = 25%

LUMBER

TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
WEBS 2x4 SP No.2

- 7) All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
8) N/A

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Structural wood sheathing directly applied.

REACTIONS (size) 2=5-0-0, 4=5-0-0, 5=5-0-0, 6=5-0-0
Max Horiz 2=42 (LC 8), 6=42 (LC 8)
Max Uplift 2=-49 (LC 8), 4=-48 (LC 1), 5=-11 (LC 12), 6=-49 (LC 8)
Max Grav 2=204 (LC 1), 4=6 (LC 12), 5=228 (LC 1), 6=204 (LC 1)

- 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.


LOAD CASE(S) Standard

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/13, 2-3=-92/51, 3-5=-88/153
BOT CHORD 2-5=-102/102, 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Corner(3E) -0-10-8 to 3-6-5, Exterior(2N) 3-6-5 to 3-10-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 2-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.



March 24, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres
J0425-1935	V01	Valley	1	1	172199018
Job Reference (optional)					

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:56
ID:Fw34KJ8q920Bu34wLuS44KzZL3t-RfC?PsB70Hq3NSgPqnl8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.07	Horz(CT)	0.00	12	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS							Weight: 62 lb	FT = 25%

LUMBER

TOP CHORD	2x4 SP No.1
BOT CHORD	2x4 SP No.1
WEBS	2x4 SP No.2
OTHERS	2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals.

BOT CHORD Structural wood sheathing directly applied.

REACTIONS	(size)	1=10-3-4, 8=10-3-4, 9=10-3-4, 10=10-3-4, 11=10-3-4, 12=10-3-4
	Max Horiz	1=235 (LC 12)
	Max Uplift	1=-5 (LC 10), 8=-72 (LC 9), 9=-37 (LC 12), 10=-47 (LC 12), 11=-50 (LC 12), 12=-32 (LC 12)
	Max Grav	1=120 (LC 12), 8=153 (LC 19), 9=157 (LC 19), 10=176 (LC 19), 11=163 (LC 19), 12=202 (LC 19)

FORCES


	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=-576/263, 2-3=-474/212, 3-4=-367/161, 4-5=-254/107, 5-6=-154/63, 6-7=-38/0, 6-8=-138/239
BOT CHORD	1-12=-143/99, 11-12=-1/2, 10-11=-1/2, 9-10=-1/2, 8-9=-1/2
WEBS	5-9=-144/177, 4-10=-137/180, 3-11=-133/190, 2-12=-138/184

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Corner(3E) 0-0-9 to 4-3-13, Exterior(2N) 4-3-13 to 11-3-13 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) All plates are 2x4 MT20 unless otherwise indicated.

- 4) Gable requires continuous bottom chord bearing.
- 5) Gable studs spaced at 2-0-0 oc.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 5 lb uplift at joint 1, 72 lb uplift at joint 8, 37 lb uplift at joint 9, 47 lb uplift at joint 10, 50 lb uplift at joint 11 and 32 lb uplift at joint 12.
- 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



March 24, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 21 Turlington Acres	
J0425-1935	V02	Valley	1	1	Job Reference (optional)	I72199019

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Fri Mar 21 08:07:56
ID:75MORW_i?h7ZLwQUD_?1sizvAGv-RfC?PsB70Hq3NSgPqnL8w3uITXbGKwRCDoi7J4zJC?f

Page: 1



Scale = 1:34.2

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.04	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.03	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	0.00	7	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS						Weight: 55 lb	FT = 25%

LUMBER

TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Structural wood sheathing directly applied.

REACTIONS (size) 1=12-7-9, 7=12-7-9, 8=12-7-9,
9=12-7-9, 10=12-7-9, 11=12-7-9,
12=12-7-9
Max Horiz 1=97 (LC 9)
Max Uplift 1=-7 (LC 8), 8=-44 (LC 13), 9=-48
(LC 13), 11=-48 (LC 12), 12=-46
(LC 12)
Max Grav 1=82 (LC 20), 7=73 (LC 26), 8=204
(LC 20), 9=169 (LC 20), 10=166
(LC 1), 11=169 (LC 19), 12=206
(LC 19)

FORCES (lb) - Maximum Compression/Maximum
Tension


TOP CHORD 1-2=-105/90, 2-3=-58/69, 3-4=-66/113,
4-5=-66/111, 5-6=-30/43, 6-7=-80/62
BOT CHORD 1-12=-55/92, 11-12=-55/79, 10-11=-55/79,
9-10=-55/79, 8-9=-55/79, 7-8=-55/79
WEBS 4-10=-122/0, 3-11=-136/124, 2-12=-138/112,
5-9=-136/124, 6-8=-138/112

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) 0-0-0 to 4-3-13, Interior (1) 4-3-13 to
6-3-13, Exterior(2R) 6-3-13 to 10-8-9, Interior (1) 10-8-9
to 12-7-9 zone;C-C for members and forces & MWFRS
for reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60

- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) All plates are 2x4 MT20 unless otherwise indicated.
- 5) Gable requires continuous bottom chord bearing.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 7 lb uplift at joint 1, 48 lb uplift at joint 11, 46 lb uplift at joint 12, 48 lb uplift at joint 9 and 44 lb uplift at joint 8.
- 11) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



March 24, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.




Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Symbols

PLATE LOCATION AND ORIENTATION




* Plate location details available in MITek software or upon request.

PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.

Industry Standards:

ANSI/TP1.1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-22: Design Standard for Bracing.
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

Numbering System



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

Product Code Approvals

ICC-ES Reports:

ESR-1988, ESR-2362, ESR-2685, ESR-3282
ESR-4722, ESL-1388

Design General Notes

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 1 section 6.3. These truss designs rely on lumber values established by others.

© 2023 MITek® All Rights Reserved

General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.

MITek®

ENGINEERING BY
TRENCO
A MITek Affiliate

MITek Engineering Reference Sheet: MII-7473 rev. 1/2/2023