



Truss Placement Plan SCALE: 1/4"=1'

3400 1

6800 2

10200 3

13600 4

17000 5

LOAD CHART FOR JACK STUDS

(BASED ON TABLES R502.5(1) & (b))
NUMBER OF JACK STUDS REQUIRED @ EA END OF
HEADER/GIRDER

5100 2

7650 3

10200 4

12750 5

15300 6

1700 1 3400 2

5100 3

6800 4 8500 5

10200 6

11900 7 13600 8 15300 9

___ = Indicates Left End of Truss (Reference Engineered Truss Drawing) Do NOT Erect Truss Backwards

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY.

BUILDER	A & G Residential	CITY / CO.	Coats / Harnett	THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer
JOB NAME	Lot 20 Turlington Acres	ADDRESS	78 Regis Lane	is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package
PLAN	Sophia B Roof	MODEL	Roof	or online @ sbcindustry.com Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables
SEAL DATE	1/24/25	DATE REV.	05/01/25	(derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those
QUOTE#		DRAWN BY	Marshall Naylor	specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#. Marshall Naylor
JOB#	J0425-1939	SALES REP.	Marshall Naylor	Signature Marshall Naylor



Fayetteville, N.C. 28309

Phone: (910) 864-8787

Fax: (910) 864-4444