

RE: 4043881 - DREAM FINDERS HOMES, Cardinal (AB\_4), A/B, Lot 464, THE COLONY  
 TRENCO  
 818 Soundside Rd  
 Edenton, NC 27932

**Site Information:**

Project Customer: DREAM FINDERS HOMES Project Name:  
 Lot/Block: 464 Subdivision: THE COLONY @ LEXINGTON PLANTATION  
 Address: 39 STEEPLE RIDGE  
 City: CAMERON State: NC

**Name Address and License # of Structural Engineer of Record, If there is one, for the building.**

Name: License #:  
 Address:  
 City, County: State:

**General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):**

Design Code: IRC2015/TPI2014 Design Program: MiTek 20/20 8.6  
 Wind Code: ASCE 7-10 Design Method: MWFRS (Envelope)/C-C hybrid Wind ASCE 7-10  
 Wind Speed: 150 mph  
 Roof Load: 40.0 psf Floor Load: N/A psf

This package includes 1 individual, dated Truss Design Drawings and 0 Additional Drawings.

No.	Seal#	Job ID#	Truss Name	Date
1	167270193	4043881	A04	8/2/24

The truss drawing(s) referenced above have been prepared by  
 Truss Engineering Co. under my direct supervision based on the parameters  
 provided by Builders FirstSource-Sumter,SC.

Truss Design Engineer's Name: Gilbert, Eric  
 My license renewal date for the state of North Carolina is December 31, 2024.

**IMPORTANT NOTE:** The seal on these truss component designs is a certification  
 that the engineer named is licensed in the jurisdiction(s) identified and that the  
 designs comply with ANSI/TPI 1. These designs are based upon parameters  
 shown (e.g., loads, supports, dimensions, shapes and design codes), which were  
 given to MiTek or TRENCO. Any project specific information included is for MiTek's or  
 TRENCO's customers file reference purpose only, and was not taken into account in the  
 preparation of these designs. MiTek or TRENCO has not independently verified the  
 applicability of the design parameters or the designs for any particular building. Before use,  
 the building designer should verify applicability of design parameters and properly  
 incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.




Gilbert, Eric

August 2, 2024

Job 4043881	Truss A04	Truss Type Common	Qty 5	Ply 1	DREAM FINDERS HOMES, Cardinal (AB_4), A/B, Lot 464, THE COL 167270193
----------------	--------------	----------------------	----------	----------	---


Builders FirstSource (Sumter, SC), Sumter, SC - 29153, ID: qesddlmiofJcJg3nOl3r8zrBHb-OF?b7TtXRH065Krx0m2DDMvprFEIMMte862Tz?TyrzV6

8.630 s Aug 30 2023 MiTek Industries, Inc. Fri Aug 2 18:25:43 2024 Page 1



Repair Condition: Missing or damaged plate(s) on one side(s) of truss at joint(s) 4.

Scale = 1:54.0



ATTACH 7/16" OSB GUSSET (7/16" RATED SHEATHING 24/16 EXP 1) TO EACH FACE OF TRUSS WITH (0.131" X 2.5" MIN.) NAILS PER THE FOLLOWING NAIL SCHEDULE: 2 X 3'S - 2 ROWS, 2 X 4'S - 3 ROWS, 2 X 6'S AND LARGER - 4 ROWS: SPACED @ 4" O.C. NAILS TO BE DRIVEN FROM BOTH FACES. STAGGER SPACING FROM FRONT TO BACK FACE FOR A NET 2" O.C. SPACING IN EACH COVERED TRUSS MEMBER. USE 2" MEMBER END DISTANCE.

Plate Offsets (X,Y)-- [2:0-1-3,0-1-8], [3:0-4-0,0-3-0], [5:0-4-0,0-3-0], [6:0-1-3,0-1-8], [7:0-5-0,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.89	Vert(LL) -0.25	6-7	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.97	Vert(CT) -0.52	6-7	>640	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.84	Horz(CT) 0.04	6	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.15	2-7	>999	240		
							Weight: 151 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x6 SP No.2  
WEBS 2x4 SP No.3

**BRACING-**

TOP CHORD Structural wood sheathing directly applied.  
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.

**REACTIONS.**

(size) 2=0-3-8, 6=Mechanical  
Max Horz 2=380(LC 11)  
Max Uplift 2=-538(LC 12), 6=-490(LC 13)  
Max Grav 2=1174(LC 1), 6=1111(LC 1)

**FORCES.**

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-1923/756, 3-4=-1555/601, 4-5=-1556/608, 5-6=-1936/772  
BOT CHORD 2-7=-733/1506, 6-7=-516/1525  
WEBS 4-7=-307/1091, 5-7=-682/615, 3-7=-660/590

**NOTES-**

- na
- na
- na
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=150mph Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 14-0-0, Exterior(2) 14-0-0 to 17-0-0, Interior(1) 17-0-0 to 27-11-4 zone; cantilever left exposed; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 538 lb uplift at joint 2 and 490 lb uplift at joint 6.



August 2, 2024

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPH Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)




818 Soundside Road  
Edenton, NC 27932

# Symbols


## PLATE LOCATION AND ORIENTATION



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



For 4 x 2 orientation, locate plates 0- 1/16" from outside edge of truss.



This symbol indicates the required direction of slots in connector plates.

\* Plate location details available in MITek software or upon request.

## PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

## LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

## BEARING



Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.


## Industry Standards:

ANSI/TP1: National Design Specification for Metal Plate Connected Wood Truss Construction.  
DSB-22: Design Standard for Bracing.  
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

# Numbering System



1 TOP CHORDS  
2 Joint ID  
3 typ.



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

# Product Code Approvals

ICC-ES Reports:

ESR-1988, ESR-2362, ESR-2685, ESR-3282  
ESR-4722, ESL-1388

# Design General Notes

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 section 6.3. These truss designs rely on Lumber values established by others.

© 2023 MITek® All Rights Reserved

# General Safety Notes

## Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability/bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.

**MITek**

ENGINEERING BY  
**TRENGO**  
A MITek Affiliate

MITek Engineering Reference Sheet: MIL-7473 rev. 1/2/2023