


Job 72423785REP1	Truss A03	Truss Type Truss	Qty 16	Ply 1	Service - 1400 RANCH PLAN RF Job Reference (optional)
---------------------	--------------	---------------------	-----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, clm

Run: 8.73 S Jul 24 2024 Print: 8.730 S Jul 24 2024 MiTek Industries, Inc. Mon Sep 16 12:07:56

Page: 1

ID:LW59KkYf1LMkKZamHvJfqsZTmD1-8VM0t4AQYYioQhufQnPutWkr1fken26pclVGPeyd48Z



Repair for a break in the web where indicated.

Attach 2x4 x 6' SP or SPF No.2 scab to each face of truss centered at the break with 2 rows of 10d (.131" x 3") nails spaced 4" oc

Plate Offsets (X, Y): [3:0-4:0,0-4-8], [6:0-3:0,Edge], [9:0-4:0,0-4-8], [12:0-1:12,0-1-8], [14:0-2:0,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFLL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	Vert(LL)	-0.24	14-15	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	Vert(CT)	-0.36	14-15	>999	180		
BCLL	0.0 *	Rep Stress Incr		WB	Horz(CT)	0.04	11	n/a	n/a		
BCDL	10.0	Code	IRC2015/TP12014	Matrix-MSH	Attic	-0.17	12-14	>587	360	Weight: 248 lb	FT = 20%


LUMBER		BRACING	
TOP CHORD	2x6 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 4-11-7 oc purlins, except end verticals.
BOT CHORD	2x6 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3 "Except" W4,W5;2x4 SP No.2	WEBS	1 Row at midpt 5-7, 3-15, 9-11

REACTIONS	(lb/size)	11=1254/ Mechanical, (min. 0-1-8), 15=1317/0-3-8, (min. 0-1-11)
Max Horiz	15=197 (LC 8)	
Max Uplift	15=14 (LC 10)	
Max Grav	11=1398 (LC 19), 15=1452 (LC 18)	

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-368/56, 3-4=-1784/102, 4-5=-1383/134, 7-8=-1391/134, 8-9=-1781/102, 9-10=-255/36, 2-15=-343/86
BOT CHORD	14-15=-110/1645, 13-14=0/1491, 12-13=0/1491, 11-12=-57/1456
WEBS	8-12=0/505, 4-14=0/522, 3-14=-259/203, 5-7=-1584/154, 3-15=-1648/76, 9-11=-1706/108

NOTES (10)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TCDD=6.0psf, BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (5.0 psf) on member(s), 4-5, 7-8, 5-7
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 12-14
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 14 lb uplift at joint 15.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TP1.
- Attic room checked for L/360 deflection.
- This repair has been prepared based on information and use conditions supplied by client. Designer has made a good faith effort to outline damage and repair conditions as reported by client. When actual field conditions do not approximate those indicated on this drawing, client shall immediately inform the engineer and refrain from applying the repair.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFP plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72423785REP1	Truss A03	Truss Type Truss	Qty 16	Ply 1	Service - 1400 RANCH PLAN RF Job Reference (optional)
---------------------	--------------	---------------------	-----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, clm

Run: 8.73 S Jul 24 2024 Print: 8.730 S Jul 24 2024 MiTek Industries, Inc. Mon Sep 16 12:07:56

Page: 1

ID:LW59KkYf1LMkKZamHvJfqsZTmD1-8VM0t4AQYYioQhufQnPutWkr1fken26pclVGpEyD48Z



Repair for a break in the web where indicated.

Attach 2x4 x 6' SP or SPF No.2 scab to each face of truss centered at the break with 2 rows of 10d (.131" x 3") nails spaced 4" oc

Plate Offsets (X, Y): [3-0-4-0,0-4-8], [6-0-3-0,Edge], [9-0-4-0,0-4-8], [12-0-1-12,0-1-8], [14-0-2-0,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	Vert(LL)	-0.24	14-15	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	Vert(CT)	-0.36	14-15	>999	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	Horz(CT)	0.04	11	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH	Attic	-0.17	12-14	>587	360	Weight: 248 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x6 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 4-11-7 oc purlins, except end verticals.
BOT CHORD	2x6 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3 *Except* W4,W5;2x4 SP No.2	WEBS	1 Row at midpt 5-7, 3-15, 9-11
REACTIONS	(lb/size) 11=1254/ Mechanical, (min. 0-1-8), 15=1317/0-3-8, (min. 0-1-11) Max Horiz 15=-197 (LC 8) Max Uplift 15=-14 (LC 10) Max Grav 11=1398 (LC 19), 15=1452 (LC 18)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown. TOP CHORD 2-3=-368/56, 3-4=-1784/102, 4-5=-1383/134, 7-8=-1391/134, 8-9=-1781/102, 9-10=-255/36, 2-15=-343/86 BOT CHORD 14-15=-110/1645, 13-14=0/1491, 12-13=0/1491, 11-12=-57/1456 WEBS 8-12=0/505, 4-14=0/522, 3-14=-259/203, 5-7=-1584/154, 3-15=-1648/76, 9-11=-1706/108		

NOTES (10)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (5.0 psf) on member(s). 4-5, 7-8, 5-7
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 12-14
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 14 lb uplift at joint 15.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Attic room checked for L/360 deflection.
- This repair has been prepared based on information and use conditions supplied by client. Designer has made a good faith effort to outline damage and repair conditions as reported by client. When actual field conditions do not approximate those indicated on this drawing, client shall immediately inform the engineer and refrain from applying the repair.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFP plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.

