

# Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 49394

JOB: 24-4823-F01

JOB NAME: LOT 0.0038 HONEYCUTT HILLS

Wind Code: N/A

Wind Speed: Vult= N/A

Exposure Category: N/A

Mean Roof Height (feet): N/A

These truss designs comply with IRC 2015 as well as IRC 2018.

*18 Truss Design(s)*

Trusses:

F101, F102, F103, F104, F105, F106, F107, F108, F109, F110, F111, F112, F113, F114, F115, F116, F117, F118



**6/5/2024**

**Mark Morris**

***Warning !—Verify design parameters and read notes before use.***


This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSL/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI

Job 24-4823-F01	Truss F101	Truss Type GABLE	Qty 2	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC
					Job Reference (optional) <b># 49394</b>

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:21 2024 Page 1  
ID:oDuW00MhLxMOj2fwcp2aKqzMG6w-EbrvnrMLPYgdSxVeBflbyhMkwG?GuzGaRQt\_6uz9Lli

0-1-8

Scale = 1:22.4



1-4-0	2-8-0	4-0-0	5-4-0	6-8-0	8-0-0	9-4-0	10-8-0	12-0-0	13-4-0	14-2-0
1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	0-10-0

Plate Offsets (X,Y)-- [1:Edge,0-1-8], [6:0-1-8,Edge], [20:0-1-8,Edge], [24:Edge,0-1-8]

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	-0.00	13	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH						Weight: 59 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

**REACTIONS.** All bearings 14-2-0.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 24, 13, 23, 22, 21, 20, 19, 18, 17, 16, 15, 14

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8-9)
- All plates are 1.5x3 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Job 24-4823-F01	Truss F102	Truss Type Floor	Qty 6	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC	# 49394
--------------------	---------------	---------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:22 2024 Page 1  
ID:oDuWOOmHxLxMoj2fwcp2aKqzMG6w-ioPI?ANzAsoU454qINpqVuurigCRdHzjg4dXfkz9Lh

1-3-0

1-0-10 0-1-8

Scale = 1:23.2



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.31	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.59	Vert(LL) -0.16 12 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.58	Vert(CT) -0.22 11-12 >757 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.04 9 n/a n/a		
	Code IRC2018/TPI2014			Weight: 71 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 15=766/0-4-8 (min. 0-1-8), 9=760/0-7-14 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-15=-759/0, 1-2=-1026/0, 2-3=-2409/0, 3-4=-3018/0, 4-5=-3018/0, 5-6=-2739/0, 6-7=-1714/0  
 BOT CHORD 13-14=0/1931, 12-13=0/2851, 11-12=0/3028, 10-11=0/2416, 9-10=0/974  
 WEBS 1-14=0/1216, 2-14=-1104/0, 2-13=0/584, 3-13=-539/0, 5-11=-353/0, 6-11=0/394, 6-10=-857/0, 7-10=0/903,  
 7-9=-1212/0

- NOTES-** (4-5)
- 1) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 3) CAUTION. Do not erect truss backwards.
  - 4) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-4823-F01	Truss F103	Truss Type Floor Supported Gable	Qty 1	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) <b># 49394</b>
--------------------	---------------	-------------------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:23 2024 Page 1  
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-A\_ygCWNbw9wLhFf1J4K326R4n3hZMtvsvkM5Bmz9Lg




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [6:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.04	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.02	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.02	Horz(CT)	0.00	4	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-R							
									Weight: 12 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)  
OTHERS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 2-1-14 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 6=66/2-1-14 (min. 0-1-8), 4=31/2-1-14 (min. 0-1-8), 5=107/2-1-14 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (7-8)
- 1) Gable requires continuous bottom chord bearing.
  - 2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - 3) Gable studs spaced at 1-4-0 oc.
  - 4) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) CAUTION, Do not erect truss backwards.
  - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-4823-F01	Truss F104	Truss Type Floor	Qty 3	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC	# 49394
--------------------	---------------	---------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:23 2024 Page 1  
ID: oDuWOOMhLxMOj2fwcp2aKqzMG6w-A\_ygCWNbw9wLhFf1J4K326R0k3adMmLsvkM5Bmz9Llg

1-3-0

0-9-10 0-1-8

Scale = 1:20.6




Plate Offsets (X,Y)-- [7:0-1-8,Edge], [14:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.30	Vert(LL)	-0.10	11	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.46	Vert(CT)	-0.14	11	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.51	Horz(CT)	0.03	8	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH							
									Weight: 64 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 14=683/0-4-8 (min. 0-1-8), 8=677/0-7-14 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-14=-676/0, 8-15=-676/0, 7-15=-675/0, 1-2=-897/0, 2-3=-2046/0, 3-4=-2415/0, 4-5=-2415/0, 5-6=-1896/0, 6-7=-635/0  
BOT CHORD 12-13=0/1685, 11-12=0/2370, 10-11=0/2303, 9-10=0/1454  
WEBS 1-13=0/1064, 2-13=-961/0, 2-12=0/441, 3-12=-396/0, 5-10=-497/0, 6-10=0/540, 6-9=-1000/0, 7-9=0/834

- NOTES-** (5-6)
- All plates are 3x4 MT20 unless otherwise indicated.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-4823-F01	Truss F105	Truss Type Floor	Qty 1	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC	# 49394
--------------------	---------------	---------------------	----------	----------	--	---------


Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:24 2024 Page 1  
ID:oDuWOOmHxMOj2fwcp2aKqzMG6w-fAW2QsODhT2CJOEDtnrlaJ\_AJTz85BQ0806ejCz9Llf

1-3-0

0-4-12

0-4-14 0-1-8

Scale = 1:23.0



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.37	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.32	Vert(LL) -0.06 14-15 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.58	Vert(CT) -0.08 14-15 >999 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.01 11 n/a n/a		
	Code IRC2018/TPI2014			Weight: 74 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 17=549/0-4-8 (min. 0-1-8), 9=613/2-1-14 (min. 0-1-8), 11=1586/2-1-14 (min. 0-1-8), 10=4/2-1-14 (min. 0-1-8)  
Max Uplift9=-613(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-17=-542/0, 9-18=0/631, 8-18=0/629, 1-2=-687/0, 2-3=-1453/0, 3-4=-1429/0, 4-5=-1429/0, 5-6=-515/0, 6-7=0/1087, 7-8=0/418  
BOT CHORD 15-16=0/1284, 14-15=0/1587, 13-14=0/1124, 11-12=-1487/0, 10-11=-1443/0  
WEBS 7-11=-1511/0, 1-16=0/815, 2-16=-728/0, 5-14=0/366, 5-13=-744/0, 6-13=0/790, 6-12=-1165/0, 7-12=0/756, 7-10=0/1221, 8-10=-791/0

- NOTES-** (6-7)
- All plates are 3x4 MT20 unless otherwise indicated.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 613 lb uplift at joint 9.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Job 24-4823-F01	Truss F106	Truss Type Floor	Qty 3	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC	# 49394
--------------------	---------------	---------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:25 2024 Page 1  
ID:oDuW00MhLxMOj2fwcp2aKqzMG6w-7N4QdCPsSnA3xYpPQVVMX7XWkktDhqeY9M2rBFfz9Lle

1-3-0

0-9-10 0-1-8

Scale = 1:24.7



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP		
TCLL	40.0	Plate Grip DOL	2-0-0	TC	0.39	in (loc)	l/defl	L/d	MT20	244/190				
TCDL	10.0	Lumber DOL	1.00	BC	0.68	Vert(LL)	-0.21 12-13	>860 480						
BCLL	0.0	Rep Stress Incr	YES	WB	0.63	Vert(CT)	-0.29 12-13	>623 360						
BCDL	5.0	Code IRC2018/TPI2014		Matrix-SH		Horz(CT)	0.05 9	n/a n/a						
													Weight: 76 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 16=821/0-4-8 (min. 0-1-8), 9=815/0-7-14 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-16=-813/0, 9-17=-814/0, 8-17=-812/0, 1-2=-1112/0, 2-3=-2651/0, 3-4=-3419/0, 4-5=-3419/0, 5-6=-3300/0, 6-7=-2437/0, 7-8=-778/0  
BOT CHORD 14-15=0/2094, 13-14=0/3171, 12-13=0/3513, 11-12=0/3051, 10-11=0/1789  
WEBS 1-15=0/1318, 2-15=-1200/0, 2-14=0/679, 3-14=-635/0, 3-13=0/299, 5-12=-261/0, 6-12=0/304, 6-11=-749/0, 7-11=0/791, 7-10=-1234/0, 8-10=0/1024

- NOTES-** (5-6)
- All plates are 3x4 MT20 unless otherwise indicated.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Job 24-4823-F01	Truss F107	Truss Type Floor	Qty 1	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC	# 49394
--------------------	---------------	---------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:26 2024 Page 1  
ID: oDuWOOMhLxMOj2fwcp2aKqzMG6w-bZeorYQUD4lwYiOb\_Cumfk3U0HcPZ5GJbiblo5z9Lld

1-3-0

0-7-12 | 1-1-14 | 0-1-8

Scale = 1:24.8



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.49	Vert(LL)	-0.09	14	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.39	Vert(CT)	-0.13	14	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.62	Horz(CT)	0.02	11	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH							
									Weight: 78 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 11-12,10-11.
WEBS 2x4 SP No.3(flat) *Except* W4: 2x4 SP No.2(flat)	

**REACTIONS.** (lb/size) 17=618/0-4-8 (min. 0-1-8), 10=-1132/1-7-14 (min. 0-1-8), 11=2149/1-7-14 (min. 0-1-8)  
Max Uplift10=-1132(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-17=-612/0, 1-2=-796/0, 2-3=-1760/0, 3-4=-1940/0, 4-5=-1940/0, 5-6=-1234/0, 7-8=0/1873  
BOT CHORD 15-16=0/1491, 14-15=0/1992, 13-14=0/1731, 12-13=0/698, 11-12=-1149/0, 10-11=-1873/0  
WEBS 8-11=-1286/0, 1-16=0/943, 2-16=-849/0, 2-15=0/328, 3-15=-284/0, 5-14=0/251, 5-13=-607/0, 6-13=0/654,  
6-12=-1116/0, 7-12=0/1138, 7-11=-1095/0, 8-10=0/2209

- NOTES-** (6-7)
- 1) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 1132 lb uplift at joint 10.
  - 2) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 3) This truss has large uplift reaction(s) from gravity load case(s). Proper connection is required to secure truss against upward movement at the bearings. Building designer must provide for uplift reactions indicated.
  - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 5) CAUTION, Do not erect truss backwards.
  - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC
24-4823-F01	F108	Floor Supported Gable	1	1	
					<b># 49394</b>

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:27 2024 Page 1  
 ID: oDuWOOMhLxMOj2fwcp2aKqzMG6w-3ICB2uQ6\_OQnAszoYwP?CyclGh2elhjSqMKIKXz9Llc

0-1-8

Scale = 1:37.3




Plate Offsets (X,Y)-- [10:0-1-8,Edge], [31:0-1-8,Edge], [38:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.07	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	20	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH						
								Weight: 92 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)  
 OTHERS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 22-9-10.  
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 38, 20, 37, 36, 35, 34, 33, 32, 31, 30, 29, 28, 26, 25, 24, 23, 22, 21

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8-9)
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 2) Gable requires continuous bottom chord bearing.
  - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - 4) Gable studs spaced at 1-4-0 oc.
  - 5) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 7) CAUTION, Do not erect truss backwards.
  - 8) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 9) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard





6/5/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-4823-F01	Truss F109	Truss Type Floor	Qty 13	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC	# 49394
--------------------	---------------	---------------------	-----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:29 2024 Page 1  
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-78KxTaSMW?gVPA6AflRTHNh1Uf5mUMIHgppPQz9Lla



LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.36	Vert(LL)	-0.06	23	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.33	Vert(CT)	-0.07	23	>999	360		
BCLL 0.0	Rep Stress Incr	NO	WB 0.47	Horz(CT)	0.01	14	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH							

Weight: 117 lb FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)


**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (lb/size) 26=364/0-7-14 (min. 0-1-8), 20=2029/0-4-8 (min. 0-1-8), 14=435/0-4-8 (min. 0-1-8)  
Max Grav 26=384(LC 3), 20=2029(LC 1), 14=497(LC 4)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 26-27=-381/0, 1-27=-380/0, 1-2=-495/0, 2-3=-1067/0, 3-4=-1118/0, 4-5=-1118/0, 5-6=-579/237, 6-7=-579/237,  
7-8=0/729, 8-9=0/801, 9-10=-964/0, 10-11=-1556/0, 11-12=-1077/0  
BOT CHORD 24-25=0/921, 23-24=0/1189, 22-23=-87/941, 21-22=-414/191, 20-21=-1556/0, 19-20=-1569/0, 18-19=-366/545,  
17-18=-366/545, 16-17=0/1356, 15-16=0/1556, 14-15=0/617  
WEBS 8-20=-1995/0, 1-25=0/562, 2-25=-520/0, 5-22=-481/0, 7-22=0/514, 7-21=-825/0, 8-21=0/953, 8-19=0/992, 9-19=-927/0,  
9-17=0/626, 10-17=-589/0, 10-16=0/359, 11-15=-568/0, 12-15=0/562, 12-14=-781/0

- NOTES-** (7-8)
- Unbalanced floor live loads have been considered for this design.
  - All plates are 3x4 MT20 unless otherwise indicated.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)**  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-26=-7, 1-13=-67  
Concentrated Loads (lb)  
Vert: 8=800 11=-350  
2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-26=-7, 1-13=-67



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC
24-4823-F01	F109	Floor	13	1	Job Reference (optional) # 49394

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:29 2024 Page 2  
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-?8KxTaSMW?gVPA6AflRTHNh1Uf5mUMIHgpPPQz9Lia

**LOAD CASE(S)**

- Concentrated Loads (lb)  
Vert: 8=-800 11=-350
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-26=-7, 1-8=-67, 8-13=-13  
Concentrated Loads (lb)  
Vert: 8=-800 11=-350
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-26=-7, 1-8=-13, 8-13=-67  
Concentrated Loads (lb)  
Vert: 8=-218 11=-350
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-26=-7, 1-8=-67, 8-13=-13  
Concentrated Loads (lb)  
Vert: 8=-800 11=-350
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-26=-7, 1-8=-13, 8-13=-67  
Concentrated Loads (lb)  
Vert: 8=-218 11=-350



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-4823-F01	Truss F110	Truss Type Floor	Qty 9	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) <b># 49394</b>
--------------------	---------------	---------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:31 2024 Page 1  
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-xXRhuFTd2dwCFTGZnmTxMomL0IKHEMx2lzJwTiz9LY





Plate Offsets (X,Y)-- [14:Edge,0-1-8], [28:Edge,0-1-8]

<b>LOADING</b> (psf)	<b>SPACING-</b>	1-4-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.47	Vert(LL)	-0.06 17-18	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.41	Vert(CT)	-0.08 17-18	>999	360		
BCLL 0.0	Rep Stress Incr	NO	WB 0.62	Horz(CT)	0.01 14	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH						
								Weight: 120 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat) \*Except\*  
W2: 2x4 SP No.2(flat)


**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (lb/size) 28=330/0-3-14 (min. 0-1-8), 21=1928/0-4-8 (min. 0-1-8), 14=1229/0-4-8 (min. 0-1-8)  
Max Grav 28=390(LC 3), 21=1928(LC 1), 14=1291(LC 4)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-28=-386/0, 1-2=-496/0, 2-3=-1077/41, 3-4=-1133/253, 4-5=-1133/253, 5-6=-600/622,  
6-7=-600/622, 7-8=0/1228, 8-9=-333/664, 9-10=-1885/22, 10-11=-1679/0, 11-12=-966/0  
BOT CHORD 26-27=0/929, 25-26=-125/1200, 24-25=-419/959, 23-24=-854/214, 22-23=-854/214,  
21-22=-2111/0, 20-21=-2123/0, 19-20=-171/1828, 18-19=-171/1828, 17-18=0/1908,  
16-17=0/1430, 15-16=0/774, 14-15=0/774  
WEBS 8-21=-1881/0, 10-17=-279/71, 11-17=-41/305, 11-16=-566/0, 12-16=0/416, 12-14=-1468/0,  
1-27=0/588, 2-27=-528/3, 5-25=0/314, 5-24=-547/0, 7-24=0/583, 7-22=-891/0,  
8-22=0/1018, 8-20=0/2204, 9-20=-1964/0

- NOTES-** (6-7)
- Unbalanced floor live loads have been considered for this design.
  - All plates are 3x4 MT20 unless otherwise indicated.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-28=-7, 1-13=-67  
Concentrated Loads (lb)  
Vert: 9=-935 12=-870



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-4823-F01	Truss F111	Truss Type GABLE	Qty 1	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) <b># 49394</b>
--------------------	---------------	---------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:32 2024 Page 1  
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-Qj?45bUFpw23GdrLT\_Av?Jd9iiqzx\_Bzd23?Iz9LIX

Scale = 1:13.0




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [4:0-1-8,Edge], [12:0-1-8,Edge], [14:Edge,0-1-8]					
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.06	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 8 n/a n/a		
BCDL 5.0	Code IRC2018/TPI2014	Matrix-P			
				Weight: 33 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)  
OTHERS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 7-2-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 7-2-0.  
(lb) - Max Uplift All uplift 100 lb or less at joint(s) 8  
Max Grav All reactions 250 lb or less at joint(s) 14, 8, 13, 12, 11, 10, 9

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8-9)
- All plates are 1.5x3 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC
24-4823-F01	F112	Floor	5	1	
Job Reference (optional)					# 49394

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:32 2024 Page 1  
 ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-Qj?45bUFpw23GdrLT\_Av?JZNii7zqUBzd23?Iz9LIX



Scale = 1:25.8




Plate Offsets (X,Y)-- [8:0-1-8,Edge], [17:Edge,0-1-8]					
<b>LOADING</b> (psf)	<b>SPACING-</b> 1-4-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.30	Vert(LL) -0.05 14 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.24	Vert(CT) -0.07 14 >999 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.45	Horz(CT) 0.01 11 n/a n/a		
BCDL 5.0	Code IRC2018/TPI2014	Matrix-SH		Weight: 81 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 17=395/0-4-8 (min. 0-1-8), 9=-348/0-7-14 (min. 0-1-8), 11=1093/0-4-8 (min. 0-1-8)  
 Max Uplift 9=-409(LC 3)  
 Max Grav 17=396(LC 3), 11=1093(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-17=-391/0, 9-18=0/415, 8-18=0/414, 1-2=-505/0, 2-3=-1101/0, 3-4=-1174/0, 4-5=-1174/0, 5-6=-657/0, 6-7=0/369, 7-8=0/549  
 BOT CHORD 15-16=0/945, 14-15=0/1233, 13-14=0/1008, 12-13=0/281, 11-12=-1191/0, 10-11=-1199/0  
 WEBS 7-11=-1062/0, 1-16=0/599, 2-16=-537/0, 5-13=-434/0, 6-13=0/467, 6-12=-791/0, 7-12=0/941, 7-10=0/769, 8-10=-666/0

- NOTES-** (7-8)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 9=409.
  - 4) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) CAUTION, Do not erect truss backwards.
  - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard




6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-4823-F01	Truss F113	Truss Type Floor	Qty 1	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC	# 49394
--------------------	---------------	---------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:33 2024 Page 1  
ID: oDuWOOMhLxMOj2fwcp2aKqzMG6w-uvZSJxVtaEAwunQyuAWPSDskB52OivLCHocYBz9LIW



<b>LOADING</b> (psf)	<b>SPACING-</b>	1-4-0	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.30	Vert(LL)	-0.05	14	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.24	Vert(CT)	-0.07	14	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.44	Horz(CT)	0.01	11	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH						Weight: 80 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (lb/size) 17=390/0-7-14 (min. 0-1-8), 9=-344/0-7-14 (min. 0-1-8), 11=1087/0-4-8 (min. 0-1-8)  
Max Uplift 9=405(LC 3)  
Max Grav 17=390(LC 3), 11=1087(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 17-18=-387/0, 1-18=-386/0, 9-19=0/411, 8-19=0/410, 1-2=-504/0, 2-3=-1094/0, 3-4=-1163/0, 4-5=-1163/0, 5-6=-642/0, 6-7=0/387, 7-8=0/545  
BOT CHORD 15-16=0/939, 14-15=0/1225, 13-14=0/995, 12-13=0/262, 11-12=-1182/0, 10-11=-1188/0  
WEBS 7-11=-1057/0, 1-16=0/573, 2-16=-531/0, 5-13=-437/0, 6-13=0/470, 6-12=-791/0, 7-12=0/918, 7-10=0/762, 8-10=-660/0

- NOTES-** (7-8)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 9=405.
  - 4) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) CAUTION, Do not erect truss backwards.
  - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-4823-F01	Truss F114	Truss Type Floor Supported Gable	Qty 1	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC	Job Reference (optional) <b># 49394</b>
--------------------	---------------	-------------------------------------	----------	----------	--	--

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:34 2024 Page 1  
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-M57qWHWVLYInWx?8Su1e\_QOzhVR9RrVURxXA4dz9LIV




Plate Offsets (X,Y)-- [5:Edge,0-1-8], [8:Edge,0-1-8]										
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.02	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	5	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-R						Weight: 16 lb	FT = 20%F, 11%E

<b>LUMBER-</b>		<b>BRACING-</b>	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 3-3-14 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

**REACTIONS.** All bearings 3-3-14.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 8, 5, 7, 6

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (7-8)
- All plates are 1.5x3 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job 24-4823-F01	Truss F115	Truss Type Floor	Qty 9	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC	Job Reference (optional) <b># 49394</b>
--------------------	---------------	---------------------	----------	----------	--	--

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:35 2024 Page 1  
ID:oDuWOOmHxLxMOJ2fwcp2aKqzMG6w-qlhCjdX76rQe75aK0bYtXex6VvjxAEgdbHjc4z9LIU







Plate Offsets (X,Y)-- [7:0-1-8,Edge], [14:Edge,0-1-8]

<b>LOADING</b> (psf)	<b>SPACING-</b>	1-4-0	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.18	Vert(LL)	-0.06	11	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.30	Vert(CT)	-0.09	11	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.32	Horz(CT)	0.02	8	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH							
									Weight: 63 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 14=444/0-7-14 (min. 0-1-8), 8=444/0-7-14 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 14-15=-441/0, 1-15=-440/0, 8-16=-445/0, 7-16=-444/0, 1-2=-588/0, 2-3=-1331/0, 3-4=-1556/0, 4-5=-1556/0, 5-6=-1189/0, 6-7=-334/0  
BOT CHORD 12-13=0/1100, 11-12=0/1539, 10-11=0/1473, 9-10=0/881  
WEBS 1-13=0/669, 2-13=-624/0, 2-12=0/283, 3-12=-253/0, 5-10=-347/0, 6-10=0/375, 6-9=-668/0, 7-9=0/499

- NOTES-** (4-5)
- All plates are 3x4 MT20 unless otherwise indicated.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Job	Truss	Truss Type	Qty	Ply	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC
24-4823-F01	F116	Floor Supported Gable	1	1	
					<b># 49394</b>

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:36 2024 Page 1  
 ID:oDuW00MhLxMOj2fwcp2aKqzMG6w-IUFaxzXlI9ZVIE9Waj363rUI8J7fv\_nuFOH8Wz9LIT

0<sub>1</sub>-8

0<sub>1</sub>-8

Scale = 1:20.1



12-5-12	
12-5-12	
Plate Offsets (X,Y)-- [6:0-1-8,Edge], [12:Edge,0-1-8], [17:0-1-8,Edge], [21:Edge,0-1-8], [23:0-1-8,0-0-8]	

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	12	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH						Weight: 53 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

**REACTIONS.** All bearings 12-5-12.  
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 21, 12, 20, 19, 18, 17, 16, 15, 14, 13

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (7-8)
- All plates are 1.5x3 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024


**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-4823-F01	Truss F117	Truss Type Floor Supported Gable	Qty 2	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) <b># 49394</b>
--------------------	---------------	-------------------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:36 2024 Page 1  
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-IUFaxzXit9ZVIE9WaJ363rUJB7mvl\_nuF0H8Wz9LIT

0<sub>1</sub>-8

Scale = 1:23.3



14-3-14  
14-3-14

Plate Offsets (X,Y)-- [6:0-1-8,Edge], [13:Edge,0-1-8], [20:0-1-8,Edge], [24:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	13	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH						
								Weight: 60 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)  
OTHERS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 14-3-14.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 24, 13, 23, 22, 21, 20, 19, 18, 17, 16, 15, 14

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8-9)
- All plates are 1.5x3 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard




6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-4823-F01	Truss F118	Truss Type Floor	Qty 8	Ply 1	LOT 0.0038 HONEYCUTT HILLS   246 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) <b># 49394</b>
--------------------	---------------	---------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.430 s Feb 12 2021 MiTek Industries, Inc. Wed Jun 5 12:17:37 2024 Page 1  
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-mgpz8JYNdThMNOKj70aLc30RujNre7rw7vmqhyz9LlS



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	1-4-0	TC 0.19	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.40	Vert(LL) -0.11 12 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.38	Vert(CT) -0.15 11-12 >999 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.03 9 n/a n/a		
	Code IRC2018/TPI2014			Weight: 72 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 15=512/0-7-14 (min. 0-1-8), 9=516/0-4-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 15-16=-508/0, 1-16=-507/0, 1-2=-694/0, 2-3=-1629/0, 3-4=-2051/0, 4-5=-2051/0, 5-6=-1881/0, 6-7=-1213/0  
BOT CHORD 13-14=0/1301, 12-13=0/1932, 11-12=0/2066, 10-11=0/1673, 9-10=0/727  
WEBS 1-14=0/790, 2-14=-741/0, 2-13=0/400, 3-13=-370/0, 6-11=0/254, 6-10=-561/0, 7-10=0/593, 7-9=-872/0

- NOTES-** (5-6)
- All plates are 3x4 MT20 unless otherwise indicated.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION. Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



6/5/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.