

---

# NORRIS-RALE

---

**RALEIGH - LOT 00.0006 HONEYCUTT HILL SF**  
(MODEL# 3186)

**ELEVATION 5 - GL**




117 Shelby Meadow Lane

INDEX

LOT SPECIFIC

AREA CALCULATIONS	HEATED	COVERED / UNHEATED	UNCOVERED
ELEVATION 5			
FIRST FLOOR	1626 SF		
GARAGE		424 SF	
FRONT PORCH - ELEVATION 5		125 SF	
SECOND FLOOR	1560 SF		
OPTINONS			
1ST FLOOR			
REAR FIREPLACE	+10 SF	-10 SF	
ELEVATION 5	+18 SF		
REAR PORCH		+462 SF	
2ND FLOOR			
ELEVATION 5	+18 SF		
TOTAL	3232 SF	1001 SF	

1	LOT 00.0006	HONEYCUTT HILL SF
		NORRIS REV. 99 ELEVATION 5
2	ADDRESS	117 SHELBY MEADOW LANE ANGIER, NC 27501



FRONT ELEVATION 5

SCALE: 1/8" = 1'-0"



REAR ELEVATION 5

SCALE: 1/8" = 1'-0"

MASTER PLAN INFORMATION	
REVISION	DATE
99	10-05-22
UPDATED DATE	09-13-2023


DRAWN BY:	ITS
DATE:	02/08/2024
PLAN NO.	3186



HOUSE NAME:	NORRIS
DRAWING TITLE	FRONT & REAR ELEVATIONS


SHEET No.	A.1
-----------	-----

FILE: Lot\_00.0006.dwg DATE: 2/8/2024 1:51 PM



**RIGHT ELEVATION 5**

SCALE: 1/8" = 1'-0"



**LEFT ELEVATION 5**

SCALE: 1/8" = 1'-0"

MASTER PLAN INFORMATION	
REVISION	DATE
99	10-05-22
UPDATED DATE	09-13-2023

DRAWN BY:	ITS
DATE:	02/08/2024
PLAN NO.	3186




HOUSE NAME:	NORRIS
DRAWING TITLE	RIGHT & LEFT ELEVATIONS

SHEET No.	A1.2
-----------	------

**UPPER ROOF VENTILATION CALCULATIONS:**

ROOF AREA = 2201 SQ. FT.  
 OVERALL REQUIRED VENTILATION:  
 1 TO 150 = 14.67 SQ. FT.  
 1 TO 300 = 7.34 SQ. FT.  
 50-80% IN TOP THIRD = 3.61 - 5.81 SQ. FT. (1 TO 300)  
 NET FREE AREA OF VENTED SOFFIT = 5.1 SQ. IN. / LINEAR FT.  
 NET FREE AREA OF RIDGE VENT = 18 SQ. IN. / LINEAR FT.  
 LOWER VENTING (BOTTOM 2/3 RDS)  
 34 LINEAR FEET OF SOFFIT X 5.1 SQ. IN. = 3.33 SQ. FT.  
 UPPER VENTING (TOP 1/3 RDS)  
 41 LINEAR FEET OF RIDGE X 18 SQ. IN. = 5.93 SQ. FT.  
 5.13 SQ. FT. BETWEEN 50% - 80%  
 (1 TO 300 ALLOWED)  
 TOTAL ROOF VENTILATION: 8.46 SQ. FT. > 7.34 SQ. FT. (R01D)



**ROOF PLAN ELEV. 5**

SCALE: 1/8" = 1'-0"


MASTER PLAN INFORMATION		UPDATED DATE
REVISION	DATE	
99	10-05-22	09-13-2023

DRAWN BY: ITS  
 DATE: 02/08/2024  
 PLAN NO. 3186



HOUSE NAME: NORRIS  
 DRAWING TITLE: ROOF PLAN

SHEET No. A13



ELEVATION 5  
CRAWL SPACE PLAN  
SCALE: 1/8" = 1'-0"


MASTER PLAN INFORMATION	
REVISION	DATE
99	10-05-22
UPDATED DATE	09-13-2023

DRAWN BY:	ITS
DATE:	02/08/2024
PLAN NO.	3186



HOUSE NAME:	NORRIS
DRAWING TITLE	CRAWL SPACE PLAN

SHEET No.	A2.1
-----------	------



**ELEVATION 5  
FIRST FLOOR PLAN**  
SCALE: 1/8" = 1'-0"

MASTER PLAN INFORMATION	
REVISION	DATE
99	10-05-22
UPDATED DATE	09-13-2023


DRAWN BY:	ITS
DATE:	02/08/2024
PLAN NO.	3186



HOUSE NAME:	NORRIS
DRAWING TITLE	FIRST FLOOR PLAN

SHEET No.	A3.1
-----------	------

FILE: Lot 00.0006.dwg DATE: 2/8/2024 1:51 PM



ELEVATION 5  
 SECOND FLOOR PLAN  
 SCALE: 1/8" = 1'-0"


MASTER PLAN INFORMATION	
REVISION	DATE
99	10-05-22
UPDATED DATE	09-13-2023

DRAWN BY:	ITS
DATE:	02/08/2024
PLAN NO.	3186



HOUSE NAME:	NORRIS
DRAWING TITLE	SECOND FLOOR PLAN

SHEET No.  
 A3.2



**SECTION I**  
SCALE: 1/8" = 1'-0"

MASTER PLAN INFORMATION	
REVISION	DATE
99	10-05-22
UPDATED DATE	09-13-2023

DRAWN BY:	ITS
DATE:	02/08/2024
PLAN NO.	3186



HOUSE NAME:	NORRIS
DRAWING TITLE	BUILDING SECTION


SHEET No.  
**A4.1**



**ELECTRICAL LEGEND**

- ⊘ SINGLE POLE SWITCH
- ⊘<sub>3</sub> THREE WAY SWITCH
- ⊘<sub>4</sub> FOUR WAY SWITCH
- ⊕ DUPLEX AFCI RECEPTACLE
- ⊕<sub>B</sub> DUPLEX AFCI RECEPTACLE - BOTTOM HALF SWITCHED
- ⊕<sub>F</sub> DUPLEX AFCI RECEPTACLE - FLOOR MOUNTED
- 220V ⊕ RECEPTACLE - 220V
- ⊕<sub>GFI</sub> DUPLEX AFCI RECEPTACLE - GFI
- ⊕<sub>WP/GFI</sub> DUPLEX AFCI RECEPTACLE - WATERPROOF GFI
- ⊕<sub>SD</sub> SMOKE DETECTOR - WIRED IN SERIES
- ⊕<sub>EM</sub> EXHAUST FAN MOTOR
- ⊕<sub>TJ</sub> TV JACK
- ⊕<sub>TJ</sub> TV JACK
- ⊕<sub>CO</sub> CO / SMOKE DETECTOR
- ⊕<sub>DC</sub> DOOR CHIME
- ⊕<sub>LM</sub> LIGHT FIXTURE - WALL MOUNTED
- ⊕<sub>CM</sub> LIGHT FIXTURE - CEILING MOUNTED
- ⊕<sub>SL</sub> LIGHT FIXTURE - SURFACE MOUNTED LED
- ⊕<sub>FL</sub> FULLCHAIN LAMPHOLDER
- ⊕<sub>KL</sub> KEYLESS LAMPHOLDER
- ⊕<sub>MS</sub> MOTION SENSOR FLOOD LIGHT

NOTE: ALL ELECTRICAL WORK SHALL CONFORM TO THE REQUIREMENTS OF THE ADOPTED VERSION OF THE NATIONAL ELECTRICAL CODE, THE LOCAL POWER COMPANY AND TO ALL APPLICABLE LOCAL REGULATIONS.



**ELECTRICAL PLAN  
FIRST FLOOR - ELEV. 5**

SCALE: 1/8" = 1'-0"

MASTER PLAN INFORMATION  
REVISION DATE 10-05-22  
UPDATED DATE 09-13-2023

DRAWN BY:  
ITS

DATE: 02/08/2024

PLAN NO.  
3186



HOUSE NAME:  
**NORRIS**  
DRAWING TITLE  
FIRST FLOOR ELECTRICAL


SHEET No.

E.I.

**ELECTRICAL LEGEND**

- ⊕ SINGLE POLE SWITCH
- ⊕<sub>3</sub> THREE WAY SWITCH
- ⊕<sub>4</sub> FOUR WAY SWITCH
- ⊕ DUPLEX AFCI RECEPTACLE
- ⊕ DUPLEX AFCI RECEPTACLE - BOTTOM HALF SWITCHED
- ⊕ DUPLEX AFCI RECEPTACLE - FLOOR MOUNTED
- 220V ⊕ RECEPTACLE - 220V
- GFI ⊕ DUPLEX AFCI RECEPTACLE - GFI
- WP/GFI ⊕ DUPLEX AFCI RECEPTACLE - WATERPROOF GFI
- ⊕ SMOKE DETECTOR - WIRED IN SERIES
- ⊕ EXHAUST FAN MOTOR
- ⊕ TV JACK
- ⊕ TV JACK
- ⊕ CO / SMOKE DETECTOR
- ⊕ DOOR CHIME
- ⊕ LIGHT FIXTURE - WALL MOUNTED
- ⊕ LIGHT FIXTURE - CEILING MOUNTED
- ⊕ LIGHT FIXTURE - SURFACE MOUNTED LED
- ⊕ FULLCHAIN LAMPHOLDER
- ⊕ KEYLESS LAMPHOLDER
- ⊕ MOTION SENSOR FLOOD LIGHT

NOTE: ALL ELECTRICAL WORK SHALL CONFORM TO THE REQUIREMENTS OF THE ADOPTED VERSION OF THE NATIONAL ELECTRICAL CODE, THE LOCAL POWER COMPANY AND TO ALL APPLICABLE LOCAL REGULATIONS.



**ELECTRICAL PLAN**  
**SECOND FLOOR - ELEV. 5**  
 SCALE: 1/8" = 1'-0"

MASTER PLAN INFORMATION	
REVISION	DATE
99	10-05-22
	09-13-2023

DRAWN BY: ITS  
 DATE: 02/08/2024  
 PLAN NO. 3186



HOUSE NAME: NORRIS  
 DRAWING TITLE: SECOND FLOOR ELECTRICAL

SHEET No. E1.2

CONNECTION SPECIFICATIONS (TYP. U.N.O.)

Table with 3 columns: DESCRIPTION OF BLDG. ELEMENT, 3"x0.131" NAILS, 3"x0.120" NAILS. Rows include JOIST TO SOLE PLATE, SOLE PLATE TO JOIST/BLK'G, STUD TO SOLE PLATE, etc.

GENERAL STRUCTURAL NOTES

- DESIGN IS BASED ON 2018 NORTH CAROLINA STATE BUILDING CODE: RESIDENTIAL CODE.
WOOD FRAME ENGINEERING IS BASED ON NDS, 'NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION' - LATEST EDITION.
DESIGN LOADS: ROOF DEAD = 7 PSF T.C., 10 PSF B.C. LIVE = 16 PSF LOAD DURATION FACTOR = 1.25

FLOOR FRAMING

- I-JOISTS/TRUSSES SHALL BE DESIGNED BY MANUF. TO MEET OR EXCEED L/480 LIVE LOAD DEFLECTION CRITERIA.
MARBLE FLOORS - CONTACT MKK FOR MARBLE FLOOR DESIGNS
AT 1-JOIST FLOORS, PROVIDE 1/8" MIN. OSB RIM BOARD.
METAL HANGERS SHALL BE SPECIFIED BY MANUFACTURER, U.N.O.

ROOF FRAMING

- BAY WINDOWS & SHED ROOFS (UP TO 6' SPAN) CAN BE 2x4 OR 2x6 RAFTERS & CEILING JOISTS @ 16/24" O.C.
FASTEN EACH ROOF TRUSS TO TOP PLATE W/ SIMPSON H25T CLIP (OR APPROVED EQUAL) @ ALL BEARING POINTS.
METAL HANGERS SHALL BE SPECIFIED BY THE MANUFACTURER, U.N.O.

GENERAL FRAMING

- ALL TYP. NAIL FASTENER REQUIREMENTS ARE NOTED IN STANDARD CONNECTIONS TABLE OR ON PLANS.
REFER TO FASTENING SCHEDULE TABLE R602.3(1) FOR ALL CONNECTIONS, TYP. U.N.O.
EXT. & INT. BRG WALLS SHALL BE 2x4 OR 2x6 (AS SHOWN ON PLANS) @ 16" O.C. SFF OR 5/8" STUD GRADE LUMBER OR BETTER, U.N.O.

LATERAL BRACING & SHEAR WALL SHEATHING SPECIFICATIONS

THIS MODEL HAS BEEN DESIGNED TO RESIST LATERAL FORCES RESULTING FROM:
120 MPH WIND IN 2018 NCSBG:RC
(120 MPH WIND SPEED IN ASCE 7-10 WIND MAP, PER IRC R301.2.1.1) EXP. B, RISK CAT. 2 & SEISMIC CAT. A/B.

THE DESIGN WAS COMPLETED PER 2015 IBC (SECTION 1604) & ASCE 7-10, AS PERMITTED BY R301.1.3 OF THE 2018 NCSBG:RC, OR THE SIMPLIFIED PRESCRIPTIVE PROCEDURE IN ACCORDANCE WITH THE 2015 IRC IF THE PARAMETERS OF SECTION R602.12 COMPLY. ACCORDINGLY, THIS MODEL, AS DOCUMENTED AND DETAILED HEREIN, IS ADEQUATE TO RESIST THE CODE REQUIRED LATERAL FORCES.

DESIGN WIND UPLIFT LOADS HAVE BEEN CALCULATED UTILIZING ASCE 7-10 (ACCEPTED ENGINEERING PRACTICE) AS ALLOWED PER 2018 NCSBG:RC SECTION R802.11.1.1. THIS MODEL HAS BEEN DETAILED WHERE REQUIRED & ENGINEERED TO RESIST THE WIND UPLIFT LOAD PATH PER SECTIONS R602.3.5 & R802.11.

EXT. WALL SHEATHING SPECIFICATION

- 7/16" OSB OR 15/32" PLYWOOD: FASTEN SHEATHING W/ 2 3/8"x0.113" NAILS @ 6" O.C. AT EDGES & @ 12" O.C. IN THE PANEL FIELD. TYP. U.N.O.
HORIZONTAL BLOCKING OF EXT. WALL/SHEAR WALL PANEL EDGES IS NOT REQUIRED BY THIS DESIGN EXCEPT FOR THOSE AREAS SPECIFICALLY NOTED.
ALL EXT. WALLS SHALL BE CONTINUOUSLY SHEATHED AND ARE CONSIDERED SHEAR WALLS.
ALT. STAPLE CONNECTION SPEC: 1 1/2" 16 GA STAPLES (3/8" CROWN) @ 3" O.C. AT EDGES & @ 6" O.C. IN FIELD.

BLOCKED PANEL EDGES

- AT DESIGNATED AREAS - FASTEN SHEATHING W/ 2 3/8" x 0.113" NAILS @ 6" O.C. AT ALL PANEL EDGES AND 12" O.C. IN THE PANEL FIELD OR 1 3/4" 16 GA STAPLES (3/8" CROWN) @ 3" O.C. AT EDGES & @ 6" O.C. IN FIELD. ALL SHEATHING PANELS SHALL BE ORIENTED AND INSTALLED FULL HEIGHT OF SHEAR WALL OR 2x HORIZONTAL BLOCKING SHALL BE PROVIDED TO SUPPORT ALL UNSUPPORTED PANEL EDGES & EDGE FASTENING.

3" O.C. EDGE NAILING

- AT DESIGNATED AREAS - FASTEN PANEL EDGES OF WOOD STRUCTURAL WALL SHEATHING TO FRAMING W/ 8d NAILS @ 3" O.C. NO STAPLE ALTERNATIVE AVAILABLE AT THIS SPEC. ALL SHEATHING PANELS SHALL BE ORIENTED AND INSTALLED FULL HEIGHT OF SHEAR WALL OR 2x HORIZONTAL BLOCKING SHALL BE PROVIDED TO SUPPORT UNSUPPORTED PANEL EDGES AND 3" O.C. EDGE FASTENING.

NOTES

- SEE CONNECTION SPECIFICATIONS CHART FOR STANDARD SHEAR TRANSFER DETAILING. IF ADDITIONAL CAPACITY IS REQUIRED BY DESIGN, IT WILL BE SPECIFICALLY NOTED ON PLAN.
DESIGN ASSUMES 16" O.C. MAX. STUD SPACING, U.N.O.
ALL STRUCTURAL PANELS ARE TO BE DIRECTLY APPLIED TO STUD FRAMING.
PRE-MANUFACTURED PANELIZED WALLS: FASTEN TOGETHER END STUDS OF WALL PANELS SHEATHED W/ OSB OR PLYWOOD W/ 3" x 0.120" NAILS @ 4" O.C. (THRU ONE SIDE ONLY)


INDICATES EXTENT OF INT. OSB SHEARWALL OR 3" O.C. OSB SHEARWALL
INDICATES HOLD-DOWN BELOW

GENERAL STRUCTURAL NOTES

FOUNDATION

- DESIGN IS BASED ON 2018 NORTH CAROLINA STATE BUILDING CODE: RESIDENTIAL CODE.
FOOTING DESIGN - 2,000 PSF ALLOWABLE SOIL BEARING PRESSURE IS ASSUMED. BUILDER/CONTRACTOR MUST VERIFY.
FASTEN 2x4/6 SILL PLATES TO FND WITH A MINIMUM OF 2 ANCHORS PER PLATE, 12" MAX. FROM PLATE ENDS - UTILIZING:
1/2" DIA. ANCHOR BOLTS @ 6'-0" O.C., 7" MIN. EMBEDMENT (CONC), 15" MIN. EMBEDMENT (CMU)
SIMPSON MASA ANCHOR STRAPS @ 6'-0" O.C. (CONC)
SIMPSON MAB23 ANCHOR STRAPS @ 2'-8" O.C. (CMU) (REFER TO DETAILS FOR 10' TALL WALL ANCHOR REQUIREMENTS)
ALL LUMBER EXPOSED TO WEATHER OR IN CONTACT W/ CONCRETE OR CMU SHALL BE PRESERVATIVE TREATED SOUTHERN PINE #2.
BUILDER TO VERIFY CORROSION-RESISTANCE COMPATIBILITY OF HARDWARE & FASTENERS IN CONTACT W/ PRESERVATIVE-TREATED WOOD. CONTACT LUMBER & HARDWARE SUPPLIERS TO COORD.
BASEMENT INTERIOR BEARING WALLS & EXTERIOR WALK-OUT BASEMENT WALLS SHALL BE 2x6 @ 16" O.C. SFF OR STP, "STUD" GRADE OR BETTER.
CONCRETE DESIGN BASED ON ACI 318. CONCRETE SHALL ATTAIN THE FOLLOWING MIN. COMPRESSIVE STRENGTHS IN 28 DAYS, U.N.O.:
fc = 4,000 psi: FOUNDATION WALLS
2,500 psi: FOOTINGS & INTERIOR SLABS ON GRADE
3,000 psi: GARAGE & EXTERIOR SLABS ON GRADE
fy = 60,000 psi
BASEMENT FOUNDATION WALL DESIGN BASED ON:
9' OR 10' HEIGHT (AS NOTED ON PLANS)
TALLER WALLS MUST BE ENGINEERED.
NOMINAL WIDTH (4 1/2" FOR 10" THICK WALL).
BASEMENT WALL DESIGN IS BASED ON 60 PCF BACKFILL SOIL TYPE CLASSIFICATIONS (SC, ML-CL, OR CL).
BASEMENT WALLS SHALL BE BRACED, PRIOR TO BACKFILLING, BY ADEQUATE TEMPORARY BRACING OR INSTALL 1st FLOOR DECK.
PROVIDE (2) #5 BARS AROUND ALL SIDES OF OPENINGS IN CONCRETE BSMT. FND. WALL WITH 2" CLEAR. REINFORCEMENT SHALL EXTEND 12" PAST CORNER OF OPENING IN ALL DIRECTIONS.
FOR OPENINGS UP TO 36", PROVIDE MINIMUM 10" CONCRETE DEPTH OVER OPENING OR (3)2x10 W/ (2)2x6 JACK STUDS, U.N.O.
LARGER OPENINGS SHALL BE PER PLAN.
ALL CONCRETE EXPOSED TO THE WEATHER SHALL NOT HAVE LESS THAN 5% OR MORE THAN 1% AIR ENTRAINMENT.
ALL FOOTINGS SHALL BEAR AT LEAST 12" BELOW FINISH GRADE.
FOOTINGS AND SLABS ON GRADE SHALL BEAR ON VIRGIN SOIL OR 95% COMPACTED FILL.
PROVIDE CONTROL JOINTS AT ALL INSIDE CORNERS OF SLAB EDGES, AND OTHER LOCATIONS WHERE SLAB CRACKS ARE LIKELY TO DEVELOP.
JOINTS SHALL BE LOCATED @ 10'-0" O.C. (RECOMMENDED) OR 15'-0" O.C. (MAXIMUM)
JOINT GRID PATTERN SHALL BE AS CLOSE TO SQUARES AS POSSIBLE (1:1 RATIO), WITH A MAXIMUM OF 1:1.5 RATIO
CONTROL JOINTS SHALL NOT BE INSTALLED IN STRUCTURAL SLABS
CONCRETE MASONRY UNITS (CMU) SHALL BE ASTM C40 WITH A MIN. COMPRESSIVE STRENGTH OF 1900 psi (Fm=1500 psi). MORTAR SHALL BE ASTM C270, TYPE S. CMU DESIGN PER ACI 530 & 530.1.
CMU FOUNDATION WALLS SHALL HAVE 'DUR-O-WALL' HORIZONTAL JOINT REINFORCEMENT (OR EQUAL) - 9 GA. MINIMUM @ 16" O.C.
PROVIDE 2x8 x 16" LONG P.T. PLATE ON TOP OF ALL CRANK SPACE PIERS. ALL PIERS SHALL BE GROUTED SOLID.
PROVIDE 2x6 P.T. PLATE ON INTERIOR CRANK SPACE WALLS, FASTENED PER ANCHORAGE SPECIFICATION NOTED ABOVE.
DIMENSIONS BY OTHERS, BUILDER TO VERIFY.
BUILDER TO VERIFY THAT MODEL HAS BEEN ADEQUATELY TREATED BY A LICENSED AND BONDED PEST CONTROL COMPANY FOR SUBTERRANEAN TERMITES. METHOD AND TYPE OF TREATMENT TO BE DETERMINED BY PEST CONTROL COMPANY.

SD2.I REFERS TO SD2.IA FOR LVL/PSL/LSL BEAMS OR SD2.IB FOR FLITCH BEAMS OR SD2.IC FOR STEEL BEAMS



MULHERN+KULP RESIDENTIAL STRUCTURAL ENGINEERING
300 Bannockburn Ave. Building 4 - Asheville, PA 18002
P: 717-948-0801 - mulhern+kulp.com
NC LIC. #C-3825

M&K project number: 126-23047
project mgr: JTR
drawn by: SJF
issue date: 02-15-24
REVISIONS:
date: initial:



STRUCTURAL NOTES
HONEYCUT HILLS
LOT 6 - NORRIS 5
RALEIGH, NC

sheet: SO.0

LEGEND

- INTERIOR BEARING WALL
BEARING WALL ABOVE
BEAM / HEADER
INDICATES SHEAR WALL & EXTENT
EXTENT OF OVERFRAMING
METAL HANGER
INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.

NON-BEARING HEADER SCHEDULE

Table with 3 columns: SPAN, 2x4 NON-BEARING PARTITION WALL, 2x6 NON-BEARING PARTITION WALL. Rows include UP TO 3'-0", UP TO 6'-0", UP TO 8'-0".

NOTES:
ALL NON-BEARING INTERIOR STUD WALLS SHALL BE CONSTRUCTED WITH 2x STUD GRADE MEMBERS SPACED @ 24" O.C. (MAX.)

MEANS & METHODS NOTES

THE STRUCTURE IS DESIGNED TO BE SELF SUPPORTING AND STABLE AFTER THE BUILDING IS FINISHED AND ALL PLAN, DETAIL, AND NOTE SPECIFICATIONS HAVE BEEN COMPLETED. IT IS THE CONTRACTOR'S SOLE RESPONSIBILITY TO DETERMINE THE ERECTION PROCEDURES AND SEQUENCE TO INSURE THE SAFETY OF THE BUILDING AND ITS COMPONENTS DURING CONSTRUCTION. THIS INCLUDES, BUT IS NOT LIMITED TO, THE ADDITION OF NECESSARY SHORING, SHEETING, TEMPORARY BRACINGS, GUYS, AND TIE-DOWNS. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL SHORING AND BRACING REQUIRED TO STABILIZE AND PROTECT EXISTING AND ADJACENT STRUCTURES AND SYSTEMS DURING COURSE OF DEMOLITION AND CONSTRUCTION OF THE PROJECT.

STRUCTURAL DESIGN AND SPECIFICATIONS ASSUME THAT ALL SUPPORTING AND NON-SUPPORTING ELEMENTS IN CONTACT WITH FLOOR FRAMING ARE LEVEL, INCLUDING, BUT NOT LIMITED TO; FOUNDATIONS, SLABS ON GRADE, BEAMS, WALLS, AND NON-BEARING ELEMENTS. IT IS THE CONTRACTOR'S RESPONSIBILITY TO VERIFY LEVELNESS AND MAKE ADJUSTMENTS AS NECESSARY, INCLUDING CONSIDERATION OF THOSE AREAS THAT MAY BE WITHIN CONTRACTUAL, INDUSTRY, OR WARRANTY TOLERANCES.

ADDITIONAL NOTES FOR TRUSS & I-JOIST MANUFACTURER

ROOF TRUSS, FLOOR TRUSS AND ENGINEERED JOISTS SHALL BE DESIGNED TO MEET THE DIFFERENTIAL DEFLECTION CRITERIA BELOW, UNLESS NOTED OTHERWISE ON PLAN.
TRUSSES/JOISTS SHALL BE DESIGNED SO THAT DIFFERENTIAL DEFLECTION BETWEEN ADJACENT PARALLEL TRUSSES/JOISTS OR GIRDER TRUSSES/FLUSH BEAMS DO NOT EXCEED THE FOLLOWING:
A. ROOF TRUSSES:
1/4" DEAD LOAD
B. FLOOR TRUSSES, ATTIC TRUSSES, & I-JOISTS:
1/8" DEAD LOAD
C. FLOOR TRUSSES & ATTIC TRUSSES ADJACENT TO FLOOR FRAMING BY OTHERS.
LIMIT ABSOLUTE TRUSS DEFLECTION TO 3/16" DEAD LOAD. (NOT DIFFERENTIAL DEFLECTION)

HOLD-DOWN SCHEDULE


Table with 2 columns: SYMBOL, SPECIFICATION. Rows include HD-1 SIMPSON HTT4 HOLD-DOWN, HD-2 SIMPSON MSTC66 STRAP TIE, HD-3 SIMPSON 5THD14/14RJ HOLD-DOWN.

ALTERNATIVE TO 501824 ANCHOR BOLT SPECIFICATION:
UTILIZE SIMPSON "SET" EPOXY SYSTEM TO FASTEN 3/8" DIA. THREADED ROD INTO CONCRETE FOUNDATION. PROVIDE 12" MIN. EMBEDMENT INTO CONCRETE. INSTALL PER MANUF. RECOMMENDATIONS. DO NOT LOCATE ANCHORS WITHIN 1 3/4" OF EDGE OF FOUNDATION.

VENEER LINTEL SCHEDULE

Table with 3 columns: SPAN (MAX), HEIGHT OF VENEER ABOVE LINTEL, STEEL ANGLE SIZE. Rows include 3'-0", 6'-0", 8'-0", 9'-6", 16'-0".

ALL LITELS:
SHALL SUPPORT 2 3/4" - 3 1/2" VENEER W/ 40 PNF MAXIMUM HEIGHT.
16" SHALL HAVE 4" MIN BEARING
18" SHALL HAVE 6" MIN BEARING
20" SHALL NOT BE FASTENED BACK TO HEADER.
18" SHALL BE FASTENED BACK TO WOOD HEADER IN WALL @ 40" O.C. W/ 1/2" DIA. x 3 1/2" LONG LAG SCREWS IN 2" LONG VERTICALLY SLOTTED HOLES.
MAX VENEER HT. APPLIES TO ANY PORTION OF BRICK OVER THE OPENING.
ALL LITELS SHALL BE LONG LEG VERTICAL.
WHEN SUPPORTING VENEER < 3" WIDE THE EXTERIOR TOE OF THE HORIZONTAL LEG MAY BE CUT IN THE FIELD TO BE 3/4" WIDE OVER THE BEARING LENGTH ONLY. THIS IS TO ALLOW FOR MORTAR JOINT FINISHING.
SEE STRUCTURAL PLANS FOR ANY LINTEL CONDITION NOT ENCOMPASSED BY THE ABOVE PARAMETERS.
FOR GREEN VENEER USE L4x3x1/2".
FOR 3/2" VENEER ONLY. SEE PLAN FOR VENEER SUPPORT IF VENEER < 3/2" THICK.



MULHERN+KULP  
RESIDENTIAL STRUCTURAL ENGINEERING  
380 Roundtable Ave, Building 4 - Asheville, PA 18002  
P 215-946-8001 - mulhernkulp.com  
NC LIC. #C-3825


M&K project number:  
126-23047  
project mgr: JTR  
drawn by: SJF  
issue date: 02-15-24

REVISIONS:  
date: initial:



FOUNDATION PLANS  
HONEYCUT HILLS  
LOT 6 - NORRIS 5  
RALEIGH, NC


sheet:  
**S1.0**



LEGEND	
	INTERIOR BEARING WALL
	BEARING WALL ABOVE
	BEAM / HEADER
	INDICATES SHEAR WALL & EXTENT
	EXTENT OF OVERFRAMING
	M METAL HANGER
	* INDICATES POST ABOVE, PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
	INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.

REFER TO SO.0 FOR  
TYPICAL STRUCTURAL NOTES  
& SCHEDULES

**1 CRAWL SPACE FOUNDATION PLAN**  
SCALE: 1/8"=1'-0"



**MULHERN+KULP**  
RESIDENTIAL STRUCTURAL ENGINEERING  
380 Remondale Ave, Building 4 - Asheville, PA 18002  
P 716-946-8001 - mulhernkulp.com  
NC LIC. #C-3825


M&K project number:  
126-23047  
project mgr: JTR  
drawn by: SJF  
issue date: 02-15-24

REVISIONS:  
date: initial:



FLOOR FRAMING PLANS  
HONEYCUT HILLS  
LOT 6 - NORRIS 5  
RALEIGH, NC

sheet:  
**S2.0**




**1** FIRST FLOOR FRAMING PLAN - CRAWL SPACE  
SCALE: 1/8"=1'-0"

SD2.1 REFERS TO SD2.1A FOR LVL/PSL/LSL BEAMS OR SD2.1B FOR FLITCH BEAMS OR SD2.1C FOR STEEL BEAMS

**LEGEND**

- ▬ INTERIOR BEARING WALL
- - - BEARING WALL ABOVE
- BEAM / HEADER
- - - INDICATES SHEAR WALL & EXTENT
- ▨ EXTENT OF OVERFRAMING
- JL METAL HANGER
- \* INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
- ▶ INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.

REFER TO S0.0 FOR TYPICAL STRUCTURAL NOTES & SCHEDULES




M&K project number: 126-23047  
project mgr: JTR  
drawn by: SJF  
issue date: 02-15-24

REVISIONS:  
date: initial:



FLOOR FRAMING PLANS  
HONEYCUT HILLS  
LOT 6 - NORRIS 5  
RALEIGH, NC

sheet: **S3.0**



● CRWL + BASEMENT FOUNDATIONS: PPB44-6Z & PPBF44 POST BASES ARE ACCEPTABLE ALTERNATIVES TO ABW44Z POST BASE

**2ND FLOOR FRAMING PLAN**  
SCALE: 1/8"=1'-0"


LEGEND	
●	INTERIOR BEARING WALL
■	BEARING WALL ABOVE
—	BEAM / HEADER
---	INDICATES SHEAR WALL & EXTENT
■	EXTENT OF OVERFRAMING
JL	METAL HANGER
*	INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
▶	INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.

REFER TO SO.0 FOR TYPICAL STRUCTURAL NOTES & SCHEDULES

SD2.1 REFERS TO SD2.1A FOR LVL/PSL/LSL BEAMS OR SD2.1B FOR FLITCH BEAMS OR SD2.1C FOR STEEL BEAMS

ENGINEERED BEAM MATERIAL SCHEDULE					
BEAM NUMBER	LVL OPTION	PSL OPTION	LSL OPTION	FLITCH OPTION	STEEL OPTION
001	(3)3/4"x11/4" - H	5/4"x11/4" - H	(3)3/4"x11/8" - H	N/A	N/A
002	(2)1 3/4"x14" - F	3 1/2"x14" - F	(3)3/4"x14" - F	(2)2x12 + (1) 3/8"x9/16" STEEL FLITCH PLATES - F	W12x14 - F
003	(2)1 3/4"x9/4" - H	3 1/2"x9/4" - H	(2)3/4"x11/4" - H	(2)2x10 + (1) 3/8"x9/16" STEEL FLITCH PLATES - H	N/A
004	(2)1 3/4"x9/4" - H	3 1/2"x9/4" - H	(2)3/4"x11/4" - H	(2)2x10 + (1) 3/8"x9/16" STEEL FLITCH PLATES - H	N/A
005	(4)1 3/4"x10" - FT	7"x10" - FT	N/A	(3)2x12 + (2) 1"x11/4" STEEL FLITCH PLATES - F	W12x30 - F
006	(3)1 3/4"x14" - H	5/4"x11/4" - H	(3)3/4"x11/8" - H	N/A	N/A
007	(2)1 3/4"x14" - H	N/A	N/A	N/A	N/A

- BEAM NOTATION:  
- "F" INDICATES FLUSH BEAM  
- "FT" INDICATES FLUSH TOP BEAM  
- "FB" INDICATES FLUSH BOTTOM BEAM  
- "D" INDICATES DROPPED BEAM  
- "H" INDICATES DROPPED OPENING HEADER
- REFER TO DETAIL E1/SD2.0 FOR TYPICAL FLITCH BEAM CONNECTIONS
- REFER TO DETAIL E2/SD2.0 FOR TYPICAL STEEL BEAM CONNECTIONS
- FOR FLUSH TOP BEAMS PROVIDE 2X STACKED PLATES BENEATH BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3"x0.120" NAILS @ 8" O.C.
- FOR FLUSH BOTTOM BEAMS PROVIDE 2X STACKED PLATES ATOP BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3"x0.120" NAILS @ 8" O.C.



**MULHERN+KULP**  
RESIDENTIAL STRUCTURAL ENGINEERING  
380 Remondale Ave, Building 4 - Ardur, PA 15002  
P 717-946-8001 • mulhern+kulp.com  
NC LIC. #C-3825

M&K project number:  
126-23047  
project mgr: JTR  
drawn by: SJF  
issue date: 02-15-24


REVISIONS:

date:	initial:



ROOF FRAMING PLANS  
HONEYCUT HILLS  
LOT 6 - NORRIS 5  
RALEIGH, NC

sheet:  
**S4.0**




**1 ROOF FRAMING PLAN**  
SCALE: 1/8"=1'-0"

LEGEND	
	INTERIOR BEARING WALL
	BEARING WALL ABOVE
	BEAM / HEADER
	INDICATES SHEAR WALL & EXTENT
	EXTENT OF OVERFRAMING
	JL METAL HANGER
	* INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
	INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.


REFER TO SO.0 FOR  
TYPICAL STRUCTURAL NOTES  
& SCHEDULES

LETTERED DETAILS ARE TYPICAL FOR THIS HOME & SHALL BE IMPLEMENTED IN ALL APPLICABLE AREAS. THESE DETAILS ARE NOT "CUT" ON THE PLANS.


NUMBERED DETAILS ARE PLAN SPECIFIC AND ARE ONLY REQUIRED WHERE SPECIFICALLY INDICATED ("CUT") ON THE PLANS.




MULHERN+KULP  
RESIDENTIAL STRUCTURAL ENGINEERING  
380 Beardslee Ave, Building 4 - Asheville, PA 18002  
P 717-948-0801 - mulhern+kulp.com  
NC LIC. #C-3825




1 TYPICAL CRAWLSPACE FOUNDATION  
SCALE: 3/8"=1'-0"




2 TYPICAL CRAWLSPACE FOUNDATION  
SCALE: 3/8"=1'-0" W/ BRICK VENEER




3 TYPICAL GARAGE FOUNDATION  
SCALE: 3/8"=1'-0"




4 TYPICAL GARAGE FOUNDATION  
SCALE: 3/8"=1'-0" W/ BRICK VENEER




5 TYPICAL CRAWLSPACE FOUNDATION @ PORCH/PATIO SLAB  
SCALE: 3/8"=1'-0"  
(REFER TO DETAIL 12 FOR WOOD PORCH OPTION)




6 TYPICAL CRAWLSPACE FOUNDATION @ PORCH/PATIO SLAB  
SCALE: 3/8"=1'-0" W/ BRICK VENEER




7A TYP. FOOTING @ PORCH SLAB  
SCALE: 3/8"=1'-0"




7B TYP. FOOTING @ PORCH SLAB  
SCALE: 3/8"=1'-0" W/ BRICK VENEER




8 TYPICAL CRAWLSPACE FND. @ INTERIOR PIER  
SCALE: 3/8"=1'-0"




9 TYPICAL CRAWLSPACE FOUNDATION @ GARAGE  
SCALE: 3/8"=1'-0"




10 TYPICAL SLAB ON GRADE GARAGE ENTRY @ PERIMETER FOOTING  
SCALE: 3/8"=1'-0"




A GARAGE PORTAL FRAME STEM WALL REINFORCEMENT  
SCALE: 3/8"=1'-0"



11 TYPICAL CRAWLSPACE FOUNDATION @ WOOD PORCH/DECK W/ PIERS  
SCALE: 3/8"=1'-0"



12 TYPICAL CRAWLSPACE FOUNDATION @ WOOD PORCH/DECK  
SCALE: 3/8"=1'-0"



13 TYPICAL CRAWLSPACE FOUNDATION @ WOOD PORCH/DECK PERIMETER  
SCALE: 3/8"=1'-0"

PLAIN CONC. FOOTINGS AS DIMENSIONED & SHOWN ARE MINIMUM SIZES REQUIRED & HAVE BEEN ENGINEERED. ADDITION OF CONTINUOUS REBAR OR LARGER FOOTINGS MAY BE PROVIDED AT THE DISCRETION OF THE BUILDER.


FILE: RLH - Honeycutt Hills - Lot 6 - Structural DATE: 2/23/2024 12:14 PM

DRB HOMES

FOUNDATION DETAILS  
HONEYCUTT HILLS  
LOT 6 - NORRIS 5  
RALEIGH, NC

SD1.2





MULHERN+KULP  
RESIDENTIAL STRUCTURAL ENGINEERING  
380 Bainsville Ave, Building 4 - Asheville, PA 18002  
P 716-946-8801 • mulhern+kulp.com  
NC LIC. #C-3825


M&K project number:  
126-23047  
project mgr: JTR  
drawn by: SJF  
issue date: 02-15-24

REVISIONS:  
date: initial:


DRB  
HOMES

FRAMING DETAILS  
HONEYCUT HILLS  
LOT 6 - NORRIS 5  
RALEIGH, NC


sheet:  
SD2.0




**A1** TYPICAL SHEAR TRANSFER DETAIL @ ROOF  
SCALE: 3/8\"/>




**A2** TYPICAL SHEAR TRANSFER DETAIL @ ROOF  
SCALE: 3/8\"/>




**A3** TYPICAL SHEAR TRANSFER DETAIL @ RAISED HEEL TRUSS  
SCALE: 3/8\"/>




**B** TYPICAL GABLE END DETAIL  
SCALE: 3/8\"/>




**C1** TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ EXTERIOR WALL  
SCALE: 3/8\"/>




**C2** TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ EXTERIOR WALL  
SCALE: 3/8\"/>




**D** TYPICAL FLITCH BEAM CONNECTION DETAIL  
SCALE: 3/4\"/>



**E** TYPICAL STEEL BEAM CONNECTION DETAIL  
SCALE: 3/4\"/>





**F1** TYPICAL HOLD DOWN INSTALLATION  
SCALE: N.T.S.




**F2** TYPICAL CMU FOUNDATION HOLD-DOWN INSTALLATION  
SCALE: N.T.S. (CORNER SHOWN - APPLICABLE TO ALL CONDITIONS)

LETTERED DETAILS ARE TYPICAL FOR THIS HOME & SHALL BE IMPLEMENTED IN ALL APPLICABLE AREAS. THESE DETAILS ARE NOT "CUT" ON THE PLANS.


NUMBERED DETAILS ARE PLAN SPECIFIC AND ARE ONLY REQUIRED WHERE SPECIFICALLY INDICATED ("CUT") ON THE PLANS.




1 TYPICAL SHEAR TRANSFER DETAIL @ EXTERIOR WALL ABOVE SCALE: 3/4"=1'-0"




2 TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL SCALE: 3/4"=1'-0"




3 SHEAR TRANSFER DETAIL @ INTERSECTING INT. SHEARWALL SCALE: 3/4"=1'-0" SHTS. ON SAME PAGE




4 DECK LEDGER CONNECTION DETAIL SCALE: 3/4"=1'-0"




5 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE SCALE: 3/4"=1'-0"




6 SHEAR TRANSFER DETAIL @ CANT'D EXTERIOR WALL



7 SHEAR TRANSFER DETAIL BETWEEN FLOORS @ CANT'D EXT. WALL



8 TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL SCALE: 3/4"=1'-0" PERPENDICULAR FRAMING



9 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE SCALE: 3/4"=1'-0"

MULHERN+KULP RESIDENTIAL STRUCTURAL ENGINEERING 300 Riverside Ave., Building 4 - Asheville, PA 18002 P: 715-946-0001 M: mulhern@mkp.com NC LIC. #C-3825


M&K project number: 126-23047 project mgr: JTR drawn by: SJF issue date: 02-15-24

REVISIONS: date: initial:

DRB HOMES

FRAMING DETAILS HONEYCUT HILLS LOT 6 - NORRIS 5 RALEIGH, NC

sheet: SD2.1A



MULHERN+KULP  
RESIDENTIAL STRUCTURAL ENGINEERING  
380 Riverside Ave., Building 4 - Asheville, PA 18002  
P: 716-946-8001 | E: mulhern@mkp.com




M&K project number:  
126-23047  
project mgr: JTR  
drawn by: SJF  
issue date: 02-15-24

REVISIONS:  
date: initial:


DRB HOMES

FRAMING DETAILS  
HONEYCUT HILLS  
LOT 6 - NORRIS 5  
RALEIGH, NC


sheet:  
SD2.1B




1 TYPICAL SHEAR TRANSFER DETAIL @ EXTERIOR WALL ABOVE  
SCALE: 3/4"=1'-0"




2 TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL  
SCALE: 3/4"=1'-0"




3 SHEAR TRANSFER DETAIL @ INTERSECTING INT. SHEARWALL  
SCALE: 3/4"=1'-0" SHTS. ON SAME PAGE




4 DECK LEDGER CONNECTION DETAIL  
SCALE: 3/4"=1'-0"




5 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




6 SHEAR TRANSFER DETAIL @ CANT'D EXTERIOR WALL




7 SHEAR TRANSFER DETAIL BETWEEN FLOORS @ CANT'D EXT. WALL




8 TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL - PERPENDICULAR FRAMING  
SCALE: 3/4"=1'-0"




9 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




MULHERN+KULP  
RESIDENTIAL STRUCTURAL ENGINEERING  
380 Riverside Ave., Building 4 - Asheville, PA 18002  
P: 716-946-8001 - mulhern+kulp.com  
NC LIC. #C-3825




1 TYPICAL SHEAR TRANSFER DETAIL @ EXTERIOR WALL ABOVE  
SCALE: 3/4"=1'-0"




2 TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL  
SCALE: 3/4"=1'-0"




3 SHEAR TRANSFER DETAIL @ INTERSECTING INT. SHEARWALL  
SCALE: 3/4"=1'-0" SHTS. ON SAME PAGE




4 DECK LEDGER CONNECTION DETAIL  
SCALE: 3/4"=1'-0"




5 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




6 SHEAR TRANSFER DETAIL @ CANT'D EXTERIOR WALL



7 SHEAR TRANSFER DETAIL BETWEEN FLOORS @ CANT'D EXT. WALL



8 TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL PERPENDICULAR FRAMING  
SCALE: 3/4"=1'-0"



9 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"


M&K project number: 126-23047  
project mgr: JTR  
drawn by: SJF  
issue date: 02-15-24

REVISIONS:  
date: initial:



FRAMING DETAILS  
HONEYCUT HILLS  
LOT 6 - NORRIS 5  
RALEIGH, NC

sheet: SD2.1C



**MULHERN+KULP**  
RESIDENTIAL STRUCTURAL ENGINEERING  
380 Beaufort Ave, Building 4 - Asheville, PA 18002  
P 716-946-8001 - mulhern+kulp.com





M&K project number:  
126-23047  
project mgr: JTR  
drawn by: SJF  
issue date: 02-15-24

REVISIONS:  
date: initial:



**DRB**  
**HOMES**

FRAMING DETAILS  
HONEYCUT HILLS  
LOT 6 - NORRIS 5  
RALEIGH, NC

sheet:  
**SD2.2**




NOTE: ALL SHEATHABLE AREAS OF EXTERIOR WALL SHALL BE FULLY SHEATHED WITH 1/2" PLYWOOD OR 3/8" OSB



ALTERNATIVE TO 1/2" DIA. ANCHOR BOLT:  
1) 1/2" DIA. THREADED ROD EPOXY SET W/ 4 1/2" EMBED. (MIN) UTILIZING HILTI HY200 EPOXY ANCHORING SYSTEM (OR EQUAL)

TWO SIDED GARAGE PORTAL FRAME BRACING  
ELEVATION ON CMU STEM  
2 SCALE: N.T.S.



**MULHERN+KULP**  
RESIDENTIAL STRUCTURAL ENGINEERING  
380 Boushield Ave, Building 4 - Asheville, PA 18007  
P 716-946-0001 - mulhern+kulp.com







M&K project number:  
**126-23047**  
project mgr: **JTR**  
drawn by: **SJF**  
issue date: **02-15-24**


REVISIONS:  
date: initial:

**DRB**  
**HOMES**

FRAMING DETAILS  
**HONEYCUT HILLS**  
LOT 6 - NORRIS 5  
RALEIGH, NC

sheet:  
**SD3.0**





▲ = LEFT END OF TRUSS

REVISIONS:



Moncks Corner/Easley, SC (800) 475-3999  
 Sparta, NC (336) 372-2226

FOR PERMIT

Client: DRB GROUP-RALEIGH

Job: LOT 0.0006 HONEYCUTT HILL

Plan Information:

NORRIS-5

NOT TO SCALE

Drawn By: CGT

Date: 02/08/24


Job #: 24-1219-R01

Sales Rep: KYLE GIBSON

Phone:

ROOF

**WARNING!** Long span trusses, 60' or greater in length, require extreme care and experience for proper and safe handling and installation. For general handling and installation guidance, see the "Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses ("BCSI"), JOINTLY PRODUCED BY SBCA and TPI. For project specific guidance, consult with a registered design professional. ATLANTIC assumes no responsibility for the handling, installation or bracing of trusses.



**NOTE PLUMBING DROPS:**  
 PLUMBING SYMBOLS SHOWN ARE APPROXIMATE LOCATIONS ONLY.  
 TRUSSES HAVE ALREADY BEEN SHIFTED WHERE NEEDED.  
 BUILDER TO FIELD VERIFY ACTUAL LOCATIONS TO AVOID POSSIBLE  
 CONFLICTS WITH TRUSSES.  
 CLEAR DISTANCE FOR FLOOR DECKING NOT TO EXCEED 24".  
**\*\*\*FLOOR TRUSSES ARE NOT TO BE DRILLED OR CUT IN ANY WAY \*\*\***

**▲ = LEFT END OF TRUSS**  
**\*\*\*CAUTION MUST TAKEN TO ENSURE TRUSSES ARE NOT FLIPPED. MAINTAIN LEFT ENDS AS NOTED ON LAYOUT\*\*\***

**FOR PERMIT**

Client: DRB GROUP-RALEIGH  
 Job: LOT 0.0006 HONEYCUTT HILL  
 Plan Information: NORRIS-5

NOT TO SCALE  
 Drawn By: CGT  
 Date: 02/08/24  
 Job #: 24-1219-F01  
 Sales Rep: KYLE GIBSON  
 Phone: 864-304-3282

**▲ = LEFT END OF TRUSS**

REVISIONS:



Moncks Corner/Easley, SC (800) 475-3999  
 Sparta, NC (336) 372-2226




**NOTE PLUMBING DROPS:**  
 PLUMBING SYMBOLS SHOWN ARE APPROXIMATE LOCATIONS ONLY.  
 TRUSSES HAVE ALREADY BEEN SHIFTED WHERE NEEDED.

BUILDER TO FIELD VERIFY ACTUAL LOCATIONS TO AVOID POSSIBLE  
 CONFLICTS WITH TRUSSES.  
 CLEAR DISTANCE FOR FLOOR DECKING NOT TO EXCEED 24".

**\*\*\*FLOOR TRUSSES ARE NOT TO BE DRILLED OR CUT IN ANY WAY \*\*\***

Products					
Net Qty	Plies		Product	Length	PlotID
2	2	1-3/4" x 9-1/2"	VERSA-LAM@ 2.0 3100 SP	8' 0"	BM3-1
3	3	1-3/4" x 11-7/8"	VERSA-LAM@ 2.0 3100 SP	20' 0"	BM3-2
2	2	1-3/4" x 14"	VERSA-LAM@ 2.0 3100 SP	14' 0"	BM3-3

Truss Connector Total List			
Qty	Product	Manuf	
17	THA413	Simpson	
4	THA422		



▲ = LEFT END OF TRUSS


FOR PERMIT

Client: DRB GROUP-RALEIGH		FLOOR	
Job: LOT 0.0006 HONEYCUTT HILL			
Plan Information: NORRIS-5			
NOT TO SCALE	Date: 02/08/24	Job #:	Sales Rep: KYLE GIBSON
Drawn By: CGT			Phone: 864-304-3282

REVISIONS:



Moncks Corner/Easley, SC (800) 475-3999  
 Sparta, NC (336) 372-2226



▲ = LEFT END OF TRUSS

REVISIONS:



Moncks Corner/Easley, SC (800) 475-3999  
 Sparta, NC (336) 372-2226

FOR PERMIT

Client: DRB GROUP-RALEIGH  
 Job: LOT 0.0006 HONEYCUTT HILL  
 Plan Information:  
**NORRIS-5**  
 NOT TO SCALE  
 Drawn By: CGT  
 Date: 02/08/24  
 Job #: 24-1219-R01  
 Sales Rep: KYLE GIBSON  
 Phone: 864-304-3282

ROOF

**WARNING!** Long span trusses, 60' or greater in length, require extreme care and experience for proper and safe handling and installation. For general handling and installation guidance, see the "Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses ("BCSI"), JOINTLY PRODUCED BY SBCA and TPI. For project specific guidance, consult with a registered design professional. ATLANTIC assumes no responsibility for the handling, installation or bracing of trusses.