


1. All bracing, blocking, beams, purlins @ 2'0" o.c., ledger, etc. provided by others.
2. Roof truss to roof truss connections provided by Riverside Roof Truss.
3. Truss to building connections provided by others.


Refer to Sealed drawings for connection detail of multiple ply trusses.

NOT ALL TRUSSES ARE SYMMETRICAL AND MAY NOT PERFORM CORRECTLY IF INSTALLED BACKWARDS. PLEASE REFER TO SEALS WHILE SETTING TRUSSES TO ENSURE TRUSSES ARE ORIENTED CORRECTLY



SHOP DRAWING APPROVAL
 THIS LAYOUT IS THE SOLE SOURCE FOR FABRICATION OF TRUSSES AND VOIDS ALL PREVIOUS ARCHITECTURAL OR OTHER TRUSS LAYOUTS. REVIEW AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TRUSSES WILL BE BUILT. VERIFY ALL CONDITIONS TO INSURE AGAINST CHANGES THAT WILL RESULT IN EXTRA CHARGES TO YOU.

REVIEWED BY: _____ APPROVED BY: _____ DATE: _____



Products				
PlotID	Length	Product	Plies	Net Qty
FJ40	40-00-00	14" NI-40x	1	19
FJ28	28-00-00	14" NI-40x	1	1
FJ22	22-00-00	14" NI-40x	1	1
FJ22-2	22-00-00	14" NI-40x	2	2
FJ20	20-00-00	14" NI-40x	1	3
FJ14	14-00-00	14" NI-40x	1	1
FJ10	10-00-00	14" NI-40x	1	3
FJ8-2	8-00-00	14" NI-40x	2	2
FJ6	6-00-00	14" NI-40x	1	2
FJ4	4-00-00	14" NI-40x	1	10
WHBM1	10-00-00	1 3/4" x 9 1/4" (2.0E 3100) LVL	2	2
WHBM34	10-00-00	1 3/4" x 9 1/4" (2.0E 3100) LVL	2	2
WHBM33	8-00-00	1 3/4" x 9 1/4" (2.0E 3100) LVL	2	2
BM30	6-00-00	1 3/4" x 14" (2.0E 3100) LVL	1	1
BM28	22-00-00	1 3/4" x 23 7/8" LVL	4	4
GDHBM6	20-00-00	1 3/4" x 23 7/8" LVL	2	2
RIM1	12-00-00	1 1/8" x 14" APA Rim Board	1	11
Bk1	29-00-00	14" NI-40x	1	1

Connector Summary		
Qty	Manuf	Product
1	Simpson	HUS1.81/10
3	Simpson	IUS2.56/14
1	Simpson	IUS2.56/14
15	Simpson	IUS2.56/14

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, columns, and sufficient blocking in floor cavity under point loads is the responsibility of the building designer. For general guidance regarding bracing, consult "Bracing of Wood Trusses" available from the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53179.

Hanger Conversion Chart

USP	Simpson
JUS26	LUS26
THD26	HUS26
THD26-2	HHUS26-2
HJC26	THJA26
MSH422	THA422

Client: **MATTAMY HOMES**

Job Name: **TETON FRENCH COUNTRY**

Model: **EWP 2ND FLOOR**

Lot #: _____

Order #: **24-4246-B**

Designer: **R S**

Date: **8/7/2024**

Sales Rep: **C Walden**

733 RIVER PARK DRIVE
DANVILLE, VA 24540
(434) 793-0217
FAX: (434) 799-8767

RIVERSIDE ROOF TRUSS, LLC

Roof Surface Area: **0 ft² Sq. Ft.**
 Floor Surface Area: **9793 ft² Sq. Ft.**

