

Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 52104

JOB: 24-7417-F01

JOB NAME: LOT 0.0036 HONEYCUTT HILLS

Wind Code: N/A

Wind Speed: Vult= N/A

Exposure Category: N/A

Mean Roof Height (feet): N/A

These truss designs comply with IRC 2015 as well as IRC 2018.

30 Truss Design(s)

Trusses:

F1-01, F1-02, F1-03, F1-04, F1-05, F1-06, F1-08, F1-09, F1-10, F1-11, F1-12, F1-12A, F1-13, F1-14, F1-15, F1-19, F1-20, F1-21, F1-22, F1-23, F1-24, F1-25, F1-26, F1-27, F1-28, F1-29, F1-



9/6/2024

Mark Morris

Warning !—Verify design parameters and read notes before use.

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSL/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI

Job 24-7417-F01	Truss F1-01	Truss Type Floor Supported Gable	Qty 1	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 52104
--------------------	----------------	-------------------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:56:58 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-UxXkPKyrdz8PFr_YhY56sZdV7ZlqSqCKHHsrZByfwEZ

0₁-8

Scale = 1:21.5




Plate Offsets (X,Y)-- [5:0-1-8,Edge], [17:0-1-8,Edge], [22:Edge,0-1-8]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.06	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 12 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH		Weight: 55 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 13-1-12.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 22, 12, 21, 20, 19, 18, 17, 16, 15, 14, 13

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (6)
- Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION. Do not erect truss backwards.

LOAD CASE(S) Standard






9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-02	Truss Type Floor	Qty 5	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC	# 52104
--------------------	----------------	---------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:56:59 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-z856dggzTOGGGt_ZkFFcLOmAbFzVvkB8cUWxcO5dyfWEY



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.35	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.54	Vert(LL) -0.12 11 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.53	Vert(CT) -0.17 11 >938 360		
BCDL 5.0	Rep Stress Incr NO	Matrix-SH	Horz(CT) 0.03 8 n/a n/a		
	Code IRC2021/TPI2014			Weight: 66 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 14=703/0-7-8 (min. 0-1-8), 8=1109/0-4-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 14-15=-698/0, 1-15=-696/0, 7-8=-1102/0, 1-2=-940/0, 2-3=-2158/0, 3-4=-2605/0, 4-5=-2605/0, 5-6=-2166/0, 6-7=-950/0
BOT CHORD 12-13=0/1759, 11-12=0/2521, 10-11=0/2523, 9-10=0/1772
WEBS 1-13=0/1070, 2-13=-1000/0, 2-12=0/487, 3-12=-443/0, 5-10=-436/0, 6-10=0/481, 6-9=-1004/0, 7-9=0/1121



NOTES- (4)
1) Load case(s) 1, 2 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
3) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 8-14=-10, 1-7=-100
Concentrated Loads (lb)
Vert: 7=-400
2) Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 8-14=-10, 1-7=-100
Concentrated Loads (lb)
Vert: 7=-400



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



1-4-8	1-6-0	2-10-8	5-4-8	10-6-0	13-0-0	14-1-12
1-4-8	0-1-8	1-4-8	2-6-0	5-1-8	2-6-0	1-1-12
Plate Offsets (X,Y)-- [1:Edge,0-1-8], [2:0-3-0,Edge], [16:Edge,0-1-8]						

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL. in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.59	Vert(LL) -0.07	12	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.34	Vert(CT) -0.10	12	>999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.58	Horz(CT) 0.01	9	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH					
							Weight: 73 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
WEBS 2x4 SP No.3(flat)	6-0-0 oc bracing: 15-16,14-15.

REACTIONS. (lb/size) 16=-964/1-7-8 (min. 0-1-8), 9=575/0-4-8 (min. 0-1-8), 15=1911/1-7-8 (min. 0-1-8)
Max Uplift16=-1011(LC 4)
Max Grav9=575(LC 4), 15=1911(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 16-17=0/1005, 1-17=0/1003, 8-9=-572/0, 1-2=0/1536, 2-3=0/514, 3-4=-954/0, 4-5=-1670/0, 5-6=-1670/0, 6-7=-1498/0, 7-8=-564/0
BOT CHORD 14-15=-1536/0, 13-14=0/413, 12-13=0/1456, 11-12=0/1734, 10-11=0/1227
WEBS 2-15=-891/0, 1-15=-1760/0, 2-14=0/1213, 3-14=-1129/0, 3-13=0/663, 4-13=-615/0, 4-12=0/257, 6-11=-288/0, 7-11=0/332, 7-10=-809/0, 8-10=0/743

- NOTES-** (6)
- Unbalanced floor live loads have been considered for this design.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 1011 lb uplift at joint 16.
 - This truss has large uplift reaction(s) from gravity load case(s). Proper connection is required to secure truss against upward movement at the bearings. Building designer must provide for uplift reactions indicated.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-05	Floor Supported Gable	1	1	Job Reference (optional) # 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:00 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-RKfVq0z59aO6U87xpy7ax_jrcNzlwjldLbLyd3yfwEX

0-1-8

Scale = 1:23.2




Plate Offsets (X,Y)-- [6:0-1-8,Edge], [18:0-1-8,Edge], [24:Edge,0-1-8]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.06	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 13 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			Weight: 59 lb FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)
 OTHERS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 14-1-12.
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 24, 13, 23, 22, 21, 20, 19, 18, 17, 16, 15, 14

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (6)
 1) Gable requires continuous bottom chord bearing.
 2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 3) Gable studs spaced at 1-4-0 oc.
 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 5) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-06	Truss Type GABLE	Qty 1	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 52104
--------------------	----------------	---------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:00 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-RKFVq0z59aO6U87xpy7ax_jqDNzGwjcdLbLyd3yfwEX

Scale = 1:12.7




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [3:0-1-8,Edge], [9:0-1-8,Edge], [12:Edge,0-1-8]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.08	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.04	Horz(CT) -0.00 9 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-P			
				Weight: 32 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-11-12 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 6-11-12.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 12, 7, 11, 10, 9, 8

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (5)
- Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-08	Floor	3	1	
					# 52104


Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:01 2024 Page 1
 ID:5fxLxLn?C6dWjia?SHK4thzkcYl-vWct2M_jwuWz6li7MgepTBFxqnFGf4inzF5V9WytwEW

1-3-0

1-4-8

0-10-10

Scale = 1:37.9



LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.35	Vert(LL)	-0.06	22	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.28	Vert(CT)	-0.08	22	>999	360		
BCLL 0.0	Rep Stress Incr	NO	WB 0.43	Horz(CT)	0.01	18	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH							
										Weight: 115 lb FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 25=384/0-7-8 (min. 0-1-8), 12=641/0-4-6 (min. 0-1-8), 18=1653/0-4-8 (min. 0-1-8)
 Max Grav 25=405(LC 3), 12=702(LC 4), 18=1653(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-25=-400/0, 11-12=-700/0, 1-2=-517/0, 2-3=-1144/0, 3-4=-1217/0, 4-5=-1217/0, 5-6=-750/59, 6-7=0/514, 7-8=0/779,
 8-9=-544/384, 9-10=-676/123, 10-11=-278/10
 BOT CHORD 23-24=0/969, 22-23=0/1296, 21-22=0/1111, 20-21=0/1111, 19-20=-210/380, 18-19=-1296/0, 17-18=-1305/0,
 16-17=-567/339, 15-16=-567/339, 14-15=-228/724, 13-14=-42/604
 WEBS 7-18=-1624/0, 1-24=0/613, 2-24=-551/0, 5-20=-474/0, 6-20=0/491, 6-19=-793/0, 7-19=0/907, 7-17=0/704, 8-17=-653/0,
 8-15=0/363, 9-15=-331/0, 10-13=-397/39, 11-13=-14/368

NOTES- (5)
 1) Unbalanced floor live loads have been considered for this design.
 2) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 4) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 12-25=-7, 1-11=-67
 Concentrated Loads (lb)
 Vert: 7=-600 11=-400
 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 12-25=-7, 1-11=-67
 Concentrated Loads (lb)
 Vert: 7=-600 11=-400
 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 12-25=-7, 1-7=-67, 7-11=-13
 Concentrated Loads (lb)
 Vert: 7=-600 11=-400



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-08	Floor	3	1	Job Reference (optional) # 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:01 2024 Page 2
ID:5fxLxLn?C6dWjia?SHK4thzkYl-vWCt2M_jwuWz6li7MgepTBFxqnFGf4inzF5V9WyfwEW

LOAD CASE(S) Standard

4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 12-25=-7, 1-7=-13, 7-11=-67

Concentrated Loads (lb)

Vert: 7=-600 11=-400

5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 12-25=-7, 1-7=-67, 7-11=-13

Concentrated Loads (lb)

Vert: 7=-600 11=-400

6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 12-25=-7, 1-7=-13, 7-11=-67

Concentrated Loads (lb)

Vert: 7=-600 11=-400




9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-09	Truss Type Floor Supported Gable	Qty 1	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 52104
--------------------	----------------	-------------------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:01 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-vWCt2M_jwuWz6li7MgepTBF?DnJWfAwnzF5V9WyfwEW

Scale = 1:37.3



22-9-2
22-9-2

Plate Offsets (X,Y)-- [1:Edge,0-1-8], [10:0-1-8,Edge], [29:0-1-8,Edge], [38:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.07	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	26	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 92 lb	FT = 20%F, 11%E

LUMBER-

TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING-

TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

All bearings 22-9-2.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 38, 20, 37, 36, 35, 34, 33, 32, 31, 30, 29, 28, 26, 25, 24, 23, 22, 21

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (5)

- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-10	Floor	6	1	
Job Reference (optional)					# 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:02 2024 Page 1
 ID:5fxLxLn?C6dWjia?SHK4thzkcYI-NjmFFi?MhBfqkSHJwN920PoyZAb5OWYwCuq3iyfWfEV





Plate Offsets (X,Y)-- [25:Edge,0-1-8]	
1-6-0	4-0-0
1-6-0	2-6-0
6-6-0	2-6-0
9-1-8	2-7-8
11-7-8	2-6-0
13-1-8	1-6-0
14-6-0	1-4-8
17-0-0	2-6-0
19-6-0	2-6-0
22-0-0	2-6-0
23-1-12	1-1-12

LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.99	Vert(LL)	-0.06	22	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.31	Vert(CT)	-0.07	22	>999	360		
BCLL 0.0	Rep Stress Incr	NO	WB 0.46	Horz(CT)	0.01	12	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH							
Weight: 115 lb FT = 20%F, 11%E										

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-8-11 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 25=363/0-7-8 (min. 0-1-8), 12=427/0-4-8 (min. 0-1-8), 18=1820/0-4-8 (min. 0-1-8)
 Max Grav 25=384(LC 3), 12=489(LC 4), 18=1820(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 25-26=-380/0, 1-26=-380/0, 11-12=-486/0, 1-2=-493/0, 2-3=-1070/0, 3-4=-1095/0, 4-5=-1095/0, 5-6=-578/232,
 6-7=0/732, 7-8=0/803, 8-9=-981/0, 9-27=-1297/0, 10-27=-1297/0, 10-11=-525/0
 BOT CHORD 23-24=0/917, 22-23=0/1198, 21-22=-72/965, 20-21=-72/965, 19-20=-409/183, 18-19=-1537/0, 17-18=-1546/0,
 16-17=-392/513, 15-16=-392/513, 14-15=0/1424, 13-14=0/1149
 WEBS 7-18=-1788/0, 1-24=0/560, 2-24=-518/0, 5-20=-505/0, 6-20=0/522, 6-19=-819/0, 7-19=0/932, 7-17=0/961, 8-17=-896/0,
 8-15=0/683, 9-15=-651/0, 10-13=-762/0, 11-13=0/691

- NOTES-** (5)
 1) Unbalanced floor live loads have been considered for this design.
 2) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 4) CAUTION, Do not erect truss backwards.

- LOAD CASE(S)**
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 12-25=-7, 1-11=-67
 Concentrated Loads (lb)
 Vert: 7=-600 27=-335
 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 12-25=-7, 1-11=-67
 Concentrated Loads (lb)
 Vert: 7=-600 27=-335
 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 12-25=-7, 1-7=-67, 7-11=-13
 Concentrated Loads (lb)
 Vert: 7=-600 27=-335



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-10	Floor	6	1	Job Reference (optional) # 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:02 2024 Page 2
 ID:5fxLxLn?C6dWjia?SHK4thzkcYI-NjmFFi?MhBfqkSHJwN920PoyZAb5OWYwCuq3iyfwEV

LOAD CASE(S)

- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 12-25=-7, 1-7=-13, 7-11=-67
 - Concentrated Loads (lb)
 - Vert: 7=-600 27=-335
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 12-25=-7, 1-7=-67, 7-11=-13
 - Concentrated Loads (lb)
 - Vert: 7=-600 27=-335
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 12-25=-7, 1-7=-13, 7-11=-67
 - Concentrated Loads (lb)
 - Vert: 7=-600 27=-335



9/6/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-11	Truss Type Floor	Qty 3	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC	# 52104
--------------------	----------------	---------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:03 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-rvKdT20_SVnhLcsWU5gHZcLiyay77_B4RYacEOyfwEU





Plate Offsets (X,Y)-- [25:Edge,0-1-8]

LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.31	Vert(LL)	-0.06	22	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.25	Vert(CT)	-0.08	22	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.43	Horz(CT)	0.01	18	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH							
									Weight: 115 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 25=380/0-7-8 (min. 0-1-8), 12=241/0-4-8 (min. 0-1-8), 18=1054/0-4-8 (min. 0-1-8)
Max Grav 25=400(LC 3), 12=303(LC 4), 18=1054(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 25-26=-397/0, 1-26=-396/0, 11-12=-301/0, 1-2=-519/0, 2-3=-1143/0, 3-4=-1216/0, 4-5=-1216/0, 5-6=-748/62,
6-7=0/516, 7-8=0/778, 8-9=-545/384, 9-10=-678/123, 10-11=-281/10
BOT CHORD 23-24=0/967, 22-23=0/1295, 21-22=0/1109, 20-21=0/1109, 19-20=-213/379, 18-19=-1300/0, 17-18=-1306/0,
16-17=-566/339, 15-16=-566/339, 14-15=-228/726, 13-14=-42/607
WEBS 7-18=-1027/0, 1-24=0/589, 2-24=-547/0, 5-20=-475/0, 6-20=0/491, 6-19=-793/0, 7-19=0/909, 7-17=0/706, 8-17=-653/0,
8-15=0/363, 9-15=-332/0, 10-13=-397/39, 11-13=-13/371

NOTES- (4)
1) Unbalanced floor live loads have been considered for this design.
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
3) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard




9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-12	Truss Type Floor	Qty 2	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC	# 52104
--------------------	----------------	---------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:03 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-rvKdT20_SVnhLcsWU5gHZcLH_axq7zu4RYacEOyfwEU



Scale = 1:38.0




Plate Offsets (X,Y)-- [14:Edge,0-1-8], [27:Edge,0-1-8]					
LOADING (psf)	SPACING- 1-4-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.37	Vert(LL) -0.06 24 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.27	Vert(CT) -0.08 24 >999 360		
BCLL 0.0	Rep Stress Incr NO	WB 0.45	Horz(CT) 0.01 14 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
				Weight: 119 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 27=379/0-4-8 (min. 0-1-8), 20=1121/0-4-8 (min. 0-1-8), 14=1049/0-4-8 (min. 0-1-8)
Max Grav 27=400(LC 3), 20=1121(LC 1), 14=1111(LC 4)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-27=-395/0, 1-2=-509/0, 2-3=-1122/0, 3-4=-1180/0, 4-5=-1180/0, 5-6=-698/127, 6-7=0/582, 7-8=0/802, 8-9=-718/224, 9-10=-718/224, 10-11=-978/0, 11-12=-672/0
BOT CHORD 25-26=0/954, 24-25=0/1266, 23-24=0/1066, 22-23=0/1066, 21-22=-288/322, 20-21=-1408/0, 19-20=-1417/0, 18-19=-513/394, 17-18=-513/394, 16-17=0/960, 15-16=0/968, 14-15=0/672
WEBS 7-20=-1093/0, 1-26=0/604, 2-26=-542/0, 5-22=-483/0, 6-22=0/499, 6-21=-804/0, 7-21=0/948, 7-19=0/804, 8-19=-744/0, 8-17=0/514, 10-17=-399/0, 11-15=-338/154, 12-14=-1277/0

- NOTES-** (5)
1) Unbalanced floor live loads have been considered for this design.
2) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
4) CAUTION, Do not erect truss backwards.

- LOAD CASE(S)** Standard
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-27=-7, 1-13=-67
Concentrated Loads (lb)
Vert: 12=-865
2) Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-27=-7, 1-13=-67
Concentrated Loads (lb)
Vert: 12=-865
3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-27=-7, 1-7=-67, 7-13=-13
Concentrated Loads (lb)
Vert: 12=-865



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-12	Floor	2	1	Job Reference (optional) # 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:03 2024 Page 2
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-rvKdT20_SVnhLcsWU5gHZcLH_axq7zu4RYacEOyfwEU

LOAD CASE(S) Standard

4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 14-27=-7, 1-7=-13, 7-13=-67

Concentrated Loads (lb)

Vert: 12=-865

5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 14-27=-7, 1-7=-67, 7-13=-13

Concentrated Loads (lb)

Vert: 12=-865

6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 14-27=-7, 1-7=-13, 7-13=-67

Concentrated Loads (lb)

Vert: 12=-865



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-12A	Truss Type Floor	Qty 7	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 52104
--------------------	-----------------	---------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:04 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-J5u?gN1cDpvYzmRi2oCW5qtQ9_FxsOUDgCJ9mqyfWET

0-3-8
0-4-0
Scale = 1:38.0




Plate Offsets (X,Y)-- [13:Edge,0-1-8], [28:Edge,0-1-8]

LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.47	Vert(LL)	-0.06	25	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.41	Vert(CT)	-0.08	16-17	>999		
BCLL 0.0	Rep Stress Incr	NO	WB 0.62	Horz(CT)	0.01	13	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 120 lb	FT = 20%F, 11%E

LUMBER-

TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat) *Except*
W2: 2x4 SP No.2(flat)

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 28=331/0-4-8 (min. 0-1-8), 21=1926/0-4-8 (min. 0-1-8), 13=1223/0-4-8 (min. 0-1-8)
Max Grav 28=351(LC 3), 21=1926(LC 1), 13=1286(LC 4)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-28=-347/0, 1-2=-434/0, 2-3=-910/37, 3-4=-831/245, 4-5=-831/245, 5-6=-206/614,
6-7=0/1210, 7-8=-332/338, 8-9=-1881/0, 9-10=-1676/0, 10-11=-963/0
BOT CHORD 26-27=0/810, 25-26=-119/986, 24-25=-400/646, 23-24=-400/646, 22-23=-845/0,
21-22=-2109/0, 20-21=-2124/0, 19-20=-2124/0, 18-19=0/1823, 17-18=0/1823, 16-17=0/1904,
15-16=0/1426, 14-15=0/770, 13-14=0/770
WEBS 7-21=-1879/0, 1-27=0/515, 2-27=-459/2, 5-25=0/258, 5-23=-568/0, 6-23=0/585,
6-22=-889/0, 7-22=0/1031, 7-19=0/2200, 8-19=-1960/0, 9-16=-278/0, 10-16=0/304,
10-15=-565/0, 11-15=0/416, 11-13=-1462/0

NOTES- (5)

- Unbalanced floor live loads have been considered for this design.
- Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.

LOAD CASE(S)

- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-28=-7, 1-12=-67
Concentrated Loads (lb)
Vert: 8=-932 11=-865
- Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-28=-7, 1-12=-67
Concentrated Loads (lb)
Vert: 8=-932 11=-865
- 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-28=-7, 1-7=-67, 7-12=-13



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-12A	Floor	7	1	Job Reference (optional) # 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:04 2024 Page 2
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-J5u?gN1cDpvYzmRi2oCW5qtQ9_FxsOUDgCJ9mqyfwET

LOAD CASE(S)

- Concentrated Loads (lb)
Vert: 8=-932 11=-865
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-28=-7, 1-7=-13, 7-12=-67
Concentrated Loads (lb)
Vert: 8=-932 11=-865
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-28=-7, 1-7=-67, 7-12=-13
Concentrated Loads (lb)
Vert: 8=-932 11=-865
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-28=-7, 1-7=-13, 7-12=-67
Concentrated Loads (lb)
Vert: 8=-932 11=-865



9/6/2024


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-19	GABLE	1	1	
					# 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:05 2024 Page 1
 ID:5fxLxLn?C6dWjia?SHK4thzkcY1-nISOtj1E_61Pbv0ubWjle1QiLgTb_xMus3jJHyfwES

0-1-8

Scale = 1:22.9



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Lumber DOL 1.00	WB 0.03	Horz(CT)	0.00	13	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH						
	Code IRC2021/TPI2014						Weight: 59 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 13-11-8.
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 24, 13, 23, 22, 21, 20, 19, 18, 17, 16, 15, 14

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (6)
- Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION. Do not erect truss backwards.

LOAD CASE(S) Standard




9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-21	Floor Girder	1	1	
					# 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:05 2024 Page 1
 ID:5fxLxLn?C6dWjia?SHK4thzkcY1-nISOtj1E_61Pbv0ubWjle1QZ8OSwbnUMus3jJHyfWES



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.58	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.94	Vert(LL) -0.29 12-13 >582 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.96	Vert(CT) -0.36 12-13 >471 360		
BCDL 5.0	Rep Stress Incr NO	Matrix-SH	Horz(CT) 0.05 8 n/a n/a		
	Code IRC2021/TPI2014				Weight: 112 lb FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat) *Except*
 W2: 2x4 SP No.2(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 17=1444/0-7-8 (min. 0-1-8), 8=1447/0-4-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-17=-1420/0, 7-8=-1434/0, 1-2=-2401/0, 2-3=-6230/0, 3-18=-7839/0, 4-18=-7839/0, 4-19=-7716/0, 5-19=-7716/0, 5-6=-5453/0, 6-7=-1493/0
 BOT CHORD 15-16=0/4497, 14-15=0/7313, 13-14=0/7314, 12-13=0/8289, 11-12=0/7252, 10-11=0/7255, 9-10=0/3697
 WEBS 3-13=0/602, 4-13=-525/0, 4-12=-669/0, 5-12=0/614, 5-10=-2063/0, 6-10=0/2048, 6-9=-2571/0, 7-9=0/2008, 1-16=0/2716, 2-16=-2445/0, 2-15=0/2022, 3-15=-1481/0

NOTES- (6)
 1) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 2) CAUTION. Do not erect truss backwards.
 3) Use Simpson Strong-Tie THA422 (6-16d Girder, 6-10d Truss) or equivalent spaced at 1-7-3 oc max. starting at 4-9-4 from the left end to 9-5-12 to connect truss(es) F1-24 (1 ply 2x4 SP), F1-23 (1 ply 2x4 SP), F1-22 (1 ply 2x4 SP) to back face of top chord.
 4) Fill all nail holes where hanger is in contact with lumber.
 5) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 8-17=-10, 1-7=-100
 Concentrated Loads (lb)
 Vert: 3=-425(B) 5=-447(B) 18=-236(B) 19=-236(B)




9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-22	Truss Type Floor Girder	Qty 1	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC	# 52104
--------------------	----------------	----------------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:05 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-nlSOtj1E_61Pbv0ubWjle1QbROdmbt3Mus3jJHyfWES



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL. in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.50	Vert(LL) -0.03	8	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.24	Vert(CT) -0.03	8	>999		
BCLL 0.0	Rep Stress Incr	NO	WB 0.47	Horz(CT) 0.01	6	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH					
							Weight: 51 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 6=528/Mechanical, 10=1370/0-8-0 (min. 0-1-8)
Max Grav6=547(LC 4), 10=1370(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 5-6=-543/0, 1-2=0/623, 3-16=-994/0, 4-16=-994/0, 4-17=-517/0, 5-17=-517/0
BOT CHORD 10-11=-902/0, 9-10=-871/0, 8-9=0/863, 7-8=0/1088
WEBS 2-10=-1320/0, 1-11=-749/0, 2-11=0/489, 2-9=0/990, 3-9=-929/0, 4-7=-697/0, 5-7=0/665

- NOTES-** (9)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) Refer to girder(s) for truss to truss connections.
 - 3) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.
 - 6) Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent spaced at 2-0-0 oc max. starting at 4-1-4 from the left end to 8-1-4 to connect truss(es) F1-27 (1 ply 2x4 SP) to back face of top chord.
 - 7) Fill all nail holes where hanger is in contact with lumber.
 - 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

- LOAD CASE(S)** Standard
- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 6-12=-10, 1-2=-190(F=-90), 2-5=-100
Concentrated Loads (lb)
Vert: 1=-264 15=-144(B) 16=-144(B) 17=-144(B)
 - 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 6-12=-10, 1-2=-190(F=-90), 2-5=-100
Concentrated Loads (lb)
Vert: 1=-264 15=-144(B) 16=-144(B) 17=-144(B)
 - 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 6-12=-10, 1-2=-190(F=-90), 2-5=-20
Concentrated Loads (lb)
Vert: 1=-264 15=-224(B) 16=-224(B) 17=-224(B)



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-22	Floor Girder	1	1	Job Reference (optional) # 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:05 2024 Page 2
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-nlSOtj1E_61Pbv0ubWjle1QbROdmbt3Mus3jJHyfwES

LOAD CASE(S) Standard

4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 6-12=-10, 1-2=-110(F=-90), 2-5=-100

Concentrated Loads (lb)

Vert: 1=-264 15=-144(B) 16=-144(B) 17=-144(B)

5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 6-12=-10, 1-2=-190(F=-90), 2-5=-20

Concentrated Loads (lb)

Vert: 1=-264 15=-224(B) 16=-224(B) 17=-224(B)

6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 6-12=-10, 1-2=-110(F=-90), 2-5=-100

Concentrated Loads (lb)

Vert: 1=-264 15=-144(B) 16=-144(B) 17=-144(B)





9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-23	Truss Type Floor Special	Qty 2	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC	Job Reference (optional) # 52104
--------------------	----------------	-----------------------------	----------	----------	--	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:06 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-FU0m532slQ9GC3b59DE?AFzncno_ZKNrW7WoGryfwER



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.35	Vert(LL)	-0.02	8	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.14	Vert(CT)	-0.02	8	>999		
BCLL 0.0	Rep Stress Incr	NO	WB 0.31	Horz(CT)	0.00	6	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 51 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 6=317/Mechanical, 10=976/0-8-0 (min. 0-1-8)
Max Grav 6=336(LC 4), 10=976(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 5-6=-332/0, 1-2=0/522, 2-3=0/501, 3-4=-546/145, 4-5=-297/2
BOT CHORD 10-11=-763/0, 9-10=-745/0, 8-9=-296/443, 7-8=-33/611
WEBS 2-10=-940/0, 1-11=-627/0, 2-11=0/423, 2-9=0/650, 3-9=-598/0, 4-7=-384/38, 5-7=-3/381

- NOTES-** (6)
- Unbalanced floor live loads have been considered for this design.
 - Refer to girder(s) for truss to truss connections.
 - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.

- LOAD CASE(S)** Standard
- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 6-12=-10, 1-5=-100
Concentrated Loads (lb)
Vert: 1=-264
 - Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 6-12=-10, 1-5=-100
Concentrated Loads (lb)
Vert: 1=-264
 - 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 6-12=-10, 1-2=-100, 2-5=-20
Concentrated Loads (lb)
Vert: 1=-264
 - 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 6-12=-10, 1-2=-20, 2-5=-100



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-23	Floor Special	2	1	Job Reference (optional) # 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:06 2024 Page 2
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-FU0m532slQ9GC3b59DE?AFznco_ZKNrW7WoGrjyfwER

LOAD CASE(S) Standard

- Concentrated Loads (lb)
Vert: 1=-264
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 6-12=-10, 1-2=-100, 2-5=-20
Concentrated Loads (lb)
Vert: 1=-264
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 6-12=-10, 1-2=-20, 2-5=-100
Concentrated Loads (lb)
Vert: 1=-264




9/6/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-24	Truss Type Floor Girder	Qty 1	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 52104
--------------------	----------------	----------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:06 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-FU0m532slQ9GC3b59DE?AFzkooz3KKLW7WoGrjyfwER



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL. in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.53	Vert(LL) -0.03	8	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.24	Vert(CT) -0.03	8	>999		
BCLL 0.0	Rep Stress Incr	NO	WB 0.47	Horz(CT) 0.01	6	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH					
							Weight: 51 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 6=506/Mechanical, 10=1382/0-8-0 (min. 0-1-8)
Max Grav 6=525(LC 4), 10=1382(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 5-6=-521/0, 1-2=0/616, 3-16=-984/0, 4-16=-984/0, 4-17=-508/0, 5-17=-508/0
BOT CHORD 10-11=-891/0, 9-10=-859/0, 8-9=0/862, 7-8=0/1068
WEBS 2-10=-1332/0, 1-11=-740/0, 2-11=0/483, 2-9=0/985, 3-9=-924/0, 4-7=-684/0, 5-7=0/653

- NOTES-** (9)
- Unbalanced floor live loads have been considered for this design.
 - Refer to girder(s) for truss to truss connections.
 - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent spaced at 2-0-0 oc max. starting at 3-9-12 from the left end to 7-9-12 to connect truss(es) F1-25 (1 ply 2x4 SP) to front face of top chord.
 - Fill all nail holes where hanger is in contact with lumber.
 - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

- LOAD CASE(S)** Standard
- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 6-12=-10, 1-2=-190, 2-5=-100
Concentrated Loads (lb)
Vert: 1=-264 15=-141(F) 16=-141(F) 17=-141(F)
 - Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 6-12=-10, 1-2=-190, 2-5=-100
Concentrated Loads (lb)
Vert: 1=-264 15=-141(F) 16=-141(F) 17=-141(F)
 - 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 6-12=-10, 1-2=-190, 2-5=-20
Concentrated Loads (lb)
Vert: 1=-264 15=-221(F) 16=-221(F) 17=-221(F)



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-24	Floor Girder	1	1	Job Reference (optional) # 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:06 2024 Page 2
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-FU0m532slQ9GC3b59DE?AFzkooz3KKLW7WoGrjyfwER

LOAD CASE(S) Standard

4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 6-12=-10, 1-2=-110, 2-5=-100

Concentrated Loads (lb)

Vert: 1=-264 15=-141(F) 16=-141(F) 17=-141(F)

5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 6-12=-10, 1-2=-190, 2-5=-20

Concentrated Loads (lb)

Vert: 1=-264 15=-221(F) 16=-221(F) 17=-221(F)

6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 6-12=-10, 1-2=-110, 2-5=-100

Concentrated Loads (lb)

Vert: 1=-264 15=-141(F) 16=-141(F) 17=-141(F)



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-25	Truss Type Floor	Qty 3	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 52104
--------------------	----------------	---------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:06 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-FU0m532slQ9GC3b59DE?AFzoko?TKQuW7WoGryfwER




Plate Offsets (X,Y)-- [4:Edge,0-1-8], [7:Edge,0-1-8]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.27	Vert(LL) -0.00 6 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.09	Vert(CT) -0.01 5-6 >999 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.11	Horz(CT) 0.00 4 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-P			
				Weight: 26 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 4-7-8 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 7=241/0-7-8 (min. 0-1-8), 4=241/Mechanical

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
BOT CHORD 5-6=0/357
WEBS 2-5=-300/0

NOTES- (3)
1) Refer to girder(s) for truss to truss connections.
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-26	Truss Type Floor Supported Gable	Qty 1	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC	Job Reference (optional) # 52104
--------------------	----------------	-------------------------------------	----------	----------	--	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:06 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-FU0m532sIQ9GC3b59DE?AFzs5o0iKRbw7WoGrjyfwER




Plate Offsets (X,Y)-- [2:0-1-8,Edge], [6:Edge,0-1-8], [8:0-1-8,Edge], [10:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	6	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-P					Weight: 23 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 4-7-8 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 4-7-8.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 10, 6, 9, 8, 7

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (6)
1) Gable requires continuous bottom chord bearing.
2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
3) Gable studs spaced at 1-4-0 oc.
4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
5) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard




9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-27	Truss Type Floor	Qty 3	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 52104
--------------------	----------------	---------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:06 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-FU0m532slQ9GC3b59DE?AFzoko?RKQrW7WoGryfW7ER



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP	
TCLL	40.0	2-0-0	Plate Grip DOL	1.00	TC	0.27	in	(loc)	l/defl	L/d	MT20	244/190	
TCDL	10.0	1.00	Lumber DOL	1.00	BC	0.09	Vert(LL)	-0.00	6	>999	480		
BCLL	0.0	YES	Rep Stress Incr	YES	WB	0.12	Vert(CT)	-0.01	5-6	>999	360		
BCDL	5.0	Code IRC2021/TPI2014	Code IRC2021/TPI2014	Matrix-P			Horz(CT)	0.00	4	n/a	n/a		
											Weight: 26 lb	FT = 20%F, 11%E	

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 4-8-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 7=244/Mechanical, 4=244/0-4-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
BOT CHORD 5-6=0/368
WEBS 2-5=-298/0

NOTES- (3)
1) Refer to girder(s) for truss to truss connections.
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




Plate Offsets (X,Y)-- [20:Edge,0-1-8]		LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP	
TCLL	40.0	1-4-0	Plate Grip DOL	1.00	TC	0.43	Vert(LL)	-0.05	17	>999	480	MT20	244/190		
TCDL	10.0	1-0-0	Lumber DOL	1.00	BC	0.28	Vert(CT)	-0.08	16	>999	360				
BCLL	0.0	1-0-0	Rep Stress Incr	NO	WB	0.65	Horz(CT)	0.01	12	n/a	n/a				
BCDL	5.0	1-0-0	Code IRC2021/TPI2014		Matrix-SH										
												Weight: 85 lb		FT = 20%F, 11%E	

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 20=402/0-7-14 (min. 0-1-8), 10=-340/1-7-8 (min. 0-1-8), 11=-396/1-7-8 (min. 0-1-8), 11=-396/1-7-8 (min. 0-1-8), 12=2204/0-4-8 (min. 0-1-8)
 Max Uplift 10=-372(LC 3), 11=-476(LC 3), 11=-396(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 20-21=-399/0, 1-21=-398/0, 1-2=-523/0, 2-3=-1149/0, 3-4=-1222/0, 4-5=-764/0, 6-7=0/1685, 7-8=0/614
 BOT CHORD 18-19=0/973, 17-18=0/1311, 16-17=0/1311, 15-16=0/1116, 14-15=0/391, 13-14=-581/0, 12-13=-581/0, 11-12=-1685/0, 10-11=-614/0
 WEBS 8-11=-462/0, 7-12=-934/0, 7-11=0/1357, 8-10=0/728, 1-19=0/594, 2-19=-550/0, 4-15=-429/0, 5-15=0/455, 5-14=-730/0, 6-14=0/589, 6-12=-1622/0

- NOTES-** (6-9)
- Unbalanced floor live loads have been considered for this design.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 372 lb uplift at joint 10 and 476 lb uplift at joint 11.
 - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard

- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 10-20=-7, 1-9=-67
 Concentrated Loads (lb)
 Vert: 6=-735



9/6/2024

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-29	Floor	1	1	Job Reference (optional) # 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:07 2024 Page 2
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-kga8lP3UWkH7qDAHjxlEjSVx1Bk3kqfMAYqN9yfwEQ

LOAD CASE(S) Standard

- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 10-20=-7, 1-9=-67
 - Concentrated Loads (lb)
 - Vert: 6=-735
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 10-20=-7, 1-7=-67, 7-9=-13
 - Concentrated Loads (lb)
 - Vert: 6=-735
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 10-20=-7, 1-7=-13, 7-9=-67
 - Concentrated Loads (lb)
 - Vert: 6=-735
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 10-20=-7, 1-7=-67, 7-9=-13
 - Concentrated Loads (lb)
 - Vert: 6=-735
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 10-20=-7, 1-7=-13, 7-9=-67
 - Concentrated Loads (lb)
 - Vert: 6=-735



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-30	Floor	2	1	Job Reference (optional) # 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:07 2024 Page 2
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-kgA8IP3UWkH7qDAHjxEJSVxxBIV3i3fMAYqN9yfwEQ

LOAD CASE(S) Standard

- Concentrated Loads (lb)
Vert: 6=-735
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 9-18=-7, 1-7=-67, 7-8=-13
Concentrated Loads (lb)
Vert: 6=-735
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 9-18=-7, 1-7=-13, 7-8=-67
Concentrated Loads (lb)
Vert: 6=-735
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 9-18=-7, 1-7=-67, 7-8=-13
Concentrated Loads (lb)
Vert: 6=-735
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 9-18=-7, 1-7=-13, 7-8=-67
Concentrated Loads (lb)
Vert: 6=-735



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-31	Truss Type Floor	Qty 1	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC	# 52104
--------------------	----------------	---------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:07 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-kga8IP3UWkH7qDAHjxEjSVxCBlm3lcfMAYqN9yfwEQ




Plate Offsets (X,Y)-- [24:Edge,0-1-8], [26:0-1-8,0-0-8]

LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.42	Vert(LL)	-0.05	21	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.27	Vert(CT)	-0.08	20	>999	360		
BCLL 0.0	Rep Stress Incr	NO	WB 0.60	Horz(CT)	0.01	15	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH							
									Weight: 96 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. All bearings 4-0-0 except (jt=length) 24=0-7-14, 15=0-4-8.
 (lb) - Max Uplift All uplift 100 lb or less at joint(s) 12 except 14=-517(LC 3), 14=-401(LC 1), 13=-129(LC 3)
 Max Grav All reactions 250 lb or less at joint(s) 13, 12 except 24=401(LC 1), 15=2117(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 24-25=-397/0, 1-25=-396/0, 1-2=-520/0, 2-3=-1142/0, 3-4=-1142/0, 4-5=-1209/0, 5-6=-746/0, 7-8=0/1716, 8-9=0/728, 9-10=0/310
 BOT CHORD 22-23=0/968, 21-22=0/1300, 20-21=0/1300, 19-20=0/1100, 18-19=0/371, 17-18=0/371, 16-17=-605/0, 15-16=-605/0, 14-15=-1716/0, 13-14=-728/0
 WEBS 9-14=-398/0, 8-15=-835/0, 8-14=0/1252, 9-13=0/513, 10-13=-328/0, 1-23=0/591, 2-23=-547/0, 5-19=-432/0, 6-19=0/459, 6-17=-733/0, 7-17=0/591, 7-15=-1634/0

- NOTES-** (6-9)
- Unbalanced floor live loads have been considered for this design.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 12 except (jt=lb) 14=517, 13=129.
 - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 12-24=-7, 1-11=-67



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-31	Floor	1	1	Job Reference (optional) # 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:07 2024 Page 2
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-kga8IP3UWkH7qDAHjxEjSVxCBIm3lcfMAYqN9yfwEQ

LOAD CASE(S) Standard

- Concentrated Loads (lb)
Vert: 7=-735
- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 12-24=-7, 1-11=-67
Concentrated Loads (lb)
Vert: 7=-735
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 12-24=-7, 1-8=-67, 8-11=-13
Concentrated Loads (lb)
Vert: 7=-735
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 12-24=-7, 1-8=-13, 8-11=-67
Concentrated Loads (lb)
Vert: 7=-735
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 12-24=-7, 1-8=-67, 8-11=-13
Concentrated Loads (lb)
Vert: 7=-735
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 12-24=-7, 1-8=-13, 8-11=-67
Concentrated Loads (lb)
Vert: 7=-735



9/6/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Plate Offsets (X,Y)-- [10:0-1-8,Edge], [23:Edge,0-1-8]					
LOADING (psf)	SPACING- 1-4-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.49	Vert(LL) -0.05 20 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.29	Vert(CT) -0.08 19 >999 360		
BCLL 0.0	Rep Stress Incr NO	WB 0.37	Horz(CT) 0.01 14 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
				Weight: 94 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 23=407/0-7-14 (min. 0-1-8), 11=-125/0-8-0 (min. 0-1-8), 14=1757/0-4-8 (min. 0-1-8)
Max Uplift 11=-244(LC 3)
Max Grav 23=410(LC 3), 11=30(LC 4), 14=1757(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 23-24=-407/0, 1-24=-406/0, 1-2=-535/0, 2-3=-1185/0, 3-4=-1185/0, 4-5=-1281/0, 5-6=-846/0, 7-8=0/1598, 8-9=0/1106, 9-10=0/289
BOT CHORD 21-22=0/997, 20-21=0/1358, 19-20=0/1358, 18-19=0/1186, 17-18=0/484, 16-17=0/484, 15-16=-512/0, 14-15=-512/0, 13-14=-1598/0, 12-13=-675/0
WEBS 8-14=-530/0, 8-13=0/694, 9-13=-651/0, 9-12=0/471, 10-12=-372/0, 1-22=0/608, 2-22=-564/0, 5-18=-420/0, 6-18=0/446, 6-16=-725/0, 7-16=0/581, 7-14=-1638/0

- NOTES-** (6-9)
- Unbalanced floor live loads have been considered for this design.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 11=244.
 - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 11-23=-7, 1-10=-67
Concentrated Loads (lb)
Vert: 7=-735



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC
24-7417-F01	F1-32	Floor	5	1	Job Reference (optional) # 52104

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:08 2024 Page 2
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-Ct8WWI46H1P_SNITheGTGg25obepoGLpaqHNvcyfwEP

LOAD CASE(S) Standard

- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 11-23=-7, 1-10=-67
 - Concentrated Loads (lb)
 - Vert: 7=-735
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 11-23=-7, 1-8=-67, 8-10=-13
 - Concentrated Loads (lb)
 - Vert: 7=-735
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 11-23=-7, 1-8=-13, 8-10=-67
 - Concentrated Loads (lb)
 - Vert: 7=-735
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 11-23=-7, 1-8=-67, 8-10=-13
 - Concentrated Loads (lb)
 - Vert: 7=-735
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 11-23=-7, 1-8=-13, 8-10=-67
 - Concentrated Loads (lb)
 - Vert: 7=-735



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-7417-F01	Truss F1-33	Truss Type Floor Supported Gable	Qty 1	Ply 1	LOT 0.0036 HONEYCUTT HILLS 286 SHELBY MEADOW LANE ANGIER, NC	Job Reference (optional) # 52104
--------------------	----------------	-------------------------------------	----------	----------	--	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Sep 7 20:57:08 2024 Page 1
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-Ct8WW46H1P_SNITHeGTGg2CabiAoLhpaqHNvcyfWEP

0-1-8

0-1-8

Scale = 1:30.1




Plate Offsets (X,Y)-- [9:0-1-8,Edge], [24:0-1-8,Edge], [32:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	17	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 74 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 18-1-14.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 32, 17, 31, 30, 29, 28, 27, 26, 25, 24, 23, 22, 20, 19, 18

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (5-8)
- Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



9/6/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.