

# Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483  
843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 53379  
JOB: 24-8565-F01  
JOB NAME: LOT 0.0015 HONEYCUTT HILLS  
Wind Code: N/A  
Wind Speed: Vult= N/A  
Exposure Category: N/A  
Mean Roof Height (feet): N/A  
These truss designs comply with IRC 2018 as well as IRC 2021.  
*30 Truss Design(s)*

## Trusses:

F1-01, F1-02, F1-03, F1-04, F1-05, F1-06, F1-08, F1-09, F1-10, F1-11, F1-12, F1-12A, F1-13, F1-14, F1-15, F1-19, F1-20, F1-21, F1-22, F1-23, F1-24, F1-25, F1-26, F1-27, F1-28, F1-29, F1-30, F1-31, F1-32, F1-33



**10/14/2024**  
**Mark Morris**

### ***Warning !—Verify design parameters and read notes before use.***

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-01	Floor Supported Gable	1	1	
					Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:32 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-wtkVDJRclryrpz6nHOGuNNQF?clZaTu8X2AeYG0yT6aD

0-1-8

Scale = 1:24.9




Plate Offsets (X,Y)-- [6:0-1-8,Edge], [20:0-1-8,Edge], [26:Edge,0-1-8]					
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.06	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 14 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH		Weight: 64 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

**REACTIONS.** All bearings 15-2-2.  
(lb) - Max Uplift All uplift 100 lb or less at joint(s) 14  
Max Grav All reactions 250 lb or less at joint(s) 26, 14, 25, 24, 23, 22, 21, 20, 19, 18, 17, 16, 15

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (7-10)
- Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 14.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

**LOAD CASE(S)** Standard



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-02	Truss Type Floor	Qty 8	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) <b># 53379</b>
--------------------	----------------	---------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:32 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-wtkVDJRclyrpZ6nHOguNNQFv8IPATICX2AeYG0yT6aD





Plate Offsets (X,Y)-- [1:Edge,0-1-8], [8:Edge,0-1-8], [16:Edge,0-1-8]

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.41	Vert(LL)	-0.21	12	>859	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.67	Vert(CT)	-0.29	12	>625	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.60	Horz(CT)	0.05	8	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH							
									Weight: 76 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)


**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 16=815/0-7-14 (min. 0-1-8), 8=821/0-4-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 16-17=-809/0, 1-17=-807/0, 7-8=-818/0, 1-2=-1112/0, 2-3=-2656/0, 3-4=-3374/0, 4-5=-3302/0, 5-6=-2437/0, 6-7=-775/0  
BOT CHORD 14-15=0/2088, 13-14=0/3188, 12-13=0/3536, 11-12=0/3536, 10-11=0/3048, 9-10=0/1791  
WEBS 1-15=0/1267, 2-15=-1191/0, 2-14=0/693, 3-14=-649/0, 4-11=-281/0, 5-11=0/311, 5-10=-745/0, 6-10=0/788, 6-9=-1240/0, 7-9=0/1066

- NOTES-** (3-6)
- 1) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 2) CAUTION, Do not erect truss backwards.
  - 3) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - 4) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - 5) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - 6) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

**LOAD CASE(S)** Standard



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-03	Truss Type Floor Supported Gable	Qty 1	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 53379
--------------------	----------------	-------------------------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:33 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-O3ItQfSEWG\_gaGMUyNPcwenAxivsCLtgHqN5oSyT6aC

0-1-8  
1 3x4 = 2 3x4 ||

Scale = 1:7.7




Plate Offsets (X,Y)-- [4:Edge,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	2-0-0 Plate Grip DOL 1.00	TC 0.02	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.00	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr YES	WB 0.00	Horz(CT)	0.00	3	n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-P					Weight: 8 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 0-11-14 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 4=35/0-11-14 (min. 0-1-8), 3=40/0-11-14 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-** (6-9)

- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.
- Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
- Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
- Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
- SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

**LOAD CASE(S)** Standard



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-04	Truss Type Floor	Qty 6	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC	# 53379
--------------------	----------------	---------------------	----------	----------	--	---------

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:34 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-sFsFe?TsHZ6XCQxgW5wrSrKGZ665xgSpWU7fLuyT6aB






Plate Offsets (X,Y)-- [1:Edge,0-1-8], [15:Edge,0-1-8]	
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0
TCLL 40.0	Plate Grip DOL 1.00
TCDL 10.0	Lumber DOL 1.00
BCLL 0.0	Rep Stress Incr YES
BCDL 5.0	Code IRC2021/TPI2014
<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d
TC 0.35	Vert(LL) -0.16 11-12 >999 480
BC 0.58	Vert(CT) -0.22 11-12 >766 360
WB 0.56	Horz(CT) 0.04 8 n/a n/a
Matrix-SH	
<b>PLATES</b>	<b>GRIP</b>
MT20	244/190
Weight: 71 lb FT = 20%F, 11%E	

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 15=758/0-7-8 (min. 0-1-8), 8=764/0-4-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 15-16=-753/0, 1-16=-751/0, 1-2=-1024/0, 2-3=-2406/0, 3-4=-2963/0, 4-5=-2724/0, 5-6=-1691/0  
BOT CHORD 13-14=0/1919, 12-13=0/2858, 11-12=0/3040, 10-11=0/3040, 9-10=0/2393, 8-9=0/951  
WEBS 1-14=0/1166, 2-14=-1093/0, 2-13=0/595, 3-13=-551/0, 4-10=-379/0, 5-10=0/405, 5-9=-857/0, 6-9=0/903, 6-8=-1197/0

- NOTES-** (3-6)
- 1) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 2) CAUTION, Do not erect truss backwards.
  - 3) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - 4) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - 5) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - 6) SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

**LOAD CASE(S)** Standard



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-05	Floor Supported Gable	1	1	Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:34 2024 Page 1  
 ID:5fxLxLn?C6dWjia?SHK4thzkcYI-sFsFe?TsHZ6XCQxgW5wrSrKL66F2xoeepWU7fLuyT6aB

0-1-8

Scale = 1:23.2




Plate Offsets (X,Y)-- [6:0-1-8,Edge], [18:0-1-8,Edge], [24:Edge,0-1-8]					
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.06	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 13 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH		Weight: 59 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)  
 OTHERS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 14-1-12.  
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 24, 13, 23, 22, 21, 20, 19, 18, 17, 16, 15, 14

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (6-9)
- Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

**LOAD CASE(S)** Standard



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job 24-8565-F01	Truss F1-06	Truss Type GABLE	Qty 1	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) <b># 53379</b>
--------------------	----------------	---------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:35 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-KSQerLTU2tEOqZWs3oR4?3tVTWbFgFozl8sCtLyT6aA

Scale = 1:12.7




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [3:0-1-8,Edge], [9:0-1-8,Edge], [12:Edge,0-1-8]

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.04	Horz(CT)	-0.00	9	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-P						Weight: 32 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)  
OTHERS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-11-12 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 6-11-12.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 12, 7, 11, 10, 9, 8

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-** (5)  
1) Gable requires continuous bottom chord bearing.  
2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).  
3) Gable studs spaced at 1-4-0 oc.  
4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

**LOAD CASE(S)** Standard




10/14/2024


**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-08	Truss Type Floor	Qty 3	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC	# 53379
--------------------	----------------	---------------------	----------	----------	--	---------

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:36 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-oe\_03hU6pBMFSj53dVyJYGpC4vtFPcu6zocmPnyT6a9



Scale = 1:37.9



LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.35	Vert(LL)	-0.06	22	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.28	Vert(CT)	-0.08	22	>999	360		
BCLL 0.0	Rep Stress Incr	NO	WB 0.43	Horz(CT)	0.01	18	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH							
										Weight: 115 lb FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (lb/size) 25=384/0-7-8 (min. 0-1-8), 12=641/0-4-6 (min. 0-1-8), 18=1653/0-4-8 (min. 0-1-8)  
Max Grav 25=405(LC 3), 12=702(LC 4), 18=1653(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-25=-400/0, 11-12=-700/0, 1-2=-517/0, 2-3=-1144/0, 3-4=-1217/0, 4-5=-1217/0, 5-6=-750/59, 6-7=0/514, 7-8=0/779,  
8-9=-544/384, 9-10=-676/123, 10-11=-278/10  
BOT CHORD 23-24=0/969, 22-23=0/1296, 21-22=0/1111, 20-21=0/1111, 19-20=-210/380, 18-19=-1296/0, 17-18=-1305/0,  
16-17=-567/339, 15-16=-567/339, 14-15=-228/724, 13-14=-42/604  
WEBS 7-18=-1624/0, 1-24=0/613, 2-24=-551/0, 5-20=-474/0, 6-20=0/491, 6-19=-793/0, 7-19=0/907, 7-17=0/704, 8-17=-653/0,  
8-15=0/363, 9-15=-331/0, 10-13=-397/39, 11-13=-14/368

**NOTES-** (5)  
1) Unbalanced floor live loads have been considered for this design.  
2) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.  
3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
4) CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-11=-67  
Concentrated Loads (lb)  
Vert: 7=-600 11=-400  
2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-11=-67  
Concentrated Loads (lb)  
Vert: 7=-600 11=-400  
3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-7=-67, 7-11=-13  
Concentrated Loads (lb)  
Vert: 7=-600 11=-400



10/14/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded continuously on page 1. The responsibility of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-08	Floor	3	1	Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:36 2024 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-oe\_03hU6pBMFSj53dVyJYGPc4vtFPcu6zocmPnyT6a9

**LOAD CASE(S)** Standard

- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 12-25=-7, 1-7=-13, 7-11=-67
  - Concentrated Loads (lb)
    - Vert: 7=-600 11=-400
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 12-25=-7, 1-7=-67, 7-11=-13
  - Concentrated Loads (lb)
    - Vert: 7=-600 11=-400
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 12-25=-7, 1-7=-13, 7-11=-67
  - Concentrated Loads (lb)
    - Vert: 7=-600 11=-400



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-09	Truss Type Floor Supported Gable	Qty 1	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) # 53379
--------------------	----------------	-------------------------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:37 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-GqXOG1VkaUU63tgFBDTY4UyrDJGk89MGCSLJxDyT6a8

Scale = 1:37.3




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [10:0-1-8,Edge], [29:0-1-8,Edge], [38:Edge,0-1-8]					
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.07	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 26 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			Weight: 92 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

**REACTIONS.** All bearings 22-9-2.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 38, 20, 37, 36, 35, 34, 33, 32, 31, 30, 29, 28, 26, 25, 24, 23, 22, 21

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (5)
- Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

**LOAD CASE(S)** Standard



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-10	Floor	6	1	Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:39 2024 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-DDf8hiX?66kqJBqdleW09v1zJ7uYcyDYfmqQ06yT6a6

**LOAD CASE(S)**

- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 12-25=-7, 1-7=-13, 7-11=-67
  - Concentrated Loads (lb)
    - Vert: 7=-600 27=-335
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 12-25=-7, 1-7=-67, 7-11=-13
  - Concentrated Loads (lb)
    - Vert: 7=-600 27=-335
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 12-25=-7, 1-7=-13, 7-11=-67
  - Concentrated Loads (lb)
    - Vert: 7=-600 27=-335



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-11	Truss Type Floor	Qty 3	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) <b># 53379</b>
--------------------	----------------	---------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:40 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-hPDXu2XdsPshwLQqsL1Fi6aJiXFaLQsiuQazYYyT6a5





Plate Offsets (X,Y)-- [25:Edge,0-1-8]								
LOADING (psf)	SPACING- 1-4-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.31	Vert(LL) -0.06	22	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.25	Vert(CT) -0.08	22	>999	360		
BCLL 0.0	Rep Stress Incr YES	WB 0.43	Horz(CT) 0.01	18	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH						
							Weight: 115 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 25=380/0-7-8 (min. 0-1-8), 12=241/0-4-8 (min. 0-1-8), 18=1054/0-4-8 (min. 0-1-8)  
Max Grav 25=400(LC 3), 12=303(LC 4), 18=1054(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 25-26=-397/0, 1-26=-396/0, 11-12=-301/0, 1-2=-519/0, 2-3=-1143/0, 3-4=-1216/0, 4-5=-1216/0, 5-6=-748/62,  
6-7=0/516, 7-8=0/778, 8-9=-545/384, 9-10=-678/123, 10-11=-281/10  
BOT CHORD 23-24=0/967, 22-23=0/1295, 21-22=0/1109, 20-21=0/1109, 19-20=-213/379, 18-19=-1300/0, 17-18=-1306/0,  
16-17=-566/339, 15-16=-566/339, 14-15=-228/726, 13-14=-42/607  
WEBS 7-18=-1027/0, 1-24=0/589, 2-24=-547/0, 5-20=-475/0, 6-20=0/491, 6-19=-793/0, 7-19=0/909, 7-17=0/706, 8-17=-653/0,  
8-15=0/363, 9-15=-332/0, 10-13=-397/39, 11-13=-13/371

- NOTES-** (4)  
1) Unbalanced floor live loads have been considered for this design.  
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
3) CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard




10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-12	Floor	2	1	
					# 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:42 2024 Page 1  
 ID:5fxLxLn?C6dWjia?SHK4thzkcYI-doLHJkZtO16PAeYC\_m3jnXfeEKwpJ3?Mk34dRyT6a3



Scale = 1:38.0




Plate Offsets (X,Y)-- [14:Edge,0-1-8], [27:Edge,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	1-4-0	TC 0.37	Vert(LL) -0.06	24	>999	480	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.27	Vert(CT) -0.08	24	>999	360		
BCLL 0.0	Lumber DOL 1.00	WB 0.45	Horz(CT) 0.01	14	n/a	n/a		
BCDL 5.0	Rep Stress Incr NO	Matrix-SH						
	Code IRC2021/TPI2014							
							Weight: 119 lb	FT = 20%F, 11%E

**LUMBER-**

TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (lb/size) 27=379/0-4-8 (min. 0-1-8), 20=1121/0-4-8 (min. 0-1-8), 14=1049/0-4-8 (min. 0-1-8)  
 Max Grav 27=400(LC 3), 20=1121(LC 1), 14=1111(LC 4)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-27=-395/0, 1-2=-509/0, 2-3=-1122/0, 3-4=-1180/0, 4-5=-1180/0, 5-6=-698/127,  
 6-7=0/582, 7-8=0/802, 8-9=-718/224, 9-10=-718/224, 10-11=-978/0, 11-12=-672/0  
 BOT CHORD 25-26=0/954, 24-25=0/1266, 23-24=0/1066, 22-23=0/1066, 21-22=-288/322, 20-21=-1408/0,  
 19-20=-1417/0, 18-19=-513/394, 17-18=-513/394, 16-17=0/960, 15-16=0/968, 14-15=0/672  
 WEBS 7-20=-1093/0, 1-26=0/604, 2-26=-542/0, 5-22=-483/0, 6-22=0/499, 6-21=-804/0,  
 7-21=0/948, 7-19=0/804, 8-19=-744/0, 8-17=0/514, 10-17=-399/0, 11-15=-338/154,  
 12-14=-1277/0

**NOTES-** (5)

- Unbalanced floor live loads have been considered for this design.
- Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard

- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
 Uniform Loads (plf)  
 Vert: 14-27=-7, 1-13=-67  
 Concentrated Loads (lb)  
 Vert: 12=-865
- Dead: Lumber Increase=1.00, Plate Increase=1.00  
 Uniform Loads (plf)  
 Vert: 14-27=-7, 1-13=-67  
 Concentrated Loads (lb)  
 Vert: 12=-865
- 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
 Uniform Loads (plf)  
 Vert: 14-27=-7, 1-7=-67, 7-13=-13  
 Concentrated Loads (lb)  
 Vert: 12=-865



10/14/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded continuously in accordance with the design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-12	Floor	2	1	Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:42 2024 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-doLHJkZtO16PAeYC\_m3jnXfeEKwlpJ3?Mk34dRyT6a3

**LOAD CASE(S)** Standard

4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 14-27=-7, 1-7=-13, 7-13=-67

Concentrated Loads (lb)

Vert: 12=-865

5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 14-27=-7, 1-7=-67, 7-13=-13

Concentrated Loads (lb)

Vert: 12=-865

6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 14-27=-7, 1-7=-13, 7-13=-67

Concentrated Loads (lb)

Vert: 12=-865



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-12A	Floor	7	1	Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:43 2024 Page 2  
ID:5fxLxLn?C6dWjja?SHK4thzkcY1-5\_vfX4aV9KEGno7PXUayKICnOKEsYkg8aOod9tyT6a2

**LOAD CASE(S)**

- Concentrated Loads (lb)  
Vert: 8=-932 11=-865
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 13-28=-7, 1-7=-13, 7-12=-67  
Concentrated Loads (lb)  
Vert: 8=-932 11=-865
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 13-28=-7, 1-7=-67, 7-12=-13  
Concentrated Loads (lb)  
Vert: 8=-932 11=-865
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 13-28=-7, 1-7=-13, 7-12=-67  
Concentrated Loads (lb)  
Vert: 8=-932 11=-865



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-13	Truss Type Floor	Qty 1	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
					Job Reference (optional) <b># 53379</b>

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:44 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-ZAS1kQa7weM6Pyib5B5BsyI?s8ciHEhlp2YBhJyT6a1

1-3-0

1-5-4

1-0-0 0-1-8

Scale = 1:26.0




Plate Offsets (X,Y)-- [8:0-1-8,Edge], [17:Edge,0-1-8]

LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.30	Vert(LL)	-0.05	14	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.24	Vert(CT)	-0.07	14	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.44	Horz(CT)	0.01	11	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH							
									Weight: 80 lb	FT = 20%F, 11%E

**LUMBER-**

TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (lb/size) 17=395/0-4-8 (min. 0-1-8), 9=-353/0-3-8 (min. 0-1-8), 11=1096/0-4-8 (min. 0-1-8)  
Max Uplift9=-413(LC 3)  
Max Grav 17=395(LC 3), 11=1096(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-17=-391/0, 9-18=0/419, 8-18=0/418, 1-2=-504/0, 2-3=-1098/0, 3-4=-1169/0, 4-5=-1169/0, 5-6=-650/0, 6-7=0/378, 7-8=0/540  
BOT CHORD 15-16=0/943, 14-15=0/1229, 13-14=0/1002, 12-13=0/272, 11-12=-1189/0, 10-11=-1196/0  
WEBS 7-11=-1065/0, 1-16=0/597, 2-16=-536/0, 5-13=-435/0, 6-13=0/468, 6-12=-791/0, 7-12=0/932, 7-10=0/777, 8-10=-661/0

**NOTES-** (5)

- Unbalanced floor live loads have been considered for this design.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 413 lb uplift at joint 9.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard




10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job 24-8565-F01	Truss F1-15	Truss Type Floor	Qty 1	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC	# 53379
--------------------	----------------	---------------------	----------	----------	--	---------

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:46 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-VZao96cOSFcqeGs\_Dc8fyNqKSxICl8NaGM1HmCyT6a?



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.29	Vert(LL)	-0.05	14	>999	480	MT20	244/190	
TCDL	10.0	Lumber DOL	1.00	BC	0.24	Vert(CT)	-0.07	14	>999	360	Weight: 80 lb FT = 20%F, 11%E		
BCLL	0.0	Rep Stress Incr	YES	WB	0.43	Horz(CT)	0.01	11	n/a	n/a			
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH									

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		

**REACTIONS.** (lb/size) 17=389/0-3-8 (min. 0-1-8), 9=348/0-7-8 (min. 0-1-8), 11=1088/0-4-8 (min. 0-1-8)  
Max Uplift=409(LC 3)  
Max Grav 17=389(LC 3), 11=1088(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 17-18=-386/0, 1-18=-385/0, 9-19=0/414, 8-19=0/414, 1-2=-503/0, 2-3=-1090/0, 3-4=-1155/0, 4-5=-1155/0, 5-6=-632/0, 6-7=0/399, 7-8=0/535  
BOT CHORD 15-16=0/936, 14-15=0/1219, 13-14=0/986, 11-12=-1178/0, 10-11=-1183/0  
WEBS 7-11=-1057/0, 1-16=0/571, 2-16=-529/0, 5-13=-439/0, 6-13=0/472, 6-12=-791/0, 7-12=0/904, 7-10=0/768, 8-10=-654/0

- NOTES-** (5)
- Unbalanced floor live loads have been considered for this design.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 409 lb uplift at joint 9.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard



10/14/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-19	GABLE	1	1	
					<b># 53379</b>

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:47 2024 Page 1  
 ID:5fxLxLn?C6dWjia?SHK4thzkcYl-\_l8AMSD0DZkhGPRAmJfuUbNZqLh5UhsKv0mrleyT6a\_

0-1-8

Scale = 1:22.9



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.06	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.01	Vert(LL) n/a - n/a 999		
BCLL 0.0	Lumber DOL 1.00	WB 0.03	Vert(CT) n/a - n/a 999		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.00 13 n/a n/a		
	Code IRC2021/TPI2014			Weight: 59 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)  
 OTHERS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 13-11-8.  
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 24, 13, 23, 22, 21, 20, 19, 18, 17, 16, 15, 14

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (6)
- Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard






10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-20	Truss Type Floor	Qty 4	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC	# 53379
--------------------	----------------	---------------------	----------	----------	--	---------

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:47 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-\_J8AMSd0DZKhGPRAmJfuUBNU7LYvUZZkV0mrleyT6a\_



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.36	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.59	Vert(LL) -0.17 11-12 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.56	Vert(CT) -0.23 11-12 >739 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.04 8 n/a n/a		
	Code IRC2021/TPI2014			Weight: 71 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 15=767/0-7-8 (min. 0-1-8), 8=773/0-4-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 15-16=-762/0, 1-16=-760/0, 1-2=-1038/0, 2-3=-2447/0, 3-4=-3029/0, 4-5=-2818/0, 5-6=-1811/0  
BOT CHORD 13-14=0/1946, 12-13=0/2911, 11-12=0/3120, 10-11=0/3120, 9-10=0/2499, 8-9=0/1084  
WEBS 1-14=0/1182, 2-14=-1108/0, 2-13=0/611, 3-13=-567/0, 4-10=-363/0, 5-10=0/389, 5-9=-840/0, 6-9=0/888, 6-8=-1302/0

**NOTES-** (3)  
1) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
2) CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard




10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-21	Floor Girder	1	1	
					# 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:48 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-SyiYande\_tsYuZ0MK1A71ovbNlprDvftkgWOp4yT6Zz



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.58	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.94	Vert(LL) -0.29 12-13 >582 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.96	Vert(CT) -0.36 12-13 >471 360		
BCDL 5.0	Rep Stress Incr NO	Matrix-SH	Horz(CT) 0.05 8 n/a n/a		
	Code IRC2021/TPI2014				Weight: 112 lb FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat) \*Except\*  
W2: 2x4 SP No.2(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 17=1444/0-7-8 (min. 0-1-8), 8=1447/0-4-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-17=-1420/0, 7-8=-1434/0, 1-2=-2401/0, 2-3=-6230/0, 3-18=-7839/0, 4-18=-7839/0, 4-19=-7715/0, 5-19=-7715/0, 5-6=-5453/0, 6-7=-1493/0  
BOT CHORD 15-16=0/4497, 14-15=0/7313, 13-14=0/7314, 12-13=0/8289, 11-12=0/7252, 10-11=0/7255, 9-10=0/3697  
WEBS 3-13=0/602, 4-13=-525/0, 4-12=-669/0, 5-12=0/614, 5-10=-2063/0, 6-10=0/2048, 6-9=-2571/0, 7-9=0/2008, 1-16=0/2716, 2-16=-2445/0, 2-15=0/2022, 3-15=-1481/0

**NOTES-** (6)  
1) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
2) CAUTION. Do not erect truss backwards.  
3) Use Simpson Strong-Tie THA422 (6-16d Girder, 6-10d Truss) or equivalent spaced at 1-7-3 oc max. starting at 4-9-4 from the left end to 9-5-12 to connect truss(es) F1-24 (1 ply 2x4 SP), F1-23 (1 ply 2x4 SP), F1-22 (1 ply 2x4 SP) to back face of top chord.  
4) Fill all nail holes where hanger is in contact with lumber.  
5) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 8-17=-10, 1-7=-100  
Concentrated Loads (lb)  
Vert: 3=-425(B) 5=-447(B) 18=-236(B) 19=-236(B)





10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-22	Truss Type Floor Girder	Qty 1	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC	# 53379
--------------------	----------------	----------------------------	----------	----------	--	---------

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:49 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-w8Gwn7eGIA?PVjaYukhMZ0SoP9KsyTU1zKFyMXyT6Zy



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.50	Vert(LL) -0.03	8	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.24	Vert(CT) -0.03	8	>999		
BCLL 0.0	Rep Stress Incr	NO	WB 0.47	Horz(CT) 0.01	6	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH					
							Weight: 51 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (lb/size) 6=528/Mechanical, 10=1370/0-8-0 (min. 0-1-8)  
Max Grav6=547(LC 4), 10=1370(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 5-6=-543/0, 1-2=0/623, 3-16=-994/0, 4-16=-994/0, 4-17=-517/0, 5-17=-517/0  
BOT CHORD 10-11=-902/0, 9-10=-871/0, 8-9=0/863, 7-8=0/1088  
WEBS 2-10=-1320/0, 1-11=-749/0, 2-11=0/489, 2-9=0/990, 3-9=-929/0, 4-7=-697/0, 5-7=0/665

- NOTES-** (9)
- Unbalanced floor live loads have been considered for this design.
  - Refer to girder(s) for truss to truss connections.
  - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent spaced at 2-0-0 oc max. starting at 4-1-4 from the left end to 8-1-4 to connect truss(es) F1-27 (1 ply 2x4 SP) to back face of top chord.
  - Fill all nail holes where hanger is in contact with lumber.
  - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

- LOAD CASE(S)** Standard
- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190(F=-90), 2-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264 15=-144(B) 16=-144(B) 17=-144(B)
  - Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190(F=-90), 2-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264 15=-144(B) 16=-144(B) 17=-144(B)
  - 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190(F=-90), 2-5=-20  
Concentrated Loads (lb)  
Vert: 1=-264 15=-224(B) 16=-224(B) 17=-224(B)



10/14/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded in accordance with the individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-22	Floor Girder	1	1	Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:49 2024 Page 2  
ID:5fxLxLn?C6dWjja?SHK4thzkcY1-w8Gwn7eGIA?PVjaYukhMZ0SoP9KsyTU1zKFyMXyT6Zy

**LOAD CASE(S)** Standard

4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 6-12=-10, 1-2=-110(F=-90), 2-5=-100

Concentrated Loads (lb)

Vert: 1=-264 15=-144(B) 16=-144(B) 17=-144(B)

5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 6-12=-10, 1-2=-190(F=-90), 2-5=-20

Concentrated Loads (lb)

Vert: 1=-264 15=-224(B) 16=-224(B) 17=-224(B)

6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 6-12=-10, 1-2=-110(F=-90), 2-5=-100

Concentrated Loads (lb)

Vert: 1=-264 15=-144(B) 16=-144(B) 17=-144(B)





10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-23	Truss Type Floor Special	Qty 2	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC	# 53379
--------------------	----------------	-----------------------------	----------	----------	--	---------

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:50 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-OKqJ?TfuWU7G7f9lSSCb6D\_?aZgfhzGAB\_?VuzyT6Zx



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.35	Vert(LL)	-0.02	8	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.14	Vert(CT)	-0.02	8	>999		
BCLL 0.0	Rep Stress Incr	NO	WB 0.31	Horz(CT)	0.00	6	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 51 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (lb/size) 6=317/Mechanical, 10=976/0-8-0 (min. 0-1-8)  
Max Grav 6=336(LC 4), 10=976(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 5-6=-332/0, 1-2=0/522, 2-3=0/501, 3-4=-546/145, 4-5=-297/2  
BOT CHORD 10-11=-763/0, 9-10=-745/0, 8-9=-296/443, 7-8=-33/611  
WEBS 2-10=-940/0, 1-11=-627/0, 2-11=0/423, 2-9=0/650, 3-9=-598/0, 4-7=-384/38, 5-7=-3/381

- NOTES-** (6)
- Unbalanced floor live loads have been considered for this design.
  - Refer to girder(s) for truss to truss connections.
  - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.

- LOAD CASE(S)** Standard
- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264
  - Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264
  - 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-100, 2-5=-20  
Concentrated Loads (lb)  
Vert: 1=-264
  - 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-20, 2-5=-100



10/14/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded in accordance with the individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-23	Floor Special	2	1	Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:50 2024 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-OKqJ?TfuWU7G7f9lSSCb6D\_?aZgfhzGAB\_?VuzyT6Zx


**LOAD CASE(S)** Standard

- Concentrated Loads (lb)  
Vert: 1=-264
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-100, 2-5=-20  
Concentrated Loads (lb)  
Vert: 1=-264
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-20, 2-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.53	Vert(LL) -0.03	8	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.24	Vert(CT) -0.03	8	>999		
BCLL 0.0	Rep Stress Incr	NO	WB 0.47	Horz(CT) 0.01	6	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH					
							Weight: 51 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (lb/size) 6=506/Mechanical, 10=1382/0-8-0 (min. 0-1-8)  
Max Grav 6=525(LC 4), 10=1382(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 5-6=-521/0, 1-2=0/616, 3-16=-984/0, 4-16=-984/0, 4-17=-508/0, 5-17=-508/0  
BOT CHORD 10-11=-891/0, 9-10=-859/0, 8-9=0/862, 7-8=0/1068  
WEBS 2-10=-1332/0, 1-11=-740/0, 2-11=0/483, 2-9=0/985, 3-9=-924/0, 4-7=-684/0, 5-7=0/653

- NOTES-** (9)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) Refer to girder(s) for truss to truss connections.
  - 3) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 5) CAUTION, Do not erect truss backwards.
  - 6) Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent spaced at 2-0-0 oc max. starting at 3-9-12 from the left end to 7-9-12 to connect truss(es) F1-25 (1 ply 2x4 SP) to front face of top chord.
  - 7) Fill all nail holes where hanger is in contact with lumber.
  - 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

- LOAD CASE(S)** Standard
- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190, 2-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264 15=-141(F) 16=-141(F) 17=-141(F)
  - 2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190, 2-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264 15=-141(F) 16=-141(F) 17=-141(F)
  - 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190, 2-5=-20  
Concentrated Loads (lb)  
Vert: 1=-264 15=-221(F) 16=-221(F) 17=-221(F)



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded in accordance with the manufacturer's instructions. The responsibility of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-24	Floor Girder	1	1	Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:51 2024 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-sXOhCpgWHoF711kx?9jqfRX7Wy?OQN0KQek2QPyT6ZW

**LOAD CASE(S)** Standard

4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 6-12=-10, 1-2=-110, 2-5=-100

Concentrated Loads (lb)

Vert: 1=-264 15=-141(F) 16=-141(F) 17=-141(F)

5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 6-12=-10, 1-2=-190, 2-5=-20

Concentrated Loads (lb)

Vert: 1=-264 15=-221(F) 16=-221(F) 17=-221(F)

6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 6-12=-10, 1-2=-110, 2-5=-100

Concentrated Loads (lb)

Vert: 1=-264 15=-141(F) 16=-141(F) 17=-141(F)



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-25	Truss Type Floor	Qty 3	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC	# 53379
--------------------	----------------	---------------------	----------	----------	--	---------

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:51 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-sXOhCpgWHoF711kx?9jqfRXBSy1oQTZKQek2QPyT6ZW




Plate Offsets (X,Y)-- [4:Edge,0-1-8], [7:Edge,0-1-8]					
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.27	Vert(LL) -0.00 6 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.09	Vert(CT) -0.01 5-6 >999 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.11	Horz(CT) 0.00 4 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-P			
				Weight: 26 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 4-7-8 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 7=241/0-7-8 (min. 0-1-8), 4=241/Mechanical

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
BOT CHORD 5-6=0/357  
WEBS 2-5=-300/0

**NOTES-** (3)  
1) Refer to girder(s) for truss to truss connections.  
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

**LOAD CASE(S)** Standard



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-26	Truss Type Floor Supported Gable	Qty 1	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC Job Reference (optional) <b># 53379</b>
--------------------	----------------	-------------------------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:52 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-Kjx3P9h825N\_MBJ7ZsF3Be4QZMOF9x5TfUcyryT6Zv

0-1-8

1 1.5x3 ||

2 3x4 =

3 1.5x3 ||

4 1.5x3 ||

5 3x4 ||

Scale = 1:8.6




Plate Offsets (X,Y)-- [2:0-1-8,Edge], [6:Edge,0-1-8], [8:0-1-8,Edge], [10:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	6	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-P						
								Weight: 23 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)  
OTHERS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 4-7-8 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 4-7-8.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 10, 6, 9, 8, 7

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-** (6)  
1) Gable requires continuous bottom chord bearing.  
2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).  
3) Gable studs spaced at 1-4-0 oc.  
4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
5) CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard




10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-8565-F01	Truss F1-27	Truss Type Floor	Qty 3	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC	# 53379
--------------------	----------------	---------------------	----------	----------	--	---------

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:52 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-Kjx3P9h825N\_MBJ7ZsF3Be4MCMN\_9wITfUcryT6Zv



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES	GRIP	
TCLL	40.0	2-0-0	Plate Grip DOL	1.00	TC	0.27	in	(loc)	l/defl	L/d	MT20	244/190
TCDL	10.0	1.00	Lumber DOL	1.00	BC	0.09	Vert(LL)	-0.00	6	>999	480	
BCLL	0.0	YES	Rep Stress Incr	YES	WB	0.12	Vert(CT)	-0.01	5-6	>999	360	
BCDL	5.0	Code IRC2021/TPI2014	Code IRC2021/TPI2014		Matrix-P		Horz(CT)	0.00	4	n/a	n/a	
											Weight: 26 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 4-8-4 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 7=244/Mechanical, 4=244/0-4-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
BOT CHORD 5-6=0/368  
WEBS 2-5=-298/0

**NOTES-** (3)  
1) Refer to girder(s) for truss to truss connections.  
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

**LOAD CASE(S)** Standard



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.





Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-29	Floor	1	1	# 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:54 2024 Page 1  
 ID:5fxLxLn?C6dWjia?SHK4thzkcYI-G53pqriPZjdicUTWhHHXG39gFA0Wdh\_m6czj1kyT6Zt




Plate Offsets (X,Y)-- [20:Edge,0-1-8]		LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP	
TCLL	40.0	1-4-0	1.00	TC	0.43	in	(loc)	l/defl	L/d	MT20	244/190	Weight: 85 lb FT = 20%F, 11%E			
TCDL	10.0	Lumber DOL	1.00	BC	0.28	Vert(LL)	-0.05	17	>999	480					
BCLL	0.0	Rep Stress Incr	NO	WB	0.65	Vert(CT)	-0.08	16	>999	360					
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH		Horz(CT)	0.01	12	n/a	n/a					

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	


**REACTIONS.** (lb/size) 20=402/0-7-14 (min. 0-1-8), 10=-340/1-7-8 (min. 0-1-8), 11=-396/1-7-8 (min. 0-1-8), 11=-396/1-7-8 (min. 0-1-8), 12=2204/0-4-8 (min. 0-1-8)  
 Max Uplift 10=-372(LC 3), 11=-476(LC 3), 11=-396(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 20-21=-399/0, 1-21=-398/0, 1-2=-523/0, 2-3=-1149/0, 3-4=-1222/0, 4-5=-764/0, 6-7=0/1685, 7-8=0/614  
 BOT CHORD 18-19=0/973, 17-18=0/1311, 16-17=0/1311, 15-16=0/1116, 14-15=0/391, 13-14=-581/0, 12-13=-581/0, 11-12=-1685/0, 10-11=-614/0  
 WEBS 8-11=-462/0, 7-12=-934/0, 7-11=0/1357, 8-10=0/728, 1-19=0/594, 2-19=-550/0, 4-15=-429/0, 5-15=0/455, 5-14=-730/0, 6-14=0/589, 6-12=-1622/0

- NOTES-** (6-9)
- Unbalanced floor live loads have been considered for this design.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 372 lb uplift at joint 10 and 476 lb uplift at joint 11.
  - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

**LOAD CASE(S)** Standard

1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 10-20=-7, 1-9=-67
Concentrated Loads (lb)
Vert: 6=-735



10/14/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded continuously in accordance with the design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-29	Floor	1	1	Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:54 2024 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-G53ppriPZjdicUTWhHHXG39gFA0Wdh\_m6czj1kyT6Zt

**LOAD CASE(S)** Standard

- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 10-20=-7, 1-9=-67
  - Concentrated Loads (lb)
    - Vert: 6=-735
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 10-20=-7, 1-7=-67, 7-9=-13
  - Concentrated Loads (lb)
    - Vert: 6=-735
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 10-20=-7, 1-7=-13, 7-9=-67
  - Concentrated Loads (lb)
    - Vert: 6=-735
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 10-20=-7, 1-7=-67, 7-9=-13
  - Concentrated Loads (lb)
    - Vert: 6=-735
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 10-20=-7, 1-7=-13, 7-9=-67
  - Concentrated Loads (lb)
    - Vert: 6=-735



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-30	Floor	2	1	Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:55 2024 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-lldC2Bj1K0lZDe2IE?ompHirvaMWM6TvLFiGzAyT6Zs

**LOAD CASE(S)** Standard

- Concentrated Loads (lb)  
Vert: 6=-735
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 9-18=-7, 1-7=-67, 7-8=-13  
Concentrated Loads (lb)  
Vert: 6=-735
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 9-18=-7, 1-7=-13, 7-8=-67  
Concentrated Loads (lb)  
Vert: 6=-735
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 9-18=-7, 1-7=-67, 7-8=-13  
Concentrated Loads (lb)  
Vert: 6=-735
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 9-18=-7, 1-7=-13, 7-8=-67  
Concentrated Loads (lb)  
Vert: 6=-735



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-31	Floor	1	1	# 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:56 2024 Page 1  
 ID:5fxLxLn?C6dWjia?SHK4thzkcYl-DUBaFWkf5KtProvoij?MUJE0vzh05cG3avSp5dyT6Zr




Plate Offsets (X,Y)-- [24:Edge,0-1-8], [26:0-1-8,0-0-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.42	Vert(LL) -0.05	21	>999	480		MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.27	Vert(CT) -0.08	20	>999	360			
BCLL 0.0	Rep Stress Incr NO	WB 0.60	Horz(CT) 0.01	15	n/a	n/a			
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH							
								Weight: 96 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)


**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** All bearings 4-0-0 except (jt=length) 24=0-7-14, 15=0-4-8.  
 (lb) - Max Uplift All uplift 100 lb or less at joint(s) 12 except 14=-517(LC 3), 14=-401(LC 1), 13=-129(LC 3)  
 Max Grav All reactions 250 lb or less at joint(s) 13, 12 except 24=401(LC 1), 15=2117(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 24-25=-397/0, 1-25=-396/0, 1-2=-520/0, 2-3=-1142/0, 3-4=-1142/0, 4-5=-1209/0, 5-6=-746/0, 7-8=0/1716, 8-9=0/728, 9-10=0/310  
 BOT CHORD 22-23=0/968, 21-22=0/1300, 20-21=0/1300, 19-20=0/1100, 18-19=0/371, 17-18=0/371, 16-17=-605/0, 15-16=-605/0, 14-15=-1716/0, 13-14=-728/0  
 WEBS 9-14=-398/0, 8-15=-835/0, 8-14=0/1252, 9-13=0/513, 10-13=-328/0, 1-23=0/591, 2-23=-547/0, 5-19=-432/0, 6-19=0/459, 6-17=-733/0, 7-17=0/591, 7-15=-1634/0

**NOTES-** (6-9)  
 1) Unbalanced floor live loads have been considered for this design.  
 2) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 12 except (jt=lb) 14=517, 13=129.  
 3) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.  
 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
 5) CAUTION, Do not erect truss backwards.  
 6) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.  
 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.  
 8) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.  
 9) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

**LOAD CASE(S)** Standard  
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
 Uniform Loads (plf)  
 Vert: 12-24=-7, 1-11=-67



10/14/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded continuously in accordance with the design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-31	Floor	1	1	Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:57 2024 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-hglyTskHse?GTyC5MQqEuinBfN1Fq3WCozBNe3yT6Zq

**LOAD CASE(S)** Standard

- Concentrated Loads (lb)  
Vert: 7=-735
- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-24=-7, 1-11=-67  
Concentrated Loads (lb)  
Vert: 7=-735
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-24=-7, 1-8=-67, 8-11=-13  
Concentrated Loads (lb)  
Vert: 7=-735
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-24=-7, 1-8=-13, 8-11=-67  
Concentrated Loads (lb)  
Vert: 7=-735
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-24=-7, 1-8=-67, 8-11=-13  
Concentrated Loads (lb)  
Vert: 7=-735
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-24=-7, 1-8=-13, 8-11=-67  
Concentrated Loads (lb)  
Vert: 7=-735



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.



Job 24-8565-F01	Truss F1-32	Truss Type Floor	Qty 5	Ply 1	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC	# 53379
--------------------	----------------	---------------------	----------	----------	--	---------

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:58 2024 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-9tJKgClvdx7746nHw7LTRvKLGnNIZaEL1DxwAVyT6Zp




Plate Offsets (X,Y)-- [10:0-1-8,Edge], [23:Edge,0-1-8]	
<b>LOADING</b> (psf)	<b>SPACING-</b> 1-4-0
TCLL 40.0	Plate Grip DOL 1.00
TCDL 10.0	Lumber DOL 1.00
BCLL 0.0	Rep Stress Incr NO
BCDL 5.0	Code IRC2021/TPI2014
<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d
TC 0.49	Vert(LL) -0.05 20 >999 480
BC 0.29	Vert(CT) -0.08 19 >999 360
WB 0.37	Horz(CT) 0.01 14 n/a n/a
Matrix-SH	
<b>PLATES</b>	<b>GRIP</b>
MT20	244/190
Weight: 94 lb FT = 20%F, 11%E	


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 23=407/0-7-14 (min. 0-1-8), 11=-125/0-8-0 (min. 0-1-8), 14=1757/0-4-8 (min. 0-1-8)  
Max Uplift 11=-244(LC 3)  
Max Grav 23=410(LC 3), 11=30(LC 4), 14=1757(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 23-24=-407/0, 1-24=-406/0, 1-2=-535/0, 2-3=-1185/0, 3-4=-1185/0, 4-5=-1281/0, 5-6=-846/0, 7-8=0/1598, 8-9=0/1106, 9-10=0/289  
BOT CHORD 21-22=0/997, 20-21=0/1358, 19-20=0/1358, 18-19=0/1186, 17-18=0/484, 16-17=0/484, 15-16=-512/0, 14-15=-512/0, 13-14=-1598/0, 12-13=-675/0  
WEBS 8-14=-530/0, 8-13=0/694, 9-13=-651/0, 9-12=0/471, 10-12=-372/0, 1-22=0/608, 2-22=-564/0, 5-18=-420/0, 6-18=0/446, 6-16=-725/0, 7-16=0/581, 7-14=-1638/0

- NOTES-** (6-9)
- Unbalanced floor live loads have been considered for this design.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 11=244.
  - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

**LOAD CASE(S)** Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 11-23=-7, 1-10=-67  
Concentrated Loads (lb)  
Vert: 7=-735



10/14/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded continuously in accordance with the design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-32	Floor	5	1	Job Reference (optional) # 53379

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:58 2024 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-9tJKgClvdx7746nHw7LTRvKLGNiZaEL1DxwAVyT6Zp

**LOAD CASE(S)** Standard

- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 11-23=-7, 1-10=-67
  - Concentrated Loads (lb)
    - Vert: 7=-735
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 11-23=-7, 1-8=-67, 8-10=-13
  - Concentrated Loads (lb)
    - Vert: 7=-735
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 11-23=-7, 1-8=-13, 8-10=-67
  - Concentrated Loads (lb)
    - Vert: 7=-735
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 11-23=-7, 1-8=-67, 8-10=-13
  - Concentrated Loads (lb)
    - Vert: 7=-735
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)
    - Vert: 11-23=-7, 1-8=-13, 8-10=-67
  - Concentrated Loads (lb)
    - Vert: 7=-735



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 HONEYCUTT HILLS   371 SHELBY MEADOW LANE ANGIER, NC
24-8565-F01	F1-33	Floor Supported Gable	1	1	
					<b># 53379</b>

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Oct 15 17:32:59 2024 Page 1  
 ID:5fxLxLn?C6dWjia?SHK4thzkcYI-d3sitYmXOFF\_iGLTTrtiz7sdoBnul6qVGtgTiyT6Zo

0-1-8

0-1-8

Scale = 1:30.1




Plate Offsets (X,Y)-- [9:0-1-8,Edge], [24:0-1-8,Edge], [32:Edge,0-1-8]					
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.06	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 17 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
				Weight: 74 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

**REACTIONS.** All bearings 18-1-14.  
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 32, 17, 31, 30, 29, 28, 27, 26, 25, 24, 23, 22, 20, 19, 18

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (5-8)
- Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

**LOAD CASE(S)** Standard



10/14/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.