

	JUS414	USP	23	NA	16d/3-1/2"	16d/3-1/2"
				•		

Products						
PlotID	Length	Product	Plies	Net Qty	Fab Type	
DB1	5-0-0	1-3/4"x 9-1/4" LVL Kerto-S	2	2	FF	
FB1	16-0-0	1-3/4"x 14" LVL Kerto-S	3	3	FF	
FB2	9-0-0	1-3/4"x 14" LVL Kerto-S	2	2	FF	
GDH	14-0-0	2x12 SP No.2	3	3	FF	

Truss Placement Plan SCALE: 1/4"=1'

LOAD CHART FOR JACK STUDS (BASED ON TABLES P502.5(1) & (b))
NUMBER OF JACK STUDS REQUIRED @ EA END OF
HEADER/GIRDER

END REACTION
(UP TO)
REQ'D STUDS FOR

5100 2

7650 3

10200 4

12750 5

15300 6

END REACTION
(UP TO)
REQ'D STUBS FOR
(2) PLY HEADER

1700 1 3400 2

5100 3

6800 4

8500 5

10200 6

11900 7 13600 8 15300 9

	_				
CK STUDS (1) & (b)) D @ EA END OF	BUILDER	A & G Residential	CITY / CO. Coats / Harnett		THIS IS A TE These trusses the building des sheets for each
3400 1 6800 2 10200 3 13600 4 17000 5	JOB NAME	Lot 11 Turlington Acres	ADDRESS	Bennett Rd.	is responsible for the overall struct walls, and colur regarding bracin or online @ sbc Bearing reactic prescriptive Co
	PLAN	Hampton 2nd Floor	MODEL	Floor Trusses	
	SEAL DATE	3/12/2020	DATE REV.	10/14/24	(derived from foundation siz than 3000# but be retained to
	QUOTE#		DRAWN BY	Marshall Naylor	specified in the retained to des
	JOB#	J1024-5560	SALES REP.	Marshall Naylor	Signature_

____ = Indicates Left End of Truss (Reference Engineered Truss Drawing) Do NOT Erect Truss Backwards

A TRUSS PLACEMENT DIAGRAM ONLY.

sees are designed as individual building components to be incorporated into g design at the specification of the building designer. See individual design each truss design identified on the placement drawing. The building designer bile for temporary and permanent bracing of the roof and floor system and for structure. The design of the truss support structure including headers, beams, columns is the responsibility of the building designer. For general guidance oracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package scindustry.com actions less than or equal to 3000# are deemed to comply with the ve Code requirements. The contractor shall refer to the attached Tables rom the prescriptive Code requirements) to determine the minimum a size and number of wood studs required to support reactions greater # but not greater than 15000#. A registered design professional shall d to design the support system for any reaction that exceeds those in the attached Tables. A registered design professional shall be to design the support system for all reactions that exceed 15000#. Marshall Naylor

Marshall Naylor



Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787 Fax: (910) 864-4444