

Job 4337300	Truss A01	Truss Type Common	Qty 4	Ply 1	Job Reference (optional)
----------------	--------------	----------------------	----------	----------	--------------------------




Plate Offsets (X, Y): [2:0-3-8,Edge], [6:0-4-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	-0.08	8-11	>999	360	MT20 244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.50	Vert(CT)	-0.14	8-11	>999	240	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.12	Horz(CT)	0.03	2	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MS		Wind(LL)	0.08	8-11	>999	240	Weight: 64 lb FT = 20%

#### LUMBER

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3  
SLIDER Left 2x4 SP No.3 -- 1-11-12, Right 2x4 SP No.3 -- 1-11-12

**REACTIONS** (lb/size) 2=637/0-3-8, (min. 0-1-8), 6=637/0-3-8, (min. 0-1-8)  
Max Horiz 2=-108 (LC 10)  
Max Uplift 2=-28 (LC 12), 6=-28 (LC 13)

**FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-354/54, 3-17=-616/31, 17-18=-552/44, 4-18=-542/66, 4-19=-542/66, 19-20=-552/44, 5-20=-616/31, 5-6=-345/0  
BOT CHORD 2-8=-184/460, 6-8=0/460  
WEBS 4-8=0/323

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TCCL=6.0psf; BCCL=6.0psf; h=32ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 7-2-8, Exterior (2) 7-2-8 to 10-2-8, Interior (1) 10-2-8 to 15-5-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 28 lb uplift at joint 2 and 28 lb uplift at joint 6.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


**LOAD CASE(S)** Standard

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

Job 4337300	Truss A01G	Truss Type Common Supported Gable	Qty 1	Ply 1	Job Reference (optional)
----------------	---------------	--------------------------------------	----------	----------	--------------------------



Scale = 1:37.5

Plate Offsets (X, Y): [10:0-1-9,0-0-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.10	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.07	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.05	Horz(CT)	0.00	10	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MR							Weight: 77 lb	FT = 20%

**LUMBER**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3  
OTHERS 2x4 SP No.3

**BRACING**  
TOP CHORD Structural wood sheathing directly applied or 6'-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10'-0-0 oc bracing.

**REACTIONS** All bearings 14-5-0.  
(lb) - Max Horiz 16=-121 (LC 10)  
Max Uplift All uplift 100 (lb) or less at joint(s) 10, 11, 12, 14, 15, 16  
Max Grav All reactions 250 (lb) or less at joint(s) 10, 11, 12, 13, 14, 15, 16


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TC DL=6.0psf; BCDL=6.0psf; h=32ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Corner (3) -1-0-0 to 2-0-0, Exterior (2) 2-0-0 to 7-2-8, Corner (3) 7-2-8 to 10-2-8, Exterior (2) 10-2-8 to 15-5-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 16, 10, 14, 15, 12, 11.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 4337300	Truss A01SG	Truss Type Common Structural Gable	Qty 1	Ply 1	Job Reference (optional)
----------------	----------------	---------------------------------------	----------	----------	--------------------------



Scale = 1:54.2

Plate Offsets (X, Y): [17:0-3-8,0-0-1]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.43	Vert(LL)	-0.12	19-40	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.61	Vert(CT)	-0.25	19-40	>688	240	MT20HS	187/143
BCLL	0.0*	Rep Stress Incr	YES	WB	0.48	Horz(CT)	-0.01	17	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MS		Wind(LL)	0.06	19-40	>999	240		Weight: 210 lb FT = 20%

**LUMBER**

TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3  
 OTHERS 2x4 SP No.3  
 SLIDER Left 2x4 SP No.3 -- 1-11-12, Right 2x4 SP No.3 -- 1-11-12

**BRACING**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 JOINTS 1 Brace at Jt(s): 29, 32

**REACTIONS** All bearings 12-5-8, except 17=0-3-8, 22=0-3-8  
 (lb) - Max Horiz 2=186 (LC 11), 34=186 (LC 11)  
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 17, 23, 26, 27, 28, 34  
 Max Grav All reactions 250 (lb) or less at joint(s) 22, 23, 26, 27 except  
 2=257 (LC 20), 17=755 (LC 1), 25=513 (LC 1), 28=263 (LC 19), 34=257 (LC 20)


**FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 10-11=-262/194, 11-12=-634/229, 12-44=-610/194, 13-44=-621/189, 13-14=-653/160, 14-15=-680/146, 15-45=-744/121,  
 16-45=-790/89, 16-17=-683/0  
 BOT CHORD 17-19=0/619  
 WEBS 11-32=-115/581, 32-33=-125/621, 19-33=-89/580, 15-19=-318/151, 25-30=-463/2, 29-30=-360/0, 11-29=-402/0

**NOTES**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TCCL=6.0psf; BCCL=6.0psf; h=32ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 13-1-12, Exterior (2) 13-1-12 to 16-1-12, Interior (1) 16-1-12 to 27-7-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are MT20 plates unless otherwise indicated.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 17, 23, 26, 28, 2.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 4337300	Truss A02	Truss Type Common	Qty 5	Ply 1	Job Reference (optional)
----------------	--------------	----------------------	----------	----------	--------------------------



Scale = 1:54.2

Plate Offsets (X, Y): [2:0-3-8,0-0-1], [10:0-3-8,0-0-1]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.54	Vert(LL)	-0.34	12-14	>935	360	MT20 244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.84	Vert(CT)	-0.46	12-14	>688	240	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.24	Horz(CT)	0.04	10	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MS		Wind(LL)	0.05	14-17	>999	240	Weight: 142 lb FT = 20%

**LUMBER**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3  
 SLIDER Left 2x4 SP No.3 -- 1-11-12, Right 2x4 SP No.3 -- 1-11-12

**BRACING**  
 TOP CHORD  
 BOT CHORD

Structural wood sheathing directly applied or 4-4-9 oc purlins.  
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


**REACTIONS** (lb/size) 2=1123/0-3-8, (min. 0-1-8), 10=1123/0-3-8, (min. 0-1-8)  
 Max Horiz 2=188 (LC 11)  
 Max Uplift 2=-40 (LC 12), 10=-40 (LC 13)

**FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-829/0, 3-23=-1440/38, 4-23=-1305/70, 4-5=-1349/104, 5-24=-1251/123, 6-24=-1251/143, 6-25=-1249/143, 7-25=-1249/123, 7-8=-1347/104, 8-26=-1303/70, 9-26=-1440/38, 9-10=-762/0  
 BOT CHORD 2-14=-188/1260, 13-14=0/835, 13-27=0/835, 12-27=0/835, 10-12=0/1138  
 WEBS 4-14=-354/198, 6-14=-91/659, 6-12=-91/655, 8-12=-354/198

- NOTES**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=32ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 13-3-8, Exterior (2) 13-3-8 to 16-3-8, Interior (1) 16-3-8 to 27-7-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 40 lb uplift at joint 2 and 40 lb uplift at joint 10.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 4337300	Truss A02G	Truss Type Common Supported Gable	Qty 1	Ply 1	Job Reference (optional)
----------------	---------------	--------------------------------------	----------	----------	--------------------------



Scale = 1:35

Plate Offsets (X, Y): [9:0-1-9,0-0-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.00	9	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MR							Weight: 61 lb	FT = 20%

**LUMBER**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3  
 OTHERS 2x4 SP No.3

**BRACING**  
 TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10'-0" oc bracing.

**REACTIONS** All bearings 12'-0".  
 (lb) - Max Horiz 15=100 (LC 9)  
 Max Uplift All uplift 100 (lb) or less at joint(s) 9, 10, 11, 13, 14, 15  
 Max Grav All reactions 250 (lb) or less at joint(s) 9, 10, 11, 12, 13, 14, 15


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TCCL=6.0psf; BCCL=6.0psf; h=32ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Corner (3) -1-0-0 to 2-0-0, Exterior (2) 2-0-0 to 6-0-0, Corner (3) 6-0-0 to 9-0-0, Exterior (2) 9-0-0 to 11-10-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 2'-0" oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-0"-0" tall by 2'-0"-0" wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 15, 9, 13, 14, 11, 10.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 4337300	Truss A03	Truss Type Common	Qty 2	Ply 1	Job Reference (optional)
----------------	--------------	----------------------	----------	----------	--------------------------



Scale = 1:37.4

Plate Offsets (X, Y): [2:0-4-0,Edge], [6:0-3-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.41	Vert(LL)	-0.04	7-10	>999	360	MT20 244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.36	Vert(CT)	-0.07	7-10	>999	240	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.10	Horz(CT)	0.02	2	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MS		Wind(LL)	0.04	7-10	>999	240	Weight: 54 lb FT = 20%

**LUMBER**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3  
 SLIDER Left 2x4 SP No.3 -- 1-11-12, Right 2x4 SP No.3 -- 1-11-12

**BRACING**  
 TOP CHORD  
 BOT CHORD

Structural wood sheathing directly applied or 6'-0" oc purlins.  
 Rigid ceiling directly applied or 10'-0" oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


**REACTIONS** (lb/size) 2=543/0-3-8, (min. 0-1-8), 6=477/0-3-8, (min. 0-1-8)  
 Max Horiz 2=88 (LC 9)  
 Max Uplift 2=-25 (LC 12), 6=-10 (LC 13)

**FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-285/0, 3-16=-498/37, 16-17=-464/44, 4-17=-454/64, 4-18=-454/67, 5-18=-463/47, 5-6=-293/0  
 BOT CHORD 2-7=-134/378, 6-7=0/378  
 WEBS 4-7=0/265

- NOTES**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TCCL=6.0psf; BCCL=6.0psf; h=32ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 6-0-0, Exterior (2) 6-0-0 to 9-0-0, Interior (1) 9-0-0 to 12-0-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-0" tall by 2'-0" wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 10 lb uplift at joint 6 and 25 lb uplift at joint 2.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 4337300	Truss AC01	Truss Type Common	Qty 6	Ply 1	Job Reference (optional)
----------------	---------------	----------------------	----------	----------	--------------------------



Scale = 1:69.1

Plate Offsets (X, Y): [2:Edge,0-0-12], [8:Edge,0-0-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.55	Vert(LL)	-0.15	13	>999	360	MT20 244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.67	Vert(CT)	-0.27	13	>999	240	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.40	Horz(CT)	0.03	8	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MS		Wind(LL)	0.03	15	>999	240	Weight: 171 lb FT = 20%

**LUMBER**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x6 SP No.2 \*Except\* B2:2x4 SP No.3  
 WEBS 2x4 SP No.3  
 WEDGE Left: 2x4 SP No.3  
 Right: 2x4 SP No.3

**BRACING**  
 TOP CHORD Structural wood sheathing directly applied or 4-0-14 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. Except:  
 6-0-0 oc bracing: 12-15

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


**REACTIONS** (lb/size) 2=1205/0-3-8, (min. 0-1-8), 8=1205/0-3-8, (min. 0-1-8)  
 Max Horiz 2=-188 (LC 10)  
 Max Grav 2=1233 (LC 19), 8=1233 (LC 20)

**FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-23=-1721/0, 3-23=-1558/0, 3-4=-1593/10, 4-24=-1494/29, 5-24=-1493/49, 5-25=-1493/49, 6-25=-1494/29,  
 6-7=-1593/10, 7-26=-1598/0, 8-26=-1721/0  
 BOT CHORD 2-16=-180/1475, 14-16=0/1077, 14-27=0/1077, 11-27=0/1077, 11-28=0/1077, 10-28=0/1077, 8-10=0/1352  
 WEBS 5-12=-33/809, 10-12=-59/707, 7-10=-359/199, 15-16=-60/707, 5-15=-33/809, 3-16=-358/199

- NOTES**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TCCL=6.0psf; BCDL=6.0psf; h=32ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 13-3-8, Exterior (2) 13-3-8 to 16-3-8, Interior (1) 16-3-8 to 27-7-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 4337300	Truss H01G	Truss Type Half Hip Supported Gable	Qty 1	Ply 1	Job Reference (optional)
----------------	---------------	----------------------------------------	----------	----------	--------------------------



Scale = 1:29.9

Plate Offsets (X, Y): [3:0-2-0,0-2-13]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.32	Vert(LL)	n/a	-	n/a	999	MT20 244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.36	Vert(CT)	n/a	-	n/a	999	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.02	4	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MP							Weight: 17 lb FT = 20%

**LUMBER**

TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2

**REACTIONS** All bearings 5-0-0.

(lb) - Max Horiz 2=24 (LC 8), 6=24 (LC 8)  
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 6  
 Max Grav All reactions 250 (lb) or less at joint(s) 4, 5 except 2=267 (LC 1), 6=267 (LC 1)

**FORCES**

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TCCL=6.0psf; BCCL=6.0psf; h=32ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Corner (3) -1-0-0 to 1-0-0, Exterior (2) 1-0-0 to 5-0-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Provide adequate drainage to prevent water ponding.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4, 2.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**BRACING**

TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins, except 2-0-0 oc purlins: 3-4.

BOT CHORD

Rigid ceiling directly applied or 10-0-0 oc bracing.  
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**LOAD CASE(S)** Standard



Job 4337300	Truss T01	Truss Type Roof Special	Qty 9	Ply 1	Job Reference (optional)
----------------	--------------	----------------------------	----------	----------	--------------------------




Plate Offsets (X, Y): [2:0-2-15,0-0-14], [4:0-3-0,0-3-0], [6:0-3-0,0-3-0], [8:0-3-12,0-0-1]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.87	Vert(LL)	-0.16	11-12	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.98	Vert(CT)	-0.39	11-12	>826	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.71	Horz(CT)	0.19	8	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MS		Wind(LL)	0.10	11-12	>999	240	Weight: 145 lb	FT = 20%

**LUMBER**  
 TOP CHORD 2x4 SP No.1 \*Except\* T3,T4:2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3  
 SLIDER Left 2x4 SP No.3 -- 1-11-12, Right 2x4 SP No.3 -- 1-11-12

**BRACING**  
 TOP CHORD Structural wood sheathing directly applied.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:  
 2-2-0 oc bracing: 2-12.  
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


**REACTIONS** (lb/size) 2=1123/0-3-8, (min. 0-1-8), 8=1123/0-3-8, (min. 0-1-8)  
 Max Horiz 2=188 (LC 11)  
 Max Uplift 2=-39 (LC 12), 8=-39 (LC 13)

**FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-949/0, 3-21=-2513/105, 4-21=-2493/137, 4-22=-2417/221, 5-22=-2298/240, 5-23=-989/115, 6-23=-1125/94,  
 6-24=-1331/60, 7-24=-1471/32, 7-8=-597/0  
 BOT CHORD 2-12=-181/2126, 11-12=0/875, 10-11=0/1172, 8-10=0/1171  
 WEBS 4-12=-303/201, 5-12=-193/1739, 5-11=-78/251, 6-11=-459/156

- NOTES**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TCCL=6.0psf; BCCL=6.0psf; h=32ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 13-3-8, Exterior (2) 13-3-8 to 16-3-8, Interior (1) 16-3-8 to 27-7-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
  - Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 39 lb uplift at joint 2 and 39 lb uplift at joint 8.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 4337300	Truss T01SG	Truss Type Roof Special Structural Gable	Qty 1	Ply 1	Job Reference (optional)
----------------	----------------	---------------------------------------------	----------	----------	--------------------------



Scale = 1:57.3

Plate Offsets (X, Y): [2:0-2-12,0-0-14], [20:0-4-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.40	Vert(LL)	-0.03	19-20	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.37	Vert(CT)	-0.07	19-20	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.46	Horz(CT)	0.01	17	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MS		Wind(LL)	0.03	19-36	>999	240	Weight: 179 lb	FT = 20%

**LUMBER**

TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3  
 OTHERS 2x4 SP No.3  
 SLIDER Left 2x4 SP No.3 -- 1-11-12, Right 2x4 SP No.3 -- 1-11-12

**BRACING**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 21-22,20-21.  
 WEBS 1 Row at midpt 11-20  
 JOINTS 1 Brace at Jt(s): 26, 28, 29

**REACTIONS**

All bearings 14-10-8, except 17=0-3-8  
 (lb) - Max Horiz 2=188 (LC 11), 30=188 (LC 11)  
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 17, 21, 24, 30 except 20=226 (LC 13), 22=-130 (LC 12), 23=-295 (LC 19)  
 Max Grav All reactions 250 (lb) or less at joint(s) 23 except 2=259 (LC 20), 17=541 (LC 1), 20=653 (LC 20), 21=284 (LC 19), 22=622 (LC 19), 24=342 (LC 19), 30=259 (LC 20)

**FORCES**

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 15-39=-457/1, 16-39=-492/0, 16-17=-295/0  
 BOT CHORD 19-20=0/380, 17-19=0/380  
 WEBS 7-22=-385/224, 20-28=-508/149, 28-29=-487/132, 15-29=-484/134, 15-19=0/275, 11-20=-271/91, 6-23=-160/269


**NOTES**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TCCL=6.0psf; BCCL=6.0psf; h=32ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 13-3-8, Exterior (2) 13-3-8 to 16-3-8, Interior (1) 16-3-8 to 27-7-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 17, 21, 24, 2 except (jt=lb) 22=129, 20=226, 23=295.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

Job 4337300	Truss T02	Truss Type Roof Special	Qty 7	Ply 1	Job Reference (optional)
----------------	--------------	----------------------------	----------	----------	--------------------------



Scale = 1:31.7

Plate Offsets (X, Y): [4:0-2-0,0-1-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.30	Vert(LL)	-0.02	4-7	>999	360	MT20 244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.25	Vert(CT)	-0.05	4-7	>999	240	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MP		Wind(LL)	0.02	4-7	>999	240	Weight: 21 lb FT = 20%

**LUMBER**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3  
OTHERS 2x4 SP No.3

**BRACING**  
TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS** (lb/size) 2=255/0-3-0, (min. 0-1-8), 4=182/0-1-8, (min. 0-1-8)  
Max Horiz 4=-59 (LC 10)  
Max Uplift 2=-44 (LC 9), 4=-19 (LC 13)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 1) Wind: ASCE 7-10; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=32ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) 0-3-8 to 4-3-0, Interior (1) 4-3-0 to 6-0-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
  - 4) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
  - 5) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 44 lb uplift at joint 2 and 19 lb uplift at joint 4.
  - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard