



CHANGING THE WAY THE WORLD INSULATES™



LEARN MORE AT

ENVERGESPRAYFOAM.COM

## INSULATION CERTIFICATE

Date Installation Completed 11/12/25Building Address 9006 CHRISTIAN LIGHT ROADCity/State/Zip FUGUAY - MARINA, NCApplication Contractor (company name) SL-W INSULATIONAddress 351 HORN DRIVECity/State/Zip GARRETT NC 27529Phone (919) 906-7680 Email BOYCE.Hudson@SLW.COMProduct Installed Closed Cell Spray Foam Baffles & Roof Deck**Area Insulated**

Exterior Stud Wall

Average Thickness

R-Value

3"22

Ceiling

Average Thickness

R-Value

3"22

Roof Deck

Average Thickness

R-Value

3"22

Crawl Space/Basement

Average Thickness

R-Value

Additional Areas Insulated

Gable End Walls 3"R- 22

I, (print name), BRANDON NICHOLLS as an independent contractor, certify that the Enverge® insulation installed on this project was applied in accordance with the Enverge recommendations and specifications as stated on the product data sheet and the Enverge application specifications in the amount as indicated on this certification.

BN  
(signature)/ 11/19/25  
(date)

Product	R-Value	3.5"	5.5"	R-13	R-20	R-30	R-38	R-49
Enverge® ProFill®	R-4.04 at 1"   R-3.93/inch at >3.5"	R-14	R-22	3.3"	5.1"	7.6"	9.7"	12.5"
Enverge® 183® HFO	R-6.4 at 1"   R-6.67/inch at >3.5"	R-23	R-37	2.0"	3.0"	4.5"	5.7"	7.4"
Enverge® OnePass® HFC	R-6.5 at 1"   R-7.2/inch at >3.5"	R-25	R-40	1.9"	2.8"	4.2"	5.3"	6.8"
Enverge® OnePass® HFO	R-7.2 at 1"   R-7.2/inch at >3.5"	R-25	R-39	1.9"	2.9"	4.3"	5.4"	7"
Enverge® SucraSeal®	R-4.0 at 1"   R-4.0/inch at >3.5"	R-13	R-21	3.5"	5.3"	8"	10"	13"
Enverge® EasySeal .5®	R-3.7 at 1"   R-3.7/inch at >3.5"	R-13	R-21	3.5"	5.3"	8"	10"	13"
Enverge® Nexseal®	R-7.2 at 1"   R-7.2/inch at >3.5"	R-25	R-39	1.9"	2.9"	4.3"	5.4"	7"
Enverge® Nexseal® LE	R-7.2 at 1"   R-7.2/inch at >3.5"	R-25	R-39	1.9"	2.9"	4.3"	5.4"	7"