

Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 54877

JOB: 24-B007-F01

JOB NAME: LOT 0.0012 CAMPBELL RIDGE

Wind Code: N/A

Wind Speed: Vult= N/A

Exposure Category: N/A

Mean Roof Height (feet): N/A

These truss designs comply with IRC 2018 as well as IRC 2021.

23 Truss Design(s)

Trusses:

F101, F102, F103, F103A, F103B, F104, F105, F106, F107, F108, F109, F110, F111, F111A, F112, F114, F115, F115A, F115B, F115C, F115D, F116, F117



12/7/2024

Mark Morris

Warning !—Verify design parameters and read notes before use.

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSL/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F101	Floor Supported Gable	1	1	Job Reference (optional) # 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:25 2024 Page 1
 ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-qBAv0ibm_10DLRpzH239otDsCOBRPXVWZstQVqyBJkO

0-1-8

Scale = 1:32.7




Plate Offsets (X,Y)-- [9:0-1-8,Edge], [26:0-1-8,Edge], [34:Edge,0-1-8]					
LOADING (psf)	SPACING- 1-7-3	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.05	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 18 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
				Weight: 86 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 20-0-6.
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 18, 34, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 30, 31, 32, 33

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (7-8)
- All plates are 1.5x3 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F102	Floor	7	1	
					# 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:27 2024 Page 1
 ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-malfROd1WfGxbIzLOT6dtI17EBDbtJnp0AMXaiyBjKm





Plate Offsets (X,Y)-- [11:0-1-8,Edge], [17:0-1-8,Edge], [22:0-1-8,Edge], [23:0-1-8,Edge], [24:Edge,0-3-0]

LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.33	Vert(LL)	-0.06	15-16	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.28	Vert(CT)	-0.05	16	>999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.49	Horz(CT)	0.01	14	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 102 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 24=336/0-5-6 (min. 0-1-8), 14=425/0-4-8 (min. 0-1-8), 19=1694/0-4-8 (min. 0-1-8)
 Max Grav 24=352(LC 10), 14=466(LC 4), 19=1694(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-668/8, 3-4=-668/8, 4-5=-668/8, 5-6=-124/340, 6-7=-124/340, 7-8=0/1220, 8-9=0/1221, 9-10=-1158/0,
 10-11=-1158/0, 11-12=-848/0
 BOT CHORD 23-24=0/425, 22-23=-8/668, 21-22=-177/489, 20-21=-507/0, 19-20=-507/0, 18-19=0/955, 17-18=0/955, 16-17=0/1158,
 15-16=0/1158, 14-15=0/544
 WEBS 5-22=0/394, 5-21=-528/0, 7-21=0/540, 7-19=-877/0, 11-15=-396/0, 12-15=0/396, 12-14=-690/0, 9-19=-2022/0,
 9-17=0/397, 2-24=-513/0, 2-23=-55/300

- NOTES-** (5-6)
- Unbalanced floor live loads have been considered for this design.
 - All plates are 3x4 MT20 unless otherwise indicated.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 14-24=-8, 1-13=-80
 Concentrated Loads (lb)
 Vert: 9=-720




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B007-F01	Truss F103	Truss Type FLOOR	Qty 3	Ply 1	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC Job Reference (optional) # 54877
--------------------	---------------	---------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:27 2024 Page 1
ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-malfR0d1WfGxblzLOT6dtll5xB6CtJ_p0AMXaiyBJkM



Scale = 1:17.4




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [4:0-1-8,Edge], [10:0-1-8,Edge]

LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00		TC 0.48	Vert(LL) -0.05	9	>999	480	MT20	244/190	
TCDL 10.0	Lumber DOL 1.00		BC 0.75	Vert(CT) -0.13	10-11	>905	360			
BCLL 0.0	Rep Stress Incr YES		WB 0.47	Horz(CT) 0.02	7	n/a	n/a			
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH							Weight: 52 lb FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 12=992/0-4-8 (min. 0-1-8), 7=564/0-4-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1619/0, 3-4=-1619/0, 4-5=-1095/0
BOT CHORD 11-12=0/1710, 10-11=0/1711, 9-10=0/1619, 8-9=0/1619, 7-8=0/651
WEBS 4-8=-703/0, 5-8=0/578, 5-7=-826/0, 2-10=-290/0, 2-12=-1944/0

- NOTES-** (4-5)
- Unbalanced floor live loads have been considered for this design.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 7-12=-8, 1-6=-80
Concentrated Loads (lb)
Vert: 2=-720




12/7/2024


Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B007-F01	Truss F103B	Truss Type Floor	Qty 1	Ply 1	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC Job Reference (optional) # 54877
--------------------	----------------	---------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:29 2024 Page 1
ID:UMCU2t6gUxCLqMIKo_q9qxyVB1-izPQr4eH2GWfq27kWt85zjNVD?tQLHw6UureebyBJkK



Scale = 1:17.4



1-6-0	3-6-8	3-8-0	4-8-0	5-8-0	7-0-8	9-6-0	9-9-0
1-6-0	2-0-8	0-1-8	1-0-0	1-0-0	1-4-8	2-5-8	0-3-0

Plate Offsets (X,Y)-- [4:0-1-8,Edge], [10:0-1-8,Edge], [12:Edge,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	1-7-3	TC 0.24	Vert(LL)	-0.04	9	>999	480	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.32	Vert(CT)	-0.05	9	>999	360		
BCLL 0.0	Lumber DOL 1.00	WB 0.25	Horz(CT)	0.01	7	n/a	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH							
	Code IRC2021/TPI2014							Weight: 50 lb	FT = 20%F, 11%E

LUMBER-

TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 12=418/0-4-8 (min. 0-1-8), 7=418/0-4-8 (min. 0-1-8)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-12=-409/0, 1-2=-425/0, 2-3=-928/0, 3-4=-928/0, 4-5=-727/0
BOT CHORD 10-11=0/811, 9-10=0/928, 8-9=0/928, 7-8=0/492
WEBS 1-11=0/533, 2-11=-502/0, 2-10=0/327, 4-8=-288/0, 5-8=0/306, 5-7=-624/0

NOTES- (4-5)

- Unbalanced floor live loads have been considered for this design.
- All plates are 3x4 MT20 unless otherwise indicated.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B007-F01	Truss F104	Truss Type FLOOR SUPPORTED GABL	Qty 1	Ply 1	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC Job Reference (optional) # 54877
--------------------	---------------	------------------------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:29 2024 Page 1
ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-izPQr4eH2GWfq27kwt85zjNYJ?yNLKV6UureebyBJkK



Scale = 1:8.5

Plate Offsets (X,Y)-- [5:0-1-8,Edge], [6:Edge,0-1-8]

LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.04	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.02	Horz(CT)	0.00	4	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-P							
									Weight: 16 lb	FT = 20%F, 11%E

LUMBER-

TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-5-6 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 6=38/2-5-6 (min. 0-1-8), 4=31/2-5-6 (min. 0-1-8), 5=119/2-5-6 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (6-7)

- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.
- Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F105	Floor	4	1	# 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:30 2024 Page 1
 ID:UMCU2t6gUxCLqMIko_q9qxyaVB1-A9zo3QfvpaeWSCiw3bfkVxwe6PBBe4h2Fi8bBB1yBJk





Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [10:0-1-8,Edge], [16:0-1-8,Edge], [26:Edge,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	1-7-3	TC 0.36	Vert(LL)	-0.07	23	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.45	Vert(CT)	-0.09	23	>999		
BCLL 0.0	Lumber DOL 1.00	WB 0.39	Horz(CT)	0.02	13	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH						
	Code IRC2021/TPI2014							
							Weight: 110 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. (lb/size) 26=488/0-5-6 (min. 0-1-8), 18=1073/0-4-8 (min. 0-1-8), 13=349/0-4-8 (min. 0-1-8)
 Max Grav 26=501(LC 10), 18=1073(LC 1), 13=388(LC 4)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 26-27=-497/0, 1-27=-496/0, 1-2=-551/0, 2-3=-1228/0, 3-4=-1369/0, 4-5=-1080/0, 5-6=-253/25, 6-7=-220/324, 7-8=-220/324, 8-9=-792/18, 9-10=-792/18, 10-11=-653/0
 BOT CHORD 24-25=0/1028, 23-24=0/1369, 22-23=0/1369, 21-22=0/1369, 20-21=0/796, 19-20=0/796, 18-19=-654/0, 17-18=-657/0, 16-17=-162/625, 15-16=-18/792, 14-15=-18/792, 13-14=0/460
 WEBS 9-16=-272/0, 6-18=-1032/0, 1-25=0/665, 2-25=-621/0, 2-24=0/260, 4-21=-440/0, 5-21=0/416, 5-19=-726/0, 6-19=0/817, 6-17=0/565, 8-17=-599/0, 8-16=0/487, 11-14=-11/252, 11-13=-584/0

- NOTES-** (5-6)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) CAUTION, Do not erect truss backwards.
 - 5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard





12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F106	FLOOR	3	1	
					# 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:32 2024 Page 1
 ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-7Y5YU5h9LBuEhWrJB0hoaM?_fct2YcQYAS4IFwyBJkH



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	1-7-3	TC 0.35	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.46	Vert(LL) -0.07 24-25 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.33	Vert(CT) -0.09 24 >999 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.02 14 n/a n/a		
	Code IRC2021/TPI2014				Weight: 113 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 27=484/0-5-6 (min. 0-1-8), 19=1715/0-4-8 (min. 0-1-8), 14=352/0-4-8 (min. 0-1-8)
 Max Grav 27=498(LC 10), 19=1715(LC 1), 14=388(LC 4)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 27-28=-494/0, 1-28=-493/0, 1-2=-548/0, 2-3=-1218/0, 3-4=-1355/0, 4-5=-1056/0,
 6-7=0/723, 7-8=-224/330, 8-9=-224/330, 9-10=-791/20, 10-11=-791/20, 11-12=-653/0
 BOT CHORD 25-26=0/1022, 24-25=0/1355, 23-24=0/1355, 22-23=0/1355, 21-22=0/765, 20-21=0/765,
 19-20=-537/0, 18-19=-643/0, 17-18=-155/618, 16-17=-20/791, 15-16=-20/791, 14-15=0/460
 WEBS 6-19=-1266/0, 10-17=-261/0, 7-19=-576/0, 1-26=0/661, 2-26=-618/0, 2-25=0/255,
 12-15=-11/251, 12-14=-584/0, 4-22=-452/0, 5-22=0/423, 5-20=-724/0, 6-20=0/701,
 7-18=0/573, 9-18=-596/0, 9-17=0/472

- NOTES-** (5-6)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) CAUTION, Do not erect truss backwards.
 - 5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 14-27=-8, 1-13=-80
 Concentrated Loads (lb)
 Vert: 6=-640





12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F107	FLOOR	2	1	# 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:34 2024 Page 1
 ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-3wDJvniQto8ywp?hIRkGgn4Fm0Xb0WKrdmZPKpyBJkF



LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.70	Vert(LL)	-0.07 24-25	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.58	Vert(CT)	-0.12 15-16	>969	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.37	Horz(CT)	0.02 14	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 114 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 19-20,18-19.

REACTIONS. (lb/size) 27=495/0-5-6 (min. 0-1-8), 14=510/0-4-8 (min. 0-1-8), 19=1785/0-4-8 (min. 0-1-8)
 Max Grav 27=509(LC 10), 14=546(LC 4), 19=1785(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 27-28=-506/0, 1-28=-505/0, 13-14=-554/0, 1-2=-562/0, 2-3=-1261/0, 3-4=-1421/0,
 4-5=-1148/0, 5-6=-354/0, 6-7=0/543, 7-8=-467/56, 8-9=-467/56, 9-10=-1283/0,
 10-11=-1283/0, 11-12=-1283/0, 12-13=-621/0
 BOT CHORD 25-26=0/1049, 24-25=0/1421, 23-24=0/1421, 22-23=0/1421, 21-22=0/872, 20-21=0/872,
 19-20=-362/0, 18-19=-450/0, 17-18=0/973, 16-17=0/1283, 15-16=0/1117
 WEBS 6-19=-1225/0, 10-17=-413/0, 7-19=-675/0, 1-26=0/679, 2-26=-634/0, 2-25=0/276,
 3-25=-269/0, 13-15=0/779, 12-15=-646/0, 4-22=-409/0, 5-22=0/396, 5-20=-704/0,
 6-20=0/675, 7-18=0/690, 9-18=-741/0, 9-17=0/700

NOTES- (5-6)
 1) Unbalanced floor live loads have been considered for this design.
 2) All plates are 3x4 MT20 unless otherwise indicated.
 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 4) CAUTION, Do not erect truss backwards.
 5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 14-27=-8, 1-13=-80
 Concentrated Loads (lb)
 Vert: 6=-640 11=-240





12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F108	FLOOR	1	1	
					# 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:35 2024 Page 1
 ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-X7mh67J2e6GpYzaus8FVC_dWpQsslzi_sQlysFyBJkE



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	1-7-3	TC 0.30	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.58	Vert(LL) -0.08 10-11 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.36	Vert(CT) -0.12 10-11 >999 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.02 8 n/a n/a		
	Code IRC2021/TPI2014			Weight: 66 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 15=561/0-5-6 (min. 0-1-8), 8=1165/0-4-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 15-16=-559/0, 1-16=-558/0, 1-2=-630/0, 2-3=-1458/0, 3-4=-1720/0, 4-5=-1562/0, 5-6=-896/0
 BOT CHORD 13-14=0/1173, 12-13=0/1720, 11-12=0/1720, 10-11=0/1720, 9-10=0/1360, 8-9=0/468
 WEBS 1-14=0/761, 2-14=-707/0, 2-13=0/395, 3-13=-463/0, 4-10=-304/0, 5-10=0/281, 5-9=-603/0, 6-9=0/586, 6-8=-1291/0

- NOTES-** (6-7)
- Unbalanced floor live loads have been considered for this design.
 - All plates are 3x4 MT20 unless otherwise indicated.
 - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

- LOAD CASE(S)** Standard
- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 8-15=-8, 1-7=-80
 Concentrated Loads (lb)
 Vert: 6=-640
 - Dead: Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 8-15=-8, 1-7=-80
 Concentrated Loads (lb)
 Vert: 6=-640
 - 1st chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 8-15=-8, 1-4=-80, 4-7=-16
 Concentrated Loads (lb)
 Vert: 6=-640



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F108	FLOOR	1	1	Job Reference (optional) # 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:35 2024 Page 2
ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-X7mh67J2e6GpYzaus8FVC_dWpQsslzi_sQlysFyBJKe

LOAD CASE(S) Standard

- 4) 2nd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 8-15=-8, 1-3=-16, 3-7=-80
 - Concentrated Loads (lb)
 - Vert: 6=-640
- 5) 3rd chase Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 8-15=-8, 1-4=-80, 4-7=-16
 - Concentrated Loads (lb)
 - Vert: 6=-640
- 6) 4th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 8-15=-8, 1-3=-16, 3-7=-80
 - Concentrated Loads (lb)
 - Vert: 6=-640



12/7/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F109	FLOOR	1	1	Job Reference (optional) # 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:36 2024 Page 2
ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-?JK3JtKgPQPgA794QsmkICAFsq9wUOL8542WOhyBJkD

LOAD CASE(S) Standard

4) 2nd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 8-16=-10, 1-3=-20, 3-7=-100

Concentrated Loads (lb)

Vert: 6=-640

5) 3rd chase Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 8-16=-10, 1-4=-100, 4-7=-20

Concentrated Loads (lb)

Vert: 6=-640

6) 4th chase Dead: Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 8-16=-10, 1-3=-20, 3-7=-100

Concentrated Loads (lb)

Vert: 6=-640



12/7/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F110	Floor Supported Gable	1	1	
					# 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:36 2024 Page 1
 ID:UMCU2t6gUxCLqMKo_q9qxyaVB1-?JK3JTkgPQPgA794QsmkICAIqL0UUL8542WOhyBJkD

0₁-8

0₁-8

Scale = 1:20.9



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.05	in	(loc)	l/defl	L/d	MT20	244/190		
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(LL)	n/a	-	n/a	Weight: 59 lb FT = 20%F, 11%E			
BCLL	0.0	Rep Stress Incr	YES	WB	0.08	Vert(CT)	n/a	-	n/a				
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH		Horz(CT)	0.00	12	n/a				

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS. All bearings 12-10-8.
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 22, 12, 21, 20, 19, 18, 17, 16, 15, 14 except 13=739(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 10-13=-729/0

- NOTES-** (7-8)
- All plates are 1.5x3 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Load case(s) 1, 2 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

- LOAD CASE(S)** Standard
- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 12-22=-8, 1-11=-80
 Concentrated Loads (lb)
 Vert: 10=-640
 - Dead: Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 12-22=-8, 1-11=-80
 Concentrated Loads (lb)
 Vert: 10=-640



12/7/2024


Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B007-F01	Truss F111	Truss Type FLOOR	Qty 1	Ply 1	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC Job Reference (optional) # 54877
--------------------	---------------	---------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:37 2024 Page 1
ID:UMCU2t6gUxCLqMKo_q9qxyaVB1-TVuRXpkI9jXXnHkG_ZHzHPitRDhsDy5HJkn3w7yBJkC



Scale = 1:17.2



1-6-0	3-8-0	3-9-8	5-2-0	7-8-0	9-4-4	9-7-4
1-6-0	2-2-0	0-1-8	1-4-8	2-6-0	1-8-4	0-3-0

Plate Offsets (X,Y)-- [12:Edge,0-1-8]

LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.22	Vert(LL)	-0.00	11	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.03	Vert(CT)	-0.00	11	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.05	Horz(CT)	0.00	7	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						Weight: 54 lb	FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 9-10.

REACTIONS. All bearings 5-11-4 except (jt=length) 12=0-4-8.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 12, 7, 9, 8 except 10=513(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 3-10=-347/0

- NOTES-** (5-6)
- All plates are 3x4 MT20 unless otherwise indicated.
 - Load case(s) 1, 2 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

- LOAD CASE(S)**
- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 7-12=-8, 1-6=-80
Concentrated Loads (lb)
Vert: 3=-240
 - Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 7-12=-8, 1-6=-80
Concentrated Loads (lb)
Vert: 3=-240



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B007-F01	Truss F111A	Truss Type Floor	Qty 1	Ply 1	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC Job Reference (optional) # 54877
--------------------	----------------	---------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:37 2024 Page 1
ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-TVuRXpkI9jXXnHkG_ZHzHPithDhUDy_HJkn3w7yBJkC




Plate Offsets (X,Y)-- [6:Edge,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	1-7-3	TC 0.21	Vert(LL)	-0.00	5	>999	480	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.05	Vert(CT)	-0.00	4-5	>999	360		
BCLL 0.0	Lumber DOL 1.00	WB 0.06	Horz(CT)	0.00	4	n/a	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-P						Weight: 24 lb	FT = 20%F, 11%E
	Code IRC2021/TPI2014								

LUMBER-

TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-1-6 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 6=401/0-5-6 (min. 0-1-8), 4=174/0-4-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 6-7=-399/0, 1-7=-398/0

NOTES- (4-5)

- 1) Load case(s) 1, 2 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- 2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 3) CAUTION, Do not erect truss backwards.
- 4) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- 5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard

- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 4-6=-8, 1-3=-80
Concentrated Loads (lb)
Vert: 1=-240
- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 4-6=-8, 1-3=-80
Concentrated Loads (lb)
Vert: 1=-240



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F112	Floor Supported Gable	1	1	
					# 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:38 2024 Page 1
 ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-xiSpk9lww1fNPRJTXGoCqdF5yd1SyO?RYNXdTayBJk

0-1-8

Scale = 1:21.6




Plate Offsets (X,Y)-- [6:0-1-8,Edge], [24:Edge,0-1-8]		7-8-10 7-8-10		13-3-6 5-6-12	
LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	PLATES
TCLL 40.0	Plate Grip DOL 1.00		TC 0.05	in (loc) l/defl L/d	GRIP
TCDL 10.0	Lumber DOL 1.00		BC 0.01	Vert(LL) n/a - n/a 999	MT20 244/190
BCLL 0.0	Rep Stress Incr YES		WB 0.07	Vert(CT) n/a - n/a 999	
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH	Horz(CT) 0.00 13 n/a n/a	Weight: 61 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 13-3-6.
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 13, 23, 22, 21, 20, 19, 17, 16, 15, 14 except 24=279(LC 1), 18=654(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 24-25=-275/0, 1-25=-275/0
 WEBS 7-18=-635/0

- NOTES-** (8-9)
- All plates are 1.5x3 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Load case(s) 1, 2 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols not considered in the structural design of the truss to support the loads indicated.

- LOAD CASE(S)** Standard
- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 13-24=-8, 1-12=-80
 Concentrated Loads (lb)
 Vert: 1=-240 7=-640
 - Dead: Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 13-24=-8, 1-12=-80
 Concentrated Loads (lb)
 Vert: 1=-240 7=-640



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F114	FLOOR SUPPORTED GABL	1	1	Job Reference (optional) # 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:39 2024 Page 1
 ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-Pu0CyVmYhLnE1buf5_JRNqoGT1Nihsvan1GA?0yBJkA

0-1-8

Scale = 1:37.5




Plate Offsets (X,Y)-- [10:0-1-8,Edge], [29:0-1-8,Edge], [38:Edge,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	1-7-3	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Lumber DOL 1.00	WB 0.03	Horz(CT)	0.00	20	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH						
	Code IRC2021/TPI2014						Weight: 97 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)
 OTHERS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 22-10-14.
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 38, 20, 37, 36, 35, 34, 33, 32, 31, 29, 28, 27, 26, 25, 24, 23, 22, 21

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (7-8)
- All plates are 1.5x3 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




Plate Offsets (X,Y)-- [5:0-1-8,Edge], [10:0-1-8,Edge], [11:0-1-8,Edge], [25:0-1-8,Edge], [28:Edge,0-1-8]								
LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc)	l/defl	L/d	
TCLL 40.0	Plate Grip DOL	1.00	TC 0.68	Vert(LL)	-0.09 25-26	>999	480	
TCDL 10.0	Lumber DOL	1.00	BC 0.69	Vert(CT)	-0.19 16-17	>603	360	
BCLL 0.0	Rep Stress Incr	YES	WB 0.53	Horz(CT)	0.03 14	n/a	n/a	
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH					
							Weight: 117 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat) *Except* B2: 2x4 SP SS(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 20-21,19-20.
WEBS 2x4 SP No.3(flat)	


REACTIONS. (lb/size) 28=576/0-5-6 (min. 0-1-8), 14=698/0-4-8 (min. 0-1-8), 20=1793/0-4-8 (min. 0-1-8)
 Max Grav 28=586(LC 10), 14=748(LC 4), 20=1793(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 28-29=-582/0, 1-29=-581/0, 13-14=-735/0, 1-2=-665/0, 2-3=-1539/0, 3-4=-1878/0,
 4-5=-1878/0, 5-30=-1636/0, 6-30=-1636/0, 6-7=-686/0, 7-8=-686/0, 8-9=0/837,
 9-10=-604/135, 10-11=-1554/0, 11-12=-1547/0, 12-31=-594/0, 13-31=-594/0
 BOT CHORD 26-27=0/1244, 25-26=0/1816, 24-25=0/1878, 23-24=0/1878, 22-23=0/1380, 21-22=0/1380,
 20-21=-311/23, 19-20=-837/0, 18-19=0/1554, 17-18=0/1554, 16-17=0/1554, 15-16=0/1361
 WEBS 10-18=0/363, 11-17=-320/0, 9-20=-842/0, 1-27=0/804, 2-27=-754/0, 2-26=0/385,
 3-26=-360/0, 3-25=-48/344, 5-23=-374/0, 6-23=0/375, 6-21=-940/0, 8-21=0/949,
 8-20=-1096/0, 9-19=0/1106, 10-19=-1374/0, 12-15=-998/0, 13-15=0/868

- NOTES-** (6-7)
- Unbalanced floor live loads have been considered for this design.
 - All plates are 3x4 MT20 unless otherwise indicated.
 - Load case(s) 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard

- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 14-28=-8, 1-30=-80, 30-31=-160, 13-31=-80
- Dead: Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 14-28=-8, 1-30=-80, 30-31=-160, 13-31=-80
- 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00



12/7/2024


Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F115	FLOOR	2	1	Job Reference (optional) # 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:41 2024 Page 2
ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-MG8yNAopDy1yGu12DPMvSFtRGrUv9edtELIH4vyBJk8

LOAD CASE(S) Standard

- Uniform Loads (plf)
 - Vert: 14-28=-8, 1-30=-80, 9-30=-160, 9-31=-96, 13-31=-16
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 14-28=-8, 1-30=-16, 9-30=-96, 9-31=-160, 13-31=-80
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 14-28=-8, 1-30=-80, 9-30=-160, 9-31=-96, 13-31=-16
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 14-28=-8, 1-30=-16, 9-30=-96, 9-31=-160, 13-31=-80
- 7) 1st chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 14-28=-8, 1-5=-80, 5-30=-16, 9-30=-96, 9-31=-160, 13-31=-80
- 8) 2nd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 14-28=-8, 1-4=-16, 4-30=-80, 30-31=-160, 13-31=-80
- 9) 3rd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 14-28=-8, 1-30=-80, 11-30=-160, 11-31=-96, 13-31=-16
- 10) 4th chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 14-28=-8, 1-30=-80, 9-30=-160, 9-10=-96, 10-31=-160, 13-31=-80
- 11) 5th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 14-28=-8, 1-5=-80, 5-30=-16, 9-30=-96, 9-31=-160, 13-31=-80
- 12) 6th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 14-28=-8, 1-4=-16, 4-30=-80, 30-31=-160, 13-31=-80
- 13) 7th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 14-28=-8, 1-30=-80, 11-30=-160, 11-31=-96, 13-31=-16
- 14) 8th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
 - Uniform Loads (plf)
 - Vert: 14-28=-8, 1-30=-80, 9-30=-160, 9-10=-96, 10-31=-160, 13-31=-80



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B007-F01	Truss F115B	Truss Type FLOOR	Qty 2	Ply 1	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC Job Reference (optional) # 54877
--------------------	----------------	---------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:44 2024 Page 1
ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-mrp5?CqhWtPX7MmcuXvc4uVzo2vGM?6JwJ_xgDyBjK5




Plate Offsets (X,Y)-- [5:0-1-8,Edge], [10:0-1-8,Edge], [11:0-1-8,Edge], [25:0-1-8,Edge], [28:Edge,0-1-8]					
LOADING (psf)	SPACING- 1-7-3	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.60	Vert(LL) -0.09 16-17 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.75	Vert(CT) -0.14 16-17 >793 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.48	Horz(CT) 0.03 14 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			Weight: 117 lb FT = 20%F, 11%E

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 20-21,19-20.

REACTIONS. (lb/size) 28=564/0-5-6 (min. 0-1-8), 14=431/0-4-8 (min. 0-1-8), 20=1749/0-4-8 (min. 0-1-8)
Max Grav 28=574(LC 10), 14=479(LC 4), 20=1749(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD
28-29=-571/0, 1-29=-570/0, 13-14=-472/0, 1-2=-649/0, 2-3=-1498/0, 3-4=-1803/0,
4-5=-1803/0, 5-30=-1535/0, 6-30=-1535/0, 6-7=-547/0, 7-8=-547/0, 8-9=0/1014,
9-10=-340/390, 10-11=-1139/0, 11-31=-1062/0, 12-31=-1062/0, 12-13=-385/0

BOT CHORD
26-27=0/1215, 25-26=0/1757, 24-25=0/1803, 23-24=0/1803, 22-23=0/1262, 21-22=0/1262,
20-21=-484/0, 19-20=-1014/0, 18-19=0/1139, 17-18=0/1139, 16-17=0/1139, 15-16=0/872


WEBS
10-18=0/256, 9-20=-806/0, 1-27=0/785, 2-27=-737/0, 2-26=0/368, 3-26=-337/0,
3-25=-85/311, 5-23=-409/0, 6-23=0/399, 6-21=-967/0, 8-21=0/984, 8-20=-1105/0,
9-19=0/1007, 10-19=-1173/0, 12-15=-635/0, 13-15=0/561

NOTES- (6-7)

- Unbalanced floor live loads have been considered for this design.
- All plates are 3x4 MT20 unless otherwise indicated.
- Load case(s) 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.
- Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard

- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-30=-80, 30-31=-160, 13-31=-80
- Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-30=-80, 30-31=-160, 13-31=-80
- 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-30=-80, 9-30=-160, 9-31=-96, 13-31=-16



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F115B	FLOOR	2	1	Job Reference (optional) # 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:44 2024 Page 2
ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-mrp5?CqhWtPX7MmCuXvc4uVzo2vGM?6JwJ_xgDyBjk5

LOAD CASE(S) Standard

- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-30=-16, 9-30=-96, 9-31=-160, 13-31=-80
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-30=-80, 9-30=-160, 9-31=-96, 13-31=-16
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-30=-16, 9-30=-96, 9-31=-160, 13-31=-80
- 7) 1st chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-5=-80, 5-30=-16, 9-30=-96, 9-31=-160, 13-31=-80
- 8) 2nd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-4=-16, 4-30=-80, 30-31=-160, 13-31=-80
- 9) 3rd chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-30=-80, 11-30=-160, 11-31=-96, 13-31=-16
- 10) 4th chase Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-30=-80, 9-30=-160, 9-10=-96, 10-31=-160, 13-31=-80
- 11) 5th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-5=-80, 5-30=-16, 9-30=-96, 9-31=-160, 13-31=-80
- 12) 6th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-4=-16, 4-30=-80, 30-31=-160, 13-31=-80
- 13) 7th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-30=-80, 11-30=-160, 11-31=-96, 13-31=-16
- 14) 8th chase Dead: Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 14-28=-8, 1-30=-80, 9-30=-160, 9-10=-96, 10-31=-160, 13-31=-80




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F115C	FLOOR	1	1	# 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:45 2024 Page 1
 ID:UMCU216gUxCLqMIKo_q9qxyaVB1-E2NTCYrJHBXOIWLpSEQrc52B9SHj5U9T9zjUDgyBJk4



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	1-7-3	TC 0.43	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.61	Vert(LL) -0.09 26-27 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.36	Vert(CT) -0.12 26-27 >999 360		
BCLD 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.03 15 n/a n/a		
	Code IRC2021/TPI2014			Weight: 120 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 29=547/0-5-6 (min. 0-1-8), 15=355/0-3-8 (min. 0-1-8), 21=1111/0-4-8 (min. 0-1-8)
 Max Grav 29=558(LC 10), 15=403(LC 4), 21=1111(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 29-30=-553/0, 1-30=-552/0, 14-15=-398/0, 1-2=-626/0, 2-3=-1438/0, 3-4=-1693/0, 4-5=-1693/0, 5-6=-1386/0, 6-7=-544/0, 7-8=-544/0, 8-9=0/692, 9-10=-346/378, 10-11=-819/114, 11-12=-792/0, 12-13=-276/0, 13-14=-279/0
 BOT CHORD 27-28=0/1173, 26-27=0/1671, 25-26=0/1693, 24-25=0/1693, 23-24=0/1086, 22-23=0/1086, 21-22=-321/7, 20-21=-692/0, 19-20=-114/819, 18-19=-114/819, 17-18=-114/819, 16-17=0/674
 WEBS 9-21=-449/0, 1-28=0/757, 2-28=-712/0, 2-27=0/344, 3-27=-304/0, 3-26=-133/263, 5-24=-460/0, 6-24=0/435, 6-22=-742/0, 8-22=0/766, 8-21=-792/0, 9-20=0/610, 10-20=-753/0, 12-16=-508/0, 14-16=0/439

- NOTES-** (5-6)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) CAUTION, Do not erect truss backwards.
 - 5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B007-F01	Truss F115D	Truss Type FLOOR	Qty 4	Ply 1	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC Job Reference (optional) # 54877
--------------------	----------------	---------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:47 2024 Page 1
ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-AQVdDdEsZpon6_pVBZfTJhW7PkFuGZMMldHCbHYyBjK2





Plate Offsets (X,Y)-- [5:0-1-8,Edge], [10:0-1-8,Edge], [11:0-1-8,Edge], [26:0-1-8,Edge], [29:Edge,0-1-8]									
LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.94	Vert(LL)	-0.09 26-27	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.92	Vert(CT)	-0.23 17-18	>493	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.51	Horz(CT)	0.04 15	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 120 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat) *Except* B2: 2x4 SP SS(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 20-21 2-2-0 oc bracing: 18-19.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 29=571/0-5-6 (min. 0-1-8), 21=1315/0-4-8 (min. 0-1-8), 15=778/0-4-8 (min. 0-1-8)
Max Grav 29=581(LC 10), 21=1315(LC 1), 15=829(LC 4)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 29-30=-578/0, 1-30=-577/0, 1-2=-658/0, 2-3=-1522/0, 3-4=-1848/0, 4-5=-1848/0, 5-6=-1592/0, 6-7=-807/0, 7-8=-807/0, 8-9=-252/336, 9-10=-988/0, 10-11=-1934/0, 11-12=-2510/0, 12-13=-1680/0
BOT CHORD 27-28=0/1232, 26-27=0/1792, 25-26=0/1848, 24-25=0/1848, 23-24=0/1323, 22-23=0/1323, 21-22=0/341, 20-21=-336/252, 19-20=0/1934, 18-19=0/1934, 17-18=0/1934, 16-17=0/2510, 15-16=0/935
WEBS 12-17=-462/0, 10-19=0/460, 11-18=-506/0, 9-21=-592/0, 1-28=0/796, 2-28=-747/0, 2-27=0/378, 3-27=-352/0, 3-26=-57/333, 5-24=-379/0, 6-24=0/383, 6-22=-701/0, 8-22=0/710, 8-21=-821/0, 9-20=0/1011, 10-20=-1369/0, 11-17=0/1073, 12-16=-1041/0, 13-16=0/969, 13-15=-1226/0

- NOTES-** (5-6)
- Unbalanced floor live loads have been considered for this design.
 - All plates are 3x4 MT20 unless otherwise indicated.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 15-29=-8, 1-14=-80
 Concentrated Loads (lb)
 Vert: 12=-640



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F116	Floor	13	1	
					# 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:48 2024 Page 1
 ID:UMCU2t6gUxCLqMlKo_q9qxyaVB1-fd3brZtCa6vzc407N_YEkgkhfLclqZvrxy8p?yBJk1





Plate Offsets (X,Y)-- [8:0-1-8,Edge], [12:0-1-8,Edge], [13:0-1-8,Edge], [16:Edge,0-1-8]							
LOADING (psf)	SPACING- 1-7-3	CSI.	DEFL. in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.29	Vert(LL) -0.08 12-13	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.40	Vert(CT) -0.11 12-13	>999	360		
BCLL 0.0	Rep Stress Incr YES	WB 0.39	Horz(CT) 0.02 9	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH					
						Weight: 70 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.1(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 16=590/0-5-6 (min. 0-1-8), 9=590/0-5-6 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 16-17=-586/0, 1-17=-585/0, 9-18=-586/0, 8-18=-585/0, 1-2=-669/0, 2-3=-1553/0, 3-4=-1897/0, 4-5=-1897/0, 5-6=-1897/0, 6-7=-1553/0, 7-8=-669/0
 BOT CHORD 14-15=0/1253, 13-14=0/1831, 12-13=0/1897, 11-12=0/1831, 10-11=0/1253
 WEBS 4-13=-268/39, 5-12=-269/39, 1-15=0/810, 2-15=-760/0, 2-14=0/390, 3-14=-363/0, 3-13=-84/379, 8-10=0/810, 7-10=-760/0, 7-11=0/390, 6-11=-363/0, 6-12=-84/380

- NOTES-** (4-5)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Job	Truss	Truss Type	Qty	Ply	LOT 0.0012 CAMPBELL RIDGE 329 ALDEN WAY ANGIER, NC
24-B007-F01	F117	GABLE	1	1	# 54877

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 16:17:48 2024 Page 1
 ID:UMCU2t6gUxCLqMIKo_q9qxyaVB1-fd3brZtCa6vzc4O7N_YEkgOQfRplwBvry8p?yBJk1

0₁-8

0₁-8

Scale = 1:22.4



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.05	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.03	Horz(CT)	0.00	13	n/a	n/a		
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH								
											Weight: 61 lb	FT = 20%F, 11%E

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS. All bearings 13-9-4.
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 24, 13, 14, 15, 16, 17, 18, 23, 22, 21, 20, 19

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (6-7)
- All plates are 1.5x3 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.