

# Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 54885

JOB: 24-B205-F02

JOB NAME: LOT 0.0015 CAMPBELL RIDGE

Wind Code: N/A

Wind Speed: Vult= N/A

Exposure Category: N/A

Mean Roof Height (feet): N/A

These truss designs comply with IRC 2018 as well as IRC 2021.

*23 Truss Design(s)*

Trusses:

F201, F202, F203, F204, F205, F207, F208, F209, F210, F211, F212, F213, F214, F215, F216, F217, F218, F219, F220, F221, F223, F224, F225



**12/7/2024**

**Mark Morris**

***Warning !—Verify design parameters and read notes before use.***


This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSL/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F201	Floor Supported Gable	1	1	# 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:22 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-ALHraSRqOzABIFesE1wBg3xFDg8pb8ZYXjQ?YyyBI7J

0<sub>1</sub>1<sub>8</sub>

Scale = 1:25.0



15-9-6  
15-9-6

Plate Offsets (X,Y)-- [7:0-1-8,Edge], [21:0-1-8,Edge], [26:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	14	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH						
								Weight: 68 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)  
 OTHERS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 15-9-6.  
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 26, 14, 25, 24, 23, 22, 21, 20, 19, 18, 17, 16, 15

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8-9)
- All plates are 1.5x3 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard




12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F202	Floor	3	1	# 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:23 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-eYrDnoST9HI2wPD2okRQDGUI84FTKSihmNAZ4OyBI7I



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.56	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 1.00	Vert(LL) -0.22 13-14 >862 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.61	Vert(CT) -0.30 13-14 >627 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.05 10 n/a n/a		
	Code IRC2018/TPI2014			Weight: 80 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 1-4-12 oc bracing.

**REACTIONS.** (lb/size) 18=851/0-3-6 (min. 0-1-8), 10=858/0-3-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 18-19=-848/0, 1-19=-847/0, 1-2=-1111/0, 2-3=-2448/0, 3-4=-3050/0, 4-5=-3152/0, 5-6=-2740/0, 6-7=-2740/0, 7-8=-1587/0  
 BOT CHORD 16-17=0/1950, 15-16=0/3050, 14-15=0/3050, 13-14=0/3050, 12-13=0/3124, 11-12=0/2291, 10-11=0/849  
 WEBS 3-15=-16/294, 4-14=-272/38, 3-16=-829/0, 2-16=0/649, 2-17=-1092/0, 1-17=0/1288, 4-13=-219/326, 5-12=-490/0, 7-12=0/573, 7-11=-916/0, 8-11=0/961, 8-10=-1189/0

- NOTES-** (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 5) CAUTION, Do not erect truss backwards.
  - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard




12/7/2024

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F203	Floor	1	1	# 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:24 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-6kPb?7S5waQvXZoEMSyfU0RpUh53xrq?1v6dryB17H



5-6-14	6-2-14	6-10-14	13-1-14	13-3-6	15-5-13
5-6-14	0-8-0	0-8-0	6-3-0	0-1-8	2-2-7

Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [17:Edge,0-1-8]

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>	
TCLL 40.0	Plate Grip DOL	1.00	TC 0.69	Vert(LL)	-0.10	13	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.59	Vert(CT)	-0.13	13	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.49	Horz(CT)	0.03	10	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH							
									Weight: 77 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 10-11.

**REACTIONS.** (lb/size) 17=690/0-3-6 (min. 0-1-8), 10=980/0-3-8 (min. 0-1-8)  
 Max Grav 17=705(LC 3), 10=980(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 17-18=-699/0, 1-18=-698/0, 1-2=-893/0, 2-3=-1875/0, 3-4=-2193/0, 4-5=-2019/0, 5-6=-1240/0  
 BOT CHORD 15-16=0/1568, 14-15=0/2193, 13-14=0/2193, 12-13=0/2193, 11-12=0/1800, 10-11=-25/676  
 WEBS 7-10=-382/0, 3-15=-503/0, 2-15=0/420, 2-16=-879/0, 1-16=0/1034, 4-12=-405/10, 5-12=0/382, 5-11=-781/0,  
 6-11=0/735, 6-10=-921/34

- NOTES-** (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 5) CAUTION, Do not erect truss backwards.
  - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard




12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-F02	Truss F204	Truss Type Floor	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC Job Reference (optional) <b># 54885</b>
--------------------	---------------	---------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:25 2024 Page 1  
ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-awzzCTTjhuYm9jNRv9TulhZgsu1ZoPz\_Ehfg9HyBI7G



	5-6-14	6-10-14	13-1-10	19-5-6
	5-6-14	6-2-14	6-2-12	6-3-12
	[3:0-1-8,Edge], [4:0-1-8,Edge], [23:Edge,0-1-8]			

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	2-0-0	TC 0.42	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.52	Vert(LL) -0.07 20 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.44	Vert(CT) -0.09 20 >999 360		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.02 15 n/a n/a		
	Code IRC2018/TPI2014			Weight: 99 lb	FT = 20%F, 11%E


<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 23=596/0-3-6 (min. 0-1-8), 12=107/0-3-8 (min. 0-1-8), 15=1410/0-3-8 (min. 0-1-8)  
Max Uplift 12=-127(LC 3)  
Max Grav 23=603(LC 3), 12=263(LC 4), 15=1410(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 23-24=-596/0, 1-24=-595/0, 1-2=-742/0, 2-3=-1477/0, 3-4=-1599/0, 4-5=-1227/0, 7-8=0/1363, 8-9=0/936, 9-10=-279/369  
BOT CHORD 21-22=0/1304, 20-21=0/1599, 19-20=0/1599, 18-19=0/1599, 17-18=0/877, 16-17=0/877, 15-16=-575/0, 14-15=-1363/0, 13-14=-621/277  
WEBS 8-15=-634/0, 3-21=-255/29, 2-22=-732/0, 1-22=0/857, 4-18=-515/0, 5-18=0/468, 5-16=-880/0, 7-16=0/917, 7-15=-1127/0, 8-14=0/730, 9-14=-671/0, 9-13=0/328, 10-13=-283/41, 10-12=-338/206

- NOTES-** (7-8)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 127 lb uplift at joint 12.
  - 4) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) CAUTION, Do not erect truss backwards.
  - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard





12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F205	Floor	1	1	# 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:26 2024 Page 1  
 ID:ZDrKgCbbXhFNjTyggSVs5OzrCRU-27XMqPULRCgdnydT?7qv6relNpXsD7SLOdhjyBI7F



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.41	Vert(LL) -0.07	24	>999	480	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.51	Vert(CT) -0.09	24	>999	360		
BCLL 0.0	Lumber DOL 1.00	WB 0.44	Horz(CT) 0.02	20	n/a	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH						
	Code IRC2018/TPI2014							
								Weight: 119 lb FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)


**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** All bearings 0-3-8 except (jt=length) 27=0-3-6, 14=Mechanical.  
 (lb) - Max Uplift All uplift 100 lb or less at joint(s) 14  
 Max Grav All reactions 250 lb or less at joint(s) 14 except 27=603(LC 5), 20=1399(LC 3), 16=552(LC 4)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 27-28=-596/0, 1-28=-595/0, 1-2=-741/0, 2-3=-1474/0, 3-4=-1595/0, 4-5=-1222/0, 7-8=0/1358, 8-9=0/919, 9-10=-154/311  
 BOT CHORD 25-26=0/1302, 24-25=0/1595, 23-24=0/1595, 22-23=0/1595, 21-22=0/871, 20-21=-566/0, 19-20=-1358/0, 18-19=-581/200, 17-18=-581/200  
 WEBS 8-20=-624/0, 11-16=-312/0, 3-25=-257/25, 2-26=-731/0, 1-26=0/856, 4-22=-511/0, 5-22=0/467, 5-21=-879/0, 7-21=0/917, 7-20=-1128/0, 8-19=0/714, 9-19=-655/0, 9-17=-73/351, 10-17=-309/111, 10-16=-359/294, 12-14=-289/13

- NOTES-** (8-9)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) Refer to girder(s) for truss to truss connections.
  - 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 14.
  - 5) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 7) CAUTION, Do not erect truss backwards.
  - 8) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 9) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard





12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F207	Floor	3	1	# 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:28 2024 Page 1  
 ID:ZDRKgCbbXhFNjTycgSVs5OzrCRU\_-Ve6rVVbzpwL0A50bl1bwKBAo53q?IWQwftKmcYBI7D



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.44	Vert(LL)	-0.07	25	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.54	Vert(CT)	-0.10	25	>999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.45	Horz(CT)	0.02	21	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH						
								Weight: 117 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)


**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (lb/size) 28=579/0-3-6 (min. 0-1-8), 14=349/Mechanical, 21=1549/0-3-8 (min. 0-1-8)  
 Max Grav 28=618(LC 3), 14=424(LC 4), 21=1549(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 28-29=-612/0, 1-29=-611/0, 13-14=-407/0, 1-2=-764/0, 2-3=-1536/0, 3-4=-1687/0,  
 4-5=-1344/18, 5-6=-367/406, 6-7=-367/406, 7-8=0/1648, 8-9=0/1648, 9-10=-69/659,  
 10-11=-686/260, 11-12=-746/67, 12-13=-281/1  
 BOT CHORD 26-27=0/1343, 25-26=0/1687, 24-25=0/1687, 23-24=0/1687, 22-23=-187/1014, 21-22=-797/0,  
 20-21=-1112/0, 19-20=-434/552, 18-19=-434/552, 17-18=-67/746, 16-17=-67/746,  
 15-16=-67/746  
 WEBS 2-26=-1/251, 2-27=-754/0, 1-27=0/884, 4-23=-593/0, 5-23=0/504, 5-22=-904/0,  
 7-22=0/943, 7-21=-1174/0, 11-18=-365/0, 10-18=0/325, 10-20=-736/0, 9-20=0/764,  
 9-21=-876/0, 12-15=-594/84, 13-15=-1/431

- NOTES-** (7-8)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) Refer to girder(s) for truss to truss connections.
  - 4) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) CAUTION, Do not erect truss backwards.
  - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F208	Floor	6	1	# 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:29 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-SiCU2rWDk72CeKgC8?YqSXkM8VN2kDNZ8JdtI2yBI7C




Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [18:Edge,0-1-8]	
<b>LOADING</b> (psf)	<b>SPACING-</b> 1-4-0
TCLL 40.0	Plate Grip DOL 1.00
TCDL 10.0	Lumber DOL 1.00
BCLL 0.0	Rep Stress Incr YES
BCDL 5.0	Code IRC2018/TPI2014
<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d
TC 0.33	Vert(LL) -0.15 13-14 >999 480
BC 0.67	Vert(CT) -0.20 13-14 >934 360
WB 0.41	Horz(CT) 0.03 10 n/a n/a
Matrix-SH	
<b>PLATES</b>	<b>GRIP</b>
MT20	244/190
Weight: 80 lb FT = 20%F, 11%E	

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 18=569/0-3-6 (min. 0-1-8), 10=573/0-3-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 18-19=-567/0, 1-19=-566/0, 1-2=-743/0, 2-3=-1638/0, 3-4=-2042/0, 4-5=-2113/0, 5-6=-1842/0, 6-7=-1842/0, 7-8=-1078/0  
 BOT CHORD 16-17=0/1304, 15-16=0/2042, 14-15=0/2042, 13-14=0/2042, 12-13=0/2097, 11-12=0/1545, 10-11=0/587  
 WEBS 3-16=-556/0, 2-16=0/435, 2-17=-730/0, 1-17=0/861, 5-12=-325/0, 7-12=0/379, 7-11=-608/0, 8-11=0/639, 8-10=-807/0

- NOTES-** (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 5) CAUTION, Do not erect truss backwards.
  - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F209	Floor	2	1	
					<b># 54885</b>

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:29 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-SiCU2rWdk72CeKgC8?YqSXkO0VR1kEZZ8JdtI2yBI7C




Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [15:Edge,0-1-8]	
5-6-14	6-2-14 6-10-14
5-6-14	0-8-0 0-8-0
	13-3-14
	6-5-0

<b>LOADING</b> (psf)	<b>SPACING-</b>	1-4-0	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.21	Vert(LL)	-0.07	11	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.42	Vert(CT)	-0.09	11	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.33	Horz(CT)	0.02	8	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH							
Weight: 67 lb FT = 20%F, 11%E										

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 15=477/0-3-6 (min. 0-1-8), 8=482/0-3-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 15-16=-474/0, 1-16=-473/0, 1-2=-607/0, 2-3=-1279/0, 3-4=-1506/0, 4-5=-1403/0, 5-6=-911/0  
 BOT CHORD 13-14=0/1065, 12-13=0/1506, 11-12=0/1506, 10-11=0/1506, 9-10=0/1269, 8-9=0/532  
 WEBS 3-13=-353/0, 2-13=0/292, 2-14=-597/0, 1-14=0/702, 5-9=-467/0, 6-9=0/493, 6-8=-698/0

- NOTES-** (6-7)
- Unbalanced floor live loads have been considered for this design.
  - All plates are 3x4 MT20 unless otherwise indicated.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F210	Floor	7	1	# 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:31 2024 Page 1  
ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-P4KFTXYUGklvteqaGQalXypidJ3UC6sscd6\_NxyBI7A




Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [18:Edge,0-1-8]	
<b>LOADING</b> (psf)	<b>SPACING-</b> 1-4-0
TCLL 40.0	Plate Grip DOL 1.00
TCDL 10.0	Lumber DOL 1.00
BCLL 0.0	Rep Stress Incr YES
BCDL 5.0	Code IRC2018/TPI2014
<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d
TC 0.33	Vert(LL) -0.15 13-14 >999 480
BC 0.67	Vert(CT) -0.20 13-14 >932 360
WB 0.41	Horz(CT) 0.03 10 n/a n/a
Matrix-SH	<b>PLATES</b> MT20
	<b>GRIP</b> 244/190
	Weight: 80 lb FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 18=570/0-3-6 (min. 0-1-8), 10=574/0-3-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 18-19=-567/0, 1-19=-566/0, 1-2=-744/0, 2-3=-1640/0, 3-4=-2045/0, 4-5=-2116/0, 5-6=-1846/0, 6-7=-1846/0, 7-8=-1083/0

BOT CHORD 16-17=0/1305, 15-16=0/2045, 14-15=0/2045, 13-14=0/2045, 12-13=0/2100, 11-12=0/1550, 10-11=0/593

WEBS 3-16=-557/0, 2-16=0/436, 2-17=-731/0, 1-17=0/862, 5-12=-324/0, 7-12=0/379, 7-11=-608/0, 8-11=0/638, 8-10=-811/0

- NOTES-** (6-7)
- Unbalanced floor live loads have been considered for this design.
  - All plates are 3x4 MT20 unless otherwise indicated.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F211	Floor	8	1	
					<b># 54885</b>

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:32 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-tGudgtZ612QmVoPnq75X4AMvkiTsx10rHrXvNyBI79






Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [18:Edge,0-1-8]

<b>LOADING</b> (psf)	<b>SPACING-</b>	1-4-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.25	Vert(LL)	-0.04	15-16	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.35	Vert(CT)	-0.06	15-16	>999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.35	Horz(CT)	0.01	11	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH						
								Weight: 81 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)


**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (lb/size) 18=380/0-3-6 (min. 0-1-8), 11=863/0-3-8 (min. 0-1-8), 9=100/0-3-8 (min. 0-1-8)  
 Max Uplift 9=188(LC 3)  
 Max Grav 18=382(LC 3), 11=863(LC 1), 9=60(LC 4)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 18-19=-377/0, 1-19=-376/0, 1-2=-464/0, 2-3=-904/0, 3-4=-945/0, 4-5=-660/0, 6-7=0/406  
 BOT CHORD 16-17=0/815, 15-16=0/945, 14-15=0/945, 13-14=0/945, 12-13=0/402, 11-12=-689/0, 10-11=-693/0  
 WEBS 6-11=-844/0, 2-17=-458/0, 1-17=0/536, 4-13=-369/0, 5-13=0/342, 5-12=-622/0, 6-12=0/738, 6-10=0/408, 7-10=-373/0,  
 7-9=-89/256

- NOTES-** (7-8)
- Unbalanced floor live loads have been considered for this design.
  - All plates are 3x4 MT20 unless otherwise indicated.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 9=188.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



12/7/2024


**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F212	Floor Supported Gable	1	1	Job Reference (optional) # 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:33 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-LTS?u CZkoLYd6x\_zNrdmdNu7S6uOg6H93xb5RpyBI78

0<sub>1</sub>8

Scale = 1:25.0



15-9-12  
15-9-12

Plate Offsets (X,Y)-- [7:0-1-8,Edge], [21:0-1-8,Edge], [26:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	14	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH						
								Weight: 68 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)  
 OTHERS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 15-9-12.  
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 26, 14, 25, 24, 23, 22, 21, 20, 19, 18, 17, 16, 15

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8-9)
- All plates are 1.5x3 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard




12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-F02	Truss F213	Truss Type Floor Girder	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC	# 54885
--------------------	---------------	----------------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:33 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-L TS?uCZkoLYd6x\_zNrdmdNu?R6uLg6f93xb5RpyBI78



Scale = 1:8.4

Plate Offsets (X,Y)-- [3:Edge,0-1-8]

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.57	Vert(LL)	-0.00	4	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	-0.00	4	>999	360		
BCLL 0.0	Rep Stress Incr	NO	WB 0.01	Horz(CT)	0.00		n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-P						Weight: 18 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 3-0-8 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 5=157/0-3-8 (min. 0-1-8), 3=157/Mechanical

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (4-5)
- 1) Refer to girder(s) for truss to truss connections.
  - 2) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 4) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard




12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F214	Floor Girder	1	1	Job Reference (optional) # 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:34 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-pf0N5YaMZfgUk5Z9xY8?9bREJWCMPWjJlBKezGyBI77

Scale = 1:11.8



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.31	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.15	Vert(LL) -0.01 6 >999 480		
BCLL 0.0	Lumber DOL 1.00	WB 0.21	Vert(CT) -0.01 6-7 >999 360		
BCDL 5.0	Rep Stress Incr NO	Matrix-P	Horz(CT) 0.00 5 n/a n/a		
	Code IRC2018/TPI2014			Weight: 33 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 8=382/0-3-8 (min. 0-1-8), 5=371/0-3-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-8=-377/0, 1-2=-347/0, 2-3=-542/0  
 BOT CHORD 6-7=0/655, 5-6=0/394  
 WEBS 1-7=0/443, 2-7=-401/0, 3-5=-510/0

- NOTES-** (6-7)
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent at 2-7-12 from the left end to connect truss(es) F213 (1 ply 2x4 SP) to front face of top chord, skewed 0.0 deg.to the right, sloping 0.0 deg. down.
  - Fill all nail holes where hanger is in contact with lumber.
  - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard  
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
 Uniform Loads (plf)  
 Vert: 5-8=-10, 1-4=-100  
 Concentrated Loads (lb)  
 Vert: 2=-57(F)



12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F215	Floor Supported Gable	1	1	Job Reference (optional) # 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:35 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-HralJub\_KzoLMF8MVGFio\_Sqwas80ISXF4CWiyBI76

0<sub>1</sub>8

Scale = 1:22.8




Plate Offsets (X,Y)-- [6:0-1-8,Edge], [20:0-1-8,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Lumber DOL 1.00	WB 0.03	Horz(CT)	0.00	13	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH						
	Code IRC2018/TPI2014						Weight: 62 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)  
 OTHERS 2x4 SP No.3(flat)


**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 14-1-14.  
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 24, 13, 23, 22, 21, 20, 19, 18, 17, 16, 15, 14

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8-9)
- All plates are 1.5x3 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard




12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-F02	Truss F216	Truss Type Floor	Qty 5	Ply 1	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC Job Reference (optional) <b># 54885</b>
--------------------	---------------	---------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:36 2024 Page 1  
ID:ZDrKgCbbXhFNjTyggSVs5OzrCRU-l278WEcd5GxCzPjY3zATE?WZ7KmZtNvblvpl28yBI75



Scale = 1:23.5




Plate Offsets (X,Y)-- [4:0-1-8,Edge], [5:0-1-8,Edge], [8:0-1-8,Edge]					
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.35	Vert(LL) -0.12 13 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.68	Vert(CT) -0.17 13 >978 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.42	Horz(CT) 0.03 9 n/a n/a		
BCDL 5.0	Code IRC2018/TPI2014	Matrix-SH			
				Weight: 72 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 9=768/0-3-6 (min. 0-1-8), 17=768/0-3-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 8-9=-771/0, 2-3=-1221/0, 3-4=-2204/0, 4-5=-2558/0, 5-6=-2403/0, 6-7=-1671/0, 7-8=-281/0  
BOT CHORD 16-17=0/540, 15-16=0/1870, 14-15=0/2558, 13-14=0/2558, 12-13=0/2558, 11-12=0/2204, 10-11=0/1109  
WEBS 4-15=-556/0, 3-15=0/458, 3-16=-844/0, 2-16=0/887, 2-17=-946/0, 5-12=-385/53, 6-12=0/338, 6-11=-694/0, 7-11=0/731, 7-10=-1079/0, 8-10=0/765

- NOTES-** (6-7)
- Unbalanced floor live loads have been considered for this design.
  - All plates are 3x4 MT20 unless otherwise indicated.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard




12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job 24-B205-F02	Truss F217	Truss Type Floor Supported Gable	Qty 2	Ply 1	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54885
--------------------	---------------	-------------------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:36 2024 Page 1  
ID:ZDrKgCbbXhFNjTygcSVs5OzrCRU-I278WEcd5GxCzPjY3zATE?WeuKwztAbIvpl28yBI75



Scale = 1:8.5

Plate Offsets (X,Y)-- [6:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.04	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.02	Horz(CT)	0.00	4	n/a	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-R							
									Weight: 10 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)  
OTHERS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 1-9-6 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


**REACTIONS.** (lb/size) 6=57/1-9-6 (min. 0-1-8), 4=11/1-9-6 (min. 0-1-8), 5=101/1-9-6 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-** (7-8)

- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.
- Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard




12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F218	Floor	4	1	
					<b># 54885</b>

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:37 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-DEhWjacFsa33bZHkhhinD3l\_j9bcr\_l\_ZZlaayBI74



Scale = 1:20.1





Plate Offsets (X,Y)-- [1:Edge,0-1-8], [4:0-1-8,Edge], [5:0-1-8,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.28	Vert(LL)	-0.07	13-14	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.50	Vert(CT)	-0.09	13	>999		
BCLL 0.0	Lumber DOL 1.00	WB 0.37	Horz(CT)	0.02	9	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH						
	Code IRC2018/TPI2014						Weight: 65 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 16=666/Mechanical, 9=660/0-3-6 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-871/0, 3-4=-1701/0, 4-5=-1934/0, 5-6=-1656/0, 6-7=-776/0  
 BOT CHORD 15-16=0/280, 14-15=0/1449, 13-14=0/1934, 12-13=0/1934, 11-12=0/1934, 10-11=0/1371, 9-10=0/271  
 WEBS 4-14=-405/0, 3-14=0/353, 3-15=-752/0, 5-11=-444/0, 6-11=0/381, 6-10=-774/0, 2-15=0/777, 2-16=-787/0, 7-10=0/724, 7-9=-775/0

- NOTES-** (7-8)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) Refer to girder(s) for truss to truss connections.
  - 4) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) CAUTION, Do not erect truss backwards.
  - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard




12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F219	Floor	2	1	# 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:38 2024 Page 1  
 ID:ZDrKgCbbXhFNjTYcgSVs5OzrCRU-iQFuxwdtduBwDjsxAOCxKQcsp7RILGluDDIs61yBI73



0-1-8  
 0-3-7  
 Scale = 1:35.7




Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [9:0-1-8,Edge], [10:0-1-8,Edge], [13:0-1-8,Edge]						
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.53	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.70	Vert(LL) -0.12 17-18 >999 480		
BCLL 0.0	Rep Stress Incr	YES	WB 0.46	Vert(CT) -0.17 17-18 >999 360		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH	Horz(CT) 0.03 14 n/a n/a		
					Weight: 110 lb FT = 20%F, 11%E	


<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 14=716/0-3-6 (min. 0-1-8), 28=230/0-3-8 (min. 0-1-8), 23=1392/0-3-8 (min. 0-1-8)  
 Max Uplift 28=-53(LC 4)  
 Max Grav 14=723(LC 7), 28=345(LC 3), 23=1392(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 13-14=-728/0, 2-3=-430/178, 3-4=-468/457, 4-5=0/885, 5-6=0/1116, 6-7=-703/0, 7-8=-703/0, 8-9=-1798/0, 9-10=-2237/0, 10-11=-2169/0, 11-12=-1546/0, 12-13=-263/0  
 BOT CHORD 27-28=-26/307, 26-27=-457/468, 25-26=-457/468, 24-25=-457/468, 23-24=-1116/0, 21-22=0/1402, 20-21=0/1402, 19-20=0/2237, 18-19=0/2237, 17-18=0/2237, 16-17=0/2030, 15-16=0/1037  
 WEBS 4-25=0/281, 5-23=-488/0, 3-27=-49/357, 2-28=-477/41, 4-24=-908/0, 5-24=0/491, 9-20=-621/0, 8-20=0/544, 8-22=-937/0, 6-22=0/975, 6-23=-1218/0, 10-17=-277/119, 11-17=0/264, 11-16=-630/0, 12-16=0/663, 12-15=-1007/0, 13-15=0/717

- NOTES-** (7-8)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 53 lb uplift at joint 28.
  - 4) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) CAUTION, Do not erect truss backwards.
  - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F220	Floor	2	1	# 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:40 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-epNeMcf78VReS00JlpFPPrhCZx7upARBgWnyBvyBI71



Scale = 1:34.8





Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [9:0-1-8,Edge], [10:0-1-8,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.51	Vert(LL)	-0.11	17	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.66	Vert(CT)	-0.15	16-17	>999		
BCLL 0.0	Lumber DOL 1.00	WB 0.45	Horz(CT)	0.03	14	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH						
	Code IRC2018/TPI2014							
							Weight: 108 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 27=236/0-3-8 (min. 0-1-8), 22=1369/0-3-8 (min. 0-1-8), 14=703/Mechanical  
 Max Uplift 27=-47(LC 4)  
 Max Grav 27=347(LC 3), 22=1369(LC 1), 14=710(LC 7)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-434/165, 3-4=-475/432, 4-5=-4/847, 5-6=0/1074, 6-7=-707/0, 7-8=-707/0,  
 8-9=-1760/0, 9-10=-2166/0, 10-11=-2064/0, 11-12=-1399/0  
 BOT CHORD 26-27=-22/308, 25-26=-432/475, 24-25=-432/475, 23-24=-432/475, 22-23=-1074/0,  
 20-21=0/1387, 19-20=0/1387, 18-19=0/2166, 17-18=0/2166, 16-17=0/2166, 15-16=0/1903,  
 14-15=0/864  
 WEBS 4-24=0/275, 5-22=-484/0, 3-26=-53/341, 2-27=-479/34, 4-23=-891/0, 5-23=0/483,  
 9-19=-583/0, 8-19=0/515, 8-21=-913/0, 6-21=0/950, 6-22=-1192/0, 10-16=-297/80,  
 11-16=0/276, 11-15=-657/0, 12-15=0/696, 12-14=-1083/0

- NOTES-** (8-9)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) Refer to girder(s) for truss to truss connections.
  - 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 47 lb uplift at joint 27.
  - 5) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 7) CAUTION, Do not erect truss backwards.
  - 8) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 9) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F221	Floor	2	1	# 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:41 2024 Page 1  
 ID:ZDrKgCbbXhFNjTyggSVs5OzrCRU-6?x1ZyflvoZV4AbVrWmex3ELdLSiYddLvAXWjMyBI70



Scale = 1:38.9




Plate Offsets (X,Y)-- [4:0-1-8,Edge], [5:0-1-8,Edge], [10:0-1-8,Edge], [11:0-1-8,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.69	Vert(LL)	-0.11	17-18	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.75	Vert(CT)	-0.15	17-18	>999		
BCLL 0.0	Lumber DOL 1.00	WB 0.46	Horz(CT)	0.03	15	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-SH						
	Code IRC2018/TPI2014							
							Weight: 120 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 29=399/0-3-8 (min. 0-1-8), 23=1489/0-3-8 (min. 0-1-8), 15=694/Mechanical  
 Max Grav 29=487(LC 3), 23=1489(LC 1), 15=700(LC 7)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-730/22, 3-4=-995/221, 4-5=-775/500, 5-6=-28/930, 6-7=0/1161, 7-8=-602/0,  
 8-9=-602/0, 9-10=-1678/0, 10-11=-2102/0, 11-12=-2018/0, 12-13=-1376/0  
 BOT CHORD 28-29=0/391, 27-28=-69/1053, 26-27=-500/775, 25-26=-500/775, 24-25=-500/775,  
 23-24=-1161/0, 22-23=-302/0, 21-22=0/1292, 20-21=0/1292, 19-20=0/2102, 18-19=0/2102,  
 17-18=0/2102, 16-17=0/1870, 15-16=0/852  
 WEBS 4-26=-339/0, 5-25=0/385, 6-23=-559/0, 4-27=0/523, 3-28=-420/61, 2-28=-34/441,  
 2-29=-607/0, 5-24=-1184/0, 6-24=0/616, 10-20=-597/0, 9-20=0/526, 9-22=-922/0,  
 7-22=0/959, 7-23=-1217/0, 11-17=-278/94, 12-17=0/262, 12-16=-643/0, 13-16=0/682,  
 13-15=-1067/0

- NOTES-** (7-8)
- Unbalanced floor live loads have been considered for this design.
  - All plates are 3x4 MT20 unless otherwise indicated.
  - Refer to girder(s) for truss to truss connections.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



12/7/2024


**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F223	Floor	15	1	Job Reference (optional) # 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:42 2024 Page 1  
 ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-aCVPnHgNg6hLhKAIPEhtUGmbEkoyH6IU8qG3FoyBI7?



Scale = 1:30.3



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.37	Vert(LL) -0.24 19-20 >933 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.75	Vert(CT) -0.32 19-20 >679 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.37	Horz(CT) 0.05 13 n/a n/a		
BCDL 5.0	Code IRC2018/TPI2014	Matrix-SH		Weight: 95 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 24=671/0-3-8 (min. 0-1-8), 13=671/Mechanical

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-24=-669/0, 12-13=-669/0, 1-2=-400/0, 2-3=-1663/0, 3-4=-1663/0, 4-5=-2520/0, 5-6=-2520/0, 6-7=-2880/0, 7-8=-2886/0, 8-9=-2542/0, 9-10=-1759/0, 10-11=-1759/0, 11-12=-462/0  
 BOT CHORD 22-23=0/1132, 21-22=0/2171, 20-21=0/2814, 19-20=0/2886, 18-19=0/2886, 17-18=0/2886, 16-17=0/2242, 15-16=0/2242, 14-15=0/1182  
 WEBS 6-21=-375/0, 4-21=0/445, 4-22=-662/0, 2-22=0/691, 2-23=-953/0, 1-23=0/738, 8-17=-535/0, 9-17=0/422, 9-15=-618/0, 11-15=0/736, 11-14=-938/0, 12-14=0/767

- NOTES-** (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 3x4 MT20 unless otherwise indicated.
  - 3) Refer to girder(s) for truss to truss connections.
  - 4) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



12/7/2024


**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC
24-B205-F02	F224	Floor Supported Gable	1	1	Job Reference (optional) # 54885

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:43 2024 Page 1  
ID:ZDrKgCbbXhFNjTycgSVs5OzrCRU-2O2n\_dh0RQpCJUluZxo61UJqp8Jk0ejdMU0doEyB17\_



Scale = 1:28.5



18-1-15  
18-1-15

Plate Offsets (X,Y)-- [9:0-1-8,Edge], [26:0-1-8,Edge]

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	-0.00	17	n/a		
BCDL 5.0	Code IRC2018/TPI2014		Matrix-SH						
								Weight: 77 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)  
OTHERS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 18-1-15.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 32, 17, 31, 30, 29, 28, 27, 26, 25, 23, 22, 21, 20, 19, 18

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (7-8)
- All plates are 1.5x3 MT20 unless otherwise indicated.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - Non Standard bearing condition. Review required.
  - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard




12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-F02	Truss F225	Truss Type GABLE	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE   271 ALDEN WAY ANGIER, NC Job Reference (optional) <b># 54885</b>
--------------------	---------------	---------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:07:44 2024 Page 1  
ID:ZDrKgCbbXhFNjTygcSVs5OzrCRU-Wac9BzieCjx3xeK4XFJLZhs?jYetl54nb8lAJgyBl6z



Scale = 1:8.5

Plate Offsets (X,Y)-- [6:Edge,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.05	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.01	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Lumber DOL 1.00	WB 0.03	Horz(CT)	0.00	4	n/a	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-R							
	Code IRC2018/TPI2014							Weight: 14 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)  
OTHERS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 2-5-14 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 6=59/2-5-14 (min. 0-1-8), 4=55/2-5-14 (min. 0-1-8), 5=126/2-5-14 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-** (7-8)

- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION. Do not erect truss backwards.
- Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

**LOAD CASE(S)** Standard



12/7/2024

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.