

Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 54883

JOB: 24-B205-R01

JOB NAME: LOT 0.0015 CAMPBELL RIDGE

Wind Code: ASCE7-16

Wind Speed: Vult= 120mph

Exposure Category: B

Mean Roof Height (feet): 23

These truss designs comply with IRC 2018 as well as IRC 2021.

54 Truss Design(s)

Trusses:

GR01, GR02, GR03, GR04, GR05, GR06, GR07, J01, J02, J04, J05, J06, J07, J09, P01, P02, R01, R02, R03, R05, R06, R07, R08, R09, R10, R11, R12, R13, R14, R14A, R14B, R14C, R15, R16, R17, R18, R19, R20, R21, R22, R23, R24, R25, R26, R27, R28, V01, V02, V03, V04, V05,



12/7/2024

Mark Morris

Warning !—Verify design parameters and read notes before use.

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




Plate Offsets (X,Y)-- [2:0-4-0,Edge], [8:0-4-0,Edge], [10:0-3-0,0-3-0]									
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15		TC 0.34	Vert(LL) -0.18	10-11	>999	240	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15		BC 0.65	Vert(CT) -0.24	10-11	>999	180		
TCDL 10.0	Rep Stress Incr YES		WB 0.20	Horz(CT) 0.03	8	n/a	n/a		
BCLL 0.0 *	Code IRC2021/TPI2014		Matrix-SH						
BCDL 10.0									Weight: 123 lb FT = 20%

LUMBER- TOP CHORD 2x4 SP No.2 BOT CHORD 2x4 SP No.2 WEBS 2x4 SP No.3 SLIDER Left 2x4 SP No.3 3-4-2, Right 2x4 SP No.3 3-4-2	BRACING- TOP CHORD Structural wood sheathing directly applied or 5-4-1 oc purlins. BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. <div style="border: 1px solid black; padding: 5px; margin-top: 5px;"> MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide. </div>
--	---

REACTIONS. (lb/size) 2=933/0-3-8 (min. 0-1-8), 8=932/0-3-8 (min. 0-1-8)
 Max Horz 2=-142(LC 10)
 Max Uplift 2=-51(LC 12), 8=-51(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1214/71, 3-4=-1084/101, 4-12=-1111/122, 5-12=-1031/149, 5-13=-1031/149,
 6-13=-1111/122, 6-7=-1084/101, 7-8=-1214/71
 BOT CHORD 2-11=-78/1027, 11-14=0/695, 14-15=0/695, 10-15=0/695, 8-10=-14/935
 WEBS 5-10=-78/530, 6-10=-280/155, 5-11=-78/530, 4-11=-280/155

- NOTES-** (8)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TC DL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 6-2-6, Exterior(2R) 6-2-6 to 15-9-10, Interior(1) 15-9-10 to 18-0-14, Exterior(2E) 18-0-14 to 22-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 51 lb uplift at joint 2 and 51 lb uplift at joint 8

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss GR02	Truss Type Hip Girder	Qty 1	Ply 2	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC	# 54883
--------------------	---------------	--------------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:30 2024 Page 1
ID:qqfH?RqemZ1wWmxuKuRIUzBcTx-CGupUeMyu7VbfqUo9vrrinpKLLN0IKzD_zmvWwyBIA?

0-10-8 0-10-8	4-1-2 4-1-2	8-0-0 3-10-14	14-0-0 6-0-0	17-10-14 3-10-14	22-0-0 4-1-2	22-10-8 0-10-8
------------------	----------------	------------------	-----------------	---------------------	-----------------	-------------------

Scale = 1:42.7




Plate Offsets (X,Y)-- [2:0-2-0,0-4-4], [2:0-0-0,0-0-12], [4:0-5-12,0-2-0], [7:0-0-0,0-0-12], [7:0-2-0,0-4-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.52	Vert(LL) -0.02	12	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.30	Vert(CT) -0.05	11-12	>999	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.10	Horz(CT) 0.02	7	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-SH						
BCDL 10.0	Code IRC2021/TPI2014							
							Weight: 285 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 2=1479/0-3-8 (min. 0-1-8), 7=1480/0-3-8 (min. 0-1-8)
Max Horz 2=-106(LC 8)
Max Uplift 2=-360(LC 10), 7=-360(LC 11)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-14=-2104/556, 3-14=-1996/555, 3-15=-1676/517, 4-15=-1550/535, 4-16=-1354/476,
16-17=-1354/476, 5-17=-1354/476, 5-18=-1551/534, 6-18=-1677/516, 6-19=-1996/557,
7-19=-2104/558
BOT CHORD 2-20=-466/1598, 13-20=-466/1598, 13-21=-466/1598, 12-21=-466/1598, 12-22=-433/1353,
22-23=-433/1353, 11-23=-433/1353, 10-11=-398/1598, 9-10=-398/1598, 9-24=-398/1598,
7-24=-398/1598
WEBS 3-12=-321/88, 4-12=-2/505, 5-11=0/507, 6-11=-321/91

- NOTES-** (12)
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TC DL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 360 lb uplift at joint 2 and 360 lb uplift at joint 7.
 - "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.



12/7/2024

LOAD CASE(S) - See design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	GR02	Hip Girder	1	2	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:30 2024 Page 2
 ID:qq1fH?RqemZ1wWmxuKuRIUzBcTx-CGupUeMyu7VbfqUo9vrrinpKLLN0IKzD_zmvWwyBIA?

LOAD CASE(S) Standard

1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-4=-60, 4-5=-60, 5-8=-60, 2-7=-20

Concentrated Loads (lb)

Vert: 4=-83(F) 5=-83(F) 10=-97(F) 3=-48(F) 13=-58(F) 12=-29(F) 11=-29(F) 6=-48(F) 9=-58(F) 14=-63(F) 15=-15(F) 16=-83(F) 17=-83(F) 18=-15(F) 19=-63(F) 20=-43(F) 21=-97(F) 22=-29(F) 23=-29(F) 24=-43(F)



12/7/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss GR03	Truss Type Jack-Open	Qty 2	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	---------------	-------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:31 2024 Page 1
ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-gSSCh_MafQdSHz3_jcM4E?M0yInF1oiNDdVS2MyBIA_




Plate Offsets (X,Y)-- [2:0-1-8,0-0-5]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.08	Vert(LL) -0.00	2	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.04	Vert(CT) -0.00	2-5	>999	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT) -0.00	4	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 11 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
SLIDER Left 2x4 SP No.3 1-5-0

BRACING-
TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 4=48/Mechanical, 2=144/0-3-8 (min. 0-1-8), 5=20/Mechanical
Max Horz 2=53(LC 12)
Max Uplift 4=-35(LC 12), 2=-3(LC 12)
Max Grav 4=52(LC 20), 2=147(LC 18), 5=40(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 35 lb uplift at joint 4 and 3 lb uplift at joint 2.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	GR04	Jack-Open Girder	2	1	
					# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:32 2024 Page 1
 ID:qqfH?RqemZ1wWmxuKuRIUzBcTx-8e0auJNCQkJv7eBHKJnJv7L93kmFdWShF0apyBI9z




Plate Offsets (X,Y)-- [3:0-2-8,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.36	Vert(LL) -0.02	5-6	>999	240		MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.28	Vert(CT) -0.05	5-6	>999	180			
TCDL 10.0	Lumber DOL 1.15	WB 0.02	Horz(CT) 0.06	4	n/a	n/a			
BCLL 0.0 *	Rep Stress Incr NO	Matrix-P							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 21 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=259/0-3-8 (min. 0-1-8), 4=123/Mechanical, 5=62/Mechanical
 Max Horz 7=50(LC 10)
 Max Uplift 7=-18(LC 10), 4=-40(LC 7)
 Max Grav 7=259(LC 1), 4=123(LC 26), 5=87(LC 5)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (12)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TC DL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 18 lb uplift at joint 7 and 40 lb uplift at joint 4.
- "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-2=-60, 2-3=-60, 3-4=-60, 5-7=-20



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	GR05	Jack-Open	2	1	
					# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:33 2024 Page 1
 ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-cray6fOqB2tAWHDN1OYKQRJHYOUVinggx_Z6FyBI9y



Scale = 1:21.2




Plate Offsets (X,Y)-- [3:0-2-8,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.22	Vert(LL) 0.05	6	>999	240		MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.31	Vert(CT) -0.06	6	>914	180			
TCDL 10.0	Lumber DOL 1.15	WB 0.03	Horz(CT) 0.09	4	n/a	n/a			
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 24 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=259/0-3-8 (min. 0-1-8), 4=108/Mechanical, 5=78/Mechanical
 Max Horz 7=87(LC 12)
 Max Uplift 4=-27(LC 9), 5=-7(LC 12)
 Max Grav 7=259(LC 1), 4=108(LC 1), 5=86(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (10)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TC DL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 8) Refer to girder(s) for truss to truss connections.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 27 lb uplift at joint 4 and 7 lb uplift at joint 5.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	GR06	Jack-Open	2	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:34 2024 Page 1
 ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-418KJ?PSyL?18RoZOlvnsd_TfyknE9lpvak6ehyBI9x



Scale = 1:28.8

Plate Offsets (X,Y)-- [3:0-2-8,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.31	Vert(LL) 0.06	6-7	>891	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.31	Vert(CT) -0.06	6-7	>898	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.05	Horz(CT) -0.09	4	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 26 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=259/0-3-8 (min. 0-1-8), 4=68/Mechanical, 5=117/Mechanical
 Max Horz 7=125(LC 12)
 Max Uplift 4=-8(LC 9), 5=-58(LC 12)
 Max Grav 7=259(LC 1), 4=68(LC 1), 5=120(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (10)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCCL=5.0psf; BCCL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 8) Refer to girder(s) for truss to truss connections.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 8 lb uplift at joint 4 and 58 lb uplift at joint 5.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	GR07	Jack-Open	4	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:35 2024 Page 1
 ID:qqllfH?RqemZ1wWmxuKuRIUzBcTx-ZDhiXLP4jf7umbNmySQ0PrXaLM4izciy8ETgA8yBI9w



Scale = 1:33.7

Plate Offsets (X,Y)-- [2:0-5-4,0-0-9]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.57	Vert(LL) -0.01	2-4	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.27	Vert(CT) -0.02	2-4	>999	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT) -0.00	3	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 30 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 SLIDER Left 2x8 SP No.2 3-4-0

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 3=143/Mechanical, 2=255/0-3-8 (min. 0-1-8), 4=49/Mechanical
 Max Horz 2=162(LC 12)
 Max Uplift 3=-132(LC 12)
 Max Grav 3=162(LC 20), 2=255(LC 1), 4=99(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 3) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 132 lb uplift at joint 3.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	J01	Jack-Open Girder	2	1	# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:36 2024 Page 1
 ID:qq1fH?RqemZ1wWmxuKuRIUzBcTx-1PF5khQiUzFINlyyWAXFx23qmmRfi3l6MuDDJayBI9v




Plate Offsets (X,Y)-- [3-0-2-8,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.21	Vert(LL) 0.02	5-6	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.22	Vert(CT) -0.03	5-6	>999	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.01	Horz(CT) 0.04	4	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MP						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 18 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=238/0-3-8 (min. 0-1-8), 4=96/Mechanical, 5=61/Mechanical
 Max Horz 7=57(LC 37)
 Max Uplift 7=-45(LC 10), 4=-37(LC 7), 5=-9(LC 10)
 Max Grav 7=238(LC 1), 4=97(LC 26), 5=74(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (12)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCCL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 8) Refer to girder(s) for truss to truss connections.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 45 lb uplift at joint 7, 37 lb uplift at joint 4 and 9 lb uplift at joint 5.
 - 10) "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
 - 11) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard
 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-2=-60, 2-3=-60, 3-4=-60, 5-7=-20
 Concentrated Loads (lb)
 Vert: 6=-15(F) 9=-15(F)




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	J02	Jack-Open	2	1	
					# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:38 2024 Page 1
 ID:qqllfH?RqemZ1wWmxuKuRIUzBcTx-zoNr9NSz0aVSd26Ldb_j1T8BvZ7SAz7PqCiKnSyBI9t



Scale = 1:20.6

Plate Offsets (X,Y)-- [3:0-2-8,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.17	Vert(LL) 0.02	6-7	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.20	Vert(CT) -0.03	6-7	>999	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.02	Horz(CT) 0.05	4	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MP						
BCDL 10.0	Code IRC2021/TPI2014							
							Weight: 21 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=221/0-3-8 (min. 0-1-8), 4=64/Mechanical, 5=79/Mechanical
 Max Horz 7=98(LC 12)
 Max Uplift 4=-15(LC 9), 5=-37(LC 12)
 Max Grav 7=221(LC 1), 4=64(LC 1), 5=81(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 15 lb uplift at joint 4 and 37 lb uplift at joint 5.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	J04	Jack-Open	23	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:39 2024 Page 1
 ID:qqfH?RqemZ1wWmxuKuRlUzBcTx-R_xDMjTbmudJEChXBIVyZhhszSNvQhY3sRtJvyBI9s



Scale = 1:27.3

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.41	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.28	Vert(LL) 0.02 4-5 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Vert(CT) -0.02 4-5 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS	Horz(CT) -0.03 3 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 17 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied, except end verticals.
 BOT CHORD Rigid ceiling directly applied.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=221/0-3-8 (min. 0-1-8), 3=100/Mechanical, 4=43/Mechanical
 Max Horz 5=135(LC 12)
 Max Uplift 3=94(LC 12), 4=5(LC 12)
 Max Grav 5=221(LC 1), 3=115(LC 20), 4=72(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (9)

- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 3) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 94 lb uplift at joint 3 and 5 lb uplift at joint 4.
- 8) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




12/7/2024


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	J05	Jack-Open	4	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:39 2024 Page 1
 ID:qq1ffH?RqemZ1wWmxuKuRIUzBcTx-R_xDMjTbmudJEChXBIVyZhhLEzTFvQhY3sRtJvyBI9s



Scale = 1:27.3



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.19	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.23	Vert(LL) 0.03 7 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Vert(CT) -0.02 7 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MR	Horz(CT) -0.02 4 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 21 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 8=221/0-3-8 (min. 0-1-8), 4=84/Mechanical, 5=59/Mechanical
 Max Horz 8=135(LC 12)
 Max Uplift 4=66(LC 12), 5=32(LC 12)
 Max Grav 8=221(LC 1), 4=95(LC 20), 5=69(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 66 lb uplift at joint 4 and 32 lb uplift at joint 5.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	J06	Jack-Open	1	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:40 2024 Page 1
 ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-vBVba3TDXBIAsmFj?0B6uEY2Np2etihHWBRsLyBI9r



Scale = 1:20.6

Plate Offsets (X,Y)-- [4:0-2-8,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.13	Vert(LL)	-0.01	8	>999	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.19	Vert(CT)	-0.02	8	>999		
TCDL 10.0	Lumber DOL 1.15	WB 0.02	Horz(CT)	0.03	5	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MSH						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 23 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 10=221/0-3-8 (min. 0-1-8), 5=60/Mechanical, 6=83/Mechanical
 Max Horz 10=98(LC 12)
 Max Uplift5=-19(LC 9), 6=-30(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 19 lb uplift at joint 5 and 30 lb uplift at joint 6.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	J07	Jack-Open Girder	1	1	# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:42 2024 Page 1
 ID:qqfH?RqemZ1wWmxuKuRIUzBcTx-rZdM?kVT3p?u5gP6sQ2fBJS2BV06nI_lqgYwEyBI9p




Plate Offsets (X,Y)-- [3:0-2-8,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.22	Vert(LL) -0.01	8	>999	240		MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.17	Vert(CT) -0.02	8	>999	180			
TCDL 10.0	Lumber DOL 1.15	WB 0.01	Horz(CT) 0.02	5	n/a	n/a			
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MSH							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 21 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 10=238/0-3-8 (min. 0-1-8), 5=102/Mechanical, 6=55/Mechanical
 Max Horz 10=57(LC 10)
 Max Uplift 10=-44(LC 10), 5=-37(LC 7), 6=-9(LC 7)
 Max Grav 10=238(LC 1), 5=103(LC 26), 6=62(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (12)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCCL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 44 lb uplift at joint 10, 37 lb uplift at joint 5 and 9 lb uplift at joint 6.
 - "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
 - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard
 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-2=-60, 2-3=-60, 3-5=-60, 8-10=-20, 6-7=-20
 Concentrated Loads (lb)
 Vert: 8=-15(B) 9=-15(B)



12/7/2024


Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	J09	Jack-Open	6	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:43 2024 Page 1
 ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-KmAkC4W5q68ljp_IQ8ZukXs3qatDrEg8zUP5TgyBI9o



Scale = 1:14.0



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.09	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.03	Vert(LL) 0.00 7 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Vert(CT) -0.00 7 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MP	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 12 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP No.2

BRACING-
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 2-6-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 3=53/Mechanical, 2=159/0-3-8 (min. 0-1-8), 4=35/Mechanical
 Max Horz 2=65(LC 12)
 Max Uplift 3=30(LC 12), 2=-10(LC 12)
 Max Grav 3=55(LC 20), 2=159(LC 1), 4=50(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 3) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 30 lb uplift at joint 3 and 10 lb uplift at joint 2.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	P01	Piggyback	4	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:44 2024 Page 1
 ID:qqIffH?RqemZ1wWmxuKuRIUzBcTx-oyk6QQWkbQGcLzZU_r57GkOFS_BHahwHC89e76yBI9n



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES	GRIP	
TCLL (roof)	20.0	2-0-0	Plate Grip DOL	1.15	TC	0.03	in	(loc)	l/defl	L/d	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.17	Vert(LL)	0.00	4	n/r	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Vert(CT)	0.00	4	n/r	80		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-P		Horz(CT)	0.00	4	n/a	n/a		
BCDL	10.0										Weight: 12 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 4-6-0 oc purlins.
BOT CHORD 2x4 SP No.3	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=148/2-11-0 (min. 0-1-8), 4=148/2-11-0 (min. 0-1-8)
 Max Horz 2=26(LC 11)
 Max Uplift 2=17(LC 12), 4=17(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCCL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 17 lb uplift at joint 2 and 17 lb uplift at joint 4.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss P02	Truss Type Piggyback	Qty 10	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	--------------	-------------------------	-----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:44 2024 Page 1
ID:qq1fH?RqemZ1wWmxuKuRIUzBcTx-oyk6QQWkbQGcLzZU_r57GkOFS_CMahwHC89e76yBI9n




Plate Offsets (X,Y)-- [3:0-3-0,Edge]		CSI.		DEFL.				PLATES	GRIP
LOADING (psf)	SPACING-	2-0-0	TC 0.03	in	(loc)	l/defl	L/d	MT20	244/190
TCLL (roof) 20.0	Plate Grip DOL 1.15		BC 0.10	Vert(LL) 0.00	4	n/r	180		
Snow (Pf) 20.0	Lumber DOL 1.15		WB 0.00	Vert(CT) 0.00	4	n/r	80		
TCDL 10.0	Rep Stress Incr YES		Matrix-P	Horz(CT) 0.00	4	n/a	n/a		
BCLL 0.0 *	Code IRC2021/TPI2014							Weight: 10 lb	FT = 20%
BCDL 10.0									

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 3-10-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS. (lb/size) 2=123/2-3-8 (min. 0-1-8), 4=123/2-3-8 (min. 0-1-8)
Max Horz 2=-22(LC 10)
Max Uplift 2=-16(LC 12), 4=-16(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (10)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCCL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 16 lb uplift at joint 2 and 16 lb uplift at joint 4.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R01	Monopitch	2	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:46 2024 Page 1
 ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-kLssr6Y_71WkaHjt5G7bL9UTJopj2bQagSel37yBI9I



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.52	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.36	Vert(LL) 0.08 4-10 >995 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Vert(CT) 0.07 4-10 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS	Horz(CT) -0.00 4 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 32 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied, except end verticals.
 BOT CHORD Rigid ceiling directly applied.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 4=230/0-1-8 (min. 0-1-8), 2=351/0-3-8 (min. 0-1-8)
 Max Horz 2=78(LC 11)
 Max Uplift 4=-76(LC 10), 2=-117(LC 10)
 Max Grav 4=312(LC 21), 2=433(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (11)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) zone; cantilever left and right exposed ; end vertical left and right exposed ; porch left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 76 lb uplift at joint 4 and 117 lb uplift at joint 2.
 - 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R02	Monopitch	6	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:46 2024 Page 1
 ID:qq1fh1?RqemZ1wWmxuKuRIUzBcTx-kLssr6Y_71WKaHjt5G7bL9UTJops2bQagSel3?yBI9I



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.52	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.36	Vert(LL) 0.06 4-8 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Vert(CT) -0.06 4-8 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.00 4 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 30 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied, except end verticals.
 BOT CHORD Rigid ceiling directly applied.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 4=230/0-1-8 (min. 0-1-8), 2=351/0-3-8 (min. 0-1-8)
 Max Horz 2=78(LC 11)
 Max Uplift 4=-76(LC 10), 2=-117(LC 10)
 Max Grav 4=312(LC 21), 2=433(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (11)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 76 lb uplift at joint 4 and 117 lb uplift at joint 2.
 - 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R03	Monopitch	3	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:47 2024 Page 1
 ID:qq1fH?RqemZ1wWmxuKuRIUzBcTx-CXQF2SZcuLeBCRI3f_equN0Z7C61n1gju6NjCRyBI9k



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15	TC 0.84	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15	BC 0.55	Vert(LL) 0.13 4-8 >745 240		
TCDL 10.0	Rep Stress Incr YES	WB 0.00	Vert(CT) -0.15 4-8 >666 180		
BCLL 0.0 *	Code IRC2021/TPI2014	Matrix-AS	Horz(CT) 0.00 4 n/a n/a		
BCDL 10.0				Weight: 37 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied, except end verticals.
 BOT CHORD Rigid ceiling directly applied.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 4=292/0-1-8 (min. 0-1-8), 2=409/0-3-8 (min. 0-1-8)
 Max Horz 2=94(LC 11)
 Max Uplift 4=97(LC 10), 2=133(LC 10)
 Max Grav 4=392(LC 21), 2=480(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 3-4=-255/131


- NOTES-** (11)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 97 lb uplift at joint 4 and 133 lb uplift at joint 2.
 - 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale = 1:53.3

Plate Offsets (X,Y)-- [6:0-2-4,0-1-12], [9:0-2-4,0-1-12], [19:0-2-4,0-1-4]					
LOADING (psf)	SPACING-	CSI.	DEFL.		PLATES
TCLL (roof) 20.0	2-0-0	TC 0.14	in (loc) l/defl L/d		GRIP
Snow (Pf) 20.0	Plate Grip DOL 1.15	WB 0.13	Vert(LL) -0.00 14 n/r 180		MT20 244/190
TCDL 10.0	Lumber DOL 1.15	Matrix-R	Vert(CT) -0.00 14 n/r 80		
BCLL 0.0 *	Rep Stress Incr YES		Horz(CT) 0.00 15 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014				Weight: 170 lb FT = 20%


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.3	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 7-22, 6-23, 8-21, 9-20
OTHERS 2x4 SP No.3	

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 20-0-0.
 (lb) - Max Horz 27=-200(LC 10)
 Max Uplift All uplift 100 lb or less at joint(s) 27, 15, 22, 24, 25, 21, 18, 17 except 26=-141(LC 12), 16=-135(LC 13)
 Max Grav All reactions 250 lb or less at joint(s) 27, 15, 22, 25, 26, 23, 21, 17, 16, 20 except 24=280(LC 20), 18=279(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 5-6=-158/329, 6-7=-119/264, 7-8=-118/263, 8-9=-119/264, 9-10=-158/329

- NOTES-** (14)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 3-11-2, Corner(3R) 3-11-2 to 16-0-14, Corner(3E) 16-0-14 to 20-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 6) Provide adequate drainage to prevent water ponding.
 - 7) All plates are 2x4 MT20 unless otherwise indicated.
 - 8) Gable requires continuous bottom chord bearing.
 - 9) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 10) Gable studs spaced at 2-0-0 oc.
 - 11) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 12) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 13) Provide mechanical connection (if any) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 27, 15, 22, 24, 25, 21, 18, 17 except (jt=lb) 26=141, 16=135.




12/7/2024

LOAD CASE(S) Standard
Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R06	Hip	1	1	# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:51 2024 Page 1
 ID: qqlfH?RqemZ1wWmxuKuRIUzBcTx-5flupc7ya8ch2bqupjm2DBOepQpjozJpkLWICyBI9g



Scale = 1:58.2




Plate Offsets (X,Y)-- [2:0-3-0,0-5-4], [5:0-4-3,Edge], [6:0-4-3,Edge], [9:0-3-0,0-5-4], [11:0-6-0,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.23	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.82	Vert(LL) -0.18 11-14 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.24	Vert(CT) -0.31 11-18 >777 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.02 2 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 132 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 SLIDER Left 2x6 SP No.2 1-11-0, Right 2x6 SP No.2 1-11-0

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=853/0-3-8 (min. 0-1-8), 9=852/0-3-8 (min. 0-1-8)
 Max Horz2=185(LC 11)
 Max Uplift2=-49(LC 12), 9=-49(LC 13)
 Max Grav2=855(LC 3), 9=855(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-730/0, 3-20=-831/131, 4-20=-705/134, 4-5=-678/156, 5-6=-459/163, 6-7=-678/156, 7-21=-705/134, 8-21=-831/131, 8-9=-730/0
 BOT CHORD 2-22=-79/645, 22-23=-79/645, 11-23=-79/645, 11-24=0/556, 24-25=0/556, 9-25=0/556
 WEBS 5-11=-54/291, 6-11=-53/291

- NOTES-** (9)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Exterior(2R) 3-11-2 to 16-0-14, Exterior(2E) 16-0-14 to 20-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 9.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss R07	Truss Type Common	Qty 2	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	--------------	----------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:52 2024 Page 1
ID:qqIh?RqemZ1wWmxuKuRIUzBcTx-ZUD859dJtGTICA1SXE?bQkYXDItSB8S2O53HyBl9f



4x4 =

Scale = 1:69.0




Plate Offsets (X,Y)-- [6:0-3-0,0-5-12], [8:0-4-0,0-3-4], [9:0-3-8,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.28	Vert(LL) -0.26	8-12	>904	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.98	Vert(CT) -0.39	8-12	>604	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.50	Horz(CT) -0.02	6	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS						
BCDL 10.0	Code IRC2021/TPI2014							
							Weight: 128 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3
SLIDER Right 2x6 SP No.2 1-11-0

BRACING-
TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Rigid ceiling directly applied.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=842/0-3-8 (min. 0-1-8), 9=796/0-3-8 (min. 0-1-8)
Max Horz 9=-222(LC 10)
Max Uplift 6=-49(LC 13), 9=-44(LC 13)
Max Grav 6=892(LC 21), 9=846(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-519/90, 2-3=-722/172, 3-4=-721/171, 4-14=-728/126, 5-14=-813/108, 5-6=-821/0,
1-9=-382/96
BOT CHORD 9-15=-89/652, 15-16=-89/652, 8-16=-89/652, 8-17=-8/594, 17-18=-8/594, 6-18=-8/594
WEBS 3-8=-127/625, 4-8=-267/196, 2-9=-488/79

- NOTES-** (9)
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCCL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-1-12 to 4-11-13, Exterior(2R) 4-11-13 to 14-11-6, Interior(1) 14-11-6 to 16-0-14, Exterior(2E) 16-0-14 to 20-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
3) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCCL = 10.0psf.
7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 9.
8) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R08	Common Supported Gable	1	1	
					# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:04:54 2024 Page 1
 ID:qqfH?RqemZ1wWmxuKuRIUzBcTx-VtLuWre?EVWBYPKZyGTgrpx80cYwBOIViaALXyBI9d




Plate Offsets (X,Y)-- [2:0-2-3,0-0-4], [12:0-2-3,0-0-4]					
LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.09	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.11	Vert(LL) 0.00 12 n/r 180		
TCDL 10.0	Lumber DOL 1.15	WB 0.07	Vert(CT) 0.00 13 n/r 80		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 12 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 96 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.3	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	
SLIDER Left 2x4 SP No.3 1-11-0, Right 2x4 SP No.3 1-11-0	

REACTIONS. All bearings 18-0-0.
 (lb) - Max Horz 2=-65(LC 19)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 19, 20, 21, 16, 15, 14, 12
 Max Grav All reactions 250 lb or less at joint(s) 2, 18, 19, 20, 21, 16, 15, 14, 12

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-** (13)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 3-11-2, Corner(3R) 3-11-2 to 14-0-14, Corner(3E) 14-0-14 to 18-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 19, 20, 21, 16, 15, 14, 12.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



4x4 =

Scale = 1:35.0




Plate Offsets (X,Y)-- [2:0-3-4,0-0-4], [8:0-3-7,0-0-4]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15		TC 0.33	Vert(LL) -0.08	11-18	>999	240	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15		BC 0.65	Vert(CT) -0.17	11-18	>999	180		
TCDL 10.0	Rep Stress Incr YES		WB 0.20	Horz(CT) 0.02	8	n/a	n/a		
BCLL 0.0 *	Code IRC2021/TPI2014		Matrix-AS						
BCDL 10.0								Weight: 87 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 SLIDER Left 2x4 SP No.3 1-11-0, Right 2x4 SP No.3 1-11-0

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=773/0-3-8 (min. 0-1-8), 8=772/0-3-8 (min. 0-1-8)
 Max Horz 2=-65(LC 15)
 Max Uplift 2=-71(LC 14), 8=-71(LC 15)
 Max Grav 2=820(LC 21), 8=820(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-775/0, 3-20=-1123/256, 4-20=-1114/270, 4-5=-888/211, 5-6=-888/211,
 6-21=-1114/270, 7-21=-1123/256, 7-8=-775/0
 BOT CHORD 2-11=-162/1036, 10-11=-162/1036, 8-10=-162/1036
 WEBS 5-11=-49/485, 6-11=-378/141, 4-11=-378/141

- NOTES-** (10)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Exterior(2R) 3-11-2 to 14-0-14, Exterior(2E) 14-0-14 to 18-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) Unbalanced snow loads have been considered for this design.
 - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8.
 - 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss R10	Truss Type Half Hip Girder	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
					# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:00 2024 Page 1
 ID:qqfH?RqemZ1wWmxuKuRIUzBcTx-K1i9nUjmqLHLGRnZwCnTw63qVRYmKl8eud1VZByBI9X



Scale = 1:65.9





Plate Offsets (X,Y)-- [2:0-2-4,0-2-0], [3:0-3-0,0-1-8], [4:0-7-12,0-2-0], [18:0-3-8,0-4-8]


LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15		TC 0.67	Vert(LL) 0.10	23	>999	240	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15		BC 0.57	Vert(CT) -0.17	23	>999	180		
TCDL 10.0	Rep Stress Incr NO		WB 0.75	Horz(CT) 0.07	18	n/a	n/a		
BCLL 0.0 *	Code IRC2021/TPI2014		Matrix-MSH						
BCDL 10.0								Weight: 256 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2 *Except* T1: 2x6 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x6 SP No.2 *Except* B3,B4: 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 13=791/Mechanical, 2=525/0-3-8 (min. 0-1-8), 18=2671/0-3-8 (min. 0-3-2)
 Max Horz 2=141(LC 9)
 Max Uplift 13=-438(LC 6), 2=-120(LC 10), 18=-1239(LC 7)
 Max Grav 13=815(LC 26), 2=525(LC 1), 18=2671(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-269/119, 3-30=-438/193, 30-31=-407/164, 4-31=-351/169, 6-34=-427/1028,
 7-34=-427/1028, 8-38=-625/436, 9-38=-625/436, 9-39=-625/436, 10-39=-625/436,
 10-40=-625/436, 40-41=-625/436, 11-41=-625/436, 11-42=-648/399, 42-43=-648/399,
 12-43=-648/399, 12-13=-745/444
 BOT CHORD 3-44=-198/340, 22-44=-198/340, 22-45=-203/356, 21-45=-203/356, 21-46=-1011/419,
 20-46=-1011/419, 6-20=-968/459, 18-48=-1243/512, 48-49=-1243/512, 49-50=-1243/512,
 17-50=-1243/512, 16-53=-352/642, 15-53=-352/642, 15-54=-352/642, 14-54=-352/642
 WEBS 4-22=-121/387, 4-21=-742/278, 5-21=-271/172, 6-21=-522/1167, 18-20=-1291/538,
 7-20=-231/438, 7-18=-1815/951, 7-17=-754/1613, 8-17=-985/551, 8-16=-384/857,
 10-16=-381/269, 11-14=-415/342, 12-14=-482/852

- NOTES-** (11)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 4) Provide adequate drainage to prevent water ponding.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Refer to girder(s) for truss to truss connections.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 13=438, 2=120, 18=1239.
 - 9) "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
 - 10) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).



12/7/2024

LOAD CASE(S) Standard
Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI I-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R10	Half Hip Girder	1	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:01 2024 Page 2
 ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-oDGX_EkObePCtaMITwu6SKb?Fru?3COn6Hm25dyBl9W

LOAD CASE(S) Standard

1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-3=-60, 3-4=-60, 4-12=-60, 23-24=-20, 20-27=-20, 13-19=-20

Concentrated Loads (lb)

Vert: 4=-24(F) 23=-36(F) 22=-39(F) 21=-39(F) 5=-24(F) 11=-40(F) 14=-23(F) 30=-43(F) 31=-5(F) 32=-24(F) 33=-24(F) 34=-40(F) 35=-40(F) 36=-40(F) 37=-40(F) 38=-40(F) 39=-40(F) 40=-40(F) 41=-40(F) 42=-40(F) 43=-40(F) 44=-63(F) 45=-39(F) 46=-39(F) 47=-23(F) 48=-23(F) 49=-23(F) 50=-23(F) 51=-23(F) 52=-23(F) 53=-23(F) 54=-23(F) 55=-23(F) 56=-23(F)




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R11	Common	1	1	# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:03 2024 Page 1
 ID:qq1fH?RqemZ1wWmxuKuRIUzBcTx-kcOIPwle7GfV7uW8bLwaXlhOeeTqX6r4abF9AWyBI9U



Scale = 1:65.4






Plate Offsets (X,Y)-- [3:0-1-4,0-1-8], [6:0-4-13,Edge], [10:0-4-13,Edge], [17:0-2-12,0-3-0], [21:0-2-12,0-4-0]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15	TC 0.48	Vert(LL) -0.17 13-15 >999 240	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15	BC 1.00	Vert(CT) -0.32 17-18 >999 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.75	Horz(CT) 0.19 12 n/a n/a		
BCLL 0.0 *	Code IRC2021/TPI2014	Matrix-AS			
BCDL 10.0				Weight: 223 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP No.2 *Except* B1: 2x6 SP No.2, B3: 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3 *Except* W2: 2x4 SP No.2	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.
WEDGE Right: 2x4 SP No.3	

REACTIONS. (lb/size) 2=1473/0-3-8 (min. 0-1-12), 12=1419/Mechanical
 Max Horz 2=130(LC 9)
 Max Uplift 2=-68(LC 12), 12=-53(LC 13)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2023/172, 3-4=-3967/326, 4-28=-2783/251, 5-28=-2734/262, 5-6=-2233/250,
 6-7=-2199/266, 7-8=-2189/265, 8-29=-2189/265, 9-29=-2189/265, 9-10=-1962/254,
 10-11=-1920/222, 11-12=-2123/231
 BOT CHORD 2-21=-139/1454, 20-21=-64/705, 4-20=-65/903, 19-20=-308/3666, 18-19=-187/2308,
 18-30=-147/1804, 17-30=-147/1804, 7-17=-345/114, 14-15=-58/1546, 13-14=-58/1546,
 12-13=-137/1698
 WEBS 6-18=-29/498, 6-17=-141/722, 15-17=-135/1823, 9-17=-64/332, 9-15=-645/185,
 10-15=-143/679, 10-13=-4/375, 3-20=-234/2709, 3-21=-1067/109, 5-19=-1/427,
 4-19=-1390/152, 5-18=-605/128

- NOTES-** (11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-10-8 to 3-11-2, Exterior(2R) 3-11-2 to 16-3-7, Interior(1) 16-3-7 to 19-2-9, Exterior(2R) 19-2-9 to 30-10-1, Exterior(2E) 30-10-1 to 35-6-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 12.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.



12/7/2024

Warning! Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale: 3/16"=1'

Plate Offsets (X,Y)--	[3:0-1-4,0-1-12], [7:0-4-13,Edge], [9:0-4-13,Edge], [16:0-5-12,0-3-0], [19:0-3-0,0-3-12]
-----------------------	--


LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.47	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.84	Vert(LL) -0.35 12-14 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.93	Vert(CT) -0.56 12-14 >766 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.20 11 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 227 lb	FT = 20%

LUMBER-	TOP CHORD	BOT CHORD	WEBS	WEDGE	BRACING-
TOP CHORD	2x4 SP No.2	2x4 SP No.1 *Except*	2x4 SP No.3 *Except*	Right: 2x4 SP No.3	TOP CHORD
BOT CHORD	B1: 2x6 SP No.2, B4: 2x4 SP No.2				BOT CHORD
WEBS					WEBS
					Structural wood sheathing directly applied.
					Rigid ceiling directly applied.
					1 Row at midpt 8-16, 8-14
					MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1473/0-3-8 (min. 0-1-12), 11=1419/Mechanical
 Max Horz2=169(LC 9)
 Max Uplift2=-90(LC 12), 11=-75(LC 13)
 Max Grav2=1473(LC 1), 11=1464(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2031/168, 3-4=-3964/308, 4-26=-2567/228, 5-26=-2532/229, 5-6=-2453/247, 6-7=-2582/355, 7-8=-1679/255, 8-9=-1617/262, 9-10=-2068/275, 10-27=-2061/236, 27-28=-2077/233, 11-28=-2219/207
 BOT CHORD 2-19=-161/1533, 18-19=-64/719, 4-18=-59/942, 17-18=-407/3900, 17-29=-66/1613, 29-30=-66/1613, 16-30=-66/1613, 14-31=-45/1440, 13-31=-45/1440, 13-32=-45/1440, 12-32=-45/1440, 12-33=-132/1774, 33-34=-132/1774, 11-34=-132/1774
 WEBS 4-17=-1782/287, 6-17=-344/189, 7-16=-59/498, 14-16=-25/1775, 8-14=-531/163, 9-14=-102/425, 9-12=-81/643, 10-12=-296/189, 7-17=-203/979, 3-18=-259/2754, 3-19=-1071/104

- NOTES-** (11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 5-8-9, Exterior(2R) 5-8-9 to 29-9-7, Interior(1) 29-9-7 to 30-8-6, Exterior(2E) 30-8-6 to 35-6-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 11.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum



When used for purposes other than those shown on this drawing, the user assumes all responsibility for its use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R12	Hip	1	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:06 2024 Page 2
ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-8B3Q1ynXQB1U_MFjGTUH9NJu9sW_kPsWGZUpnryBI9R

LOAD CASE(S) Standard




12/7/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss R13	Truss Type PIGGYBACK BASE	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC	# 54883
--------------------	--------------	------------------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:09 2024 Page 1
ID:qqIqH?RqemZ1wWmxuKuRIUzBcTx-ZmIZfzqPi6P3rpzlx1_n0xJ43WFxoOzyXiTN9yBI90



Scale = 1:72.7




Plate Offsets (X,Y)--	[3:0-1-4,0-1-12], [5:0-2-10,0-1-12], [7:0-4-13,Edge], [8:0-4-13,Edge], [16:0-2-4,0-2-12], [18:0-4-4,0-3-4], [19:0-3-0,0-3-12]
-----------------------	---

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15		TC 0.87	Vert(LL) -0.44	12-14	>971	240	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15		BC 1.00	Vert(CT) -0.68	12-14	>624	180		
TCDL 10.0	Rep Stress Incr YES		WB 0.81	Horz(CT) 0.23	11	n/a	n/a		
BCLL 0.0 *	Code IRC2021/TPI2014		Matrix-AS						
BCDL 10.0								Weight: 227 lb	FT = 20%


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP No.1 *Except*	BOT CHORD Rigid ceiling directly applied.
B1: 2x6 SP No.2, B3,B4: 2x4 SP No.2	WEBS 1 Row at midpt 7-14, 8-14
WEBS 2x4 SP No.3 *Except*	
W2: 2x4 SP No.2	
WEDGE	
Right: 2x4 SP No.3	

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1473/0-3-8 (min. 0-1-12), 11=1419/0-3-8 (min. 0-1-13)
 Max Horz2=208(LC 9)
 Max Uplift2=-107(LC 12), 11=-92(LC 13)
 Max Grav2=1473(LC 1), 11=1530(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2046/134, 3-4=-3991/369, 4-26=-4297/469, 5-26=-4261/491, 5-6=-1885/186,
 6-7=-1764/223, 7-8=-1296/228, 8-9=-1993/255, 9-10=-2113/217, 10-27=-2061/182,
 11-27=-2241/159
 BOT CHORD 2-19=-209/1613, 18-19=-88/772, 17-18=-190/2172, 16-17=-190/2173, 15-16=-265/0,
 14-28=0/1283, 13-28=0/1283, 12-13=0/1283, 12-29=-76/1787, 29-30=-76/1787,
 11-30=-76/1787
 WEBS 5-17=0/309, 5-16=-808/215, 14-16=0/1548, 7-16=-115/1052, 7-14=-499/150, 8-12=-146/935,
 10-12=-416/242, 3-18=-323/2774, 3-19=-1174/142, 5-18=-320/1935

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-10-8 to 3-11-2, Interior(1) 3-11-2 to 8-8-9, Exterior(2R) 8-8-9 to 26-9-7, Interior(1) 26-9-7 to 30-8-6, Exterior(2E) 30-8-6 to 35-6-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.0; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 11 except (jt=lb) 2=107.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.




12/7/2024

Warning! Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R14	PIGGYBACK BASE	1	1	# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:12 2024 Page 1
 ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-zLRil?si?1neiHitdkbhPeZqNHX?88nPeVx7_UyBI9L



Scale = 1:72.2




Plate Offsets (X,Y)--	[3:0-1-4,0-1-12], [5:0-2-10,0-1-12], [7:0-5-8,0-1-12], [8:0-5-12,0-2-0], [16:0-2-4,0-2-12], [18:0-4-5,0-3-4], [19:0-2-12,0-4-0]
-----------------------	---

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15		TC 0.87	Vert(LL) -0.44	12-14	>968	240	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15		BC 0.99	Vert(CT) -0.69	12-14	>621	180		
TCDL 10.0	Rep Stress Incr YES		WB 0.84	Horz(CT) 0.24	11	n/a	n/a		
BCLL 0.0 *	Code IRC2021/TPI2014		Matrix-AS						
BCDL 10.0								Weight: 228 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP No.2 *Except*	BOT CHORD Rigid ceiling directly applied.
B1: 2x6 SP No.2, B5,B6: 2x4 SP No.1	WEBS 1 Row at midpt 7-14, 8-14
WEBS 2x4 SP No.3 *Except*	
W2: 2x4 SP No.2	
WEDGE	
Right: 2x4 SP No.3	

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1473/0-3-8 (min. 0-1-12), 11=1419/0-3-8 (min. 0-1-13)
 Max Horz2=210(LC 9)
 Max Uplift2=-106(LC 12), 11=-92(LC 13)
 Max Grav2=1473(LC 1), 11=1530(LC 25)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2042/133, 3-4=-4044/376, 4-26=-4291/467, 5-26=-4255/489, 5-6=-1881/186,
 6-7=-1761/224, 7-8=-1283/229, 8-9=-2001/257, 9-10=-2119/218, 10-27=-2063/183,
 11-27=-2243/159
 BOT CHORD 2-19=-209/1611, 18-19=-91/797, 17-18=-192/2177, 16-17=-192/2177, 15-16=-266/0,
 14-28=0/1271, 13-28=0/1271, 12-13=0/1271, 12-29=-77/1790, 29-30=-77/1790,
 11-30=-77/1790
 WEBS 5-17=0/309, 5-16=-831/219, 14-16=0/1535, 7-16=-116/1058, 7-14=-493/152, 8-12=-150/957,
 10-12=-441/246, 3-18=-335/2860, 3-19=-1221/148, 5-18=-319/1927

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-10-8 to 3-11-2, Interior(1) 3-11-2 to 8-8-9, Exterior(2R) 8-8-9 to 26-9-7, Interior(1) 26-9-7 to 30-8-6, Exterior(2E) 30-8-6 to 35-6-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 11 except (jt=lb) 2=106.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.




12/7/2024

Warning! Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss R14A	Truss Type Piggyback Base	Qty 2	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	---------------	------------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:16 2024 Page 1
ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-s6gC7Mvo3F13Au0esZfeZUjXRuv24yE?Z7vL7FyBI9H



Scale = 1:73.4




Plate Offsets (X,Y)--	[2:0-0,0-0-7], [3:0-1-4,0-2-8], [5:0-2-10,0-1-12], [7:0-5-8,0-1-12], [8:0-5-12,0-2-0], [21:0-2-4,0-3-4], [23:0-4-2,0-3-3], [24:Edge,0-4-0]
-----------------------	--


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15	TC 0.80	Vert(LL) -0.61	17	>702	240	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15	BC 0.98	Vert(CT) -0.95	17	>450	180		
TCDL 10.0	Rep Stress Incr YES	WB 0.87	Horz(CT) 0.25	11	n/a	n/a		
BCLL 0.0 *	Code IRC2021/TPI2014	Matrix-AS						
BCDL 10.0							Weight: 243 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2 *Except* T1: 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP No.2 *Except* B1: 2x6 SP No.2, B2,B3: 2x4 SP No.1, B5,B7: 2x4 SP SS	BOT CHORD Rigid ceiling directly applied. Except: 5-10-0 oc bracing: 15-18
WEBS 2x4 SP No.3 *Except* W2: 2x4 SP No.2	WEBS 1 Row at midpt 7-19, 8-18
WEDGE Right: 2x4 SP No.3	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1550/0-3-8 (min. 0-1-15), 11=1579/0-3-8 (min. 0-2-2)
Max Horz2=-214(LC 10)
Max Uplift2=-68(LC 12), 11=-53(LC 13)
Max Grav2=1623(LC 20), 11=1808(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2272/75, 3-4=-4491/251, 4-31=-4773/335, 5-31=-4737/357, 5-6=-2212/106,
6-7=-2092/144, 7-8=-1552/166, 8-9=-2406/157, 9-10=-2522/118, 10-32=-2469/82,
11-32=-2649/57
BOT CHORD 2-24=-159/1789, 23-24=-65/867, 22-23=-116/2484, 21-22=-116/2485, 20-21=-398/0,
19-33=0/1598, 17-33=0/1598, 17-34=0/1598, 14-34=0/1598, 13-14=0/1598, 13-35=0/2121,
35-36=0/2121, 11-36=0/2121
WEBS 5-22=0/320, 5-21=-865/212, 19-21=0/1864, 7-21=-99/1079, 7-19=-429/219, 8-15=-103/1149,
13-15=-133/997, 10-13=-426/249, 3-23=-240/3125, 3-24=-1310/107, 5-23=-266/2059

- NOTES-** (10)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 8-8-9, Exterior(2R) 8-8-9 to 26-9-7, Interior(1) 26-9-7 to 31-6-14, Exterior(2E) 31-6-14 to 36-4-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 11.
 - 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.




12/7/2024

Warning! Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss R14B	Truss Type PIGGYBACK BASE	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	---------------	------------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:19 2024 Page 1
ID:qqfH?RqemZ1wWmxuKuRIUzBcTx-GhMLmOxhMAge2MkDXiDLB7L2R5wHJ?RF57?kayBI9E



Scale = 1:73.8




Plate Offsets (X,Y)-- [2:0-0,0-0-7], [3:0-1-4,0-2-8], [5:0-2-10,0-1-12], [7:0-5-8,0-1-12], [8:0-5-12,0-2-0], [20:0-2-4,0-3-4], [22:0-4-3,0-3-3], [23:Edge,0-4-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.81	Vert(LL) -0.61	16	>699	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.98	Vert(CT) -0.95	16	>448	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.87	Horz(CT) 0.25	11	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 242 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2 *Except* T1: 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP No.2 *Except* B1: 2x6 SP No.2, B2,B3: 2x4 SP No.1, B5,B7: 2x4 SP SS	BOT CHORD Rigid ceiling directly applied. Except: 5-10-0 oc bracing: 14-17
WEBS 2x4 SP No.3 *Except* W2: 2x4 SP No.2	WEBS 1 Row at midpt 7-18, 8-17
WEDGE Right: 2x4 SP No.3	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1550/0-3-8 (min. 0-1-15), 11=1526/0-3-8 (min. 0-2-1)
Max Horz 2=210(LC 11)
Max Uplift 2=-68(LC 12), 11=-38(LC 13)
Max Grav 2=1624(LC 20), 11=1759(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2273/75, 3-4=-4487/259, 4-30=-4768/344, 5-30=-4732/366, 5-6=-2213/111,
6-7=-2093/149, 7-8=-1552/168, 8-9=-2408/163, 9-10=-2524/124, 10-31=-2471/88,
11-31=-2651/64
BOT CHORD 2-23=-166/1784, 22-23=-69/864, 21-22=-125/2478, 20-21=-125/2479, 19-20=-398/0,
18-32=0/1593, 16-32=0/1593, 16-33=0/1593, 13-33=0/1593, 12-13=0/1593, 12-34=0/2123,
34-35=0/2123, 11-35=0/2123
WEBS 5-21=0/320, 5-20=-864/213, 18-20=0/1859, 7-20=-104/1080, 7-18=-429/219,
8-14=-103/1151, 12-14=-134/1000, 10-12=-426/249, 3-22=-252/3117, 3-23=-1306/113,
5-22=-273/2054

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 8-8-9, Exterior(2R) 8-8-9 to 26-9-7, Interior(1) 26-9-7 to 30-8-6, Exterior(2E) 30-8-6 to 35-6-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 11.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum



12/7/2024

When used, approved, fabricated, installed or used before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R14B	PIGGYBACK BASE	1	1	Job Reference (optional) # 54883


Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:19 2024 Page 2
ID:qq1ffH?RqemZ1wWmxuKuRIUzBcTx-GhMLmOxhMAge2MkDXiDLB7L2R5wHJ?RF57?kayBI9E

LOAD CASE(S) Standard



12/7/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale = 1:75.5

Plate Offsets (X,Y)-- [5:0-3-12,0-2-0], [6:0-5-12,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.85	Vert(LL) -0.67	13	>639	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.92	Vert(CT) -0.96	12-13	>443	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.67	Horz(CT) 0.09	9	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS						
BCDL 10.0	Code IRC2021/TPI2014							
							Weight: 211 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP SS *Except*
 B3: 2x4 SP No.1
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3


BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied. Except:
 6-0-0 oc bracing: 12-15
 WEBS 1 Row at midpt 3-16, 6-15

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1551/0-3-8 (min. 0-2-1), 9=1525/Mechanical
 Max Horz2=208(LC 9)
 Max Uplift2=-66(LC 12), 9=-38(LC 13)
 Max Grav2=1766(LC 20), 9=1789(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2598/133, 3-4=-2053/118, 4-25=-1964/131, 5-25=-1937/158, 5-6=-1619/183,
 6-26=-2442/186, 7-26=-2474/159, 7-8=-2555/147, 8-9=-2707/118
 BOT CHORD 2-27=-117/2210, 18-27=-117/2210, 18-28=-117/2210, 17-28=-117/2210, 16-17=-117/2210,
 16-29=0/1650, 14-29=0/1650, 14-30=0/1650, 11-30=0/1650, 10-11=0/1650, 10-31=-23/2171,
 31-32=-23/2171, 9-32=-23/2171
 WEBS 3-18=0/274, 3-16=-665/213, 5-16=0/807, 6-15=-91/252, 6-12=-86/1145, 10-12=-118/970,
 8-10=-417/243

- NOTES-** (11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 10-6-2, Exterior(2R) 10-6-2 to 24-11-14, Interior(1) 24-11-14 to 30-8-6, Exterior(2E) 30-8-6 to 35-6-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 9.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.




12/7/2024

LOAD CASE(S) Standard

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI I-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R15	Piggyback Base	1	1	# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:25 2024 Page 1
 ID:qqjlfH?RqemZ1wWmxuKuRIUzBcTx-5rjc0R0Sx0QomHCNtyKIRNb3OW_nh1KJe0aJyEyBI98



Scale = 1:76.4

Plate Offsets (X,Y)-- [5:0-4-4,0-2-4], [6:0-6-4,0-2-4], [8:0-3-0,0-2-3]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.78	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.94	Vert(LL) -0.60 14-16 >706 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.82	Vert(CT) -0.89 14-16 >481 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.09 10 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 237 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.1 *Except*
 B2,B3: 2x4 SP SS
 WEBS 2x4 SP No.3 *Except*
 W5: 2x4 SP No.2
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3


BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.
 WEBS 1 Row at midpt 3-17, 6-16, 7-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1549/0-3-8 (min. 0-2-1), 10=1518/Mechanical
 Max Horz2=208(LC 9)
 Max Uplift2=-67(LC 12), 10=-48(LC 13)
 Max Grav2=1750(LC 20), 10=1705(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2567/130, 3-4=-2014/116, 4-26=-1925/129, 5-26=-1897/156, 5-6=-1586/182,
 6-7=-2488/292, 7-8=-1740/193, 8-27=-2307/148, 9-27=-2391/116, 9-10=-2584/132
 BOT CHORD 2-28=-118/2190, 19-28=-118/2190, 19-29=-118/2190, 18-29=-118/2190, 17-18=-118/2190,
 17-30=0/1446, 15-30=0/1446, 15-31=0/1446, 12-31=0/1446, 12-32=0/1446, 11-32=0/1446,
 11-33=-46/2075, 33-34=-46/2075, 10-34=-46/2075
 WEBS 3-19=0/285, 3-17=-671/210, 5-17=0/797, 6-16=-119/264, 6-13=-213/1215, 11-13=-269/1165,
 7-11=-996/84, 9-11=-320/194, 8-11=0/717

- NOTES-** (11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 10-6-2, Exterior(2R) 10-6-2 to 19-2-4, Exterior(2E) 19-2-4 to 21-9-0, Exterior(2R) 21-9-0 to 27-6-10, Interior(1) 27-6-10 to 30-8-6, Exterior(2E) 30-8-6 to 35-6-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R16	Piggyback Base	1	1	# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:28 2024 Page 1
 ID:qqiffH?RqemZ1wWmxuKuRIUzBcTx-VQOIFT2KExoMdkwyZ5tS20Damj1OulgmK_pzYzYBI95



Scale = 1:77.6




Plate Offsets (X,Y)-- [5:0-4-4,0-2-4], [6:0-6-4,0-2-4], [8:0-4-4,0-2-4]

LOADING (psf)	SPACING	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.78	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.89	Vert(LL) -0.70 15 >611 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.97	Vert(CT) -1.01 11-15 >420 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.09 10 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 230 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.1 *Except*
 B2,B3: 2x4 SP SS
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3


BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.
 WEBS 1 Row at midpt 3-17, 6-16, 7-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1551/0-3-8 (min. 0-2-1), 10=1523/Mechanical
 Max Horz 2=208(LC 9)
 Max Uplift 2=-66(LC 12), 10=-46(LC 13)
 Max Grav 2=1747(LC 20), 10=1664(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2560/146, 3-4=-2013/131, 4-26=-1924/145, 5-26=-1897/172, 5-6=-1585/194,
 6-27=-2568/283, 7-27=-2621/257, 7-8=-1976/149, 8-9=-2378/135, 9-10=-2559/153
 BOT CHORD 2-28=-117/2184, 19-28=-117/2184, 19-29=-117/2184, 18-29=-117/2184, 17-18=-117/2184,
 17-30=0/1461, 15-30=0/1461, 15-31=0/1461, 12-31=0/1461, 12-32=0/1461, 11-32=0/1461,
 10-11=-75/2048
 WEBS 3-19=0/276, 3-17=-665/211, 5-17=0/797, 6-16=-113/301, 6-13=-168/1268, 11-13=-218/1194,
 7-11=-1445/205, 8-11=-7/968

- NOTES-** (11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 10-6-2, Exterior(2R) 10-6-2 to 23-11-14, Interior(1) 23-11-14 to 24-9-0, Exterior(2R) 24-9-0 to 30-9-1, Exterior(2E) 30-9-1 to 35-6-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.




12/7/2024

LOAD CASE(S) Standard

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss R17	Truss Type Piggyback Base	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC	# 54883
--------------------	--------------	------------------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:31 2024 Page 1
 ID:qqfH?RqemZ1wWmxuKuRIUzBcTx-w?4tHV5CXsBxUCfWEDR9ger5?x205oiC0y1e9uyBI92



Scale = 1:77.6





Plate Offsets (X,Y)-- [5:0-4-4,0-2-4], [6:0-6-4,0-2-4], [9:0-4-4,0-2-4]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15	TC 0.78	Vert(LL) -0.63 16 >675 240	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15	BC 0.89	Vert(CT) -0.95 15 >450 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.62	Horz(CT) 0.08 10 n/a n/a		
BCLL 0.0 *	Code IRC2021/TPI2014	Matrix-AS			
BCDL 10.0				Weight: 232 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP SS *Except* B3: 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied. Except: 6-0-0 oc bracing: 14-17
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 3-18, 6-17
WEDGE Left: 2x4 SP No.3, Right: 2x4 SP No.3	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1551/0-3-8 (min. 0-2-1), 10=1523/Mechanical
 Max Horz 2=208(LC 9)
 Max Uplift 2=-66(LC 12), 10=-46(LC 13)
 Max Grav 2=1761(LC 20), 10=1726(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2582/137, 3-4=-2036/121, 4-27=-1947/135, 5-27=-1919/162, 5-6=-1604/186,
 6-28=-2671/250, 7-28=-2760/219, 7-8=-2627/123, 8-9=-2140/137, 9-29=-2479/122,
 10-29=-2598/105
 BOT CHORD 2-30=-117/2203, 20-30=-117/2203, 20-31=-117/2203, 19-31=-117/2203, 18-19=-117/2203,
 18-32=0/1575, 16-32=0/1575, 16-33=0/1575, 13-33=0/1575, 13-34=0/1575, 12-34=0/1575,
 11-12=-12/2301, 11-35=-27/2076, 10-35=-27/2076
 WEBS 3-20=0/275, 3-18=-665/212, 5-18=0/808, 6-17=-110/272, 6-14=-158/1390, 12-14=-194/1270,
 7-12=-412/199, 8-12=-270/94, 8-11=-1114/0, 9-11=0/1062

- NOTES-** (11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 10-6-2, Exterior(2R) 10-6-2 to 23-11-14, Interior(1) 23-11-14 to 27-9-0, Exterior(2R) 27-9-0 to 30-8-6, Exterior(2E) 30-8-6 to 35-6-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.




12/7/2024

LOAD CASE(S) Standard parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss R18	Truss Type Piggyback Base	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	--------------	------------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:34 2024 Page 1
ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-Kam0vW75qnZWLfO5vL_sIHtDR83AI9BeiwGimDyBI9?



Scale = 1:77.6




Plate Offsets (X,Y)-- [5:0-4-4,0-2-4], [6:0-6-4,0-2-4], [9:0-4-4,0-2-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.76	Vert(LL) -0.65	15	>655	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.93	Vert(CT) -0.97	15	>440	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.58	Horz(CT) 0.08	10	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS						
BCDL 10.0	Code IRC2021/TPI2014							
							Weight: 228 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS *Except*
B3: 2x4 SP No.1
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3


BRACING-
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied. Except:
6-0-0 oc bracing: 14-17
WEBS 1 Row at midpt 3-18, 6-17

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1551/0-3-8 (min. 0-2-1), 10=1523/Mechanical
Max Horz2=208(LC 9)
Max Uplift2=-66(LC 12), 10=-46(LC 13)
Max Grav2=1747(LC 20), 10=1660(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2559/132, 3-4=-2013/116, 4-27=-1924/130, 5-27=-1896/157, 5-6=-1585/182,
6-28=-2618/242, 7-28=-2711/211, 7-8=-2645/108, 8-9=-2132/103, 9-10=-2475/99
BOT CHORD 2-29=-117/2184, 20-29=-117/2184, 20-30=-117/2184, 19-30=-117/2184, 18-19=-117/2184,
18-31=0/1552, 16-31=0/1552, 16-32=0/1552, 13-32=0/1552, 13-33=0/1552, 12-33=0/1552,
11-12=-58/2489, 10-11=-40/1989
WEBS 3-20=0/274, 3-18=-665/212, 5-18=0/795, 6-17=-109/293, 6-14=-167/1347, 12-14=-203/1223,
7-12=-426/224, 8-12=-470/131, 8-11=-1474/63, 9-11=-31/1337

- NOTES-** (11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 10-6-2, Exterior(2R) 10-6-2 to 23-11-14, Interior(1) 23-11-14 to 30-9-0, Exterior(2R) 30-9-0 to 31-9-0, Exterior(2E) 31-9-0 to 35-6-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheathing be applied directly to the bottom chord.




12/7/2024

LOAD CASE(S) Standard

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss R19	Truss Type PIGGYBACK BASE	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC	# 54883
--------------------	--------------	------------------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:37 2024 Page 1
ID:qq1fH?RqemZ1wWmxuKuRlUzBcTx-k9R8YY9z6ix5C76gaUXZwv58AM4AVX74OuUyMYyBlBy



Scale = 1:67.3




Plate Offsets (X,Y)-- [5:0-6-4,0-2-4], [6:0-6-4,0-2-4]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15		TC 0.67	Vert(LL) -0.22	12-14	>999	240	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15		BC 0.91	Vert(CT) -0.35	12-14	>999	180		
TCDL 10.0	Rep Stress Incr YES		WB 0.57	Horz(CT) 0.08	9	n/a	n/a		
BCLL 0.0 *	Code IRC2021/TPI2014		Matrix-AS						
BCDL 10.0								Weight: 197 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2 *Except*
B2: 2x4 SP No.1
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3


BRACING-
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 5-12, 6-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1433/0-3-8 (min. 0-1-15), 9=1379/0-3-8 (min. 0-1-14)
Max Horz 2=208(LC 9)
Max Uplift 2=-104(LC 12), 9=-90(LC 13)
Max Grav 2=1619(LC 20), 9=1570(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-21=-2317/146, 3-21=-2138/170, 3-4=-2266/237, 4-5=-2151/276, 5-6=-1398/223,
6-7=-2154/277, 7-8=-2270/238, 8-22=-2141/175, 9-22=-2319/151
BOT CHORD 2-23=-166/1978, 23-24=-166/1978, 14-24=-166/1978, 14-25=-4/1405, 13-25=-4/1405,
13-26=-4/1405, 12-26=-4/1405, 12-27=0/1373, 11-27=0/1373, 11-28=0/1373, 10-28=0/1373,
10-29=-71/1851, 29-30=-71/1851, 9-30=-71/1851
WEBS 3-14=-446/253, 5-14=-196/903, 5-12=-79/356, 6-12=-80/356, 6-10=-197/908,
8-10=-448/254

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 8-6-5, Exterior(2R) 8-6-5 to 25-11-11, Interior(1) 25-11-11 to 29-8-6, Exterior(2E) 29-8-6 to 34-6-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9 except (jt=lb) 2=164
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.



12/7/2024

LOAD CASE(S) Standard

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss R20	Truss Type Piggyback Base	Qty 4	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	--------------	------------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:39 2024 Page 1
ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-hXZvyEBEeJBoRQG3iua1?KAUh9mkzRhNsCz3QQyBI8w

0-10-8 7-8-5 15-3-12 19-2-4 26-9-11 34-6-0 35-4-8
0-10-8 7-8-5 7-7-7 3-10-8 7-7-7 7-8-5 0-10-8

Scale = 1:67.7




Plate Offsets (X,Y)-- [5:0-6-4,0-2-4], [6:0-6-4,0-2-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.67	Vert(LL) -0.22	11-13	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.90	Vert(CT) -0.35	11-13	>999	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.57	Horz(CT) 0.08	9	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS						
BCDL 10.0	Code IRC2021/TPI2014							

Weight: 199 lb FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2 *Except*
B2: 2x4 SP No.1
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 5-13, 6-13

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS. (lb/size) 2=1432/0-3-8 (min. 0-1-15), 9=1433/0-3-8 (min. 0-1-15)
Max Horz 2=-211(LC 10)
Max Uplift 2=-104(LC 12), 9=-104(LC 13)
Max Grav 2=1619(LC 20), 9=1619(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-22=-2316/144, 3-22=-2137/168, 3-4=-2266/237, 4-5=-2150/276, 5-6=-1397/221,
6-7=-2150/276, 7-8=-2266/237, 8-23=-2137/168, 9-23=-2316/144
BOT CHORD 2-24=-158/1983, 24-25=-158/1983, 15-25=-158/1983, 15-26=0/1410, 14-26=0/1410,
14-27=0/1410, 13-27=0/1410, 13-28=0/1378, 12-28=0/1378, 12-29=0/1378, 11-29=0/1378,
11-30=-44/1848, 30-31=-44/1848, 9-31=-44/1848
WEBS 3-15=-446/253, 5-15=-196/903, 5-13=-79/356, 6-13=-79/356, 6-11=-196/904,
8-11=-446/253


- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-10-8 to 3-11-2, Interior(1) 3-11-2 to 8-6-5, Exterior(2R) 8-6-5 to 25-11-11, Interior(1) 25-11-11 to 30-6-14, Exterior(2E) 30-6-14 to 35-4-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=104 9=104.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



12/7/2024



Scale = 1:67.4

Plate Offsets (X,Y)-- [5:0-4-13,Edge], [6:0-4-13,Edge]		
--	--	--


LOADING (psf)	TCLL (roof) 20.0	SPACING-	2-0-0	CSI.		DEFL.		PLATES	GRIP
	Snow (Pf) 20.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	-0.22 12-14 >999 240	MT20	244/190
	TCDL 10.0	Lumber DOL	1.15	BC	0.91	Vert(CT)	-0.34 12-14 >999 180		
	BCLL 0.0 *	Rep Stress Incr	YES	WB	0.56	Horz(CT)	0.08 9 n/a n/a		
	BCDL 10.0	Code IRC2021/TPI2014		Matrix-AS				Weight: 197 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP No.2 *Except* B2: 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 5-12, 6-12
WEDGE Left: 2x4 SP No.3 , Right: 2x4 SP No.3	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1433/0-3-8 (min. 0-1-15), 9=1379/0-3-8 (min. 0-1-14)
 Max Horz 2=205(LC 11)
 Max Uplift 2=-105(LC 12), 9=-90(LC 13)
 Max Grav 2=1620(LC 20), 9=1570(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-21=-2316/146, 3-21=-2137/170, 3-4=-2258/237, 4-5=-2141/274, 5-6=-1413/222,
 6-7=-2144/275, 7-8=-2262/238, 8-22=-2140/174, 9-22=-2318/151
 BOT CHORD 2-23=-164/1975, 23-24=-164/1975, 14-24=-164/1975, 14-25=-5/1419, 13-25=-5/1419,
 13-26=-5/1419, 12-26=-5/1419, 12-27=0/1387, 11-27=0/1387, 11-28=0/1387, 10-28=0/1387,
 10-29=-71/1849, 29-30=-71/1849, 9-30=-71/1849
 WEBS 3-14=-419/249, 5-14=-193/877, 5-12=-78/357, 6-12=-79/356, 6-10=-194/882,
 8-10=-421/250

- NOTES-** (10)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 8-6-5, Exterior(2R) 8-6-5 to 25-11-11, Interior(1) 25-11-11 to 29-8-6, Exterior(2E) 29-8-6 to 34-6-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9 except (jt=lb) 2=105.
 - 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.




LOAD CASE(S) Standard

12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI I-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss R22	Truss Type Hip	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC	# 54883
--------------------	--------------	-------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:43 2024 Page 1
 ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-ZloQobEkiYhEw2aqkzez9ALEPm9?vJ7zmqxGZByBl8s



Scale = 1:59.8





Plate Offsets (X,Y)-- [5:0-4-13,Edge], [7:0-4-13,Edge]							
LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP		
TCLL (roof) 20.0	2-0-0	TC 0.43	in (loc) l/defl L/d	MT20	244/190		
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.82	Vert(LL) -0.26 12-14 >999 240				
TCDL 10.0	Lumber DOL 1.15	WB 0.22	Vert(CT) -0.40 12-14 >999 180				
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.09 10 n/a n/a			Weight: 196 lb FT = 20%	
BCDL 10.0	Code IRC2021/TPI2014						

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP No.2 *Except* B2: 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 6-14
WEDGE Left: 2x4 SP No.3 , Right: 2x4 SP No.3	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1432/0-3-8 (min. 0-1-12), 10=1433/0-3-8 (min. 0-1-12)
 Max Horz 2=-170(LC 10)
 Max Uplift 2=-88(LC 12), 10=-88(LC 13)
 Max Grav 2=1499(LC 3), 10=1499(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-23=-2198/196, 23-24=-2103/221, 3-24=-2058/224, 3-4=-2055/235, 4-5=-1966/265,
 5-6=-1640/251, 6-7=-1640/251, 7-8=-1966/265, 8-9=-2055/235, 9-25=-2058/224,
 25-26=-2103/221, 10-26=-2198/196
BOT CHORD 2-27=-129/1804, 27-28=-129/1804, 16-28=-129/1804, 16-29=-53/1442, 15-29=-53/1442,
 15-30=-53/1442, 14-30=-53/1442, 14-31=-19/1442, 13-31=-19/1442, 13-32=-19/1442,
 12-32=-19/1442, 12-33=-101/1755, 33-34=-101/1755, 10-34=-101/1755
WEBS 3-16=-285/185, 5-16=-85/597, 5-14=-95/473, 6-14=-338/117, 7-14=-95/473, 7-12=-85/597,
 9-12=-285/185

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 5-6-5, Exterior(2R) 5-6-5 to 28-11-11, Interior(1) 28-11-11 to 30-6-14, Exterior(2E) 30-6-14 to 35-4-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.




LOAD CASE(S) Standard

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


12/7/2024

Job 24-B205-R01	Truss R23	Truss Type Hip	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC	# 54883
--------------------	--------------	-------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:45 2024 Page 1
 ID:qqfH?RqemZ1wWmxuKuRIUzBcTx-VhwADHG_E9xy9LjD29hREbQW6asnNA9GE7QNe4yBI8q



Scale = 1:59.4



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.67	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.73	Vert(LL) -0.19 10-12 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.44	Vert(CT) -0.33 10-12 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.09 8 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 186 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1432/0-3-8 (min. 0-1-11), 8=1432/0-3-8 (min. 0-1-11)
 Max Horz 2=-131(LC 10)
 Max Uplift 2=-67(LC 10), 8=-67(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-21=-2052/211, 3-21=-1940/231, 3-4=-1872/223, 4-22=-1962/265, 5-22=-1964/264, 5-23=-1964/264, 6-23=-1962/265, 6-7=-1872/223, 7-24=-1940/231, 8-24=-2052/211
 BOT CHORD 2-14=-143/1636, 13-14=-114/1532, 13-25=-114/1532, 12-25=-114/1532, 12-26=-38/1532, 11-26=-38/1532, 10-11=-38/1532, 8-10=-114/1636
 WEBS 4-14=0/390, 4-12=-148/658, 5-12=-561/189, 6-12=-148/658, 6-10=0/390


- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Exterior(2R) 3-11-2 to 16-1-3, Interior(1) 16-1-3 to 18-4-13, Exterior(2R) 18-4-13 to 30-6-14, Exterior(2E) 30-6-14 to 35-4-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale = 1:58.2




Plate Offsets (X,Y)-- [2:0-0-0,0-0-3], [4:0-5-12,0-2-0], [9:0-5-12,0-2-0], [11:0-0-0,0-0-3]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.76	Vert(LL) 0.28	17	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.71	Vert(CT) -0.39	17	>999	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.66	Horz(CT) 0.09	11	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MSH						
BCDL 10.0	Code IRC2021/TPI2014							
							Weight: 226 lb	FT = 20%


LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 2-6-4 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 5-11-10 oc bracing.
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1967/0-3-8 (min. 0-2-5), 11=1955/0-3-8 (min. 0-2-5)
 Max Horz 2=-97(LC 8)
 Max Uplift 2=-733(LC 10), 11=-715(LC 6)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-28=-2908/1168, 3-28=-2813/1165, 3-29=-2813/1222, 4-29=-2724/1231, 4-30=-3362/1546, 30-31=-3362/1546, 5-31=-3362/1546, 5-32=-3705/1692, 32-33=-3705/1692, 6-33=-3705/1692, 6-34=-3705/1692, 7-34=-3705/1692, 7-35=-3705/1692, 35-36=-3705/1692, 8-36=-3705/1692, 8-37=-3351/1531, 37-38=-3351/1531, 9-38=-3351/1531, 9-39=-2703/1202, 10-39=-2791/1194, 10-40=-2795/1140, 11-40=-2890/1143
 BOT CHORD 2-41=-1025/2357, 21-41=-1025/2357, 21-42=-1025/2357, 20-42=-1025/2357, 20-43=-1045/2294, 43-44=-1045/2294, 19-44=-1045/2294, 18-19=-1551/3362, 18-45=-1551/3362, 17-45=-1551/3362, 17-46=-1508/3351, 46-47=-1508/3351, 16-47=-1508/3351, 16-48=-1508/3351, 15-48=-1508/3351, 15-49=-963/2276, 49-50=-963/2276, 14-50=-963/2276, 14-51=-916/2342, 13-51=-916/2342, 13-52=-916/2342, 11-52=-916/2342
 WEBS 4-20=-58/358, 4-19=-705/1429, 5-19=-765/481, 5-17=-228/468, 6-17=-422/299, 8-17=-247/482, 8-15=-772/490, 9-15=-718/1439, 9-14=-56/348

- NOTES-** (11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCCL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=733, 11=715.
 - "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
 - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).



12/7/2024

LOAD CASE(S) Standard parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R24	Hip Girder	1	1	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:49 2024 Page 2
ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-OSAh3fJVHOSOez1_H?INPRbBkBE?Jwhr9lObnryBI8m

LOAD CASE(S) Standard

1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-4=-60, 4-9=-60, 9-12=-60, 22-25=-20

Concentrated Loads (lb)

Vert: 18=-23(B) 20=-23(B) 19=-23(B) 4=-40(B) 5=-40(B) 9=-40(B) 14=-23(B) 28=-37(B) 29=-10(B) 30=-40(B) 31=-40(B) 32=-40(B) 33=-40(B) 34=-40(B) 35=-40(B) 36=-40(B) 37=-40(B) 38=-40(B) 39=-10(B) 40=-37(B) 41=-42(B) 42=-59(B) 43=-23(B) 44=-23(B) 45=-23(B) 46=-23(B) 47=-23(B) 48=-23(B) 49=-23(B) 50=-23(B) 51=-59(B) 52=-42(B)



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




Plate Offsets (X,Y)-- [5:0-4-0,0-0-15], [7:0-4-0,0-0-15]					
LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.14	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.07	Vert(LL) -0.00 11 n/r 180		
TCDL 10.0	Lumber DOL 1.15	WB 0.06	Vert(CT) -0.00 11 n/r 80		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-R	Horz(CT) 0.00 12 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 87 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 12-0-0.
(lb) - Max Horz 20=120(LC 11)
Max Uplift All uplift 100 lb or less at joint(s) 20, 12, 17, 15, 16 except 19=-112(LC 12), 13=-109(LC 13)
Max Grav All reactions 250 lb or less at joint(s) 20, 12, 18, 19, 14, 13, 17, 15, 16

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (14)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 4-2-0, Corner(3R) 4-2-0 to 7-10-0, Corner(3E) 7-10-0 to 12-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 6) Provide adequate drainage to prevent water ponding.
 - 7) All plates are 2x4 MT20 unless otherwise indicated.
 - 8) Gable requires continuous bottom chord bearing.
 - 9) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 10) Gable studs spaced at 2-0-0 oc.
 - 11) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 12) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 20, 12, 17, 15, 16 except (jt=lb) 19=112, 13=109.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss R26	Truss Type Hip Girder	Qty 1	Ply 2	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC	# 54883
--------------------	--------------	--------------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:52 2024 Page 1
ID:qqllfh?RqemZ1wWmxuKuRIUzBcTx-o1rphgLNajyVQmZz7J414DoXPFFWL8lrjdFOayBI8j



Scale = 1:36.2

Plate Offsets (X,Y)-- [4:0-6-4,0-1-12], [5:0-2-4,0-1-12], [8:0-4-0,0-4-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.28	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.74	Vert(LL) -0.05 8-12 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.42	Vert(CT) -0.09 8-12 >999 180		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MSH	Horz(CT) -0.01 7 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 167 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 1-11-0, Right 2x4 SP No.3 1-11-0


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 7=3568/0-3-8 (min. 0-2-2), 2=2438/0-3-8 (min. 0-1-8)
Max Horz 2=110(LC 33)
Max Uplift 7=-346(LC 11), 2=-406(LC 10)
Max Grav 7=3592(LC 4), 2=2438(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1717/362, 3-4=-2734/463, 4-5=-2264/331, 5-6=-3152/397, 6-7=-2657/302
BOT CHORD 2-18=-307/1846, 18-19=-307/1846, 9-19=-307/1846, 9-20=-319/1861, 8-20=-319/1861,
8-21=-230/2211, 21-22=-230/2211, 22-23=-230/2211, 7-23=-230/2211
WEBS 4-9=-463/567, 4-8=0/1439, 5-8=-261/2050

NOTES- (14)

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-7-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 7=346, 2=406.
- Use Simpson Strong-Tie HTU26 (10-16d Girder, 14-10dx1 1/2 Truss) or equivalent spaced at 2-0-0 oc max. starting at 4-0-12 from the left end to 8-0-12 to connect truss(es) R10 (1 ply 2x6 SP), R11 (1 ply 2x4 SP), R12 (1 ply 2x4 SP) to back face of bottom chord.
- Fill all nail holes where hanger is in contact with lumber.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1491 lb down and 112 lb up at 10-0-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.



12/7/2024

Warning! Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer - not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R26	Hip Girder	1	2	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:53 2024 Page 2
ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-GEPCu0M0Ldyp7aLIWqrqJZHlzHobTFoOR4NMowcyB18i


LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (plf)
 - Vert: 1-4=-60, 4-5=-60, 5-7=-60, 10-14=-20
- Concentrated Loads (lb)
 - Vert: 19=-795(B) 20=-1399(B) 21=-1399(B) 23=-1399



12/7/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale = 1:30.5

Plate Offsets (X,Y)-- [5:0-2-8,Edge], [7:0-2-8,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15		TC 0.14	Vert(LL) -0.00	11	n/r	180	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15		BC 0.07	Vert(CT) -0.00	11	n/r	80		
TCDL 10.0	Rep Stress Incr YES		WB 0.06	Horz(CT) 0.00	12	n/a	n/a		
BCLL 0.0 *	Code IRC2021/TPI2014		Matrix-R						
BCDL 10.0								Weight: 90 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 12-3-8.
 (lb) - Max Horz 20=123(LC 11)
 Max Uplift All uplift 100 lb or less at joint(s) 20, 12, 17, 15, 16 except 19=-115(LC 12), 13=-113(LC 13)
 Max Grav All reactions 250 lb or less at joint(s) 20, 12, 18, 19, 14, 13, 17, 15, 16

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (14)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 4-1-12, Corner(3R) 4-1-12 to 8-1-12, Corner(3E) 8-1-12 to 13-2-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 6) Provide adequate drainage to prevent water ponding.
 - 7) All plates are 2x4 MT20 unless otherwise indicated.
 - 8) Gable requires continuous bottom chord bearing.
 - 9) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 10) Gable studs spaced at 2-0-0 oc.
 - 11) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 12) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 20, 12, 17, 15, 16 except (jt=lb) 19=115, 13=113.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss R28	Truss Type Hip Girder	Qty 1	Ply 2	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC	# 54883
--------------------	--------------	--------------------------	----------	----------	--	---------

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:54 2024 Page 1
ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-kQza6MNe6w4gkvw4YLY6V17VCuT_CZbl16LS3yBl8h



Scale = 1:37.6

Plate Offsets (X,Y)--		[1:0-3-0,0-2-0], [3:0-6-4,0-1-12], [4:0-2-4,0-1-12], [7:0-4-0,0-4-12]	
LOADING (psf)		SPACING-	2-0-0
TCLL (roof)	20.0	Plate Grip DOL	1.15
Snow (Pf)	20.0	Lumber DOL	1.15
TCDL	10.0	Rep Stress Incr	NO
BCLL	0.0 *	Code IRC2021/TPI2014	
BCDL	10.0		
		CSI.	
		TC	0.37
		BC	0.95
		WB	0.62
		Matrix-MSH	
		DEFL.	
		in (loc)	l/defl L/d
		Vert(LL)	-0.07 8-11 >999 240
		Vert(CT)	-0.13 8-11 >999 180
		Horz(CT)	0.02 1 n/a n/a
		PLATES	GRIP
		MT20	244/190
		Weight: 168 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 1-11-0, Right 2x4 SP No.3 1-11-0

BRACING-
TOP CHORD Structural wood sheathing directly applied or 5-8-3 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 1=4299/0-3-8 (min. 0-2-13), 6=4196/0-3-8 (min. 0-2-11)
Max Horz 1=-101(LC 31)
Max Uplift 1=-157(LC 10), 6=-158(LC 11)
Max Grav 1=4761(LC 3), 6=4577(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-3653/158, 2-3=-4379/199, 3-4=-3170/191, 4-5=-4408/201, 5-6=-3555/161
BOT CHORD 1-17=-121/3073, 17-18=-121/3073, 18-19=-121/3073, 8-19=-121/3073, 8-20=-124/3147,
7-20=-124/3147, 7-21=-91/3093, 21-22=-91/3093, 22-23=-91/3093, 6-23=-91/3093
WEBS 3-8=-119/2907, 4-7=-122/2997

- NOTES-** (12)
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-5-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=157, 6=158.
 - Use Simpson Strong-Tie HTU26 (10-16d Girder, 14-10dx1 1/2 Truss) or equivalent spaced at 2-0-0 oc max. starting at 2-0-12 from the left end to 10-0-12 to connect truss(es) R14C (1 ply 2x4 SP), R15 (1 ply 2x4 SP), R16 (1 ply 2x4 SP), R17 (1 ply 2x4 SP), R18 (1 ply 2x4 SP) to back face of bottom chord.
 - Fill all nail holes where hanger is in contact with lumber.



12/7/2024

LOAD CASE(S) Standard

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	R28	Hip Girder	1	2	Job Reference (optional) # 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:54 2024 Page 2
ID:qqfH?RqemZ1wWmxuKuRIUzBcTx-kQza6MNe6w4gkxv4YLY6V17VCuT_CZbl16LS3yBl8h

LOAD CASE(S) Standard

1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-3=-60, 3-4=-60, 4-6=-60, 9-13=-20

Concentrated Loads (lb)

Vert: 17=-1505(B) 19=-1498(B) 20=-1503(B) 21=-1503(B) 23=-1503(B)



12/7/2024

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Job 24-B205-R01	Truss V01	Truss Type Valley	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	--------------	----------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:54 2024 Page 1
ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-kQza6MNe6w4gkvvx4YLY6VI44C1i_KRb16LS3yBI8h



4x4 =

Scale = 1:35.5



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.53	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.36	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.12	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 38 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 7-3-8 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=40/7-3-8 (min. 0-1-8), 3=193/7-3-8 (min. 0-1-8), 4=310/7-3-8 (min. 0-1-8)
Max Horz 5=-133(LC 8)
Max Uplift 5=-54(LC 9), 3=-11(LC 9), 4=-46(LC 8)
Max Grav 5=79(LC 19), 3=210(LC 19), 4=449(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BC DL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BC DL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 3, 4.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Job 24-B205-R01	Truss V02	Truss Type Valley	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	--------------	----------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:55 2024 Page 1
ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-DcXyJiNGtECXMuU8eGsneirJqcQfjohkXhrv_VyBI8g



4x4 =

Scale = 1:27.0



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.27	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.19	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.05	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 29 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 5-11-8 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=54/5-11-8 (min. 0-1-8), 3=142/5-11-8 (min. 0-1-8), 4=241/5-11-8 (min. 0-1-8)
Max Horz 5=-93(LC 8)
Max Uplift 5=-36(LC 9), 3=-12(LC 9), 4=-28(LC 8)
Max Grav 5=76(LC 19), 3=154(LC 23), 4=266(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 3, 4.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss V03	Truss Type Valley	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	--------------	----------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:55 2024 Page 1
ID:qqllfH?RqemZ1wWmxuKuRIUzBcTx-DcXyJiNGtECXMuU8eGsneirMZcP1joVkXhrv_VyBl8g



Scale = 1:16.3

Plate Offsets (X,Y)-- [2:0-3-0,Edge], [4:0-5-0,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15		TC 0.10	Vert(LL) n/a	-	n/a	999		MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15		BC 0.23	Vert(CT) n/a	-	n/a	999			
TCDL 10.0	Rep Stress Incr YES		WB 0.00	Horz(CT) 0.00	3	n/a	n/a			
BCLL 0.0 *	Code IRC2021/TPI2014		Matrix-R							
BCDL 10.0									Weight: 17 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 4-7-8 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 4=165/4-7-8 (min. 0-1-8), 3=165/4-7-8 (min. 0-1-8)
Max Horz 4=-54(LC 8)
Max Uplift 4=-13(LC 13), 3=-8(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 3.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss V04	Truss Type Valley	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	--------------	----------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:55 2024 Page 1
ID:qqfH?RqemZ1wWmxuKuRIUzBcTx-DcXyJiNGtECXMuU8eGsneirNocRCjoVkXhrv_VyBI8g



Scale = 1:9.7

Plate Offsets (X,Y)-- [2:0-3-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.02	Vert(LL)	n/a	-	n/a	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.09	Vert(CT)	n/a	-	n/a		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 9 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 2-10-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=85/2-10-0 (min. 0-1-8), 3=85/2-10-0 (min. 0-1-8)
Max Horz 1=-21(LC 8)
Max Uplift 1=-4(LC 13), 3=-4(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCCL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC
24-B205-R01	V05	Valley	1	1	
					# 54883

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:56 2024 Page 1
 ID:qqfH?RqemZ1wWmxuKuRIUzBcTx-ho5KX2OueYKO_13KCzN0BwNSY0gYSE?tmLbSxxyBl8f



Scale = 1:34.9

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.40	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.46	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.11	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 46 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6'-0-0 oc purlins.
 Rigid ceiling directly applied or 10'-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS. (lb/size) 1=234/11-1-8 (min. 0-1-8), 3=234/11-1-8 (min. 0-1-8), 4=366/11-1-8 (min. 0-1-8)
 Max Horz 1=-102(LC 8)
 Max Uplift1=-34(LC 13), 3=-34(LC 13)
 Max Grav 1=234(LC 1), 3=234(LC 1), 4=461(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BC DL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-4-4 to 5-1-13, Exterior(2R) 5-1-13 to 5-11-11, Exterior(2E) 5-11-11 to 10-9-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3'-6-0 tall by 1'-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Job 24-B205-R01	Truss V06	Truss Type Valley	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	--------------	----------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:56 2024 Page 1
ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-ho5KX2OueYKO_13KCzN0BwNUA0jSF?tmLbSXyB18f



4x4 =

Scale = 1:27.8



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.30	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.26	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.05	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 34 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=187/8-5-8 (min. 0-1-8), 3=187/8-5-8 (min. 0-1-8), 4=247/8-5-8 (min. 0-1-8)
Max Horz 1=-76(LC 8)
Max Uplift1=35(LC 13), 3=35(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss V07	Truss Type Valley	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	--------------	----------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:57 2024 Page 1
ID:qq1fH?RqemZ1wWmxuKuRIUzBcTx-9?fikOPWPrSFbBeWlguFk7whXQ?Lbi?1?K03NyBi8e



Scale = 1:19.7

Plate Offsets (X,Y)-- [2:0-3-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.13	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.56	Vert(CT)	n/a	-	n/a	999		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 20 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 5-9-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=204/5-9-8 (min. 0-1-8), 3=204/5-9-8 (min. 0-1-8)
Max Horz 1=-50(LC 8)
Max Uplift 1=-10(LC 12), 3=-10(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 24-B205-R01	Truss V08	Truss Type Valley	Qty 1	Ply 1	LOT 0.0015 CAMPBELL RIDGE 271 ALDEN WAY ANGIER, NC Job Reference (optional) # 54883
--------------------	--------------	----------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat Dec 7 18:05:57 2024 Page 1
ID:qqIfH?RqemZ1wWmxuKuRIUzBcTx-9?fikOPWPrSFbBeWlguFk7wj0Q6FBi?1?K03NyBI8e



Scale = 1:10.4

Plate Offsets (X,Y)-- [2:0-3-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.04	Vert(LL)	n/a	-	n/a	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.11	Vert(CT)	n/a	-	n/a		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 10 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 3-1-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=97/3-1-8 (min. 0-1-8), 3=97/3-1-8 (min. 0-1-8)
Max Horz 1=24(LC 11)
Max Uplift 1=-5(LC 12), 3=-5(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCCL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard



12/7/2024

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.