





Client: QUEST DEV.
Project:
Address:

Date: 8/12/2025
Input by: LENNY NORRIS
Job Name: HENSLEY
Project #:

Page 1 of 2

BM1 Kerto-S LVL 1.750" X 9.250" 2-Ply - PASSED

Level: Level



Member Information

| | | | |
|---------------------|---------------|----------------|--------------|
| Type: | Girder | Application: | Floor |
| Plies: | 2 | Design Method: | ASD |
| Moisture Condition: | Dry | Building Code: | IBC/IRC 2015 |
| Deflection LL: | 480 | Load Sharing: | No |
| Deflection TL: | 360 | Deck: | Not Checked |
| Importance: | Normal - II | | |
| Temperature: | Temp <= 100°F | | |

Reactions UNPATTERNED lb (Uplift)

| Brg | Direction | Live | Dead | Snow | Wind | Const |
|-----|-----------|------|------|------|------|-------|
| 1 | Vertical | 0 | 477 | 456 | 0 | 0 |
| 2 | Vertical | 0 | 463 | 443 | 0 | 0 |

Bearings

| Bearing | Length | Dir. | Cap. | React D/L lb | Total | Ld. Case | Ld. Comb. |
|-------------------|--------|------|------|--------------|-------|----------|-----------|
| 1 - SPF End Grain | 3.500" | Vert | 9% | 477 / 456 | 932 | L | D+S |
| 2 - Hanger | 2.500" | Vert | 12% | 463 / 443 | 906 | L | D+S |

Analysis Results

| Analysis | Actual | Location | Allowed | Capacity | Comb. | Case |
|--------------|----------------|-----------|---------------|----------|-------|------|
| Moment | 1174 ft-lb | 2'11 1/2" | 14423 ft-lb | 8% | D+S | L |
| Unbraced | 1174 ft-lb | 2'11 1/2" | 11110 ft-lb | 11% | D+S | L |
| Shear | 598 lb | 1' 3/4" | 7943 lb | 8% | D+S | L |
| LL Defl inch | 0.009 (L/7526) | 2'11 1/2" | 0.136 (L/480) | 6% | S | L |
| TL Defl inch | 0.018 (L/3677) | 2'11 1/2" | 0.182 (L/360) | 10% | D+S | L |

Design Notes

- 1 Provide support to prevent lateral movement and rotation at the end bearings.
- 2 Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- 3 Refer to last page of calculations for fasteners required for specified loads.
- 4 Fill all hanger nailing holes.
- 5 Right Header: SPF, Thickness: 3 1/2"
- 6 Girders are designed to be supported on bottom edge only and across their full width.
- 7 Top loads must be supported equally by all plies.
- 8 Top must be laterally braced at end bearings.
- 9 Bottom must be laterally braced at end bearings.
- 10 Lateral slenderness ratio based on single ply width.

| ID | Load Type | Location | Trib Width | Side | Dead 0.9 | Live 1 | Snow 1.15 | Wind 1.6 | Const. 1.25 | Comments |
|----|-------------|----------|------------|------|----------|--------|-----------|----------|-------------|----------|
| 1 | Uniform | | | Top | 154 PLF | 0 PLF | 154 PLF | 0 PLF | 0 PLF | M2 TRUSS |
| | Self Weight | | | | 7 PLF | | | | | |

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/28/2028

Manufacturer Info

Metsä Wood
301 Merritt 7 Building, 2nd Floor
Norwalk, CT 06851
(800) 622-5850
www.metsawood.com/us





Client: QUEST DEV.
Project:
Address:

Date: 8/12/2025
Input by: LENNY NORRIS
Job Name: HENSLEY
Project #:

Page 2 of 2

BM1 Kerto-S LVL 1.750" X 9.250" 2-Ply - PASSED

Level: Level



Multi-Ply Analysis

Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c.. Maximum end distance not to exceed 6".

| | |
|--------------------------|-----------|
| Capacity | 0.0 % |
| Load | 0.0 PLF |
| Yield Limit per Foot | 163.7 PLF |
| Yield Limit per Fastener | 81.9 lb. |
| C _m | 1 |
| Yield Mode | IV |
| Edge Distance | 1 1/2" |
| Min. End Distance | 3" |
| Load Combination | |
| Duration Factor | 1.00 |

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/28/2028

Manufacturer Info

Metsä Wood
301 Merritt 7 Building, 2nd Floor
Norwalk, CT 06851
(800) 622-5850
www.metsawood.com/us