

# Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 56404

JOB: 25-0726-F02

JOB NAME: LOT 0.0008 CAMPBELL RIDGE

Wind Code: N/A

Wind Speed: Vult= N/A

Exposure Category: N/A

Mean Roof Height (feet): N/A

These truss designs comply with IRC 2018 as well as IRC 2021.

6 Truss Design(s)

Trusses:

F01, F02, F03, F04, F05, F06



2/3/2025

Mark Morris

**Warning !—Verify design parameters and read notes before use.**

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI

Job 25-0726-F02	Truss F01	Truss Type Floor Supported Gable	Qty 1	Ply 1	LOT 0.0008 CAMPBELL RIDGE   214 ALDEN WAY ANGIER, NC Job Reference (optional) <b># 56404</b>
--------------------	--------------	-------------------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Feb 3 18:29:21 2025 Page 1  
ID:TI8BXP?rb369B\_B636Qe0HyKJdu-KcJP7ujVjhdDpyG4p5pu?8xkomv6qXxv1PTUnzonEi

0-1-8

Scale = 1:17.5




Plate Offsets (X,Y)-- [4:0-1-8,Edge], [14:0-1-8,Edge], [18:Edge,0-1-8]		9-9-6 9-9-6			
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.06	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 10 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
				Weight: 42 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

**REACTIONS.** All bearings 9-9-6.  
(lb) - Max Uplift All uplift 100 lb or less at joint(s) 10  
Max Grav All reactions 250 lb or less at joint(s) 18, 10, 17, 16, 15, 14, 13, 12, 11

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (7)
- Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 10.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard



2/3/2025

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job 25-0726-F02	Truss F03	Truss Type Floor Girder	Qty 1	Ply 1	LOT 0.0008 CAMPBELL RIDGE   214 ALDEN WAY ANGIER, NC Job Reference (optional) <b># 56404</b>
--------------------	--------------	----------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Feb 3 18:29:22 2025 Page 1  
ID:T18BXP?rb369B\_B636Qe0HyKJdu-oosnLEK7U?14R6FSeWc2RDh\_tBuWrCJ58h800DzonEh




Plate Offsets (X,Y)--	[2:0-1-8,Edge], [3:0-1-8,Edge], [12:Edge,0-1-8]
-----------------------	---

LOADING (psf)	SPACING-	CSL	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.55	Vert(LL) -0.13	8-9	>886	480	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.94	Vert(CT) -0.16	8-9	>699	360		
BCLL 0.0	Lumber DOL 1.00	WB 0.38	Horz(CT) 0.01	6	n/a	n/a		
BCDL 5.0	Rep Stress Incr NO	Matrix-SH						
	Code IRC2021/TPI2014						Weight: 48 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 12=508/0-3-6 (min. 0-1-8), 6=506/Mechanical

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 12-13=-488/0, 1-13=-487/0, 5-6=-495/0, 1-2=-701/0, 2-3=-1195/0, 3-14=-1302/0, 4-14=-1302/0, 4-5=-689/0  
 BOT CHORD 10-11=0/1195, 9-10=0/1195, 8-9=0/1195, 7-8=0/1228  
 WEBS 2-10=0/382, 1-11=0/801, 2-11=-824/0, 4-7=-659/0, 5-7=0/789

- NOTES-** (7)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) Refer to girder(s) for truss to truss connections.
  - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 4) CAUTION, Do not erect truss backwards.
  - 5) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 154 lb up at 6-3-10 on top chord. The design/selection of such connection device(s) is the responsibility of others.
  - 6) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
 Uniform Loads (plf)  
 Vert: 6-12=-10, 1-5=-100  
 Concentrated Loads (lb)  
 Vert: 14=28(B)




2/3/2025

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 25-0726-F02	Truss F04	Truss Type Floor Girder	Qty 1	Ply 1	LOT 0.0008 CAMPBELL RIDGE   214 ALDEN WAY ANGIER, NC Job Reference (optional) <b># 56404</b>
--------------------	--------------	----------------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Feb 3 18:29:22 2025 Page 1  
ID: T18BXP?rb369B\_B636Qe0HyKJdu-oosnLEk7U?4R6FSeWc2RDh1oB6zrHZ58h800DzonEh



Scale = 1:7.8

Plate Offsets (X,Y)-- [6:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.36	Vert(LL)	0.00	5	****	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.02	Vert(CT)	-0.00	6	>999		
BCLL 0.0	Rep Stress Incr	NO	WB 0.05	Horz(CT)	0.00	4	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-P						
								Weight: 19 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 2-10-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 6=126/2-0-8 (min. 0-1-8), 4=-31/Mechanical, 5=414/2-0-8 (min. 0-1-8)  
Max Uplift4=-67(LC 3)  
Max Grav6=129(LC 3), 5=414(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
WEBS 2-5=-408/0

- NOTES-** (9)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) Refer to girder(s) for truss to truss connections.
  - 3) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4.
  - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 5) CAUTION, Do not erect truss backwards.
  - 6) Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent at 1-5-4 from the left end to connect truss(es) F05 (1 ply 2x4 SP) to front face of top chord.
  - 7) Fill all nail holes where hanger is in contact with lumber.
  - 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 4-6=-10, 1-3=-100  
Concentrated Loads (lb)  
Vert: 7=-225(F)



2/3/2025

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 25-0726-F02	Truss F05	Truss Type Floor	Qty 1	Ply 1	LOT 0.0008 CAMPBELL RIDGE   214 ALDEN WAY ANGIER, NC Job Reference (optional) <b># 56404</b>
--------------------	--------------	---------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Feb 3 18:29:22 2025 Page 1  
ID:T18BXP?rb369B\_B636Qe0HyKJdu-oosnLEK7U?14R6FSeWc2RDh4a3B3grEA58h800DzonEh






Plate Offsets (X,Y)-- [2:0-1-8,Edge], [3:0-1-8,Edge], [5:Edge,0-1-8], [10:Edge,0-1-8]

<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.18	Vert(LL) -0.02 8 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.23	Vert(CT) -0.02 8 >999 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.20	Horz(CT) 0.00 5 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
				Weight: 32 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 10=319/0-3-6 (min. 0-1-8), 5=325/Mechanical

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 10-11=-313/0, 1-11=-312/0, 4-5=-315/0, 1-2=-368/0, 2-3=-519/0  
BOT CHORD 8-9=0/519, 7-8=0/519, 6-7=0/519  
WEBS 1-9=0/416, 2-9=-250/0, 3-6=-472/0, 4-6=0/282

- NOTES-** (5)  
1) Unbalanced floor live loads have been considered for this design.  
2) Refer to girder(s) for truss connections.  
3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
4) CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard



2/3/2025

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 25-0726-F02	Truss F06	Truss Type Floor	Qty 5	Ply 1	LOT 0.0008 CAMPBELL RIDGE   214 ALDEN WAY ANGIER, NC Job Reference (optional) <b># 56404</b>
--------------------	--------------	---------------------	----------	----------	--

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Feb 3 18:29:22 2025 Page 1  
ID: T18BXP?rb369B\_B636Qe0HyKJdu-oosnLEk7U?l4R6FSeWc2RDh4pB3urEy58h800DzonEh




Plate Offsets (X,Y)--	[2:0-1-8,Edge], [3:0-1-8,Edge], [4:0-1-8,Edge], [5:Edge,0-1-8], [10:Edge,0-1-8]
-----------------------	---

<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.17	Vert(LL) -0.02 8 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.21	Vert(CT) -0.02 8 >999 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.21	Horz(CT) 0.00 5 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
				Weight: 32 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 10=334/0-3-6 (min. 0-1-8), 5=334/0-3-6 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 10-11=-327/0, 1-11=-326/0, 5-12=-332/0, 4-12=-332/0, 1-2=-395/0, 2-3=-576/0  
BOT CHORD 8-9=0/576, 7-8=0/576, 6-7=0/576  
WEBS 1-9=0/447, 2-9=-301/0, 3-6=-435/0, 4-6=0/316

**NOTES-** (3)  
1) Unbalanced floor live loads have been considered for this design.  
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

**LOAD CASE(S)** Standard



2/3/2025

**Warning!**—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.