

- Refer to Sealed drawings for connection detail of multiple ply trusses.**

TRUSS



Connector Summary		
Qty	Manuf	Product
1	Simpson	HUC414
14	Simpson	IUS2.56/14
2	Simpson	IUS2.56/14
8	Simpson	IUS2.56/14
6	Simpson	MIU5.12/14
1	Simpson	MIU5.12/14

SHOP DRAWING APPROVAL

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss. The building designer is responsible for temporary and permanent bracing of the roof system and for the design of the roof framing system and for the overall structure. The design of the truss support structure including headers, beams, walls, columns, and sufficient blocking in floor cavity under point loads is the responsibility of the building designer. For general guidance regarding bracing, consult "Bracing of Wood Trusses" available from the Truss Plate Institute, 983 D'Oro Drive, Madison, WI 53711.

REVIEWED BY: _____
APPROVED BY: _____

DATE:

Hanger Conversion Chart

Client: **MATTAMY HOMES**

Simpson

SHENANDOAH - CRAFTSMAN

LUS26

Model: **EWP 2ND FLOOR**

HUS26

EOY ETEI D EADM

7-07C0111	7C1A7C
-----------	--------

Sales Rep:	Designer:
------------	-----------

ИПАЗО	
ТНЛАЗО	

1/28/2025



RIVERSIDE ROOF TRUSS, LLC

Roof Surface Area: **0** Sq. Ft.
Floor Surface Area: **3801** Sq. Ft.



SIMPSON
Strong-Tie