\*tervaluated after Heavy rain

DEPARTMENT OF HEALTH AND HUMAN SERVICES
DIVISION OF PUBLIC HEALTH, ENVIRONMENTAL HEALTH SECTION
ON-SITE WATER PROTECTION BRANCH

## SOIL/SITE EVALUATION for ON-SITE WASTEWATER SYSTEM (Complete all fields in full)

OWNE	R: Stephen	Daniel	Lee	(Complete an			DA7	ΓΕ EVALU	ATED: 3-	17-25
LOCA	TION OF SITE:			OPOSED DESIGN			PROPI	ERTY SIZ	ORDED:	
	R SUPPLY: ( UATION METH		ngle Family Well	Shared Well		ner			SETBACK:	
180.0	DATION METH	OD: Atige	Pit Pit	Cut TY	PE OF WASTE	EWATER:	Domest	ic) High	Strength	IPWW
P R O F			SOIL MORPHOLOGY		OTHER PROFIL		E FACTORS			
L E #	.0502 LANDSCAPE POSITION/ SLOPE %	HORIZON DEPTH (IN.)	.0503 STRUCTURE/ TEXTURE	.0503 CONSISTENCE/ MINERALOGY	.0504 SOIL WETNESS/ COLOR	.0505 SOIL DEPTH	.0506 SAPRO CLASS	.0507 RESTR HORIZ	.0509 PROFILE CLASS & LTAR*	.0503 SLOPE CORRE CTION
1	2%. LS	7-18	32,9			18" to works Table				
		18 - Table								
						lavie				
	2% 13	0-19	56,90		7.5/L 7/2:36"	48"	Water Table out 3 4/1	Water	1977	
2		19-34	5ch, 50K	1				.35		
2		34- 48	CL, with	F1, 55, 29,5E				34"		
	2 %.	0-70	56,9"	,	7 5VR			Water		
	LS	20-38	SCL, SBK	Fr, 55, NP, SE	7.5/R 7/2=40"	48"		Table	.35	
3/4/5		38-48	CL, "BEK					38"		
4										

DESCRIPTION	INITIAL SYSTEM	REPAIR SYSTEM				
Available Space (.0508)		/	SITE CLASSIFICATION (.0509):			
System Type(s)	25% Res	25%. Red	EVALUATED BY: RL			
Site LTAR	,35	.33	OTHER(S) PRESENT:			
Maximum Trench Depth	18-22	18-26"				
Comments:		-				

## **LEGEND**

LANDSCAPE SOIL GROUP		SOIL TEXTURE	CONVENTIONAL LTAR (gpd/ft²)	SAPROLITE LTAR (gpd/ft²)	LPP LTAR (gpd/ft²)	MINERALOGY/ CONSISTENCE		STRUCTURE
CC (Concave slope)		S (Sand)	0.8 - 1.2	0.6 - 0.8		MOIST	WET	SG (Single grain)
CV (Convex Slope)	1	LS (Loamy sand)		0.5 -0.7	0.4 -0.6	Lo (Loose)	NS (Non-sticky)	M (Massive)
D (Drainage way)	. 11	SL (Sandy loam)	0.6 - 0.8	0.4 -0.6	0.3 - 0.4	VFR (Very friable)	SS (Slightly sticky)	GR (Granular)
FP (Flood plain)		L (Loam)		0.2 - 0.4		FR (Friable)	S (Sticky)	SBK (Subangular blocky)
FS (Foot slope)	III	SiL (Silt loam)	0.3 - 0.6	0.1 - 0.3	0.15 - 0.3	FI (Firm)	VS (Very sticky)	ABK (Angular blocky)
H (Head slope)		SCL (Sandy clay loam)		0.05 - 0.15**		VFI (Very firm)	NP (Non-plastic)	PR (Prismatic)
L (Linear Slope)		CL (Clay loam)		None		EFI (Extremely firm)	SP (Slightly plastic)	PL (Platy)
N (Nose slope)		SiCL (Silty clay loam)					P (Plastic)	
R (Ridge/summit)		Si (Silt)					VP (Very plastic)	
S (Shoulder slope)		SC (Sandy clay)	0.1 - 0.4		0.05 - 0.2	SEXP (Slightly expansive)		
T (Terrace)	IV	SiC (Silty clay)				EXP (Expansive)		
TS (Toe Slope)		C (Clay)						
		O (Organic)	None					

\* Adjust LTAR due to depth, consistence, structure, soil wetness, landscape, position, wastewater flow and quality. Denning Ra Angill

\*\*Sandy clay loam saprolite can only be used with advanced pretreatment in accordance with 15A NCAC 18E .1200. HORIZON DEPTH In inches below natural soil surface

DEPTH OF FILL

SOIL WETNESS

In inches from land surface

RESTRICTIVE HORIZON **SAPROLITE** 

Thickness and depth from land surface

S(suitable) or U(unsuitable); Evaluation of saprolite shall be by pit

Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation

CLASSIFICATION S (Suitable) or U (Unsuitable)

