


Job 28531	Truss G1	Truss Type Common Supported Gable	Qty 1	Ply 1	Wellons Realty/Lot 3 FH
C&R Building Supply, Autryville NC					Job Reference (optional)



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.10	Vert(LL)	-0.00	13	n/r	120	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.06	Vert(CT)	-0.00	12	n/r	120		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.06	Horz(CT)	0.00	12	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S							
									Weight: 119 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS. All bearings 22-0-0.
 (lb) - Max Horz 2=-86(LC 6)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 19, 20, 21, 22, 17, 16, 15, 14, 12
 Max Grav All reactions 250 lb or less at joint(s) 2, 18, 19, 20, 21, 22, 17, 16, 15, 14, 12

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) All plates are 1.5x4 MT20 unless otherwise indicated.
 - 5) Gable requires continuous bottom chord bearing.
 - 6) Gable studs spaced at 2-0-0 oc.
 - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 19, 20, 21, 22, 17, 16, 15, 14, 12.
 - 10) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 2.
 - 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 28531	Truss G2	Truss Type Common Structural Gable	Qty 1	Ply 1	Wellons Realty/Lot 3 FH
C&R Building Supply, Autryville NC					Job Reference (optional)



4x4 =

Scale = 1:30.9

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.13	Vert(LL)	-0.01	9	n/r	120	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.04	Vert(CT)	-0.01	9	n/r	120		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.08	Horz(CT)	0.00	10	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-R						Weight: 73 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 12-0-0.
 (lb) - Max Horz 16=-125(LC 6)
 Max Uplift All uplift 100 lb or less at joint(s) 16, 10, 14, 15, 12, 11
 Max Grav All reactions 250 lb or less at joint(s) 16, 10, 13, 14, 15, 12, 11

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) All plates are 1.5x4 MT20 unless otherwise indicated.
 - 5) Gable requires continuous bottom chord bearing.
 - 6) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 7) Gable studs spaced at 2-0-0 oc.
 - 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 16, 10, 14, 15, 12, 11.
 - 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 28531	Truss G3	Truss Type GABLE	Qty 1	Ply 1	Wellons Realty/Lot 3 FH
C&R Building Supply, Autryville NC					Job Reference (optional)




Plate Offsets (X,Y)-- [19:0-2-14,Edge]	42-8-8 42-8-8	43-0-0 0-3-8
--	------------------	-----------------

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.04	Vert(LL)	0.00	23	n/r	120	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.03	Vert(CT)	0.00	24	n/r	120		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.14	Horz(CT)	0.00	23	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S							
									Weight: 377 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	WEBS 1 Row at midpt 12-35, 11-36, 10-37, 13-34, 14-33

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS. All bearings 43-0-0.
 (lb) - Max Horz 1=-159(LC 6)
 Max Uplift All uplift 100 lb or less at joint(s) 37, 39, 40, 41, 42, 43, 44, 45, 33, 31, 30, 29, 28, 27, 26, 25
 Max Grav All reactions 250 lb or less at joint(s) 1, 23, 35, 36, 37, 39, 40, 41, 42, 43, 44, 34, 33, 31, 30, 29, 28, 27, 26 except 45=281(LC 19), 25=261(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) All plates are 2x4 MT20 unless otherwise indicated.
 - 5) Gable requires continuous bottom chord bearing.
 - 6) Gable studs spaced at 2-0-0 oc.
 - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 37, 39, 40, 41, 42, 43, 44, 45, 33, 31, 30, 29, 28, 27, 26, 25.
 - 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 28531	Truss G4	Truss Type GABLE	Qty 1	Ply 1	Wellons Realty/Lot 3 FH
C&R Building Supply, Autryville NC					Job Reference (optional)



5-1-12 5-1-12	36-10-4 31-8-8	40-10-4 4-0-0	45-8-8 4-10-4	46-0-0 0-3-8
LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES
TCLL 20.0	2-0-0	TC 0.03	in (loc) l/defl L/d	GRIP
TCDL 10.0	Plate Grip DOL 1.15	BC 0.02	Vert(LL) -0.00 1 n/r 120	MT20 244/190
BCLL 0.0 *	Lumber DOL 1.15	WB 0.13	Vert(CT) 0.00 1 n/r 120	
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 26 n/a n/a	
	Code IRC2018/TPI2014			Weight: 416 lb FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x6 SP No.1 *Except*	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
B2: 2x6 SP 2400F 2.0E	WEBS 1 Row at midpt 14-38, 13-39, 12-40, 11-41, 15-37, 16-36, 17-35
OTHERS 2x4 SP No.3	

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 46-0-0.
 (lb) - Max Horz 2=169(LC 7)
 Max Uplift All uplift 100 lb or less at joint(s) 40, 41, 43, 44, 45, 46, 47, 48, 49, 36, 35, 33, 32, 31, 30, 29, 28, 27
 Max Grav All reactions 250 lb or less at joint(s) 2, 26, 38, 39, 40, 41, 43, 44, 45, 46, 47, 48, 49, 37, 36, 35, 33, 32, 31, 30, 29, 28, 27

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 40, 41, 43, 44, 45, 46, 47, 48, 49, 36, 35, 33, 32, 31, 30, 29, 28, 27.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job 28531	Truss GR1	Truss Type Common Girder	Qty 1	Ply 2	Wellons Realty/Lot 3 FH
--------------	--------------	-----------------------------	----------	----------	-------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:20 2025 Page 1

ID:oOrFoot17C2KibuW93NW5By3q3T-XK1dUS0nAHUch39dRELO9JHPzI83ix8BxYubczfNbj



Scale = 1:36.7




Plate Offsets (X,Y)-- [1:0-5-0,0-2-0], [7:0-5-0,0-2-0], [8:0-4-4,0-1-8], [9:0-3-8,0-4-8], [11:0-3-8,0-4-8], [12:0-4-4,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.56	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.69	Vert(LL) -0.16 10-11 >999 360	MT20HS	187/143
BCLL 0.0 *	Lumber DOL 1.15	WB 0.89	Vert(CT) -0.31 10-11 >844 240		
BCDL 10.0	Rep Stress Incr NO	Matrix-MS	Horz(CT) 0.11 7 n/a n/a		
	Code IRC2018/TPI2014		Wind(LL) 0.12 10-11 >999 240	Weight: 314 lb	FT = 20%

LUMBER-
TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP 2400F 2.0E
WEBS 2x4 SP No.3 *Except*
W5: 2x4 SP 2400F 2.0E

BRACING-
TOP CHORD Structural wood sheathing directly applied or 3-6-4 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 1=8802/0-3-8 (req. 0-3-10), 7=8874/0-3-8 (req. 0-3-11)
Max Horz 1=78(LC 7)
Max Uplift 1=-733(LC 8), 7=-740(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-16763/1423, 2-3=-13957/1206, 3-4=-10840/966, 4-5=-10839/966,
5-6=-13991/1209, 6-7=-16816/1428
BOT CHORD 1-19=-1240/14942, 12-19=-1240/14942, 12-20=-1240/14942,
11-20=-1240/14942, 11-21=-1011/12480, 21-22=-1011/12480,
10-22=-1011/12480, 10-23=-1014/12510, 23-24=-1014/12510,
9-24=-1014/12510, 9-25=-1244/14989, 8-25=-1244/14989, 8-26=-1244/14989,
7-26=-1244/14989
WEBS 4-10=-805/9245, 5-10=-4155/379, 5-9=-355/4293, 6-9=-2883/267,
6-8=-207/2624, 3-10=-4109/375, 3-11=-350/4244, 2-11=-2863/265,
2-12=-205/2609

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-6-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - All plates are MT20 plates unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Continued on page 2

Job 28531	Truss GR1	Truss Type Common Girder	Qty 1	Ply 2	Wellons Realty\Lot 3 FH Job Reference (optional)
--------------	--------------	-----------------------------	----------	-----------------	---

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:20 2025 Page 2
ID:oOrFoot17C2KibuW93NW5By3q3T-XK1dUS0nAHUcH39dRELO9JHPzI83izx8BxYubczfNbj

NOTES-

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- 8) WARNING: Required bearing size at joint(s) 1, 7 greater than input bearing size.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=733, 7=740.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 11) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1592 lb down and 159 lb up at 2-0-12, 1592 lb down and 159 lb up at 4-0-12, 1592 lb down and 159 lb up at 6-0-12, 1592 lb down and 159 lb up at 8-0-12, 1592 lb down and 159 lb up at 10-0-12, 1592 lb down and 159 lb up at 12-0-12, 1592 lb down and 159 lb up at 14-0-12, 1592 lb down and 159 lb up at 16-0-12, and 1592 lb down and 159 lb up at 18-0-12, and 1592 lb down and 159 lb up at 20-0-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-4=-60, 4-7=-60, 13-16=-20

Concentrated Loads (lb)


Vert: 8=-1592(F) 12=-1592(F) 19=-1592(F) 20=-1592(F) 21=-1592(F) 22=-1592(F) 23=-1592(F) 24=-1592(F) 25=-1592(F) 26=-1592(F)

Job 28531	Truss GR2	Truss Type Common Girder	Qty 1	Ply 2	Wellons Realty/Lot 3 FH Job Reference (optional)
--------------	--------------	-----------------------------	----------	----------	---

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:20 2025 Page 1

ID:oOrFoot17C2KibuW93NW5By3q3T-XK1dUS0nAHUcH39dRELO9JHQV19DizD8BxYubczfNbj



Scale = 1:34.2

Plate Offsets (X,Y)-- [9:0-4-0,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0 Plate Grip DOL 1.15	TC 0.47	Vert(LL) -0.04	8-9	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.62	Vert(CT) -0.08	8-9	>999	240		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.87	Horz(CT) 0.02	7	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014	Matrix-MS	Wind(LL) 0.03	8-9	>999	240		
							Weight: 168 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.3
 SLIDER Left 2x4 SP No.3 -D 1-6-0, Right 2x4 SP No.3 -D 1-6-0

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-2-8 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 1=4151/0-3-8 (min. 0-2-7), 7=4091/0-3-8 (min. 0-2-7)
 Max Horz 1=-88(LC 6)
 Max Uplift 1=-299(LC 8), 7=-294(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-2858/201, 2-3=-4601/363, 3-4=-3546/315, 4-5=-3546/315,
 5-6=-4603/363, 6-7=-2830/199
 BOT CHORD 1-19=-236/3417, 10-19=-236/3417, 10-20=-236/3417, 9-20=-236/3417,
 9-21=-233/3416, 8-21=-233/3416, 8-22=-233/3416, 7-22=-233/3416
 WEBS 4-9=-357/4204, 5-9=-1049/124, 5-8=-110/1463, 3-9=-1050/124,
 3-10=-108/1457

NOTES-

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-7-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=299, 7=294.

Continued on page 2

Job 28531	Truss GR2	Truss Type Common Girder	Qty 1	Ply 2	Wellons Realty\Lot 3 FH Job Reference (optional)
--------------	--------------	-----------------------------	----------	-----------------	---

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:21 2025 Page 2
ID:oOrFoot17C2KibuW93NW5By3q3T-?Wb?io1PxbcTvDkq_ysdiWpbF9VSRQTHQbHS73zfNbi

NOTES-

- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1457 lb down and 131 lb up at 1-11-4, 1457 lb down and 131 lb up at 3-11-4, 1457 lb down and 131 lb up at 5-11-4, and 1457 lb down and 131 lb up at 7-11-4, and 1457 lb down and 131 lb up at 9-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-4=-60, 4-7=-60, 11-15=-20
Concentrated Loads (lb)
Vert: 9=-1457(F) 19=-1457(F) 20=-1457(F) 21=-1457(F) 22=-1457(F)

Job 28531	Truss SG1	Truss Type GABLE	Qty 1	Ply 1	Wellons Realty Lot 3 FH
--------------	--------------	---------------------	----------	----------	-------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:21 2025 Page 1
 ID:oOrFoot17C2KibuW93NW5By3q3T-?Wb?io1PxbcTvDkq_ysdiWpe59UIRV6HQbHS73zfNbi




Plate Offsets (X,Y)-- [9:0-1-5,0-0-0], [13:0-3-12,0-4-8], [14:0-3-12,0-4-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.28	Vert(LL)	-0.44 13-14	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.69	Vert(CT)	-0.65 13-14	>760	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.57	Horz(CT)	0.06 12	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Wind(LL)	0.05 14	>999	240		
	Code IRC2018/TPI2014						Weight: 376 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x6 SP No.1 *Except*	BOT CHORD Rigid ceiling directly applied.
B2: 2x6 SP 2400F 2.0E	WEBS 1 Row at midpt 3-14, 9-12
WEBS 2x4 SP No.3 *Except*	
W4: 2x4 SP No.2	
OTHERS 2x4 SP No.3	

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1672/0-3-8 (min. 0-2-0), 12=2168/0-3-8 (min. 0-2-9), 10=-29/0-3-8 (min. 0-1-8)
 Max Horz 2=-170(LC 6)
 Max Uplift 10=-133(LC 21)
 Max Grav 2=1672(LC 13), 12=2171(LC 14), 10=54(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-3087/0, 3-4=-2469/0, 4-5=-2377/11, 5-6=-2481/103, 6-7=-2003/118,
 7-8=-1914/25, 8-9=-2011/0, 9-10=-4/722
 BOT CHORD 2-15=0/2807, 14-15=0/2738, 14-37=0/1502, 37-38=0/1502, 13-38=0/1502,
 12-13=0/904, 10-12=-561/50
 WEBS 5-14=-472/121, 7-13=-461/121, 3-14=-660/86, 6-14=0/1400, 6-13=-23/627,
 9-13=0/942, 9-12=-2458/28, 3-15=0/387

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=6ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) All plates are 2x4 MT20 unless otherwise indicated.
 - 5) Gable studs spaced at 2-0-0 oc.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 10=133.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Wellons Realty\Lot 3 FH
28531	SG1	GABLE	1	1	Job Reference (optional)

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:21 2025 Page 2
 ID:oOrFoot17C2KibuW93NW5By3q3T-?Wb?io1PxbcTvDkq_ysdiWpe59UIRV6HQBHS73zfNbi

NOTES-

- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Job 28531	Truss T1	Truss Type FAN	Qty 10	Ply 1	Wellons Realty Lot 3 FH
C&R Building Supply, Autryville NC					Job Reference (optional)




Plate Offsets (X,Y)-- [1:0-5-0,0-1-12], [9:0-5-0,0-1-12]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.38	Vert(LL) -0.24 15-18 >999 360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.63	Vert(CT) -0.54 15-18 >452 240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.69	Horz(CT) 0.08 9 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014	Matrix-AS	Wind(LL) 0.09 15-18 >999 240	Weight: 297 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3	

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=1612/Mechanical, 9=1689/0-3-8 (min. 0-2-0), 13=205/0-3-8 (min. 0-1-8)
 Max Horz 1=-158(LC 6)
 Max Grav 1=1612(LC 1), 9=1689(LC 1), 13=468(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-2915/40, 2-3=-2423/1, 3-4=-2318/26, 4-5=-2408/117, 5-6=-2433/112, 6-7=-2343/0, 7-8=-2447/0, 8-9=-2933/34
 BOT CHORD 1-15=0/2578, 15-22=0/1556, 14-22=0/1556, 13-14=0/1556, 12-13=0/1556, 12-23=0/1556, 11-23=0/1556, 9-11=0/2592
 WEBS 4-15=-408/121, 6-11=-410/122, 2-15=-572/90, 5-15=-18/1013, 5-11=-10/1081, 8-11=-563/88

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Refer to girder(s) for truss to truss connections.
 - 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 7) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Job 28531	Truss T2	Truss Type FAN	Qty 5	Ply 1	Wellons Realty Lot 3 FH
--------------	-------------	-------------------	----------	----------	-------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:23 2025 Page 1
ID:oOrFoot17C2KibuW93NW5By3q3T-xvjm7U2FTCsA8XtC6Nu6nxv_bzAmvPbatmYCxfNbg




Plate Offsets (X,Y)-- [13:0-3-12,0-4-12], [14:0-3-12,0-4-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.28	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.69	Vert(LL) -0.44 13-14 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.57	Vert(CT) -0.65 13-14 >760 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.06 12 n/a n/a		
	Code IRC2018/TPI2014		Wind(LL) 0.05 14 >999 240	Weight: 336 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x6 SP No.1 *Except*	BOT CHORD Rigid ceiling directly applied.
B2: 2x6 SP 2400F 2.0E	WEBS 1 Row at midpt 3-14, 9-12
WEBS 2x4 SP No.3 *Except*	
W4: 2x4 SP No.2	

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1672/0-3-8 (min. 0-2-0), 12=2168/0-3-8 (min. 0-2-9), 10=29/0-3-8 (min. 0-1-8)
Max Horz 2=170(LC 7)
Max Uplift 10=-133(LC 21)
Max Grav 2=1672(LC 13), 12=2171(LC 14), 10=54(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-3087/0, 3-4=-2469/0, 4-5=-2377/11, 5-6=-2481/103, 6-7=-2003/118, 7-8=-1914/25, 8-9=-2011/0, 9-10=-4/722
BOT CHORD 2-15=0/2807, 14-15=0/2738, 14-22=0/1502, 22-23=0/1502, 13-23=0/1502, 12-13=0/904, 10-12=-561/50
WEBS 5-14=-472/121, 7-13=-461/121, 3-14=-660/86, 6-14=0/1400, 6-13=-23/627, 9-13=0/942, 9-12=-2458/28, 3-15=0/387

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=6ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 10=133.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Job 28531	Truss T3	Truss Type FAN	Qty 2	Ply 1	Wellons Realty Lot 3 FH
--------------	-------------	-------------------	----------	----------	-------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:24 2025 Page 1
 ID:0OrFoot17C2KibuW93NW5By3q3T-P5H8Kq3HEW_1mhSOg4PLJ9R9gMXjercj6ZW6kNzfNbf




Plate Offsets (X,Y)-- [13:0-3-12,0-4-8], [14:0-3-12,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.26	Vert(LL)	-0.37 13-14	>925	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.58	Vert(CT)	-0.56 13-14	>615	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.59	Horz(CT)	0.01 12	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Wind(LL)	0.02 13-14	>999	240	Weight: 332 lb	FT = 20%
	Code IRC2018/TPI2014							

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x6 SP No.1 *Except*	BOT CHORD Rigid ceiling directly applied.
B2: 2x6 SP 2400F 2.0E	
WEBS 2x4 SP No.3 *Except*	
W4: 2x4 SP No.2	

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 0-3-8.
 (lb) - Max Horz 2=-170(LC 6)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 10
 Max Grav All reactions 250 lb or less at joint(s) except 2=382(LC 1),
 12=1579(LC 14), 10=424(LC 1), 15=1555(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 3-4=-1206/0, 4-5=-1106/33, 5-6=-1188/125, 6-7=-1115/125, 7-8=-1079/39,
 8-9=-1112/6
 BOT CHORD 14-22=0/823, 22-23=0/823, 13-23=0/823
 WEBS 5-14=-445/120, 7-13=-390/108, 3-14=0/1030, 6-14=-16/490, 6-13=-18/353,
 9-13=0/995, 9-12=-1468/34, 3-15=-1446/43

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=6ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.
 - 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 7) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Job 28531	Truss T4	Truss Type FAN	Qty 1	Ply 1	Wellons Realty Lot 3 FH
C&R Building Supply, Autryville NC					Job Reference (optional)



Scale = 1:78.1




Plate Offsets (X,Y)-- [12:0-3-12,0-4-8], [13:0-3-12,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.27	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.58	Vert(LL) -0.37 12-13 >925 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.59	Vert(CT) -0.56 12-13 >615 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.01 11 n/a n/a		
	Code IRC2018/TPI2014		Wind(LL) 0.02 11-20 >999 240	Weight: 329 lb	FT = 20%

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1 *Except*
 B2: 2x6 SP 2400F 2.0E
 WEBS 2x4 SP No.3 *Except*
 W4: 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 0-3-8.
 (lb) - Max Horz 2=169(LC 7)
 Max Uplift All uplift 100 lb or less at joint(s) 2
 Max Grav All reactions 250 lb or less at joint(s) except 2=382(LC 1),
 11=1582(LC 14), 10=355(LC 1), 14=1554(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 3-4=-1206/0, 4-5=-1107/29, 5-6=-1189/120, 6-7=-1114/121, 7-8=-1079/35,
 8-9=-1112/1
 BOT CHORD 13-21=0/819, 21-22=0/819, 12-22=0/819
 WEBS 5-13=-445/120, 7-12=-389/108, 3-13=0/1029, 6-13=-13/490, 6-12=-16/353,
 9-12=0/992, 9-11=-1468/38, 3-14=-1445/47

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Job 28531	Truss T5	Truss Type FAN	Qty 5	Ply 1	Wellons Realty/Lot 3 FH
--------------	-------------	-------------------	----------	----------	-------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:25 2025 Page 1

ID:oOrFoot17C2KibuW93NW5By3q3T-ulqWYA4w?q6uNq1bDnwasM_K2msdNHctLDfGqzfnbe



Scale = 1:78.1




Plate Offsets (X,Y)-- [12:0-3-12,0-4-12], [13:0-3-12,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.29	Vert(LL)	-0.41 12-13	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.66	Vert(CT)	-0.62 12-13	>733	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.67	Horz(CT)	0.04 10	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Wind(LL)	0.05 12	>999	240		
	Code IRC2018/TPI2014						Weight: 331 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x6 SP No.1 *Except*	BOT CHORD Rigid ceiling directly applied.
B2: 2x6 SP 2400F 2.0E	WEBS 1 Row at midpt 6-13, 9-12
WEBS 2x4 SP No.3 *Except*	
W4: 2x4 SP No.2	

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS. (lb/size) 2=223/0-3-8 (min. 0-1-8), 10=1477/Mechanical, 14=2045/0-3-8 (min. 0-2-8)
 Max Horz 2=169(LC 7)
 Max Uplift 2=-11(LC 8)
 Max Grav 2=282(LC 19), 10=1493(LC 14), 14=2095(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-18/392, 3-4=-1475/0, 4-5=-1374/26, 5-6=-1451/118, 6-7=-2214/102, 7-8=-2110/0, 8-9=-2202/0, 9-10=-2828/0
 BOT CHORD 2-14=-275/48, 13-14=-275/48, 13-21=0/1212, 21-22=0/1212, 12-22=0/1212, 11-12=0/2383, 10-11=0/2460
 WEBS 5-13=-443/121, 7-12=-471/121, 3-13=0/1622, 6-12=0/1403, 9-12=-669/90, 3-14=-1977/38, 9-11=0/388

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=6ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Job 28531	Truss V1	Truss Type Valley	Qty 1	Ply 1	Wellons Realty/Lot 3 FH
C&R Building Supply, Autryville NC					Job Reference (optional)



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.19	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.12	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.07	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 5 n/a n/a		
	Code IRC2018/TPI2014			Weight: 48 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 11-9-3.
 (lb) - Max Horz 1=-80(LC 6)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 5, 8, 6
 Max Grav All reactions 250 lb or less at joint(s) 1, 5, 7 except
 8=301(LC 13), 6=301(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5, 8, 6.
 - 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 28531	Truss V2	Truss Type Valley	Qty 1	Ply 1	Wellons Realty\Lot 3 FH
--------------	-------------	----------------------	----------	----------	-------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:26 2025 Page 1
 ID:oOrFoot17C2KlbuW93NW5By3q3T-MUOuIW5YI7EI?_cnnVRpPaXVFAJL6uP0ZI?DoGzfNbd



Scale = 1:23.7



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.26	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.19	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.06	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2018/TPI2014			Weight: 35 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=181/9-4-6 (min. 0-1-8), 3=181/9-4-6 (min. 0-1-8), 4=322/9-4-6 (min. 0-1-8)
 Max Horz 1=63(LC 7)
 Max Uplift 1=-8(LC 8), 3=-8(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 28531	Truss V3	Truss Type Valley	Qty 1	Ply 1	Wellons Realty/Lot 3 FH
--------------	-------------	----------------------	----------	----------	-------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:27 2025 Page 1
ID:oOrFoot17C2KibuW93NW5By3q3T-qgyHzr5AWRMcd8BzL.Cz2xn3iFagzrL4AoXkmlzfnbc



Scale = 1:18.3

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.18	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.10	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.03	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2018/TPI2014			Weight: 26 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=141/6-11-10 (min. 0-1-8), 3=141/6-11-10 (min. 0-1-8), 4=210/6-11-10 (min. 0-1-8)
Max Horz 1=-45(LC 6)
Max Uplift 1=-12(LC 8), 3=-12(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 28531	Truss V4	Truss Type Valley	Qty 1	Ply 1	Wellons Realty Lot 3 FH
--------------	-------------	----------------------	----------	----------	-------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:27 2025 Page 1
ID:oOrFoot17C2KlbuW93NW5By3q3T-qgyHzr5AWRMcd8BzL.Cz2xn3k3ahvrLIAoXkmlzifNbc



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.06	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.04	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2018/TPI2014			Weight: 16 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-6-13 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=86/4-6-13 (min. 0-1-8), 3=86/4-6-13 (min. 0-1-8), 4=128/4-6-13 (min. 0-1-8)
Max Horz 1=28(LC 7)
Max Uplift 1=-7(LC 8), 3=-7(LC 8)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 28531	Truss V5	Truss Type Valley	Qty 1	Ply 1	Wellons Realty/Lot 3 FH
C&R Building Supply, Autryville NC					Job Reference (optional)



Scale = 1:29.6



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.26	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.16	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.07	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 5 n/a n/a		
	Code IRC2018/TPI2014			Weight: 67 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 18-2-0.
 (lb) - Max Horz 1=60(LC 7)
 Max Uplift All uplift 100 lb or less at joint(s) 9, 6
 Max Grav All reactions 250 lb or less at joint(s) 1, 5, 7 except
 9=411(LC 19), 6=411(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-9=-304/76, 4-6=-304/76


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9, 6.
 - 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 28531	Truss V6	Truss Type Valley	Qty 1	Ply 1	Wellons Realty/Lot 3 FH
--------------	-------------	----------------------	----------	----------	-------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:28 2025 Page 1
 ID:oOrFoot17C2KibuW93NW5By3q3T-ItWfAB6oHIUTEImAwwUHU?ct4_0sanyJ1BUJt9zfNbb



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.17	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.12	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.05	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 5 n/a n/a		
	Code IRC2018/TPI2014			Weight: 50 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS. All bearings 14-2-0.
 (lb) - Max Horz 1=46(LC 7)
 Max Uplift All uplift 100 lb or less at joint(s) 8, 6
 Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=284(LC 1),
 8=312(LC 19), 6=312(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8, 6.
 - 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 28531	Truss V7	Truss Type Valley	Qty 1	Ply 1	Wellons Realty/Lot 3 FH
C&R Building Supply, Autryville NC					Job Reference (optional)



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.28	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.20	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.06	Vert(CT) n/a - n/a 999		
BCDL 10.0	Code IRC2018/TPI2014	Matrix-S	Horz(CT) 0.00 3 n/a n/a		
				Weight: 33 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=164/10-2-0 (min. 0-1-8), 3=164/10-2-0 (min. 0-1-8), 4=391/10-2-0 (min. 0-1-8)
 Max Horz 1=32(LC 7)
 Max Uplift 1=-4(LC 8), 3=-4(LC 8)
 Max Grav 1=166(LC 19), 3=166(LC 20), 4=391(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-4=-259/33

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job 28531	Truss V8	Truss Type Valley	Qty 1	Ply 1	Wellons Realty/Lot 3 FH
--------------	-------------	----------------------	----------	----------	-------------------------


C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Sat Mar 1 07:01:29 2025 Page 1

ID:oOrFoot17C2KibuW93NW5By3q3T-m341NX7Q22cKsSLMSd?W0C93pNNyJEdSGrDtPbzNba



Scale = 1:11.6



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.11	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.06	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.03	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2018/TPI2014			Weight: 19 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=101/6-2-0 (min. 0-1-8), 3=101/6-2-0 (min. 0-1-8), 4=197/6-2-0 (min. 0-1-8)
 Max Horz 1=18(LC 7)
 Max Uplift 1=5(LC 8), 3=5(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard